

# Deep Learning

Lecture 21

# Reinforcement Learning

Part 1

# So far... Supervised Learning

**Data:**  $(x, y)$

$x$  is data,  $y$  is label

**Goal :** Learn a *function* to map  $x \rightarrow y$

**Examples :** Classification,  
regression, object detection,  
semantic segmentation, image  
captioning, etc.



→ Cat

Classification

[This image is CC0 public domain](#)

# So far... Unsupervised Learning

**Data:**  $x$



Just data, no labels!

**Goal :** Learn some underlying hidden *structure* of the data

**Examples :** Clustering, dimensionality reduction, feature learning, density estimation, etc.



Figure copyright Ian Goodfellow, 2016. Reproduced with permission.




2-d density estimation

2-d density images [left](#) and [right](#) are CC0 public domain

# Today: Reinforcement Learning

Problems involving an **agent** interacting with an **environment**, which provides numeric **reward** signals

**Goal** : Learn how to take actions in order to maximize reward



Atari games figure copyright Volodymyr Mnih et al., 2013. Reproduced with permission.

# Overview

- What is Reinforcement Learning?
- Markov Decision Processes
- Q-Learning
- Policy Gradients

# Reinforcement Learning




Agent

The diagram illustrates the Reinforcement Learning loop. It consists of two main components: the Agent and the Environment. The Agent is represented by an orange box at the top, and the Environment is represented by a blue box at the bottom. The Agent interacts with the Environment, and the Environment provides feedback to the Agent.


Environment

# Reinforcement Learning







# Reinforcement Learning




# Reinforcement Learning



# Reinforcement Learning



# Cart-Pole Problem




**Objective :** Balance a pole on top of a movable cart

**State:** angle, angular speed, position, horizontal velocity

**Action:** horizontal force applied on the cart

**Reward:** 1 at each time step if the pole is upright

# Robot Locomotion



**Objective :** Make the robot move forward

**State:** Angle and position of the joints

**Action:** Torques applied on joints

**Reward:** 1 at each time step upright + forward movement

Figures copyright John Schulman et al., 2016. Reproduced with permission.

# Atari Games



**Objective :** Complete the game with the highest score

**State:** Raw pixel inputs of the game state


**Action:** Game controls e.g. Left, Right, Up, Down

**Reward:** Score increase/decrease at each time step

Figures copyright Volodymyr Mnih et al., 2013. Reproduced with permission.



# Go



**Objective :** Win the game!


**State:** Position of all pieces

**Action:** Where to put the next piece down

**Reward:** 1 if win at the end of the game, 0 otherwise

[This image is CC0 public domain](#)

# How can we mathematically formalize the RL problem?





# Markov Decision Process

- Mathematical formulation of the RL problem
- **Markov property** : Current state completely characterizes the state of the world

Defined by:  $(\mathcal{S}, \mathcal{A}, \mathcal{R}, \mathbb{P}, \gamma)$

$\mathcal{S}$  : set of possible states

$\mathcal{A}$  : set of possible actions

$\mathcal{R}$  : distribution of reward given (state, action) pair

$\mathbb{P}$  : transition probability i.e. distribution over next state given (state, action) pair

$\gamma$  : discount factor

# Markov Decision Process

- At time step  $t=0$ , environment samples initial state  $s_0 \sim p(s_0)$
- Then, for  $t=0$  until done:
  - Agent selects action  $a_t$
  - Environment samples reward  $r_t \sim R(\cdot | s_t, a_t)$
  - Environment samples next state  $s_{t+1} \sim P(\cdot | s_t, a_t)$
  - Agent receives reward  $r_t$  and next state  $s_{t+1}$
- A policy  $\pi$  is a function from  $S$  to  $A$  that specifies what action to take in each state
- **Objective** : find policy  $\pi^*$  that maximizes cumulative discounted reward:

$$\sum_{t \geq 0} \gamma^t r_t$$

# A simple MDP: Grid World

actions = {

1. right 


2. left 

3. up 

4. down 

}


states




Set a negative “reward”  
for each transition  
(e.g.  $r = -1$ )

**Objective:** reach one of terminal states (greyed out) in  
least number of actions

# A simple MDP: Grid World



## Random Policy



# Optimal Policy

# The optimal policy $\pi^*$

We want to find optimal policy  $\pi^*$  that maximizes the sum of rewards.

How do we handle the randomness (initial state, transition probability...)?

# The optimal policy $\pi^*$

We want to find optimal policy  $\pi^*$  that maximizes the sum of rewards.

How do we handle the randomness (initial state, transition probability...)?

Maximize the **expected sum of rewards!**

$$\text{Formally: } \pi^* = \arg \max_{\pi} \mathbb{E} \left[ \sum_{t \geq 0} \gamma^t r_t | \pi \right] \quad \text{with } s_0 \sim p(s_0), a_t \sim \pi(\cdot | s_t), s_{t+1} \sim p(\cdot | s_t, a_t)$$

# Definitions: Value function and Q-value function

Following a policy produces sample trajectories (or paths)  $s_0, a_0, r_0, s_1, a_1, r_1, \dots$

# Definitions: Value function and Q-value function

Following a policy produces sample trajectories (or paths)  $s_0, a_0, r_0, s_1, a_1, r_1, \dots$

How good is a state?

The **value function** at state  $s$ , is the expected cumulative reward from following the policy from state  $s$ :

$$V^\pi(s) = \mathbb{E} \left[ \sum_{t \geq 0} \gamma^t r_t \mid s_0 = s, \pi \right]$$



# Definitions: Value function and Q-value function

Following a policy produces sample trajectories (or paths)  $s_0, a_0, r_0, s_1, a_1, r_1, \dots$

How good is a state?

The **value function** at state  $s$ , is the expected cumulative reward from following the policy from state  $s$ :

$$V^\pi(s) = \mathbb{E} \left[ \sum_{t \geq 0} \gamma^t r_t \mid s_0 = s, \pi \right]$$

How good is a state-action pair?

The **Q-value function** at state  $s$  and action  $a$ , is the expected cumulative reward from taking action  $a$  in state  $s$  and then following the policy:

$$Q^\pi(s, a) = \mathbb{E} \left[ \sum_{t \geq 0} \gamma^t r_t \mid s_0 = s, a_0 = a, \pi \right]$$

# Bellman equation

The optimal Q-value function  $Q^*$  is the maximum expected cumulative reward achievable from a given (state, action) pair:

$$Q^*(s, a) = \max_{\pi} \mathbb{E} \left[ \sum_{t \geq 0} \gamma^t r_t \mid s_0 = s, a_0 = a, \pi \right]$$

# Bellman equation

The optimal Q-value function  $Q^*$  is the maximum expected cumulative reward achievable from a given (state, action) pair:

$$Q^*(s, a) = \max_{\pi} \mathbb{E} \left[ \sum_{t \geq 0} \gamma^t r_t \mid s_0 = s, a_0 = a, \pi \right]$$

$Q^*$  satisfies the following **Bellman equation** :

$$Q^*(s, a) = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q^*(s', a') \mid s, a \right]$$

**Intuition:** if the optimal state-action values for the next time-step  $Q^*(s', a')$  are known, then the optimal strategy is to take the action that maximizes the expected value of  $r + \gamma Q^*(s', a')$

# Bellman equation

The optimal Q-value function  $Q^*$  is the maximum expected cumulative reward achievable from a given (state, action) pair:

$$Q^*(s, a) = \max_{\pi} \mathbb{E} \left[ \sum_{t \geq 0} \gamma^t r_t \mid s_0 = s, a_0 = a, \pi \right]$$

$Q^*$  satisfies the following **Bellman equation** :

$$Q^*(s, a) = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q^*(s', a') \mid s, a \right]$$

**Intuition:** if the optimal state-action values for the next time-step  $Q^*(s', a')$  are known, then the optimal strategy is to take the action that maximizes the expected value of  $r + \gamma Q^*(s', a')$

The optimal policy  $\boldsymbol{\pi}^*$  corresponds to taking the best action in any state as specified by  $Q^*$

# Solving for the optimal policy

**Value iteration** algorithm: Use Bellman equation as an iterative update

$$Q_{i+1}(s, a) = \mathbb{E} \left[ r + \gamma \max_{a'} Q_i(s', a') | s, a \right]$$

$Q_i$  will converge to  $Q^*$  as  $i \rightarrow \infty$

# Solving for the optimal policy

**Value iteration** algorithm: Use Bellman equation as an iterative update

$$Q_{i+1}(s, a) = \mathbb{E} \left[ r + \gamma \max_{a'} Q_i(s', a') | s, a \right]$$

$Q_i$  will converge to  $Q^*$  as  $i \rightarrow \infty$

What's the problem with this?

# Solving for the optimal policy

**Value iteration** algorithm: Use Bellman equation as an iterative update

$$Q_{i+1}(s, a) = \mathbb{E} \left[ r + \gamma \max_{a'} Q_i(s', a') | s, a \right]$$

$Q_i$  will converge to  $Q^*$  as  $i \rightarrow \infty$

What's the problem with this?

Not scalable. Must compute  $Q(s, a)$  for every state-action pair. If state is e.g. current game state pixels, computationally infeasible to compute for entire state space!



# Solving for the optimal policy

**Value iteration** algorithm: Use Bellman equation as an iterative update

$$Q_{i+1}(s, a) = \mathbb{E} \left[ r + \gamma \max_{a'} Q_i(s', a') | s, a \right]$$

$Q_i$  will converge to  $Q^*$  as  $i \rightarrow \infty$

What's the problem with this?

Not scalable. Must compute  $Q(s, a)$  for every state-action pair. If state is e.g. current game state pixels, computationally infeasible to compute for entire state space!

**Solution:** use a function approximator to estimate  $Q(s, a)$ . E.g. a **neural network**!



# Solving for the optimal policy: Q-learning

Q-learning: Use a function approximator to estimate the action-value function

$$Q(s, a; \theta) \approx Q^*(s, a)$$

# Solving for the optimal policy: Q-learning

Q-learning: Use a function approximator to estimate the action-value function

$$Q(s, a; \theta) \approx Q^*(s, a)$$

If the function approximator is a deep neural network => **deep q-learning !**

# Solving for the optimal policy: Q-learning

Q-learning: Use a function approximator to estimate the action-value function

$$Q(s, a; \theta) \approx Q^*(s, a)$$

function parameters (weights)

If the function approximator is a deep neural network => **deep q-learning !**

# Solving for the optimal policy: Q-learning

Remember: want to find a Q-function that satisfies the Bellman Equation:

$$Q^*(s, a) = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q^*(s', a') | s, a \right]$$

# Solving for the optimal policy: Q-learning

Remember: want to find a Q-function that satisfies the Bellman Equation:

$$Q^*(s, a) = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q^*(s', a') | s, a \right]$$

Forward Pass

$$L_i(\theta_i) = \mathbb{E}_{s, a \sim \rho(\cdot)} \left[ (y_i - Q(s, a; \theta_i))^2 \right]$$

where  $y_i = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q(s', a'; \theta_{i-1}) | s, a \right]$

# Solving for the optimal policy: Q-learning

Remember: want to find a Q-function that satisfies the Bellman Equation:

$$Q^*(s, a) = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q^*(s', a') | s, a \right]$$

Forward Pass

$$L_i(\theta_i) = \mathbb{E}_{s, a \sim \rho(\cdot)} \left[ (y_i - Q(s, a; \theta_i))^2 \right]$$

where  $y_i = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q(s', a'; \theta_{i-1}) | s, a \right]$

Backward Pass

Gradient update (with respect to Q-function parameters  $\theta$ ):

$$\nabla_{\theta_i} L_i(\theta_i) = \mathbb{E}_{s, a \sim \rho(\cdot); s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q(s', a'; \theta_{i-1}) - Q(s, a; \theta_i) \right] \nabla_{\theta_i} Q(s, a; \theta_i)$$

# Solving for the optimal policy: Q-learning

Remember: want to find a Q-function that satisfies the Bellman Equation:

$$Q^*(s, a) = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q^*(s', a') | s, a \right]$$

Forward Pass

$$L_i(\theta_i) = \mathbb{E}_{s, a \sim \rho(\cdot)} \left[ (y_i - Q(s, a; \theta_i))^2 \right]$$

where  $y_i = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q(s', a'; \theta_{i-1}) | s, a \right]$

Iteratively try to make the Q-value close to the target value  $y_i$ ,  
if Q-function corresponds to optimal  $Q^*$  (and optimal policy  $\pi^*$ )

Backward Pass

Gradient update (with respect to Q-function parameters  $\theta$ ):

$$\nabla_{\theta_i} L_i(\theta_i) = \mathbb{E}_{s, a \sim \rho(\cdot); s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q(s', a'; \theta_{i-1}) - Q(s, a; \theta_i) \right] \nabla_{\theta_i} Q(s, a; \theta_i)$$



# Case Study: Playing Atari Games



**Objective :** Complete the game with the highest score

**State:** Raw pixel inputs of the game state

**Action:** Game controls e.g. Left, Right, Up, Down


**Reward:** Score increase/decrease at each time step

Figures copyright Volodymyr Mnih et al., 2013. Reproduced with permission.



# Q-network Architecture


$Q(s, a; \theta)$  :  
neural network  
with weights  $\theta$



**Current state  $s_t$ : 84x84x4 stack of last 4 frames**  
(after RGB->grayscale conversion, downsampling, and cropping)

# Q-network Architecture

$Q(s, a; \theta)$  :  
neural network  
with weights  $\theta$




← Input: state  $s_t$

**Current state  $s_t$ : 84x84x4 stack of last 4 frames**  
(after RGB->grayscale conversion, downsampling, and cropping)

# Q-network Architecture

$Q(s, a; \theta)$  :  
neural network  
with weights  $\theta$




← Familiar conv layers,  
FC layer

**Current state  $s_t$ : 84x84x4 stack of last 4 frames**  
(after RGB->grayscale conversion, downsampling, and cropping)

# Q-network Architecture

$Q(s, a; \theta)$  :  
neural network  
with weights  $\theta$




Last FC layer has 4-d  
output (if 4 actions),  
corresponding to  
 $Q(s_t, a_1)$ ,  $Q(s_t, a_2)$ ,  $Q(s_t, a_3)$ ,  
 $Q(s_t, a_4)$

**Current state  $s_t$ : 84x84x4 stack of last 4 frames**  
(after RGB->grayscale conversion, downsampling, and cropping)

# Q-network Architecture

$Q(s, a; \theta)$  :  
neural network  
with weights  $\theta$



Last FC layer has 4-d  
output (if 4 actions),  
corresponding to  
 $Q(s_t, a_1)$ ,  $Q(s_t, a_2)$ ,  $Q(s_t, a_3)$ ,  
 $Q(s_t, a_4)$



Number of actions between 4-18  
depending on Atari game


**Current state  $s_t$ : 84x84x4 stack of last 4 frames**  
(after RGB->grayscale conversion, downsampling, and cropping)



# Q-network Architecture

$Q(s, a; \theta)$  :  
neural network  
with weights  $\theta$

A single feedforward pass  
to compute Q-values for all  
actions from the current  
state => efficient!



Last FC layer has 4-d  
output (if 4 actions),  
corresponding to  
 $Q(s_t, a_1)$ ,  $Q(s_t, a_2)$ ,  $Q(s_t, a_3)$ ,  
 $Q(s_t, a_4)$

Number of actions between 4-18  
depending on Atari game

**Current state  $s_t$ : 84x84x4 stack of last 4 frames**  
(after RGB->grayscale conversion, downsampling, and cropping)

# Solving for the optimal policy: Q-learning

Remember: want to find a Q-function that satisfies the Bellman Equation:

$$Q^*(s, a) = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q^*(s', a') | s, a \right]$$

Forward Pass

$$L_i(\theta_i) = \mathbb{E}_{s, a \sim \rho(\cdot)} \left[ (y_i - Q(s, a; \theta_i))^2 \right]$$

where  $y_i = \mathbb{E}_{s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q(s', a'; \theta_{i-1}) | s, a \right]$

Iteratively try to make the Q-value close to the target value  $y_i$ ,  
if Q-function corresponds to optimal  $Q^*$  (and optimal policy  $\pi^*$ )

Backward Pass

Gradient update (with respect to Q-function parameters  $\theta$ ):

$$\nabla_{\theta_i} L_i(\theta_i) = \mathbb{E}_{s, a \sim \rho(\cdot); s' \sim \mathcal{E}} \left[ r + \gamma \max_{a'} Q(s', a'; \theta_{i-1}) - Q(s, a; \theta_i) \right] \nabla_{\theta_i} Q(s, a; \theta_i)$$



# Training the Q-network: Experience Replay

Learning from batches of consecutive samples is problematic:

- Samples are correlated => inefficient learning
- Current Q-network parameters determines next training samples (e.g. if maximizing action is to move left, training samples will be dominated by samples from left-hand size) => can lead to bad feedback loops

# Training the Q-network: Experience Replay

Learning from batches of consecutive samples is problematic:

- Samples are correlated  $\Rightarrow$  inefficient learning
- Current Q-network parameters determines next training samples (e.g. if maximizing action is to move left, training samples will be dominated by samples from left-hand size)  $\Rightarrow$  can lead to bad feedback loops

Address these problems using **experience replay**

- Continually update a **replay memory** table of transitions ( $s_t, a_t, r_t, s_{t+1}$ ) as game (experience) episodes are played
- Train Q-network on random minibatches of transitions from the replay memory, instead of consecutive samples

# Training the Q-network: Experience Replay

Learning from batches of consecutive samples is problematic:

- Samples are correlated  $\Rightarrow$  inefficient learning
- Current Q-network parameters determines next training samples (e.g. if maximizing action is to move left, training samples will be dominated by samples from left-hand size)  $\Rightarrow$  can lead to bad feedback loops

Address these problems using **experience replay**

- Continually update a **replay memory** table of transitions  $(s_t, a_t, r_t, s_{t+1})$  as game (experience) episodes are played
- Train Q-network on random minibatches of transitions from the replay memory, instead of consecutive samples

Each transition can also contribute  
to multiple weight updates  
 $\Rightarrow$  greater data efficiency



# Putting it together: Deep Q-Learning with Experience Replay

---

**Algorithm 1** Deep Q-learning with Experience Replay

---

Initialize replay memory  $\mathcal{D}$  to capacity  $N$

Initialize action-value function  $Q$  with random weights

**for** episode = 1,  $M$  **do**

    Initialize sequence  $s_1 = \{x_1\}$  and preprocessed sequenced  $\phi_1 = \phi(s_1)$

**for**  $t = 1, T$  **do**

        With probability  $\epsilon$  select a random action  $a_t$

        otherwise select  $a_t = \max_a Q^*(\phi(s_t), a; \theta)$

        Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$

        Set  $s_{t+1} = s_t, a_t, x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$

        Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in  $\mathcal{D}$

        Sample random minibatch of transitions  $(\phi_j, a_j, r_j, \phi_{j+1})$  from  $\mathcal{D}$

        Set  $y_j = \begin{cases} r_j & \text{for terminal } \phi_{j+1} \\ r_j + \gamma \max_{a'} Q(\phi_{j+1}, a'; \theta) & \text{for non-terminal } \phi_{j+1} \end{cases}$

        Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))^2$  according to equation 3

**end for**

**end for**

---



# Putting it together: Deep Q-Learning with Experience Replay

---

**Algorithm 1** Deep Q-learning with Experience Replay
 

---

Initialize replay memory  $\mathcal{D}$  to capacity  $N$

Initialize action-value function  $Q$  with random weights

← Initialize replay memory, Q-network

**for** episode = 1,  $M$  **do**

    Initialize sequence  $s_1 = \{x_1\}$  and preprocessed sequenced  $\phi_1 = \phi(s_1)$

**for**  $t = 1, T$  **do**

        With probability  $\epsilon$  select a random action  $a_t$

        otherwise select  $a_t = \max_a Q^*(\phi(s_t), a; \theta)$

        Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$

        Set  $s_{t+1} = s_t, a_t, x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$

        Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in  $\mathcal{D}$

        Sample random minibatch of transitions  $(\phi_j, a_j, r_j, \phi_{j+1})$  from  $\mathcal{D}$

        Set  $y_j = \begin{cases} r_j & \text{for terminal } \phi_{j+1} \\ r_j + \gamma \max_{a'} Q(\phi_{j+1}, a'; \theta) & \text{for non-terminal } \phi_{j+1} \end{cases}$

        Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))^2$  according to equation 3

**end for**

**end for**

---



# Putting it together: Deep Q-Learning with Experience Replay

---

**Algorithm 1** Deep Q-learning with Experience Replay
 

---

Initialize replay memory  $\mathcal{D}$  to capacity  $N$

Initialize action-value function  $Q$  with random weights

**for** episode = 1,  $M$  **do**

    Initialize sequence  $s_1 = \{x_1\}$  and preprocessed sequenced  $\phi_1 = \phi(s_1)$

**for**  $t = 1, T$  **do**

        With probability  $\epsilon$  select a random action  $a_t$

        otherwise select  $a_t = \max_a Q^*(\phi(s_t), a; \theta)$

        Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$

        Set  $s_{t+1} = s_t, a_t, x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$

        Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in  $\mathcal{D}$

        Sample random minibatch of transitions  $(\phi_j, a_j, r_j, \phi_{j+1})$  from  $\mathcal{D}$

        Set  $y_j = \begin{cases} r_j & \text{for terminal } \phi_{j+1} \\ r_j + \gamma \max_{a'} Q(\phi_{j+1}, a'; \theta) & \text{for non-terminal } \phi_{j+1} \end{cases}$

        Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))^2$  according to equation 3

**end for**

**end for**

---

← Play M episodes (full games)



# Putting it together: Deep Q-Learning with Experience Replay

---

**Algorithm 1** Deep Q-learning with Experience Replay
 

---

Initialize replay memory  $\mathcal{D}$  to capacity  $N$

Initialize action-value function  $Q$  with random weights

**for** episode = 1,  $M$  **do**

    Initialize sequence  $s_1 = \{x_1\}$  and preprocessed sequenced  $\phi_1 = \phi(s_1)$

**for**  $t = 1, T$  **do**

        With probability  $\epsilon$  select a random action  $a_t$

        otherwise select  $a_t = \max_a Q^*(\phi(s_t), a; \theta)$

        Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$

        Set  $s_{t+1} = s_t, a_t, x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$

        Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in  $\mathcal{D}$

        Sample random minibatch of transitions  $(\phi_j, a_j, r_j, \phi_{j+1})$  from  $\mathcal{D}$

        Set  $y_j = \begin{cases} r_j & \text{for terminal } \phi_{j+1} \\ r_j + \gamma \max_{a'} Q(\phi_{j+1}, a'; \theta) & \text{for non-terminal } \phi_{j+1} \end{cases}$

        Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))^2$  according to equation 3

**end for**

**end for**

---

← Initialize state  
(starting game  
screen pixels) at the  
beginning of each  
episode



# Putting it together: Deep Q-Learning with Experience Replay

---

**Algorithm 1** Deep Q-learning with Experience Replay
 

---

Initialize replay memory  $\mathcal{D}$  to capacity  $N$

Initialize action-value function  $Q$  with random weights

**for** episode = 1,  $M$  **do**

    Initialize sequence  $s_1 = \{x_1\}$  and preprocessed sequenced  $\phi_1 = \phi(s_1)$

**for**  $t = 1, T$  **do**

        With probability  $\epsilon$  select a random action  $a_t$

        otherwise select  $a_t = \max_a Q^*(\phi(s_t), a; \theta)$

        Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$

        Set  $s_{t+1} = s_t, a_t, x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$

        Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in  $\mathcal{D}$

        Sample random minibatch of transitions  $(\phi_j, a_j, r_j, \phi_{j+1})$  from  $\mathcal{D}$

        Set  $y_j = \begin{cases} r_j & \text{for terminal } \phi_{j+1} \\ r_j + \gamma \max_{a'} Q(\phi_{j+1}, a'; \theta) & \text{for non-terminal } \phi_{j+1} \end{cases}$

        Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))^2$  according to equation 3

**end for**

**end for**

---



For each timestep  $t$   
of the game



# Putting it together: Deep Q-Learning with Experience Replay

---

**Algorithm 1** Deep Q-learning with Experience Replay
 

---

Initialize replay memory  $\mathcal{D}$  to capacity  $N$

Initialize action-value function  $Q$  with random weights

**for** episode = 1,  $M$  **do**

    Initialize sequence  $s_1 = \{x_1\}$  and preprocessed sequenced  $\phi_1 = \phi(s_1)$

**for**  $t = 1, T$  **do**

        With probability  $\epsilon$  select a random action  $a_t$

        otherwise select  $a_t = \max_a Q^*(\phi(s_t), a; \theta)$

        Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$

        Set  $s_{t+1} = s_t, a_t, x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$

        Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in  $\mathcal{D}$

        Sample random minibatch of transitions  $(\phi_j, a_j, r_j, \phi_{j+1})$  from  $\mathcal{D}$

        Set  $y_j = \begin{cases} r_j & \text{for terminal } \phi_{j+1} \\ r_j + \gamma \max_{a'} Q(\phi_{j+1}, a'; \theta) & \text{for non-terminal } \phi_{j+1} \end{cases}$

        Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))^2$  according to equation 3

**end for**

**end for**

---

← With small probability, select a random action (explore), otherwise select greedy action from current policy



# Putting it together: Deep Q-Learning with Experience Replay

---

**Algorithm 1** Deep Q-learning with Experience Replay

---

Initialize replay memory  $\mathcal{D}$  to capacity  $N$

Initialize action-value function  $Q$  with random weights

**for** episode = 1,  $M$  **do**

    Initialize sequence  $s_1 = \{x_1\}$  and preprocessed sequenced  $\phi_1 = \phi(s_1)$

**for**  $t = 1, T$  **do**

        With probability  $\epsilon$  select a random action  $a_t$

        otherwise select  $a_t = \max_a Q^*(\phi(s_t), a; \theta)$

        Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$

        Set  $s_{t+1} = s_t, a_t, x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$

        Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in  $\mathcal{D}$

        Sample random minibatch of transitions  $(\phi_j, a_j, r_j, \phi_{j+1})$  from  $\mathcal{D}$

        Set  $y_j = \begin{cases} r_j & \text{for terminal } \phi_{j+1} \\ r_j + \gamma \max_{a'} Q(\phi_{j+1}, a'; \theta) & \text{for non-terminal } \phi_{j+1} \end{cases}$

        Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))^2$  according to equation 3

**end for**

**end for**

---

Take the action  $a_t$ ,  
and observe the  
reward  $r_t$  and next  
state  $s_{t+1}$



# Putting it together: Deep Q-Learning with Experience Replay

---

**Algorithm 1** Deep Q-learning with Experience Replay

---

Initialize replay memory  $\mathcal{D}$  to capacity  $N$

Initialize action-value function  $Q$  with random weights

**for** episode = 1,  $M$  **do**

    Initialize sequence  $s_1 = \{x_1\}$  and preprocessed sequenced  $\phi_1 = \phi(s_1)$

**for**  $t = 1, T$  **do**

        With probability  $\epsilon$  select a random action  $a_t$

        otherwise select  $a_t = \max_a Q^*(\phi(s_t), a; \theta)$

        Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$

        Set  $s_{t+1} = s_t, a_t, x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$

        Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in  $\mathcal{D}$

        Sample random minibatch of transitions  $(\phi_j, a_j, r_j, \phi_{j+1})$  from  $\mathcal{D}$

        Set  $y_j = \begin{cases} r_j & \text{for terminal } \phi_{j+1} \\ r_j + \gamma \max_{a'} Q(\phi_{j+1}, a'; \theta) & \text{for non-terminal } \phi_{j+1} \end{cases}$

        Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))^2$  according to equation 3

**end for**

**end for**

---

Store transition in  
replay memory





# Putting it together: Deep Q-Learning with Experience Replay

---

**Algorithm 1** Deep Q-learning with Experience Replay
 

---

Initialize replay memory  $\mathcal{D}$  to capacity  $N$

Initialize action-value function  $Q$  with random weights

**for** episode = 1,  $M$  **do**

    Initialize sequence  $s_1 = \{x_1\}$  and preprocessed sequenced  $\phi_1 = \phi(s_1)$

**for**  $t = 1, T$  **do**

        With probability  $\epsilon$  select a random action  $a_t$

        otherwise select  $a_t = \max_a Q^*(\phi(s_t), a; \theta)$

        Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$

        Set  $s_{t+1} = s_t, a_t, x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$

        Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in  $\mathcal{D}$

        Sample random minibatch of transitions  $(\phi_j, a_j, r_j, \phi_{j+1})$  from  $\mathcal{D}$

        Set  $y_j = \begin{cases} r_j & \text{for terminal } \phi_{j+1} \\ r_j + \gamma \max_{a'} Q(\phi_{j+1}, a'; \theta) & \text{for non-terminal } \phi_{j+1} \end{cases}$

        Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))^2$  according to equation 3


**end for**

**end for**

---

← Experience Replay:  
Sample a random  
minibatch of transitions  
from replay memory  
and perform a gradient  
descent step





<https://www.youtube.com/watch?v=V1eYniJ0Rnk>

Video by Károly Zsolnai-Fehér. Reproduced with permission.