Numerical Solution of Elliptic Boundary Value Problems with Variable and Discontinuous Diffusion Coefficients

Project 2 (PDE BVP) Report — Direction 3: Variable Diffusion

Team Q
Tianrui Ji, 2361367 Meichen Ding, 2362344 Jingyan Wei, 2361411
Han Liu, 2364393 Jiasheng Xu, 2251640
Department of Applied Mathematics

November 6, 2026

Abstract

We solve the two-dimensional variable-diffusion boundary value problem $-\nabla \cdot (a\nabla u) = f$ on the unit square using a conservative five-point finite-difference method (FDM). A conforming triangular $\mathcal{P}_1$ finite-element method (FEM) provides a matched depth comparison. With positive shared face conductances and symmetric Dirichlet elimination, the FDM matrix is symmetric positive definite and satisfies a discrete maximum principle. On the smooth manufactured problem $a = 1 + x$, both methods show approximately second-order error in nodal and common reconstructed L^2 norms over four mesh levels. For a layered coefficient jump from 1 to 10, harmonic face averaging recovers the exact solution at nodes to round-off, while arithmetic averaging gives a maximum nodal error of 9.60×10^{-3} at $N = 63$ and a maximum interface-flux error of 0.662. The latter persists near the prescribed horizontal boundaries under refinement, even though the arithmetic matrix remains symmetric and its shared flux is locally conservative. A matched FDM–FEM comparison records errors, residuals, sparse costs, and solver iterations. Independent validation confirms the main numerical claims and identifies the limits of the diagnostics.

Keywords: elliptic boundary value problem, variable diffusion, discontinuous coefficients, conservative finite difference method, harmonic averaging, discrete maximum principle, method of manufactured solutions, finite element method

Contents

1 Introduction and Motivation **3**
1.1 Problem Background 3
1.2 Mathematical Model 3
1.3 Overview of the Report 5

2 Discretisation and Analysis **6**
2.1 Discrete Scheme 6
2.2 Consistency, Truncation Error, and Interface Conductance 8
2.3 Boundary Treatment and Benchmark Exactness 10
2.4 Discrete Structure and Finite Element Comparison Framework 13

3 Algorithm and Implementation **18**
3.1 Data layout and conservative FDM assembly 18
3.2 Linear solvers, residuals and measured cost 19
3.3 Two-dimensional P1 FEM and matched settings 20
3.4 Verification evidence produced by the implementation 20
3.5 Interface diagnostics and coefficient contrast 22
3.6 Reproduction and integration 24

4 Verification and Numerical Experiments **25**
4.1 Checks before interpreting error tables 25
4.2 Smooth coefficient: convergence and method comparison 25
4.3 Layered interface: accuracy, flux, and maximum principle 26
4.4 Mesh size, contrast, and iterative work 26

5 Conclusions **27**

A AI Transparency Log **28**

B Individual Contribution Statements **31**

C Reproducibility and Data Provenance **36**

1 Introduction and Motivation

1.1 Problem Background

Second-order elliptic partial differential equations (PDEs) in divergence form constitute the foundational mathematical framework for modelling steady-state diffusive transport across heterogeneous media [3, 7]. In engineering and physical sciences, the governing law arises from combining a universal conservation principle (such as conservation of thermal energy, mass, or electric charge) with a constitutive flux-gradient relation, notably Fourier's law of heat conduction $\boldsymbol{j} = -a(x,y)\nabla u$, Fick's law of diffusion, or Darcy's law for single-phase fluid flow in porous formations [1, 3].

In realistic applications—such as thermal management of multi-layered semiconductor packaging, groundwater hydrology through stratified sedimentary rock, or electrostatic field simulation in composite dielectrics—the material diffusivity or conductivity $a(x,y)$ varies spatially and frequently exhibits sharp jump discontinuities across internal material interfaces [7]. Solving these problems numerically presents a fundamental challenge: standard pointwise discretisations of the expanded non-divergence operator $-a\Delta u - \nabla a \cdot \nabla u$ break down at material interfaces where ∇a is classically undefined. Failing to honour the divergence structure leads to a loss of local flux conservation, destroys the symmetry of the discrete operator, and produces spurious $\mathcal{O}(1)$ errors in the interfacial transport rate. Consequently, designing and verifying conservative numerical schemes that rigorously preserve physical flux continuity and discrete structural invariants (symmetry, positive definiteness, and monotonicity) is essential for reliable scientific computing.

1.2 Mathematical Model

We consider the two-dimensional stationary diffusion equation posed on the open unit square domain $\Omega = (0,1)^2 \subset \mathbb{R}^2$ with boundary $\partial\Omega = \Gamma_D$ subject to prescribed Dirichlet boundary conditions:

$$-\nabla \cdot \big(a(x,y)\nabla u(x,y)\big) = f(x,y) \quad \text{in } \Omega, \qquad u(x,y) = g(x,y) \quad \text{on } \partial\Omega, \tag{1}$$

where $u : \bar{\Omega} \to \mathbb{R}$ denotes the unknown scalar potential (e.g., temperature or hydraulic head), $f \in L^2(\Omega)$ represents the volumetric source density, and $g \in H^{1/2}(\partial\Omega) \cap C^0(\partial\Omega)$ is the given boundary data. In the special homogeneous, isotropic limit where $a(x,y) \equiv 1$, Equation (1) reduces to the classical Poisson problem:

$$-\Delta u = f \quad \text{in } \Omega, \qquad u|_{\partial\Omega} = g. \tag{2}$$

Assumption 1.1 (Uniform Ellipticity and Boundedness)**.** The diffusion coefficient $a \in L^\infty(\Omega)$ is uniformly positive and bounded almost everywhere in Ω; that is, there exist constants $a_{\min}, a_{\max} \in \mathbb{R}$ such that

$$0 < a_{\min} \le a(x,y) \le a_{\max} < \infty \quad \text{for a.e. } (x,y) \in \Omega. \tag{3}$$

We define the global material contrast ratio as $\varrho_a := a_{\max}/a_{\min} \ge 1$.

Divergence Form vs. Non-Divergence Form and Interface Conditions. When $a \in C^1(\bar{\Omega})$ and $u \in C^2(\Omega) \cap C^0(\bar{\Omega})$, applying the product rule of vector calculus yields the equivalent non-divergence representation:

$$-\nabla \cdot \big(a(x,y)\nabla u\big) = -a(x,y)\Delta u - \nabla a(x,y) \cdot \nabla u = f(x,y). \tag{4}$$

However, when Ω is partitioned into two disjoint subdomains Ω_1 and Ω_2 separated by a smooth internal interface $\Sigma = \partial\Omega_1 \cap \partial\Omega_2$ (such as the vertical material interface $\Sigma = \{x = 1/2\}$), the

coefficient $a(x, y)$ may have a finite jump discontinuity across Σ. In this regime, ∇a involves a Dirac delta distribution supported on Σ, rendering the pointwise differential operator (4) mathematically invalid.

To interpret (1) rigorously for piecewise-smooth coefficients, we invoke the integral conservation law $\int_V \nabla \cdot \boldsymbol{j}\, dxdy = \int_{\partial V} \boldsymbol{j} \cdot \boldsymbol{n}\, ds = \int_V f\, dxdy$ over an arbitrary control volume $V \subset \Omega$ straddling Σ, where $\boldsymbol{j}(x, y) := -a(x, y)\nabla u(x, y)$ is the physical diffusive flux. Shrinking V onto the interface Σ yields the classical piecewise strong formulation coupled with physical transmission conditions:

$$\begin{cases} -\nabla \cdot (a\nabla u) = f & \text{in } \Omega_1 \cup \Omega_2, \\ [\![u]\!]_\Sigma := u|_{\Omega_1} - u|_{\Omega_2} = 0 & \text{on } \Sigma \quad \text{(continuity of potential)}, \\ [\![-a\nabla u \cdot \boldsymbol{n}_\Sigma]\!]_\Sigma := \big(-a_1\nabla u_1 + a_2\nabla u_2\big) \cdot \boldsymbol{n}_\Sigma = 0 & \text{on } \Sigma \quad \text{(continuity of normal flux)}, \end{cases} \tag{5}$$

where $\boldsymbol{n}_\Sigma$ denotes the unit normal vector pointing from Ω_1 into Ω_2. Preserving both conditions in (5) is the central mathematical requirement of our numerical discretisation; classical treatments either resolve the interface by the mesh or modify the stencil across it [4].

Variational Formulation and Well-Posedness. Because $a \in L^\infty(\Omega)$ does not admit classical derivatives across interfaces, the natural mathematical setting for (1) is the Sobolev space $H^1(\Omega)$. Let $\tilde{g} \in H^1(\Omega)$ be a continuous lifting (extension) of the Dirichlet boundary data such that $\tilde{g}|_{\partial\Omega} = g$ in the trace sense, and decompose the solution as $u = u_0 + \tilde{g}$, where $u_0 \in H^1_0(\Omega) := \{v \in H^1(\Omega) : v|_{\partial\Omega} = 0\}$. Multiplying (1) by an arbitrary test function $v \in H^1_0(\Omega)$ and applying Green's first identity over Ω_1 and Ω_2 yields:

$$\int_\Omega a(x, y)\nabla u \cdot \nabla v\, dxdy - \int_{\partial\Omega} a\partial_n u\, v\, ds + \int_\Sigma [\![-a\nabla u \cdot \boldsymbol{n}_\Sigma]\!]_\Sigma v\, ds = \int_\Omega fv\, dxdy. \tag{6}$$

Since $v = 0$ on $\partial\Omega$, the outer-boundary term vanishes. For a piecewise-smooth exact solution, comparison with the weak formulation shows that the interface flux jump must vanish in the trace sense. This is the continuous transmission condition. A conforming Galerkin method enforces the weak equations only for its finite-dimensional test functions; its raw piecewise-linear element fluxes may still jump. The fitted-mesh method below requires no explicit interface multiplier.

We thus arrive at the standard weak formulation: find $u_0 \in H^1_0(\Omega)$ such that

$$\mathcal{B}(u_0, v) = \ell(v) - \mathcal{B}(\tilde{g}, v) \qquad \forall v \in H^1_0(\Omega), \tag{7}$$

where the bilinear form $\mathcal{B}(\cdot, \cdot) : H^1_0(\Omega) \times H^1_0(\Omega) \to \mathbb{R}$ and linear functional $\ell : H^1_0(\Omega) \to \mathbb{R}$ are defined by

$$\mathcal{B}(w, v) := \int_\Omega a(x, y)\nabla w \cdot \nabla v\, dxdy, \qquad \ell(v) := \int_\Omega f(x, y)v(x, y)\, dxdy. \tag{8}$$

Theorem 1.2 (Well-Posedness and A Priori Stability Estimate)**.** *Suppose Assumption 1.1 holds, $f \in L^2(\Omega)$, and $g \in H^{1/2}(\partial\Omega)$. Then the weak formulation* (7) *admits a unique solution $u \in H^1(\Omega)$ with $u - \tilde{g} \in H^1_0(\Omega)$. Moreover, for homogeneous Dirichlet data ($g = 0$), the solution satisfies the a priori stability bound*

$$\|\nabla u\|_{L^2(\Omega)} \le \frac{C_P}{a_{\min}}\|f\|_{L^2(\Omega)}, \qquad \|u\|_{H^1(\Omega)} \le \frac{C_P\sqrt{1 + C_P^2}}{a_{\min}}\|f\|_{L^2(\Omega)}, \tag{9}$$

where $C_P > 0$ is the Poincaré constant of the domain $\Omega = (0, 1)^2$.

Proof. We verify the hypotheses of the Lax–Milgram Lemma [7] on the Hilbert space $V = H^1_0(\Omega)$ equipped with the full norm $\|v\|_{H^1(\Omega)} = (\|v\|^2_{L^2(\Omega)} + \|\nabla v\|^2_{L^2(\Omega)})^{1/2}$:

(i) *Continuity of $\mathcal{B}(\cdot,\cdot)$:* By the Cauchy–Schwarz inequality and the upper bound in (3), for all $w, v \in H_0^1(\Omega)$,

$$\begin{aligned}|\mathcal{B}(w,v)| &\le \int_\Omega |a(x,y)|\,|\nabla w \cdot \nabla v|\,dxdy \le a_{\max}\|\nabla w\|_{L^2(\Omega)}\|\nabla v\|_{L^2(\Omega)} \\ &\le a_{\max}\|w\|_{H^1(\Omega)}\|v\|_{H^1(\Omega)}.\end{aligned}$$

(ii) *Coercivity of $\mathcal{B}(\cdot,\cdot)$:* Recall the Poincaré–Friedrichs inequality on $H_0^1(\Omega)$: there exists $C_P > 0$ (specifically $C_P = 1/(\sqrt{2}\pi)$ on $(0,1)^2$) such that $\|v\|_{L^2(\Omega)} \le C_P\|\nabla v\|_{L^2(\Omega)}$ for all $v \in H_0^1(\Omega)$. Consequently, $\|v\|^2_{H^1(\Omega)} \le (1 + C_P^2)\|\nabla v\|^2_{L^2(\Omega)}$. Using the lower bound in (3), we obtain

$$\mathcal{B}(v,v) = \int_\Omega a(x,y)|\nabla v|^2\,dxdy \ge a_{\min}\|\nabla v\|^2_{L^2(\Omega)} \ge \frac{a_{\min}}{1+C_P^2}\|v\|^2_{H^1(\Omega)} =: \alpha\|v\|^2_{H^1(\Omega)}.$$

(iii) *Boundedness of the right-hand side:* By the Cauchy–Schwarz and Poincaré inequalities, $|\ell(v)| \le \|f\|_{L^2(\Omega)}\|v\|_{L^2(\Omega)} \le C_P\|f\|_{L^2(\Omega)}\|\nabla v\|_{L^2(\Omega)}$, and $|\mathcal{B}(\tilde{g}, v)| \le a_{\max}\|\tilde{g}\|_{H^1(\Omega)}\|v\|_{H^1(\Omega)}$.

By the Lax–Milgram Lemma, a unique weak solution exists. Setting $v = u \in H_0^1(\Omega)$ when $g = 0$ gives $a_{\min}\|\nabla u\|^2_{L^2(\Omega)} \le \mathcal{B}(u,u) = \ell(u) \le C_P\|f\|_{L^2(\Omega)}\|\nabla u\|_{L^2(\Omega)}$, which immediately yields (9). □

Remark 1.3 (Continuous Maximum Principle). In addition to H^1 stability, the divergence-form elliptic operator satisfies a weak maximum principle [1]: when the source term vanishes ($f \equiv 0$ in Ω), the weak solution $u \in H^1(\Omega) \cap C^0(\bar{\Omega})$ attains its extrema on the boundary $\partial\Omega$, satisfying

$$\min_{\partial\Omega} g \le u(x,y) \le \max_{\partial\Omega} g \qquad \forall (x,y) \in \bar{\Omega}. \tag{10}$$

In Section 2.4, we prove that our conservative finite difference scheme preserves an exact discrete analogue of (10) via its M-matrix sign structure.

1.3 Overview of the Report

The remainder of this report is structured as follows. In Section 2, we derive the conservative five-point finite difference scheme from local control-volume flux balances, establish the second-order truncation error for smooth coefficients, derive the resistor-in-series harmonic averaging formula for discontinuous interfaces, and rigorously prove the symmetry, positive definiteness, and M-matrix properties of the assembled algebraic system. Section 3 details our sparse matrix implementation, algorithmic vectorisation in `scipy.sparse`, and solver selection criteria. Section 4 presents our comprehensive verification campaign—including the smooth Method of Manufactured Solutions (MMS) benchmark, algebraic-versus-discretisation error separation, the stratified discontinuous interface benchmark, conditioning sensitivity to coefficient contrast, and a matched-setting depth comparison against $\mathcal{P}_1$ finite elements. Finally, Section 5 summarises our main findings and discusses structural limitations.

2 Discretisation and Analysis

2.1 Discrete Scheme

To discretise the divergence-form elliptic boundary value problem (1) while strictly honouring the local conservation law, we employ a vertex-centred (node-centred) conservative finite-volume discretisation, written in finite-difference form, derived via the finite volume balance principle [1, 3].

Uniform Mesh and Dual Control Volumes. Let $N \in \mathbb{N}$ ($N \geq 2$) denote the number of subintervals along each coordinate axis, defining a uniform Cartesian mesh of spacing $h := 1/N$. Let $n := N - 1$ be the number of interior grid points per spatial direction. The set of all grid nodes on $\bar{\Omega} = [0, 1]^2$ is given by

$$\bar{\Omega}_h := \big\{\boldsymbol{x}_{ij} = (x_i, y_j) = (ih, jh) : 0 \leq i, j \leq N\big\}, \tag{11}$$

which partitions into the interior node set $\Omega_h := \{\boldsymbol{x}_{ij} \in \bar{\Omega}_h : 1 \leq i, j \leq n\}$ of cardinality n^2 and the boundary node set $\Gamma_h := \bar{\Omega}_h \setminus \Omega_h$. Around each interior node $\boldsymbol{x}_{ij} \in \Omega_h$, we construct the dual square control volume (cell)

$$K_{ij} := \big[x_{i-1/2}, x_{i+1/2}\big] \times \big[y_{j-1/2}, y_{j+1/2}\big], \qquad \text{with } x_{i\pm1/2} := x_i \pm \frac{h}{2}, \quad y_{j\pm1/2} := y_j \pm \frac{h}{2}, \tag{12}$$

whose area is $|K_{ij}| = h^2$ and whose boundary $\partial K_{ij} = \gamma_{ij}^E \cup \gamma_{ij}^W \cup \gamma_{ij}^N \cup \gamma_{ij}^S$ consists of four straight cell faces of length h centred at the staggered midpoints $\boldsymbol{x}_{i+1/2,j}$ (East), $\boldsymbol{x}_{i-1/2,j}$ (West), $\boldsymbol{x}_{i,j+1/2}$ (North), and $\boldsymbol{x}_{i,j-1/2}$ (South).

Flux Balance and Five-Point Stencil Derivation. Integrating the governing PDE (1) over the control volume K_{ij} and applying the Gauss divergence theorem yields the exact local balance identity:

$$\int_{K_{ij}} -\nabla \cdot \big(a(x, y)\nabla u\big)\, dxdy = \int_{\partial K_{ij}} \boldsymbol{j} \cdot \boldsymbol{n}\, ds = \int_{K_{ij}} f(x, y)\, dxdy, \tag{13}$$

where $\boldsymbol{j} = -a\nabla u$ is the diffusive flux and $\boldsymbol{n}$ is the outward unit normal on ∂K_{ij}. Approximating the cell source integral by the midpoint quadrature rule $\int_{K_{ij}} f\, dxdy \approx h^2 f_{ij}$ with $f_{ij} := f(x_i, y_j)$, and decomposing the boundary integral over the four faces gives

$$\frac{1}{h}\big(F_{i+1/2,j} - F_{i-1/2,j}\big) + \frac{1}{h}\big(G_{i,j+1/2} - G_{i,j-1/2}\big) = f_{ij}, \tag{14}$$

where $F_{i\pm1/2,j} \approx \frac{1}{h}\int_{\gamma_{ij}^{E/W}} (-a\partial_x u)\, dy$ and $G_{i,j\pm1/2} \approx \frac{1}{h}\int_{\gamma_{ij}^{N/S}} (-a\partial_y u)\, dx$ denote the face-averaged numerical fluxes in the $+x$ and $+y$ directions, respectively; the net outward flux through ∂K_{ij} is then $h(F_{i+1/2,j} - F_{i-1/2,j}) + h(G_{i,j+1/2} - G_{i,j-1/2})$. Let $U_{ij} \approx u(x_i, y_j)$ denote the discrete nodal approximation. Replacing the normal derivatives at the cell faces with centred two-point finite difference quotients scaled by effective face conductances, we define the numerical fluxes:

$$F_{i+1/2,j} := -a_{i+1/2,j}\frac{U_{i+1,j} - U_{ij}}{h}, \qquad F_{i-1/2,j} := -a_{i-1/2,j}\frac{U_{ij} - U_{i-1,j}}{h}, \tag{15}$$

$$G_{i,j+1/2} := -a_{i,j+1/2}\frac{U_{i,j+1} - U_{ij}}{h}, \qquad G_{i,j-1/2} := -a_{i,j-1/2}\frac{U_{ij} - U_{i,j-1}}{h}. \tag{16}$$

For compactness, at node (i, j) we denote the four local face coefficients by $a_E := a_{i+1/2,j}$, $a_W := a_{i-1/2,j}$, $a_N := a_{i,j+1/2}$, and $a_S := a_{i,j-1/2}$. Substituting (15)–(16) into (14) yields the conservative five-point finite difference operator A_h:

$$(A_h U)_{ij} := \frac{1}{h^2}\Big[a_E(U_{ij} - U_{i+1,j}) + a_W(U_{ij} - U_{i-1,j}) + a_N(U_{ij} - U_{i,j+1}) + a_S(U_{ij} - U_{i,j-1})\Big] = f_{ij}. \tag{17}$$

Collecting terms with respect to the five nodal values in the stencil shows that row (i, j) takes the form

$$(A_h U)_{ij} = \frac{1}{h^2}\Big[(a_E + a_W + a_N + a_S)U_{ij} - a_W U_{i-1,j} - a_E U_{i+1,j} - a_S U_{i,j-1} - a_N U_{i,j+1}\Big] = f_{ij}. \quad (18)$$

In difference-star (stencil) notation [1], the discrete operator at node (i, j) is represented as

$$A_h\big|_{(i,j)} = \frac{1}{h^2}\begin{bmatrix} 0 & -a_{i,j+1/2} & 0 \\ -a_{i-1/2,j} & a_\Sigma^{(i,j)} & -a_{i+1/2,j} \\ 0 & -a_{i,j-1/2} & 0 \end{bmatrix}, \quad (19)$$

where $a_\Sigma^{(i,j)} := a_{i+1/2,j} + a_{i-1/2,j} + a_{i,j+1/2} + a_{i,j-1/2}$ denotes the sum of the four face conductances, so that the interior row sums of A_h vanish.

Example 2.1 (Reduction to the Standard Five-Point Laplacian Stencil)**.** In the homogeneous Poisson limit $a(x, y) \equiv 1$, all face conductances equal unity ($a_E = a_W = a_N = a_S = 1$ and $a_\Sigma^{(i,j)} = 4$). Equation (18) reduces identically to the classical five-point discrete Laplacian operator. For any $w \in C^6(\bar{\Omega})$ the operator applied to the *exact* nodal values reads

$$(A_h w)_{ij} = \frac{4w_{ij} - w_{i-1,j} - w_{i+1,j} - w_{i,j-1} - w_{i,j+1}}{h^2} = -\Delta w(x_i, y_j) + \mathcal{O}(h^2), \quad (20)$$

so that A_h is a second-order approximation of $-\Delta$. Note that the discrete unknown satisfies $U_{ij} = u(x_i, y_j) + \mathcal{O}(h^2)$ only, so the two must not be identified.

Grid-to-Vector Index Mapping and Sparsity Structure. To assemble (18) into a matrix-vector algebraic system $A_h \boldsymbol{u} = \boldsymbol{b}$ over the n^2 interior unknowns, we establish a bijective grid-to-vector ordering map. Following the 'indexing='ij'' convention (where axis 0 corresponds to x_i and axis 1 corresponds to y_j, so that y varies fastest within each vertical grid line x_i), we define the zero-based row-major lexicographical index map $\phi : \{1, \ldots, n\}^2 \to \{0, 1, \ldots, n^2 - 1\}$ by

$$k = \phi(i, j) := (i - 1)n + (j - 1), \qquad 1 \le i, j \le n. \quad (21)$$

In Python zero-based interior grid coordinates $(i_0, j_0) := (i - 1, j - 1) \in \{0, \ldots, n - 1\}^2$, Equation (21) reads simply $k = i_0 n + j_0$. The inverse mapping $\phi^{-1}(k)$ uniquely recovers the two-dimensional spatial indices via integer division and modulo arithmetic [7]:

$$i = \lfloor k/n \rfloor + 1, \qquad j = (k \bmod n) + 1, \qquad 0 \le k \le n^2 - 1. \quad (22)$$

Under this ordering, an interior node (i, j) at global row index $k = \phi(i, j)$ couples to its four cardinal neighbours at column indices:

$$\phi(i, j \pm 1) = k \pm 1 \quad \text{(North/South)}, \qquad \phi(i \pm 1, j) = k \pm n \quad \text{(East/West)}. \quad (23)$$

Consequently, the global stiffness matrix $A_h \in \mathbb{R}^{n^2 \times n^2}$ exhibits a symmetric block-tridiagonal structure partitioned into $n \times n$ blocks of size $n \times n$ each:

$$A_h = \frac{1}{h^2}\begin{bmatrix} T_1 & -D_{1,2} & 0 & \cdots & 0 \\ -D_{1,2} & T_2 & -D_{2,3} & \ddots & \vdots \\ 0 & -D_{2,3} & \ddots & \ddots & 0 \\ \vdots & \ddots & \ddots & T_{n-1} & -D_{n-1,n} \\ 0 & \cdots & 0 & -D_{n-1,n} & T_n \end{bmatrix}, \quad (24)$$

where each diagonal block $T_i \in \mathbb{R}^{n\times n}$ $(1 \le i \le n)$ is itself a symmetric tridiagonal matrix encoding the vertical (y-direction) couplings along grid line x_i:

$$(T_i)_{j,j} = a_\Sigma^{(i,j)}, \qquad (T_i)_{j,j+1} = (T_i)_{j+1,j} = -a_{i,j+1/2} \quad (1 \le j \le n-1), \tag{25}$$

and each off-diagonal block $D_{i,i+1} \in \mathbb{R}^{n\times n}$ $(1 \le i \le n-1)$ is a positive diagonal matrix encoding the horizontal (x-direction) face conductances between grid lines x_i and x_{i+1}:

$$D_{i,i+1} = \operatorname{diag}\big(a_{i+1/2,1},\, a_{i+1/2,2},\, \ldots,\, a_{i+1/2,n}\big). \tag{26}$$

Every row of A_h contains at most 5 non-zero entries (located at offsets $0, \pm 1, \pm n$ from the main diagonal). Accounting for boundary-adjacent rows where exterior couplings are transferred to the right-hand side vector $\boldsymbol{b}$, the exact number of non-zero entries in A_h is

$$\operatorname{nnz}(A_h) = n^2 + 4n(n-1) = 5n^2 - 4n = \mathcal{O}(n^2), \tag{27}$$

yielding a sparsity density of $\operatorname{nnz}(A_h)/n^4 \sim 5/n^2 \to 0$ as $n \to \infty$. Storing A_h in compressed sparse row (CSR) format reduces both memory complexity and matrix-vector multiplication cost from $\mathcal{O}(n^4)$ to $\mathcal{O}(n^2)$; all sparse algebra in this report is carried out through SciPy's `scipy.sparse` interface [8, 2].

2.2 Consistency, Truncation Error, and Interface Conductance

The accuracy and physical fidelity of the conservative scheme (17) depend critically on how the face conductances $a_{i\pm1/2,j}$ and $a_{i,j\pm1/2}$ are constructed in smooth versus discontinuous regimes.

Taylor Expansion and Second-Order Consistency for Smooth Coefficients. Let $\mathcal{L}u := -\nabla\cdot(a\nabla u)$ denote the continuous differential operator. For any sufficiently smooth function $w \in C^6(\bar\Omega)$, the local truncation error (LTE) at an interior node $\boldsymbol{x}_{ij} \in \Omega_h$ is defined as the residual left by substituting the exact nodal values $w_{ij} = w(x_i, y_j)$ into the discrete operator:

$$\tau_{ij}(w) := (A_h w)_{ij} - (\mathcal{L}w)(x_i, y_j). \tag{28}$$

In regions where $a(x,y)$ is smooth, the face coefficient at $\boldsymbol{x}_{i+1/2,j}$ can be evaluated either by direct midpoint sampling $a^{\text{mid}}_{i+1/2,j} := a(x_{i+1/2}, y_j)$ or by arithmetic averaging of adjacent nodal values:

$$a^{\text{arith}}_{i+1/2,j} := \frac{a(x_i,y_j) + a(x_{i+1},y_j)}{2}. \tag{29}$$

Theorem 2.2 (Second-Order Local Truncation Error in Smooth Regimes)**.** *Suppose $a \in C^5(\bar\Omega)$ and the exact solution satisfies $u \in C^6(\bar\Omega)$. Then under either exact midpoint evaluation $a_{i\pm1/2,j} = a(x_{i\pm1/2}, y_j)$ or arithmetic averaging* (29)*, the conservative five-point scheme* (17) *is second-order consistent with* (1)*. Specifically, for all $\boldsymbol{x}_{ij} \in \Omega_h$,*

$$\tau_{ij}(u) = \mathcal{O}(h^2) \quad \text{as } h \to 0, \qquad \text{with} \quad \|\boldsymbol{\tau}(u)\|_\infty \le C_{LTE} h^2, \tag{30}$$

where $C_{LTE} > 0$ depends only on $\|a\|_{C^5(\bar\Omega)}$ and $\|u\|_{C^6(\bar\Omega)}$.

Proof. By linearity and coordinate symmetry, it suffices to analyse the x-direction conservative difference operator $\mathcal{D}^h_x u_{ij} := \frac{1}{h}\big[a_{i+1/2,j}\frac{u_{i+1,j}-u_{ij}}{h} - a_{i-1/2,j}\frac{u_{ij}-u_{i-1,j}}{h}\big]$ at a fixed y_j. Suppressing the index j and expanding $u(x_i+h)$ and $u(x_i)$ in Taylor series about the half-point $x_{i+1/2} = x_i + h/2$ (with step $\delta = h/2$) gives

$$u(x_{i+1/2}+\delta) = u_{i+1/2} + \delta u_x\big|_{i+1/2} + \frac{\delta^2}{2}u_{xx}\big|_{i+1/2} + \frac{\delta^3}{6}u_{xxx}\big|_{i+1/2} + \frac{\delta^4}{24}u_{xxxx}\big|_{i+1/2} + \mathcal{O}(h^5), \tag{31}$$

$$u(x_{i+1/2}-\delta) = u_{i+1/2} - \delta u_x\big|_{i+1/2} + \frac{\delta^2}{2}u_{xx}\big|_{i+1/2} - \frac{\delta^3}{6}u_{xxx}\big|_{i+1/2} + \frac{\delta^4}{24}u_{xxxx}\big|_{i+1/2} + \mathcal{O}(h^5). \tag{32}$$

Subtracting the two expansions cancels all even powers of δ, yielding the central difference approximation of the first derivative at $x_{i+1/2}$:

$$\frac{u_{i+1}-u_i}{h} = \frac{u(x_{i+1/2}+\delta)-u(x_{i+1/2}-\delta)}{2\delta} = u_x\big|_{i+1/2} + \frac{h^2}{24}u_{xxx}\big|_{i+1/2} + \mathcal{O}(h^4). \tag{33}$$

Similarly, expanding $a(x_i)$ and $a(x_{i+1})$ about $x_{i+1/2}$ shows that the arithmetic average (29) satisfies

$$a^{\text{arith}}_{i+1/2} = \frac{a(x_{i+1/2}-\delta)+a(x_{i+1/2}+\delta)}{2} = a(x_{i+1/2}) + \frac{h^2}{8}a_{xx}\big|_{i+1/2} + \mathcal{O}(h^4). \tag{34}$$

Thus we may write $a_{i+1/2} = a(x_{i+1/2}) + \theta\frac{h^2}{8}a_{xx}|_{i+1/2} + \mathcal{O}(h^4)$, where $\theta = 0$ for exact midpoint evaluation and $\theta = 1$ for arithmetic averaging. Multiplying $a_{i+1/2}$ by (33) gives the numerical flux expansion at $x_{i+1/2}$:

$$a_{i+1/2}\frac{u_{i+1}-u_i}{h} = (au_x)\big|_{i+1/2} + h^2\psi(x_{i+1/2}) + \mathcal{O}(h^4), \qquad \psi := \frac{1}{24}au_{xxx} + \frac{\theta}{8}a_{xx}u_x. \tag{35}$$

Analogously, at $x_{i-1/2}$ we have $a_{i-1/2}\frac{u_i-u_{i-1}}{h} = (au_x)|_{i-1/2} + h^2\psi(x_{i-1/2}) + \mathcal{O}(h^4)$. Taking the outer central difference of (35) across $[x_{i-1/2}, x_{i+1/2}]$ centered at x_i and applying (33) to the smooth flux function $q(x) := a(x)u_x(x)$ and to $\psi(x)$ yields

$$\begin{aligned}
\mathcal{D}^h_x u_i &= \frac{q(x_i+h/2)-q(x_i-h/2)}{h} + h^2\frac{\psi(x_i+h/2)-\psi(x_i-h/2)}{h} + \mathcal{O}(h^3) \\
&= \partial_x(au_x)\big|_{x_i} + \frac{h^2}{24}\partial_x^3(au_x)\big|_{x_i} + h^2\partial_x\psi\big|_{x_i} + \mathcal{O}(h^4) \\
&= \partial_x(au_x)\big|_{x_i} + \frac{h^2}{24}\partial_x\Big[\partial_x^2(au_x) + au_{xxx} + 3\theta a_{xx}u_x\Big]_{x_i} + \mathcal{O}(h^4).
\end{aligned} \tag{36}$$

Summing the negative of (36) and its y-direction counterpart proves $\tau_{ij}(u) = -\mathcal{D}^h_x u_{ij} - \mathcal{D}^h_y u_{ij} + \nabla\cdot(a\nabla u)|_{ij} = \mathcal{O}(h^2)$, completing the proof. □

Remark 2.3 (The Smooth Benchmark Is Blind to the θ-Correction). Because $a(x,y) = 1+x$ is affine in x and independent of y, the perturbation term $\theta a_{xx}u_x$ in (35) vanishes identically: arithmetic midpoint averaging (29) then coincides *exactly* with pointwise evaluation at the face midpoint, so that the two assembled matrices and right-hand sides are entrywise identical. The smooth benchmark therefore verifies the $\mathcal{O}(h^2)$ order of the conservative stencil but is *blind* to the θ-correction; detecting that correction would require a coefficient with $a_{xx} \not\equiv 0$ (such as $a = 1+x+x^2$). This is a useful check on what a benchmark does and does not test.

Discontinuous Coefficients and Resistor-in-Series Harmonic Averaging. When $a(x,y)$ exhibits a jump discontinuity across a material interface Σ, $a \notin C^1(\bar{\Omega})$ and the Taylor expansion (34) breaks down completely across any grid edge intersected by Σ. To derive the physically consistent face coefficient, consider a horizontal grid edge $[x_i, x_{i+1}]$ of length h at fixed y_j that is intersected by a vertical interface at $x_\Sigma \in (x_i, x_{i+1})$. Let $d_L := x_\Sigma - x_i > 0$ and $d_R := x_{i+1} - x_\Sigma > 0$ (with $d_L + d_R = h$) denote the segment lengths lying in the left medium (diffusivity a_L) and right medium (diffusivity a_R), respectively.

Proposition 2.4 (Exactness of Harmonic/Resistance Face Averaging)**.** *Assume steady one-dimensional flux conservation holds along $[x_i, x_{i+1}]$ with constant normal flux $F = -a(x)\partial_x u(x)$. Then the exact flux across the composite edge $[x_i, x_{i+1}]$ is given by*

$$F = -a_E^{harm}\frac{u(x_{i+1})-u(x_i)}{h}, \qquad \textit{where} \quad a_E^{harm} := \frac{h}{\dfrac{d_L}{a_L} + \dfrac{d_R}{a_R}}. \tag{37}$$

In particular, when the interface bisects the grid edge ($d_L = d_R = h/2$), the effective face conductance reduces to the harmonic mean of a_L and a_R:

$$a_E^{harm} = \frac{2}{\dfrac{1}{a_L} + \dfrac{1}{a_R}} = \frac{2a_L a_R}{a_L + a_R}. \tag{38}$$

Conversely, using the arithmetic average $a_E^{arith} = \frac{1}{2}(a_L + a_R)$ on a bisected interface edge incurs a relative flux error of $\mathcal{O}(1)$ that does not vanish as $h \to 0$:

$$\frac{a_E^{arith} - a_E^{harm}}{a_E^{harm}} = \frac{(a_L - a_R)^2}{4a_L a_R} = \frac{(1-c)^2}{4c} > 0 \qquad \forall c := \frac{a_R}{a_L} \neq 1. \tag{39}$$

Proof. Inside each homogeneous sub-segment (x_i, x_Σ) and (x_Σ, x_{i+1}), the relation $-a(x)\partial_x u = F$ implies $\partial_x u = -F/a(x)$. Integrating $\partial_x u$ over the left and right sub-segments and invoking the continuity of the potential $[\![u]\!]_{x_\Sigma} = 0$ (so that $u(x_\Sigma^-) = u(x_\Sigma^+) =: u_\Sigma$) yields two potential-drop equations:

$$u(x_i) - u_\Sigma = \int_{x_i}^{x_\Sigma} \frac{F}{a_L}\, dx = F\frac{d_L}{a_L}, \qquad u_\Sigma - u(x_{i+1}) = \int_{x_\Sigma}^{x_{i+1}} \frac{F}{a_R}\, dx = F\frac{d_R}{a_R}. \tag{40}$$

Adding the two equations in (40) eliminates the intermediate interface value u_Σ:

$$u(x_i) - u(x_{i+1}) = F\left(\frac{d_L}{a_L} + \frac{d_R}{a_R}\right) = F\big(R_L + R_R\big), \tag{41}$$

where $R_L = d_L/a_L$ and $R_R = d_R/a_R$ represent the thermal/diffusive resistances of the two sub-layers connected in series. Solving (41) for F immediately yields (37), and setting $d_L = d_R = h/2$ gives (38). Finally, direct algebraic manipulation gives

$$\frac{a_E^{\text{arith}}}{a_E^{\text{harm}}} - 1 = \frac{(a_L + a_R)/2}{2a_L a_R/(a_L + a_R)} - 1 = \frac{(a_L + a_R)^2 - 4a_L a_R}{4a_L a_R} = \frac{(a_L - a_R)^2}{4a_L a_R},$$

which depends solely on the material contrast $c = a_R/a_L$ and is independent of the mesh spacing h. □

Remark 2.5 (Mesh Parity Requirement for Interface Benchmarks). A critical choice is mesh parity. With odd N the interface $x = 1/2$ bisects a horizontal grid edge, so the two nodal coefficients on that edge lie in different materials and arithmetic and harmonic rules can be compared directly. We use $N \in \{31, 63, 127, 255\}$. With even N the interface passes through a grid column; a simple average of nodal values then depends on the arbitrary value assigned to $a(1/2)$. An aligned-grid interface scheme must specify its one-sided face construction. The present FDM experiment uses odd N to avoid that ambiguity.

2.3 Boundary Treatment and Benchmark Exactness

For an elliptic boundary value problem, the treatment of boundary rows dictates whether the assembled algebraic system preserves symmetry, positive definiteness, and global convergence order [1, 7].

Symmetric Elimination of Dirichlet Boundary Conditions. On the unit square $\Omega = (0,1)^2$, Dirichlet data $U_{ij} = g(x_i, y_j) =: g_{ij}$ is prescribed at all $4N$ boundary nodes $\boldsymbol{x}_{ij} \in \Gamma_h$ (where $i \in \{0, N\}$ or $j \in \{0, N\}$). Consider two competing assembly strategies:

(i) *Naive identity-row replacement (unsymmetric):* Retaining all $(N+1)^2$ grid nodes in the state vector and replacing each boundary row $k \in \Gamma_h$ of the full matrix $\tilde{A}_h$ by the unit canonical row $\boldsymbol{e}_k^T$ (with $b_k = g_k$), while leaving the couplings $-a_f/h^2$ to node k inside adjacent interior rows $l \in \Omega_h$ untouched, yields $(\tilde{A}_h)_{kl} = 0 \neq (\tilde{A}_h)_{lk} = -a_f/h^2$. This destroys matrix symmetry ($\tilde{A}_h \neq \tilde{A}_h^T$) and precludes the use of conjugate gradient (CG) or sparse Cholesky solvers.

(ii) *Symmetric interior elimination (adopted):* We restrict the unknown vector $\boldsymbol{u} \in \mathbb{R}^{n^2}$ strictly to the n^2 interior nodes ($1 \le i, j \le n$). Whenever an interior stencil (18) at node (i, j) references a boundary neighbour $(i', j') \in \Gamma_h$, the known term $-\frac{a_f}{h^2} g_{i',j'}$ is moved to the right-hand side vector $\boldsymbol{b} \in \mathbb{R}^{n^2}$, where a_f is the specific half-point face conductance connecting (i, j) to (i', j').

Explicitly, using the Kronecker delta $\delta_{m,p}$ ($\delta_{m,p} = 1$ if $m = p$ and 0 otherwise), the modified equation for any interior node $(i, j) \in \{1, \dots, n\}^2$ at global row index $k = \phi(i, j)$ reads:

$$(A_h \boldsymbol{u})_k = \frac{1}{h^2}\Big[a_\Sigma^{(i,j)} U_{ij} - (1-\delta_{i,1}) a_W U_{i-1,j} - (1-\delta_{i,n}) a_E U_{i+1,j} \\ - (1-\delta_{j,1}) a_S U_{i,j-1} - (1-\delta_{j,n}) a_N U_{i,j+1}\Big] = b_k, \tag{42}$$

with the corresponding right-hand side entry assembled as

$$b_k := f_{ij} + \frac{1}{h^2}\Big[\delta_{i,1}\, a_{1/2,j}\, g_{0,j} + \delta_{i,n}\, a_{n+1/2,j}\, g_{N,j} + \delta_{j,1}\, a_{i,1/2}\, g_{i,0} + \delta_{j,n}\, a_{i,n+1/2}\, g_{i,N}\Big]. \tag{43}$$

Crucially, in variable-diffusion problems the boundary value $g_{0,j}$ is weighted by the *actual* conductance $a_{1/2,j}$ of the boundary-adjacent edge (e.g. a_L or a_R in the layered benchmark), *not* by a constant unit weight; replacing $a_{1/2,j}$ by 1 would give an inconsistent boundary row. Because the boundary values g_{ij} are exact, symmetric Dirichlet elimination introduces zero additional boundary closure error and preserves the global $\mathcal{O}(h^2)$ accuracy of the interior operator.

Hand-Checked 4×4 System for $n = 2$ ($N = 3, h = 1/3$). To verify our assembly logic and grid-to-vector map (21) prior to large-scale computation (Tutorial 5 gate), we derive the exact 4×4 matrix by hand for $n = 2$ interior points per direction. The four interior nodes are ordered as $k = 0 \leftrightarrow (1,1)$, $k = 1 \leftrightarrow (1,2)$, $k = 2 \leftrightarrow (2,1)$, and $k = 3 \leftrightarrow (2,2)$:

$$\boldsymbol{u} = \begin{bmatrix} U_{1,1} \\ U_{1,2} \\ U_{2,1} \\ U_{2,2} \end{bmatrix}, \qquad A_h = \frac{1}{h^2}\hat{K} = \frac{1}{h^2}\begin{bmatrix} a_\Sigma^{(1,1)} & -a_{1,3/2} & -a_{3/2,1} & 0 \\ -a_{1,3/2} & a_\Sigma^{(1,2)} & 0 & -a_{3/2,2} \\ -a_{3/2,1} & 0 & a_\Sigma^{(2,1)} & -a_{2,3/2} \\ 0 & -a_{3/2,2} & -a_{2,3/2} & a_\Sigma^{(2,2)} \end{bmatrix}, \tag{44}$$

where each corner node has two interior neighbours and two boundary faces, giving the right-hand side vector

$$\boldsymbol{b} = \begin{bmatrix} f_{1,1} \\ f_{1,2} \\ f_{2,1} \\ f_{2,2} \end{bmatrix} + \frac{1}{h^2}\begin{bmatrix} a_{1/2,1} g_{0,1} + a_{1,1/2} g_{1,0} \\ a_{1/2,2} g_{0,2} + a_{1,5/2} g_{1,3} \\ a_{5/2,1} g_{3,1} + a_{2,1/2} g_{2,0} \\ a_{5/2,2} g_{3,2} + a_{2,5/2} g_{2,3} \end{bmatrix}. \tag{45}$$

In the constant-coefficient Poisson limit $a(x, y) \equiv 1$, the scaled stiffness matrix $\hat{K} = h^2 A_h$ reduces to

$$\hat{K}_{\text{Poisson}} = \begin{bmatrix} 4 & -1 & -1 & 0 \\ -1 & 4 & 0 & -1 \\ -1 & 0 & 4 & -1 \\ 0 & -1 & -1 & 4 \end{bmatrix}, \tag{46}$$

which matches the output of our sparse assembly routine entry-by-entry to machine precision.

Analytical Derivation and Nodal Exactness for the Stratified Benchmark. Consider the second benchmark problem: $f \equiv 0$ in $\Omega = (0,1)^2$ with a piecewise-constant layered diffusivity jumping across the vertical interface $\Sigma = \{x = 1/2\}$:

$$a(x,y) = a(x) = \begin{cases} a_L, & 0 \le x < 1/2, \\ a_R, & 1/2 < x \le 1, \end{cases} \qquad \text{with contrast ratio } c := \frac{a_R}{a_L} > 0, \tag{47}$$

subject to Dirichlet boundary conditions $u(0,y) = 0$, $u(1,y) = 1$, and $u(x,0) = u(x,1) = u_*(x)$. Because the data is independent of y, the two-dimensional BVP reduces to the one-dimensional interface problem $-(a(x)u_*'(x))' = 0$ on $(0,1)$ with $u_*(0) = 0$ and $u_*(1) = 1$.

Integrating $-(au_*')' = 0$ shows that the physical normal flux $J_* := -a(x)u_*'(x)$ is constant within each subdomain, so $u_*(x)$ is piecewise linear: $u_*(x) = k_L x$ for $x \in [0, 1/2]$ (satisfying $u_*(0) = 0$) and $u_*(x) = k_R(x-1) + 1$ for $x \in [1/2, 1]$ (satisfying $u_*(1) = 1$). Enforcing the two physical transmission conditions (5) at $x = 1/2$:

(1) *Potential continuity:* $u_*(1/2^-) = u_*(1/2^+) \implies \frac{1}{2}k_L = -\frac{1}{2}k_R + 1 \implies k_L + k_R = 2.$

(2) *Normal flux continuity:* $-a_L u_*'(1/2^-) = -a_R u_*'(1/2^+) \implies a_L k_L = a_R k_R \implies k_L = c k_R.$

Solving this 2×2 linear system yields $k_L = \frac{2c}{1+c}$ and $k_R = \frac{2}{1+c}$. Hence, for any contrast $c = a_R/a_L$, the exact analytical solution and constant physical flux are

$$u_*(x) = \begin{cases} \dfrac{2c}{1+c}x, & 0 \le x \le \frac{1}{2}, \\ \dfrac{2x+c-1}{1+c}, & \frac{1}{2} \le x \le 1, \end{cases} \qquad J_* = -a(x)u_*'(x) = -\frac{2a_L a_R}{a_L + a_R} = -a_E^{\text{harm}} \frac{u_*(1) - u_*(0)}{1-0}, \tag{48}$$

Note the dimensions in the last equality: the flux equals the harmonic face conductance multiplied by the mean potential gradient across $[0,1]$. The two quantities coincide numerically only because $u_*(1) - u_*(0) = 1$ and the interval has unit length.

Specifically, for the benchmark specification $a_L = 1$ and $a_R = 10$ ($c = 10$), Equation (48) gives

$$u_*(x) = \begin{cases} \dfrac{20}{11}x, & 0 \le x \le \frac{1}{2}, \\ \dfrac{2x+9}{11}, & \frac{1}{2} \le x \le 1, \end{cases} \qquad u_*\big(\tfrac{1}{2}\big) = \frac{10}{11}, \qquad J_* = -\frac{20}{11}. \tag{49}$$

Remark 2.6 (Why Theorem 2.2 Does Not Cover the Stratified Benchmark). For the layered coefficient (47) the exact solution u_* is only piecewise linear, hence $u_* \notin H^2(\Omega)$ and the Taylor expansions behind Theorem 2.2 fail across Σ; the interface conductance is not a small perturbation of a smooth midpoint value but an exactly derived composite resistance. Consequently the stratified benchmark must be verified through *exactness* (Theorem 2.7) rather than through an asymptotic order, while refinement studies reveal the behaviour of the arithmetic comparison. The two benchmarks therefore play complementary roles: one certifies the order, the other certifies the interface condition.

Theorem 2.7 (Nodal exactness of the harmonic interface rule)**.** *Let $N = 2m+1$, so that the interface $x = 1/2$ bisects the edge from x_m to x_{m+1}. With the exact boundary data in* (48)*, harmonic averaging reproduces the exact solution at every grid node and the numerical x-flux equals $J_* = -2a_L a_R/(a_L + a_R)$ on every vertical face.*

Proof. The exact solution is independent of y, so all discrete y-fluxes vanish. On a face contained in either material, the solution is linear and the two-point flux equals J_*. On the bisected interface edge, Proposition 2.4 gives the same flux. Hence every interior flux difference is zero and the exact nodal vector satisfies the discrete equations and boundary values. Positive definiteness from Theorem 2.9 gives uniqueness. □

Remark 2.8 (Arithmetic averaging and the two-dimensional boundary). The arithmetic interface conductance has the fixed relative error (39). In a one-dimensional chain with only endpoint Dirichlet data, summing edge resistances gives

$$J_h^{\text{arith}} = -\left(\frac{1-h}{2a_L} + \frac{h}{(a_L+a_R)/2} + \frac{1-h}{2a_R}\right)^{-1}, \qquad \frac{J_h^{\text{arith}} - J_*}{J_*} = h\frac{(a_L-a_R)^2}{(a_L+a_R)^2} + \mathcal{O}(h^2).$$

This one-dimensional expression is not the two-dimensional solution here: the exact Dirichlet trace is also imposed on $y = 0$ and $y = 1$, whereas the arithmetic interior solution differs from that trace. The numerical results therefore report the full two-dimensional nodal and face-flux errors rather than extending the one-dimensional formula to the square. A shared face flux still gives discrete conservation under arithmetic averaging.

2.4 Discrete Structure and Finite Element Comparison Framework

We now establish the fundamental algebraic properties of the assembled finite difference matrix $A_h \in \mathbb{R}^{n^2\times n^2}$ after symmetric Dirichlet elimination (42) and state the variational finite element formulation used in our $\star\star$ depth comparison.

Theorem 2.9 (Symmetry, Positive Definiteness, M-Matrix Structure, and Discrete Maximum Principle)**.** *Suppose Assumption 1.1 holds so that every face conductance satisfies* $0 < a_{\min} \le a_f \le a_{\max}$. *Then the* $n^2\times n^2$ *matrix* A_h *defined by* (42) *satisfies the following structural properties:*

(i) ***Symmetry*** *(*$A_h = A_h^T$*):* A_h *is exactly symmetric whenever adjacent nodes share the same face conductance (*$a_{i+1/2,j}$ *for row* (i,j) *East and row* $(i+1,j)$ *West), irrespective of whether arithmetic or harmonic averaging is employed.*

(ii) ***Positive Definiteness*** *(*$\boldsymbol{v}^T A_h \boldsymbol{v} > 0$*):* *For any non-zero vector* $\boldsymbol{v} \in \mathbb{R}^{n^2} \setminus \{\mathbf{0}\}$ *(extended by* $v_{ij} = 0$ *on* Γ_h*), the quadratic form satisfies the discrete energy identity*

$$\boldsymbol{v}^T A_h \boldsymbol{v} = \frac{1}{h^2} \sum_{e=(k,l)\in\mathcal{E}_{int}} a_e (v_k - v_l)^2 + \frac{1}{h^2} \sum_{b=(k,\partial)\in\mathcal{E}_{bdry}} a_b v_k^2 > 0, \tag{50}$$

where $\mathcal{E}_{int}$ *is the set of* $2n(n-1)$ *interior grid edges and* $\mathcal{E}_{bdry}$ *is the set of* $4n$ *boundary-connecting edges. Hence* A_h *is Symmetric Positive Definite (SPD).*

(iii) ***M-Matrix Sign Structure and Inverse Positivity*** *(*$A_h^{-1} > 0$*):* A_h *is a Z-matrix with strictly positive diagonal entries* $(A_h)_{kk} = a_\Sigma^{(i,j)}/h^2 > 0$, *non-positive off-diagonal entries* $(A_h)_{kl} \le 0$ $(k \ne l)$, *and non-negative row sums* $\sum_{l=0}^{n^2-1}(A_h)_{kl} \ge 0$, *with strict inequality* $\sum_l (A_h)_{kl} \ge a_{\min}/h^2 > 0$ *on all* $4n-4$ *boundary-adjacent rows. Since the underlying* $n\times n$ *grid graph is connected,* A_h *is irreducibly diagonally dominant and therefore a non-singular* ***M-matrix*** *with a strictly positive inverse* $(A_h^{-1})_{kl} > 0$ *for all* k, l *[1].*

(iv) ***Discrete Maximum Principle (DMP):*** *When* $f \equiv 0$, *the discrete solution* $\boldsymbol{u} = A_h^{-1}\boldsymbol{b}$ *satisfies*

$$\min_{\boldsymbol{x}_{ij}\in\Gamma_h} g_{ij} \le U_{ij} \le \max_{\boldsymbol{x}_{ij}\in\Gamma_h} g_{ij} \qquad \forall (i,j) \in \{1,\dots,n\}^2. \tag{51}$$

Proof. (i) Consider any pair of adjacent interior nodes $k = \phi(i,j)$ and $l = \phi(i+1,j)$. In row k of (42), the coefficient multiplying $U_{i+1,j}$ is $-a_E^{(i,j)}/h^2 = -a_{i+1/2,j}/h^2$. In row l, the coefficient multiplying U_{ij} is $-a_W^{(i+1,j)}/h^2 = -a_{(i+1)-1/2,j}/h^2 = -a_{i+1/2,j}/h^2$. Thus $(A_h)_{kl} = (A_h)_{lk}$; vertical neighbours k and $k+1$ follow identically, and all other off-diagonal entries are zero.

(ii) Let $\boldsymbol{v} \in \mathbb{R}^{n^2}$ be extended by zero to boundary nodes ($v_m = 0$ for $m \in \Gamma_h$). Each interior edge $e = (k,l) \in \mathcal{E}_{\text{int}}$ contributes $a_e(v_k - v_l)/h^2$ to row k (multiplied by v_k) and $a_e(v_l - v_k)/h^2$ to row l (multiplied by v_l). Summing over all k pairs these two terms into $\frac{a_e}{h^2}[v_k(v_k - v_l) + v_l(v_l -$

$v_k)] = \frac{a_e}{h^2}(v_k - v_l)^2$. Each boundary edge $b = (k, \partial) \in \mathcal{E}_{\text{bdry}}$ contributes $\frac{a_b}{h^2} v_k(v_k - 0) = \frac{a_b}{h^2} v_k^2$. This establishes (50). Since $a_e, a_b \geq a_{\min} > 0$, $\boldsymbol{v}^T A_h \boldsymbol{v} \geq 0$. If $\boldsymbol{v}^T A_h \boldsymbol{v} = 0$, then $v_k = 0$ on all boundary-adjacent nodes ($b \in \mathcal{E}_{\text{bdry}}$) and $v_k = v_l$ across all interior edges ($e \in \mathcal{E}_{\text{int}}$); by grid connectivity, $\boldsymbol{v} = \mathbf{0}$.

(iii)–(iv) By (42), for an interior row $k = \phi(i, j)$, subtracting the magnitudes of the off-diagonal entries from the diagonal entry leaves the boundary face conductances:

$$\sum_{l=0}^{n^2-1} (A_h)_{kl} = \frac{1}{h^2}\Big[\delta_{i,1} a_{1/2,j} + \delta_{i,n} a_{n+1/2,j} + \delta_{j,1} a_{i,1/2} + \delta_{j,n} a_{i,n+1/2}\Big] =: r_k \geq 0, \tag{52}$$

with $r_k > 0$ whenever $i \in \{1, n\}$ or $j \in \{1, n\}$. By Taussky's theorem [1], an irreducibly diagonally dominant Z-matrix is an M-matrix with $A_h^{-1} > 0$. Now let $\mathbf{1} = (1, \ldots, 1)^T \in \mathbb{R}^{n^2}$; Equation (52) states that $(A_h \mathbf{1})_k = r_k$. When $f \equiv 0$, the right-hand side (43) satisfies $r_k g_{\min} \leq b_k \leq r_k g_{\max}$, where $g_{\min} = \min_{\Gamma_h} g$ and $g_{\max} = \max_{\Gamma_h} g$. Consequently,

$$A_h\big(\boldsymbol{u} - g_{\min}\mathbf{1}\big) = \boldsymbol{b} - g_{\min}\boldsymbol{r} \geq \mathbf{0}, \qquad A_h\big(g_{\max}\mathbf{1} - \boldsymbol{u}\big) = g_{\max}\boldsymbol{r} - \boldsymbol{b} \geq \mathbf{0}.$$

Multiplying both inequalities by the non-negative matrix $A_h^{-1} > 0$ preserves the componentwise order, proving $g_{\min}\mathbf{1} \leq \boldsymbol{u} \leq g_{\max}\mathbf{1}$. □

Remark 2.10 (Structural Invariants vs. Interfacial Accuracy and SPD Verification). Theorem 2.9 reveals two vital methodological lessons for our verification campaign in Section 4:

(1) **Matrix symmetry and DMP do not imply interfacial accuracy:** Because arithmetic face averaging (29) produces positive shared face coefficients $a_f^{\text{arith}} > 0$, the arithmetic-averaged matrix A_h^{arith} is *also* symmetric, SPD, and an M-matrix, and its stratified solution *also* obeys $0 \leq U_{ij}^{\text{arith}} \leq 1$. Thus, observing that a numerical solution lies between $[0, 1]$ or that $\|A_h - A_h^T\| = 0$ is purely a consequence of the algebraic sign structure and shared face assembly—it is **not** evidence that the physical interface condition $[\![-a\partial_n u]\!]_\Sigma = 0$ is accurately resolved!

(2) **Rigorous verification of positive definiteness:** In numerical experiments, computing $\boldsymbol{v}^T A_h \boldsymbol{v} > 0$ for a finite collection of random vectors $\boldsymbol{v}$ is merely a sanity diagnostic, not a proof of positive definiteness. The primary proof of SPD is Theorem 2.9(ii) combined with verifying $\max_{k,l} |(A_h)_{kl} - (A_h)_{lk}|/\|A_h\| \approx 0$ and either succeeding in a sparse Cholesky factorisation $A_h = LL^T$ or computing the smallest eigenvalue $\lambda_{\min}(A_h) > 0$ via Lanczos iteration ('scipy.sparse.linalg.eigsh').

Discrete Stability and $\mathcal{O}(h^2)$ Convergence. The truncation error of Theorem 2.2 controls consistency; convergence additionally needs a stability estimate. The M-matrix structure of Theorem 2.9 supplies one, but only in the energy norm: as we point out below, it does *not* give an entrywise comparison of inverses, so the maximum-norm bound requires a separate barrier argument.

Theorem 2.11 (Discrete Stability and $\mathcal{O}(h^2)$ Convergence in the Smooth Regime)**.** *Suppose $a \in C^5(\bar{\Omega})$ satisfies Assumption 1.1, let $u \in C^6(\bar{\Omega})$ solve (1) with $f \in C^2(\bar{\Omega})$ and $g = 0$, and let $\boldsymbol{U}$ solve (42)–(43) with $\boldsymbol{b} = \boldsymbol{f}$. Write $\boldsymbol{\tau}(u)$ for the truncation error of Theorem 2.2 and set $\boldsymbol{e} := \boldsymbol{U} - \boldsymbol{u}$, $\boldsymbol{u} := (u(\boldsymbol{x}_{ij}))$.*

(i) ***Energy stability, uniform bound.*** *For every $h \leq 1$ the smallest eigenvalue of A_h satisfies $\lambda_{\min}(A_h) \geq 8a_{\min}$. Hence $\|A_h^{-1}\|_2 \leq 1/(8a_{\min})$ and, in the discrete L^2 norm $\|\boldsymbol{v}\|_{h,2} := h\|\boldsymbol{v}\|_2$,*

$$\|\boldsymbol{e}\|_{h,2} \;\leq\; \frac{1}{8a_{\min}} \|\boldsymbol{\tau}(u)\|_{h,2} \;\leq\; \frac{C_{LTE}}{8a_{\min}} h^2. \tag{53}$$

(ii) ***Maximum-norm stability.*** *There is a constant $C_{stab} > 0$, depending only on $a_{\min}$ and $\|a_x\|_{L^\infty(\Omega)}$ and not on h, such that for all sufficiently small h*

$$\|\boldsymbol{e}\|_\infty \;\le\; C_{stab}\,\|\boldsymbol{\tau}(u)\|_\infty \;\le\; C_{stab}C_{LTE}\,h^2, \tag{54}$$

and C_{stab} may be taken as the uniform upper bound $1/(8a_{\min})$ when a is constant.

Proof. Since the exact boundary data cancel in (43), subtracting $A_h\boldsymbol{u}$ from $A_h\boldsymbol{U} = \boldsymbol{b}$ gives the error equation $A_h\boldsymbol{e} = -\boldsymbol{\tau}(u)$, the quadrature error of f having been absorbed into $\boldsymbol{\tau}(u)$.

(i) The energy identity (50) together with $a_f \ge a_{\min}$ gives $\boldsymbol{v}^T A_h \boldsymbol{v} \ge a_{\min}\boldsymbol{v}^T A_h^{(1)}\boldsymbol{v}$ for all $\boldsymbol{v} \in \mathbb{R}^{n^2}$, i.e. $A_h \succeq a_{\min}A_h^{(1)}$ in the Loewner order. By Courant–Fischer min–max, $\lambda_{\min}(A_h) \ge a_{\min}\lambda_{\min}(A_h^{(1)})$. The lowest eigenvalue of the two-dimensional discrete Laplacian is $\lambda_{\min}(A_h^{(1)}) = \frac{8}{h^2}\sin^2(\frac{\pi h}{2})$, and $\sin\theta \ge \frac{2}{\pi}\theta$ on $[0, \frac{\pi}{2}]$ yields $\lambda_{\min}(A_h) \ge 8a_{\min}$ for all $h \le 1$ (asymptotically $\lambda_{\min}(A_h) \ge 2\pi^2 a_{\min} + \mathcal{O}(h^2)$, a much stronger bound). Since A_h is symmetric positive definite, $\|A_h^{-1}\|_2 = \lambda_{\min}(A_h)^{-1} \le 1/(8a_{\min})$. Multiplying $\|\boldsymbol{e}\|_2 \le \|A_h^{-1}\|_2\|\boldsymbol{\tau}(u)\|_2$ by h gives $\|\boldsymbol{e}\|_{h,2} \le \|A_h^{-1}\|_2\|\boldsymbol{\tau}(u)\|_{h,2}$, and $\|\boldsymbol{\tau}(u)\|_{h,2} = h\|\boldsymbol{\tau}(u)\|_2 \le hn\|\boldsymbol{\tau}(u)\|_\infty \le \|\boldsymbol{\tau}(u)\|_\infty \le C_{\mathrm{LTE}}h^2$ because $hn = 1 - 1/N < 1$. This proves (53).

(ii) A Loewner bound such as (i) does *not* control $\|\boldsymbol{e}\|_\infty$. By Theorem 2.9(iii) we have $A_h^{-1} \ge 0$ entrywise, hence $\|A_h^{-1}\|_\infty = \max_k(A_h^{-1}\mathbf{1})_k = \|\boldsymbol{w}\|_\infty$ for the vector $\boldsymbol{w} := A_h^{-1}\mathbf{1}$ solving $A_h\boldsymbol{w} = \mathbf{1}$ with zero boundary data, and the entrywise comparison that would deliver $\boldsymbol{w}$ from the constant-coefficient case is unavailable (Remark 2.12). We therefore use a barrier in the spirit of Hackbusch [1]. Set

$$\gamma := \frac{\|a_x\|_{L^\infty(\Omega)} + 1}{a_{\min}} > 0, \qquad \Phi(x,y) := C_0\big(e^{\gamma} - e^{\gamma x}\big), \qquad C_0 := \frac{2}{\gamma}.$$

Then $\Phi \ge 0$ on $\bar\Omega$ because $x \le 1$, and $\nabla\Phi = (-C_0\gamma e^{\gamma x}, 0)$, so

$$-\nabla\cdot(a\nabla\Phi) \;=\; C_0\gamma e^{\gamma x}\big(a\gamma + a_x\big) \;\ge\; C_0\gamma e^{\gamma x}\big(a_{\min}\gamma - \|a_x\|_\infty\big) \;=\; C_0\gamma e^{\gamma x} \;\ge\; 2.$$

Because Φ is smooth and independent of y, the truncation error estimate of Theorem 2.2 applies to Φ, giving $\big|(A_h\boldsymbol{\Phi})_k + \nabla\cdot(a\nabla\Phi)(\boldsymbol{x}_k)\big| \le Ch^2$; hence $(A_h\boldsymbol{\Phi})_k \ge 1$ for all k once $h \le h_0$, where $\boldsymbol{\Phi}$ denotes the nodal vector of Φ. Let $\boldsymbol{z} := \boldsymbol{\Phi} - \boldsymbol{w}$. Then $A_h\boldsymbol{z} = A_h\boldsymbol{\Phi} - \mathbf{1} \ge \mathbf{0}$, and on Γ_h we have $z_k = \Phi(\boldsymbol{x}_k) - 0 \ge 0$ because $\boldsymbol{w}$ vanishes on the boundary. Multiplying by the non-negative matrix A_h^{-1} gives $\boldsymbol{z} \ge \mathbf{0}$, that is $\mathbf{0} \le \boldsymbol{w} \le \boldsymbol{\Phi}$, whence

$$\|A_h^{-1}\|_\infty = \|\boldsymbol{w}\|_\infty \le \|\boldsymbol{\Phi}\|_\infty = C_0\big(e^{\gamma} - 1\big) =: C_{\mathrm{stab}},$$

independent of h and depending only on $a_{\min}$ and $\|a_x\|_{L^\infty(\Omega)}$. This proves (54). Finally, if $a \equiv a_{\min}$ is constant, take $\varphi(x) = \frac{1}{2a_{\min}}x(1-x)$ and extend $\boldsymbol{\varphi}$ by its own boundary values. The full five-point stencil is exact on this quadratic. After eliminating the boundary nodes, the matrix action on its interior values satisfies $A_h\boldsymbol{\varphi} \ge \mathbf{1}$ because the omitted boundary values are non-negative. Since $A_h\boldsymbol{w} = \mathbf{1}$ and A_h^{-1} is non-negative, $\mathbf{0} \le \boldsymbol{w} \le \boldsymbol{\varphi}$. Thus $\|\boldsymbol{w}\|_\infty \le \|\boldsymbol{\varphi}\|_\infty = 1/(8a_{\min})$, which is a uniform bound for the two-dimensional problem. Equality holds in the corresponding one-dimensional problem, where φ vanishes on its whole boundary. □

Remark 2.12 (Why the Loewner order does not give an entrywise bound). The step "$A_h \succeq a_{\min}A_h^{(1)}$ and both matrices are M-matrices, hence $A_h^{-1} \le a_{\min}^{-1}(A_h^{(1)})^{-1}$ entrywise" would be convenient but is *false*: it confuses the spectral (Loewner) order with the entrywise order. The classical monotonicity of M-matrix inverses, $A \ge B \Rightarrow A^{-1} \le B^{-1}$, requires the *entrywise* hypothesis $A \ge B$, which fails here, since diagonal dominance forces the off-diagonal entries $-a_f/h^2$ to become *more* negative as a grows. The spectral comparison yields $\|A_h^{-1}\|_2 \le a_{\min}^{-1}\|(A_h^{(1)})^{-1}\|_2$, which does not control row sums. This is why the maximum-norm result above uses a barrier argument instead.

Remark 2.13. The sharp constant $1/(8a_{\min})$ is attained for constant coefficients in one space dimension, where the discrete solution of $-\Delta_h u = 1$ is $\frac{1}{2}x(1-x)$, whose maximum is $\frac{1}{8}$. In two dimensions the function $\frac{1}{2}x(1-x)$, extended constantly in y, is a supersolution of $-\Delta u = 1$ with non-negative boundary data, so $\max u \le \frac{1}{8}$ there as well, although the exact maximum is 0.0736 and the constant is therefore not attained; both statements are consistent with, but not implied by, the variable-coefficient case. Note also that Theorem 2.11 does not cover the stratified benchmark: there $u_* \notin H^2(\Omega)$ and the relevant statement is the exactness of Theorem 2.7 (see Remark 2.6).

Spectral Conditioning with Respect to Mesh Size h and Contrast Ratio ϱ_a. From the discrete quadratic form (50) and the uniform bounds $a_{\min} \le a_f \le a_{\max}$, we can bound the Rayleigh quotient of A_h in terms of the standard constant-coefficient Poisson matrix $A_h^{(1)}$ ($a \equiv 1$):

$$a_{\min} \frac{\boldsymbol{v}^T A_h^{(1)} \boldsymbol{v}}{\boldsymbol{v}^T \boldsymbol{v}} \le \frac{\boldsymbol{v}^T A_h \boldsymbol{v}}{\boldsymbol{v}^T \boldsymbol{v}} \le a_{\max} \frac{\boldsymbol{v}^T A_h^{(1)} \boldsymbol{v}}{\boldsymbol{v}^T \boldsymbol{v}} \qquad \forall \boldsymbol{v} \neq \boldsymbol{0}. \tag{55}$$

Since the extreme eigenvalues of the 2D discrete Laplacian $A_h^{(1)}$ on $(0,1)^2$ are $\lambda_{\min}(A_h^{(1)}) = \frac{8}{h^2}\sin^2(\frac{\pi h}{2}) = 2\pi^2 + \mathcal{O}(h^2)$ and $\lambda_{\max}(A_h^{(1)}) = \frac{8}{h^2}\cos^2(\frac{\pi h}{2}) = \frac{8}{h^2} - 2\pi^2 + \mathcal{O}(h^2)$ [7], Courant–Fischer min-max theory implies that the spectral condition number $\kappa_2(A_h) := \lambda_{\max}(A_h)/\lambda_{\min}(A_h)$ scales as

$$\kappa_2(A_h) \le \frac{a_{\max}}{a_{\min}} \kappa_2\big(A_h^{(1)}\big) = \varrho_a \cot^2\left(\frac{\pi h}{2}\right) = \frac{4}{\pi^2}\, \varrho_a\, h^{-2} + \mathcal{O}(\varrho_a). \tag{56}$$

Equation (56) is an *upper bound*, and it suggests two distinct asymptotic regimes that we test in Section 4: (i) at fixed material contrast $\varrho_a = c$, refining the mesh lets $\kappa_2(A_h)$ grow at most quadratically, $\mathcal{O}(h^{-2})$; (ii) on a fixed mesh h, the bound grows linearly in the diffusivity jump ratio $c = a_R/a_L$, i.e. $\mathcal{O}(c)$, directly inflating the iteration count of unpreconditioned Krylov or stationary iterative solvers (e.g., CG iter $\propto \sqrt{\kappa_2(A_h)}$).

Conforming Linear Finite Element ($\mathcal{P}_1$-FEM) Formulation for Depth Comparison ($\star\star$). To conduct a rigorous $\star\star$ depth comparison against our conservative FDM scheme, we also discretise the weak formulation (7) using conforming piecewise-linear finite elements ($\mathcal{P}_1$-FEM) [3, 7]. We partition $\bar{\Omega} = [0,1]^2$ into a uniform Friedrichs–Keller triangulation $\mathcal{T}_h$ obtained by splitting each $h \times h$ grid cell into two right triangles along its diagonal, yielding $2N^2$ triangular elements $T \in \mathcal{T}_h$ and n^2 interior vertices. Crucially, for the stratified problem (47), choosing N even in FEM aligns the vertical grid line $x = 1/2$ with element edges so that no triangle $T \in \mathcal{T}_h$ straddles the interface Σ, ensuring $a|_T$ is smooth (or constant) inside each element. This is deliberately the *opposite* parity from the FDM experiments of Remark 2.5, where N is taken odd so that the interface is *not* resolved by the mesh — which is exactly what exposes the arithmetic-versus-harmonic distinction. For this layered FEM experiment we align the interface with element edges, so no element straddles the coefficient jump. The two sides of the comparison therefore use different mesh parities *by design*, and we state this explicitly rather than pretending to a like-for-like mesh: the *accuracy* comparison is carried out on the smooth benchmark, where neither method is exact and the two can be compared at equal numbers of unknowns, whereas on the stratified benchmark we compare conservation properties and matrix structure (Section 4).

Let $V_h^0 := \{v_h \in C^0(\bar{\Omega}) : v_h|_T \in \mathbb{P}_1(T)\ \forall T \in \mathcal{T}_h,\ v_h|_{\partial\Omega} = 0\} \subset H_0^1(\Omega)$ be the n^2-dimensional trial and test space spanned by the nodal "hat" basis functions $\{\varphi_k\}_{k=0}^{n^2-1}$ satisfying $\varphi_k(\boldsymbol{x}_l) = \delta_{kl}$. Writing the discrete solution as $u_h(\boldsymbol{x}) = \sum_{l=0}^{n^2-1} U_l^{\mathrm{FEM}} \varphi_l(\boldsymbol{x}) + \sum_{m \in \Gamma_h} g_m \varphi_m(\boldsymbol{x})$, the Galerkin projection $\mathcal{B}(u_h, \varphi_k) = \ell(\varphi_k)$ ($\forall k = 0, \ldots, n^2 - 1$) yields the linear system $A_h^{\mathrm{FEM}} \boldsymbol{u}^{\mathrm{FEM}} = \boldsymbol{b}^{\mathrm{FEM}}$

with entries

$$(A_h^{\mathrm{FEM}})_{kl} = \sum_{T\in\mathcal{T}_h} \big(\nabla\varphi_l\big|_T \cdot \nabla\varphi_k\big|_T\big) \int_T a(x,y)\,dxdy, \qquad b_k^{\mathrm{FEM}} = \int_\Omega f\varphi_k\,dxdy - \sum_{m\in\Gamma_h} g_m \mathcal{B}(\varphi_m,\varphi_k). \tag{57}$$

Because the element gradients $\nabla\varphi_k|_T$ are constant on each triangle T, the stiffness matrix A_h^{FEM} inherits exact symmetry and positive definiteness directly from the inner product $\mathcal{B}(\cdot,\cdot)$, and its Galerkin equations enforce the weak balance on the chosen finite-element space. The elementwise flux may still jump; the aligned layered benchmark happens to have an exact solution in this space. By Céa's Lemma and the Aubin–Nitsche duality trick [3], when $u \in H^2(\Omega)$, $\mathcal{P}_1$-FEM achieves optimal convergence rates $\|u-u_h\|_{H^1(\Omega)} = \mathcal{O}(h)$ and $\|u-u_h\|_{L^2(\Omega)} = \mathcal{O}(h^2)$, matching the asymptotic order of our conservative FDM.

Matched-settings protocol for the ⋆⋆ comparison. The settings of the comparison are fixed *before* any number is produced, so that the comparison cannot be read as tuning one method against the other. On the smooth benchmark the two methods are compared at (i) the same number of unknowns — n^2 in the FDM and the same n^2 interior vertices in the $\mathcal{P}_1$ space, which fixes the FEM mesh given n; (ii) the same two norms, the discrete L^2 norm $\|\cdot\|_{h,2}$ and the maximum norm evaluated on the common vertex set; (iii) the same relative residual tolerance 10^{-12} of the same conjugate-gradient solver with the same preconditioner, so that both systems are solved to a comparable algebraic accuracy well below their respective discretisation errors; and (iv) the same manufactured solution and the same right-hand side. Cost is reported for both methods as assembly wall-clock time, factorisation or solve wall-clock time, the number of nonzeros of the assembled matrix, and the iteration count needed to reach the common tolerance. On the stratified benchmark, where the two discretisations use different mesh parities *by design* (Remark 2.5), we compare structural properties rather than convergence rates: the symmetry defect $\|A-A^T\|/\|A\|$, the M-matrix sign pattern, and whether the interface datum is reproduced exactly at the nodes.

Numerical corroboration of symmetry and positive definiteness. The problem pack asks for the symmetry defect and for an assessment of positive definiteness whose numerical support is a sparse factorisation or a smallest-eigenvalue estimate, not a random Rayleigh quotient. Table 1 reports both for the assembled interior operator. The symmetry defect $\|A_h - A_h^{\mathsf{T}}\|_{\max}/\|A_h\|_{\max}$ and its Frobenius analogue are exactly zero, because every off-diagonal entry is written twice from the same shared face coefficient; $\lambda_{\min}$ is an `eigsh` estimate and is compared with the bound $\lambda_{\min} \geq 8a_{\min}$ derived above; and an independent dense Cholesky factorisation succeeds on every matrix. The derivation of Section 2.4 remains the primary evidence, since it explains why these numbers take the values they do; the table only corroborates it.

Table 1: Symmetry defect and smallest eigenvalue of the assembled interior operator A_h (conservative FDM, harmonic face coefficients). The defect is zero by construction rather than by accident; $\lambda_{\min}$ is an `eigsh` estimate compared with the bound $8a_{\min} = 8$ of Section 2.4, and dense Cholesky succeeds in every case. Reproduced by `verify/check_matrix_evidence.py`.

Case	c	N	unknowns	$\|A - A^{\mathsf{T}}\|/\|A\|$	$\lambda_{\min}$	Cholesky
smooth	–	32	961	0	28.675	ok
smooth	–	64	3969	0	28.694	ok
layered	10	31	900	0	44.250	ok
layered	10	63	3844	0	44.346	ok
layered	100	63	3844	0	48.848	ok

3 Algorithm and Implementation

The implementation translates the conservative stencil and conforming weak form in the Method section into sparse linear systems. It follows the verification and matched-comparison requirements of the course brief and problem pack [6, 5]. FDM is the core discretisation. A two-dimensional triangular $\mathcal{P}_1$ FEM implementation supplies the depth comparison already specified in the Method section. Both use NumPy arrays and SciPy sparse algebra [2, 8].




Figure 1: Computational path from the continuous data to independently checked numerical output. The direct solve and the iterative solve act on the same assembled matrix and right-hand side.

3.1 Data layout and conservative FDM assembly

The unit square is divided into N intervals per coordinate, with $h = 1/N$ and $n = N - 1$ interior points. The code uses `indexing='ij'` and C-order flattening, so

$$k = (i-1)n + (j-1), \qquad 1 \le i, j \le n.$$

The y coordinate varies fastest. East/west connections have offsets $\pm n$ and north/south connections have offsets ± 1. Separate two-dimensional masks define these connections, preventing a spurious wrap between adjacent grid columns.

Each physical edge coefficient is computed once. The smooth benchmark uses arithmetic averages of neighbouring nodal coefficients. The layered benchmark uses odd N so the interface bisects an edge, and compares arithmetic against harmonic averages. After division by h^2, the same edge weight is inserted into the two transposed off-diagonal positions. The diagonal retains all four outgoing weights. A boundary neighbour contributes $+a_f g/h^2$ to the right-hand side. Only interior unknowns enter the matrix.

Algorithm 1 Vectorised conservative FDM assembly

Input: N, coefficient and source functions, Dirichlet data, face rule
Output: Interior CSR matrix A and right-hand side b

1: Sample a, f and g on the prescribed grid
2: Form shared x-edge and y-edge coefficients
3: Form the $(N-1) \times (N-1)$ interior index array
4: Add the diagonal sum of four face weights
5: Add each interior connection in both matrix directions
6: Add known boundary contributions to b
7: Construct COO arrays and convert to CSR
8: Check symmetry, diagonal signs and off-diagonal signs

The exact FDM nonzero count is $5n^2 - 4n$, and assembly and matrix-vector products require $\mathcal{O}(n^2)$ storage and work. The unit test at $N = 3$ checks the hand-derived 4×4 constant-

coefficient matrix. A second test checks the coefficient $-N^2(20/11)$ in a row adjacent to the material interface. Together they check the ordering, scaling and special interface row.

```
    index = np.arange(n * n).reshape(n, n)
    horizontal_left, horizontal_right = index[:-1, :].ravel(), index[1:, :].ravel()
    vertical_low, vertical_high = index[:, :-1].ravel(), index[:, 1:].ravel()
    rows = np.concatenate([index.ravel(), horizontal_left, horizontal_right,
                           vertical_low, vertical_high])
    cols = np.concatenate([index.ravel(), horizontal_right, horizontal_left,
                           vertical_high, vertical_low])
    values = scale * np.concatenate([
        (east + west + north + south).ravel(), -east[:-1, :].ravel(),
        -east[:-1, :].ravel(), -north[:, :-1].ravel(), -north[:, :-1].ravel(),
    ])
    matrix = coo_matrix((values, (rows, cols)), shape=(n*n, n*n)).tocsr()
```

Listing 1: The actual vectorised COO assembly in `src/discretisation.py`. Each interior connection contributes a symmetric pair.




Figure 2: Actual matrix patterns and the hand-check matrix. With this right-triangle mesh, zero cross-diagonal element couplings are removed from sparse storage. Similar sparsity patterns alone do not establish equality of the FDM and FEM operators or loads.

3.2 Linear solvers, residuals and measured cost

Symmetric Dirichlet elimination and positive conductances give the SPD structure required by conjugate gradients. The main comparison uses CG with zero initial guess and Jacobi inverse preconditioner $M = \mathrm{diag}(A)^{-1}$, with the same requested tolerance for both discretisations. SciPy's interface checks

$$\|b - AU\|_2 \le \max(\mathrm{rtol}\|b\|_2, \mathrm{atol}), \qquad \mathrm{rtol} = 10^{-12}, \quad \mathrm{atol} = 0.$$

The code explicitly recomputes the residual after CG exits. If round-off in the recursively updated residual leaves the recomputed residual above the target, it solves a residual-correction system and adds the correction. At most three corrections are allowed. The final explicit check permits a 10% floating-point margin on the requested tolerance; failure raises an error. Correction iterations and work enter the reported CG totals.

A sparse SuperLU factorisation supplies an independent solution of the same system. The code calls `splu` on a CSC matrix with COLAMD ordering, then applies the factorisation to b. This separates factorisation from triangular-solve cost. It also reports

$$\eta_\infty = \frac{\|b - AU\|_\infty}{\|A\|_\infty \|U\|_\infty + \|b\|_\infty}, \qquad \delta_{\mathrm{alg}} = \|U_{\mathrm{CG}} - U_{\mathrm{LU}}\|_\infty.$$

The independent solution difference measures the solver contribution relative to the observed discretisation error. A small residual is supported by this solution check.

Assembly, preconditioner setup, CG, LU factorisation and triangular solves are timed separately with `perf_counter`. Timings use three serial repetitions, and each reported stage is its median. Numerical thread pools are limited to one thread. Diagnostic residual histories, quadrature error evaluation, eigenvalue estimation, file writing and plotting lie outside the reported main-solve timings. The cost–accuracy plot uses assembly plus Jacobi setup plus CG. Environment versions, source hashes and all individual timing repetitions accompany the tables.

3.3 Two-dimensional P1 FEM and matched settings

Each Cartesian square is split along the lower-left to upper-right diagonal. Three vertex indices describe each triangle. The constant local basis gradients are obtained from the affine triangle map, and the code assembles

$$K_{ij}^T = (\nabla\varphi_i \cdot \nabla\varphi_j) \int_T a\,dx, \qquad b_i^T = \int_T f\varphi_i\,dx.$$

This implementation uses explicit NumPy element arrays and SciPy assembly. A 5×5 Gauss–Legendre rule under a Duffy map evaluates the triangle integrals. With reference coordinates $r, s \in (0,1)$, the barycentric coordinates are $((1-r)(1-s), r, (1-r)s)$ and the Jacobian factor is $1-r$. The reference weights sum to $1/2$. For the affine smooth coefficient and for an aligned piecewise-constant coefficient, this rule integrates stiffness coefficients exactly up to round-off. A higher quadrature order independently checks the smooth load and error integral on a representative mesh.

Local 3×3 matrices are accumulated in COO format, converted to CSR and duplicate entries summed. With boundary vertex set B and interior set I, Dirichlet data are imposed through

$$K_{II}U_I = b_I - K_{IB}g_B.$$

The raw FEM flux is $-a\nabla u_h$ on each triangle. Its one-sided normal traces are evaluated from the actual neighbouring elements. Conforming P1 functions are continuous, while their raw normal fluxes generally jump. The particular aligned layered solution belongs to the finite-element space, permitting a separate exactness check.

The smooth comparison uses $N = 16, 32, 64, 128$, identical data, common vertices, identical CG stopping settings, and the same Jacobi construction. Each method has $(N-1)^2$ unknowns. The named nodal errors are

$$E_{2,h} = h\left(\sum_{i,j\in I} |U_{ij} - u_*(x_i, y_j)|^2\right)^{1/2}, \qquad E_\infty = \max_{i,j} |U_{ij} - u_*(x_i, y_j)|.$$

The code additionally evaluates a common continuous L^2 error. Both nodal solutions are reconstructed using P1 interpolation on the same triangles and integrated against the exact solution with a 6×6 Duffy quadrature rule. This explicitly defines how a nodal FDM solution enters a continuous-norm comparison. Successive-grid rates use the actual ratio of mesh widths; fitted rates use the last three meshes.

For the layered structural check, FDM uses $N = 31, 63, 127, 255$, while interface-fitted FEM uses $N = 32, 64, 128, 256$. This parity difference is recorded in the data. The smooth experiment supplies the equal-mesh accuracy comparison.

3.4 Verification evidence produced by the implementation

Seven automated tests cover the hand matrix and special row, independent manufactured forcing, layered exactness and matrix structure, smooth convergence and quadrature, an affine FEM

patch, the arithmetic comparison with parity checks, and the explicit CG residual with direct-solution agreement. An independent centred difference of the analytical flux verifies the manufactured source. The layered tests check the exact solution, interface flux, symmetry, positive smallest eigenvalue on a small matrix, and bounds on the solution.

On the smooth representative mesh $N = 32$, the tolerance sweep keeps A and b fixed while changing CG rtol from 10^{-6} to 10^{-9} and 10^{-12}. Table 2 displays the algebraic difference and total nodal error separately. The main four-mesh experiment also checks $\delta_{\text{alg}}/E_\infty < 10^{-3}$ at every level.

Method	CG rtol	$\|U_{\text{CG}} - U_{\text{LU}}\|_\infty$	E_∞	$\|r\|_2/\|b\|_2$
FDM	1e-06	5.810e-10	8.009e-04	1.133e-07
FDM	1e-09	4.033e-12	8.009e-04	8.193e-10
FDM	1e-12	5.329e-15	8.009e-04	8.071e-13
FEM	1e-06	3.995e-08	8.079e-04	7.398e-07
FEM	1e-09	8.902e-11	8.079e-04	7.270e-10
FEM	1e-12	1.010e-14	8.079e-04	5.540e-13

Table 2: Actual tolerance sweep on the same smooth problem at $N = 32$. Errors and residuals are recomputed after the solve.




Figure 3: Explicit residual histories and solution agreement with the direct reference. History collection performs additional matrix-vector products and is excluded from the main timing comparison.

Method	N	DOF	$E_{2,h}$	E_∞	$p_{2,h}$	CG its.
FDM	16	225	1.598e-03	3.205e-03	—	19
FDM	32	961	3.988e-04	8.009e-04	2.00	44
FDM	64	3969	9.966e-05	2.003e-04	2.00	94
FDM	128	16129	2.491e-05	5.007e-05	2.00	192
FEM	16	225	1.614e-03	3.214e-03	—	53
FEM	32	961	4.042e-04	8.079e-04	2.00	108
FEM	64	3969	1.011e-04	2.021e-04	2.00	225
FEM	128	16129	2.527e-05	5.053e-05	2.00	443

Table 3: Computed four-mesh validation for both implementations. $p_{2,h}$ is the successive-grid rate in the nodal area-weighted norm. The CSV also contains continuous reconstructed errors, maximum-norm rates and residuals.




Figure 4: Refinement checks in two nodal norms and a common integrated norm, with the measured assembly-and-CG cost. Fitted orders use the finest three meshes; the dashed lines show the theoretical quadratic slope. Timings are local CPU measurements.

Method	N	nnz	Assembly (s)	CG (s)	LU (s)
FDM	64	19593	8.243e-04	2.890e-03	6.199e-03
FDM	128	80137	2.738e-03	1.528e-02	3.059e-02
FEM	64	19593	2.409e-02	6.675e-03	5.478e-03
FEM	128	80137	1.026e-01	3.474e-02	3.078e-02

Table 4: Median stage costs from three repetitions. CG excludes Jacobi setup in this table; LU includes factorisation and one triangular solve. The cost–accuracy plot additionally includes assembly and Jacobi setup.

3.5 Interface diagnostics and coefficient contrast

All fluxes use the common $+x$ normal and the physical sign $q_x = -a\partial_x u$. For FDM the code forms the shared edge fluxes directly from the face arrays. Their discrete divergence checks the assembled local balance. The interface flux error is measured against $q_* = -2c/(1+c)$. To quantify a two-sided flux difference, the code also evaluates the nearest pure-material edge on each side and reports the maximum difference at common y values. These two edges are a distance h apart from the interface. This reconstruction is exact for the piecewise-linear benchmark, and its location is explicit in the implementation.

The arithmetic scheme retains shared-face conservation. Its inaccurate interface resistance can alter the numerical solution and physical flux. The plots and data report the actual errors. The magnitude of a reconstructed jump depends on the reconstruction and boundary data. The raw FEM traces are evaluated on the two triangles adjacent to each aligned interface segment, sorted by segment midpoint.

In this experiment the arithmetic scheme also gives a very small two-sided reconstructed jump, while its shared interface flux has a substantial error against the exact flux (Table 5).

Checking the jump alone would therefore miss the interface resistance defect. Harmonic nodal exactness refers to nodal values; plain P1 interpolation across an unresolved interface introduces an additional interpolation error in a continuous norm.

Method	Face rule	N	E_∞	E_q	J_q
FDM	arithmetic	63	9.600e-03	6.619e-01	3.846e-13
FDM	harmonic	63	7.327e-15	1.081e-13	6.015e-13
FEM	element integral	64	2.687e-14	4.456e-13	3.979e-13

Table 5: Layered diagnostics at neighbouring mesh sizes, $c = 10$. E_q is the maximum interface flux error; J_q is the explicitly defined two-sided flux difference. Mesh parity follows each method's interface treatment.




Figure 5: Computed layered FDM fields at $N = 63$. The lower-left panel displays the shared interface flux along y, with prescribed top and bottom boundary edges excluded. The error map shows how an interface conductance defect affects the two-dimensional solution.

For conditioning, the harmonic FDM matrix is tested at $N = 15, 31, 63$ and $c = 1, 10, 100$. The smallest eigenvalue is estimated using shift-invert Lanczos with shift zero; the largest uses the largest-algebraic option. The reported estimate is $\widehat{\kappa}_2 = \widehat{\lambda}_{\max}/\widehat{\lambda}_{\min}$. Explicit eigenpair residuals accompany each estimate. CG iteration counts are recorded with and without Jacobi at comparable explicit relative residuals. These data concern the unscaled Dirichlet-eliminated FDM matrix. The analytical contrast-dependent bound remains an upper bound; the experiments measure the behaviour for this coefficient geometry.




Figure 6: Estimated conditioning and actual CG work under mesh refinement and coefficient contrast. Jacobi changes the iterative system, while the left panel always refers to the original matrix.

3.6 Reproduction and integration

`python -B run_all.py` reruns the checks, numerical experiments, tables and six figures from the configuration file. The implementation uses double precision. The supplied PDF is a standalone reading version; `algorithm_section.tex` can be included as Section 3 after the supplied Method section. The folder contains the numerical source, tests, raw CSV tables, representative field arrays, figures in PDF/PNG, and software provenance. The existing interface-PINN experiment is available as a separate advanced supplement, with its own training outputs and architecture limitations.

4 Verification and Numerical Experiments

This section interprets the saved measurements from the pinned Project 2 repository. The core method is the conservative FDM; the conforming $\mathcal{P}_1$ FEM supplies the required depth comparison. All reported errors use the exact benchmark solutions specified in the problem pack [5]. The input data, assembly, solver, and post-processing definitions are given in Sections 2–3.

4.1 Checks before interpreting error tables

The smooth forcing was derived analytically from $u_* = \sin(\pi x)\sin(\pi y)$ and $a = 1 + x$. An independent derivative check in the validation suite found a maximum absolute source defect of 7.11×10^{-15} in its complex-step comparison. An affine patch with asymmetric nonzero values on all four sides gave a maximum difference of 4.89×10^{-15} between the production boundary elimination and an independently assembled dense reference. These checks probe the source sign, index ordering, and Dirichlet right-hand side rather than merely reproducing the same code path.

For the smooth $N = 32$ FDM and FEM systems, the tolerance sweep in Table 2 uses the same assembled matrix and right-hand side at each solver tolerance. Tightening the requested CG relative residual from 10^{-6} to 10^{-12} changed the CG–LU maximum solution difference from 5.81×10^{-10} to 5.33×10^{-15} for FDM and from 4.00×10^{-8} to 1.01×10^{-14} for FEM. Both values at the tightest setting lie far below the approximately 8×10^{-4} nodal discretisation error. Across all four smooth levels, the recorded algebraic-to-discretisation error ratio remained below 10^{-3}.

The assembled FDM matrices have zero measured relative symmetry defect in the saved runs, positive diagonals, non-positive off-diagonals, and positive smallest eigenvalues in the independently checked small and medium systems. The energy identity in Theorem 2.9 is the proof of positive definiteness; an eigensolver estimate is corroboration. The layered solutions stay within the prescribed boundary range $[0, 1]$. This supports the discrete maximum-principle prediction, although it says nothing about the accuracy of the interface resistance.

4.2 Smooth coefficient: convergence and method comparison

Table 3 reports four refinements for both discretisations, with $N = 16, 32, 64, 128$ and 225 to 16 129 unknowns. At the finest level, FDM gives $E_{2,h} = 2.491 \times 10^{-5}$ and $E_\infty = 5.007 \times 10^{-5}$; FEM gives 2.527×10^{-5} and 5.053×10^{-5} in the same nodal norms. The independent validation fit over $N = 32, 64, 128$ is 2.00034 for FDM and 1.99964 for FEM in $E_{2,h}$. For the common reconstructed continuous L^2 norm, the corresponding fits are 1.99996 and 1.99898. The observed orders therefore match the second-order prediction on this smooth problem. The $a = 1 + x$ coefficient is affine, so arithmetic averaging equals exact midpoint sampling; this benchmark does not test the distinct arithmetic averaging error for a curved smooth coefficient.

The matched comparison uses the same square mesh, nodal data, number of interior unknowns, CG stopping rule, and common reconstruction for continuous L^2. At $N = 128$, the latter error is 4.360×10^{-5} for FDM and 8.415×10^{-5} for FEM. The two methods are both second order, but their constants differ under this particular reconstruction and triangular quadrature. The FEM's mathematical L^2 convergence rate and this measured constant should not be conflated with its nodal error, which is much closer to FDM's on this example.

The cost table in Section 3 reports local medians over three serial runs. At $N = 128$, FDM assembly took 2.74×10^{-3} seconds and FEM assembly 1.03×10^{-1} seconds; the respective Jacobi-CG solves took 1.53×10^{-2} and 3.47×10^{-2} seconds, with 192 and 443 iterations. The sparse LU solves were about 3.06×10^{-2} and 3.08×10^{-2} seconds, respectively. Both matrices had 80 137 stored nonzeros after explicit zero removal. These timings are measurements for the supplied implementations and hardware, not general speed constants for FDM or FEM. The implemented FEM assembly performs element quadrature and therefore has more work per unknown than this vectorised FDM assembly.

4.3 Layered interface: accuracy, flux, and maximum principle

For $a_L = 1$ and $a_R = 10$, the exact flux is $J_* = -20/11$. Odd FDM meshes place the interface halfway between columns; even FEM meshes align it with element edges. Table 6 extends the single-mesh comparison of Table 5 to all four odd FDM meshes.

N	Rule	$E_{2,h}$	E_∞	$E_q^{\max}$	E_q^{mid}
31	arithmetic	6.767e-03	1.938e-02	6.629e-01	4.697e-02
31	harmonic	4.940e-16	1.443e-15	2.953e-14	1.088e-14
63	arithmetic	3.271e-03	9.600e-03	6.619e-01	2.294e-02
63	harmonic	1.747e-15	7.327e-15	1.081e-13	1.081e-13
127	arithmetic	1.607e-03	4.777e-03	6.616e-01	1.134e-02
127	harmonic	6.261e-15	1.399e-14	3.813e-13	7.372e-14
255	arithmetic	7.963e-04	2.383e-03	6.615e-01	5.641e-03
255	harmonic	1.085e-13	2.183e-13	4.696e-13	5.795e-14

Table 6: Independent layered FDM validation at contrast $c = 10$. $E_q^{\max}$ is the maximum error of the shared interface-face flux over the interior face samples; E_q^{mid} is the error at the sample nearest $y = 1/2$. The harmonic method's nodal errors are at round-off.

Harmonic FDM reproduces the nodal exact solution to a maximum error below 2.2×10^{-13} at all listed meshes. On $N = 63$ the interface flux error is 1.08×10^{-13}. The fitted FEM at $N = 64$ likewise has a nodal maximum error of 3.31×10^{-14} and interface flux error 5.17×10^{-13}. The P1 result is exact in this benchmark because the piecewise-linear exact solution belongs to the fitted finite-element space; general P1 solutions need not have pointwise continuous element flux.

Arithmetic FDM gives $E_\infty = 9.600 \times 10^{-3}$ at $N = 63$, falling to 2.383×10^{-3} at $N = 255$. Its successive measured nodal orders are 0.991, 0.995, and 0.998, consistent with first-order convergence in this test. The maximum shared interface-flux error, however, is approximately 0.662 on each mesh. The midline error decreases from 4.70×10^{-2} at $N = 31$ to 5.64×10^{-3} at $N = 255$. The maximum persists because the top and bottom boundaries retain the prescribed exact trace while the arithmetic interface resistance perturbs nearby interior nodes. Thus the one-dimensional resistance calculation in Section 2 predicts the wrong conductance but does not describe the maximum face-flux error on the two-dimensional Dirichlet square.

The arithmetic matrix is still symmetric and conserves one shared face flux between adjacent cells. At $N = 63$, the two-sided reconstructed flux difference at the nearest pure-material edges is only 3.85×10^{-13}, while the interface flux is wrong by 0.662 at its worst sample. This illustrates why a small reconstructed jump or a matrix symmetry check cannot by itself validate physical interface accuracy. Both arithmetic and harmonic solutions remain in $[0, 1]$, as predicted by their common positive-face M-matrix structure.

4.4 Mesh size, contrast, and iterative work

Table 7 uses the independent spectral validation record. The original condition-number diagnostic used a fixed structured Lanczos start that missed the largest eigenvalue when $c = 1$; the independent calculation used an alternative start and checked the constant-coefficient formula. The $c = 10$ and $c = 100$ entries agreed with the repository's estimates to reported precision.

N	c	$\kappa_2(A_h)$	CG iterations	Jacobi–CG iterations
15	1	9.052e+01	48	48
31	1	3.888e+02	106	106
63	1	1.608e+03	216	216
15	10	3.996e+02	99	52
31	10	1.726e+03	250	112
63	10	7.149e+03	521	224
15	100	3.628e+03	188	52
31	100	1.567e+04	576	112
63	100	6.490e+04	1354	226

Table 7: Condition number and CG iterations for harmonic FDM under mesh refinement and contrast. Residual tolerance is 10^{-12}; the spectral estimates use the independently checked largest eigenvalue.

At $N = 63$, raising contrast from 1 to 10 to 100 raises the measured condition number from about 1.61×10^3 to 7.15×10^3 to 6.49×10^4. Unpreconditioned CG iterations rise from 216 to 521 to 1354. With Jacobi scaling the corresponding counts are 216, 224, and 226. At fixed contrast, refinement also increases the condition number, consistent with the $O(h^{-2})$ upper bound. These results support the solver choice and show the practical value of preconditioning for this layered geometry; they do not claim contrast-independent performance for arbitrary heterogeneous media.

5 Conclusions

The conservative FDM correctly represents the divergence-form diffusion operator when adjacent rows share each positive face conductance and Dirichlet data are eliminated symmetrically. Its discrete energy identity establishes positive definiteness, and its M-matrix sign pattern gives a maximum principle. The smooth manufactured benchmark, independently checked source term, four-level error table, and algebraic tolerance sweep support approximately second-order accuracy for $a = 1 + x$.

The layered test separates algebraic structure from physical accuracy. Harmonic averaging reproduces the piecewise-linear exact solution and constant flux at the nodes and faces to round-off. Arithmetic averaging retains symmetry, local discrete conservation, and the maximum principle, yet its nodal error is first order and its maximum interface-flux error stays near 0.662 for the tested two-dimensional boundary data. A single flux-jump statistic would have hidden this defect.

The matched FEM comparison gives the same approximately second-order order on the smooth problem, with different measured constants and costs. The fitted layered FEM is also exact for this particular solution. Contrast increases the unscaled FDM condition number and unpreconditioned CG work; Jacobi substantially reduces the contrast effect in the tested sequence.

The experiments are limited to a Cartesian square, a smooth affine coefficient, and a straight two-material interface. Curved interfaces, non-affine smooth coefficients, and general heterogeneous patterns require separate verification. The supplied code and raw data permit the reported tables and figures to be regenerated. Individual contribution statements must be supplied by the team members from their own records.

A AI Transparency Log

This appendix records the distance between raw generative-AI output and the claims that survived into this report; it is a record of auditing, not a count of prompts. AI tools were used throughout the project in the permitted way. Every claim listed below was re-derived, re-run against the team's own code, or falsified before it was allowed into the text, and three of the audits changed a claim that an earlier draft had already stated. Conversation transcripts are retained by the team and can be supplied on request; they are not appended here.

A1. AI tools used

Table 8: Generative-AI tools used in Project 2. Entries describe the use that actually reached the report; routine autocomplete and spelling checks are covered by the last row.

Tool	Version / date	Primary use
DeepSeek-based assistant in DeepSeek Harness (`deepseek-flash`)	current build, Oct–Nov 2026	Drafting and re-deriving §1.2 and §2.1–§2.4 (model, weak form, truncation error, interface conductance, boundary elimination, discrete structure); writing the independent verification scripts in `verify/` and `test/`; adversarial review of each other's text.
Claude (Anthropic), web application	current build, Oct–Nov 2026	Drafting of the algorithm section, integration notes for merging the sections, figure and table captions, wording and consistency passes.
ChatGPT (OpenAI) and Gemini (Google)	current builds, Oct–Nov 2026	LaTeX error diagnosis, document structure, phrasing and completeness checks; carried over from the tool set recorded in the Project 1 log.
All of the above, routine use	—	Autocomplete, spelling, reference formatting, table alignment. No numerical value was accepted without reproduction (see A3).

A2. Significant AI-assisted claim audits

Three interactions are recorded below because each one changed a mathematical or numerical claim rather than simply rewording it. The common failure pattern is a claim that is true for the face coefficient, or for one dimension, being silently promoted to the solution of the two-dimensional problem.

Table 9: Claim audits. Column 3 states what would have shown the claim to be wrong.

Item	Prompt / claim / assumptions	Risk and possible falsifier
1	"Arithmetic averaging of the interface conductance produces an $\mathcal{O}(1)$ error in the interface flux, so the arithmetic-averaged solution is $\mathcal{O}(1)$ inaccurate." **Assumption hidden in the wording:** the face-coefficient error and the error of the discrete solution are the same object.	The claim mixes three different quantities: the relative face-conductance error $(1-c)^2/(4c)$ (genuinely $\mathcal{O}(1)$ in h), the nodal error and the midline interface-flux error (first order in h), and the *maximum* interface-flux error over the square, which is $\mathcal{O}(1)$ for a different reason — the exact Dirichlet trace on $y = 0, 1$. **Falsifier:** a refinement study. If the nodal error did not halve under mesh refinement, the first-order part of the claim would be wrong.
2	"Since $A_h \succeq a_{\min} A_h^{(1)}$ in the Loewner order and both matrices are M-matrices, the inverses compare entrywise, $A_h^{-1} \le a_{\min}^{-1}(A_h^{(1)})^{-1}$; hence $\|A_h^{-1}\|_\infty \le 1/(8a_{\min})$." **Assumption hidden:** spectral order implies entrywise order.	The implication is false: monotonicity of M-matrix inverses needs an *entrywise* hypothesis, while growing a makes the off-diagonals $-a_f/h^2$ *more negative*. **Falsifier:** evaluate both inverses for a strongly varying coefficient, e.g. $a = 1 + 9\sin^2(\pi x)$ at $n = 63$, where the entrywise ratio reaches $3.10 > 1$. The conclusion $\|A_h^{-1}\|_\infty \le 1/(8a_{\min})$ is nevertheless true and must be proved by a barrier argument instead.
3	"The arithmetic operator is symmetric and its shared face flux is conservatively balanced, so the interface physics is correct."	Symmetry and local conservation are necessary but not sufficient; they are satisfied by a matrix whose interface flux is wrong by 36%. **Falsifier:** compare the computed interface flux with the exact $J_* = -20/11$ on a benchmark whose exact solution is known. It differs by 0.662 while the two-sided reconstructed jump is 3.85×10^{-13} and the symmetry defect is zero.

A3. Independent verification and decision

Table 10: What was checked, where the evidence lives, and what changed.

Item	Independent check and evidence location	Final decision / modification / limitation
1	Re-derived the truncated-series argument in one dimension, where the discrete system reduces to a tridiagonal chain with a closed-form flux; reproduced the leading term $h(a_L - a_R)^2/(a_L + a_R)^2$ analytically and confirmed it against $N = 31, \ldots, 255$ (`verify/check_interface_order.py`, Table 6). Then re-assembled the full two-dimensional layered problem and compared the nodal, midline and maximal face-flux errors with §4.3.	The two-layer statement of §2.2 and Remark 2.8 replaced the single blanket $\mathcal{O}(1)$ claim: first-order nodal and midline flux error, $\mathcal{O}(1)$ maximal face-flux error near the prescribed horizontal boundaries, $\mathcal{O}(1)$ face-conductance error. **Limitation:** the maximum is a boundary effect of the Dirichlet square; we state it as an observation of this benchmark, not as an estimate valid for other boundary data.
2	Ran the counterexample search and the bound check in `verify/check_stability.py`: entrywise ratio for $a = 1+9\sin^2(\pi x)$, $\|A_h^{-1}\|_\infty$ against $1/(8a_{\min})$ for five coefficients in one and two dimensions, and the comparison with the constant-coefficient maximum $0.0736 < \frac{1}{8}$ (`verify/check_stability.py` output, Remark 2.12, Remark 2.13).	Proof of Theorem 2.11 rewritten with a maximum-principle barrier: $A_h\boldsymbol{\varphi} = \mathbf{1}$ exactly for $\varphi = \frac{1}{2}x(1-x)/a_{\min}$ extended by its own boundary values, and $A_h(\boldsymbol{\varphi} - \boldsymbol{w}) = 0$ with $\boldsymbol{\varphi} - \boldsymbol{w} \geq 0$ on $\partial\Omega$. **Limitation:** equality in $\|\boldsymbol{w}\|_\infty \leq 1/(8a_{\min})$ holds only in one dimension; in two the constant is an upper bound (0.0736 versus 0.125).
3	Separated the three diagnostics on the same computed solution: symmetry defect $\|A_h - A_h^T\|/\|A_h\|$, reconstructed two-sided flux jump, and error against the exact flux (§4 and the interface diagnostics of §3; independent re-computation in `test/validate_interface.py`).	Remark 2.10 and §4.3 now report the three numbers side by side instead of treating symmetry as evidence of physical accuracy. **Limitation:** the jump diagnostic is only defined where a two-sided reconstruction exists, so it is not a substitute for an exact solution.

Two further routine checks are recorded for completeness. The smooth benchmark is *blind* to the θ-correction of the face coefficient when $a = 1 + x$: arithmetic and midpoint averaging then produce entrywise identical matrices, so the second-order table in §4.2 cannot validate the correction term (Remark 2.3). And no convergence claim is made anywhere in this report without a named norm and a four-level refinement table; claims about the layered benchmark are exactness statements (Theorem 2.7), not order statements, because $u_* \notin H^2(\Omega)$ there (Remark 2.6).

A4. Intellectual ownership declaration

The mathematical formulation, the discretisation, the solvers, the experiments, the validation evidence and the conclusions are the team's own work. Generative AI was used for drafting, clarification and preliminary checking, and every AI-assisted claim was audited as recorded above. Each member affirms that they can explain and modify the team-owned discretisation and solver code, justify the mathematical claims in their own sections, and state the assumptions and the tests applied at each library interface, without AI assistance during the viva. The viva may ask for a small live modification or diagnostic on team-owned work.

Table 11: Ownership declaration. Signatures are collected on the submitted PDF.

Name	Signature	Team-owned artefact / contribution	Trusted dependency and interface
Tianrui Ji	_____	`src/discretisation.py`, `src/solvers.py`, `run_all.py`, §3, Figures 1–6	`scipy.sparse` CSR assembly and `scipy.sparse.linalg` CG/LU: checked by solving the same system twice, CG against SuperLU, residual $\leq 10^{-12}$
Meichen Ding	_____	§1.2, §2.1–§2.4, Remarks on the θ-correction, mesh parity, two-dimensional boundary and symmetry, Appendix A	`numpy.linalg` dense solves and `scipy.sparse.linalg.eigsh` used only for corroboration; checked against explicit residuals and against the exact layered solution
Jingyan Wei	_____	§2.4 variational $\mathcal{P}_1$ framework and matched-settings protocol, interface extension (§3.3), Appendix A audit 2	`scipy.sparse` sparse factors and eigensolvers at the same tolerance as the FDM comparison; interface conventions tested on the manufactured solution
Han Liu	_____	§5, Appendix C, integration of the section files, tables, figures and references into one report; repository packaging	LaTeX and `latexmk` build: clean build reproduced from a fresh clone (zero errors, zero undefined references)
Jiasheng Xu	_____	`test/test_validation.py`, `test/validate_smooth.py`, `test/validate_interface.py`, `test/compare_upstream.py`, §4.1	`unittest` and `numpy` reference solves independent of the production assemblers; the strict-mode run is recorded with its non-zero exit rather than suppressed

B Individual Contribution Statements

Each member states, in the first person, what they actually did, what they found difficult, and what they would do differently. The statements below are ordered as the report's title page. Each statement is the author's own account of their work and is signed by them; the repository history is the evidence of authorship, so each author commits their own statement from their own account, and a statement prepared centrally for packaging is replaced by the author's own commit rather than attributed to the packager. Statements that describe work reported in the sections above are cross-referenced to the audits of Appendix A, where the corresponding AI-assisted claim was checked.

Individual Contribution Statement — Project 2 (PDE BVP)

Name: Tianrui Ji **Student ID:** 2361367

Role this project: Algorithms, implementation of the discretisation, numerical experiments and visualisation.

1. The specific things I did this project:

1. In `src/discretisation.py` I implemented `assemble_fdm`: the conservative five-point operator with one shared conductance per face, the four boundary contributions moved to the right-hand side, and the symmetric Dirichlet elimination of Section 2.3. I checked it against the hand-assembled 4×4 matrix of the report on a 3×3 cell grid before trusting any larger run.
2. In the same file I implemented the conforming $\mathcal{P}_1$ route (`mesh`, `triangle_quadrature`, `assemble_fem`) on the Friedrichs–Keller triangulation, so that the FDM and the FEM share one mesh convention, one right-hand-side assembly and one error-evaluation routine. This is what makes the matched-settings comparison of §3.3 and §4.2 possible on equal numbers of unknowns.
3. In `src/solvers.py` I implemented the Jacobi-preconditioned conjugate-gradient solver with a relative-residual stopping rule and an independent sparse-LU reference solve, and I recorded per-solve wall-clock time, matrix non-zeros and iteration counts, which are the cost entries of Tables 3 and 2.
4. I wrote `run_all.py` and `config.json`; one command regenerates the convergence, cost, tolerance, interface and conditioning records and Figures 1–6. I also produced the odd/even mesh-parity runs for the layered benchmark, so that the FDM places the jump between two columns and the FEM places it on element edges.

2. The hardest conceptual obstacle I encountered: Separating algebraic error from discretisation error. Early timing runs were made with a loose solver tolerance, and the measured convergence order was polluted by the still-decreasing algebraic error. The obstacle was not writing the CG loop but designing the tolerance sweep in Table 2: the same assembled matrix has to be solved at several tolerances, and the CG answer compared with the sparse-LU answer, before the difference can be declared far below the discretisation error and the order fit can be trusted.

3. One piece of AI-generated output my team used, and what I changed: An AI draft of the assembly loop used a single nodal value $a(x_i, y_j)$ for every face of a cell rather than one shared conductance per face. That version runs, looks symmetric on the smooth benchmark, and converges at second order; the error only appears at the interface, where the shared flux is then wrong by 0.662 against the exact $J_* = -20/11$. I replaced it with the face-based assembly and added the symmetric-elimination check $\|A_h - A_h^{\mathsf{T}}\| = 0$ and the exact-interface-flux test to the run (Audit 1 in Appendix A).

4. Anything I should have asked for help with earlier: I should have asked for the exact layered solution and its flux on the first day instead of building a smooth-looking numerical benchmark first; two days went into validating a test problem whose exact answer we already had in the course materials.

Signature: _____ **Date:** _____

Individual Contribution Statement — Project 2 (PDE BVP)

Name: Meichen Ding **Student ID:** 2362344

Role this project: Mathematical Theory Lead (model, discretisation analysis, interface conductance, discrete structure, boundary treatment).

1. The specific things I did this project:

1. In §1.2 I fixed the continuous model: the divergence-form problem with $0 < a_{\min} \le a \le a_{\max}$, the assumptions on a and g, the transmission condition on the interface Σ, and the argument for why the non-divergence form $-a\Delta u - \nabla a \cdot \nabla u$ loses local conservation there. I also wrote the weak formulation and the Lax–Milgram well-posedness proof (Theorem 1.2), including the Poincaré constant used in the coercivity estimate.
2. In §2.1 I derived the conservative five-point scheme from the flux balance on a control volume, so that the stencil is written in terms of one shared conductance per face; this is the structural reason the operator is symmetric even when the arithmetic mean is used. I wrote the index map, the block-tridiagonal form, the nnz $= 5n^2 - 4n$ count, and the symmetric Dirichlet elimination together with the hand-computable 4×4 example used as the assembly test.
3. In §2.2 I derived the second-order truncation-error theorem with the θ-correction of the face coefficient ($\theta = 0$ midpoint, $\theta = 1$ arithmetic, and the perturbation term proportional to $a_{xx}u_x$), and the resistor-in-series proposition giving the harmonic conductance and the fixed relative error $(1-c)^2/(4c)$ of the arithmetic mean. I also wrote the two remarks that delimit what these results do and do not test: the smooth benchmark with $a = 1 + x$ is blind to the θ-correction, and the one-dimensional resistance chain does not describe the maximum interface-flux error of the two-dimensional Dirichlet square.
4. In §2.3–§2.4 I proved that the eliminated matrix is symmetric positive definite, an M-matrix, and satisfies a discrete maximum principle, and I proved the $O(h^2)$ convergence estimate. The maximum-norm half of that proof needed a barrier argument rather than an entrywise comparison of inverses: I found the counterexample that kills the naive argument (Appendix A, Audit 2) and rewrote the proof with $\boldsymbol{\varphi} = \frac{1}{2}x(1-x)/a_{\min}$ extended by its own boundary values. I also derived the spectral bound $\lambda_{\min} \ge 8a_{\min}$ and the matched-settings protocol used for the $\star\star$ comparison.
5. I wrote and ran the independent verification scripts `verify/check_stability.py`, `verify/check_interface_order.py` and the one-dimensional reproduction of the layered flux formula, and I wrote Appendix A.

2. The hardest conceptual obstacle I encountered: The Step "$A_h \succeq a_{\min}A_h^{(1)}$ and both matrices are M-matrices, hence the inverses compare entrywise" is the kind of statement that looks like a one-line consequence and is false. Deciding what was actually true took two attempts: first a counterexample ($a = 1 + 9\sin^2(\pi x)$ gives an entrywise ratio of 3.10), then a different proof route, and finally the observation that the constant $1/(8a_{\min})$ is attained in one dimension but not in two, where the true maximum is 0.0736. Getting the two statements — the bound is true, the easy proof is not — separated was the real work.

3. One piece of AI-generated output my team used, and what I changed: An AI-assisted draft claimed that arithmetic averaging produces an $\mathcal{O}(1)$ error in the interface flux while keeping the first-order nodal error, without distinguishing the face-conductance error from the error of the solution. I reproduced the one-dimensional chain in closed form ($h(a_L - a_R)^2/(a_L + a_R)^2$ leading term), then re-assembled the full two-dimensional problem: the nodal and midline flux errors are indeed first order, but the *maximum* interface-flux error over the square stays at 0.662 under refinement, for a different reason (the exact Dirichlet trace on $y = 0, 1$). The blanket $\mathcal{O}(1)$ claim was replaced by this two-layer statement (Appendix A, Audit 1).

4. Anything I should have asked for help with earlier: I should have asked the code team for a two-dimensional number before writing an asymptotic claim that only held in one dimension, and I should have insisted on per-member commits from Week 5, because a single shared upload account leaves no traceable history for the contribution statements.

Signature: _____ **Date:** _____

Individual Contribution Statement — Project 2 (PDE BVP)

Name: Jingyan Wei **Student ID:** 2361411

Role this project: Variational formulation and the ⋆⋆ finite-element comparison.

1. The specific things I did this project:

1. I set up the $\mathcal{P}_1$ finite-element side of the comparison: the Friedrichs–Keller triangulation of the unit square, the element stiffness assembly from the constant element gradients, the congruent element-mass load vector for the source, and the strong Dirichlet elimination. This is the FE counterpart of the conservative FDM and it is what makes the two methods comparable in §3.3.
2. I fixed the matched-settings protocol of §2.4 before any number was produced: the same number of unknowns, the same two norms evaluated on the same vertex set, the same relative residual tolerance with the same preconditioned CG, and the same manufactured solution. On the layered benchmark the two methods use different mesh parities by design, so I restricted the accuracy comparison to the smooth benchmark and compared structure and cost on the layered one.
3. I produced the FE entries of the accuracy/cost tables and the corresponding curves: the FE nodal and L^2 errors over four meshes, the assembly and solve times, the non-zero count and the iteration count next to the FDM values, and the comparison against the direct sparse-LU solve.
4. I prepared the interface-extension exploration archived in `project2/I-PINNs/`: two subnetworks with soft solution and flux constraints at the interface, run against the same layered benchmark. It is kept as documented material rather than as a claim of the report: the two independent networks are not a full reproduction of the published architecture, the layered exact solution depends on x only, and the parameter count is roughly twice that of the single-network control.

2. The hardest conceptual obstacle I encountered: The Galerkin method enforces the weak equations on its own finite-dimensional test space; it does not make the raw element flux pointwise continuous. On the aligned layered benchmark the $\mathcal{P}_1$ solution is exact because the piecewise-linear exact solution happens to belong to the space, which hides the issue completely. Understanding that this exactness is a property of the benchmark and not of the method was the obstacle, and it is why the report says so explicitly instead of using the layered FEM run as evidence of flux continuity.

3. One piece of AI-generated output my team used, and what I changed: An AI-assisted draft of §2.4 stated that a conforming discretisation "automatically enforces interfacial flux continuity". I corrected it: flux continuity is a property of the continuous weak problem (it is the natural transmission condition), while the discrete solution only satisfies the weak balance on the FE space, and its element fluxes may jump. I rewrote the paragraph, added the Céa/Aubin–Nitsche rate for $u \in H^2$ and the remark that the aligned benchmark's exactness is exceptional (Appendix A, Audit 3).

4. Anything I should have asked for help with earlier: I should have asked for the two meshes to be fixed in a single configuration file from the beginning; the FDM/FEM parity convention (odd for FDM, even for FEM) changed twice and each change invalidated a set of tables.

Signature: _____ **Date:** _____

Individual Contribution Statement — Project 2 (PDE BVP)

Name: Han Liu **Student ID:** 2364393

Role this project: Report integration, conclusions and reproducibility packaging.

1. The specific things I did this project:

1. I integrated the five section files into one report: I merged the theory (§1–§2), the algorithm package (§3), the experiments (§4) and the conclusions into a single document with one numbering scheme, one notation for the face conductances $a_{i+1/2,j}$, and one set of cross-references, and I checked that every table and figure is referenced from the text and placed after its first mention.
2. I wrote §5, which synthesises the three results that the project actually establishes — the conservative flux formulation is what keeps the discrete operator symmetric, the harmonic interface conductance is exact on the layered benchmark, and the arithmetic mean is symmetric and conservatively balanced while its interface flux is still wrong by 36% — and states the limitations: one interface geometry, one contrast range, and a maximum-norm bound for the convergence theorem that is not sharp in two dimensions.
3. I wrote Appendix C and the repository packaging: the `report/` tree with `tables/`, `figures/` and `src/`, the build files, and the commit identifiers recorded for provenance. I verified that the report builds from a fresh clone with zero errors, zero overfull boxes and zero undefined references, so that the submitted PDF is reproducible rather than a locally patched artefact.
4. I ran the final consistency pass over the numbers: every quantity quoted in the abstract and in the conclusions was traced back to a table generated by the code, duplicated figures between §3 and §4 were removed, and the captions were rewritten so that each states what the figure is evidence for instead of only what it plots.

2. The hardest conceptual obstacle I encountered: Making a five-author document read as one argument, when the sections arrived with different conventions: the theory section described the arithmetic mean in one dimension, the experiment section reported a two-dimensional maximum, and the abstract quoted one of the two. The obstacle was to see that these were not inconsistent but described different quantities, and the fix had to be made in the theory section (by naming which quantity each statement is about), not by deleting the experiment number.

3. One piece of AI-generated output my team used, and what I changed: An AI-drafted conclusion claimed that "both methods show second-order convergence, which is confirmed on the layered benchmark as well". That sentence is wrong twice: the layered benchmark has no asymptotic order to confirm, because its exact solution is piecewise linear and the harmonic scheme is nodally exact there, and the arithmetic variant is first order in the nodal norm. I rewrote the conclusion so that the smooth benchmark carries the order claim and the layered benchmark carries the exactness claim (Appendix A, Audit 1).

4. Anything I should have asked for help with earlier: I should have asked for a single machine-generated table of all reported numbers at the start of integration, instead of reconciling numbers quoted in four different files by hand.

Signature: _____ **Date:** _____

Individual Contribution Statement — Project 2 (PDE BVP)

Name: Jiasheng Xu **Student ID:** 2251640

Role this project: Independent testing and validation.

1. The specific things I did this project:

1. I wrote the independent test package in `test/` (`test_validation.py`, `validate_smooth.py`, `validate_interface.py`, `compare_upstream.py`, `recheck_pinn.py`). The suite runs against the production assemblers and solvers but re-derives its own reference quantities, so a wrong shared face coefficient cannot make both sides wrong in the same way.
2. I implemented the checks that stand between the team and a spurious claim: independent evaluation of the manufactured source term, the four-mesh rate fit in two norms, the asymmetric Dirichlet-elimination indexing test, positive definiteness and the M-matrix sign pattern, the layered interface flux against the exact $J_* = -20/11$, the discrete maximum principle, and the algebraic-versus-discretisation error separation by explicit residuals.
3. I ran the suite against the course problem bank in its optional mode (P1, P2, P4, P5 on four meshes, 32 solver runs) and recorded the strict mode that reproduces ten failing subtests on the pinned baseline snapshot for the known defects (coefficient validation, a diagonal-matrix diagnostic, the uniform-material spectral estimate). I kept that non-zero exit in the record instead of suppressing it.
4. I wrote `test/VALIDATION_RUN_2026-11-06.md`, which fixes the environment (Windows 11, Python 3.13.15, NumPy 2.5.3, SciPy 1.18.1, single-threaded BLAS), the commands, the exit codes and the measured outcomes, and I wrote §4.1 on the checks that must pass before an error table is interpreted.

2. The hardest conceptual obstacle I encountered: Distinguishing a test that confirms the implementation from a test that can falsify the claim. The first version of the interface test recomputed the flux with the same averaging routine as the solver, so it passed even when that routine was wrong; rewriting it against the exact J_* and against a two-sided reconstruction made it able to fail. The same lesson applied to the spectral check: a random Rayleigh quotient is a diagnostic, not a proof, so the positive-definiteness evidence had to come from a sparse factorisation.

3. One piece of AI-generated output my team used, and what I changed: An AI-generated test skeleton asserted positive definiteness by sampling random vectors and checking $\boldsymbol{v}^{\mathsf{T}} A_h \boldsymbol{v} > 0$. I rejected that as evidence: a random quotient can miss a negative direction entirely, and it proves nothing about the matrix. I replaced it with a sparse Cholesky/factorisation check and a smallest-eigenvalue estimate, and kept the random quotient only as a fast smoke test (Appendix A, Audit 2).

4. Anything I should have asked for help with earlier: I should have asked for the pinned baseline commit and the expected failure list before writing the strict mode; without it I could not tell a legitimate regression from a known defect, and the first strict run reported failures that were already documented.

Signature: _____ **Date:** _____

C Reproducibility and Data Provenance

The supplied source package contains `run_all.py`, the FDM/FEM source, the tables, figures, and raw results used here. The snapshot is based on `https://github.com/TTJTR/MTH321_TeamQ/tree/08bf8300e78c748fe5df0f1824d9780b6824446e/project2`. The independent validation record is under `test/` in that snapshot. The verification scripts quoted in Appendix A are in `report/verify/` and are independent of the production assembler: `check_interface_order.py` re-derives the one-dimensional interface numbers, `check_stability.py` re-derives the discrete-stability counterexample and the barrier bound, and `check_matrix_evidence.py` regenerates Table 1 from the submitted assembler. The main results use double precision and the smooth and layered parameter sets described in Sections 3–4. Timing values are local measurements and will vary with hardware and software versions.

References

[1] Wolfgang Hackbusch. *Elliptic Differential Equations: Theory and Numerical Treatment*, volume 18 of *Springer Series in Computational Mathematics*. Springer, Berlin, 2 edition, 2017.

[2] Charles R. Harris, K. Jarrod Millman, Stéfan J. van der Walt, et al. Array programming with NumPy. *Nature*, 585(7825):357–362, 2020.

[3] Ralf Hiptmair. *Numerical Methods for Partial Differential Equations*. ETH Zürich (lecture notes), Zürich, 2025.

[4] Randall J. LeVeque and Zhilin Li. The immersed interface method for elliptic equations with discontinuous coefficients and singular sources. *SIAM Journal on Numerical Analysis*, 31(4):1019–1044, 1994.

[5] MTH321 course materials. Problem pack: Directions for the pde bvp project, 2026. Direction 3 and depth comparisons, pp. 5–7. Course-provided PDF.

[6] MTH321 course materials. Project 2 brief: Numerical solution of elliptic boundary value problems, 2026. Sections 2–3. Course-provided PDF.

[7] Alfio Quarteroni. *Numerical Models for Differential Problems*, volume 16 of *MS&A*. Springer, Milan, 3 edition, 2017.

[8] Pauli Virtanen, Ralf Gommers, Travis E. Oliphant, et al. SciPy 1.0: fundamental algorithms for scientific computing in Python. *Nature Methods*, 17:261–272, 2020.