CHEAT SHEETS		BLOG	POLSCAN	WEBSCAN			
Agile	DBUS						
76110	DKMS						
Containers	DRBD						
	Debian						
DevOps Automation	Debugging						
DevOps Linux	Filesystem	esystem YAML Cheat Sheet					
	GPG						
DevOps Services	IPMI	<u>Links</u>					
	Kernel Tracing	LIIKS					
Glib Examples	LVM		AML 1.2 Spec				
Co Evamples	Linux Insides 🚱	Online YAML Linter (Ruby) Online YAML Parser (Python) kwalify - YAML schema validator (Ruby) Walify - YAML schema validator (Ruby)					
Go Examples	Linux-Commands						
Javascript Examples	Linux-HA	<u> </u>	Wally PAIVIL S	Solicina Validator (Nuby)			
3 h h		Syntax	Syntax Snippets				
Languages	Linux-Networking Linux-Sysadmin						
	Linux-Sysadinin						
Network				# scalar = value a: 1			
PHP Examples	Mail			a: 1.234			
THI Examples	Package Management			b: 'abc' b: "abc"			
Python Examples	Packaging	Scalar	S	b: abc			
	Partitioning		c: false # boolean type d: 2015-04-05 # date type				
Regex Examples	Quota 🗗			# F=f===i== at=i==			
Ceripting	RAID			# Enforcing strings b: !str 2015-04-05			
Scripting	SSH						
Security	Solaris						
	SysRq			# sequence			
Solutions	Sysctl - Net 🗗			array:			
Arrive Design	UEFI Install 🗗			- 132 - 2.434			
Virtualization	ffmpeg	Seque	nces	- 'abc'			
Windows	jq			# sequence of sequences			
	screen-vs-tmux			my_array: - [1, 2, 3]			
visual-ops	sssd 🗗			- [4, 5, 6]			
	systemd						
	ulimit						
	vi			# Nested hash			
	vi - Advanced 🗗			my_hash: subkey:			
				subsubkey1: 5			
		Hashe	S	subsubkey2: 6 another:			
				somethingelse: 'Important!'			
				# Hash of hashes			
				my_hash: {nr1: 5, nr2: 6}			
				# block notation (newlines become spaces)			
				content: Arbitrary free text			
				over multiple lines stopping			
				after indentation changes			
				<pre># literal style (newlines are preserved) content: </pre>			
		l		Arbitrary free text			
		HereD	oc	over "multiple lines" stopping after indentation changes			
				<pre># + indicator (keep extra newlines after block) content: +</pre>			
				Arbitrary free text with two newlines after			
				# - indicator (remove extra newlines after block)			
				content: -			

1 of 2 26/4/18, 5:55 pm

vi - Advanced 🚱

CHEAT SHEETS			Arbitrary free text without newlines after it
Agile	DBUS DKMS		<pre># folded style (folded newlines are preserved) content: ></pre>
Containers	DRBD		Arbitrary free text over "multiple lines" stopping
DevOps Automation	Debian Debugging		after indentation changes
DevOps Linux	Filesystem GPG		
DevOps Services	IPMI		content: doc1 content: doc2
Glib Examples	Kernel Tracing LVM	Multiple Documents	
Go Examples	Linux Insides 🗗 Linux-Commands		
Javascript Examples	Linux-HA	Reference Content	values: - &ref Something to reuse - *ref # Reused content
Languages	Linux-Networking Linux-Sysadmin	Reference Content	
Network	Linux-Virtualization		
PHP Examples	Mail Package Management		<pre>default_settings: install: dir: /usr/local owner: root config: enabled: false # Derive settings for 'my_app' from default and change install::owner my_app_settings: <<: *default_settings install: owner: my_user</pre>
Python Examples	Packaging Partitioning		
Regex Examples	Quota 🚱 RAID	Merging Keys	
Scripting	SSH		
Security	Solaris SysRq		
Solutions	Sysctl - Net 🚱		
Virtualization	UEFI Install ₫ ffmpeg	Complex Mapping	 ? - key : - value # Note: key and value can be multiple, complex structures
Windows	jq screen-vs-tmux	сотпрієх імаррітіў	
visual-ops	sssd 🗗		
	systemd		
	ulimit		is .
	νi		

2 of 2 26/4/18, 5:55 pm