


## Customer drawing

37	25	15	9	contacts	Nb of		
69.40	53.09	39.10	30.89	⊳			
63.50	47.04	33.32	24.99	В			
54.84	38.38	24.66	16.33	С	Dimensions		
49.86	33.24	19.18	10.96	гп			
2.77	2.77	2.77	2.77	77			

ЖЖ

SCALE NONE

SHEET 1 OF 1



## D-SUB TECHNICAL DATA

SHELL : Steel, 2.5um(100u") min. tin over 1.25um(50u") min. nickel

Glass filled thermoplastic.

Flame retardant to UL94 V-0 Color Black

CONTACTS: Brass, gold falsh over

1.25um(50u") min nickel in mating area,

2.54um(100u") min tin over 1.25um(50u") min nickel on termination area

Steel, 50u" min. nickel

BOARDLOCK : Brass,100u" min. tin over 50u" min. nickel

ELECTRICAL: Voltage rating: 250 V RMS at 50 Hz Current rating: 3A per contact

Insulation resistance >5000 M Ohms Withstanding Voltage >1000 V RMS at 50 Hz for one minute

Contact resistance 20 m0hms max.

Amphenol-...(Series No.) Temperature range —55 °C up to 125°C

MARKING : CLIMATIC :

5.80 20,85

