

Declare Your Language

Chapter 11: Data-Flow Analysis


Jeff Smits

IN4303 Compiler Construction


TU Delft

November 2017

**Source
Code
Editor**




**Abstract
Syntax
Tree**




Errors

Check such things as final fields being initialised by a constructor


**Source
Code
Editor**



**Abstract
Syntax
Tree**



**Annotated
AST**



**Transformed
AST**


Use analysis information to do optimisations

Reading Material

Chapter 10: Liveness Analysis

Chapter 17: Dataflow Analysis

The applied/“cookbook” version




Chapter 1: Introduction

Chapter 2: Data Flow Analysis

FLEMMING NIELSON
HANNE RIIS NIELSON
CHRIS HANKIN

Principles of Program Analysis



The theoretical/“general” version

Data-Flow Examples in Tiger

Available Expressions

```
let
  var x : int := a + b
  var y : int := a * b
in
  while y > a + b do
    (
      a := a + 1;
      x := a + b
    )
end
```

Available Expressions

```
let
  var x : int := a + b
  var y : int := a * b
in
  while y > a + b do
    (
      a := a + 1;
      x := a + b
    )
end
```

Available Expressions

```
let
  var x : int := a + b
  var y : int := a * b
in
  while y > a + b do
    (
      a := a + 1;
      x := a + b
    )
end
```

Available Expressions

```
let
  var x : int := a + b
  var y : int := a * b
in
  while y > a + b do
    (
      a := a + 1;
      x := a + b
    )
end
```

Available Expressions

Common subexpression elimination

```
let
  var x : int := a + b
  var y : int := a * b
in
  while y > a + b do
    (
      a := a + 1;
      x := a + b
    )
end
```

Available Expressions

Common subexpression elimination

```
let
  var x : int := a + b
  var y : int := a * b
in
  while y > x do
    (
      a := a + 1;
      x := a + b
    )
end
```

Available Expressions

```
let
  var x : int := a + b _____ a + b
  var y : int := a * b _____ a + b, a * b
in
  while y > a + b do
    (
      a := a + 1; _____
      x := a + b _____ a + b
    )
end
```

Live Variables

```
x := 2;  
y := 4;  
x := 1;  
if y > x then  
    z := y  
else  
    z := y * y;  
x := z
```

Live Variables

```
x := 2;  
y := 4;  
x := 1;  
if y > x then  
    z := y  
else  
    z := y * y;  
x := z
```

Live Variables

Dead code elimination

```
y := 4;  
x := 1;  
if y > x then  
    z := y  
else  
    z := y * y;  
x := z
```

What is Data-Flow Analysis?

Data-flow analysis is a technique for gathering information about the possible set of values calculated at various points in a [computer program](#). A program's control flow graph (CFG) is used to determine those parts of a program to which a particular value assigned to a variable might propagate. The information gathered is often used by [compilers](#) when [optimizing](#) a program. A canonical example of a data-flow analysis is [reaching definitions](#).

What is Data-Flow Analysis?

Data-flow analysis is a technique for gathering information about the possible set of values calculated at various points in a [computer program](#). A program's control flow graph (CFG) is used to determine those parts of a program to which a particular value assigned to a variable might propagate. The information gathered is often used by [compilers](#) when [optimizing](#) a program. A canonical example of a data-flow analysis is [reaching definitions](#).

Gathering information about

What is Data-Flow Analysis?

Data-flow analysis is a technique for gathering information about the possible set of values calculated at various points in a [computer program](#). A program's control flow graph (CFG) is used to determine those parts of a program to which a particular value assigned to a variable might propagate. The information gathered is often used by [compilers](#) when [optimizing](#) a program. A canonical example of a data-flow analysis is [reaching definitions](#).

Gathering information about

- The *possible* set of values at various point in a program

What is Data-Flow Analysis?

Data-flow analysis is a technique for gathering information about the possible set of values calculated at various points in a [computer program](#). A program's control flow graph (CFG) is used to determine those parts of a program to which a particular value assigned to a variable might propagate. The information gathered is often used by [compilers](#) when [optimizing](#) a program. A canonical example of a data-flow analysis is [reaching definitions](#).

Gathering information about

- The *possible* set of values at various point in a program
- The program's *control flow graph* is used to ...

Control Flow Graphs

What is a Control Flow Graph?


A **control flow graph** (CFG) in computer science is a representation, using graph notation, of all paths that might be traversed through a program during its execution.

Control Flow Graphs

```
let
  var x : int := a + b
  var y : int := a * b
in
  while y > a + b do
    (
      a := a + 1;
      x := a + b
    )
end
```


Control Flow Graphs

Full flow graph



Control Flow Graphs

Basic Blocks



Control Flow Graphs

Ingredients

Control Nodes

- Usually outermost statements and expressions
- Or blocks for consecutive statements


Control Edges

- Back edges: show loops
- Splits: conditionally split the control flow
- Merges: combine previously split control flow

Control Flow Graphs

Supports unstructured control flow

```
a < 0
L1: b < a + 1
      c <= c + b
      a <= 2 * b
      if a < N goto L1
      return c
```



What is Data-Flow Analysis?

Data-flow analysis is a technique for gathering information about the possible set of values calculated at various points in a computer program. A program's control flow graph (CFG) is used to determine those parts of a program to which a particular value assigned to a variable might propagate. The information gathered is often used by compilers when optimizing a program. A canonical example of a data-flow analysis is reaching definitions.

What is Data-Flow Analysis?

Data-flow analysis is a technique for gathering information about the possible set of values calculated at various points in a [computer program](#). A program's control flow graph (CFG) is used to determine those parts of a program to which a particular value assigned to a variable might propagate. The information gathered is often used by [compilers](#) when [optimizing](#) a program. A canonical example of a data-flow analysis is [reaching definitions](#).

A simple way to perform data-flow analysis of programs is to set up data-flow equations for each [node](#) of the control flow graph and solve them by repeatedly calculating the output from the input locally at each node until the whole system stabilizes, i.e., it reaches a [fixpoint](#). This general approach was developed by [Gary Kildall](#) while teaching at the [Naval Postgraduate School](#).^[1]

What is Data-Flow Analysis?

Possible set of values

- at various points in a computer program

Data-flow equations

- for each node of the control flow graph

Solve them by repetition

- i.e., it reaches a fixpoint

What is Data-Flow Analysis?

What is Data-Flow Analysis?

Some information about

What is Data-Flow Analysis?

Some information about

- What may or must happen, in the previous or next part of the program

What is Data-Flow Analysis?

Some information about

- What may or must happen, in the previous or next part of the program
- Usually some approximation of values that the program computes

What is Data-Flow Analysis?

Some information about

- What may or must happen, in the previous or next part of the program
- Usually some approximation of values that the program computes

Transfer functions

What is Data-Flow Analysis?

Some information about

- What may or must happen, in the previous or next part of the program
- Usually some approximation of values that the program computes

Transfer functions

- for each node of the control flow graph

What is Data-Flow Analysis?

Some information about

- What may or must happen, in the previous or next part of the program
- Usually some approximation of values that the program computes

Transfer functions

- for each node of the control flow graph
- express the ‘effect’ of a control node

What is Data-Flow Analysis?

Some information about

- What may or must happen, in the previous or next part of the program
- Usually some approximation of values that the program computes

Transfer functions

- for each node of the control flow graph
- express the ‘effect’ of a control node

Calculate a fixpoint

What is Data-Flow Analysis?

Some information about

- What may or must happen, in the previous or next part of the program
- Usually some approximation of values that the program computes

Transfer functions

- for each node of the control flow graph
- express the ‘effect’ of a control node

Calculate a fixpoint

- because loops

Traditional Gen/Kill Sets

Traditional set base analysis

Traditional set base analysis

Traditional set based analysis has

Traditional set base analysis

Traditional set based analysis has

- Sets as the type of information that's calculated

Traditional set base analysis

Traditional set based analysis has

- Sets as the type of information that's calculated
- A transfer function of:

Traditional set base analysis

Traditional set based analysis has

- Sets as the type of information that's calculated
- A transfer function of:
 - ▶ $\text{previousSet} \setminus \text{kill}(\text{currentNode}) \cup \text{gen}(\text{currentNode})$

Traditional set base analysis

Traditional set based analysis has

- Sets as the type of information that's calculated
- A transfer function of:
 - ▶ $\text{previousSet} \setminus \text{kill}(\text{currentNode}) \cup \text{gen}(\text{currentNode})$
- Usually the initial set is empty

Traditional set base analysis

Traditional set based analysis has

- Sets as the type of information that's calculated
- A transfer function of:
 - ▶ `previousSet \ kill(currentNode) ∪ gen(currentNode)`
- Usually the initial set is empty

Traditional set base analysis

Traditional set based analysis has

- Sets as the type of information that's calculated
- A transfer function of:
 - ▶ `previousSet \ kill(currentNode) ∪ gen(currentNode)`
- Usually the initial set is empty

Depends on the direction of the analysis

Available Expressions

“An **expression** is **available** if it *must* have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```

AllAE

- All Available Expressions in the program

FV

- Free Variables of the argument

SE

- Subexpressions of the argument

Available Expressions

“An **expression** is **available** if it *must* have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∉ FV(e2) }
```

AllAE

- All Available Expressions in the program

FV

- Free Variables of the argument

SE

- Subexpressions of the argument

Available Expressions

“An **expression** is **available** if it *must* have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∉ FV(e2) }
```

AllAE

- All Available Expressions in the program

FV

- Free Variables of the argument

SE

- Subexpressions of the argument


This mistake can be prevented by making the control flow more explicit in the graph:
First we execute the right-hand side, then we do the assignment.

Available Expressions

“An **expression** is **available** if it must have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```




Available Expressions

“An **expression** is **available** if it must have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```




Available Expressions

“An **expression** is **available** if it must have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```




Available Expressions

“An **expression** is **available** if it must have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```




Available Expressions

“An **expression** is **available** is it *must* have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```




Available Expressions

“An **expression** is **available** is it *must* have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```




Available Expressions

“An **expression** is **available** is it *must* have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```




Available Expressions

“An **expression** is **available** if it must have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```




Available Expressions

“An **expression** is **available** is it *must* have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```




Available Expressions

“An **expression** is **available** if it must have already been computed, and not later modified, on all paths to the program point”

```
kill(Assign(var, e1)) :=  
{ e2 ∈ AllAE | var ∈ FV(e2) }
```

```
gen(Assign(var, e1)) :=  
{ e2 ∈ SE(e1) | var ∈ FV(e2) }
```

A *must* analysis intersects sets where control flow merges



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path. ”

```
kill(Assign(var, e1)) :=  
{ var }
```

```
gen(Assign(var, e1)) :=  
{ FV(e1) }
```


```
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }
```

```
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```

Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”


```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”


```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”


```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”


```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”


```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”


```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”


```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”


```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”


```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Live Variables

“A **variable** is **live** if there exists a path from there to a use of the variable, with no re-definition of the variable on that path.”

```
kill(Assign(var, e1)) :=  
{ var }  
  
gen(Assign(var, e1)) :=  
{ FV(e1) }  
  
gen(b@BinOp(_, _, _)) :=  
{ FV(b) }  
  
gen(u@UnOp(_, _)) :=  
{ FV(u) }
```



Traditional set based analysis

Sets as analysis information

Kill and **gen** sets per control node type

- $\text{previousSet} \setminus \mathbf{kill}(\text{currentNode}) \cup \mathbf{gen}(\text{currentNode})$

Can propagate either **forward** or **backward**

Can merge information with either **union** or **intersection**

- Respectively called **may** and **must** analyses


Beyond Sets

Constant propagation and folding

```
let
  var a : int := 0
  var b : int := a + 1
in
  c := c + b;
  a := 2 * b
end
```

Constant propagation and folding

```
let
  var a : int := 0
  var b : int := a + 1
in
  c := c + b;
  a := 2 * b
end
```



```
let
  var a : int := 0
  var b : int := 0 + 1
in
  c := c + b;
  a := 2 * b
end
```

Constant propagation and folding

```
let
  var a : int := 0
  var b : int := a + 1
in
  c := c + b;
  a := 2 * b
end
```

single step

```
let
  var a : int := 0
  var b : int := 0 + 1
in
  c := c + b;
  a := 2 * b
end
```

full propagation

```
let
  var a : int := 0
  var b : int := 0 + 1
in
  c := c + 1;
  a := 2 * 1
end
```



Constant propagation and folding

```
let
  var a : int := 0
  var b : int := a + 1
in
  c := c + b;
  a := 2 * b
end
```

Constant propagation and folding

```
let
  var a : int := 0           a ↦ 0
  var b : int := a + 1
in
  c := c + b;
  a := 2 * b
end
```

Constant propagation and folding

```
let
  var a : int := 0          a ↦ 0
  var b : int := a + 1      a ↦ 0, b ↦ 1
in
  c := c + b;
  a := 2 * b
end
```

Constant propagation and folding

```
let
  var a : int := 0          a ↦ 0
  var b : int := a + 1      a ↦ 0, b ↦ 1
in
  c := c + b;              a ↦ 0, b ↦ 1, c ↦ ?
  a := 2 * b
end
```

Constant propagation and folding

```
let
  var a : int := 0          a ↦ 0
  var b : int := a + 1      a ↦ 0, b ↦ 1
in
  c := c + b;              a ↦ 0, b ↦ 1, c ↦ ?
  a := 2 * b
end                         a ↦ 2, b ↦ 1, c ↦ ?
```

Constant propagation and folding

The type of the analysis information

- Variables bound to either a particular *constant* or a *marker for non-constants*

The transfer functions per control node

- Basically an interpreter implementation for constants
- Needs to propagate markers when found

Monotone Frameworks

Termination

Termination

Data-Flow Analysis needs fixpoint computation

- Because of loops

Termination

Data-Flow Analysis needs fixpoint computation

- Because of loops

To terminate, there needs to *be* a fixpoint

- **And** we need to actually *get* to that fix point
- How can we check this?

Lattice Theory

Lattice Theory

A set X is totally ordered under \leq if for $a, b, c \in X$

Lattice Theory

A set X is totally ordered under \leq if for $a, b, c \in X$

- $a \leq b \wedge b \leq a \Rightarrow a = b$ (antisymmetry)

Lattice Theory

A set X is totally ordered under \leq if for $a, b, c \in X$

- $a \leq b \wedge b \leq a \Rightarrow a = b$ (antisymmetry)
- $a \leq b \wedge b \leq c \Rightarrow a \leq c$ (transitivity)

Lattice Theory

A set X is totally ordered under \leq if for $a, b, c \in X$

- $a \leq b \wedge b \leq a \Rightarrow a = b$ (antisymmetry)
- $a \leq b \wedge b \leq c \Rightarrow a \leq c$ (transitivity)
- $a \leq b \vee b \leq a$ (totality)

Lattice Theory

A set X is totally ordered under \leq if for $a, b, c \in X$

- $a \leq b \wedge b \leq a \Rightarrow a = b$ (antisymmetry)
- $a \leq b \wedge b \leq c \Rightarrow a \leq c$ (transitivity)
- $a \leq b \vee b \leq a$ (totality)

A partial ordering drop the totality constraint

Lattice Theory

A set X is totally ordered under \leq if for $a, b, c \in X$

- $a \leq b \wedge b \leq a \Rightarrow a = b$ (antisymmetry)
- $a \leq b \wedge b \leq c \Rightarrow a \leq c$ (transitivity)
- $a \leq b \vee b \leq a$ (totality)

A partial ordering drop the totality constraint

- e.g. subset inclusion:


Lattice Theory

A set X is totally ordered under \leq if for $a, b, c \in X$


- $a \leq b \wedge b \leq a \Rightarrow a = b$ (antisymmetry)
- $a \leq b \wedge b \leq c \Rightarrow a \leq c$ (transitivity)
- $a \leq b \vee b \leq a$ (totality)

A partial ordering drop the totality constraint

- e.g. subset inclusion:




Lattice Theory



Lattice Theory

A *Lattice* is a partially ordered set where

- every two elements have a *unique* least upper bound (or supremum or join)
- every two elements have a *unique* greatest lower bound (or infimum or meet)




Lattice Theory

A *Lattice* is a partially ordered set where

- every two elements have a *unique* least upper bound (or supremum or join)
- every two elements have a *unique* greatest lower bound (or infimum or meet)

Least upper bound (LUB)

- $a \sqsubseteq b \Leftrightarrow a \sqcup b = b$
- $a \sqcup b = c \Rightarrow a \sqsubseteq c \wedge b \sqsubseteq c$



Lattice Theory

A *Lattice* is a partially ordered set where


- every two elements have a *unique* least upper bound (or supremum or join)
- every two elements have a *unique* greatest lower bound (or infimum or meet)

Least upper bound (LUB)

- $a \sqsubseteq b \Leftrightarrow a \sqcup b = b$
- $a \sqcup b = c \Rightarrow a \sqsubseteq c \wedge b \sqsubseteq c$

Greatest lower bound (GLB)

- $a \sqsubseteq b \Leftrightarrow a \sqcap b = a$
- $a \sqcap b = c \Rightarrow c \sqsubseteq a \wedge c \sqsubseteq b$



Lattice Theory

A *Lattice* is a partially ordered set where

- every two elements have a *unique* least upper bound (or supremum or join)
- every two elements have a *unique* greatest lower bound (or infimum or meet)

Least upper bound (LUB)


- $a \sqsubseteq b \Leftrightarrow a \sqcup b = b$
- $a \sqcup b = c \Rightarrow a \sqsubseteq c \wedge b \sqsubseteq c$

Greatest lower bound (GLB)

- $a \sqsubseteq b \Leftrightarrow a \sqcap b = a$
- $a \sqcap b = c \Rightarrow c \sqsubseteq a \wedge c \sqsubseteq b$

A *bounded lattice* has a top and bottom

- These are \top and \perp respectively



Lattices for data-flow analysis

Consider T as the coarsest approximation

- It's a safe approximation, because it says we're not sure of anything

Then we can combine data-flow information with \sqcup

- It is the most information preserving combination of information

Lattices for data-flow analysis

Lattices for data-flow analysis

Transfer functions should be monotone increasing

Lattices for data-flow analysis

Transfer functions should be monotone increasing

- i.e. for transfer function f , $a \sqsubseteq b \Rightarrow f(a) \sqsubseteq f(b)$

Lattices for data-flow analysis

Transfer functions should be monotone increasing

- i.e. for transfer function f , $a \sqsubseteq b \Rightarrow f(a) \sqsubseteq f(b)$
- This includes the identity function

Lattices for data-flow analysis

Transfer functions should be monotone increasing

- i.e. for transfer function f , $a \sqsubseteq b \Rightarrow f(a) \sqsubseteq f(b)$
- This includes the identity function

Monotone transfer functions give a termination guarantee

Lattices for data-flow analysis

Transfer functions should be monotone increasing

- i.e. for transfer function f , $a \sqsubseteq b \Rightarrow f(a) \sqsubseteq f(b)$
- This includes the identity function

Monotone transfer functions give a termination guarantee

- In a loop we reach a fixpoint if the functions start returning the same thing

Lattices for data-flow analysis

Transfer functions should be monotone increasing

- i.e. for transfer function f , $a \sqsubseteq b \Rightarrow f(a) \sqsubseteq f(b)$
- This includes the identity function

Monotone transfer functions give a termination guarantee

- In a loop we reach a fixpoint if the functions start returning the same thing
- Worst case scenario: the loop reaches \top

Lattices for data-flow analysis

Transfer functions should be monotone increasing

- i.e. for transfer function f , $a \sqsubseteq b \Rightarrow f(a) \sqsubseteq f(b)$
- This includes the identity function

Monotone transfer functions give a termination guarantee

- In a loop we reach a fixpoint if the functions start returning the same thing
- Worst case scenario: the loop reaches \top
- **IMPORTANT:** This only works if the lattice is *finite*

Lattices for data-flow analysis

Transfer functions should be monotone increasing

- i.e. for transfer function f , $a \sqsubseteq b \Rightarrow f(a) \sqsubseteq f(b)$
- This includes the identity function

Monotone transfer functions give a termination guarantee

- In a loop we reach a fixpoint if the functions start returning the same thing
- Worst case scenario: the loop reaches \top
- **IMPORTANT:** This only works if the lattice is *finite*

General interval analysis has an infinite lattice

Lattices for data-flow analysis

Transfer functions should be monotone increasing

- i.e. for transfer function f , $a \sqsubseteq b \Rightarrow f(a) \sqsubseteq f(b)$
- This includes the identity function

Monotone transfer functions give a termination guarantee

- In a loop we reach a fixpoint if the functions start returning the same thing
- Worst case scenario: the loop reaches \top
- **IMPORTANT:** This only works if the lattice is *finite*

General interval analysis has an infinite lattice

- $\top = [-\infty, \infty]$

Lattices for data-flow analysis

Transfer functions should be monotone increasing

- i.e. for transfer function f , $a \sqsubseteq b \Rightarrow f(a) \sqsubseteq f(b)$
- This includes the identity function

Monotone transfer functions give a termination guarantee

- In a loop we reach a fixpoint if the functions start returning the same thing
- Worst case scenario: the loop reaches \top
- **IMPORTANT:** This only works if the lattice is *finite*

General interval analysis has an infinite lattice

- $\top = [-\infty, \infty]$
- If a loop adds a finite number to a variable, you never get to ∞

Recap

An analysis consists of

- The type of the analysis information
- The *transfer functions* that express the ‘effect’ of a control node
- The initial analysis information

Recap

An analysis consists of

- The type of the analysis information, **and the lattice instance for that type**
- The *transfer functions* that express the ‘effect’ of a control node
 - ▶ **These should be monotone with respect to the lattice**
- The initial analysis information

Data-Flow Languages

**How to define the
data-flow
rules of a language**



Data-Flow specification approaches

Languages used for specifying data-flow analysis

- Attribute grammars: JastAdd [Söderberg'13]
- Datalog [Smaragdakis'15]: Doop [Kasterinis'13], Flix [Madsen'16]
- INCA_L / MPS-DF [Szabó'18 / '16]
- Temporal Logic: Silver [VanWyk'10]

Separation of Concerns

Representation

- Control Flow Graphs
- Before/After data-flow information on CFG nodes

Declarative Rules

- To define control-flow rules of a language
- To define data-flow rules of a language

Language-Independent Tooling

- Analysis
- Code completion
- Refactoring
- Optimisation
- ...

Control-flow graphs in FlowSpec

FlowSpec

Example program

```
x := 1;  
if y > x then  
    z := y;  
else  
    z := y * y;  
    y := a * b;  
while y > a + b do  
    (a := a + 1;  
     x := a + b)
```

Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end
```

Example program

```
x := 1;  
if y > x then  
  z := y;  
else  
  z := y * y;  
y := a * b;  
while y > a + b do  
  (a := a + 1;  
   x := a + b)
```

Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end
```

start

Example program

```
x := 1;  
if y > x then  
  z := y;  
else  
  z := y * y;  
y := a * b;  
while y > a + b do  
  (a := a + 1;  
   x := a + b)
```

end

Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end  
  
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

Example program

start

x := 1;

if y > x then

z := y;

else

z := y * y;

y := a * b;

while y > a + b do

(a := a + 1;

x := a + b)

end

Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end  
  
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

Example program

```
start  
  
x := 1;  
  
if y > x then  
  z := y;  
else  
  z := y * y;  
  
y := a * b;  
  
while y > a + b do  
  (a := a + 1;  
   x := a + b)  
  
end
```

Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end
```

```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

Example program

start

x := 1;

if y > x then

z := y;

else

z := y * y;

y := a * b;

while y > a + b do

(a := a + 1;

x := a + b)

end

Control-flow graphs in FlowSpec


FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end
```

```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

Example program



Control-flow graphs in FlowSpec

FlowSpec


```
cfg root Mod(s) =  
  start -> cfg s -> end
```

```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

Example program



if y > x **then**

```
z := y;
```

else

```
z := y * y;
```

```
y := a * b;
```

while y > a + b **do**

```
(a := a + 1;
```

```
x := a + b)
```

end

Control-flow graphs in FlowSpec

FlowSpec


```
cfg root Mod(s) =  
  start -> cfg s -> end
```

```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

Example program



Control-flow graphs in FlowSpec

FlowSpec


```
cfg root Mod(s) =  
  start -> cfg s -> end
```

```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

Example program



Control-flow graphs in FlowSpec

FlowSpec


```
cfg root Mod(s) =  
  start -> cfg s -> end
```

```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

Example program



Control-flow graphs in FlowSpec

FlowSpec


```
cfg root Mod(s) =  
  start -> cfg s -> end
```

```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

Example program



Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end
```


```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

```
cfg While(c, b) =  
  entry -> c -> cfg b -> c -> exit
```

Example program



Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end
```


```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

```
cfg While(c, b) =  
  entry -> c -> cfg b -> c -> exit
```

Example program



Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end
```


```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

```
cfg While(c, b) =  
  entry -> c -> cfg b -> c -> exit
```

Example program



Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end
```


```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

```
cfg While(c, b) =  
  entry -> c -> cfg b -> c -> exit
```

Example program



Control-flow graphs in FlowSpec

FlowSpec

```
cfg root Mod(s) =  
  start -> cfg s -> end
```


```
cfg a@Assign(_, _) =  
  entry -> a -> exit
```

```
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit
```

```
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit
```

```
cfg While(c, b) =  
  entry -> c -> cfg b -> c -> exit
```

Example program




Control-flow graphs in FlowSpec

FlowSpec


```
cfg root Mod(s) =  
  start -> cfg s -> end  
  
cfg a@Assign(_, _) =  
  entry -> a -> exit  
  
cfg Seq(s1, s2) =  
  entry -> cfg s1 -> cfg s2 -> exit  
  
cfg IfThenElse(c, t, e) =  
  entry -> c -> cfg t -> exit,  
    c -> cfg e -> exit  
  
cfg While(c, b) =  
  entry -> c -> cfg b -> c -> exit
```

Example program



Live Variables in FlowSpec


A variable is *live* if the current value of the variable *may* be read further along in the program



Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: Set(name)
```



Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program

```
prop live: Set(name)  
  
live(end) =  
{}  
  
live(_ -> next) =  
live(next)
```



Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: Set(name)
```

```
live(end) =
```

```
{}
```

```
live(_ -> next) =
```

```
live(next)
```



{ } { } { } { } { } { }

Live Variables in FlowSpec


A variable is *live* if the current value of the variable *may* be read further along in the program

```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \/\ {n}

live(end) =
  {}

live(_ -> next) =
  live(next)
```



{ } { } { } { } { } { }

Live Variables in FlowSpec


A variable is *live* if the current value of the variable *may* be read further along in the program

```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \wedge {n}

live(end) =
  {}

live(_ -> next) =
  live(next)
```



Live Variables in FlowSpec


A variable is *live* if the current value of the variable *may* be read further along in the program

```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \/\ {n}

live(end) =
  {}

live(_ -> next) =
  live(next)
```



{z, x}
{z, x}
{z, x}
{z, x}
{z, x}
{z}
{ }
{ }

Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \/\ {n}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```



$\{z, x\}$
 $\{z, x\}$
 $\{z, x\}$
 $\{z, x\}$
 $\{z, x\}$
 $\{z\}$
 $\{\}$
 $\{\}$

Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \vee {n}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```



Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: Set(name)
```

```
live(Ref(n) -> next) =  
  live(next) \/\ {n}
```

```
live(Assign(n, _) -> next) =  
  { m | m <- live(next), n != m }
```

```
live(end) =  
  {}
```

```
live(_ -> next) =  
  live(next)
```



Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \vee {n}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```



Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program

```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \/\ {n}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```

```
x := 2;
y := 4;
x := 1;
if y > 0 then
  z := x;
else
  z := y * y;
x := z;
```

Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program

```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \vee {n}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```

```
x := 2;
y := 4;
x := 1;
if y > 0 then
  z := x;
else
  z := y * y;
x := z;
```

Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \wedge \{n\}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```



{z}
{ }
{ }

Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program

```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \/\ {n}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```

```
x := 2;
y := 4;
x := 1;
if y > 0 then
  z := x;
else
  z := y * y;
x := z;
```

{z}
{
{}

Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program

```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \wedge \{n\}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```

```
x := 2;
y := 4;
x := 1;
if y > 0 then
  z := x;
else
  z := y * y;
x := z;
```

{z}
{ }
{ }

Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: Set(name)

live(Ref(n) -> next) =
  live(next) \vee {n}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```



Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: MaySet(name)

live(Ref(n) -> next) =
  live(next) \/\ {n}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```



Live Variables in FlowSpec

A variable is *live* if the current value of the variable *may* be read further along in the program


```
prop live: MaySet(name)

live(Ref(n) -> next) =
  live(next) \ / {n}

live(Assign(n, _) -> next) =
  { m | m <- live(next), n != m }

live(end) =
  {}

live(_ -> next) =
  live(next)
```



Closing

But wait! There's more!

But wait! There's more!

Context-sensitivity

But wait! There's more!

Context-sensitivity

- Follow function calls / where were we called from?

But wait! There's more!

Context-sensitivity

- Follow function calls / where were we called from?
- Dynamic dispatch: where did objects come from?

But wait! There's more!

Context-sensitivity

- Follow function calls / where were we called from?
- Dynamic dispatch: where did objects come from?
- Control-flow depends on data-flow depends on control-flow...

But wait! There's more!

Context-sensitivity

- Follow function calls / where were we called from?
- Dynamic dispatch: where did objects come from?
- Control-flow depends on data-flow depends on control-flow...

Incrementality

But wait! There's more!

Context-sensitivity

- Follow function calls / where were we called from?
- Dynamic dispatch: where did objects come from?
- Control-flow depends on data-flow depends on control-flow...

Incrementality

- Optimisation: transform the program into a more efficient one

But wait! There's more!

Context-sensitivity

- Follow function calls / where were we called from?
- Dynamic dispatch: where did objects come from?
- Control-flow depends on data-flow depends on control-flow...

Incrementality

- Optimisation: transform the program into a more efficient one
- User changes part of the program (typing, or refactoring)

But wait! There's more!

Context-sensitivity

- Follow function calls / where were we called from?
- Dynamic dispatch: where did objects come from?
- Control-flow depends on data-flow depends on control-flow...

Incrementality

- Optimisation: transform the program into a more efficient one
- User changes part of the program (typing, or refactoring)
- Analysis results are *partially* invalid now

But wait! There's more!

Context-sensitivity

- Follow function calls / where were we called from?
- Dynamic dispatch: where did objects come from?
- Control-flow depends on data-flow depends on control-flow...

Incrementality

- Optimisation: transform the program into a more efficient one
- User changes part of the program (typing, or refactoring)
- Analysis results are *partially* invalid now

External PhD candidate Tamás Szabó researches incremental static analysis under supervision of Sebastian Erdweg

But wait! There's more!

But wait! There's more!

Correctness

But wait! There's more!

Correctness

- Are you sure your analysis is correct?

But wait! There's more!

Correctness

- Are you sure your analysis is correct?
- Are the results guaranteed to safely approximate the dynamic semantics?

But wait! There's more!

Correctness

- Are you sure your analysis is correct?
- Are the results guaranteed to safely approximate the dynamic semantics?
- Abstract Interpretation

But wait! There's more!

Correctness

- Are you sure your analysis is correct?
- Are the results guaranteed to safely approximate the dynamic semantics?
- Abstract Interpretation
 - ▶ Principled transformation of dynamic semantics into static approximations

But wait! There's more!

Correctness

- Are you sure your analysis is correct?
- Are the results guaranteed to safely approximate the dynamic semantics?
- Abstract Interpretation
 - ▶ Principled transformation of dynamic semantics into static approximations
 - ▶ Galois connections

But wait! There's more!

Correctness

- Are you sure your analysis is correct?
- Are the results guaranteed to safely approximate the dynamic semantics?
- Abstract Interpretation
 - ▶ Principled transformation of dynamic semantics into static approximations
 - ▶ Galois connections

PhD candidate Sven Keidel (HB08.260) researches abstract interpretation under supervision of Sebastian Erdweg

But wait! There's more!

But wait! There's more!

Correctness (2)

- Are you sure your optimisations are correct?
- Are the results guaranteed to have the same semantics?
- Can you generate a proof to show this property?
 - ▶ Perhaps using parameterised program equivalence
 - ▶ You might leverage scope graphs in your model!

But wait! There's more!

Correctness (2)

- Are you sure your optimisations are correct?
- Are the results guaranteed to have the same semantics?
- Can you generate a proof to show this property?
 - ▶ Perhaps using parameterised program equivalence
 - ▶ You might leverage scope graphs in your model!

PhD candidate Arjen Rouvoet (HB08.260) researches optimisation correctness under supervision of Eelco Visser

Future Work

A running FlowSpec prototype

- So, no, you can't try out FlowSpec yet
- Almost done though, promise!

Evaluation of FlowSpec

- Is it powerful enough to capture everything we want?

Expand the control flow model

- Unordered control flow in expressions
- Parallel control flow for concurrent/parallel loops

Path-sensitive data-flow analysis

- Learning facts about conditions in conditional control flow

Supporting mechanised language meta-theory

- Relating static analysis and dynamic semantics

Summary: Data-Flow Analysis

Representation: Control Flow Graphs + Data Flow information

- Standardised representation for control flow
- Annotate with information from analysis

Formalism: Lattices and Transfer Functions

- Captures the type of information
- How to combine that information
- How to check that the analysis terminates

Limitations: Intra-procedural, context-insensitive

- So no function/method calls
- No tracking of objects or pointers for dynamic dispatch
- But at least we are *flow-sensitive*

Separation of Concerns

Representation

- Control Flow Graphs
- Before/After data-flow information on CFG nodes

Declarative Rules

- To define control-flow rules of a language
- To define data-flow rules of a language

Language-Independent Tooling

- Analysis
- Code completion
- Refactoring
- Optimisation
- ...

Separation of Concerns

Representation

- Control Flow Graphs
- Before/After data-flow information on CFG nodes

Declarative Rules

- FlowSpec

Language-Independent Tooling

- Analysis
- Code completion
- Refactoring
- Optimisation
- ...