

API Call Flow

1. Generate Access Token

Use Basic Authentication where:

Username = API User

Password = API Key

Base64 Encode:

c6aa9738-7e6b-4de5-ad8c-947fbdee032f:07069f088b8c4e48ade327c18289609a

Request:

```
curl --location --request POST 'https://proxy.momoapi.mtn.com/collection/token/' </span>
--header 'Ocp-Apim-Subscription-Key: dbb663a2429e4d9ca84dbbcbe2bb59e6' </span>
--header 'X-Target-Environment: mtnsouthafrica' </span>
--header 'Authorization: Basic <Base64EncodedCredentials>'
```

Expected Response:

```
{
  "access_token": "eyJ...",
  "token_type": "access_token",
  "expires_in": 3600
}
```

2. Initiate Request to Pay

Replace <ACCESS_TOKEN> with the token obtained above.

```
curl --location 'https://proxy.momoapi.mtn.com/collection/v1_0/requesttopay' </span>
--header 'X-Reference-Id: 7fcc9bf5-2b41-42d5-99e9-7ab5d5b62625' </span>
--header 'X-Target-Environment: mtnsouthafrica' </span>
--header 'Content-Type: application/json' </span>
--header 'Ocp-Apim-Subscription-Key: dbb663a2429e4d9ca84dbbcbe2bb59e6' </span>
--header 'Authorization: Bearer <ACCESS_TOKEN>' </span>
--data '{
  "amount": "5",
  "currency": "ZAR",
```

```
"externalId": "00004335",  
  
"payer": {  
  
"partyIdType": "MSISDN",  
  
"partyId": "2700000000"  
  
},  
  
"payerMessage": "MoMo Payment",  
  
"payeeNote": "MoMo Payment"  
  
}'
```

Expected Response:

202 Accepted

The returned X-Reference-Id becomes the transaction reference.

3. Check Transaction Status

```
curl --location --request GET </span>
```

```
'https://proxy.momoapi.mtn.com/collection/v1_0/requesttopay/7fcc9bf5-2b41-42d5-99e9-7ab5d5b62625' </span>
```

```
--header 'Authorization: Bearer <ACCESS_TOKEN>' </span>
```

```
--header 'X-Target-Environment: mtnsouthafrica' </span>
```

```
--header 'Ocp-Apim-Subscription-Key: dbb663a2429e4d9ca84dbbcbe2bb59e6'
```

Sample Response:

```
{  
  
"amount": "5",  
  
"currency": "ZAR",  
  
"financialTransactionId": "123456789",  
  
"externalId": "00004335",  
  
"status": "SUCCESSFUL"  
  
}
```

Common Issues

Error	Possible Cause
401 Unauthorized	Invalid token or expired token
400 Bad Request	Incorrect request payload
404 Not Found	Incorrect transaction reference
409 Conflict	Duplicate X-Reference-Id
500 Internal Server Error	Backend service issue
503 Service Unavailable	Environment temporarily unavailable

Test Data Validation

For your sample payload:

```
{  
  "amount": "5",  
  "currency": "ZAR",  
  "payer": {  
    "partyIdType": "MSISDN",  
    "partyId": "27788033288"  
  }  
}
```

Validate that:

- Currency = ZAR
- Environment = mtnsouthafrica
- MSISDN uses South African format without +
- X-Reference-Id is a unique UUID for every transaction
- Access token has not expired