



Aqua-Duct Documentation

Release 0.2.26

Tomasz Magdziarz

Jul 27, 2019

CONTENTS

1	Aqua-Duct installation guide	1
2	<i>Valve</i> manual	7
3	Configuration file options	13
4	<i>Valve</i> tutorial	23
5	aquaduct	27
	Python Module Index	51
	Index	53

AQUA-DUCT INSTALLATION GUIDE

1.1 Overview

Aqua-Duct software is software written in Python (CPython) and comprises of two elements:

1. aquaduct - a Python package,
2. valve - a script that uses *aquaduct* to perform calculations.

Download

You can download Aqua-Duct packages directly from [Aqua-Duct homepage](#). This page includes older versions of Aqua-Duct as well as development version.

If you follow this installation guide you will install current release.

1.2 Troubleshooting

If you encounter any problems with installation do not hesitate to contact us at info@aquaduct.pl. We are **RE-ALLY** willing to help!

Please, provide us with as much info as you can. In particular try to include following information:

- Operating system's name and version, and CPU architecture (if relevant).
- Python version.
- Command(s) you have used for installation.
- Any error/warning/info message(s) that emerged during or after installation.

1.3 Requirements

1.3.1 Software-wise requirements

- **Python 2.7 (CPython implementation)**
 - numpy $\geq 1.7.0$
 - scipy $\geq 0.13.0$
 - scikit-learn $\geq 0.16.0$
 - MDAnalysis[amber] $\geq 0.15.0$
 - roman $\geq 2.0.0$

1.3.2 Hardware-wise requirements

Aqua-Duct should work on every machine on which you can install the above mentioned software. On computers older then 10 years it may work very slow though. We recommend 64bit SMP architecture, with at least 4GB RAM (32 GB RAM is recommended).

1.4 Installation

1.4.1 Generic Python installation

The easiest way to install Aqua-Duct is to install Python 2.7 and use following command:

```
pip install aquaduct
```

If *pip* is not available try to install it by typing:

```
easy_install pip
```

Depending on the settings of your system you can prepend the above command with *sudo* or *doas* or do *user* installation:

```
# sudo
sudo pip install aquaduct

# doas
doas pip install aquaduct

# 'user' installation
pip install aquaduct --user
```

It is also good idea to try to install Aqua-Duct using virtualenv:

```
virtualenv aquaduct_installation
cd aquaduct_installation
. bin/activate
pip install aquaduct
```

Installation of PyMOL

Under most modern GNU/Linux distributions PyMOL is available as a package in repositories. For example if you are under Ubuntu/Debian you can install it by following command:

```
sudo apt-get install pymol
```

Under Windows there are several ways to install PyMOL, for more details see [PyMOL web site](#).

Instructions for macOS and OpenBSD are in appropriate sections below.

1.4.2 GNU/Linux

Installation was tested on limited number of GNU/Linux systems. On the most of modern installations you can simply follow generic instructions, for example under Ubuntu 16.04 you can type:

```
sudo pip install aquaduct
```

Other systems may require additional work, in particular installation of NetCDF4 is sometimes cumbersome. Following is an example how to install all required packages under Ubuntu 14.04:

```
# install required python packages
sudo apt-get install python-dev python-pip python-numpy python-scipy python-
↳matplotlib python-scikits-learn

# install necessary libraries and git - all required to compile netCDF4
sudo apt-get -y install libnetcdf-dev libhdf5-dev git

# clone netcdf4 python repository
git clone https://github.com/Unidata/netcdf4-python.git
# cd to cloned repository
cd netcdf4-python
# modify setup.cfg to add paths of hdf5 and netcdf4 libraries
sed -i '/\[directories\]/a \
HDF5_dir = /usr/lib \
HDF5_libdir = /usr/lib \
HDF5_incl_dir = /usr/include \
netCDF4_dir = /usr/lib \
netCDF4_libdir = /usr/lib \
netCDF4_incl_dir = /usr/include' setup.cfg
# run setup.py
sudo python setup.py install

# install MDAnalysis
sudo pip install "MDAnalysis[amber]>=0.15"
```

If everything went fine you can follow generic instructions, type:

```
sudo pip install aquaduct
```

1.4.3 MacOS

Aqua-Duct installation was tested on MacOS Sierra and is quite straightforward. It can be installed either with existing system Python or with custom Python installation. In both cases one have to install Xcode for the App Store.

System native Python

```
sudo easy_install pip
sudo pip install aquaduct
```

The drawback of using system Python installation is a lack of PyMOL. It should be, however, relatively easy to compile PyMOL on your own. Try to follow compilation instruction under BSD systems.

Custom Python

This is recommended way of Aqua-Duct installation. If you do not have custom Python installation you can get it by using one of package managers available for macOS, for example [homebrew](#). With this package manager you can do following:

```
brew install python
sudo easy_install pip
sudo pip install aquaduct
```

Next, you can install PyMOL:

```
brew install pymol
brew cask install xquartz
```

Once XQuartz is installed you should reboot. The above procedure installs PyMOL, however, PyMOL Python modules are not visible. To fix it you can issue following commands:

```
cd /usr/local/lib/python2.7/site-packages
sudo ln -s /usr/local/Cellar/pymol/*/libexec/lib/python2.7/site-packages/* ./
```

The above instruction assumes that you are using *brew* and you have only one PyMOL installation.

1.4.4 Windows

Installation under Windows is also possible. The limiting factor is MDAnalysis which is not officially available under Windows yet. You can, however, install Cygwin and perform Aqua-Duct installation in Cygwin.

First, start with [Cygwin installation](#). During the setup select following packages:

- python (2.7)
- python-devel (2.7)
- python-cython
- libnetcdf-devel
- libhdf5-devel
- liblapack-devel
- libopenblas
- python-numpy
- python-six

Another key component that have to be installed is C, C++ and Fortran compilers. You can simply install **gcc-g++** and **gcc-fortran** packages as a first choice, select following packages:

- gcc-g++
- gcc-fortran

Once Cygwin is installed with all required libraries you can perform following steps:

```
# install pip
easy_install-2.7 pip
```

First, try to install SciPy:

```
# install SciPy
pip install scipy
```

If you encounter any problems related to missing **xlocale.h** header file try the following workaround:

```
# prepare fake xlocale.h
ln -s /usr/include/locale.h xlocale.h
export CFLAGS="I"$( pwd )

# install SciPy
pip install scipy
```

Note: The above procedure for SciPy installation might not be optimal. For more information please got to [SciPy web page](#).

Now, install **scikit-learn** and then Aqua-Duct:


```
# install scikit-learn
pip install scikit-learn

# finally, install aquaduct
pip install aquaduct
```

1.4.5 OpenBSD

Aqua-Duct can be also installed under OpenBSD (5.9 and 6.0 amd64). NetCDF-c version 4 has to be installed as OpenBSD ships only netCDF in version 3. First, install hdf5 library and GNU make:

```
# install hdf5 and GNU make
pkg_add hdf5 gmake
```

Next, download netCDF sources. Version 4.2.1.1 works out of the box but is a bit outdated. Visit [NetCDF web page](#) and select version of your choice. Older versions are available in the [FTP archive](#). Once netCDF is downloaded and extracted go to the source directory and try following procedure:

```
# set LD and CPP flags
export LDFLAGS=-L/usr/local/lib
export CPPFLAGS=-I/usr/local/include

# configure project
./configure --enable-shared --enable-dap --disable-doxygen --enable-netcdf-4 --
↪prefix=/path/to/netCDF4/lib

# make and install
gmake
gmake install
```

You may now install py-scipy package:

```
pkg_add py-scipy
```

Install pip if it is missing:

```
pkg_add py-pip
```

Install netCDF4 Python:

```
# define netcdf-4 installation directory
export NETCDF4_DIR=/path/to/netCDF4/lib
pip2.7 install netCDF4
```

At this point you can follow generic Python instructions, type:

```
pip2.7 install aquaduct
```

PyMOL at OpenBSD

According to our knowledge it is possible to install PyMOL 1.4.1 and it is sufficient to work with Aqua-Duct. Go to [SourceForge PyMOL download page](#) and download, save, and extract sources.

PyMOL requires Python Mega Widgets. Download, for example Pmw 1.3.3b from [SourceForge Pmw download page](#). Extract it and install by:

```
python2.7 setup.py install
```

TKinter (2.7) and several other packages are also required:

```
pkg_add python-tkinter freeglut glew png
```

Next, go to the extracted PyMOL sources open `setup.py` and modify `inc_dirs` variable at line 129 by adding following paths:

```
"/usr/X11R6/include/freetype2",  
"/usr/X11R6/include",  
"/usr/local/include",
```

Now, you can build and install PyMOL by typing following commands:

```
python2.7 setup.py build  
python2.7 setup.py install  
python2.7 setup2.py install  
cp pymol /usr/local/bin
```

PyMOL can be run by typing *pymol* or can be used as Python module.

Other BSDs

Installation on other BSDs might be easier. For example, Python netCDF4 is available in ports of FreeBSD and DragonFlyBSD. Try to install it and SciPy, then proceed to generic Python installation instructions.

If you are using NetBSD or other BSD try to follow OpenBSD instructions.

VALVE MANUAL

Valve application is a driver that uses *aquaduct* module to perform analysis of trajectories of selected residues in MD simulation.

2.1 Valve invocation

Once *aquaduct* module is installed (see *Aqua-Duct installation guide*) properly on the machine *Valve* is available as `valve.py` command line tool.

2.1.1 Usage

Basic help of *Valve* usage can be displayed by following command:

```
valve.py --help
```

It should display following information:

```
usage: valve.py [-h] [--dump-template-config] [-t THREADS] [-c CONFIG_FILE]
               [--max-frame MAX_FRAME]

Valve, Aqua-Duct driver

optional arguments:
  -h, --help                show this help message and exit
  --dump-template-config    Dumps template config file. Suppress all other output
                           or actions. (default: False)
  -t THREADS                Limit Aqua-Duct calculations to given number of
                           threads. (default: None)
  -c CONFIG_FILE            Config file filename. (default: None)
  --max-frame MAX_FRAME    Limit number of frames. (default: None)
  --version                Prints versions and exits.. (default: False)
```

2.1.2 Configuration file template

Configuration file used by *Valve* is of moderate length and complexity. It can be easily prepared with a template file that can be printed by *Valve*. Use following command to print configuration file template on the screen:

```
valve.py --dump-template-config
```

Configuration file template can also be easily saved in to a file with:

```
valve.py --dump-template-config > config.txt
```

Where `config.txt` is a configuration file template.

For detailed description of configuration file and available options see [Configuration file options](#)

2.1.3 Valve calculation run

Once configuration file is ready *Valve* calculations can be run with a following simple command:

```
valve.py -c config.txt
```

Some of *Valve* calculations can be run in parallel. By default all available CPU cores are used. This is not always desired - limitation of used CPU cores can be done with `-t` option which limits number of concurrent threads used by *Valve*. If it equals 1 no parallelism is used.

Note: Specifying number of threads greater than available CPU cores is generally not optimal.

However, in order to maximize usage of available CPU power it is recommended to set it as number of cores + 1. The reason is that *Valve* uses one thread for the main process and the excess over one for processes for parallel calculations. When parallel calculations are executed the main threads waits for results.

Note: Option `--max-frame` can be used for testing or debugging purposes. It allows to limit number of frames processed by *Valve*. If it set, for example, to 1000 only first 1000 frames will be processed making all calculations very fast.

2.2 How does Valve work

Application starts with parsing input options. If `--help` or `--dump-template-config` options are provided appropriate messages are printed on the screen and *Valve* quits with signal 0.

Note: In current version *Valve* does not check the validity of the config file.

If config file is provided *Valve* parse it quickly and regular calculations starts according to its content. Calculations performed by *Valve* are done in several stages described in the next sections.

2.2.1 Traceable residues

The first stage finds all residues that should be traced and appends them to the list of *traceable residues*. It is done in a loop over all frames. In each frame residues of interest are searched and appended to the list but only if they are not already present on the list.

The search of the residues is done according to user provided definitions.. Two requirements have to be met to append residue to the list:

1. The residue have to be found according to the *Object* definition.
2. The residues have to be within the *Scope* of interest.

The *Object* definition encompasses usually the active site of the protein. The *Scope* of interest defines, on the other hand, the boundaries in which residues are traced and is usually defined as protein.

Since *aqueduct* in its current version uses *MDAnalysis* Python module for reading, parsing and searching of MD trajectory data, definitions of *Object* and *Scope* have to be given as its *Selection Commands*.

Object definition

Object definition have to comprise of two elements:

1. It have to define residues to trace.
2. It have to define spatial boundaries of the *Object* site.

For example, proper *Object* definition could be following:

```
(resname WAT) and (sphzone 6.0 (resnum 99 or resnum 147))
```

It defines WAT as residues that should be traced and defines spatial constrains of the *Object* site as spherical zone within 6 Angstroms of the center of masses of residues with number 99 and 147.

Scope definition

Scope can be defined in two ways: as *Object* but with broader boundaries or as the convex hull of selected molecular object.

In the first case definition is very similar to *Object* and it have to follow the same limitations. For example, proper *Scope* definition could be following:

```
resname WAT around 2.0 protein
```

It consequently have to define WAT as residues of interest and defines spatial constrains as all WAT residues that are within 2 Angstroms of the protein.

If the *Scope* is defined as the convex hull of selected molecular object (which is recommended), the definition itself have to comprise of this molecular object only, for example `protein`. In that case the scope is interpreted as the interior of the convex hull of atoms from the definition. Therefore, *traceable residues* would be in the scope only if they are within the convex hull of atoms of `protein`.

2.2.2 Raw paths

The second stage of calculations uses the list of all traceable residues from the first stage and finds coordinates of center of masses for each residue in each frame. As in the first stage, it is done in a loop over all frames. For each residue in each frame *Valve* calculates or checks two things:

1. Is the residue in the *Scope* (this is always calculated according to the *Scope* definition).
2. Is the residue in the *Object*. This information is calculated in the first stage and can be reused in the second. However, it is also possible to recalculate this data according to the new *Object* definition.

For each of the *traceable residues* a special *Path* object is created. If the residue is in the *Scope* its center of mass is added to the appropriate *Path* object together with the information if it is in the *Object* or not.

2.2.3 Separate paths

The third stage uses collection of *Path* objects to create *Separate Path* objects. Each *Path* comprise data for one residue. It may happen that the residue enters and leaves the *Scope* and the *Object* many times over the entire MD. Each such an event is considered by *Valve* as a separate path.

Each *separate path* comprises of three parts:

1. *Incoming* - Defined as a path that leads from the point in which residue enters the *Scope* and enters the object for the first time.
2. *Object* - Defined as a path that leads from the point in which residue enters the *Object* for the first time and leaves it for the last time.

3. *Outgoing* - Defined as a path that leads from the point in which residue leaves the *Object* for the last time and leaves the *Scope*.

Auto Barber

After the initial search of *Separate Path* objects it is possible to run procedure which trims paths down to the surface of macromolecule or other molecular entity defined by the user. This is done by removing parts of raw paths that are inside spheres that originate in the points marking these ends of separate paths that end at the boundary of *Scope*. Recreation of separate paths is run automatically after Auto Barber procedure.

2.2.4 Clusterization of inlets

Each of the separate paths has beginning and end. If either of them are at the boundaries of the *Scope* they are considered as *Inlets*, i.e. points that mark where the *traceable residues* enters or leaves the *Scope*. Clusters of inlets, on the other hand, mark endings of tunnels or ways in the system which was simulated in the MD.

Clusterization of inlets is performed in following steps:

1. Initial clusterization. Depending on the method, some of the inlets might not be arranged to any cluster and are considered as outliers.
2. [Optional] Outliers detection. Arrangement of inlets to clusters is sometimes far from optimal. In this step, *inlets* that do not fit to cluster are detected and annotated as outliers. This step can be executed in two modes:
 1. Automatic mode. Inlet is considered to be an outlier if its distance from the centroid is greater then $\text{mean distance} + 4 * \text{standard deviation of all distances within the cluster}$.
 2. Defined threshold. Inlet is considered to be an outlier if its minimal distance from any other point in the cluster is greater then the threshold.
3. [Optional] Reclusterization of outliers. It may happen that the outliers form actually clusters but it was not recognized in initial clusterization. In this step clusterization is executed for outliers only and found clusters are appended to the clusters identified in the first step. Rest of the inlets are marked as outliers.

Potentially recursive clusterization

Both *Initial clusterization* and *Reclusterization* can be run in a recursive manner. If in the appropriate sections defining clusterization methods option *recursive_clusterization* is used appropriate method is run for each cluster separately. Clusters of specific size can be excluded from recursive clusterization (option *recursive_threshold*). It is also possible to limit maximal number of recursive levels - option *max_level*. For additional information see [Clusterization sections](#).

2.2.5 Analysis

Fifth stage of *Valve* calculations analyses results calculated in stages 1 to 4. Results of the analysis is displayed on the screen or can be save to text file and comprise of following parts:

- Tile and data stamp.
- [Optional] Dump of configuration options.
- **Basic information on traceable residues and separate paths.**
 - Number of traceable residues.
 - Number of separate paths.
- **Basic information on inlets.**
 - Number of inlets.

- Number of clusters.
- Are outliers detected.

- **Summary of inlets clusters. Table with 5 columns:**

1. **Nr:** Row number, starting from 0.
2. **Cluster:** ID of the cluster. Outliers have 0.
3. **Size:** Size of the cluster.
4. **INCOMING:** Number of inlets corresponding to separate paths that enter the scope.
5. **OUTGOING:** Number of inlets corresponding to separate paths that leave the scope.

- **Summary of separate paths clusters types. Table with 9 columns.**

1. **Nr:** Row number, starting from 0.
2. **CType:** Separate path Cluster Type.
3. **Size:** Number of separate paths belonging to Cluster type.
4. **Inp:** Average length of incoming part of the path. If no incoming part is available it is nan.
5. **InpStd:** Standard deviation of length Inp.
6. **Obj:** Average length of object part of the path. If no incoming part is available it is nan.
7. **ObjStd:** Standard deviation of length Inp.
8. **Out:** Average length of outgoing part of the path. If no incoming part is available it is nan.
9. **OutStd:** Standard deviation of length Inp.

- **List of separate paths and their properties. Table with 17 columns.**

1. **Nr:** - Row number, starting from 0.
2. **ID:** - Separate path ID.
3. **BeginF:** Number of frame in which the path begins.
4. **InpF:** Number of frame in which path begins Incoming part.
5. **ObjF:** Number of frame in which path begins Object part.
6. **OutF:** Number of frame in which path begins Outgoing part.
7. **EndF:** Number of frame in which the path ends.
8. **InpL:** Length of Incoming part. If no incoming part nan is given.
9. **ObjL:** Length of Object part.
10. **OutL:** Length of Outgoing part. If no outgoing part nan is given.
11. **InpS:** Average step of Incoming part. If no incoming part nan is given.
12. **InpStdS:** Standard deviation of InpS.
13. **ObjS:** Average step of Object part.
14. **ObjStdS:** Standard deviation of ObjS.
15. **OutS:** Average step of Outgoing part. If no outgoing part nan is given.
16. **OutStdS:** Standard deviation of OutS.
17. **CType:** Cluster type of separate path.

Separate path ID

Separate Paths IDs are composed of two numbers separated by colon. First number is the residue number. Second number is consecutive number of the separate path made by the residue. Numeration starts with 0.

Cluster Type of separate path

Each separate paths has two ends: beginning and end. Both of them either belong to one of the inlets clusters, or are among outliers, or are inside the scope. If an end belongs to one of the clusters (including outliers) it has ID of the cluster. If it is inside the scope it has special ID of N. Cluster type is an ID composed of IDs of both ends of separate path separated by colon charter.

2.2.6 Visualization

Sixth stage of *Valve* calculations visualizes results calculated in stages 1 to 4. Visualization is done with PyMOL. *Valve* automatically starts PyMOL and loads visualizations in to it. Molecule is loaded as PDB file. Other objects like Inlets clusters or paths are loaded as CGO objects.

Following is a list of objects created in PyMOL (all of them are optional). PyMOL object names given in **bold** text or short explanation is given.

- Selected frame of the simulated system. Object name: *molecule*.
- Inlets clusters, each cluster is a separate object. Object name: **cluster_** followed by cluster annotation: outliers are annotated as Out; regular clusters by ID.
- List of cluster types, raw paths. Each cluster type is a separate object. Object name composed of cluster type (colon replaced by underline) plus **_raw**.
- List of cluster types, smooth paths. Each cluster type is a separate object. Object name composed of cluster type (colon replaced by underline) plus **_smooth**.
- All raw paths. They can be displayed as one object or separated in to Incoming, Object and Outgoing part. Object name: **all_raw**, or **all_raw_in**, **all_raw_obj**, and **all_raw_out**.
- All raw paths inlets arrows. Object name: **all_raw_paths_io**.
- All smooth paths. They can be displayed as one object or separated in to Incoming, Object and Outgoing part. Object name: **all_smooth**, or **all_smooth_in**, **all_smooth_obj**, and **all_smooth_out**.
- All raw paths inlets arrows. Object name: **all_raw_paths_io**.
- Raw paths displayed as separate objects or as one object with several states. Object name: **raw_paths_** plus number of path or **raw_paths** if displayed as one object.
- Smooth paths displayed as separate objects or as one object with several states. Object name: **smooth_paths_** plus number of path or **smooth_paths** if displayed as one object.
- Raw paths arrows displayed as separate objects or as one object with several states. Object name: **raw_paths_io_** plus number of path or **raw_paths_io** if displayed as one object.
- Smooth paths arrows displayed as separate objects or as one object with several states. Object name: **smooth_paths_io_** plus number of path or **smooth_paths_io** if displayed as one object.

Color schemes

Inlets clusters are colored automatically. Outliers are gray.

Incoming parts of paths are red, Outgoing parts are blue. Object parts in case of smooth paths are green and in case of raw paths are green if residue is precisely in the object area or yellow if is leaved object area but it is not in the Outgoing part yet.

Arrows are colored in accordance to paths colors.

CONFIGURATION FILE OPTIONS

Valve Configuration file is a simple and plain text file. It has similar structure as INI files commonly used in one of the popular operating systems and is compliant with Python module `ConfigParser`.

Configuration file comprises of several *sections*. They can be grouped in to three categories. Names of sections given in **bold** text.

1. **Global settings:**

- **global**

2. **Stages options:**

1. **traceable_residues**
2. **raw_paths**
3. **separate_paths**
4. **inlets_clusterization**
5. **analysis**
6. **visualize**

3. **Methods options:**

- **smooth**
- **clusterization**
- **reclusteriation**

3.1 Section global

This section allows settings of trajectory data and some other future global options.

Option	Default value	Description
top	None	Path to topology file. Aqua-Duct supports PDB, PRMTOP, PFS topology files.
trj	None	Path to trajectory file. Aqua-Duct supports NC and DCD trajectory files.

Note: Options **top** and **trj** are mandatory.

3.2 Common settings of stage sections

Stages 1-4 which perform calculations have some common options allowig for execution control and saving/loading data.

Option	Default value	Description
execute	runonce	Option controls stage execution. It can have one of three possible values: <code>run</code> , <code>runonce</code> , and <code>skip</code> . If it is set to <code>run</code> calculations are always performed and if dump is set dump file is saved. If it is set to <code>runonce</code> calculations are performed if there is no dump file specified by dump option. If it is present calculations are skipped and data is loaded from the file. If it is set to <code>skip</code> calculations are skip and if dump is set data is loaded from the file.
dump	[dump file name]	File name of dump data. It is used to save results of calculations or to load previously calculated data - this depends on execute option. Default value of this option depends on the stage and for stages 1 to 4 is one of the following (listed in order): <ul style="list-style-type: none">• 1_traceable_residues_data.dump• 2_raw_paths_data.dump• 3_separate_paths_data.dump• 4_inlets_clusterization_data.dump

Stages 5-6 also uses **execute** option, however, since they do not perform calculations *per se* in stead of **dump** option they use **save**.

Option	Default value	Description
execute	run	Option controls stage execution. It can have one of three possible values: <code>run</code> , <code>runonce</code> , and <code>skip</code> . If it is set to <code>run</code> or <code>runonce</code> stage is executed and results is saved according to save option. If it is set to <code>skip</code> stage is skipped.
save	[save file name]	File name for saving results. Default value of this option depends on the stage and for stages 1 to 4 is one of the following (listed in order): <ul style="list-style-type: none"> • 5_analysis_results.txt • 6_visualize_results.py Stage 6 can save results in two file types: <ol style="list-style-type: none"> 1. As Python script - extension <code>.py</code> plus companion archive <code>.tar.gz</code>, 2. As PyMOL session - extension <code>.pse</code>.

3.3 Stage traceable_residues

Option	Default value	Description
scope	None	Definition of <i>Scope</i> of interest. See also Scope definition .
scope_convexhull	True	Flag to set if the <i>Scope</i> is direct or convex hull definition.
object	None	Definition of <i>Object</i> of interest. See also Object definition .

Note: Options **scope** and **object** are mandatory.

3.4 Stage raw_paths

This stage also requires definition of the *Scope* and *Object*. If appropriate settings are not given, settings from the previous stage are used.

Option	Default value	Description
scope	None	Definition of <i>Scope</i> of interest. See also Scope definition . If <code>None</code> value from previous stage is used.
scope_convexhull	True	Flag to set if the <i>Scope</i> is direct or convex hull definition. If <code>None</code> value from previous stage is used.
object	None	Definition of <i>Object</i> of interest. See also Object definition . If <code>None</code> , value from the previous stage is used
clear_in_object_info	False	If it is set to <code>True</code> information on occupation of <i>Object</i> site by traceable residues calculated in the previous stage is cleared and have to be recalculated. This is useful if definition of <i>Object</i> was changed.

3.5 Stage separate_paths

Option	Default value	Description
discard_empty_paths	True	If set to <code>True</code> empty paths are discarded.
sort_by_id	True	If set to <code>True</code> separate paths are sorted by ID. Otherwise they are sorted in order of appearance.
apply_smoothing	False	If set to <code>True</code> smooth paths are precalculated according to smooth setting. This speed up access to smooth paths in later stages but makes dump data much bigger.
apply_soft_smoothing	True	If set to <code>True</code> raw paths are replaced by smooth paths calculated according to smooth section.
discard_short_paths	1	This option allows to discard paths that are shorter then the threshold.
auto_barber	None	This option allows to select molecular entity used in Auto Barber procedure. See also Auto Barber and barber_with_spheres() .

3.6 Stage inlets_clusterization

Option	Default value	Description
recluster_outliers	False	If set to <code>True</code> reclusterization of outliers is executed according to the method defined in reclusterization section.
detect_outliers	False	If set detection of outliers is executed. It could be set as a floating point distance threshold or set to <code>Auto</code> . See Clusterization of inlets for more details.
singletons_outliers	False	Maximal size of cluster to be considered as outliers. If set to number > 0 clusters of that size are removed and their objects are moved to outliers. See Clusterization of inlets for more details.
max_level	5	Maximal number of recursive clusterization levels.
create_master_paths	False	If set to <code>True</code> master paths are created (fast CPU and big RAM recommended; 50k frames long simulation may need ca 20GB of memory)

3.7 Stage analysis

Option	Default value	Description
dump_config	True	If set to <code>True</code> configuration options, as seen by Valve, are added to the head of results.

3.8 Stage visualize

Option	Default value	Description
<code>simply_smooths</code>	<code>RecursiveVector</code>	<p>Option indicates linear simplification method to be used in plotting smooth paths. Simplification removes points which do not (or almost do not) change the shape of smooth path. Possible choices are:</p> <ul style="list-style-type: none"> • <code>RecursiveVector</code> (see LinearizeRecursiveVector), • <code>HobbitVector</code> (see LinearizeHobbitVector), • <code>OneWayVector</code> (see LinearizeOneWayVector), • <code>RecursiveTriangle</code> (see LinearizeRecursiveTriangle), • <code>HobbitTriangle</code> (see LinearizeHobbitTriangle), • <code>OneWayTriangle</code> (see LinearizeOneWayTriangle). <p>Optionally name of the method can be followed by a threshold value in parentheses, ie <code>RecursiveVector(0.05)</code>. For sane values of thresholds see appropriate documentation of each method. Default values works well. This option is not case sensitive. It is recommended to use default method or <code>HobbitVector</code> method.</p>
<code>all_paths_raw</code>	<code>False</code>	If <code>True</code> produces one object in PyMOL that holds all paths visualized by raw coordinates.
<code>all_paths_smooth</code>	<code>False</code>	If <code>True</code> produces one object in PyMOL that holds all paths visualized by smooth coordinates.
<code>all_paths_split</code>	<code>False</code>	If is set <code>True</code> objects produced by <code>all_paths_raw</code> and <code>all_paths_smooth</code> are split into Incoming, Object, and Outgoing parts and visualized as three different objects.
<code>all_paths_raw_io</code>	<code>False</code>	If set <code>True</code> arrows pointing beginning and end of paths are displayed oriented accordingly to raw paths orientation.
<code>all_paths_smooth_io</code>	<code>False</code>	If set <code>True</code> arrows pointing beginning and end of paths are displayed oriented accordingly to smooth paths orientation.
<code>paths_raw</code>	<code>False</code>	If set <code>True</code> raw paths are displayed as separate objects or as one object with states corresponding to number of path.
<code>paths_smooth</code>	<code>False</code>	If set <code>True</code> smooth paths are displayed as separate objects or as one object with states corresponding to number of path.
18	Chapter 3. Configuration file options	
<code>paths_raw_io</code>	<code>False</code>	If set <code>True</code> arrows indicating beginning and end of paths, oriented

Note: Possibly due to limitations of `MDAnalysis` only whole molecules can be displayed. If `show_molecule` is set to `backbone` complete protein will be displayed any way. This may change in future version of `MDAnalysis` and or `aqueduct`.

Note: If several frames are selected they are displayed as states which may interfere with other PyMOL objects displayed with several states.

Note: If several states are displayed protein tertiary structure data might be lost. This seems to be limitation of either `MDAnalysis` or PyMOL.

3.9 Clusterization sections

Default section for definition of clusterization method is named **clusterization** and default section for reclusterization method definition is named **reclusterization**. All clusterization sections shares some common options. Other options depends on the method.

Option	Default value	Description
method	mean-shift or dbscan	Name of clasteriation method. It have to be one of the following: dbscan, affprop, mean-shift, birch, kmeans. Default value depends if it is clusterization section (meanshift) or reclusterization section (dbscan).
recursive_clusterization	clusterization or None	If it is set to name of some section that holds clusterization method settings this method will be called in the next recursion of clusteriation. Default value for reclusterization is None.
recursive_threshold	None	Allows to set threshold of that excludes clusters of certain size from reclusterization. Value of this option comprises of <i>operator</i> and <i>value</i> . Operator can be one of the following: >, >=, <=, <. Value have to be expressed as floating number and it have to be in the range of 0 to 1.

3.9.1 dbscan

For detailed description look at `sklearn.cluster.DBSCAN` documentation. Following table summarized options available in *Valve* and is a copy of original documentation.

Option	Value type	Description
eps	float	The maximum distance between two samples for them to be considered as in the same neighborhood.
min_samples	int	The number of samples (or total weight) in a neighborhood for a point to be considered as a core point. This includes the point itself.
metric	str	The metric to use when calculating distance between instances in a feature array. Can be one of the following: <ul style="list-style-type: none">• cityblock,• cosine,• euclidean,• manhattan.
algorithm	str	The algorithm to be used by the NearestNeighbors module to compute pointwise distances and find nearest neighbors. Can be one of the following: <ul style="list-style-type: none">• auto,• ball_tree,• kd_tree,• brute.
leaf_size	int	Leaf size passed to BallTree or cKDTree.

3.9.2 affprop

For detailed description look at [AffinityPropagation](#) documentation. Following table summarized options available in *Valve* and is a copy of original documentation.

Option	Value type	Description
damping	float	Damping factor between 0.5 and 1.
convergence_iter	int	Number of iterations with no change in the number of estimated clusters that stops the convergence.
max_iter	int	Maximum number of iterations.
preference	float	Points with larger values of preferences are more likely to be chosen as exemplars.

3.9.3 meanshift

For detailed description look at [MeanShift](#) documentation. Following table summarized options available in *Valve* and is a copy of original documentation.

Option	Value type	Description
bandwidth	Auto or float	Bandwidth used in the RBF kernel. If <code>Auto</code> or <code>None</code> automatic method for bandwidth estimation is used. See <code>estimate_bandwidth()</code> .
cluster_all	bool	If true, then all points are clustered, even those orphans that are not within any kernel.
bin_seeding	bool	If true, initial kernel locations are not locations of all points, but rather the location of the discretized version of points, where points are binned onto a grid whose coarseness corresponds to the bandwidth.
min_bin_freq	int	To speed up the algorithm, accept only those bins with at least <code>min_bin_freq</code> points as seeds. If not defined, set to 1.

3.9.4 birch

For detailed description look at [Birch](#) documentation. Following table summarized options available in *Valve* and is a copy of original documentation.

Option	Value type	Description
threshold	float	The radius of the subcluster obtained by merging a new sample and the closest subcluster should be lesser than the threshold. Otherwise a new subcluster is started.
branching_factor	int	Maximum number of CF subclusters in each node.
n_clusters	int	Number of clusters after the final clustering step, which treats the subclusters from the leaves as new samples. By default, this final clustering step is not performed and the subclusters are returned as they are.

3.9.5 kmeans

For detailed description look at [KMeans](#) documentation. Following table summarized options available in *Valve* and is a copy of original documentation.

Option	Value type	Description
n_clusters	int	The number of clusters to form as well as the number of centroids to generate.
max_iter	int	Maximum number of iterations of the k-means algorithm for a single run.
n_init	int	Number of time the k-means algorithm will be run with different centroid seeds. The final results will be the best output of <code>n_init</code> consecutive runs in terms of inertia.
init	str	Method for initialization, defaults to <code>k-means++</code> . Can be one of following: <code>k-means++</code> or <code>random</code> .
tol	float	Relative tolerance with regards to inertia to declare convergence.

3.10 Smooth section

Section **smooth** supports following options:

Option	Value type	Description
method	str	Smoothing method. Can be one of the following: <ul style="list-style-type: none">• window, (see WindowSmooth)• mss, (see MaxStepSmooth)• window_mss, (see WindowOverMaxStepSmooth)• awin, (see ActiveWindowSmooth)• awin_mss, (see ActiveWindowOverMaxStepSmooth)• dwin, (see DistanceWindowSmooth)• dwin_mss. (see DistanceWindowOverMaxStepSmooth)
recursive	int	Number of recursive runs of smoothing method.
window	int or float	In window based method defines window size. In plain window it has to be int number.
step	int	In step based method defines size of the step.
function	str	In window based methods defines averaging function. Can be mean or median.

VALVE TUTORIAL

This is a tentative *Valve* manual. Created for the sake of Aqua-Duct training we have today. Eventually, it will be rewritten to the official version.

This tutorial assumes *aqueduct* and *Valve* is already installed - see *Aqua-Duct installation guide*. It is also assumed that user is acquainted with *Valve manual* and *Valve Configuration file options*.

4.1 Valve invocation

Usually *Valve* is run by:

```
valve.py
```

To check if *Valve* is installed and works properly try to issue following commands:

```
valve.py --help  
valve.py --version
```

4.2 Test data

Mouse!

We will use 10ns Amber MD simulation data of sEH protein (PDBID **1cqz**). Necessary files can be found [here](#), see Download section:

- Go to download server.
- Download sample data zip and extract it.

4.3 Inspect your system

Before we start any calculations let's have a look at the protein of interest. Start *PyMOL* and get **1cqz** PDB structure (for example by typing in *PyMOL* command prompt `fetch 1cqz`).

To setup *Valve* calculations we need to know active site of the protein. More precisely we need to know IDs or residues that are in the active site. This would allow us to create *Object definition*.

But wait. Is it really the correct structure? How many chains there are? What is the numeration of residues?

4.3.1 Create *Object definition*

Let's load another structure. Open file `1cqz_sample_topology.pdb` (see *Test data*). It is a first frame of the MD simulation and it is an example of how the frame of MD looks like. In order to create *Object definition* you have to discover following things:

1. What is the name of water residue?
2. What are numbers of residues in the active site?
3. What size the active site is?

Note: It is also good idea to open `.pdb` file in your favorite text editor and look at residue numbers and names.

4.3.2 Create *Scope* definition

Scope definition is easy to create. We will use *Convex hull* version so the scope definition could be simply backbone.

4.4 Prepare config file

Valve performs calculations according to the configuration (aka *config*) file.

Lets start from dumping config file template to `config.txt` file. Open it in your favorite editor and fill all options. If you have troubles look at *Configuration file options* (and *Valve manual*).

Things to remember:

1. Provide correct paths to topology and trajectory data.
2. Enter correct *Object* and *Scope* definitions.
3. Provide file name of result in analysis section, for example `results.txt` (for future reference).
4. Make sure visualization is switched on and `save` option points to session file name (`.pse`)

4.5 Run *Valve*

Make sure all necessary data is in place. Open terminal, go to your working directory and type in:

```
valve.py -c config.txt
```

Depending on your machine and current load it may take a while (matter of minutes) to complete all calculations.

4.5.1 Visual inspection

In the last stage *PyMOL* should pop up and *Valve* should start to feed it with visualization data. This would take a moment and if you set up `save` option a *PyMOL* session would be saved. Once it is done *Valve* quits and switches off *PyMOL*. Now, you can restart it and read saved session.

4.5.2 Clusterization

Improve clusterization of Inlets. See *Configuration file options* for more hints on available clusterization options.

4.5.3 Analysis tables

Open `5_analysys_results.txt` file and look at summaries and tables. See also *Valve manual*.

4.6 Feedback

Give us your opinion. Send your questions, inquires, anything to developer(s): <mailto:info@aquaduct.pl>. This are couple of questions that might be useful to form your opinion.

1. What do you like in *Valve* and *Aqua-Duct*?
2. What do you do not like in *Valve* or *Aqua-Duct*?
3. What is missing?
4. Do you find it useful?

AQUADUCT

5.1 aquaduct package

5.1.1 Subpackages

aquaduct.geom package

Submodules

aquaduct.geom.cluster module

This module provides functions for clusterization. Clusterization is done by `scikit-learn` module.

MeanShiftBandwidth (*X*, ***kwargs*)

class PerformClustering (*method*, ***kwargs*)

Bases: `object`

__init__ (*method*, ***kwargs*)

x.__init__(...) initializes *x*; see `help(type(x))` for signature

__call__ (...) \Leftrightarrow *x*(...)

_get_noclusters (*n*)

fit (*coords*)

centers ()

aquaduct.geom.convexhull module

_vertices_ids (*convexhull*)

_vertices_points (*convexhull*)

_point_within_convexhull (*convexhull*, *point*)

_facets (*convexhull*)

_edges (**args*, ***kwargs*)

is_point_within_convexhull (*point_chull*)

aquaduct.geom.master module

fit_trace_to_points (*trace*, *points*)

decide_on_type (*cont*, *s2o_threshold=0.5*)

```
get_weights_ (spaths, smooth=None)
get_mean_coord_ (coords, l)
concatenate (*args)
class CTypeSpathsCollectionWorker (spaths=None,          ctype=None,          bias_long=5,
                                   smooth=None)
    Bases: object
    __init__ (spaths=None, ctype=None, bias_long=5, smooth=None)
        x.__init__(...) initializes x; see help(type(x)) for signature
    coords_types_prob_widths (sp_slices_)
    __call__ (...) <==> x(...)
class CTypeSpathsCollection (spaths=None,          ctype=None,          bias_long=5,          pbar=None,
                             threads=1)
    Bases: object
    parts = (0, 1, 2)
    __init__ (spaths=None, ctype=None, bias_long=5, pbar=None, threads=1)
        x.__init__(...) initializes x; see help(type(x)) for signature
    beat ()
    update ()
    lens ()
    lens_norm ()
    lens_real ()
    full_size ()
    static simple_types_distribution (types)
    types_distribution ()
    types_prob_to_types (types_prob)
    get_master_path (smooth=None, resid=0)
create_master_spath (spaths, smooth=None, resid=0, ctype=None, bias_long=5, pbar=None)
calculate_master (spaths_resid_ctype_smooth)
```

aquaduct.geom.pca module

```
class Center (X)
    Bases: object
    __init__ (X)
        x.__init__(...) initializes x; see help(type(x)) for signature
    __call__ (...) <==> x(...)
    undo (X)
class Normalize (X)
    Bases: object
    __init__ (X)
        x.__init__(...) initializes x; see help(type(x)) for signature
    __call__ (...) <==> x(...)
    undo (X)
```



```
class Standartize(X)
    Bases: aquaduct.geom.pca.Center, aquaduct.geom.pca.Normalize

    __init__(X)
        x.__init__(...) initializes x; see help(type(x)) for signature

    __call__(...) <==> x(...)

    undo(X)

class PCA(X, prepro=None)
    Bases: object

    __init__(X, prepro=None)
        x.__init__(...) initializes x; see help(type(x)) for signature

    P

    preprocess(X)

    preprocess_undo(X)

    __call__(...) <==> x(...)

    undo(T)
```

aquaduct.geom.smooth module

```
class Smooth(recursive=None, **kwargs)
    Bases: object

    __init__(recursive=None, **kwargs)
        x.__init__(...) initializes x; see help(type(x)) for signature

    smooth(coords)

    __call__(...) <==> x(...)

class GeneralWindow

    static max_window_at_pos(pos, size)

    check_bounds_at_max_window_at_pos(lb, ub, pos, size)

class WindowSmooth(window=5, function=<function mean>, **kwargs)
    Bases: aquaduct.geom.smooth.Smooth, aquaduct.geom.smooth.GeneralWindow

    __init__(window=5, function=<function mean>, **kwargs)
        x.__init__(...) initializes x; see help(type(x)) for signature

    smooth(**kwargs)

class DistanceWindowSmooth(window=5, function=<function mean>, **kwargs)
    Bases: aquaduct.geom.smooth.Smooth, aquaduct.geom.smooth.GeneralWindow

    __init__(window=5, function=<function mean>, **kwargs)
        x.__init__(...) initializes x; see help(type(x)) for signature

    smooth(**kwargs)

class ActiveWindowSmooth(window=5, function=<function mean>, **kwargs)
    Bases: aquaduct.geom.smooth.Smooth, aquaduct.geom.smooth.GeneralWindow

    __init__(window=5, function=<function mean>, **kwargs)
        x.__init__(...) initializes x; see help(type(x)) for signature

    smooth(**kwargs)
```

```
class MaxStepSmooth (step=1.0, **kwargs)
    Bases: aquaduct.geom.smooth.Smooth
    __init__ (step=1.0, **kwargs)
        x.__init__(...) initializes x; see help(type(x)) for signature
    smooth (**kwargs)
```

```
class WindowOverMaxStepSmooth (**kwargs)
    Bases: aquaduct.geom.smooth.Smooth
    __init__ (**kwargs)
        x.__init__(...) initializes x; see help(type(x)) for signature
    smooth (coords)
```

```
class ActiveWindowOverMaxStepSmooth (**kwargs)
    Bases: aquaduct.geom.smooth.Smooth
    __init__ (**kwargs)
        x.__init__(...) initializes x; see help(type(x)) for signature
    smooth (coords)
```

```
class DistanceWindowOverMaxStepSmooth (**kwargs)
    Bases: aquaduct.geom.smooth.Smooth
    __init__ (**kwargs)
        x.__init__(...) initializes x; see help(type(x)) for signature
    smooth (coords)
```

aquaduct.geom.traces module

diff (trace)
This function calculates the distance between 2 given points.

Parameters **trace** – coordinates in numpy array object

Returns distance between points

tracepoints (start, stop, nr)

Parameters

- **start** – coordinates of the first point as a numpy array object
- **stop** – coordinates of the second point as a numpy array object
- **nr** – number of elements between the first and second point

Returns two-dimentional numpy array; number of dimentions depends on nr parameter

midpoints (paths)

The function returns a tuple of numpy arrays extended with mid point spanning last and first element(column) of these arrays.

Parameters **paths** – a tuple of 2-dimentional np.arrays that hold 3D coordinates; each element holds one trace, all elements are supposed to make one path divided in to sections

Returns paths elements with additional mid points as a generator object

length_step_std (trace)

This function calculates sum, mean and standard deviation from all segments of a trace.

Parameters **trace** – coordinates of points as numpy array

Returns a tuple with basics statistics of a trace

derrivative (*values*)

vector_norm (*V*)

Parameters **V** – a vector in a form of array-like object, tuple or a list

Returns normalized length of a vector

triangle_angles (*A, B, C*)

Parameters are coordinates of points which are tops of triangle. The function calculates angles in a triangle formed by given coordinates.

Parameters

- **A** – coordinates of the first point
- **B** – coordinates of the second point
- **C** – coordinates of the third point

Returns list of arguments where angle is given in radians , the output is as follow:
[BAC,CAB,ABC]

triangle_angles_last (*A, B, C*)

Parameters are coordinates of points which are tops of triangle. The function calculates the [ABC] angle.

Parameters

- **A** – coordinates of the first point [A top]
- **B** – coordinates of the second point [B top]
- **C** – coordinates of the third point [C top]

Returns list with one value of ABC angle in radians

triangle_height (*A, B, C*)

Parameters are coordinates of points which are tops of triangle. The function calculates the ABC triangle height.

Parameters

- **A** – coordinates of the first point [A top]
- **B** – coordinates of the second point [B top]
- **C** – coordinates of the third point [C top]

Returns one value of ABC triangle height

vectors_angle (*A, B*)

This function calculates the angle between two given vectors (starting from the [0,0,0] to the given coordinates).

Parameters

- **A** – coordinates of the first point which is the end of the vector
- **B** – coordinates of the second point which is the end of the vector

Returns the angle between vectors in question (in radians)

vectors_angle_alt (*A, B*)

This function calculates the angle between two given vectors (starting from the [0,0,0] to the given coordinates

- alternative method.

Parameters

- **A** – coordinates of the first point which is the end of the vector
- **B** – coordinates of the second point which is the end of the vector

Returns the angle between vectors in question (in radians)

vectors_angle_alt_anorm (*A*, *B*, *A_norm*)

This function calculates the angle between two given vectors (starting from the [0,0,0] to the given coordinates

- alternative method with additional *A_norm* holding norm of *A*.

Parameters

- **A** – coordinates of the first point which is the end of the vector
- **B** – coordinates of the second point which is the end of the vector
- **A_norm** – additional parameter holding normalized of vector *A*

Returns the angle between vectors in question (in radians)

vectors_angle_anorm (*A*, *B*, *A_norm*)

This function calculates the angle between two given vectors (starting from the [0,0,0] to the given coordinates using additional *A_norm* holding norm of *A*.

Parameters

- **A** – coordinates of the first point which is the end of the vector
- **B** – coordinates of the second point which is the end of the vector
- **A_norm** – additional parameter holding normalized of vector *A*

Returns the angle between vectors in question (in radians)

class LinearizeOneWay

Bases: `object`

here (*coords*)

This function simplifies the trace by removing the redundant, linear points :param coords: 3D coordinates of a trace as an array-like object :return: indices of coordinates which are a starting and ending points of linear fragments and other non-linear points of the trace

class LinearizeHobbit

Bases: `aquaduct.geom.traces.LinearizeOneWay`

and_back_again (*coords*)

__call__ (...) <==> *x*(...)

class LinearizeRecursive

Bases: `object`

Base class for linearization methods classes.

It implements recursive algorithm.

here (*coords*, *depth*=0)

Core of recursive linearization algorithm.

It checks if the first, the last and the middle point are linear according to the criterion. The middle point is a selected point that is in the middle of length of the paths made by input coordinates.

If these points are linear their indices are returned. Otherwise, coordinates are split into two parts. First part spans points from the first point to the middle point (inclusive) and the second part spans points from the middle (inclusive) to the last point. Next, these two parts are submitted recursively to `here()`.

Results of these recursive calls are joined, redundant indices are removed and sorted result is returned.

Parameters

- **coords** (*numpy.ndarray*) – Input coordinates.
- **depth** (*int*) – Depth of recurrence.

Returns Indices of **coords** points that can be used instead of all points in visualization.

Return type list of int

`__call__` (...) <==> x(...)

class **TriangleLinearize** (*threshold=0.01*)

Bases: *object*

`__init__` (*threshold=0.01*)

x.`__init__`(...) initializes x; see `help(type(x))` for signature

is_linear (*coords, **kwargs*)

class **VectorLinearize** (*threshold=0.05236*)

Bases: *object*

Base class for linearization methods classes.

It implements vector linearization criterion.

`__init__` (*threshold=0.05236*)

x.`__init__`(...) initializes x; see `help(type(x))` for signature

is_linear_core (*coords, depth=None*)

Method checks if input coordinates are linear according to the threshold and depth.

It begins with calculation of the threshold. If *depth* is None it is set to 1. Current threshold is calculated with following simple equation:

$$threshold_{current} = threshold_{initial} * (2 - 0.9^{depth})$$

Next, in a loop over all points but the first and the last the angle is calculated between two vectors. The first one made by the point and the first point, and the second vector made by the last and the first point. If any of the calculated angles is bigger than the threshold methods returns False; otherwise method returns True.

Parameters

- **coords** (*numpy.ndarray*) – Coordinates for which linearization criterion is checked.
- **depth** (*int*) – Depth of recurrence.

Returns True if input coordinates are linear and False otherwise.

Return type bool

is_linear (*coords, depth=None, **kwargs*)

For more detail see `is_linear_core()` which is used as the criterion of linearity in this method.

Parameters

- **coords** (*numpy.ndarray*) – Coordinates for which linearization criterion is checked.
- **depth** (*int*) – Depth of recurrence.

Returns True if input coordinates are linear and False otherwise. Criterion is checked for coordinates in normal and reverse order.

Return type bool

class **LinearizeRecursiveVector** (*threshold=0.05236*)

Bases: *aquaduct.geom.traces.LinearizeRecursive*, *aquaduct.geom.traces.VectorLinearize*

Class provides recursive linearization of coordinates with *LinearizeRecursive* algorithm and the criterion of linearity implemented by *VectorLinearize*. This is default method.

class LinearizeRecursiveTriangle (*threshold=0.01*)

Bases: *aquaduct.geom.traces.LinearizeRecursive*, *aquaduct.geom.traces.TriangleLinearize*

Class provides recursive linearization of coordinates with *LinearizeRecursive* algorithm and the criterion of linearity implemented by *TriangleLinearize*.

class LinearizeHobbitVector (*threshold=0.05236*)

Bases: *aquaduct.geom.traces.LinearizeHobbit*, *aquaduct.geom.traces.VectorLinearize*

Class provides recursive linearization of coordinates with *LinearizeHobbit* algorithm and the criterion of linearity implemented by *VectorLinearize*.

class LinearizeHobbitTriangle (*threshold=0.01*)

Bases: *aquaduct.geom.traces.LinearizeHobbit*, *aquaduct.geom.traces.TriangleLinearize*

Class provides recursive linearization of coordinates with *LinearizeHobbit* algorithm and the criterion of linearity implemented by *TriangleLinearize*.

class LinearizeOneWayVector (*threshold=0.05236*)

Bases: *aquaduct.geom.traces.LinearizeOneWay*, *aquaduct.geom.traces.VectorLinearize*

Class provides recursive linearization of coordinates with *LinearizeOneWay* algorithm and the criterion of linearity implemented by *VectorLinearize*.

class LinearizeOneWayTriangle (*threshold=0.01*)

Bases: *aquaduct.geom.traces.LinearizeOneWay*, *aquaduct.geom.traces.TriangleLinearize*

Class provides recursive linearization of coordinates with *LinearizeOneWay* algorithm and the criterion of linearity implemented by *TriangleLinearize*.

Module contents

aquaduct.traj package

Submodules

aquaduct.traj.dumps module

class TmpDumpWriterOfMDA

Bases: *object*

__init__ ()

x.**__init__**(...) initializes x; see help(type(x)) for signature

dump_frames (*reader, frames, selection='protein'*)

close ()

__del__ ()

aquaduct.traj.inlets module

class ProtoInletTypeCodes

```

    surface = 'surface'
    internal = 'internal'
    incoming = 'inin'
    outgoing = 'inout'

class InletTypeCodes
    Bases: aquaduct.traj.inlets.ProtoInletTypeCodes
    all_surface = [('surface', 'inin'), ('surface', 'inout')]
    all_internal = [('internal', 'inin'), ('internal', 'inout')]
    all_incoming = [('surface', 'inin'), ('internal', 'inin')]
    all_outgoing = [('surface', 'inout'), ('internal', 'inout')]
    surface_incoming = ('surface', 'inin')
    internal_incoming = ('internal', 'inin')
    internal_outgoing = ('internal', 'inout')
    surface_outgoing = ('surface', 'inout')
    itype = 'internal'

class InletClusterGenericType(inp, out)
    Bases: object
    __init__(inp, out)
        x.__init__(...) initializes x; see help(type(x)) for signature
    input
    output
    static cluster2str(cl)
    __getitem__(item)
    __len__()
    __str__() <==> str(x)
    __repr__() <==> repr(x)
    make_val(base)
    __cmp__(other)
    __hash__() <==> hash(x)
    make_spherical(xyz)

class InletClusterExtendedType(surfin, interin, interout, surfout)
    Bases: aquaduct.traj.inlets.InletClusterGenericType
    __init__(surfin, interin, interout, surfout)
        x.__init__(...) initializes x; see help(type(x)) for signature
    generic

class Inlet(coords, type, reference)
    Bases: tuple
    __getnewargs__()
        Return self as a plain tuple. Used by copy and pickle.
    __getstate__()
        Exclude the OrderedDict from pickling

```

```
static __new__ (_cls, coords, type, reference)
    Create new instance of Inlet(coords, type, reference)

__repr__ ()
    Return a nicely formatted representation string

__slots__ = ()

__asdict ()
    Return a new OrderedDict which maps field names to their values

__fields = ('coords', 'type', 'reference')

classmethod __make (iterable, new=<built-in method __new__ of type object>, len=<built-in function len>)
    Make a new Inlet object from a sequence or iterable

__replace (**kws)
    Return a new Inlet object replacing specified fields with new values

coords
    Alias for field number 0

reference
    Alias for field number 2

type
    Alias for field number 1

class Inlets (spaths, center_of_system=None, onlytype=[('surface', 'inin'), ('surface', 'inout')])
    Bases: object

    __init__ (spaths, center_of_system=None, onlytype=[('surface', 'inin'), ('surface', 'inout')])
        x.__init__(...) initializes x; see help(type(x)) for signature

    extend_inlets (spath, onlytype=None)

    add_cluster_annotations (clusters)

    size

    coords

    types

    refs

    call_clusterization_method (method, data)

    perform_clustering (method)

    perform_reclustering (method, skip_outliers=False, skip_size=None)

    recluster_cluster (method, cluster)

    recluster_outliers (method)

    small_clusters_to_outliers (maxsize)

    renumber_clusters ()

    sort_clusters ()

    clusters_list

    clusters_centers

    clusters_size

    clusters_std

    spath2types (**kwargs)

    lim_to (what, towhat)
```



```
lim2spaths (spaths)
lim2types (types)
lim2clusters (clusters)
limspaths2 (**kwargs)
```

aquaduct.traj.paths module

```
union (a, b)
glue (a, b)
xor (*args, **kwargs)
left (a, b)
right (a, b)
class PathTypesCodes

    path_in_code = 'i'
    path_object_code = 'c'
    path_out_code = 'o'
class GenericPathTypeCodes

    object_name = 'c'
    scope_name = 's'
    out_name = 'n'
class GenericPaths (id_of_res, min_pf=None, max_pf=None)
    Bases: object, aquaduct.traj.paths.GenericPathTypeCodes
    __init__ (id_of_res, min_pf=None, max_pf=None)
        x.__init__(...) initializes x; see help(type(x)) for signature
    add_coord (coord)
    add_object (frame)
    add_scope (frame)
    add_type (frame, ftype)
    max_frame
    min_frame
    get_paths_in ()
    get_paths_out ()
    get_paths_for_frames_range (**kwargs)
    find_paths (fullonly=False)
    find_paths_coords (fullonly=False)
    find_paths_types (fullonly=False)
    find_paths_coords_types (fullonly=False)
    get_single_path_coords (spath)
    get_single_path_types (spath)
```

barber_with_spheres (*spheres*)

class **SinglePathID** (*path_id=None, nr=None*)

Bases: `object`

__init__ (*path_id=None, nr=None*)

x.**__init__**(...) initializes x; see help(type(x)) for signature

__str__ () <==> *str(x)*

yield_single_paths (*gps, fullonly=False, progress=False*)

class **SinglePath** (*path_id, paths, coords, types*)

Bases: `object`, `aquaduct.traj.paths.PathTypesCodes`, `aquaduct.traj.inlets.InletTypeCodes`

empty_coords = `array([], shape=(0, 3), dtype=float32)`

__init__ (*path_id, paths, coords, types*)

x.**__init__**(...) initializes x; see help(type(x)) for signature

coords_first_in

coords_last_out

coords_filo

get_inlets ()

coords

coords_cont

paths

paths_cont

types

types_cont

gtypes

gtypes_cont

etypes

etypes_cont

size

begins

ends

has_in

has_object

has_out

get_coords (***kwargs*)

get_coords_cont (*smooth=None*)

_make_smooth_coords (***kwargs*)

apply_smoothing (*smooth*)

get_distance_cont (*smooth=None, normalize=False*)

get_distance_rev_cont (**args, **kwargs*)

get_distance_both_cont (***kwargs*)

get_velocity_cont (***kwargs*)

```
    get_acceleration_cont (**kwargs)

class MasterPath(sp)
    Bases: aquaduct.traj.paths.SinglePath
    __init__(sp)
        x.__init__(...) initializes x; see help(type(x)) for signature
    add_width(width)
```

aquaduct.traj.reader module

```
class Reader(topology, trajectory)
    Bases: object
    __init__(topology, trajectory)
        x.__init__(...) initializes x; see help(type(x)) for signature
    open_trajectory()
    number_of_frames
    set_current_frame(frame)
    next_frame()
    iterate_over_frames()
    parse_selection(selection)
    select_resnum(resnum)
    select_multiple_resnum(resnum_list)

class ReadViaMDA(topology, trajectory)
    Bases: aquaduct.traj.reader.Reader
    number_of_frames
    set_current_frame(frame)
    next_frame()
    parse_selection(selection)
    select_resnum(resnum)
    select_multiple_resnum(resnum_list)
    __enter__()
    __exit__(typ, value, traceback)
    open_trajectory()

class ReadAmberNetCDFviaMDA(topology, trajectory)
    Bases: aquaduct.traj.reader.ReadViaMDA
    open_trajectory()

class ReadDCDviaMDA(topology, trajectory)
    Bases: aquaduct.traj.reader.ReadViaMDA
    open_trajectory()
```

aquaduct.traj.selections module**class Selection**Bases: `object``def __init__(self, selection, selection_string=None):``self.selection_object = selection self.selection_string = selection_string``center_of_mass()``iterate_over_residues()``unique_resids()``unique_resids_number()``atom_positions()``center_of_mass_of_residues()``get_convexhull_of_atom_positions()``contains_residues(other, convex_hull=False, map_fun=None)``containing_residues(other, *args, **kwargs)``uniquify()``__add__(other)``first_resid()`**class SelectionMDA(*args, **kwargs)**Bases: `MDAnalysis.core.AtomGroup.new_class, aquaduct.traj.selections.Selection``iterate_over_residues()``unique_resids(ikwid=False)``atom_positions()``__add__(other)`

Concatenate the Group with another Group or Component of the same level.

Unexpected section title.

`Parameters`

other [Group or Component] Group or Component with *other.level* same as *self.level*

Unexpected section title.

`Returns`

Group Group with elements of *self* and *other* concatenated`uniquify()`**class CompactSelectionMDA(sMDA)**Bases: `object``__init__(sMDA)``x.__init__(...)` initializes x; see `help(type(x))` for signature`toSelectionMDA(reader)`

Module contents

aquaduct.utils package

Submodules

aquaduct.utils.clui module

Module comprises conveniences functions and definitions for different operations related to command line user interface.

emit_message_to_file_in_root_logger (*mess*)

message_special (*mess*)

message (*mess*, *cont=False*)

Prints message to standard error. If FileHandler is present in the `root_logger` the same message is appended to the log file.

Parameters

- **mess** (*str*) – message to print
- **cont** (*bool*) – if set True no new line is printed

class fbm (*info*, *cont=True*)

Bases: `object`

__init__ (*info*, *cont=True*)

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature

__enter__ ()

__exit__ (*typ*, *value*, *traceback*)

__call__ (...) <==> `x(...)`

class tictoc (*mess*)

Bases: `object`

__init__ (*mess*)

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature

__enter__ ()

__exit__ (*typ*, *value*, *traceback*)

gregorian_year_in_days = 365.2425

Length of Gregorian year in days. Average value. Source: <https://en.wikipedia.org/wiki/Year>

smart_time_string (*s*, *rl=0*, *t=1.1*, *maximal_length=None*, *maximal_units=5*)

Function transforms time in seconds to nicely formatted string of length defined by `maximal_length`. Depending on number of seconds time is represented with one or more of the following units:

Unit name	Unit abbreviation
seconds	s
minutes	m
hours	h
days	d
years	y

Maximal number of units used in time string can be set with `maximal_units`.

Parameters

- **s** (*int*) – Input time in seconds.

- **rl** (*int*) – Number of units already used for representing time.
- **t** (*float*) – Exces above standard number of current time units.
- **maximal_length** (*int*) – Maximal length of the output string. Must be greater then 0.
- **maximal_units** (*int*) – Maximal number of units used in the output string. Must be greater then 0 and lower then 6.

Returns string of nicely formatted time

Return type `str`

gsep (*sep*='-', *times*=72, *length*=None)
Generic separator.

Parameters

- **sep** (*str*) – Element(s) of separator.
- **times** (*int*) – Number of times `sep` is printed.
- **length** (*int*) – Optional maximal length of output.

Returns String separator.

Return type `str`

tsep (*line*)

Parameters **line** (*str*) – Input line.

Returns Returns default `gsep()` of length of `line`.

underline (*line*)

Parameters **line** (*str*) – Input line.

Returns String made by concatenation of `line`, `os.linesep`, and output of `tsep()` called with `line`.

Return type `str`

thead (*line*)

Parameters **line** (*str*) – Input line.

Returns String made by concatenation of output of `tsep()` called with `line`, `line`, `os.linesep`, and again output of `tsep()` called with `line`.

Return type `str`

class SimpleProgressBar (*maxval*=None, *mess*=None)

Bases: `object`

Simple progress bar displaying progress with percent indicator, progress bar and ETA. Progress is measured by iterations.

Variables

- **rotate** (*str*) – String comprising characters with frames of a rotating toy.
- **barlength** (*int*) – Length of progress bar.
- **maxval** (*int*) – maximal number of iterations
- **current** (*int*) – current number of iterations
- **overrun_notice** (*bool*) – if True, overrun above **ivar:‘maxval’** iterations causes insert of newline
- **overrun** (*bool*) – flag of overrun

- **begin** (*int*) – time in seconds at the initialization of the *SimpleProgressBar* class.
- **tcurrent** (*int*) – time in seconds of current iteration

rotate = '\\|/-'

barlength = 24

__init__ (*maxval=None, mess=None*)

Parameters

- **maxval** (*int*) – Maximal number of iterations stored to *maxval*.
- **mess** (*str*) – Optional message displayed at progress bar initialization.

bar ()

ETA ()

Returns ETA calculated on the basis of current number of iterations *current* and current time *tcurrent*. If number of iterations is 0 returns ?. Time is formatted with *smart_time_string()*.

Returns ETA as string.

Return type *str*

percent ()

Returns float number of percent progress calculated in the basis of current number of iterations *current*. Should return number between 0 and 100.

Returns percent progress number

Return type *float*

show ()

Shows current progress.

If value returned by *percent()* is ≤ 100 then progress is printed as percent indicator leaded by ETA calculated by *ETA()*.

If value returned by *percent()* is > 100 then progress is printed as number of iterations and total time.

Progress bar is written to standard error.

heartbeat ()

update (*step*)

Updates number of current iterations *current* by one if *step* is > 0 . Otherwise number of current iterations is not updated. In both cases time of current iteration *tcurrent* is updated and *show()* is called.

Parameters **step** (*int*) – update step

ttime ()

Calculates and returns total time string formatted with *smart_time_string()*.

Returns string of total time

Return type *str*

finish ()

Finishes progress bar. First, *update()* is called with *step* = 0. Next message of total time is written to standard error.

pbar

alias of *aquaduct.utils.clui.SimpleProgressBar*

get_str_timestamp ()

aquaduct.utils.helpers module

Collection of helpers - functions and decorators.

combine (*seqin*)

This is an alien function. It is not extensively used.

Directly taken from http://aspn.activestate.com/ASPN/Cookbook/Python/Recipe/302478/index_txt

Returns a list of all combinations of argument sequences. For example, following call:

```
combine(( (1,2), (3,4) ))
```

gives following list of combinations:

```
[[1, 3], [1, 4], [2, 3], [2, 4]]
```

Parameters *seqin* (*tuple*) – Tuple of sequences to combine.

Returns All possible combinations of all input sequences.

Return type list of lists

is_number (*s*)

lind (*l*, *ind*)

Indexes lists using lists of integers as identifiers. For example:

```
lind(['a', 'b', 'c', 'd', 'e'], [1,4,2])
```

returns:

```
['b', 'e', 'c']
```

Parameters

- **l** (*list*) – List to be indexed.
- **ind** (*list*) – Integer indexes.

Returns Reindexed list.

Return type list

class Auto

Auto type definition. The class is used as an alternative value for options (if particular option supports it). If options (or variables/parameters etc.) have value of *Auto* it means that an automatic process for parametrization should be performed.

For example, if the input parameter is set to *Auto* it is supposed that its value is calculated on the basis of input data or other parameters.

__repr__ ()

Returns String *Auto*.

Return type *str*

__str__ ()

Calls *__repr__* ().

create_tmpfile (*ext=None*)

Creates temporary file. File is created, closed and its file name is returned.

Note: It is responsibility of the caller to delete the file.

Parameters **ext** (*str*) – Optional extension of the file.

Returns File name of created temporary file.

Return type *str*

range2int (*r*, *uniq=True*)

Transforms a string range in to a list of integers (with added missing elements from given ranges).

For example, a following string:

```
'0:2 4:5 7 9'
```

is transformed into:

```
[0, 1, 2, 4, 5, 7, 9]
```

Parameters

- **r** (*str*) – String of input range.
- **uniq** (*bool*) – Optional parameter, if set to *True* only unique and sorted integers are returned.

Returns List of integers.

Return type list of int

int2range (*l*)

Transforms a list of integers in to a string of ranges.

For example, a following list:

```
[0, 1, 2, 4, 5, 7, 9]
```

is transformed into:

```
0:2 4:5 7 9
```

Parameters **l** (*list*) – input list of int

Returns String of ranges.

Return type *str*

is_iterable (*l*)

Checks if provided object is iterable. Returns True is it is iterable, otherwise returns False.

Parameters **l** (*list*) – input object

Returns True if submitted object is iterable otherwise returns False.

Return type *bool*

Warning: Current implementation cannot be used with generators!

Todo: Current implementation is primitive and HAVE TO be replaced.

sortify (*gen*)

Decorator to convert functions' outputs into a sorted list. If the output is iterable it is converted in to a list of appropriate length. If the output is not iterable it is converted in to a list of length 1.

Written on the basis of *listify()*.

Returns Output of decorated function converted to a sorted list.

Return type list

uniqify (*gen*)

Decorator to convert functions' outputs into a sorted list of unique objects. If the output is iterable it is converted in to a list of appropriate length. If the output is not iterable it is converted in to a list of length 1.

Written on the basis of `listify()`.

Returns Output of decorated function converted to a sorted list of unique objects.

Return type list

listify (*gen*)

Decorator to convert functions' outputs into a list. If the output is iterable it is converted in to a list of appropriate length. If the output is not iterable it is converted in to a list of length 1.

This function was copied from:

<http://argandgahandapandpa.wordpress.com/2009/03/29/python-generator-to-list-decorator/>

and further improved by tljm@wp.pl.

Returns Output of decorated function converted to a list.

Return type list

tupleify (*gen*)

Decorator to convert functions' outputs into a tuple. If the output is iterable it is converted in to a tuple of appropriate length. If the output is not iterable it is converted in to a tuple of length 1.

Written on the basis of `listify()`.

Returns Output of decorated function converted to a tuple.

Return type tuple

arrayify (*gen*)

Decorator to convert functions' outputs into a 2D numpy array. If the output is iterable it is converted in to a 2D numpy array of appropriate shape. If the output is not iterable it is converted in to a 2D numpy array of shape 1x1.

Written on the basis of `listify()`.

Returns Output of decorated function converted to a 2D numpy array.

Return type `numpy.ndarray`

arrayify1 (*gen*)

Decorator to convert functions' outputs into a 1D numpy array. If the output is iterable it is converted in to a 2D numpy array of appropriate shape. If the output is not iterable it is converted in to a 2D numpy array of shape 1x1.

Written on the basis of `listify()`.

Returns Output of decorated function converted to a 1D numpy array.

Return type `numpy.ndarray`

list_blocks_to_slices (*l*)

Slices list in to block according to its elements identity. Resulting slices correspond to blocks of identical elements.

Parameters **1** (*list*) – List of any objects.

Returns Generator of slices.

Return type generator

what2what (*what*, *towhat*)

This function search if elements of the one list (:attr: 'what') are present in the other list (:attr: 'towhat') and returns indices of elements form :attr:'what' list as a tuple. If elements from the first list are not present in the second list the tuple is empty. :param list what: Input list for which indices of elements present in towhat are returned. :param list towhat: List of elements which input list is indexed to. :return: Indices of what list that are present in towhat list. :rtype: tuple

make_iterable (*something*)

If input object is not iterable returns it as one element list. Otherwise returns the object.

Parameters **something** (*object*) – Input object.

Returns Iterable object.

Return type iterable or list

stretch_zip (**args*)

compress_zip (**args*)

zip_zip (**args*, ***kwargs*)

xzip_xzip (**args*, ***kwargs*)

aquaduct.utils.maths module

make_default_array (*array_like*)

aquaduct.utils.multip module

Module contents

aquaduct.visual package

Submodules

aquaduct.visual.cmaps module

aquaduct.visual.helpers module

euclidean (*A*, *B*)

cityblock (*A*, *B*)

cc_safe (*c*)

cc (*c*)

color_codes (*code*, *custom_codes=None*)

get_cmap (*size*)

class ColorMapDistMap

Bases: *object*

grey = (0.5, 0.5, 0.5, 1)

__init__ ()

x.__init__(...) initializes x; see help(type(x)) for signature

distance (*E1*, *E2*)

static color_distance (*e1*, *e2*)

```
__call__ (...) <==> x(...)
__ColorMapDistMap__do_cadex()
f_like(n)
```

aquaduct.visual.pymol_cgo module

aquaduct.visual.pymol_connector module

```
class BasicPymolCGO
    Bases: object
    cgo_entity_begin = []
    cgo_entity_end = []
    __init__()
        x.__init__(...) initializes x; see help(type(x)) for signature
    clean()
    new()
    get()
    static make_color_triple(color_definition)

class BasicPymolCGOLines
    Bases: aquaduct.visual.pymol_connector.BasicPymolCGO
    cgo_entity_begin = [2.0, 1.0]
    cgo_entity_end = [3.0]
    add(coords=None, color=None)

class BasicPymolCGOSpheres
    Bases: aquaduct.visual.pymol_connector.BasicPymolCGO
    cgo_entity_begin = []
    cgo_entity_end = []
    add(coords=None, radius=None, color=None)

class BasicPymolCGOPointers
    Bases: aquaduct.visual.pymol_connector.BasicPymolCGO
    cgo_entity_begin = []
    cgo_entity_end = []
    add_cone(coords1=None, coords2=None, radius1=None, radius2=None, color1=None,
              color2=None)
    add_pointer(point=None, direction=None, length=None, color=None, reverse=False)

class SimpleTarWriteHelper
    Bases: object
    __init__()
        x.__init__(...) initializes x; see help(type(x)) for signature
    open(filename)
    save_object2tar(obj, name)
    save_file2tar(filename, name)
    __del__()
```

```

class ConnectToPymol
    Bases: object

    cgo_line_width = 2.0

    ct_pymol = 'pymol'

    ct_file = 'file'

    __init__ ()
        x.__init__(...) initializes x; see help(type(x)) for signature

    decode_color ( **kwargs )

    init_pymol ()

    init_script (filename)

    add_cgo_object (name, cgo_object, state=None)

    del_cgo_object (name, state=None)

    load_pdb (name, filename, state=None)

    orient_on (name)

    __del__ ()

class SinglePathPlotter (pymol_connector, linearize=None)
    Bases: object

    __init__ (pymol_connector, linearize=None)
        x.__init__(...) initializes x; see help(type(x)) for signature

    add_single_path_continuous_trace (spath, smooth=None, plot_in=True,
                                      plot_object=True, plot_out=True, **kwargs)

    paths_trace (spaths, smooth=None, name='paths', state=None, **kwargs)

    paths_inlets (spaths, smooth=None, color=None, plot_in=True, plot_out=True, name='in-out-
                  let', state=None, **kwargs)

    scatter (coords, radius=0.4, color='r', name='scatter', state=None)

    convexhull (chull, color='m', name='convexhull', state=None)

```

aquaduct.visual.quickplot module

```

yield_spath_len_and_smooth_diff_in_types_slices (sp, smooth=None,
                                                  smooth_len=None,
                                                  smooth_diff=None,
                                                  types='etypes')

plot_colorful_lines (x, y, c, **kwargs)

spaths_spectra (spaths, **kwargs)

plot_spath_spectrum (sp, **kwargs)

spath_spectrum (sp, **kwargs)

showit (gen)

get_ax3d (fig, sub=111)

class SimpleTracePlotter
    Bases: object

    plot_line (coords, color, **kwargs)

    single_trace (coords, color='r', **kwargs)

```

```
path_trace(path, color=('r', 'g', 'b'), plot_in=True, plot_object=True, plot_out=True,
            **kwargs)

class SimpleProteinPlotter
    Bases: aquaduct.visual.quickplot.SimpleTracePlotter

    protein_trace(protein, smooth=None, color=('c', 'm', 'y'), **kwargs)

class SimplePathPlotter
    Bases: aquaduct.visual.quickplot.SimpleTracePlotter

    single_path_traces(spaths, smooth=None, color=('r', 'g', 'b'), **kwargs)

class MPLTracePlotter
    Bases: aquaduct.visual.quickplot.SimplePathPlotter, aquaduct.visual.
           quickplot.SimpleProteinPlotter

    init_ax(**kwargs)

    plot_line(**kwargs)

    scatter(**kwargs)
```

Module contents

5.1.2 Module contents

Aqua-Duct - a collection of tools to trace residues in MD simulation.

version()

Returns *aquaduct* version number.

Returns 3 element tuple of int numbers

Return type tuple

version_nice()

Returns *aquaduct* version number as nicely formatted string.

Returns string composed on the basis of the number returned by *version()*.

Return type str

greetings()

Returns fancy greetings of *aquaduct*. It has a form of ASCII-like graphic. Currently it returns following string:

```
-----
~ ~ ~ A Q U A - D U C T ~ ~ ~
#####
####          #####          #####          ####
##           #####          #####          ##
#            ##           ##           #
#            ##           ##           #
#            ##           ##           #
#            ##           ##           #
-----
```

Returns *aquaduct* fancy greetings.

Return type str

Documentation for other versions of Aqua-Duct:

- [development version](#) (use with care)

PYTHON MODULE INDEX

a

- aquaduct, 50
- aquaduct.geom, 34
 - cluster, 27
 - convexhull, 27
 - master, 27
 - pca, 28
 - smooth, 29
 - traces, 30
- aquaduct.traj, 41
 - dumps, 34
 - inlets, 34
 - paths, 37
 - reader, 39
 - selections, 40
- aquaduct.utils, 47
 - clui, 41
 - helpers, 44
 - maths, 47
 - multip, 47
- aquaduct.visual, 50
 - cmaps, 47
 - helpers, 47
 - pymol_cgo, 48
 - pymol_connector, 48
 - quickplot, 49

Symbols

- `_ColorMapDistMap__do_cadex()` (`ColorMapDistMap` method), 48
- `__add__()` (`Selection` method), 40
- `__add__()` (`SelectionMDA` method), 40
- `__call__()` (`CTypeSpathsCollectionWorker` method), 28
- `__call__()` (`Center` method), 28
- `__call__()` (`ColorMapDistMap` method), 47
- `__call__()` (`LinearizeHobbit` method), 32
- `__call__()` (`LinearizeRecursive` method), 33
- `__call__()` (`Normalize` method), 28
- `__call__()` (`PCA` method), 29
- `__call__()` (`PerformClustering` method), 27
- `__call__()` (`Smooth` method), 29
- `__call__()` (`Standartize` method), 29
- `__call__()` (`fbm` method), 41
- `__cmp__()` (`InletClusterGenericType` method), 35
- `__del__()` (`ConnectToPymol` method), 49
- `__del__()` (`SimpleTarWriteHelper` method), 48
- `__del__()` (`TmpDumpWriterOfMDA` method), 34
- `__enter__()` (`ReadViaMDA` method), 39
- `__enter__()` (`fbm` method), 41
- `__enter__()` (`tictoc` method), 41
- `__exit__()` (`ReadViaMDA` method), 39
- `__exit__()` (`fbm` method), 41
- `__exit__()` (`tictoc` method), 41
- `__getitem__()` (`InletClusterGenericType` method), 35
- `__getnewargs__()` (`Inlet` method), 35
- `__getstate__()` (`Inlet` method), 35
- `__hash__()` (`InletClusterGenericType` method), 35
- `__init__()` (`ActiveWindowOverMaxStepSmooth` method), 30
- `__init__()` (`ActiveWindowSmooth` method), 29
- `__init__()` (`BasicPymolCGO` method), 48
- `__init__()` (`CTypeSpathsCollection` method), 28
- `__init__()` (`CTypeSpathsCollectionWorker` method), 28
- `__init__()` (`Center` method), 28
- `__init__()` (`ColorMapDistMap` method), 47
- `__init__()` (`CompactSelectionMDA` method), 40
- `__init__()` (`ConnectToPymol` method), 49
- `__init__()` (`DistanceWindowOverMaxStepSmooth` method), 30
- `__init__()` (`DistanceWindowSmooth` method), 29
- `__init__()` (`GenericPaths` method), 37
- `__init__()` (`InletClusterExtendedType` method), 35
- `__init__()` (`InletClusterGenericType` method), 35
- `__init__()` (`Inlets` method), 36
- `__init__()` (`MasterPath` method), 39
- `__init__()` (`MaxStepSmooth` method), 30
- `__init__()` (`Normalize` method), 28
- `__init__()` (`PCA` method), 29
- `__init__()` (`PerformClustering` method), 27
- `__init__()` (`Reader` method), 39
- `__init__()` (`SimpleProgressBar` method), 43
- `__init__()` (`SimpleTarWriteHelper` method), 48
- `__init__()` (`SinglePath` method), 38
- `__init__()` (`SinglePathID` method), 38
- `__init__()` (`SinglePathPlotter` method), 49
- `__init__()` (`Smooth` method), 29
- `__init__()` (`Standartize` method), 29
- `__init__()` (`TmpDumpWriterOfMDA` method), 34
- `__init__()` (`TriangleLinearize` method), 33
- `__init__()` (`VectorLinearize` method), 33
- `__init__()` (`WindowOverMaxStepSmooth` method), 30
- `__init__()` (`WindowSmooth` method), 29
- `__init__()` (`fbm` method), 41
- `__init__()` (`tictoc` method), 41
- `__len__()` (`InletClusterGenericType` method), 35
- `__new__()` (`Inlet` static method), 35
- `__repr__()` (`Auto` method), 44
- `__repr__()` (`Inlet` method), 36
- `__repr__()` (`InletClusterGenericType` method), 35
- `__slots__` (`Inlet` attribute), 36
- `__str__()` (`Auto` method), 44
- `__str__()` (`InletClusterGenericType` method), 35
- `__str__()` (`SinglePathID` method), 38
- `__asdict__()` (`Inlet` method), 36
- `__edges__()` (in module `aquaduct.geom.convexhull`), 27
- `__facets__()` (in module `aquaduct.geom.convexhull`), 27
- `__fields__` (`Inlet` attribute), 36
- `__get_noclusters__()` (`PerformClustering` method), 27
- `__make__()` (`aquaduct.traj.inlets.Inlet` class method), 36
- `__make_smooth_coords__()` (`SinglePath` method), 38
- `__point_within_convexhull__()` (in module `aquaduct.geom.convexhull`), 27
- `__replace__()` (`Inlet` method), 36
- `__vertices_ids__()` (in module `aquaduct.geom.convexhull`), 27
- `__vertices_points__()` (in module `aquaduct.geom.convexhull`), 27

A

ActiveWindowOverMaxStepSmooth (class in aquaduct.geom.smooth), 30

ActiveWindowSmooth (class in aquaduct.geom.smooth), 29

add() (BasicPymolCGOLines method), 48

add() (BasicPymolCGOSpheres method), 48

add_cgo_object() (ConnectToPymol method), 49

add_cluster_annotations() (Inlets method), 36

add_cone() (BasicPymolCGOPointers method), 48

add_coord() (GenericPaths method), 37

add_object() (GenericPaths method), 37

add_pointer() (BasicPymolCGOPointers method), 48

add_scope() (GenericPaths method), 37

add_single_path_continuous_trace() (SinglePathPlotter method), 49

add_type() (GenericPaths method), 37

add_width() (MasterPath method), 39

all_incoming (InletTypeCodes attribute), 35

all_internal (InletTypeCodes attribute), 35

all_outgoing (InletTypeCodes attribute), 35

all_surface (InletTypeCodes attribute), 35

and_back_again() (LinearizeHobbit method), 32

apply_smoothing() (SinglePath method), 38

aquaduct (module), 50

aquaduct.geom (module), 34

aquaduct.geom.cluster (module), 27

aquaduct.geom.convexhull (module), 27

aquaduct.geom.master (module), 27

aquaduct.geom.pca (module), 28

aquaduct.geom.smooth (module), 29

aquaduct.geom.traces (module), 30

aquaduct.traj (module), 41

aquaduct.traj.dumps (module), 34

aquaduct.traj.inlets (module), 34

aquaduct.traj.paths (module), 37

aquaduct.traj.reader (module), 39

aquaduct.traj.selections (module), 40

aquaduct.utils (module), 47

aquaduct.utils.clui (module), 41

aquaduct.utils.helpers (module), 44

aquaduct.utils.maths (module), 47

aquaduct.utils.multip (module), 47

aquaduct.visual (module), 50

aquaduct.visual.cmaps (module), 47

aquaduct.visual.helpers (module), 47

aquaduct.visual.pymol_cgo (module), 48

aquaduct.visual.pymol_connector (module), 48

aquaduct.visual.quickplot (module), 49

arrayify() (in module aquaduct.utils.helpers), 46

arrayify1() (in module aquaduct.utils.helpers), 46

atom_positions() (Selection method), 40

atom_positions() (SelectionMDA method), 40

Auto (class in aquaduct.utils.helpers), 44

B

bar() (SimpleProgressBar method), 43

barber_with_spheres() (GenericPaths method), 37

barlenght (SimpleProgressBar attribute), 43

BasicPymolCGO (class in aquaduct.visual.pymol_connector), 48

BasicPymolCGOLines (class in aquaduct.visual.pymol_connector), 48

BasicPymolCGOPointers (class in aquaduct.visual.pymol_connector), 48

BasicPymolCGOSpheres (class in aquaduct.visual.pymol_connector), 48

beat() (CTypeSpathsCollection method), 28

begins (SinglePath attribute), 38

C

calculate_master() (in module aquaduct.geom.master), 28

call_clusterization_method() (Inlets method), 36

cc() (in module aquaduct.visual.helpers), 47

cc_safe() (in module aquaduct.visual.helpers), 47

Center (class in aquaduct.geom.pca), 28

center_of_mass() (Selection method), 40

center_of_mass_of_residues() (Selection method), 40

centers() (PerformClustering method), 27

cgo_entity_begin (BasicPymolCGO attribute), 48

cgo_entity_begin (BasicPymolCGOLines attribute), 48

cgo_entity_begin (BasicPymolCGOPointers attribute), 48

cgo_entity_begin (BasicPymolCGOSpheres attribute), 48

cgo_entity_end (BasicPymolCGO attribute), 48

cgo_entity_end (BasicPymolCGOLines attribute), 48

cgo_entity_end (BasicPymolCGOPointers attribute), 48

cgo_entity_end (BasicPymolCGOSpheres attribute), 48

cgo_line_width (ConnectToPymol attribute), 49

check_bounds_at_max_window_at_pos() (GeneralWindow method), 29

cityblock() (in module aquaduct.visual.helpers), 47

clean() (BasicPymolCGO method), 48

close() (TmpDumpWriterOfMDA method), 34

cluster2str() (InletClusterGenericType static method), 35

clusters_centers (Inlets attribute), 36

clusters_list (Inlets attribute), 36

clusters_size (Inlets attribute), 36

clusters_std (Inlets attribute), 36

color_codes() (in module aquaduct.visual.helpers), 47

color_distance() (ColorMapDistMap static method), 47

ColorMapDistMap (class in aquaduct.visual.helpers), 47

combine() (in module aquaduct.utils.helpers), 44

CompactSelectionMDA (class in aquaduct.traj.selections), 40

compress_zip() (in module aquaduct.utils.helpers), 47

concatenate() (in module aquaduct.geom.master), 28

ConnectToPymol (class in aquaduct.visual.pymol_connector), 48

containing_residues() (Selection method), 40

contains_residues() (Selection method), 40

convexhull() (SinglePathPlotter method), 49
 coords (Inlet attribute), 36
 coords (Inlets attribute), 36
 coords (SinglePath attribute), 38
 coords_cont (SinglePath attribute), 38
 coords_filo (SinglePath attribute), 38
 coords_first_in (SinglePath attribute), 38
 coords_last_out (SinglePath attribute), 38
 coords_types_prob_widths() (CTypeSpathsCollection-Worker method), 28
 create_master_spath() (in module aquaduct.geom.master), 28
 create_tmpfile() (in module aquaduct.utils.helpers), 44
 ct_file (ConnectToPymol attribute), 49
 ct_pymol (ConnectToPymol attribute), 49
 CTypeSpathsCollection (class in aquaduct.geom.master), 28
 CTypeSpathsCollectionWorker (class in aquaduct.geom.master), 28

D

decide_on_type() (in module aquaduct.geom.master), 27
 decode_color() (ConnectToPymol method), 49
 del_cgo_object() (ConnectToPymol method), 49
 derrivative() (in module aquaduct.geom.traces), 30
 diff() (in module aquaduct.geom.traces), 30
 distance() (ColorMapDistMap method), 47
 DistanceWindowOverMaxStepSmooth (class in aquaduct.geom.smooth), 30
 DistanceWindowSmooth (class in aquaduct.geom.smooth), 29
 dump_frames() (TmpDumpWriterOfMDA method), 34

E

emit_message_to_file_in_root_logger() (in module aquaduct.utils.clui), 41
 empty_coords (SinglePath attribute), 38
 ends (SinglePath attribute), 38
 ETA() (SimpleProgressBar method), 43
 etypes (SinglePath attribute), 38
 etypes_cont (SinglePath attribute), 38
 euclidean() (in module aquaduct.visual.helpers), 47
 extend_inlets() (Inlets method), 36

F

f_like() (in module aquaduct.visual.helpers), 48
 fbm (class in aquaduct.utils.clui), 41
 find_paths() (GenericPaths method), 37
 find_paths_coords() (GenericPaths method), 37
 find_paths_coords_types() (GenericPaths method), 37
 find_paths_types() (GenericPaths method), 37
 finish() (SimpleProgressBar method), 43
 first_resid() (Selection method), 40
 fit() (PerformClustering method), 27
 fit_trace_to_points() (in module aquaduct.geom.master), 27
 full_size() (CTypeSpathsCollection method), 28

G

GeneralWindow (class in aquaduct.geom.smooth), 29
 generic (InletClusterExtendedType attribute), 35
 GenericPaths (class in aquaduct.traj.paths), 37
 GenericPathTypeCodes (class in aquaduct.traj.paths), 37
 get() (BasicPymolCGO method), 48
 get_acceleration_cont() (SinglePath method), 39
 get_ax3d() (in module aquaduct.visual.quickplot), 49
 get_cmap() (in module aquaduct.visual.helpers), 47
 get_convexhull_of_atom_positions() (Selection method), 40
 get_coords() (SinglePath method), 38
 get_coords_cont() (SinglePath method), 38
 get_distance_both_cont() (SinglePath method), 38
 get_distance_cont() (SinglePath method), 38
 get_distance_rev_cont() (SinglePath method), 38
 get_inlets() (SinglePath method), 38
 get_master_path() (CTypeSpathsCollection method), 28
 get_mean_coord_() (in module aquaduct.geom.master), 28
 get_paths_for_frames_range() (GenericPaths method), 37
 get_paths_in() (GenericPaths method), 37
 get_paths_out() (GenericPaths method), 37
 get_single_path_coords() (GenericPaths method), 37
 get_single_path_types() (GenericPaths method), 37
 get_str_timestamp() (in module aquaduct.utils.clui), 43
 get_velocity_cont() (SinglePath method), 38
 get_weights_() (in module aquaduct.geom.master), 27
 glue() (in module aquaduct.traj.paths), 37
 greetings() (in module aquaduct), 50
 gregorian_year_in_days (in module aquaduct.utils.clui), 41
 grey (ColorMapDistMap attribute), 47
 gsep() (in module aquaduct.utils.clui), 42
 gtypes (SinglePath attribute), 38
 gtypes_cont (SinglePath attribute), 38

H

has_in (SinglePath attribute), 38
 has_object (SinglePath attribute), 38
 has_out (SinglePath attribute), 38
 heartbeat() (SimpleProgressBar method), 43
 here() (LinearizeOneWay method), 32
 here() (LinearizeRecursive method), 32

I

incoming (ProtoInletTypeCodes attribute), 35
 init_ax() (MPLTracePlotter method), 50
 init_pymol() (ConnectToPymol method), 49
 init_script() (ConnectToPymol method), 49
 Inlet (class in aquaduct.traj.inlets), 35
 InletClusterExtendedType (class in aquaduct.traj.inlets), 35
 InletClusterGenericType (class in aquaduct.traj.inlets), 35

Inlets (class in aquaduct.traj.inlets), 36
InletTypeCodes (class in aquaduct.traj.inlets), 35
input (InletClusterGenericType attribute), 35
int2range() (in module aquaduct.utils.helpers), 45
internal (ProtoInletTypeCodes attribute), 35
internal_incoming (InletTypeCodes attribute), 35
internal_outgoing (InletTypeCodes attribute), 35
is_iterable() (in module aquaduct.utils.helpers), 45
is_linear() (TriangleLinearize method), 33
is_linear() (VectorLinearize method), 33
is_linear_core() (VectorLinearize method), 33
is_number() (in module aquaduct.utils.helpers), 44
is_point_within_convexhull() (in module aquaduct.geom.convexhull), 27
iterate_over_frames() (Reader method), 39
iterate_over_residues() (Selection method), 40
iterate_over_residues() (SelectionMDA method), 40
itype (InletTypeCodes attribute), 35

L

left() (in module aquaduct.traj.paths), 37
length_step_std() (in module aquaduct.geom.traces), 30
lens() (CTypeSpathsCollection method), 28
lens_norm() (CTypeSpathsCollection method), 28
lens_real() (CTypeSpathsCollection method), 28
lim2clusters() (Inlets method), 37
lim2spaths() (Inlets method), 36
lim2types() (Inlets method), 37
lim_to() (Inlets method), 36
limspaths2() (Inlets method), 37
lind() (in module aquaduct.utils.helpers), 44
LinearizeHobbit (class in aquaduct.geom.traces), 32
LinearizeHobbitTriangle (class in aquaduct.geom.traces), 34
LinearizeHobbitVector (class in aquaduct.geom.traces), 34
LinearizeOneWay (class in aquaduct.geom.traces), 32
LinearizeOneWayTriangle (class in aquaduct.geom.traces), 34
LinearizeOneWayVector (class in aquaduct.geom.traces), 34
LinearizeRecursive (class in aquaduct.geom.traces), 32
LinearizeRecursiveTriangle (class in aquaduct.geom.traces), 34
LinearizeRecursiveVector (class in aquaduct.geom.traces), 33
list_blocks_to_slices() (in module aquaduct.utils.helpers), 46
listify() (in module aquaduct.utils.helpers), 46
load_pdb() (ConnectToPymol method), 49

M

make_color_triple() (BasicPymolCGO static method), 48
make_default_array() (in module aquaduct.utils.maths), 47
make_iterable() (in module aquaduct.utils.helpers), 47
make_spherical() (in module aquaduct.traj.inlets), 35

make_val() (InletClusterGenericType method), 35
MasterPath (class in aquaduct.traj.paths), 39
max_frame (GenericPaths attribute), 37
max_window_at_pos() (GeneralWindow static method), 29
MaxStepSmooth (class in aquaduct.geom.smooth), 29
MeanShiftBandwidth() (in module aquaduct.geom.cluster), 27
message() (in module aquaduct.utils.clui), 41
message_special() (in module aquaduct.utils.clui), 41
midpoints() (in module aquaduct.geom.traces), 30
min_frame (GenericPaths attribute), 37
MPLTracePlotter (class in aquaduct.visual.quickplot), 50

N

new() (BasicPymolCGO method), 48
next_frame() (Reader method), 39
next_frame() (ReadViaMDA method), 39
Normalize (class in aquaduct.geom.pca), 28
number_of_frames (Reader attribute), 39
number_of_frames (ReadViaMDA attribute), 39

O

object_name (GenericPathTypeCodes attribute), 37
open() (SimpleTarWriteHelper method), 48
open_trajectory() (ReadAmberNetCDFviaMDA method), 39
open_trajectory() (ReadDCDviaMDA method), 39
open_trajectory() (Reader method), 39
open_trajectory() (ReadViaMDA method), 39
orient_on() (ConnectToPymol method), 49
out_name (GenericPathTypeCodes attribute), 37
outgoing (ProtoInletTypeCodes attribute), 35
output (InletClusterGenericType attribute), 35

P

P (PCA attribute), 29
parse_selection() (Reader method), 39
parse_selection() (ReadViaMDA method), 39
parts (CTypeSpathsCollection attribute), 28
path_in_code (PathTypesCodes attribute), 37
path_object_code (PathTypesCodes attribute), 37
path_out_code (PathTypesCodes attribute), 37
path_trace() (SimpleTracePlotter method), 49
paths (SinglePath attribute), 38
paths_cont (SinglePath attribute), 38
paths_inlets() (SinglePathPlotter method), 49
paths_trace() (SinglePathPlotter method), 49
PathTypesCodes (class in aquaduct.traj.paths), 37
pbar (in module aquaduct.utils.clui), 43
PCA (class in aquaduct.geom.pca), 29
percent() (SimpleProgressBar method), 43
perform_clustering() (Inlets method), 36
perform_reclustering() (Inlets method), 36
PerformClustering (class in aquaduct.geom.cluster), 27
plot_colorful_lines() (in module aquaduct.visual.quickplot), 49

plot_line() (MPLTracePlotter method), 50
 plot_line() (SimpleTracePlotter method), 49
 plot_spath_spectrum() (in module aquaduct.visual.quickplot), 49
 preprocess() (PCA method), 29
 preprocess_undo() (PCA method), 29
 protein_trace() (SimpleProteinPlotter method), 50
 ProtoInletTypeCodes (class in aquaduct.traj.inlets), 34

R

range2int() (in module aquaduct.utils.helpers), 45
 ReadAmberNetCDFviaMDA (class in aquaduct.traj.reader), 39
 ReadDCDviaMDA (class in aquaduct.traj.reader), 39
 Reader (class in aquaduct.traj.reader), 39
 ReadViaMDA (class in aquaduct.traj.reader), 39
 recluster_cluster() (Inlets method), 36
 recluster_outliers() (Inlets method), 36
 reference (Inlet attribute), 36
 refs (Inlets attribute), 36
 renumber_clusters() (Inlets method), 36
 right() (in module aquaduct.traj.paths), 37
 rotate (SimpleProgressBar attribute), 43

S

save_file2tar() (SimpleTarWriteHelper method), 48
 save_object2tar() (SimpleTarWriteHelper method), 48
 scatter() (MPLTracePlotter method), 50
 scatter() (SinglePathPlotter method), 49
 scope_name (GenericPathTypeCodes attribute), 37
 select_multiple_resnum() (Reader method), 39
 select_multiple_resnum() (ReadViaMDA method), 39
 select_resnum() (Reader method), 39
 select_resnum() (ReadViaMDA method), 39
 Selection (class in aquaduct.traj.selections), 40
 SelectionMDA (class in aquaduct.traj.selections), 40
 set_current_frame() (Reader method), 39
 set_current_frame() (ReadViaMDA method), 39
 show() (SimpleProgressBar method), 43
 showit() (in module aquaduct.visual.quickplot), 49
 simple_types_distribution() (CTypeSpathsCollection static method), 28
 SimplePathPlotter (class in aquaduct.visual.quickplot), 50
 SimpleProgressBar (class in aquaduct.utils.clui), 42
 SimpleProteinPlotter (class in aquaduct.visual.quickplot), 50
 SimpleTarWriteHelper (class in aquaduct.visual.pymol_connector), 48
 SimpleTracePlotter (class in aquaduct.visual.quickplot), 49
 single_path_traces() (SimplePathPlotter method), 50
 single_trace() (SimpleTracePlotter method), 49
 SinglePath (class in aquaduct.traj.paths), 38
 SinglePathID (class in aquaduct.traj.paths), 38
 SinglePathPlotter (class in aquaduct.visual.pymol_connector), 49
 size (Inlets attribute), 36

size (SinglePath attribute), 38
 small_clusters_to_outliers() (Inlets method), 36
 smart_time_string() (in module aquaduct.utils.clui), 41
 Smooth (class in aquaduct.geom.smooth), 29
 smooth() (ActiveWindowOverMaxStepSmooth method), 30
 smooth() (ActiveWindowSmooth method), 29
 smooth() (DistanceWindowOverMaxStepSmooth method), 30
 smooth() (DistanceWindowSmooth method), 29
 smooth() (MaxStepSmooth method), 30
 smooth() (Smooth method), 29
 smooth() (WindowOverMaxStepSmooth method), 30
 smooth() (WindowSmooth method), 29
 sort_clusters() (Inlets method), 36
 sortify() (in module aquaduct.utils.helpers), 45
 spath_spectrum() (in module aquaduct.visual.quickplot), 49
 spaths2ctypes() (Inlets method), 36
 spaths_spectra() (in module aquaduct.visual.quickplot), 49
 Standartize (class in aquaduct.geom.pca), 28
 strech_zip() (in module aquaduct.utils.helpers), 47
 surface (ProtoInletTypeCodes attribute), 34
 surface_incoming (InletTypeCodes attribute), 35
 surface_outgoing (InletTypeCodes attribute), 35

T

thead() (in module aquaduct.utils.clui), 42
 tictoc (class in aquaduct.utils.clui), 41
 TmpDumpWriterOfMDA (class in aquaduct.traj.dumps), 34
 toSelectionMDA() (CompactSelectionMDA method), 40
 tracepoints() (in module aquaduct.geom.traces), 30
 triangle_angles() (in module aquaduct.geom.traces), 31
 triangle_angles_last() (in module aquaduct.geom.traces), 31
 triangle_height() (in module aquaduct.geom.traces), 31
 TriangleLinearize (class in aquaduct.geom.traces), 33
 tsep() (in module aquaduct.utils.clui), 42
 ttime() (SimpleProgressBar method), 43
 tupleify() (in module aquaduct.utils.helpers), 46
 type (Inlet attribute), 36
 types (Inlets attribute), 36
 types (SinglePath attribute), 38
 types_cont (SinglePath attribute), 38
 types_distribution() (CTypeSpathsCollection method), 28
 types_prob_to_types() (CTypeSpathsCollection method), 28

U

underline() (in module aquaduct.utils.clui), 42
 undo() (Center method), 28
 undo() (Normalize method), 28
 undo() (PCA method), 29
 undo() (Standartize method), 29

`union()` (in module `aquaduct.traj.paths`), 37
`uniquify()` (in module `aquaduct.utils.helpers`), 46
`unique_resids()` (Selection method), 40
`unique_resids()` (SelectionMDA method), 40
`unique_resids_number()` (Selection method), 40
`uniquify()` (Selection method), 40
`uniquify()` (SelectionMDA method), 40
`update()` (CTypeSpathsCollection method), 28
`update()` (SimpleProgressBar method), 43

V

`vector_norm()` (in module `aquaduct.geom.traces`), 31
`VectorLinearize` (class in `aquaduct.geom.traces`), 33
`vectors_angle()` (in module `aquaduct.geom.traces`), 31
`vectors_angle_alt()` (in module `aquaduct.geom.traces`), 31
`vectors_angle_alt_anorm()` (in module `aquaduct.geom.traces`), 32
`vectors_angle_anorm()` (in module `aquaduct.geom.traces`), 32
`version()` (in module `aquaduct`), 50
`version_nice()` (in module `aquaduct`), 50

W

`what2what()` (in module `aquaduct.utils.helpers`), 46
`WindowOverMaxStepSmooth` (class in `aquaduct.geom.smooth`), 30
`WindowSmooth` (class in `aquaduct.geom.smooth`), 29

X

`xor()` (in module `aquaduct.traj.paths`), 37
`xzip_xzip()` (in module `aquaduct.utils.helpers`), 47

Y

`yield_single_paths()` (in module `aquaduct.traj.paths`), 38
`yield_spath_len_and_smooth_diff_in_types_slices()` (in module `aquaduct.visual.quickplot`), 49

Z

`zip_zip()` (in module `aquaduct.utils.helpers`), 47