

EE6310 Image and Video Processing, Fall 2021

Indian Institute of Technology Hyderabad

Homework 3, Assigned 06.10.2021, Due 11:59 pm on 13.10.2021

Remarks:

- For this assignment, use gray scale images from the University of Southern California's image database at <http://sipi.usc.edu/database/database.php?volume=misc>.
- Do not use built-in functions.
- Please turn in Python Notebooks with the following notation for the file name: `your-roll-number-hw3.ipynb`.

1 2D-DFT

Recall the definition of the 2D-DFT from class. Assume that you are working with square images. Write a program that implements the DFT/IDFT pair using the following techniques.

1. From first principles i.e., as a summation over two dimensions. (5)
2. Matrix multiplication using the complex exponential matrix. (5)

Now do the following using three of your favorite images from the above set:

1. Display the image, its DFT magnitude, phase, DFT magnitude subject to the logarithmic transformation. (1)
2. Generate the centered DFT using $(-1)^{i+j}I$ and display its magnitude. (1)
3. Verify that $\text{IDFT}[\text{DFT}[I]] = I$. (1)
4. Show the importance of phase by transposing the phase matrix and then synthesizing the image. Repeat by a) setting the phase to 0, and b) by adding noise. (2)

2 Periodic Convolution

Write a program to do the following:

1. Circularly convolve two images. Test your program by using an image and an averaging filter of size 5×5 . (5)
2. Linearly convolve the same image and filter using the circular convolution function above after appropriate zero padding. (2)
3. Now, verify that you can perform linear convolution using the DFT of zero padded images. (3)

3 Image Denoising using Linear Filters

In this problem you will denoise images using the linear filtering techniques discussed in class. Use additive white Gaussian noise (AWGN) with zero mean and variance $\sigma^2 = 25$. Write a program to denoise the image using the following techniques:

1. Average filter of size $M \times M$. Vary M from 3 to 15 in increments of 2 and observe the tradeoff between denoising and smoothing. What could be an appropriate window size for this noise level? (5)
2. Gaussian filter of size 5×5 . Experiment with the standard deviation σ_h of the filter from 0.5 to 5 in steps of 0.5 and observe its effect on denoising. (5)