

PassRoute

Texas CDL Class A — Practice Question Bank
All categories · 633 unique questions · answers & references

Category	Questions
General Knowledge	137
Air Brakes	78
Combination Vehicles	70
Texas Special Requirements	70
HazMat (H) Endorsement	70
Tanker (N) Endorsement	52
Doubles/Triples (T) Endorsement	52
Passenger (P) Endorsement	52
School Bus (S) Endorsement	52
TOTAL	633

Correct answers are marked with a green check (✓). Each answer line shows a short explanation and the official Texas CDL Handbook reference. In the app, option order is shuffled on every attempt.

1. What is the minimum tread depth for front (steer) tires?

- A. 2/32 inch
- ✓ B. 4/32 inch
- C. 6/32 inch
- D. 8/32 inch

Answer: B — Steer tires need at least 4/32 inch; other tires 2/32 inch. (§2.1 Inspection)

2. Minimum tread depth for tires other than the front is:

- A. 1/32 inch
- ✓ B. 2/32 inch
- C. 4/32 inch
- D. 6/32 inch

Answer: B — Non-steer tires need at least 2/32 inch. (§2.1 Inspection)

3. How much steering-wheel play should make you suspect a problem?

- A. More than 5 degrees
- ✓ B. More than 10 degrees
- C. More than 20 degrees
- D. More than 45 degrees

Answer: B — More than about 10 degrees (2 in on a 20-in wheel) is too much. (§2.1 Inspection)

4. How many reflective warning triangles must you carry?

- A. One
- B. Two
- ✓ C. Three
- D. Six

Answer: C — Three reflective triangles (or 6 fusees / 3 liquid flares). (§2.1 Inspection)

5. Which fire extinguisher rating works on fuel and electrical fires?

- A. Class A
- ✓ B. B:C
- C. Water type
- D. None work

Answer: B — A B:C extinguisher works on burning liquids and electrical fires. (§2.20 Fires)

6. You must carry spare electrical fuses unless the vehicle has:

- ✓ A. Circuit breakers
- B. A spare battery
- C. LED lights
- D. Two alternators

Answer: A — Spare fuses are required unless the vehicle uses circuit breakers. (§2.1 Inspection)

7. The first step of the seven-step inspection is:

- A. Check the lights
- ✓ B. Vehicle overview
- C. Start the engine
- D. Check the brakes

Answer: B — Step 1 is the vehicle overview. (§2.1 Inspection)

8. With the engine off, the inspection includes checking:

- A. Tire pressure only
- ✓ **B. Oil, coolant and belts**
- C. Fifth-wheel grease
- D. The radio

Answer: B — Check oil, coolant, power-steering fluid, belts and leaks. (§2.1 Inspection)

9. Accelerating on a slippery road should be done:

- ✓ **A. Smoothly and gradually**
- B. As fast as possible
- C. With the clutch out
- D. In high gear

Answer: A — Speed up smoothly; too much power can spin the drive wheels. (§2.2 Basic Control)

10. When backing, you should generally:

- A. Back toward the right
- ✓ **B. Back toward the driver's side**
- C. Back quickly
- D. Use mirrors only

Answer: B — Back toward the driver's side, use a helper, and go slowly. (§2.2 Basic Control)

11. You should downshift to the right gear:

- A. In the curve
- ✓ **B. Before a hill or curve**
- C. After the curve
- D. Never on grades

Answer: B — Select the gear before the hill or curve. (§2.3 Shifting)

12. Total stopping distance is made up of:

- A. Braking only
- ✓ **B. Perception + reaction + braking**
- C. Reaction + braking
- D. Perception + braking

Answer: B — Perception plus reaction plus braking distance. (§2.6 Speed)

13. At 55 mph in good conditions, total stopping distance is about:

- A. 140 ft
- B. 220 ft
- C. 320 ft
- ✓ **D. 420 ft**

Answer: D — About 419 ft at 55 mph. (§2.6 Speed)

14. If you double your speed, braking distance increases about:

- A. 2 times
- B. 3 times
- ✓ **C. 4 times**
- D. 10 times

Answer: C — Braking distance grows with the square of speed — about 4 times. (§2.6 Speed)

15. On a wet road you should reduce speed by about:

- A. One-tenth
- ✓ **B. One-third**
- C. One-half
- D. Three-quarters

Answer: B — About one-third on wet roads (half on packed snow). (§2.6 Speed)

16. Compared with a loaded truck, an empty truck usually:

- A. Stops sooner
- ✓ **B. Needs a longer stop**
- C. Cannot skid
- D. Has more traction

Answer: B — Empty trucks have less traction; wheels can lock and skid. (§2.6 Speed)

17. If your vehicle starts to hydroplane, you should:

- A. Brake hard
- ✓ **B. Release the accelerator**
- C. Steer sharply
- D. Accelerate

Answer: B — Release the accelerator and push in the clutch; don't brake hard. (§2.6 Speed)

18. Brake fade is most often caused by:

- A. Cold weather
- ✓ **B. Overheating from overuse**
- C. Low tire pressure
- D. Air in the lines

Answer: B — Heat from using the brakes too much instead of engine braking. (§2.15 Mountain)

19. Posted curve speed limits are set for:

- A. Loaded trucks
- ✓ **B. Cars in good conditions**
- C. Buses
- D. Empty trucks

Answer: B — They are for cars; slow well below them in a truck. (§2.6 Speed)

20. The following-distance rule for a heavy vehicle is:

- A. Always a flat 2 seconds
- ✓ **B. 1 second per 10 ft, +1 over 40 mph**
- C. About three car lengths
- D. 100 ft at any road speed

Answer: B — One second per 10 ft of length; add one second over 40 mph. (§2.7 Space)

21. How far ahead should you look while driving?

- A. Just past the hood
- B. 4 to 6 seconds
- ✓ **C. 12 to 15 seconds**
- D. 30 seconds

Answer: C — Look 12 to 15 seconds ahead. (§2.4 Seeing)

22. You should signal a turn:

- A. Only if cars are near
- ✓ **B. Early and continuously**
- C. After you start turning
- D. With your hand only

Answer: B — Signal early and keep signaling through the turn. (§2.5 Communicating)

23. If you are being tailgated, you should:

- A. Speed up
- ✓ **B. Open up room ahead**
- C. Brake-check them
- D. Slow in the left lane

Answer: B — Increase space ahead so you can slow gradually; avoid quick moves. (§2.7 Space)

24. Before turning right, you should NOT:

- A. Turn slowly
- ✓ **B. Swing wide left first**
- C. Keep the rear near the curb
- D. Check your mirrors

Answer: B — Swinging left invites a pass on your right; turn wide as you finish. (§2.7 Space)

25. Posted clearance heights at bridges:

- A. Are always exact
- ✓ **B. Should not be fully trusted**
- C. Apply only to cars
- D. Increase when loaded

Answer: B — Repaving or snow can reduce clearance; an empty van rides higher. (§2.7 Space)

26. Convex (curved) mirrors show:

- A. A magnified close-up
- ✓ **B. A wider area; objects look farther**
- C. The same as flat mirrors
- D. Only the cab

Answer: B — Wider view, but objects look smaller and farther away. (§2.4 Seeing)

27. A 'hazard' on the road is:

- A. Only a fast-moving speeding car
- ✓ **B. Any condition or user that could be a danger**
- C. Just plain bad weather
- D. Only an actual crash ahead

Answer: B — Anything that could become an emergency. (§2.8 Hazards)

28. The correct response to an aggressive driver is to:

- A. Race them
- ✓ **B. Stay out of their way**
- C. Brake-check them
- D. Block them in

Answer: B — Give them room, avoid eye contact, and do not engage. (§2.9 Aggressive)

29. Texting or holding a phone while driving a CMV is:

- A. Allowed below 30 mph
- ✓ **B. Prohibited**
- C. Fine in light traffic
- D. Banned only for new drivers

Answer: B — Banned; it greatly raises crash risk and can disqualify you. (§2.9 Distracted)

30. Not 'overdriving' your headlights at night means:

- A. Use only low beams
- ✓ **B. Stop within the lit distance**
- C. Follow another vehicle
- D. Use high beams in fog

Answer: B — Drive slowly enough to stop within the range you can see. (§2.10 Night)

31. To avoid glare from oncoming headlights, look:

- A. Straight back at them
- ✓ **B. To the right edge of your lane**
- C. Down at your dashboard
- D. Far down at the road

Answer: B — Look toward the right edge/markings until they pass. (§2.10 Night)

32. In dense fog you should use:

- A. Your bright high beams
- ✓ **B. Low beams and slow down**
- C. Only the hazard flashers
- D. No lights at all

Answer: B — High beams reflect back; use low beams and slow down. (§2.11 Fog)

33. In winter, which usually freezes first?

- A. The open road
- ✓ **B. Bridges and overpasses**
- C. Hills
- D. Tunnels

Answer: B — Bridges freeze before the road. (§2.12 Winter)

34. The road looks wet but tires throw no spray in the cold. This is likely:

- A. Drying pavement
- ✓ **B. Black ice**
- C. Fresh asphalt
- D. A dirty windshield

Answer: B — Black ice — slow down, no sudden steering or braking. (§2.12 Winter)

35. In very hot weather you should especially check:

- ✓ **A. Tire pressure**
- B. The horn
- C. The radio
- D. Window tint

Answer: A — Heat raises tire pressure; check tires and coolant. (§2.13 Hot Weather)

36. On a long downgrade, speed is controlled mainly by:

- A. Constantly riding the brakes
- ✓ **B. A low gear and engine braking**
- C. Just the parking brake
- D. Coasting in neutral

Answer: B — Engine braking in a low gear; brakes only supplement. (§2.15 Mountain)

37. A runaway-truck escape ramp should be used when:

- A. You want a break
- ✓ **B. Your brakes fail on a grade**
- C. You are slightly speeding
- D. Traffic is heavy

Answer: B — Use it if your brakes fail and you cannot stop. (§2.15 Mountain)

38. If a front tire blows out, your first action is to:

- A. Brake hard right away
- ✓ **B. Hold the wheel, stay off the brake**
- C. Steer sharply aside
- D. Shift into neutral gear

Answer: B — Grip the wheel, stay off the brake, let it slow, then ease off the road. (§2.16 Emergencies)

39. If your hydraulic brakes fail, first try to:

- ✓ **A. Pump the brake pedal**
- B. Turn off the engine
- C. Pull the trailer knob
- D. Steer into traffic

Answer: A — Pump to build pressure, then downshift and use the parking brake. (§2.16 Emergencies)

40. To recover from a drive-wheel (rear) skid, you should:

- A. Brake even harder
- ✓ **B. Stop accelerating and steer**
- C. Lock up all the brakes
- D. Speed up to pull out

Answer: B — Ease off the accelerator and steer where you want to go. (§2.18 Skids)

41. A front-wheel skid is usually caused by:

- A. Braking too gently
- ✓ **B. Driving too fast for conditions**
- C. Too much rear weight
- D. Engine braking

Answer: B — Going too fast (or worn/under-inflated front tires); slow down. (§2.18 Skids)

42. The main benefit of ABS in a hard stop is:

- A. A shorter stop every time
- ✓ **B. Keeping steering control**
- C. No need for following space
- D. Automatic steering

Answer: B — Prevents lockup so you can steer; not necessarily a shorter stop. (§2.17 ABS)

43. First at an accident scene, you should:

- A. Move the injured people
- ✓ **B. Protect the area with warning devices**
- C. Leave to find a phone
- D. Push the wrecks aside fast

Answer: B — Prevent another crash first; usually do not move the injured. (§2.19 Accidents)

44. For an engine fire you should:

- A. Open the hood up wide
- ✓ **B. Keep the hood down if you can**
- C. Add more diesel fuel
- D. Drive faster to the shop

Answer: B — Opening the hood adds oxygen; shut off the engine. (§2.20 Fires)

45. The blood alcohol limit for driving a CMV is:

- A. 0.10%
- B. 0.08%
- ✓ **C. 0.04%**
- D. 0.02%

Answer: C — 0.04% or more is a violation for CMV drivers. (§2.21 Alcohol)

46. What actually makes a drinker sober?

- A. Coffee
- B. A cold shower
- C. Fresh air
- ✓ **D. Time**

Answer: D — Only time removes alcohol from the body. (§2.21 Alcohol)

47. A driver with detectable alcohol under 0.04% will be:

- A. Warned only
- ✓ **B. Out of service for 24 hours**
- C. Disqualified for life
- D. Fined and released

Answer: B — Out of service 24 hours; 0.04% or more is a DUI offense. (§2.21 Alcohol)

48. You should inspect your cargo within the first:

- A. 10 miles
- ✓ **B. 50 miles**
- C. 100 miles
- D. 150 miles

Answer: B — Within 50 miles, then every 150 miles or 3 hours. (§3.1 Cargo)

49. The minimum tie-down rule for cargo is:

- A. Just one tie-down total
- ✓ **B. One per 10 ft, at least two**
- C. One for every 25 ft
- D. Only loads over 20 ft

Answer: B — At least one per 10 ft, minimum two. (§3.2 Cargo)

50. A high center of gravity makes a vehicle:

- A. More stable
- ✓ **B. More likely to roll over**
- C. Easier to stop
- D. Better in curves

Answer: B — More top-heavy; load heavy cargo low. (§3.1 Cargo)

51. A Texas Class A CDL is for combinations with a GCWR of:

- A. 16,001 lb or more total
- ✓ **B. 26,001 lb+ towing over 10,000 lb**
- C. 10,000 lb or more total
- D. 40,000 lb or more total

Answer: B — GCWR 26,001+ where the towed unit is over 10,000 lb. (§1 CDL Classes)

52. You get an air-brake restriction if you:

- A. Pass the air-brake test
- ✓ **B. Test in a vehicle without air brakes**
- C. Drive at night
- D. Have a clean record

Answer: B — Failing or skipping the air-brake test (or testing without them) restricts you. (§1 Restrictions)

53. At a railroad crossing, buses with passengers and placarded hazmat must:

- A. Slow only
- ✓ **B. Always stop**
- C. Speed up
- D. Ignore it

Answer: B — They must stop, even when no train is visible. (§2.14 Railroad)

54. A typical tractor-trailer clears a single track in about:

- A. 3 seconds
- ✓ **B. At least 14 seconds**
- C. 1 second
- D. Time does not matter

Answer: B — At least 14 seconds (over 15 for a double track). (§2.14 Railroad)

55. In low light or rain, turn on your headlights mainly to:

- A. Save fuel
- ✓ **B. Be seen by others**
- C. Warm the engine
- D. Charge the battery

Answer: B — Headlights (not just markers) make you visible. (§2.5 Communicating)

56. A header board ('headache rack') is there to:

- A. To hold the spare tire in place
- ✓ **B. Stop cargo from shifting into the cab**
- C. To save a little bit of fuel
- D. To mark an extra-wide load

Answer: B — It protects you from forward-shifting cargo. (§3.2 Cargo)

57. Which tire condition is a defect?

- A. Tread over 4/32 in front
- ✓ **B. Dual tires touching**
- C. Matching tire sizes
- D. Proper inflation

Answer: B — Dual tires must not touch; do not mix radial and bias-ply. (§2.1 Inspection)

58. Which is a sign you are too tired to drive?

- A. Drifting in your lane
- B. Heavy eyelids
- C. Not recalling the last few miles
- ✓ **D. All of the above**

Answer: D — All are danger signs of fatigue — stop and rest. (§2.22 Fatigue)

59. Which is NOT required emergency equipment?

- A. Fire extinguisher
- B. Spare fuses (no breakers)
- C. Three triangles
- ✓ **D. A spare tire**

Answer: D — A spare tire is not required; the others are. (§2.1 Inspection)

60. Which is NOT a correct way to handle a skid?

- A. Stop braking
- B. Steer where you want to go
- ✓ **C. Keep accelerating**
- D. Countersteer as it straightens

Answer: C — Do not keep accelerating; ease off and steer. (§2.18 Skids)

61. Why should you inspect the vehicle before a trip?

- A. To find safety defects
- B. Because the law requires it
- C. To prevent breakdowns
- ✓ **D. All of the above**

Answer: D — All three — safety, legal duty, and avoiding breakdowns. (§2.1 Inspection)

62. Stopping is not always the safest action because:

- A. It just wastes your time
- ✓ **B. Steering away can be quicker**
- C. The brakes will overheat
- D. It is against the law

Answer: B — You can often steer to miss a hazard faster than you can stop. (§2.16 Emergencies)

63. Which is the correct order of the stopping-distance parts?

- A. Braking, reaction, perception
- ✓ **B. Perception, reaction, braking**
- C. Reaction, braking, perception
- D. Perception, braking, reaction

Answer: B — Perceive, react, then brake. (§2.6 Speed)

64. To warn drivers behind that you are slowing a lot, you should:

- A. Just do nothing at all
- ✓ **B. Tap the brake to flash the lights**
- C. Switch on your high beams
- D. Honk the horn repeatedly

Answer: B — Tap the brakes to flash early, or use hazards if very slow. (§2.5 Communicating)

65. The CDL blood alcohol limit while driving a CMV is:

- A. 0.08%
- ✓ **B. 0.04%**
- C. 0.10%
- D. 0.02%

Answer: B — A CDL driver is legally intoxicated at 0.04% BAC — half the limit for car drivers. (§1.4)

66. If your brakes fail on a long downgrade, you should:

- A. Pump harder and hope
- ✓ **B. Use an escape ramp if there is one**
- C. Shift into neutral
- D. Open the door and jump

Answer: B — Runaway escape ramps are built to stop vehicles with failed brakes. (§2.7)

67. Hydroplaning is most likely when:

- A. The road surface is dry
- ✓ **B. There is water and you drive too fast**
- C. You are driving very slowly
- D. The tires are brand-new ones

Answer: B — Hydroplaning happens on wet roads at higher speeds; slow down. (§2.6)

68. To check tire inflation correctly, you should:

- A. Kick the tire hard
- ✓ **B. Use a gauge when the tires are cool**
- C. Just look at the tire
- D. Press it with your hand

Answer: B — Use a pressure gauge and check when tires are cool for an accurate reading. (§2.1)

69. The 'No-Zone' refers to:

- A. A highway rest area
- ✓ **B. A truck's large blind spots**
- C. A toll-only lane
- D. A no-parking curb

Answer: B — The No-Zone is the area around a truck where other vehicles disappear from view. (§2.4)

70. When backing, the safest practice is to:

- A. Back toward the blind right side
- ✓ **B. Back toward your left side and use a helper**
- C. Back as fast as you can
- D. Skip using your mirrors

Answer: B — Back toward the driver's side when possible and use a helper or spotter. (§2.2)

71. Sometimes the best way to avoid a crash is to:

- A. Always brake as hard as you can
- ✓ **B. Steer around the hazard**
- C. Close your eyes and brace
- D. Speed straight through it

Answer: B — You often can steer around an obstacle in less distance than it takes to stop. (§2.7)

72. A safe driver gives turn signals:

- A. Right after the turn
- ✓ **B. Well before the turn**
- C. Only at night
- D. Only on highways

Answer: B — Signal early and keep signaling so others know your intentions. (§2.4)

73. On a slippery road, an engine brake or retarder should usually be:

- A. Turned on fully
- ✓ **B. Turned off**
- C. Used at maximum
- D. Removed entirely

Answer: B — Retarders can make the drive wheels skid on slick roads, so switch them off. (§2.6)

74. Going up a long, steep grade, you should:

- A. Stay in overdrive
- ✓ **B. Shift to a lower gear for power**
- C. Coast in neutral
- D. Switch the engine off

Answer: B — On a steep upgrade, select a lower gear to keep engine power and a steady speed. (§2.6)

75. If you double your speed, braking distance roughly:

- A. Stays roughly the same
- ✓ **B. Increases about four times**
- C. Only doubles, nothing more
- D. Is cut roughly in half

Answer: B — Braking distance grows with the square of speed — about four times when speed doubles. (§2.6)

76. The only sure cure for driving fatigue is to:

- A. Open a window wide
- ✓ **B. Stop and rest or sleep**
- C. Turn the music up
- D. Drink coffee and keep going

Answer: B — Rest or sleep is the only real fix for fatigue; pull over somewhere safe. (§2.8)

77. Texting while driving a CMV is:

- A. Allowed at red lights
- ✓ **B. Prohibited**
- C. Required by law
- D. Fine on the highway

Answer: B — Texting and hand-held phone use are prohibited for CMV drivers. (§2.8)

78. In a work zone you should:

- A. Speed up to clear it fast
- ✓ **B. Slow down and watch for workers**
- C. Change lanes quickly
- D. Follow closely to save time

Answer: B — Reduce speed, keep space, and watch for workers; fines are often doubled. (§2.4)

79. Cargo with a high center of gravity makes the vehicle:

- A. More stable and steady
- ✓ **B. More likely to roll over**
- C. Noticeably faster
- D. Much lighter

Answer: B — A high center of gravity raises rollover risk; load heavy items low. (§3.2)

80. The combined working load limit of tie-downs must be at least:

- A. A quarter of the cargo weight
- ✓ **B. Half of the cargo weight**
- C. Twice the cargo weight
- D. Equal to the truck weight

Answer: B — Combined tie-down WLL must be at least one-half the weight of the cargo secured. (§3.2)

81. When making a right turn, you should:

- A. Swing wide to the left first
- ✓ **B. Keep right and not swing wide**
- C. Speed up through it
- D. Skip the turn signal

Answer: B — Do not swing left before a right turn; it lets others try to pass on the right. (§2.4)

82. Posted curve speeds are set for:

- A. Loaded heavy trucks
- ✓ **B. Cars in good conditions**
- C. Completely empty roads
- D. Night driving only

Answer: B — Posted curve speeds are for cars; heavy trucks should go slower. (§2.6)

83. Brake fade on a long hill is caused by:

- A. Cold, fresh brakes
- ✓ **B. Overheated, overused brakes**
- C. Brand-new brake shoes
- D. A very light load

Answer: B — Riding the brakes overheats them until they fade; use a low gear and engine braking. (§2.7)

84. Antilock brakes (ABS) mainly help you:

- A. Always stop in a shorter distance
- ✓ **B. Keep steering control in a hard stop**
- C. Save a lot of fuel
- D. Skip the brake inspection

Answer: B — ABS keeps wheels from locking so you can steer; it does not necessarily shorten stops. (§5.3)

85. Compared with loaded trucks, empty trucks:

- A. Always stop more quickly
- ✓ **B. May take longer to stop**
- C. Can never skid
- D. Have much more traction

Answer: B — Empty trucks have less traction and can bounce, taking longer to stop. (§2.6)

86. You should turn on your headlights:

- A. Only around midnight
- ✓ **B. At dusk and in rain, fog, or low light**
- C. Never while it is raining
- D. Only out on the highway

Answer: B — Use headlights in low light and bad weather so others can see you. (§2.11)

87. Convex (curved) mirrors:

- A. Make objects look much closer
- ✓ **B. Show more area but make things look farther**
- C. Show nothing useful at all
- D. Are not allowed on big trucks

Answer: B — Convex mirrors show a wider area, but objects appear smaller and farther than they are. (§2.4)

88. The first thing to do when you spot a hazard ahead is:

- A. Ignore it and drive on
- ✓ **B. Get ready to react and adjust**
- C. Speed up to pass it
- D. Just honk your horn

Answer: B — Spotting a hazard early gives you time to plan and act before an emergency. (§2.5)

89. To recover from hydroplaning, you should:

- A. Brake very hard
- ✓ **B. Ease off the accelerator**
- C. Steer hard and sharp
- D. Speed right up

Answer: B — Take your foot off the gas and let the tires slow until they grip again; don't brake hard. (§2.6)

90. If your brakes get wet in a deep puddle, you should:

- A. Stop using them for good
- ✓ **B. Dry them with light braking**
- C. Pour cold water on them
- D. Just ignore the problem

Answer: B — Apply light pressure while driving slowly to dry the brakes. (§2.6)

91. You should NOT pass another vehicle:

- A. On a straight, clear, open road
- ✓ **B. On a hill or curve where you can't see**
- C. In a marked passing lane
- D. When it is clearly safe

Answer: B — Never pass where you can't see far enough ahead, like hills and curves. (§2.4)

92. When merging onto a highway, you should:

- A. Stop and wait there
- ✓ **B. Match traffic speed and merge**
- C. Crawl along very slowly
- D. Force your way in

Answer: B — Accelerate to match traffic and merge smoothly into a gap. (§2.4)

93. For an emergency vehicle with lights and siren, you should:

- A. Speed up to get away
- ✓ **B. Pull over and stop when safe**
- C. Try to block its path
- D. Completely ignore it

Answer: B — Pull to the right and stop when it is safe to let it pass. (§2.4)

94. The fire-extinguisher PASS method is Pull, Aim, Squeeze, and:

- A. Stop
- ✓ **B. Sweep**
- C. Spin
- D. Stand

Answer: B — Sweep the nozzle side to side at the base of the fire. (§2.9)

95. For a tire fire, you should:

- A. Just let it burn out
- ✓ **B. Use water to cool it**
- C. Add more air to it
- D. Keep driving on it

Answer: B — A tire fire needs plenty of water to cool it down. (§2.9)

96. Skids are usually caused by:

- A. Driving along too slowly
- ✓ **B. Driving too fast for conditions**
- C. Smooth, gentle steering
- D. Having good new tires

Answer: B — Most skids come from going too fast for the road and conditions. (§2.7)

97. The best way to prevent a skid is:

- A. Sudden, jerky inputs
- ✓ **B. Smooth, gentle inputs**
- C. Hard panic braking
- D. Very high speed

Answer: B — Steer, brake, and accelerate smoothly to keep traction. (§2.7)

98. In hot weather you should check tires more often because:

- A. The tires get cold
- ✓ **B. Pressure rises and they can fail**
- C. The tires shrink down
- D. Nothing really changes

Answer: B — Heat raises tire pressure and can cause a blowout. (§2.10)

99. In very thick fog, the safest choice is often to:

- A. Speed on through it
- ✓ **B. Pull off the road and wait**
- C. Use your high beams
- D. Tailgate another car

Answer: B — If fog is too thick to see, pull completely off and wait. (§2.11)

100. A vehicle inspection should be done:

- A. Only when it breaks down
- ✓ **B. Before, during, and after a trip**
- C. Just once every year
- D. Never at all, ever

Answer: B — Inspect before the trip, en route, and after the trip. (§2.1)

101. You should first check your cargo within:

- A. The first 500 miles
- ✓ **B. 50 miles, then periodically**
- C. No real need to check
- D. Only after 1000 miles

Answer: B — Inspect cargo within the first 50 miles, then regularly. (§3.1)

102. Cargo must be secured so it does not:

- A. Just look neat and tidy
- ✓ **B. Shift, fall, or block controls**
- C. Stay completely dry
- D. Get cold in the winter

Answer: B — Secured cargo can't shift, fall off, or block the driver's controls. (§3.2)

103. When the sun causes glare, you should:

- A. Just close your eyes
- ✓ **B. Use the visor and slow down**
- C. Speed up to pass it
- D. Turn off your lights

Answer: B — Use the sun visor, wear sunglasses, and reduce your speed. (§2.11)

104. You should use four-way flashers when:

- A. Driving along quickly
- ✓ **B. Stopped or moving very slowly**
- C. Making a normal turn
- D. Parked at your home

Answer: B — Flashers warn others when you are stopped or much slower than traffic. (§2.4)

105. To warn drivers behind that you are slowing, your brake lights should:

- A. Stay off completely
- ✓ **B. Come on as you slow**
- C. Flash on randomly
- D. Be taken off

Answer: B — Slowing with the brake pedal lights your brake lamps to warn others. (§2.4)

106. At a roundabout, you should:

- A. Stop right in the circle
- ✓ **B. Yield to traffic already in it**
- C. Go through very fast
- D. Back up if needed

Answer: B — Yield to vehicles already in the roundabout, then enter a gap. (§2.4)

107. An angry, aggressive driver behind you is best handled by:

- A. Brake-checking them hard
- ✓ **B. Giving room and not engaging**
- C. Speeding up to race them
- D. Blocking them on purpose

Answer: B — Don't engage; give them room and let them pass. (§2.8)

108. Standing water on the road can:

- A. Improve your grip
- ✓ **B. Cause hydroplaning — slow down**
- C. Cool the engine down
- D. Do nothing at all

Answer: B — Water between the tire and road causes hydroplaning; reduce your speed. (§2.6)

109. Which statement about speed and stopping is TRUE?

- A. Heavier loads stop faster
- ✓ **B. More speed = a much longer stop**
- C. Wet roads stop you faster
- D. ABS shortens stops a lot

Answer: B — Stopping distance grows quickly with speed; going faster needs much more room. (§2.6)

110. Which of these is NOT a cause of skidding?

- A. Driving way too fast
- B. Hard panic braking
- ✓ **C. Smooth, gentle steering**
- D. Heavy over-acceleration

Answer: C — Smooth inputs prevent skids; speed, hard braking, and over-acceleration cause them. (§2.7)

111. Which statement about night driving is TRUE?

- A. Drive faster to finish sooner
- ✓ **B. Use low beams when meeting traffic**
- C. High beams cut through fog
- D. You see better in the dark

Answer: B — Switch to low beams for oncoming traffic so you don't blind the other driver. (§2.11)

112. Which is NOT a proper use of four-way flashers?

- A. Warning of a breakdown
- ✓ **B. Signaling a normal turn**
- C. Marking a slow vehicle
- D. Warning when you're stopped

Answer: B — Flashers warn of trouble or a slow/stopped vehicle — not normal turns. (§2.4)

113. Following-distance rule (1 second per 10 ft of length, +1 over 40 mph): a 40-ft vehicle at 45 mph needs:

- A. 4 seconds
- ✓ B. 5 seconds
- C. 6 seconds
- D. 3 seconds

Answer: B — $40 \div 10 = 4$ seconds, plus 1 because you are over 40 mph = 5 seconds. (\$2.6)

114. Following distance: a 50-ft rig traveling at 35 mph needs:

- A. 4 seconds
- ✓ B. 5 seconds
- C. 6 seconds
- D. 7 seconds

Answer: B — $50 \div 10 = 5$ seconds; no extra second because you are under 40 mph. (\$2.6)

115. Following distance: a 60-ft combination at 55 mph needs:

- A. 6 seconds
- ✓ B. 7 seconds
- C. 8 seconds
- D. 5 seconds

Answer: B — $60 \div 10 = 6$ seconds, plus 1 over 40 mph = 7 seconds. (\$2.6)

116. Following distance: a 30-ft truck at 30 mph needs:

- A. 2 seconds
- ✓ B. 3 seconds
- C. 4 seconds
- D. 5 seconds

Answer: B — $30 \div 10 = 3$ seconds; under 40 mph so no extra second. (\$2.6)

117. Following distance: a 70-ft doubles set at 50 mph needs:

- A. 7 seconds
- ✓ B. 8 seconds
- C. 9 seconds
- D. 6 seconds

Answer: B — $70 \div 10 = 7$ seconds, plus 1 over 40 mph = 8 seconds. (\$2.6)

118. Following distance: a 20-ft straight truck at 25 mph needs:

- A. 1 second
- ✓ B. 2 seconds
- C. 3 seconds
- D. 4 seconds

Answer: B — $20 \div 10 = 2$ seconds; under 40 mph so no extra second. (\$2.6)

119. Following distance: an 80-ft triples set at 60 mph needs:

- A. 8 seconds
- ✓ B. 9 seconds
- C. 10 seconds
- D. 7 seconds

Answer: B — $80 \div 10 = 8$ seconds, plus 1 over 40 mph = 9 seconds. (\$2.6)

120. Following distance: a 50-ft rig at 45 mph needs:

- A. 5 seconds
- ✓ B. 6 seconds
- C. 7 seconds
- D. 4 seconds

Answer: B — $50 \div 10 = 5$ seconds, plus 1 over 40 mph = 6 seconds. (\$2.6)

121. Following distance: a 60-ft rig at 35 mph needs:

- A. 5 seconds
- ✓ B. 6 seconds
- C. 7 seconds
- D. 8 seconds

Answer: B — $60 \div 10 = 6$ seconds; under 40 mph so no extra second. (\$2.6)

122. Which of these can cause a vehicle to skid?

- A. Driving too fast for conditions
- B. Braking too hard in a panic
- C. Accelerating too hard
- ✓ D. All of the above

Answer: D — Excess speed, hard panic braking, and over-acceleration can each cause a skid. (\$2.7)

123. You should slow down when:

- A. The road surface is wet
- B. You are entering a curve
- C. Visibility is poor
- ✓ D. All of the above

Answer: D — Wet roads, curves, and poor visibility all call for a lower speed. (\$2.6)

124. Your emergency equipment should include:

- A. Three red warning triangles
- B. Spare electrical fuses
- C. A working fire extinguisher
- ✓ D. All of the above

Answer: D — You must carry warning triangles, spare fuses, and a fire extinguisher. (\$2.1)

125. Which is an acceptable reason to drive over the posted speed limit?

- A. You are running late
- B. Traffic is moving faster
- C. The road looks empty
- ✓ D. None of the above

Answer: D — Nothing justifies driving over the posted speed limit. (\$2.6)

126. Which is a safe place to pass another vehicle?

- A. On a sharp curve
- B. Near the top of a hill
- C. At a busy intersection
- ✓ D. None of the above

Answer: D — None of these are safe places to pass — you cannot see far enough ahead. (\$2.4)

127. Which is a good reason to skip the pre-trip inspection?

- A. You are in a hurry
- B. You drove it yesterday
- C. It looks fine to you
- ✓ **D. None of the above**

Answer: D — There is never a good reason to skip the pre-trip inspection. (§2.1)

128. At night on a dark two-lane road, an oncoming car keeps its high beams on. What is the safest response?

- A. Flash your own high beams at them repeatedly so they finally dim their lights.
- ✓ **B. Look toward the right edge of your lane and slow down until the car has passed.**
- C. Turn on your own high beams so you can see out past the glare of their lights.
- D. Close your eyes briefly and steer straight ahead until the bright car goes by.

Answer: B — Looking to the right edge keeps you on course without being blinded. (§2.11)

129. You are descending a long, steep mountain grade with a heavy load. How should you control your speed?

- A. Hold the brake pedal down firmly the whole way to keep a low, steady speed.
- ✓ **B. Shift to a low gear and use light, steady braking so the brakes do not overheat.**
- C. Put the transmission in neutral and coast down to save fuel and reduce wear.
- D. Pump the brakes hard and fast the entire way down the long, steep grade.

Answer: B — A low gear holds your speed so light braking won't overheat the brakes. (§2.16)

130. A front tire blows out while you are at highway speed. What should you do first?

- A. Brake hard right away and steer sharply toward the right shoulder of the road.
- ✓ **B. Hold the steering wheel firmly, stay off the brake, and let the vehicle slow down.**
- C. Speed up briefly so you can pull away from the traffic that is close behind you.
- D. Take both hands off the wheel and let the vehicle find its own way to a stop.

Answer: B — Holding the wheel and staying off the brake keeps the vehicle straight. (§2.14)

131. You approach a railroad crossing with no gates and the warning lights begin to flash. What should you do?

- A. Speed up so that you can cross the tracks before any train is able to reach you.
- ✓ **B. Stop before the tracks and wait until the lights stop and it is safe to cross over.**
- C. Drive onto the tracks and stop there so you can look both ways for a coming train.
- D. Shift into a lower gear while you are on the tracks and then drive on across them.

Answer: B — Flashing lights mean stop and wait until it is safe. (§2.15)

132. Heavy rain is falling, your steering feels light, and the truck starts to hydroplane. What should you do?

- A. Brake firmly and steer hard to force the tires back down onto the road surface.
- ✓ **B. Ease off the accelerator, keep the wheel straight, and let the truck slow down.**
- C. Press the accelerator harder to push the tires down through the standing water.
- D. Turn the steering wheel quickly back and forth to shake the water off the tires.

Answer: B — Easing off the gas lets the tires regain grip; don't brake hard. (§2.6)

133. You are merging onto a busy freeway from an on-ramp and the right lane is moving fast. What is best?

- A. Stop at the end of the ramp and wait for a complete gap with no cars at all.
- ✓ **B. Match your speed to traffic and merge smoothly into a safe gap in the lane.**
- C. Merge slowly at a low speed and make the faster traffic brake for your truck.
- D. Force your way into the lane and expect the other drivers to move over for you.

Answer: B — Matching speed lets you blend into a gap safely. (§2.7)

134. An aggressive driver is tailgating you closely and flashing their lights. What should you do?

- A. Brake suddenly to warn the tailgater that they need to back off and give space.
- ✓ **B. Increase your following distance ahead and move over to let the driver go past.**
- C. Speed up well above the limit so the aggressive driver cannot stay behind you.
- D. Hold your position in the lane and block the driver from getting around you.

Answer: B — Give them room and let them pass; don't engage. (§2.8)

135. You smell something burning and see smoke coming from the rear of your trailer. What should you do?

- A. Keep driving to the next exit and hope the smoke clears on its own before long.
- ✓ **B. Pull off the road away from others, shut off the engine, and check the problem.**
- C. Open the trailer doors right away while the engine and the wheels are still moving.
- D. Pour the water from your drink bottle on the tires without stopping the truck.

Answer: B — Pull off, shut down, and investigate before it gets worse. (§2.14)

136. The road ahead is covered with thick fog that hides the lane lines. What is the safest choice?

- A. Turn on your high beams so the bright light is able to cut through the thick fog.
- ✓ **B. Slow down, use low beams, and pull off the road if you cannot see well enough.**
- C. Keep your normal speed and just follow the tail lights of the vehicle in front.
- D. Speed up to get out of the foggy stretch as quickly as your truck can manage.

Answer: B — Low beams and lower speed are safest; pull off if needed. (§2.11)

137. You must back your truck into a tight loading dock and you have no one to help. What should you do?

- A. Back up quickly while the area is clear so you finish before anyone arrives.
- ✓ **B. Get out and walk the path first, then back slowly while using your mirrors.**
- C. Rely only on your mirrors and back at a steady speed without getting out first.
- D. Ask a passing bystander to stand right behind the trailer to watch as you reverse.

Answer: B — Get out and look, then back slowly with your mirrors. (§2.13)

1. An air brake system is really how many separate systems?

- A. One
- B. Two
- ✓ C. Three
- D. Four

Answer: C — Three: service, parking, and emergency. (§5.1 Parts)

2. The governor stops the compressor (cut-out) at about:

- A. 100 psi
- B. 110 psi
- ✓ C. 125 psi
- D. 150 psi

Answer: C — Cut-out is usually around 125 psi (cut-in around 100 psi). (§5.1 Governor)

3. The governor lets the compressor start again (cut-in) at about:

- A. 60 psi
- ✓ B. 100 psi
- C. 140 psi
- D. 150 psi

Answer: B — Cut-in is about 100 psi. (§5.1 Governor)

4. The safety relief valve usually opens at:

- A. 100 psi
- B. 125 psi
- ✓ C. 150 psi
- D. 200 psi

Answer: C — It opens at about 150 psi to protect the system. (§5.1 Reservoirs)

5. The low-air warning must come on before pressure falls below:

- A. 40 psi
- B. 55 psi
- ✓ C. 60 psi
- D. 80 psi

Answer: C — Before 60 psi (Texas handbook). (§5.1 Warning)

6. Spring (emergency) brakes apply automatically at about:

- A. 5–10 psi
- ✓ B. 20–45 psi
- C. 60 psi
- D. 100 psi

Answer: B — They come on at about 20–45 psi. (§5.1 Spring Brakes)

7. The brake pedal in an air system is also called the:

- A. Governor
- ✓ B. Foot (treadle) valve
- C. Slack adjuster
- D. Glad hand

Answer: B — The foot/treadle valve sends air to the brakes. (§5.1 Parts)

8. Air tanks must be drained to remove:

- A. Air
- ✓ **B. Water and oil**
- C. Brake fluid
- D. Coolant

Answer: B — Compressed air collects water and some oil. (§5.1 Tanks)

9. What does an air dryer do?

- A. Raises pressure
- ✓ **B. Removes moisture**
- C. Cools the brakes
- D. Warns of low air

Answer: B — It removes water and contaminants from the air. (§5.1 Parts)

10. The supply pressure gauge shows:

- ✓ **A. Tank pressure**
- B. Pressure applied to brakes
- C. Engine oil pressure
- D. Tire pressure

Answer: A — It shows how much air is in the tanks. (§5.1 Gauges)

11. The application pressure gauge shows:

- A. The air tank pressure
- ✓ **B. Pressure applied to the brakes**
- C. The engine rpm reading
- D. The tire inflation pressure

Answer: B — It shows how much pressure you are applying. (§5.1 Gauges)

12. Pressing the brakes twists the S-cam, which:

- A. Drains the tanks
- ✓ **B. Spreads the brake shoes**
- C. Closes the governor
- D. Raises the trailer

Answer: B — The S-cam forces the shoes against the drum. (§5.1 Parts)

13. A manual slack adjuster should move no more than about:

- ✓ **A. 1 inch**
- B. 3 inches
- C. 5 inches
- D. It can move freely

Answer: A — More than about an inch means brakes are out of adjustment. (§5.3 Inspection)

14. Air brake lag is about:

- A. 1/10 second
- ✓ **B. 1/2 second**
- C. 2 seconds
- D. 5 seconds

Answer: B — About half a second for air to act after the pedal. (§5.4 Using)

15. Air-brake stopping distance adds which extra part?

- A. Perception
- B. Reaction
- ✓ C. Brake lag
- D. Nothing extra

Answer: C — Perception + reaction + brake lag + braking. (§5.4 Using)

16. Engine off, brakes released, single vehicle: air loss should be under:

- ✓ A. 2 psi/min
- B. 3 psi/min
- C. 4 psi/min
- D. 6 psi/min

Answer: A — Single under 2 psi/min; combination under 3. (§5.3 Inspection)

17. Engine off, brakes released, combination: air loss should be under:

- A. 2 psi/min
- ✓ B. 3 psi/min
- C. 4 psi/min
- D. 6 psi/min

Answer: B — Combination under 3 psi/min released. (§5.3 Inspection)

18. With the brakes applied, a single vehicle should lose under:

- A. 2 psi/min
- ✓ B. 3 psi/min
- C. 4 psi/min
- D. 6 psi/min

Answer: B — Applied: single under 3, combination under 4. (§5.3 Inspection)

19. In a dual system, pressure should build 85 to 100 psi within:

- A. 10 seconds
- ✓ B. 45 seconds
- C. 3 minutes
- D. 5 minutes

Answer: B — Within 45 seconds at operating rpm. (§5.3 Inspection)

20. To test the low-air warning, you:

- A. Pump up the pressure
- ✓ B. Fan it down until it lights
- C. Drain all the air fast
- D. Turn off the lights

Answer: B — Fan the brakes down; the warning must light by 60 psi. (§5.3 Inspection)

21. To test the service brakes, you:

- A. Brake hard from highway speed
- ✓ B. Roll at 5 mph and brake firmly
- C. Only test the parking brake
- D. Pump ten times

Answer: B — At 5 mph, brake firmly; it should stop straight, no pulling. (§5.3 Inspection)

22. A brake drum is unsafe if a crack is longer than:

- A. A hairline
- ✓ **B. Half the friction width**
- C. Any length
- D. Drums never crack

Answer: B — Cracks over half the friction width are out of service. (§5.3 Inspection)

23. Brake linings are defective if they are:

- A. Thick and dry
- ✓ **B. Oil-soaked or too thin**
- C. Newly replaced
- D. Properly seated

Answer: B — Loose, oil-soaked, or dangerously thin linings are bad. (§5.3 Inspection)

24. On a long downgrade, the brakes should be:

- A. The main speed control
- ✓ **B. A supplement to engine braking**
- C. Held down lightly
- D. Pumped constantly

Answer: B — Engine braking in a low gear is primary; brakes supplement. (§5.4 Downgrades)

25. In the snub-braking method, you:

- A. Hold light pressure all the way
- ✓ **B. Brake firmly, release, and repeat**
- C. Pump rapidly
- D. Coast in neutral

Answer: B — Brake to about 5 mph below your safe speed, release, repeat. (§5.4 Downgrades)

26. Fanning (pumping) the brakes on a long grade:

- A. Saves the brakes
- ✓ **B. Wastes air and can lose pressure**
- C. Builds pressure faster
- D. Cools the engine

Answer: B — Air can drop until the brakes fail; use a low gear instead. (§5.4 Using)

27. You should NOT set the parking brakes when:

- A. Parked overnight
- ✓ **B. The brakes are very hot**
- C. On level ground
- D. After a short trip

Answer: B — Hot brakes can be damaged or freeze; chock the wheels. (§5.4 Parking)

28. If the low-air warning comes on while driving, you should:

- A. Keep going to the next town
- ✓ **B. Stop and park as soon as safe**
- C. Turn off the warning
- D. Speed up to build air

Answer: B — Loss of air can apply the spring brakes suddenly. (§5.4 Using)

29. With ABS, you make an emergency stop by:

- A. Pumping the pedal
- ✓ **B. Braking hard and holding**
- C. Using only the trailer brakes
- D. Releasing at each skid

Answer: B — Brake fully and keep steering; ABS prevents lockup. (§5.4 ABS)

30. Without ABS, the best hard-stop method is:

- A. Locking the wheels
- ✓ **B. Controlled or stab braking**
- C. Pressing to the floor
- D. Pumping the steering

Answer: B — Keep the wheels from staying locked so you can steer. (§5.4 Using)

31. In stab braking, you reapply the brakes:

- A. Almost right away
- ✓ **B. After the wheels roll again**
- C. After about 10 seconds
- D. Never reapply them

Answer: B — Release when locked; reapply once rolling (up to 1 sec). (§5.4 Using)

32. If your ABS malfunction lamp stays on, you:

- A. Have no brakes
- ✓ **B. Have normal brakes; fix the ABS**
- C. Must stop the engine
- D. Should pump the brakes

Answer: B — You lose only the anti-lock function; service it soon. (§5.1 ABS)

33. ABS is required on truck tractors built on or after:

- A. 1995
- ✓ **B. 1997**
- C. 1998
- D. 2000

Answer: B — Tractors 3/1/1997; other vehicles and trailers 3/1/1998. (§5.1 ABS)

34. If one circuit of a dual system fails while driving:

- A. You lose all braking
- ✓ **B. The other still stops you**
- C. The engine stops
- D. Only the lights fail

Answer: B — The other circuit still brakes you; the warning comes on. (§5.2 Dual)

35. Why drain the air tanks (or use automatic drains)?

- A. To raise pressure
- ✓ **B. To remove water that can freeze**
- C. To clean the linings
- D. To reset the governor

Answer: B — Water can freeze the brakes in cold weather. (§5.1 Tanks)

36. Before driving, let the air system charge to:

- A. A low pressure of about 50 psi
- ✓ **B. The normal range (about 125 psi)**
- C. Exactly 150 psi every time
- D. Almost any pressure level

Answer: B — Charge to the normal operating range before moving. (§5.3 Inspection)

37. Why check the air-compressor drive belt (if belt-driven)?

- A. It quietly runs the cab radio
- ✓ **B. A loose belt may not build enough air**
- C. It helps cool the wheel brakes
- D. It charges the trailer battery

Answer: B — A slipping belt means the compressor can't keep up. (§5.3 Inspection)

38. A full pre-trip air-brake check includes which test?

- A. Low-air warning
- B. Build-up time
- C. Leak-down rate
- ✓ **D. All of the above**

Answer: D — All of these are part of the air-brake check. (§5.3 Inspection)

39. Which is NOT a way to test air brakes?

- A. Leak-down test
- B. Build-up time
- ✓ **C. Draining the radiator**
- D. Low-air warning

Answer: C — The radiator is cooling, not the air-brake system. (§5.3 Inspection)

40. Which is NOT true of ABS?

- A. It prevents wheel lockup
- B. It helps you steer
- ✓ **C. It always shortens the stop**
- D. It works in hard stops

Answer: C — ABS does not necessarily shorten the stopping distance. (§5.1 ABS)

41. Water and oil collect in the air tanks, so the tanks must be:

- A. Painted over
- ✓ **B. Drained regularly**
- C. Removed entirely
- D. Filled with oil

Answer: B — Drain the tanks (manually or automatically) to remove water and oil that harm the system. (§5.1)

42. The air compressor is driven by:

- A. The trailer
- ✓ **B. The engine**
- C. The driver
- D. Plain gravity

Answer: B — The engine drives the air compressor by belt or directly. (§5.1)

43. An air dryer's job is to:

- A. Cool down the cab
- ✓ **B. Remove moisture from the air**
- C. Add oil to the air
- D. Inflate the tires

Answer: B — The air dryer removes water and some oil before air reaches the tanks. (§5.1)

44. Most heavy vehicles use what kind of foundation brakes?

- A. Small bicycle brakes
- ✓ **B. S-cam drum brakes**
- C. A hand brake lever
- D. No brakes at all

Answer: B — S-cam drum brakes are the most common type on air-braked vehicles. (§5.1)

45. When you press the brake pedal harder, the brakes:

- A. Get weaker
- ✓ **B. Get more air and force**
- C. Release fully
- D. Switch off

Answer: B — The foot (treadle) valve sends more air pressure for more braking force. (§5.1)

46. Brake lag is the time it takes for:

- A. The engine to start
- ✓ **B. Air to apply the brakes**
- C. The tires to warm up
- D. The lights to flash

Answer: B — Air brakes have about a half-second lag before they take hold. (§5.2)

47. With air brakes, total stopping distance also includes:

- A. The tire size
- ✓ **B. Brake lag distance**
- C. The fuel level
- D. The mirror angle

Answer: B — Add brake-lag distance to perception, reaction, and braking distance. (§5.2)

48. To test the service brakes, you should:

- A. Honk the horn twice
- ✓ **B. Roll at 5 mph and brake**
- C. Rev the engine hard
- D. Open the engine hood

Answer: B — Move slowly, apply the brakes, and feel the vehicle stop promptly with no pull. (§5.3)

49. Slack adjusters control:

- A. The cab radio
- ✓ **B. Brake pushrod travel**
- C. The tire pressure
- D. The air horn

Answer: B — Slack adjusters set pushrod travel; too much travel means the brakes need adjustment. (§5.3)

50. A drain valve that empties the tank by itself is called:

- A. A manual drain valve
- ✓ **B. An automatic drain valve**
- C. A relay valve
- D. A glad hand

Answer: B — Automatic drain valves expel water and oil without manual draining. (§5.1)

51. A dual air brake system has:

- A. A single air tank
- ✓ **B. Two separate air systems**
- C. No tanks at all
- D. One shared line

Answer: B — Dual systems use separate primary and secondary systems for safety. (§5.1)

52. If one system in a dual air brake setup fails, the other:

- A. Also fails completely
- ✓ **B. Still works to stop the vehicle**
- C. Suddenly speeds up
- D. Locks on forever

Answer: B — The remaining system can still stop the vehicle, though stopping distance is longer. (§5.1)

53. Spring brakes are held in the released position by:

- A. Plain gravity
- ✓ **B. Air pressure**
- C. A strong rope
- D. The cab radio

Answer: B — Air pressure holds the powerful springs back; if air is lost, the springs apply the brakes. (§5.1)

54. Because spring-brake springs are so strong, you should:

- A. Release them by hand often
- ✓ **B. Not release them unless trained**
- C. Paint them bright
- D. Remove them fully

Answer: B — Caging spring brakes is dangerous; only trained personnel should do it. (§5.1)

55. To test that the parking (spring) brakes hold, you should:

- A. Rev the engine loudly
- ✓ **B. Gently pull forward against them**
- C. Honk the horn twice
- D. Open the cab door

Answer: B — With the parking brake set, gently tug against it to confirm it holds. (§5.3)

56. On a long downgrade with air brakes, you should:

- A. Fan the brakes on and off
- ✓ **B. Use low gear and steady braking**
- C. Hold the brakes hard throughout
- D. Coast down in neutral

Answer: B — Pick a safe speed, use engine braking in a low gear, and apply the brakes steadily. (§5.3)

57. The brake that the foot pedal controls is the:

- A. The parking brake
- ✓ **B. The service brake**
- C. The emergency brake
- D. The trailer hand valve

Answer: B — The foot pedal (treadle valve) operates the service brakes. (§5.1)

58. Brake drums or discs are dangerous when they are:

- A. Clean and cool
- ✓ **B. Cracked or badly worn**
- C. Freshly painted
- D. Cool to the touch

Answer: B — Cracked drums/discs or worn linings can fail and must be inspected. (§5.3)

59. For an air leak that keeps dropping pressure, you should:

- A. Keep on driving anyway
- ✓ **B. Stop and get it repaired**
- C. Drive faster to a shop
- D. Just ignore the leak

Answer: B — A continuing air leak is dangerous; stop safely and repair before driving. (§5.3)

60. The yellow ABS malfunction lamp staying on means:

- A. The brakes are off
- ✓ **B. ABS may not be working**
- C. You must stop at once
- D. The cab radio is on

Answer: B — A lit ABS lamp warns the antilock system may not function; normal brakes still work. (§5.3)

61. Air brakes keep working as long as there is:

- A. Plenty of fuel
- ✓ **B. Enough air pressure**
- C. Bright sunlight
- D. A second passenger

Answer: B — The system needs adequate air pressure to apply and release the brakes. (§5.1)

62. After a full charge, building air from 85 to 100 psi should take:

- A. Several long minutes
- ✓ **B. A short time, in seconds**
- C. A full hour
- D. No time, instantly

Answer: B — A healthy compressor builds pressure quickly; slow build means a problem. (§5.3)

63. Brake linings that are too thin must be:

- A. Painted over
- ✓ **B. Replaced with new ones**
- C. Lightly oiled
- D. Left and ignored

Answer: B — Worn linings reduce braking and must be replaced. (§5.3)

64. Pressing and releasing the brakes many times on a hill ('fanning') can:

- A. Help cool the brakes
- ✓ **B. Use air faster than it builds**
- C. Charge the trailer tank
- D. Save a little fuel

Answer: B — Fanning air brakes can drop air pressure faster than the compressor rebuilds it. (§5.3)

65. Compared with hydraulic brakes, air brakes transmit force using:

- A. Brake fluid under pressure
- ✓ **B. Compressed air**
- C. A steel cable
- D. Electric current

Answer: B — Air brakes use compressed air, not hydraulic fluid, to apply the brakes. (§5.1)

66. A safety advantage of air brakes over hydraulic brakes is that:

- A. They never need draining
- ✓ **B. Spring brakes apply if air is lost**
- C. They have no warning light
- D. They stop in a shorter distance

Answer: B — If air pressure is lost, the spring (emergency) brakes apply automatically. (§5.1)

67. Which statement about spring brakes is TRUE?

- A. They need air to apply
- ✓ **B. They apply when air is lost**
- C. They are the service brakes
- D. They release without air

Answer: B — Spring brakes apply when air pressure is lost; air holds them released. (§5.1)

68. The tractor protection valve closes automatically when air pressure drops to about:

- A. 60–80 psi
- ✓ **B. 20–45 psi**
- C. 100–125 psi
- D. 5–10 psi

Answer: B — It closes between about 20 and 45 psi to keep air in the tractor. (§6.2)

69. The red, eight-sided knob in the cab controls the:

- ✓ **A. Trailer air supply valve**
- B. Cab heater fan speed
- C. Windshield wiper motor
- D. Headlight beam switch

Answer: A — The red octagonal knob is the trailer air supply (and trailer parking) valve. (§6.2)

70. The control that applies the parking (spring) brakes is usually a:

- A. Round blue button
- ✓ **B. Yellow diamond-shaped knob**
- C. Red round knob
- D. Green square lever

Answer: B — The parking brake control is a yellow, diamond-shaped knob. (§5.3)

71. A one-way check valve between the compressor and the first tank:

- A. Drains water from the tanks
- ✓ **B. Keeps air from flowing back out**
- C. Warns you of low air pressure
- D. Cools the compressed air

Answer: B — The check valve keeps tank air from leaking back if the compressor loses pressure. (§5.1)

72. An alcohol evaporator in the air system helps to:

- A. Boost engine power
- ✓ **B. Reduce ice in cold weather**
- C. Clean the windshield
- D. Charge the battery

Answer: B — Alcohol reduces the risk of ice in the air system and valves in cold weather. (§5.1)

73. Which is NOT a part of an S-cam foundation brake?

- A. Brake shoes and linings
- ✓ **B. A hydraulic master cylinder**
- C. The brake drum
- D. The slack adjuster

Answer: B — S-cam air brakes use shoes, a drum, an S-cam, and a slack adjuster — not a hydraulic master cylinder. (§5.1)

74. On steep grades, a modulating control valve lets you:

- A. Turn off the ABS
- ✓ **B. Apply spring brakes gradually**
- C. Skip the parking brake
- D. Raise the governor cut-out

Answer: B — The modulating valve applies the spring brakes gradually if the service brakes fail. (§5.3)

75. Unlike a hydraulic-brake leak, a small air-brake leak:

- A. Stops the brakes at once
- ✓ **B. Still lets you stop while air remains**
- C. Gives you no warning
- D. Cannot be detected

Answer: B — Air brakes keep working while pressure remains and a warning alerts you — unlike instant hydraulic failure. (§5.1)

76. A complete air-brake walkaround should check the:

- A. Low-air warning
- B. Spring (parking) brakes
- C. Service brakes
- ✓ **D. All of the above**

Answer: D — Test the low-air warning, the parking/spring brakes, and the service brakes. (§5.3)

77. Unlike hydraulic-brake vehicles, vehicles with air brakes legally require:

- A. No special license
- ✓ **B. An air-brake (no-restriction) test**
- C. Only a Class C license
- D. A motorcycle endorsement

Answer: B — You must pass the air-brake test or you get an air-brake restriction on your license. (§5.1)

78. Which statement about ABS is TRUE?

- A. It shortens your stopping distance a lot
- ✓ **B. It lets you steer while braking hard**
- C. It replaces the service brakes
- D. It works only when parked

Answer: B — ABS keeps the wheels from locking so you can steer during hard braking; it doesn't necessarily shorten stops. (§5.3)

1. As a long vehicle turns, the rear wheels follow:

- A. The same path as the front
- ✓ **B. A path inside the front wheels**
- C. A wider path than the front
- D. No predictable path

Answer: B — Off-tracking: the rear wheels cut inside the front path. (§6.1 Driving)

2. To keep the trailer off the curb on a right turn, you:

- A. Swing wide left first
- ✓ **B. Turn wide as you finish the turn**
- C. Turn sharply early
- D. Speed through it

Answer: B — Keep the rear near the curb; turn wide as you complete the turn. (§6.1 Driving)

3. How many air lines connect the tractor and trailer?

- A. One
- ✓ **B. Two**
- C. Three
- D. Four

Answer: B — Two: the service line and the emergency (supply) line. (§6.2 Air Brakes)

4. The glad-hand color for the emergency (supply) line is:

- A. Blue
- ✓ **B. Red**
- C. Green
- D. Yellow

Answer: B — Red = emergency; blue = service. (§6.2 Air Brakes)

5. The red, eight-sided knob in the cab controls the:

- A. Tractor parking brake
- ✓ **B. Trailer air supply**
- C. Trailer service brakes
- D. Headlights

Answer: B — It is the trailer air supply / emergency line. (§6.2 Air Brakes)

6. The tractor protection valve is there to:

- A. Inflate the tractor and trailer tires
- ✓ **B. Keep air in the tractor if the trailer breaks away**
- C. Raise and lower the landing gear
- D. Lock the fifth wheel onto the kingpin

Answer: B — It closes to preserve tractor air during a breakaway or leak. (§6.2 Air Brakes)

7. The trailer hand valve should be used:

- A. For parking
- ✓ **B. Only to test the trailer brakes**
- C. Instead of the foot brake
- D. On every downgrade

Answer: B — Using it to drive can cause a trailer skid. (§6.2 Air Brakes)

8. After coupling, the locking jaws must close around the kingpin's:

- A. Head (top)
- ✓ **B. Shank (neck)**
- C. Base plate
- D. Release arm

Answer: B — Jaws must close around the shank, not the head. (§6.4 Coupling)

9. How much gap should there be between the fifth-wheel halves?

- ✓ **A. None**
- B. About 1 inch
- C. About 2 inches
- D. A small gap is fine

Answer: A — No gap; a gap means the kingpin may not be locked. (§6.4 Coupling)

10. The tug test checks the coupling by:

- A. Gently tapping on the trailer
- ✓ **B. Pulling against locked trailer brakes**
- C. Checking all the trailer lights
- D. Listening for a faint click

Answer: B — Pull gently forward; the trailer should stay attached. (§6.4 Coupling)

11. Before driving, the landing gear should be:

- A. Left partway down
- ✓ **B. Fully raised, handle secured**
- C. Touching the road surface
- D. Removed and stored away

Answer: B — Fully up so it does not catch; secure the crank handle. (§6.5 Inspection)

12. To make a trailer go right while backing, first turn the wheel:

- A. Right
- ✓ **B. Left, then follow it**
- C. Straight
- D. You can't steer in reverse

Answer: B — Backing a trailer is opposite; turn left first, then follow. (§6.1 Driving)

13. Glad-hand seals should be:

- A. Removed for a tight fit
- ✓ **B. In good condition**
- C. Coated with oil
- D. Cross-connected

Answer: B — Worn seals leak air and reduce trailer braking. (§6.4 Coupling)

14. The two keys to preventing a rollover are low cargo and:

- A. High speed in turns
- ✓ **B. Slow speed in turns**
- C. Hard braking
- D. Quick lane changes

Answer: B — Keep cargo low and centered, and go slowly around turns. (§6.1 Rollover)

15. Compared with an empty one, a fully loaded rig is about:

- A. Half as likely to roll
- B. Just as likely to roll
- ✓ **C. 10 times more likely to roll**
- D. Unable to roll

Answer: C — A loaded rig has a higher center of gravity. (§6.1 Rollover)

16. A quick, hard steering move can 'crack the whip,' which means:

- A. The tractor cab spins out
- ✓ **B. The trailer whips and can flip**
- C. The service brakes fade out
- D. The diesel engine stalls

Answer: B — Rearward amplification; steer gently and smoothly. (§6.1 Driving)

17. If your trailer begins to skid, you should:

- A. Use the hand valve
- ✓ **B. Release the brakes**
- C. Brake harder
- D. Accelerate

Answer: B — Release the brakes so the trailer wheels grip again. (§6.1 Skids)

18. A tractor jackknife starts when the:

- A. Trailer wheels lock
- ✓ **B. Drive wheels skid**
- C. Steer tires wear
- D. Landing gear drops

Answer: B — A drive-wheel skid swings the tractor; ease off the brake. (§6.1 Skids)

19. A bobtail tractor (no trailer) usually:

- A. Stops much shorter
- ✓ **B. Takes longer to stop**
- C. Cannot skid
- D. Has the best traction

Answer: B — Little weight on the drive axle means poor traction. (§6.1 Driving)

20. Losing pressure in the emergency line causes:

- A. Nothing at all to happen
- ✓ **B. The trailer emergency brakes to apply**
- C. The trailer to speed right up
- D. The trailer lights to fail

Answer: B — A breakaway applies the trailer emergency brakes. (§6.2 Air Brakes)

21. The service line carries:

- ✓ **A. The brake-pedal signal**
- B. Air to inflate tires
- C. Trailer lighting
- D. Nothing while driving

Answer: A — It sends the signal from the brake pedal or hand valve. (§6.2 Air Brakes)

22. The red trailer-air knob pops out by itself at about:

- A. 55-60 psi
- ✓ **B. 20-45 psi**
- C. 5-10 psi
- D. 100 psi

Answer: B — At 20-45 psi the tractor protection valve closes. (§6.2 Air Brakes)

23. If the glad hands are crossed, you may have:

- A. Brighter lights
- ✓ **B. No trailer brakes**
- C. A smoother ride
- D. Better fuel use

Answer: B — Crossed lines send air to the wrong place. (§6.4 Coupling)

24. You position the tractor for coupling by:

- A. Backing in at an angle
- ✓ **B. Lining up directly in front**
- C. Pulling forward over it
- D. Approaching from the side

Answer: B — Never back under at an angle; line up squarely. (§6.4 Coupling)

25. Before backing under, the trailer should be:

- A. Resting on the ground
- ✓ **B. Low enough to be raised slightly**
- C. Higher than the fifth wheel
- D. At any height

Answer: B — The tractor should raise it slightly when backing under. (§6.4 Coupling)

26. The fifth-wheel release arm should be:

- A. Pulled fully open
- ✓ **B. Locked, safety latch closed**
- C. Removed completely
- D. Loose and rattling

Answer: B — Engaged/locked with the safety latch over it. (§6.5 Inspection)

27. A sliding fifth wheel must be:

- A. As far forward as possible
- ✓ **B. Locked with pins engaged**
- C. Left loose
- D. Set only by weight

Answer: B — Locked in place; an unlocked slider is dangerous. (§6.5 Inspection)

28. A sliding fifth wheel set too far forward:

- A. Improves the ride
- ✓ **B. Overloads the steer axle**
- C. Lightens the steer axle
- D. Has no effect

Answer: B — It puts too much weight on the steer axle and reduces clearance. (§6.5 Inspection)

29. Air and electrical lines should be:

- A. Left dragging for slack
- ✓ **B. Secured and not dragging**
- C. Coiled very tightly
- D. Disconnected for turns

Answer: B — Dragging lines can be damaged or torn off. (§6.5 Inspection)

30. Mud flaps (splash guards) must be:

- A. Removed for fuel economy
- ✓ **B. Present and secured**
- C. Dragging on the road
- D. Made of metal

Answer: B — They reduce spray onto following vehicles. (§6.5 Inspection)

31. When uncoupling, before pulling out you should:

- A. Raise the landing gear up
- ✓ **B. Lower the landing gear to support the trailer**
- C. Release the trailer parking brakes
- D. Drive forward quickly away

Answer: B — Lower the landing gear, disconnect lines, then unlock. (§6.4 Coupling)

32. The trailer's ABS malfunction lamp is usually:

- A. Inside the cab
- ✓ **B. Yellow, on the left side**
- C. On the kingpin
- D. Not present

Answer: B — If it stays on, the trailer ABS is not working. (§6.3 ABS)

33. To avoid a hazard in a combination, it is usually best to:

- A. Brake hard and steer
- ✓ **B. Steer smoothly, then back**
- C. Lock the brakes
- D. Use the hand valve

Answer: B — Countersteer smoothly; hard braking can jackknife. (§6.1 Driving)

34. A correct coupling check includes:

- A. No gap at the fifth wheel
- B. Jaws around the kingpin
- C. A successful tug test
- ✓ **D. All of the above**

Answer: D — All three confirm a safe coupling. (§6.4 Coupling)

35. Which is NOT a coupling step?

- A. Line up the tractor
- B. Back under and lock
- ✓ **C. Drain the air tanks**
- D. Connect the air lines

Answer: C — Draining the tanks is not part of coupling. (§6.4 Coupling)

36. Your low trailer is stuck on a railroad crossing. You should:

- A. Try to rock it free
- ✓ **B. Get out and call the posted emergency number**
- C. Unhook the trailer on the tracks
- D. Sit and wait inside the cab

Answer: B — Leave the vehicle and call using the DOT crossing number. (§6.1 Railroad)

37. A combination vehicle is:

- A. A single large city bus
- ✓ **B. A tractor pulling one or more trailers**
- C. A small pickup truck only
- D. A two-wheeled motorcycle

Answer: B — A combination is a power unit (tractor) coupled to one or more trailers. (§6.1)

38. The trailer's kingpin locks into:

- A. The rear bumper
- ✓ **B. The fifth wheel's jaws**
- C. A mud flap
- D. The tail light

Answer: B — The kingpin drops into the fifth wheel and the locking jaws close around it. (§6.2)

39. The fifth wheel should be kept:

- A. Dry and rusty
- ✓ **B. Greased (lubricated)**
- C. Brightly painted
- D. Loose and worn

Answer: B — Keep the fifth wheel properly greased so it pivots and to reduce wear. (§6.3)

40. The flat plate under the front of the trailer that rests on the fifth wheel is the:

- A. The front bumper
- ✓ **B. The apron**
- C. The engine hood
- D. The dashboard

Answer: B — The trailer apron rests flat on the fifth wheel; the kingpin extends down from it. (§6.2)

41. To confirm the locking jaws closed, you should:

- A. Tap all the tires
- ✓ **B. Look under with a flashlight**
- C. Honk the horn twice
- D. Check the cab radio

Answer: B — Look directly under the trailer with a light to see the jaws closed around the kingpin. (§6.2)

42. Before backing under a trailer, you set its height so the tractor will:

- A. Crush right down on it
- ✓ **B. Lift the trailer as it backs under**
- C. Completely miss the trailer
- D. Tip it over to one side

Answer: B — Set trailer height so the tractor lifts it a little as the fifth wheel slides under. (§6.2)

43. The supply (emergency) air line:

- A. Plays the cab radio
- ✓ **B. Charges the trailer air tanks**
- C. Opens the trailer doors
- D. Cools down the cab

Answer: B — The supply line sends air to fill the trailer's air tanks. (§6.2)

44. The trailer's spring (emergency) brakes come on when:

- A. The cab radio is on
- ✓ **B. The supply line loses air**
- C. You honk the horn
- D. The marker lights flash

Answer: B — Loss of air in the supply line lets the trailer's spring brakes apply. (§6.2)

45. A longer combination needs ___ following distance:

- A. Much less
- ✓ **B. More than usual**
- C. No extra
- D. Zero extra

Answer: B — Longer, heavier rigs take longer to stop and need more space. (§6.1)

46. Because the trailer off-tracks, you should start a turn:

- A. Earlier than a car would
- ✓ **B. A bit later so the trailer clears**
- C. Without using any signal
- D. At full open road speed

Answer: B — Trailer wheels cut inside the tractor's path, so begin the turn a little later and watch the trailer. (§6.1)

47. To park a combination safely, you should:

- A. Leave it parked only in gear
- ✓ **B. Set the brakes and chock the wheels**
- C. Leave the engine running idle
- D. Lower the trailer roof down

Answer: B — Apply the parking brakes; chock wheels on a grade or when uncoupling. (§6.3)

48. The trailer hand valve should NOT be used:

- A. For a quick brake test
- ✓ **B. To hold a parked trailer**
- C. On a steep ramp only
- D. On flat ground only

Answer: B — Don't use the hand valve to park — air can leak off and the trailer could roll. (§6.2)

49. Using only the trailer hand valve in a skid can cause:

- A. A smooth, gentle stop
- ✓ **B. A trailer skid or jackknife**
- C. A much faster trip
- D. A cooler engine

Answer: B — Braking only the trailer with the hand valve can make it skid; use the foot brake. (§6.2)

50. Compared with loaded trailers, empty trailers:

- A. Grip the road better
- ✓ **B. Bounce and skid more easily**
- C. Always stop faster
- D. Never roll over

Answer: B — Light or empty trailers have less traction and bounce; brake gently. (§6.1)

51. The electrical pigtail between tractor and trailer powers:

- A. The tractor engine
- ✓ **B. The trailer lights and ABS**
- C. The tractor tires
- D. The fifth wheel

Answer: B — The pigtail cord supplies power for the trailer's lights and antilock system. (§6.2)

52. You should inspect the fifth-wheel mounting for:

- A. A nice clean shiny look
- ✓ **B. Cracks and loose or missing bolts**
- C. Just exactly the right color
- D. A working cab radio

Answer: B — Check the fifth-wheel platform and mounting bolts for cracks or looseness. (§6.3)

53. A sliding fifth wheel lets you:

- A. Change its color
- ✓ **B. Shift weight between axles**
- C. Add extra seats
- D. Play loud music

Answer: B — Sliding it adjusts weight distribution over the tractor axles. (§6.2)

54. The trailer air tanks should be:

- A. Painted bright red
- ✓ **B. Drained of water and oil**
- C. Kept full of water
- D. Removed entirely

Answer: B — Drain the trailer tanks like the tractor's to remove water and oil. (§6.3)

55. After charging the trailer air, you should next:

- A. Completely ignore the brakes
- ✓ **B. Test that the trailer brakes work**
- C. Remove the air supply lines
- D. Lower the trailer down

Answer: B — After charging, test the trailer service and emergency brakes before the road. (§6.2)

56. A combination is taller than a car, so watch for:

- A. A very low fuel level
- ✓ **B. Overhead clearance (bridges, signs)**
- C. A loud blaring cab radio
- D. The cold winter weather

Answer: B — Check posted clearances and don't assume they fit; the rig may be too tall. (§6.1)

57. A trailer's marker, clearance, and tail lights must be:

- A. Switched off always
- ✓ **B. Working and the right colors**
- C. Painted over fully
- D. Removed from the trailer

Answer: B — Trailer lights must work and show the correct colors front and rear. (§6.3)

58. If the kingpin is not locked in the fifth wheel, the trailer can:

- A. Brake much better
- ✓ **B. Come loose from the tractor**
- C. Go a lot faster
- D. Save extra fuel

Answer: B — An unlocked kingpin can let the trailer separate — always check the jaws. (§6.2)

59. A loaded combination's stopping distance is:

- A. Shorter than a car's
- ✓ **B. Longer than a lighter vehicle's**
- C. Exactly zero feet
- D. Same as a small car's

Answer: B — Heavier combinations take more distance to stop; keep more space. (§6.1)

60. The walk-around of a coupled rig should include:

- A. Only the tractor cab area itself
- ✓ **B. Trailer tires, lights, brakes, connections**
- C. Just one side mirror glass
- D. Nothing extra is really needed

Answer: B — Inspect trailer tires, lights, brakes, the coupling, and the air/electrical lines. (§6.3)

61. You are making a tight right turn at an intersection with your combination. How should you make the turn?

- A. Swing wide to the left as you start so a car can squeeze up on your right side.
- ✓ **B. Keep the rear close to the curb and turn wide only as you complete the turn.**
- C. Turn sharply and early, letting the trailer wheels ride up over the curb corner.
- D. Move into the left lane first and make the entire turn from the far left lane.

Answer: B — Keep the rear near the curb and turn wide at the end so cars can't pass on the right. (§6.1)

62. While coupling, you have backed under the trailer. How do you confirm the fifth wheel is locked?

- A. Assume it locked if you heard a click and then drive away without any other check.
- ✓ **B. Do a tug test: with the trailer brakes locked, gently pull forward against the kingpin.**
- C. Shake the trailer by hand and watch the landing gear for any sign of movement.
- D. Look only at the outside of the fifth wheel and trust that the jaws have closed.

Answer: B — A tug test against the kingpin confirms the jaws have locked. (§6.3)

63. Your trailer starts to skid and swing out to the side (a trailer jackknife is beginning). What should you do?

- A. Brake harder with the trailer hand valve to drag the trailer back into line again.
- ✓ **B. Release the brakes to let the trailer wheels roll and regain grip, then steer gently.**
- C. Steer sharply in the opposite direction and hold the brakes down all the way.
- D. Speed up quickly so the trailer is pulled straight out behind the tractor again.

Answer: B — Release the brakes so the trailer wheels regain traction, then correct your steering. (§6.4)

64. You are driving an empty combination on a windy day. How does the empty rig behave?

- A. It grips the road better than a loaded one, so you can corner and brake harder.
- ✓ **B. It bounces and can skid or roll more easily, so use gentle braking and steering.**
- C. It handles exactly the same as a loaded rig, so no change in driving is needed.
- D. It is so heavy in front that the trailer cannot bounce or leave the road at all.

Answer: B — Empty rigs bounce and lose grip; drive gently. (§6.4)

65. You are about to uncouple the trailer. What should you do before pulling the tractor out?

- A. Pull out first and then lower the landing gear once the trailer is sitting on it.
- ✓ **B. Lower the landing gear, disconnect the lines, and unlock the fifth wheel first.**
- C. Leave the air lines connected so the trailer brakes stay on while you pull away.
- D. Release the trailer brakes so the trailer can roll freely as you drive forward.

Answer: B — Lower the gear, disconnect lines, and unlock the fifth wheel before pulling out. (§6.3)

66. On a right curve at speed, your loaded combination feels like it might tip. What reduces rollover risk most?

- A. Carry the load stacked as high as possible so the weight presses straight down.
- ✓ **B. Keep the cargo low and centered, and slow down well before entering the curve.**
- C. Speed up through the curve so you spend the least possible time leaning over.
- D. Brake hard in the middle of the curve to force the trailer back down flat.

Answer: B — Low, centered cargo plus slowing before the curve prevents rollovers. (§6.4)

67. After coupling you suspect the glad hands on the air lines may be crossed. What could happen?

- A. Crossed glad hands make the trailer brakes stronger, which is actually safer for you.
- ✓ **B. You could get no trailer brakes because the supply and service air are reversed.**
- C. Nothing happens at all; the glad hands work the same no matter how they connect.
- D. The electrical pigtail will spark and the marker lights will glow much brighter.

Answer: B — Crossed glad hands swap supply and service air and can leave you without trailer brakes. (§6.2)

68. You need to park your combination on a slight downhill grade. What should you do?

- A. Leave it in neutral with the parking brakes off so it is easy to move later on.
- ✓ **B. Set the parking brakes, chock the wheels, and turn the wheels toward the curb.**
- C. Rely on the service brakes by leaving your foot resting on the brake pedal there.
- D. Park across two spaces so the trailer is at an angle and cannot roll straight off.

Answer: B — Set the parking brakes, chock the wheels, and turn the wheels toward the curb. (§6.1)

69. Backing your trailer toward a dock, you want the trailer to go to your right. Which way do you first turn the wheel?

- A. Turn the steering wheel to the right, the same direction you want the trailer to go.
- ✓ **B. Turn the steering wheel to the left first, then follow the trailer and straighten out.**
- C. Keep the wheel perfectly straight and just push back until the trailer drifts to the right.
- D. Turn the wheel hard right and hold it there for the entire length of the backing.

Answer: B — To send the trailer right while backing, first turn the wheel left. (§6.5)

70. Your loaded low trailer gets stuck on a railroad crossing and a train is coming. What should you do?

- A. Stay in the cab and keep trying to rock the trailer free until the train has passed.
- ✓ **B. Get out, move far away from the tracks, and call for help from a safe distance away.**
- C. Stand beside the trailer and wave your arms so the train engineer is able to see you.
- D. Quickly unhook the trailer from the tractor and try to push it off all by yourself.

Answer: B — Get out, get well away from the tracks, and call for help. (§6.4)

1. What is the maximum legal width of a commercial vehicle or its load in Texas?

- A. 96 inches
- ✓ B. 102 inches
- C. 108 inches
- D. 120 inches

Answer: B — The maximum width, including the load, is 102 inches (8.5 ft); anything wider needs a permit. (§14 Size and Weight)

2. What is the maximum height of a vehicle and load on Texas highways?

- A. 13 ft
- B. 13 ft 6 in
- ✓ C. 14 ft
- D. 15 ft

Answer: C — Maximum height is 14 feet; the driver is responsible for clearing all bridges. (§14 Size and Weight)

3. The maximum gross weight (vehicle plus load) without a permit is:

- A. 72,000 lb
- B. 76,000 lb
- ✓ C. 80,000 lb
- D. 90,000 lb

Answer: C — The maximum gross weight is 80,000 pounds without an overweight permit. (§14 Size and Weight)

4. The slow-moving vehicle (SMV) emblem is for vehicles designed to go:

- A. 15 mph or less
- ✓ B. 25 mph or less
- C. 35 mph or less
- D. 45 mph or less

Answer: B — The orange triangle warns of vehicles built for 25 mph or less. (§14 Special Equipment)

5. On an 80-inch-wide truck, the front clearance lamps must be:

- ✓ A. Amber
- B. Red
- C. White
- D. Green

Answer: A — Front clearance lamps are amber; rear ones are red. (§14 Lighting)

6. The rear clearance lamps on a wide truck must be:

- A. Amber
- B. White
- ✓ C. Red
- D. Blue

Answer: C — Rear clearance lamps and reflectors are red. (§14 Lighting)

7. The two reflectors required on the rear of a CMV must be:

- A. Amber
- ✓ B. Red
- C. White
- D. Green

Answer: B — Rear reflectors are red. (§14 Lighting)

8. Tail lamps must show what color to the rear?

- A. White
- B. Amber
- ✓ C. Red
- D. Blue

Answer: C — Tail lamps show red to the rear. (§14 Lighting)

9. Headlamps on a commercial vehicle must show what color?

- A. Amber
- ✓ B. White
- C. Yellow
- D. Blue

Answer: B — Headlamps must show white light. (§14 Lighting)

10. A red flag marking a projecting load must be at least:

- A. 6 inches square
- B. 9 inches square
- ✓ C. 12 inches square
- D. 18 inches square

Answer: C — The red flag must be at least 12 inches square. (§14 Flags)

11. A load must be flagged when it extends past the rear by more than:

- A. 2 feet
- B. 3 feet
- ✓ C. 4 feet
- D. 6 feet

Answer: C — A red flag is required when the load extends more than 4 feet past the rear. (§14 Flags)

12. A load may not extend beyond the front of the vehicle by more than:

- ✓ A. 3 feet
- B. 4 feet
- C. 6 feet
- D. 10 feet

Answer: A — A load may not extend more than 3 feet past the front. (§14 Load Limits)

13. When towing with a chain, the connection must display a flag that is:

- A. Red
- ✓ B. White
- C. Amber
- D. Orange

Answer: B — A towing chain/rope/cable needs a white flag; red is for projecting loads. (§14 Towing)

14. The towing connection between two vehicles may not be longer than:

- A. 10 feet
- ✓ B. 15 feet
- C. 20 feet
- D. 25 feet

Answer: B — The connection may not exceed 15 feet (except a pole/rigid bar). (§14 Towing)

15. Trailer brakes on the rear axle are required over a gross weight of:

- A. 2,500 lb
- B. 3,000 lb
- ✓ C. 4,500 lb
- D. 10,000 lb

Answer: C — Brakes are required on trailers over 4,500 lb. (§14 Brakes)

16. After becoming a Texas resident, out-of-state plates are recognized for:

- A. 10 days
- B. 20 days
- ✓ C. 30 days
- D. 60 days

Answer: C — Out-of-state plates are good for 30 days after residency or employment. (§14 Registration)

17. A buyer's temporary cardboard tag is valid for:

- ✓ A. 20 days
- B. 30 days
- C. 45 days
- D. 60 days

Answer: A — A temporary buyer's tag is valid 20 days. (§14 Registration)

18. Mud flaps must reach to within what distance of the road?

- A. 4 inches
- B. 6 inches
- ✓ C. 8 inches
- D. 12 inches

Answer: C — Mud flaps must reach within 8 inches of the road. (§14 Equipment)

19. When passing a motorcycle, you must allow at least:

- A. 3 feet
- ✓ B. 6 feet
- C. 9 feet
- D. 12 feet

Answer: B — Allow at least 6 feet and change lanes to pass. (§14 Sharing the Road)

20. A single vehicle (not a truck-tractor) may not be longer than:

- A. 40 feet
- ✓ B. 45 feet
- C. 53 feet
- D. 65 feet

Answer: B — A single vehicle is limited to 45 feet. (§14 Size and Weight)

21. The maximum number of vehicles allowed in one combination is:

- A. 2
- ✓ B. 3
- C. 4
- D. 5

Answer: B — No more than three vehicles may be combined. (§14 Size and Weight)

22. Tail lamps must be plainly visible from the rear at:

- A. 300 ft
- B. 500 ft
- C. 750 ft
- ✓ **D. 1,000 ft**

Answer: D — Tail lamps must be visible 1,000 feet to the rear. (§14 Lighting)

23. A stop lamp must be visible in daylight from at least:

- A. 100 ft
- ✓ **B. 300 ft**
- C. 500 ft
- D. 1,000 ft

Answer: B — Stop lamps must be visible 300 feet in normal daylight. (§14 Lighting)

24. At night, a load projecting more than 4 feet past the rear must show a:

- A. White flag
- B. Red flag
- ✓ **C. Red light**
- D. Amber light

Answer: C — At night use a red light (visible 500 ft) instead of the flag. (§14 Flags)

25. Rear reflectors must be mounted at a height of:

- A. 12-48 inches
- B. 24-54 inches
- ✓ **C. 24-60 inches**
- D. 12-60 inches

Answer: C — Rear reflectors mount 24 to 60 inches above the road. (§14 Lighting)

26. Headlamps must be mounted at a height of:

- A. 12-48 inches
- ✓ **B. 24-54 inches**
- C. 24-60 inches
- D. 20-50 inches

Answer: B — Headlamps mount 24 to 54 inches high. (§14 Lighting)

27. Outside a city, a truck may not follow another truck closer than:

- A. 100 ft
- B. 200 ft
- ✓ **C. 300 ft**
- D. 500 ft

Answer: C — Leave at least 300 feet between trucks (passing is still allowed). (§14 Following)

28. You must dim your high beams for an oncoming vehicle within:

- A. 200 ft
- B. 300 ft
- ✓ **C. 500 ft**
- D. 1,000 ft

Answer: C — Dim high beams within 500 ft of oncoming traffic (300 ft when following). (§14 Lighting)

29. A combination weighing over 3,000 lb must stop from 20 mph within:

- A. 30 ft
- B. 40 ft
- ✓ C. 50 ft
- D. 60 ft

Answer: C — Over 3,000 lb must stop within 50 ft; 3,000 lb or less within 40 ft. (§14 Brakes)

30. Which light color may NOT be shown toward the front of a vehicle?

- A. White
- B. Amber
- ✓ C. Red
- D. All are allowed

Answer: C — Red may not be shown to the front; it is reserved for the rear. (§14 Lighting)

31. At a railroad crossing, a placarded hazmat truck must:

- A. Stop
- B. Check the way is clear
- C. Cross without shifting gears
- ✓ D. All of the above

Answer: D — It must stop, make sure the way is clear, and cross without shifting gears. (§14 Railroad Crossings)

32. Which of these is NOT a Texas limit (without a permit)?

- A. Width 102 in
- B. Height 14 ft
- C. Length 45 ft (single)
- ✓ D. Gross 100,000 lb

Answer: D — Maximum gross is 80,000 lb, not 100,000; the others are correct limits. (§14 Size and Weight)

33. Tail lamps are visible at ____; stop lamps are visible at ____.

- ✓ A. 1,000 ft / 300 ft
- B. 500 ft / 1,000 ft
- C. 300 ft / 1,000 ft
- D. 1,000 ft / 500 ft

Answer: A — Tail lamps 1,000 ft; stop lamps 300 ft in daylight. (§14 Lighting)

34. Headlamps mount at ____; rear reflectors mount at ____.

- ✓ A. 24-54 in / 24-60 in
- B. 24-60 in / 24-54 in
- C. both 24-54 in
- D. both 24-60 in

Answer: A — Headlamps 24-54 in; reflectors 24-60 in. (§14 Lighting)

35. When towing a vehicle by chain, which is required?

- A. A white flag on the connection
- B. A connection no longer than 15 feet
- C. Safety chains as a backup
- ✓ D. All of the above

Answer: D — A white flag, a connection within 15 feet, and safety chains are all required. (§14 Towing)

36. Which of the following is LEGAL in Texas?

- A. Coasting downhill in neutral
- B. Showing a red light to the front
- ✓ C. Covering a gravel load
- D. A hazmat truck skipping a crossing

Answer: C — Covering loose loads is required; the other three are prohibited. (§14 Rules of Operation)

37. In Texas you must hold your CLP for at least how long before the skills test?

- A. 1 day
- ✓ B. 14 days
- C. 6 months
- D. No waiting at all

Answer: B — You must hold the commercial learner's permit at least 14 days before the skills test. (§1)

38. The minimum age to drive a CMV across state lines (interstate) is:

- A. 16
- B. 18
- ✓ C. 21
- D. 25

Answer: C — Interstate driving requires age 21; 18 is allowed only intrastate (within Texas). (§1)

39. Texas's 'Move Over / Slow Down' law applies when you pass a stopped:

- A. An ordinary parked car
- ✓ B. A stopped emergency or TxDOT vehicle
- C. A roadside mailbox post
- D. A bicycle on the shoulder

Answer: B — Move over a lane or slow to 20 mph under the limit for stopped emergency, tow, and TxDOT vehicles with lights on. (§2)

40. A CMV stopped on the shoulder must put out warning devices within:

- A. 1 hour
- ✓ B. 10 minutes
- C. 30 minutes
- D. A full day

Answer: B — Place warning devices within 10 minutes of stopping. (§2)

41. On a two-lane road, you place the three warning triangles at about:

- A. All bunched in one spot
- ✓ B. 10 ft, 100 ft, and 100 ft from the vehicle
- C. Only directly behind it
- D. At 200 ft only, nowhere else

Answer: B — One about 10 ft, one about 100 ft behind, and one about 100 ft ahead on a two-way road. (§2)

42. Required emergency equipment on a CMV includes:

- A. Just a single spare tire
- ✓ B. A fire extinguisher, fuses, and triangles
- C. Only a basic first-aid kit
- D. No special equipment at all

Answer: B — Carry a charged fire extinguisher, spare fuses (if used), and three warning triangles. (§2.1)

43. How many reflective warning triangles must a CMV carry?

- A. One
- B. Two
- ✓ C. Three
- D. Six

Answer: C — Carry three reflective triangles (or equivalent warning devices). (§2.1)

44. In Texas, headlights are required during which hours?

- A. From around noon until midnight
- ✓ B. 30 min after sunset to 30 min before sunrise
- C. Only right around midnight
- D. From sunrise through to sunset

Answer: B — Use headlights from 30 minutes after sunset to 30 minutes before sunrise, and when visibility is low. (§2.11)

45. In Texas you must also use headlights when:

- A. Only on rural dirt roads
- ✓ B. Windshield wipers are on in rain
- C. Never during the daytime
- D. Only while it is parked

Answer: B — Texas law requires headlights when weather requires windshield wipers. (§2.11)

46. On an undivided road, you must stop for a school bus with red lights flashing:

- A. Only if you are behind it
- ✓ B. From both directions
- C. Never at all
- D. Only after dark

Answer: B — On undivided roads, traffic in both directions must stop; a physical median exempts oncoming traffic. (§2)

47. A load wider or taller than Texas legal limits requires:

- A. Nothing extra at all
- ✓ B. An oversize/overweight permit
- C. Only a single red flag
- D. A police escort every time

Answer: B — Loads over legal size or weight need a TxDMV oversize/overweight permit. (§14)

48. A first major offense such as DUI in a CMV disqualifies your CDL for at least:

- A. 30 days
- ✓ B. 1 year
- C. 1 week
- D. No time at all

Answer: B — A first major violation (such as DUI) disqualifies you for at least one year. (§1.4)

49. To get a Texas CDL you must also pass a:

- A. A timed swim test
- ✓ B. DOT medical (physical) exam
- C. A fast typing test
- D. A basic cooking test

Answer: B — A valid DOT medical certificate (physical exam) is required. (§1)

50. In the city, you should signal a turn:

- A. Right at the corner
- ✓ **B. About 100 feet before**
- C. After you turn
- D. No signal is needed

Answer: B — Signal continuously for about 100 feet before turning. (§2.4)

51. When disabled on the highway, you should turn on the:

- A. Your bright high beams
- ✓ **B. Four-way flashers (hazard lights)**
- C. The interior dome light
- D. Just the turn signal

Answer: B — Use four-way hazard flashers and set out warning devices. (§2)

52. In Texas, the driver and front passengers must:

- A. Stand up straight
- ✓ **B. Wear a seat belt**
- C. Keep windows open
- D. Remove the headrests

Answer: B — Seat belt use is required by Texas law. (§2)

53. A commercial driver using a hand-held phone while driving is:

- A. Completely allowed
- ✓ **B. Breaking federal/Texas rules**
- C. Required by law
- D. Fine inside the city

Answer: B — Hand-held phone use and texting are prohibited for CMV drivers. (§2.8)

54. On a divided highway, a warning triangle toward approaching traffic goes about:

- A. 10 ft back
- B. 100 ft back
- ✓ **C. 200 ft back**
- D. Right at the bumper

Answer: C — On a divided or one-way road, place devices about 10, 100, and 200 ft toward approaching traffic. (§2)

55. Texas requires drivers to carry proof of:

- A. A monthly gym membership
- ✓ **B. Financial responsibility (insurance)**
- C. A valid travel passport
- D. A public library card

Answer: B — Proof of financial responsibility (liability insurance) is required. (§1)

56. When you must park, the safest choice is to:

- A. Block a travel lane
- ✓ **B. Park as far off the road as possible**
- C. Leave it running in a lane
- D. Park on a blind curve

Answer: B — Get the vehicle completely off the traveled road where possible. (§2)

57. A driver who refuses a required alcohol or drug test:

- A. Just gets a written warning
- ✓ **B. Is disqualified like a failed test**
- C. Gets a small discount
- D. Nothing happens at all

Answer: B — Refusing a required test brings the same disqualification as failing it. (§1.4)

58. Spare electrical fuses must be carried unless the vehicle:

- A. Is painted bright red
- ✓ **B. Uses circuit breakers, not fuses**
- C. Is brand-new from the lot
- D. Has a working radio

Answer: B — Spare fuses are required unless the vehicle uses circuit breakers. (§2.1)

59. In Texas, open alcohol containers in a CMV cab are:

- A. Generally allowed
- ✓ **B. Prohibited**
- C. Required
- D. Fine when parked

Answer: B — Possessing or drinking alcohol in a commercial vehicle on duty is prohibited. (§1.4)

60. A driver vehicle inspection report (DVIR) is completed:

- A. Just once a year
- ✓ **B. Each day, as required**
- C. Never at all
- D. Only when it is sold

Answer: B — Drivers complete a vehicle inspection report as required (daily or after the trip). (§2.1)

61. In daylight you are hauling a load that extends 5 feet past the rear of your trailer. What does Texas require?

- A. Nothing extra is needed because the load is only a few feet past the rear end.
- ✓ **B. Mark the end of the load with a red or orange flag at least 12 inches square.**
- C. Cover the projecting load with a tarp so other drivers cannot see the overhang.
- D. Put a bright white light on the very end of the load even during daylight hours.

Answer: B — A daytime projecting load must be flagged with a red or orange flag at least 12 inches square. (§TX)

62. Ahead on the shoulder a tow truck is stopped with its emergency lights flashing. Under Texas 'Move Over / Slow Down,' what must you do?

- A. Keep your speed and lane since the law only applies to police patrol vehicles.
- ✓ **B. Move over a lane if you can do so safely, or slow well below the posted limit.**
- C. Stop completely in your lane until the stopped vehicle has finished its work.
- D. Speed up to clear the area as quickly as possible and spend less time beside it.

Answer: B — Move over if safe; otherwise slow down well below the speed limit. (§TX)

63. Your CMV breaks down on a level, straight two-lane road. Where do you place your three warning triangles?

- A. All three triangles directly behind the rear bumper so they stay close together.
- ✓ **B. About 10 feet behind, 100 feet behind, and 100 feet ahead of the stopped vehicle.**
- C. One on the hood, one in the cab window, and one up high on the trailer roof.
- D. Only a single triangle is needed, placed right next to the driver's door area.

Answer: B — On a straight road, place triangles about 10 ft, 100 ft behind, and 100 ft ahead. (§TX)

64. On an undivided two-lane road, a school bus ahead stops and turns on its flashing red lights. What must you do?

- A. Slow down and pass carefully on the left while the red lights are still flashing.
- ✓ **B. Stop and stay stopped until the red lights go off and the bus begins to move on.**
- C. Continue at a reduced speed because only the lane behind the bus has to stop.
- D. Sound your horn twice to warn the children and then drive on past the school bus.

Answer: B — On an undivided road you must stop and remain stopped for flashing red bus lights. (§TX)

65. You are carrying placarded hazardous materials and come to a railroad crossing. What does Texas law require?

- A. Slow down a little and roll across without stopping if no train is in sight at all.
- ✓ **B. Stop 15 to 50 feet before the tracks, look and listen, then cross if it is clear.**
- C. Stop on the tracks briefly to make sure the crossing gate is working correctly.
- D. Speed up to cross the tracks quickly so the heavy load spends less time on them.

Answer: B — A placarded vehicle must stop 15–50 ft before the tracks, look and listen, then cross. (§TX)

66. You must park your truck beside a rural highway at night. What is the safest choice?

- A. Park in the traffic lane with your headlights on so other drivers can see you.
- ✓ **B. Pull completely off the road, set the parking brake, and put out warning devices.**
- C. Stop halfway on the shoulder and halfway in the lane to keep the cab on pavement.
- D. Leave the truck running in gear so it does not roll while you are parked there.

Answer: B — Pull fully off, set the parking brake, and put out warning devices. (§TX)

67. While driving your CMV in Texas, your phone rings and you want to answer it. What is the law?

- A. You may hold and use the phone freely as long as both hands return to the wheel.
- ✓ **B. Using a hand-held phone while driving a CMV is prohibited; use hands-free only.**
- C. Texting is banned but holding the phone for calls is always completely allowed.
- D. Phone use is fine below 30 mph and is only banned at higher highway speeds.

Answer: B — Hand-held phone use while driving a CMV is prohibited; use hands-free. (§TX)

68. Your truck is 80 inches wide and you are checking the lamps before a night trip. What is required at the front?

- A. A single white lamp mounted in the center of the front bumper is all that you need.
- ✓ **B. Amber clearance (side-marker) lamps showing toward the front of the wide vehicle.**
- C. Red clearance lamps on the front corners so the traffic ahead sees you coming.
- D. No clearance lamps are needed at the front of a truck this size anywhere in Texas.

Answer: B — A wide vehicle needs amber clearance lamps showing toward the front. (§TX)

69. You are about to pass a motorcycle on a Texas highway. How should you treat it?

- A. Pass close and quickly since a motorcycle takes up much less of the lane width.
- ✓ **B. Give it a full lane width and a safe amount of space, just as you would a car.**
- C. Straddle the lane line so part of your truck stays beside the motorcycle longer.
- D. Honk and move into its lane to make the rider pull over onto the shoulder for you.

Answer: B — Give a motorcycle a full lane and safe space, the same as a car. (§TX)

70. After a serious incident, a Texas DPS officer asks you to take an alcohol or drug test. What if you refuse?

- A. Nothing happens to your CDL as long as you were not actually drinking that day.
- ✓ **B. Refusing the required test disqualifies your CDL, just like failing the test would.**
- C. You simply pay a small fine and keep driving your commercial vehicle as before.
- D. You may retake the test later at home with no penalty for the first refusal at all.

Answer: B — Refusing a required test disqualifies your CDL the same as failing it. (§TX)

1. The main purpose of the hazardous materials rules is to:

- A. Collect extra government tax revenue each year
- ✓ **B. Contain the risk and warn others of the danger**
- C. Speed up deliveries to waiting customers
- D. Reduce fuel use on long highway trips

Answer: B — The rules exist to contain the material, communicate the risk, and ensure safe drivers and equipment. (§9.1)

2. To carry placarded amounts of hazardous materials you must have:

- ✓ **A. A hazardous materials (H) endorsement**
- B. A passenger endorsement
- C. A doubles/triples endorsement
- D. No special endorsement

Answer: A — A HazMat (H) endorsement is required, and it needs a TSA background check. (§9.1)

3. Getting the HazMat endorsement requires:

- ✓ **A. A TSA security background check**
- B. A new vision test only
- C. A doctor's note
- D. Nothing extra

Answer: A — Federal law requires a TSA security threat assessment (background check and fingerprints). (§9.1)

4. Who must identify the hazmat and prepare the shipping papers?

- A. The driver
- ✓ **B. The shipper**
- C. The mechanic
- D. The receiver

Answer: B — The shipper identifies the hazard, names it, packages it, and prepares the shipping papers. (§9.1)

5. Where must hazmat shipping papers be kept?

- A. In the trailer with the freight
- ✓ **B. Within the driver's reach and in clear view**
- C. Locked in the trunk
- D. Mailed ahead of the load

Answer: B — Keep them in a pouch on the driver's door, in clear view within reach, or on the seat when out of the cab. (§9.2)

6. On the shipping paper, hazmat is usually listed:

- A. Last, in small print
- ✓ **B. First, or highlighted/marked**
- C. Only on the back page
- D. Not listed at all

Answer: B — Hazmat must be entered first, or highlighted, or marked with an 'X' in the HM column. (§9.2)

7. Placards are used to:

- A. Decorate the trailer
- ✓ **B. Warn others of the hazard**
- C. Show the carrier's logo
- D. Mark the cargo weight

Answer: B — Placards are diamond-shaped warnings carried on the vehicle. (§9.3)

8. A placarded load must display its placards:

- A. Only on the rear of the trailer
- B. Only on the two sides of the tank
- ✓ C. On the front, rear, and both sides
- D. On the roof and front bumper only

Answer: C — Placards go on all four sides: front, rear, and both sides. (§9.3)

9. The book that tells emergency crews how to handle a spill is the:

- A. The driver's daily logbook
- ✓ B. Emergency Response Guidebook (ERG)
- C. The truck owner's manual
- D. The freight bill of lading

Answer: B — The ERG helps responders identify the hazard and take protective action. (§9.2)

10. Before transporting hazmat, the driver should:

- ✓ A. Inspect the vehicle and the load carefully
- B. Remove the placards
- C. Disconnect the brakes
- D. Skip the pre-trip to save time

Answer: A — Hauling hazmat requires a careful inspection of the vehicle, tires, and securement. (§9.4)

11. While driving a placarded load, you must check your tires:

- A. Only once at the very start
- ✓ B. At the start and at each stop
- C. Never during the whole trip
- D. Just once a week is enough

Answer: B — Check tires before the trip and each time you stop; remove a leaking or flat tire. (§9.4)

12. If a tire on a placarded vehicle is overheated, you must:

- A. Pour water on it and continue
- ✓ B. Remove it and place it a safe distance away
- C. Keep driving to the next town
- D. Add air and keep going

Answer: B — Remove an overheated tire and set it a safe distance from the vehicle; don't drive until fixed. (§9.4)

13. You may NOT smoke within how many feet of explosives, flammables, or oxidizers?

- A. 5 feet
- B. 10 feet
- ✓ C. 25 feet
- D. 100 feet

Answer: C — No smoking or open flame within 25 feet of these materials. (§9.4)

14. Before loading or unloading explosives, you must:

- A. Leave the engine running
- ✓ B. Turn off the engine and set the brakes
- C. Open all the windows
- D. Sound the horn

Answer: B — Turn off the engine (unless needed to run a pump) and secure the vehicle. (§9.4)

15. Hazard Class 3 covers:

- A. Explosives
- ✓ **B. Flammable liquids**
- C. Corrosives
- D. Radioactive materials

Answer: B — Class 3 is flammable liquids, such as gasoline. Explosives are Class 1. (§9.2)

16. Explosives belong to which hazard class?

- ✓ **A. Class 1**
- B. Class 3
- C. Class 7
- D. Class 8

Answer: A — Class 1 is explosives; Class 7 is radioactive; Class 8 is corrosives. (§9.2)

17. A 'placarded amount' means you:

- A. Always need placards for any hazmat
- ✓ **B. Need placards only for certain quantities or classes**
- C. Never need placards
- D. Need placards only at night

Answer: B — Some materials need placards in any amount; others only above set quantities — the tables tell you. (§9.3)

18. The shipper certifies the shipment is correct by:

- A. Making a quick phone call
- ✓ **B. Signing the shipping paper**
- C. Sending a short text message
- D. Doing nothing at all

Answer: B — The shipper signs a certification that the material is properly named, packaged, and labeled. (§9.2)

19. If you find a hazmat leak, you should:

- A. Touch it to identify it
- ✓ **B. Not touch it and keep people away**
- C. Drive faster to a shop
- D. Hide the placards

Answer: B — Never touch a leak; keep people away, avoid ignition sources, and get help. (§9.5)

20. A serious hazmat incident is reported to the:

- A. Local newspaper
- ✓ **B. National Response Center**
- C. Nearest gas station
- D. Vehicle manufacturer

Answer: B — Serious incidents are reported to the National Response Center (1-800-424-8802). (§9.5)

21. The CHEMTREC emergency information line is staffed:

- A. Only on weekdays
- ✓ **B. 24 hours a day**
- C. Only at night
- D. Once a month

Answer: B — CHEMTREC (1-800-424-9300) provides 24-hour emergency response information. (§9.5)

22. When parking a placarded vehicle (except explosives), you should:

- A. Leave it parked just about anywhere
- ✓ **B. Not park within 5 feet of the traveled road**
- C. Park up on the public sidewalk
- D. Block the nearest fire hydrant

Answer: B — Don't park within 5 ft of the traveled part of a road; keep it attended where required. (§9.6)

23. A vehicle carrying Class 1 explosives must be parked how far from open fire?

- ✓ **A. At least 300 feet**
- B. 5 feet
- C. 10 feet
- D. No rule applies

Answer: A — Keep explosives at least 300 feet from open fire. (§9.6)

24. 'Attended parking' means someone is:

- ✓ **A. Within sight and able to reach the vehicle quickly**
- B. Asleep in a nearby roadside motel
- C. Living over in the next town
- D. Checking on it once a day

Answer: A — An attendant must be awake, within 100 ft, in clear view, and able to move the vehicle. (§9.6)

25. Which of these is NOT a driver responsibility for hazmat?

- A. Refusing leaking packages
- B. Placarding when required
- ✓ **C. Manufacturing the product**
- D. Following the route rules

Answer: C — Drivers don't manufacture the product; they refuse leaks, placard, and follow the rules. (§9.1)

26. Cargo heaters generally may NOT be used when hauling:

- A. Ordinary canned food
- ✓ **B. Explosives or flammable materials**
- C. Household furniture and boxes
- D. Sealed bottled drinking water

Answer: B — Cargo heaters are restricted or prohibited with explosives and flammables. (§9.4)

27. Carriers keep hazmat shipping papers after the trip because:

- A. They are souvenirs
- ✓ **B. Regulators may require the records**
- C. They are worthless
- D. The driver keeps them forever

Answer: B — Carriers must retain records for the required time for inspection. (§9.2)

28. The Hazardous Materials Table lists all of the following EXCEPT:

- A. Proper shipping name
- B. Hazard class
- C. Identification number
- ✓ **D. The driver's home address**

Answer: D — The table lists shipping name, class, ID number, packing group, and labels — not personal info. (§9.2)

29. If placards are required but the shipper didn't provide them, you should:

- A. Just drive without any placards
- B. Make your own placards from cardboard
- ✓ **C. Get and apply the correct placards before moving**
- D. Ignore the load and leave it

Answer: C — The vehicle must be correctly placarded before transport; obtain and apply the right ones. (§9.3)

30. Hazard labels on packages are:

- A. Identical to the vehicle placards
- ✓ **B. Smaller diamonds on each package**
- C. Printed on the truck bumper only
- D. Not used in the US

Answer: B — Labels are smaller diamond markings the shipper puts on packages; placards go on the vehicle. (§9.3)

31. Hazard Class 2 materials are:

- ✓ **A. Gases**
- B. Solids only
- C. Liquids only
- D. Paper products

Answer: A — Class 2 is gases — flammable, non-flammable, and poison gas. (§9.2)

32. The proper shipping name on the paper must match:

- A. The product's brand name
- ✓ **B. The name in the Hazardous Materials Table**
- C. The driver's personal nickname
- D. The number painted on the trailer

Answer: B — Use the proper shipping name from the table, not a trade name. (§9.2)

33. On a placarded vehicle, the fire extinguisher should be:

- A. Empty
- ✓ **B. Charged and properly rated**
- C. Left at the terminal
- D. Just for decoration

Answer: B — A properly rated, charged fire extinguisher is required. (§9.4)

34. When fueling a placarded vehicle, someone must:

- A. Stand and smoke right nearby
- ✓ **B. Control the nozzle at the point of fuel flow**
- C. Leave the fueling area entirely
- D. Rev the engine while fueling

Answer: B — Turn the engine off and keep a person at the nozzle; never smoke while fueling. (§9.4)

35. Routes for explosives and certain hazmat should:

- A. Go through the busiest downtown
- ✓ **B. Avoid populated areas and tunnels when required**
- C. Always use bridges
- D. Never be planned

Answer: B — Follow required routing — avoid tunnels, crowds, and prohibited routes. (§9.6)

36. Different hazmat that can react together must be:

- A. Stacked tightly together on one pallet
- ✓ **B. Loaded separately per the segregation rules**
- C. Mixed together in a single box
- D. Ignored and just loaded anyway

Answer: B — The segregation table tells you which materials must be kept apart. (§9.4)

37. Hazard Class 8 is:

- A. Explosives
- ✓ **B. Corrosives**
- C. Gases
- D. Radioactive

Answer: B — Class 8 is corrosives (such as acids). Class 1 is explosives. (§9.2)

38. Hazard Class 7 is:

- A. Flammable liquids
- ✓ **B. Radioactive materials**
- C. Corrosives
- D. Gases

Answer: B — Class 7 is radioactive materials. (§9.2)

39. Hazard Class 6 covers:

- A. Oxidizers
- ✓ **B. Poisons (toxic)**
- C. Explosives
- D. Gases

Answer: B — Class 6 is poisons and toxic materials. (§9.2)

40. Hazard Class 5 is:

- ✓ **A. Oxidizers**
- B. Corrosives
- C. Explosives
- D. Radioactive

Answer: A — Class 5 is oxidizers and organic peroxides. (§9.2)

41. The 'DANGEROUS' placard may be used when:

- A. In just about every case
- ✓ **B. Hauling several mixed classes**
- C. In no case ever at all
- D. Only for boxed food items

Answer: B — The DANGEROUS placard can be used for certain mixed loads of two or more hazard classes. (§9.3)

42. The four-digit ID number on a placard or paper identifies:

- A. The truck driver
- ✓ **B. The specific material**
- C. The truck's weight
- D. The planned route

Answer: B — The 4-digit UN/NA number identifies the specific hazardous material. (§9.2)

43. The packing group shows the material's:

- A. The color
- ✓ **B. Degree of danger**
- C. The price
- D. The weight

Answer: B — Packing group (I, II, III) shows the degree of danger. (§9.2)

44. An emergency response phone number must appear:

- A. Nowhere at all
- ✓ **B. On the shipping paper**
- C. On the tire walls
- D. On the rear bumper

Answer: B — A 24-hour emergency response phone number must be on the shipping paper. (§9.2)

45. Hazard Class 4 materials are:

- A. Very cold solids
- ✓ **B. Flammable solids**
- C. Quiet liquids
- D. Heavy metals

Answer: B — Class 4 covers flammable solids. (§9.2)

46. Some Class 4 materials are dangerous when:

- A. Freshly painted
- ✓ **B. Wet (react with water)**
- C. Kept very cold
- D. Packed in boxes

Answer: B — 'Dangerous when wet' materials react with water and can ignite. (§9.2)

47. Compressed gas cylinders should be:

- A. Laid in loosely
- ✓ **B. Secured and upright**
- C. Just thrown in
- D. Left fully open

Answer: B — Secure gas cylinders and keep them upright as required. (§9.4)

48. Poison/toxic materials must NOT be loaded with:

- A. Other ordinary boxes
- ✓ **B. Food for people or animals**
- C. Hand tools and gear
- D. Clean dry sand

Answer: B — Never load poisons with food meant for humans or animals. (§9.4)

49. Corrosives (Class 8) can:

- A. Cool the truck down
- ✓ **B. Burn skin and eyes**
- C. Improve the mileage
- D. Do nothing at all

Answer: B — Corrosives can burn skin and eyes; handle with care. (§9.2)

50. Before loading hazmat, the cargo space should be:

- A. Soaking wet inside
- ✓ **B. Clean, no spark hazards**
- C. Full of loose tools
- D. Already on fire

Answer: B — The cargo area must be clean and free of spark hazards before loading. (§9.4)

51. A placard must be readable and:

- A. Kept fully hidden
- ✓ **B. Turned square, point up**
- C. Painted over solid
- D. Taken off entirely

Answer: B — Placards are diamonds set as a square pointing up, kept clean and readable. (§9.3)

52. A leaking or damaged hazmat package should be:

- A. Just loaded anyway
- ✓ **B. Refused / not transported**
- C. Hidden inside cargo
- D. Mixed with the cargo

Answer: B — Refuse any leaking or damaged hazardous materials package. (§9.4)

53. An empty tank that held hazmat may still need placards because of:

- A. Its painted color
- ✓ **B. Leftover residue or vapors**
- C. The tired driver
- D. The cold weather

Answer: B — Residue or vapors can keep an 'empty' tank placarded. (§9.3)

54. Hazardous WASTE requires a special:

- A. A special paint color
- ✓ **B. Uniform hazardous waste manifest**
- C. A loud cab radio
- D. A bright warning flag

Answer: B — Hazardous waste requires a uniform hazardous waste manifest. (§9.2)

55. Tools used near Class 1 explosives should be:

- A. Steel that sparks
- ✓ **B. Non-sparking tools**
- C. Very heavy bars
- D. Painted red ones

Answer: B — Use non-sparking tools near explosives. (§9.4)

56. You should check that placards are in place:

- A. Never during it
- ✓ **B. Before and during the trip**
- C. Only at delivery time
- D. Only after dark

Answer: B — Make sure placards are in place before and during the trip. (§9.3)

57. The shipper's emergency information helps:

- A. Help sell the product
- ✓ **B. Responders handle a spill**
- C. Pick a radio station
- D. Choose the right tires

Answer: B — It helps emergency responders handle a spill or fire. (§9.5)

58. Radioactive (Class 7) shipments are controlled partly by a:

- A. A music play index
- ✓ **B. Transport index limiting exposure**
- C. A simple color code only
- D. A road speed index

Answer: B — A transport index limits total radiation exposure on the vehicle. (§9.2)

59. On the road, transferring hazmat between vehicles is:

- A. Strongly encouraged
- ✓ **B. Avoided except in emergency**
- C. Required every hour
- D. Done while still moving

Answer: B — Avoid transferring hazmat between vehicles except in an emergency. (§9.4)

60. Marine pollutants must be:

- A. Kept fully hidden
- ✓ **B. Marked as required**
- C. Poured out first
- D. Left fully unmarked

Answer: B — Marine pollutants must carry the required markings. (§9.3)

61. En route you discover a hazardous-materials leak from a package in your trailer. What should you do?

- A. Keep driving to the destination quickly so the consignee can deal with the leak there.
- ✓ **B. Stop, secure the area, keep people away, and do not move the vehicle unnecessarily.**
- C. Open all the trailer doors and keep driving so the fumes blow out of it as you go.
- D. Wash the leaking material off the road with water and then continue on your route.

Answer: B — Stop, secure the area, keep people back, and don't move the vehicle needlessly. (§9.5)

62. You are loading hazmat and must verify the shipment. Whose job is it to describe the hazmat correctly on the papers?

- A. The mechanic who last serviced the truck before it was sent out on this trip today.
- ✓ **B. The shipper, who must name and describe the hazmat correctly on the shipping papers.**
- C. The receiver at the destination, who checks the load only after it has been delivered.
- D. Any other driver at the terminal who happens to be standing nearby at the moment.

Answer: B — The shipper names and describes the hazmat correctly on the papers. (§9.1)

63. You are carrying placarded explosives (Division 1.1) and need to stop for fuel and food. Where should you park?

- A. In a crowded restaurant parking lot right next to the building's front entrance there.
- ✓ **B. Away from open fire, bridges, tunnels, and crowds, attended where it is required.**
- C. On a busy downtown street so the truck is easy to watch from inside a café nearby.
- D. Next to other parked trucks with running engines so your cargo is kept nice and warm.

Answer: B — Park away from fire, bridges, tunnels, and crowds; attend it where required. (§9.5)

64. Before a trip with placarded hazmat, you check your fire extinguisher. What is required?

- A. No extinguisher is needed because the trailer is sealed and locked for the whole trip.
- ✓ **B. A properly rated, charged, and accessible fire extinguisher must be on the vehicle.**
- C. A small household spray bottle of water is enough to meet the requirement for hazmat.
- D. Only the receiver needs an extinguisher, kept at the delivery dock at the destination.

Answer: B — A placarded vehicle must carry a properly rated, charged, accessible extinguisher. (§9.5)

65. You reach a railroad crossing while hauling placarded hazardous materials. What must you do?

- A. Roll across slowly without stopping as long as you do not see a train approaching now.
- ✓ **B. Stop 15 to 50 feet before the tracks, check it's clear, then cross without shifting gears.**
- C. Stop right on the tracks to look both ways carefully before you continue across them.
- D. Speed up to cross the tracks fast so the placarded load is on the rails for less time.

Answer: B — Stop 15-50 ft before the tracks, then cross without changing gears. (§9.5)

66. Checking your shipping papers, you find the hazmat is not listed first or marked. What does this tell you?

- A. The paperwork is correct, since hazmat can appear anywhere on the shipping document.
- ✓ **B. The paperwork is wrong; hazmat must be entered first or clearly marked or highlighted.**
- C. It means there is no hazmat on board, so you can remove the placards from the truck.
- D. It only matters for the receiver, so you can begin the trip and sort it out later on.

Answer: B — Hazmat must be entered first or clearly marked/highlighted on the paper. (§9.2)

67. You are about to transport a load and must decide whether placards are needed. Who is responsible for placarding?

- A. Only the police, who add placards at a roadside inspection if they decide it is needed.
- ✓ **B. The driver and carrier must placard the vehicle when the load requires placards on it.**
- C. The receiver places the placards on the truck after the shipment has been delivered.
- D. Placards are optional decorations and nobody in particular is responsible for them at all.

Answer: B — The driver and carrier placard the vehicle when the load requires it. (§9.3)

68. A tire on your placarded hazmat vehicle is overheating at a stop. What should you do?

- A. Pour water on it and keep driving to the destination since the load is on a schedule.
- ✓ **B. Remove the overheated tire and place it a safe distance from the vehicle, then check.**
- C. Add more air to the hot tire and continue driving the rest of the route as planned.
- D. Ignore the hot tire because heat is normal for tires on a fully loaded hazmat truck.

Answer: B — Remove the overheated tire and place it away from the vehicle before checking. (§9.5)

69. You are planning a route for a placarded hazmat load through a metro area. What is the best practice?

- A. Always drive through the busiest downtown center to reach the destination the fastest.
- ✓ **B. Avoid heavily populated areas, crowds, and tunnels where required, and plan ahead.**
- C. Always use the longest bridge available so the heavy load stays on a smooth surface.
- D. Never plan a route in advance; just follow the navigation app turn by turn each time.

Answer: B — Avoid crowds and tunnels where required and plan the route ahead. (§9.5)

70. After delivering, you still have placards on an empty trailer that no longer holds hazmat. What should you do?

- A. Leave all the placards up permanently so you never have to put them on again later on.
- ✓ **B. Remove or cover the placards once the vehicle no longer requires them for the load.**
- C. Add even more placards to the empty trailer to be on the safe side just in case now.
- D. It makes no difference at all whether the placards stay up on an empty hazmat trailer.

Answer: B — Remove or cover placards when the vehicle no longer requires them. (§9.3)

1. A tank vehicle (N) endorsement is needed to haul:

- A. Dry boxed freight
- ✓ B. Liquids or gases in bulk tanks
- C. Empty trailers
- D. Refrigerated produce

Answer: B — The N endorsement is for hauling liquids or gases in bulk tank containers. (§8.1)

2. The biggest handling problem with a liquid tank is:

- A. Tire wear
- ✓ B. Liquid surge
- C. Bright paint
- D. Light weight

Answer: B — Liquid moving inside the tank (surge) can push the vehicle and affect control. (§8.2)

3. Tanks are loaded with some empty space called:

- ✓ A. Outage
- B. Overflow
- C. Ballast
- D. Surge

Answer: A — Outage is the room left so the liquid can expand as it warms. (§8.1)

4. Compared with other loads, a loaded liquid tank has a:

- A. Low center of gravity
- ✓ B. High center of gravity
- C. No center of gravity
- D. Negative weight

Answer: B — A high center of gravity makes a tank more likely to roll over. (§8.2)

5. Because of the high center of gravity, you should:

- A. Take curves fast
- ✓ B. Slow down before curves
- C. Brake only in the curve
- D. Steer sharply

Answer: B — Reduce speed well before curves and ramps to avoid rollover. (§8.2)

6. A tank divided into separate compartments by solid walls has:

- A. Baffles
- ✓ B. Bulkheads
- C. A smooth bore
- D. Vents

Answer: B — Bulkheads are solid walls that divide the tank into compartments. (§8.2)

7. Baffles in a tank are meant to reduce:

- ✓ A. Front-to-back surge
- B. Side-to-side surge
- C. Tire pressure
- D. Engine heat

Answer: A — Baffles have holes that slow forward-and-back surge; they don't stop side-to-side surge. (§8.2)

8. A smooth bore (unbaffled) tank has:

- A. Many internal compartment dividers
- ✓ **B. Nothing inside to slow surge**
- C. Extra emergency brakes
- D. A raised-up high floor

Answer: B — Smooth bore tanks have no baffles, so surge is strong; often used for food. (§8.2)

9. Side-to-side surge can cause a tank to:

- A. Speed up
- ✓ **B. Roll over**
- C. Use less fuel
- D. Stop faster

Answer: B — Side surge in turns can tip a high-center-of-gravity tank over. (§8.2)

10. When you brake, front-to-back surge can:

- ✓ **A. Push the truck forward**
- B. Stop the truck instantly
- C. Lower the tank
- D. Cool the brakes

Answer: A — Surging liquid can shove the vehicle forward, e.g., into an intersection. (§8.2)

11. To handle surge when stopping, you should:

- A. Brake hard at the very last second
- ✓ **B. Brake early and smoothly with more following space**
- C. Tailgate closely to save some space
- D. Coast along in neutral gear

Answer: B — Brake gently and early, leave extra space, and stay alert for surge. (§8.2)

12. A partly filled tank is risky mainly because of:

- ✓ **A. Strong surge**
- B. Low weight
- C. Bright color
- D. Extra mirrors

Answer: A — Partial loads surge the most; control braking and steering carefully. (§8.2)

13. Before driving a tank, you should check special items such as:

- A. The cab radio only
- ✓ **B. Vents, hoses, and manhole covers**
- C. The color of the seats
- D. Only the rear mud flaps

Answer: B — Inspect tank-specific equipment: vents, valves, hoses, manhole/dome covers, and leaks. (§8.3)

14. Tank vents must be:

- A. Sealed shut
- ✓ **B. Kept clear and working**
- C. Painted over
- D. Removed

Answer: B — A clogged vent can cause a vacuum and collapse the tank; keep vents working. (§8.3)

15. On a curve or ramp, a tank's speed should be:

- A. Above the limit
- ✓ **B. Below the posted speed**
- C. Ignored
- D. Exactly the posted speed

Answer: B — Posted ramp/curve speeds are for ordinary vehicles; tanks should go even slower. (§8.2)

16. The amount of liquid to load depends on all EXCEPT:

- A. The liquid's weight
- B. Legal weight limits
- C. Expansion (outage)
- ✓ **D. The driver's height**

Answer: D — Load amount depends on liquid weight, legal limits, and outage — not the driver. (§8.1)

17. Smooth bore tanks are most often used to haul:

- A. Loose gravel and sand
- ✓ **B. Food products (sanitation)**
- C. Cut timber and logs
- D. Passenger cars and vans

Answer: B — Food-grade tanks are often smooth bore because baffles are hard to clean. (§8.2)

18. The most important rule to prevent a tank rollover is:

- A. Keep the load sitting up high
- ✓ **B. Keep speed low in turns and on ramps**
- C. Brake firmly only once
- D. Use just one side mirror

Answer: B — Most tank rollovers come from too much speed in turns; slow down. (§8.2)

19. To absorb surge that pushes you at a light, you should have:

- A. No following space
- ✓ **B. Extra space ahead**
- C. Closed eyes
- D. More speed

Answer: B — Extra space ahead absorbs the forward push from surge. (§8.2)

20. Bulkhead tanks help you by:

- A. Completely removing absolutely all surge
- ✓ **B. Reducing front-to-back surge between compartments**
- C. Adding more dead weight to the rig
- D. Cooling the liquid load right down

Answer: B — Bulkheads separate compartments; watch weight distribution when filling them. (§8.2)

21. When loading a tank with bulkheads, watch your:

- A. The truck's exterior paint job
- ✓ **B. Weight distribution over the axles**
- C. The loud air horn
- D. The radio antenna mast

Answer: B — Filling only front or rear compartments can overload an axle; balance the load. (§8.2)

22. Which statement about driving tank vehicles is TRUE?

- A. Surge never affects braking
- B. Empty tanks can never roll
- ✓ C. **Slow down for curves and brake early**
- D. A high center of gravity helps

Answer: C — Slow for curves and brake early; surge affects control and tanks roll easily. (§8.2)

23. Liquids that expand a lot need:

- A. No outage
- ✓ B. **More outage room**
- C. A sealed vent
- D. A flat tank

Answer: B — Some liquids expand more with heat and need more outage space. (§8.1)

24. Hauling hazardous liquids in a tank may also require:

- A. A passenger endorsement
- ✓ B. **A hazardous materials endorsement**
- C. A motorcycle license
- D. Nothing more

Answer: B — Placarded hazardous liquids need the HazMat (H) endorsement in addition to N. (§8.1)

25. Steering in a tank should be:

- A. Sudden and sharp
- ✓ B. **Smooth and gradual**
- C. Done with one finger
- D. Avoided in curves

Answer: B — Sudden steering can start a side surge and a rollover; steer smoothly. (§8.2)

26. The safest following distance with a loaded tank is:

- A. Shorter than normal
- ✓ B. **Longer than normal**
- C. Zero
- D. Only used at night

Answer: B — A longer following distance gives room for surge and longer stops. (§8.2)

27. A tank's product (wet) lines should be checked for:

- A. Loud noises
- ✓ B. **Leaks and damage**
- C. The paint color
- D. The road speed

Answer: B — Inspect the tank's product lines and valves for leaks and damage. (§8.3)

28. Manhole and dome covers on a tank must be:

- A. Left wide open
- ✓ B. **Closed and sealed**
- C. Taken off
- D. Painted shut

Answer: B — Keep manhole and dome covers closed and sealed so the tank does not leak. (§8.3)

29. When loading flammable liquid, the cargo tank must be:

- A. Left ungrounded
- ✓ **B. Grounded/bonded**
- C. Filled with air
- D. Kept hot

Answer: B — Ground and bond the tank to prevent a static spark during loading. (§8.4)

30. A loaded tanker's stopping distance, vs a similar dry van, is:

- A. Much shorter
- ✓ **B. Longer because of surge**
- C. Exactly zero
- D. Exactly the same

Answer: B — Surge makes a loaded tank take longer to stop. (§8.2)

31. Before loading or unloading a tank, you should:

- A. Leave the engine racing
- ✓ **B. Park and set the brakes**
- C. Keep driving slowly
- D. Open every valve at once

Answer: B — Park, set the brakes, and follow the loading/unloading steps. (§8.4)

32. During acceleration or braking, surge mainly affects your:

- A. Cab radio
- ✓ **B. Control of the vehicle**
- C. Paint job
- D. Mirror color

Answer: B — Surge can affect control when you speed up or slow down. (§8.2)

33. To reduce rollover risk, the load's weight should be kept:

- A. As high as possible
- ✓ **B. As low as possible**
- C. All on one side
- D. Up above the tank

Answer: B — A lower weight lowers the center of gravity and rollover risk. (§8.2)

34. Compared with most other trucks, tank vehicles have a:

- A. Lower rollover rate
- ✓ **B. Higher rollover rate**
- C. Zero rollover rate
- D. Smaller size

Answer: B — Tank vehicles roll over more easily than most other CMVs. (§8.2)

35. You should know a tank's contents because:

- A. To pick a good radio station
- ✓ **B. Different liquids need different handling**
- C. To choose a nice paint color
- D. There is no real reason at all

Answer: B — Different liquids must be handled differently and safely. (§8.1)

36. Going down a hill in a loaded tanker, you should:

- A. Speed up to clear it
- ✓ **B. Slow down and use a low gear**
- C. Coast in neutral
- D. Brake once very hard

Answer: B — Slow down and use a low gear so surge and weight don't run away with you. (§8.2)

37. A tank that is leaking should be:

- A. Driven much faster
- ✓ **B. Not driven until repaired**
- C. Hidden away somewhere
- D. Filled up even more

Answer: B — Never drive a leaking tank; have it repaired first. (§8.3)

38. Because liquids are heavy, you may reach legal weight:

- A. Never at all
- ✓ **B. Before the tank is full**
- C. Only when empty
- D. Only at night

Answer: B — Liquids are heavy, so you can be at legal weight before the tank is full. (§8.1)

39. Empty or partly filled tanks tend to:

- A. Grip the road better
- ✓ **B. Bounce and surge**
- C. Stop much faster
- D. Never move at all

Answer: B — Light loads bounce and surge; brake with care. (§8.2)

40. A tank hauling hazardous liquid must display:

- A. A single flag
- ✓ **B. The required placards**
- C. Nothing at all
- D. A company banner

Answer: B — Hazardous liquids require the proper placards on the tank. (§8.1)

41. A tank's emergency shut-off valves should be:

- A. Painted over
- ✓ **B. Working and accessible**
- C. Removed entirely
- D. Tied open

Answer: B — Emergency shut-off valves must work and be reachable. (§8.3)

42. Parking a loaded tanker on a slope, you should:

- A. Leave it in neutral
- ✓ **B. Set brakes and chock wheels**
- C. Leave it running
- D. Lower the tank down

Answer: B — Set the parking brakes and chock the wheels on a slope. (§8.3)

43. You're driving a tanker that is partly full of liquid and you brake at a stop sign. What should you expect?

- A. The liquid stays perfectly still, so braking feels exactly like a dry-box load does.
- ✓ **B. The liquid surges forward and can push the truck, so brake early and smoothly here.**
- C. The liquid makes the truck stop much faster than usual, so you can brake later on.
- D. The liquid has no effect at all on braking, so you may stop hard at the last second.

Answer: B — Liquid surge pushes a partly full tanker; brake early and smoothly. (§8.2)

44. You are loading a liquid tank and must decide how full to fill it. Why might you leave some space (outage)?

- A. To make the truck lighter so it can legally carry more boxes on top of the tank.
- ✓ **B. Liquids expand with heat, so you leave outage room so the tank will not overflow.**
- C. So the liquid can slosh as much as possible and keep the cargo well mixed in transit.
- D. There is no reason to leave space; always fill a liquid tank completely to the very top.

Answer: B — Liquids expand as they warm, so you must leave outage room. (§8.1)

45. Your tank has a smooth bore (no baffles) inside. How does this affect your driving?

- A. It removes all surge, so you can brake and corner as hard as you like with no effect.
- ✓ **B. Surge is strong front-to-back, so brake gently and leave extra space and extra time.**
- C. It makes the load shift only side to side, which never affects your stopping at all.
- D. It lets you fill the tank higher than normal because the liquid cannot move around.

Answer: B — Smooth-bore tanks have strong front-to-back surge; brake gently with extra room. (§8.2)

46. You're taking a curve on an exit ramp with a full liquid tanker. What is the safest approach?

- A. Enter the curve at the posted speed since a heavy tanker grips the road very well.
- ✓ **B. Slow well below the posted ramp speed because a high center of gravity tips easily.**
- C. Speed up in the curve so the liquid is pressed outward and holds the truck down.
- D. Brake hard in the middle of the curve to keep the liquid from surging forward at all.

Answer: B — A high center of gravity tips easily; slow well below the ramp speed. (§8.2)

47. You are checking a cargo tank before a trip. What should you inspect that is special to tankers?

- A. Only the radio and the seat adjustment, since tankers drive like any other truck.
- ✓ **B. Valves, vents, hoses, and manhole covers for leaks and that they are closed right.**
- C. Just the outside paint color so the tank matches the rest of the company's fleet.
- D. Nothing extra at all; a tanker needs the same checks as an empty flatbed trailer.

Answer: B — Inspect valves, vents, hoses, and manhole covers for leaks and proper closing. (§8.3)

48. Your liquid tanker begins to roll on a curve more than you expected. What most likely caused it?

- A. The tank was completely empty, so there was no weight to make it tip over at all.
- ✓ **B. A high center of gravity plus liquid surge made the tank tip over on the curve.**
- C. The tires were brand new, which always makes a tanker much more likely to roll.
- D. The smooth, dry road surface, which removes all the rollover risk on every curve.

Answer: B — A high center of gravity plus surge tips a tanker on a curve. (§8.2)

49. You must stop quickly in a tanker hauling liquid. How does surge change your stop?

- A. Surge shortens your stop because the liquid pushes the wheels down onto the road.
- ✓ **B. Surge can shove the truck forward, so you need more distance and a smooth stop.**
- C. Surge has no effect; a tanker stops in exactly the same distance as a dry van does.
- D. Surge locks the brakes for you automatically, so you do not need to plan your stop.

Answer: B — Surge can shove the truck forward; allow more distance and stop smoothly. (§8.2)

50. You are hauling several small tank compartments with bulkheads. Why are these used?

- A. To make the tank look fancier and to add extra weight to the back of the trailer.
- ✓ **B. They divide the load so weight is balanced and front-to-back surge is reduced well.**
- C. They let you fill the whole tank far past its legal limit without any real problem.
- D. They have no real purpose and only make the tank heavier and harder to clean out.

Answer: B — Bulkheads divide the load to balance weight and reduce surge. (§8.1)

51. You're driving a tanker on a wet road and need to change lanes. What should you do?

- A. Make a quick, sharp lane change so the surging liquid has no time to push the truck.
- ✓ **B. Change lanes smoothly and gradually, since sudden moves plus surge can cause a skid.**
- C. Brake hard as you change lanes so the liquid is pinned to the front wall of the tank.
- D. Speed up sharply during the lane change so the truck stays ahead of the liquid surge.

Answer: B — Move smoothly; sudden moves plus surge can cause a skid. (§8.2)

52. You're assigned a smooth-bore tanker for the first time. How should you treat following distance?

- A. Keep a shorter distance than usual because a liquid load helps the truck stop sooner.
- ✓ **B. Keep extra following distance and brake early because surge lengthens your stops.**
- C. Keep the same distance as a dry box, since liquids do not change stopping at all.
- D. Do not worry about distance; the tanker's weight alone will stop it quickly enough.

Answer: B — Smooth-bore surge is heavy; keep extra distance and brake early. (§8.2)

Doubles/Triples (T) Endorsement

52 questions

1. To pull two or three trailers you need:

- A. A passenger endorsement
- ✓ **B. A doubles/triples (T) endorsement**
- C. A tank endorsement
- D. No endorsement

Answer: B — The T endorsement is required to pull more than one trailer. (§7.1)

2. Compared with a single trailer, doubles and triples are:

- ✓ **A. Harder to control and more likely to roll**
- B. Much easier to control overall
- C. Lighter and a good deal slower
- D. Far less affected by side wind

Answer: A — More trailers mean more rollover and handling problems. (§7.1)

3. The unit that connects a second trailer to the first is the:

- ✓ **A. Converter dolly**
- B. Glad hand
- C. Tractor
- D. Kingpin

Answer: A — A converter dolly (tow bar, pintle, fifth wheel) couples the next trailer. (§7.2)

4. A sudden steering move with doubles can make the rear trailer:

- A. Gradually slow right down
- ✓ **B. Crack the whip and roll over**
- C. Stop short very suddenly
- D. Settle and sit lower

Answer: B — Rearward amplification ('crack the whip') can flip the last trailer. (§7.1)

5. To avoid the crack-the-whip effect, you should:

- A. Steer suddenly
- B. Brake hard
- ✓ **C. Steer gently and gradually**
- D. Speed up in turns

Answer: C — Smooth, gradual steering keeps the rear trailer stable. (§7.1)

6. On a double, the shut-off valve at the rear of the LAST trailer must be:

- A. Open
- ✓ **B. Closed**
- C. Removed
- D. Leaking

Answer: B — Shut-off valves are open on all trailers except the rear of the last one, which is closed. (§7.2)

7. The shut-off valves between trailers must be:

- A. Closed tight and shut off
- ✓ **B. Open so air reaches the rear trailers**
- C. Painted over completely
- D. Disconnected from the line

Answer: B — Valves between trailers stay open so air reaches the rear brakes. (§7.2)

8. Before driving doubles, make sure air reaches the:

- A. Radio
- ✓ **B. Rear trailer brakes**
- C. Headlights only
- D. Side mirrors

Answer: B — Charge the system and check that air gets to the last trailer before driving. (§7.3)

9. Doubles and triples need ___ room to stop and maneuver:

- A. Less
- B. No extra
- ✓ **C. More**
- D. Half the

Answer: C — They are longer and heavier, needing more room. (§7.1)

10. On a double, the trailer most likely to roll over is the:

- A. Front trailer
- ✓ **B. Rear (last) trailer**
- C. Tractor
- D. Converter dolly

Answer: B — The rear trailer feels the amplified motion and rolls most easily. (§7.1)

11. When coupling a converter dolly, the locking jaws must close on the:

- A. Tow bar
- ✓ **B. Trailer kingpin**
- C. Mud flap
- D. Tire

Answer: B — The dolly's fifth-wheel jaws must lock around the rear trailer's kingpin. (§7.2)

12. Safety chains on a converter dolly are there to:

- A. Decorate the dolly nicely
- ✓ **B. Hold the dolly if the coupling fails**
- C. Help carry extra cargo
- D. Cool the dolly brakes down

Answer: B — They secure the dolly to the trailer ahead if the pintle hook releases. (§7.2)

13. Which trailer should be loaded heaviest in a set?

- A. The rear trailer at the back
- B. The middle trailer of the set
- C. Either end loaded equally
- ✓ **D. The front trailer, nearest the tractor**

Answer: D — Put the heaviest trailer first (behind the tractor) and the lightest at the rear. (§7.3)

14. To check that air flows to the rear trailer, you:

- A. Honk the horn a few times
- ✓ **B. Open the emergency line and feel for air**
- C. Look closely at the paint
- D. Kick the trailer tire hard

Answer: B — Open the valve at the rear and confirm air comes through before connecting. (§7.3)

15. Backing a set of doubles is:

- A. Quite easy to do
- ✓ **B. Very difficult and usually avoided**
- C. Illegal in every state
- D. Just like backing a car

Answer: B — Doubles are extremely hard to back; avoid situations that require it. (§7.1)

16. When uncoupling a converter dolly, you should first:

- A. Drive away from it quickly
- ✓ **B. Secure the rear trailer and chock the wheels**
- C. Remove all of the tires
- D. Deflate the suspension air bags

Answer: B — Secure the rear trailer (landing gear down, wheels chocked) before releasing the dolly. (§7.2)

17. Glad hands connect the:

- ✓ **A. Air lines between units**
- B. Fuel lines
- C. Seat belts
- D. Trailer doors

Answer: A — Glad hands couple the service and emergency air lines. (§7.2)

18. If the glad hands are crossed, the trailer brakes will:

- A. Keep working normally
- ✓ **B. Not get the right air and may fail**
- C. Lock up forever
- D. Get noticeably stronger

Answer: B — Crossed air lines send air to the wrong system; brakes may fail. (§7.2)

19. In bad weather, doubles and triples should:

- A. Go faster
- B. Keep less space
- ✓ **C. Slow down more than usual**
- D. Brake hard once

Answer: C — Reduced traction plus length means slow down and add space. (§7.1)

20. Which statement about doubles and triples is TRUE?

- A. They stop quicker than a car
- ✓ **B. The rear trailer can crack the whip**
- C. Sudden steering is safe
- D. They need no extra space

Answer: B — The rear trailer amplifies motion; steer gently and keep space. (§7.1)

21. The pintle hook on the trailer ahead holds the dolly's:

- A. Kingpin
- ✓ **B. Tow bar eye**
- C. Mud flap
- D. Air tank

Answer: B — The pintle hook holds the dolly's tow bar eye to the trailer ahead. (§7.2)

22. ABS is required on converter dollies built on or after:

- A. 1990
- ✓ **B. 1998**
- C. 2005
- D. 2012

Answer: B — Dollies and trailers built on/after March 1, 1998 must have ABS. (§7.3)

23. When changing lanes with doubles, you should:

- A. Do it quickly and sharply
- ✓ **B. Make a slow, gradual move with room**
- C. Skip checking your mirrors
- D. Brake hard first

Answer: B — Gradual lane changes prevent the rear trailer from swinging. (§7.1)

24. The greatest danger of turning too fast with doubles is:

- A. Better mileage
- ✓ **B. Rolling the rear trailer**
- C. Faster stopping
- D. Less tire wear

Answer: B — Excess turn speed rolls the amplified rear trailer. (§7.1)

25. After coupling, you should check the connection by:

- A. Driving off with it at once
- ✓ **B. A gentle pull test against the locked unit**
- C. Honking the horn twice
- D. Repainting the whole unit

Answer: B — A gentle tug confirms the jaws and pintle are locked before the road. (§7.2)

26. Triples are ___ doubles to handle:

- A. Easier than
- B. The same as
- ✓ **C. Even harder than**
- D. No different from

Answer: C — A third trailer increases length, rollover risk, and crack-the-whip. (§7.1)

27. When you inspect a converter dolly, check its:

- A. The loud cab radio
- ✓ **B. Tires, lights, and air lines**
- C. The exterior paint color
- D. The vinyl seat covers

Answer: B — Inspect the dolly's tires, lights, and air lines like any other part. (§7.2)

28. A set of triples has how many trailers?

- A. One
- ✓ **B. Three**
- C. Two
- D. Five

Answer: B — Triples means three trailers behind the tractor. (§7.1)

29. The more trailers you pull, the rig is ___ to stop:

- A. Easier
- ✓ **B. Harder**
- C. Faster
- D. Lighter

Answer: B — More trailers mean more weight and length, so it is harder to stop. (§7.1)

30. When inspecting a double, make sure the trailers are:

- A. Freshly painted nice
- ✓ **B. Securely coupled and locked**
- C. Completely empty inside
- D. Cold to the touch

Answer: B — Check that every trailer is securely coupled and locked before driving. (§7.2)

31. On a double, the supply (emergency) air must reach:

- A. Only the front trailer
- ✓ **B. All the trailers**
- C. None of the trailers
- D. Only the cab

Answer: B — Air must reach all trailers' brakes before you drive. (§7.2)

32. To couple a second trailer, the converter dolly goes:

- A. On the cab roof top
- ✓ **B. In front of the second trailer**
- C. Behind everything else
- D. Tucked inside the cab

Answer: B — Place the dolly in front of the second trailer to couple it. (§7.2)

33. When uncoupling a rear trailer, lower its landing gear:

- A. Only about halfway
- ✓ **B. Until it supports the trailer**
- C. Not at all down
- D. Down onto the dolly

Answer: B — Lower the landing gear until it supports the trailer before releasing it. (§7.2)

34. Doubles and triples give you more:

- A. Better fuel economy always
- ✓ **B. Length and blind spots to manage**
- C. Comfort and quiet ride
- D. A higher top speed

Answer: B — They are longer with more blind spots to watch. (§7.1)

35. In strong crosswinds, pulling trailers:

- A. Has no real effect
- ✓ **B. Can push the rig — drive with care**
- C. Speeds you right up
- D. Improves your road grip

Answer: B — Crosswinds can push a multi-trailer rig; slow down and steer carefully. (§7.1)

36. When connecting, keep the air and electrical lines from:

- A. Being too clean
- ✓ **B. Dragging or tangling**
- C. Being cut short
- D. Being too colorful

Answer: B — Secure the lines so they don't drag, tangle, or get pinched. (§7.2)

37. If you must back a set of doubles, it is best to:

- A. Do it very quickly
- ✓ **B. Avoid it or use a spotter**
- C. Close both your eyes
- D. Skip all the mirrors

Answer: B — Backing doubles is very hard; avoid it or use a helper to guide you. (§7.1)

38. The dolly's air lines connect to the trailer ahead with:

- A. A rope
- ✓ **B. Glad hands**
- C. A chain
- D. A magnet

Answer: B — Glad hands couple the dolly's air lines to the trailer ahead. (§7.2)

39. A double rolls more easily than a single because of its:

- A. Its bright paint color
- ✓ **B. Length and rearward amplification**
- C. Its very light weight
- D. Its small overall size

Answer: B — Length and the crack-the-whip effect make the rear trailer roll easily. (§7.1)

40. Keep extra space around a long combination so you can:

- A. Drive a lot faster
- ✓ **B. Stop and maneuver safely**
- C. Tailgate up closely
- D. Skip using signals

Answer: B — A longer rig needs more room to stop and maneuver. (§7.1)

41. Triples are legal only where:

- A. Just about everywhere
- ✓ **B. State law allows them**
- C. Almost never at all
- D. Only late at night

Answer: B — Some states do not allow triples; obey state law. (§7.1)

42. On turns with a long combination, you should:

- A. Turn early and sharp
- ✓ **B. Swing wider, watch the trailer**
- C. Skip signaling first
- D. Speed up through it

Answer: B — Swing wider and watch the trailer's path because the rear wheels off-track. (§7.1)

43. You're coupling a second trailer to make a set of doubles. Which trailer should be in front?

- A. Put the lightest trailer first and the heaviest one at the very back of the set there.
- ✓ **B. Put the more heavily loaded trailer first, right behind the tractor, for stability.**
- C. It does not matter where each trailer goes; couple them in whatever order is easy.
- D. Always put the empty trailer in front so the loaded one pushes it down the road.

Answer: B — The more heavily loaded trailer goes first, right behind the tractor. (§7.1)

44. You are driving a set of doubles and a strong crosswind hits. How does the rig respond?

- A. It is more stable than a single trailer, so wind has no real effect on it at all here.
- ✓ **B. The rear trailer can sway and 'crack the whip,' so slow down and steer smoothly.**
- C. The wind pushes the front trailer down so hard that the rear cannot move at all.
- D. Nothing happens because the two trailers cancel out any wind force between them.

Answer: B — The rear trailer can sway and crack the whip; slow down and steer smoothly. (§7.2)

45. Before pulling a set of doubles, you must charge the air in the rear trailer. What must you check?

- A. That the shut-off (cut-out) valves at the back of the rear trailer are left wide open.
- ✓ **B. That the shut-off valves are open between trailers but closed at the very last trailer.**
- C. That all the valves on every trailer are fully closed so no air can escape at all here.
- D. Nothing; the air reaches all trailers automatically no matter how the valves are set.

Answer: B — Valves open between trailers, closed on the last trailer. (§7.3)

46. You make a sudden steering move in a triples set to avoid a hazard. What is the danger?

- A. The last trailer barely moves, so a quick jerk of the wheel is perfectly safe to do.
- ✓ **B. Rearward amplification can flip the last trailer; steer gently and avoid quick moves.**
- C. All three trailers move as one solid unit, so there is no extra risk from steering.
- D. The tractor will spin out first, long before the rear trailers feel anything at all.

Answer: B — Rearward amplification can throw the last trailer; steer gently. (§7.2)

47. You need extra following distance in a long doubles set. Why?

- A. A long combination stops faster than a single, so you actually need less distance.
- ✓ **B. It is longer and heavier and takes more room to stop, so keep extra distance ahead.**
- C. Following distance does not change with length; keep the same gap as a small truck.
- D. You can tailgate safely because the extra trailers add braking power at the rear end.

Answer: B — Longer and heavier means more stopping room; keep extra distance. (§7.2)

48. You are inspecting a doubles set and check the converter dolly. What should you confirm?

- A. Only that the dolly is painted to match, since it has no effect on safe towing at all.
- ✓ **B. That the pintle hook is latched, the safety chains are secure, and air lines connect.**
- C. That the dolly tires are fully bald so the trailer rides lower for better stability now.
- D. Nothing; a converter dolly never needs to be inspected before pulling a set of doubles.

Answer: B — Pintle hook latched, safety chains secure, air lines connected. (§7.4)

49. You're about to back a set of doubles. What is the recommended practice?

- A. Back the full set quickly in a long, smooth motion since doubles back like a single.
- ✓ **B. Avoid backing doubles if you can; they are very hard to control in reverse, so go slow.**
- C. Back at full speed so the trailers stay perfectly straight behind the tractor the whole time.
- D. Push hard on the throttle so the rear trailer steers itself into the spot you want it.

Answer: B — Avoid backing doubles; they are very hard to control in reverse. (§7.4)

50. You finish coupling the converter dolly and second trailer. How do you check the connection is locked?

- A. Assume it is fine if it looks connected and drive off without testing it any further now.
- ✓ **B. Do a tug test by pulling gently against the locked trailer to confirm it is held secure.**
- C. Bounce the trailer up and down by hand and trust that motion means it is locked in place.
- D. Only check the lights; if the trailer lights work, the coupling must be locked too then.

Answer: B — Confirm with a tug test against the locked trailer. (§7.4)

51. You're assigned a triples set and the road has sharp curves. How should you take them?

- A. Take the curves at the posted speed since three trailers track straight through them.
- ✓ **B. Slow down extra and steer smoothly, because the rear trailers swing wide and amplify.**
- C. Speed up through curves so the trailers are pulled straight and cannot swing at all here.
- D. Brake hard in each curve so the rear trailer is forced to follow the front one exactly.

Answer: B — Slow extra and steer smoothly; rear trailers swing wide. (§7.2)

52. One of the trailers in your doubles set starts to skid. Which trailer is most likely to swing out?

- A. The front trailer always swings first because it carries the heaviest part of the load.
- ✓ **B. The rear trailer is most likely to swing out from rearward amplification, so ease off.**
- C. Neither trailer can swing because the dolly locks them both perfectly in line always.
- D. The tractor swings out first, and the trailers simply follow wherever it goes calmly.

Answer: B — The rear trailer most likely swings out due to rearward amplification. (§7.2)

1. The passenger (P) endorsement is required to drive:

- ✓ **A. A bus carrying enough passengers**
- B. An ordinary pickup truck
- C. A two-wheeled motorcycle
- D. An empty box trailer

Answer: A — The P endorsement is needed for a bus designed to carry the threshold number of passengers. (§4.1)

2. During the pre-trip, passenger items you must check include:

- A. The favourite local radio station
- ✓ **B. Handrails, seats, exits, and signaling devices**
- C. The exterior body paint color
- D. The plastic drink cup holders

Answer: B — Check passenger safety equipment before driving. (§4.2)

3. Riders may NOT stand:

- A. Near the rear seats
- ✓ **B. Forward of the standee line**
- C. Anywhere on the bus
- D. By the windows

Answer: B — No passenger may stand ahead of the standee line (rear of the driver's seat). (§4.3)

4. Most hazardous materials are:

- ✓ **A. Forbidden on buses, with few exceptions**
- B. Allowed freely on any bus
- C. Required on every bus
- D. Stored safely under the seats

Answer: A — Buses may carry only small specified amounts of certain materials. (§4.2)

5. Carry-on baggage must be secured so it does not:

- A. Look untidy or messy
- B. Touch the nearby seats
- ✓ **C. Block the aisle or doorway**
- D. Get cold during the trip

Answer: C — Keep aisles and exits clear so passengers can move and exit. (§4.2)

6. At a railroad crossing, a bus must:

- A. Speed across
- ✓ **B. Stop, look, and listen before crossing**
- C. Honk and go
- D. Change gears on the tracks

Answer: B — Buses stop 15-50 ft before the tracks, look and listen, and don't shift while crossing. (§4.3)

7. While crossing railroad tracks, you should:

- A. Shift to a lower gear
- ✓ **B. Not change gears**
- C. Stop on the tracks
- D. Reverse over them

Answer: B — Don't shift gears while on the tracks, to avoid stalling. (§4.3)

8. At a drawbridge with no signal or attendant, a bus must:

- A. Cross over at full speed
- B. Honk the horn twice and go
- ✓ **C. Stop about 50 feet before and check it is safe**
- D. Follow the car ahead very closely

Answer: C — Stop ~50 ft before and verify the bridge is closed and safe. (§4.3)

9. A transit bus brake-door interlock:

- A. Locks the steering wheel
- ✓ **B. Applies the brakes when the doors open**
- C. Plays background music
- D. Opens the engine hood

Answer: B — It holds the bus while rear doors are open; don't use it as a parking brake. (§4.4)

10. You should announce stops:

- ✓ **A. Clearly and in advance**
- B. Never
- C. Only at the very end
- D. Only at night

Answer: A — Announce stops and major points so passengers are ready. (§4.3)

11. If a passenger is disruptive, you should:

- A. Stop on a busy highway and remove them
- ✓ **B. Discharge them only at a safe place**
- C. Speed up to scare them
- D. Ignore all safety

Answer: B — Don't put riders off where it's unsafe; use a stop or safe, well-lit location. (§4.3)

12. The standee line marks:

- A. The emergency exit row
- ✓ **B. How far forward riders may stand**
- C. Where the riders should sit
- D. The current fuel level

Answer: B — It shows the limit; no standing forward of that line. (§4.3)

13. After the trip ends, you should check the bus for:

- A. Better mileage
- B. New paint
- ✓ **C. Sleeping riders and left items**
- D. Lower tire pressure

Answer: C — Walk through for sleeping passengers and articles left behind. (§4.3)

14. Buses should be fueled:

- A. With passengers aboard always
- ✓ **B. Not with riders aboard when possible**
- C. Only while moving
- D. Never at all

Answer: B — Avoid fueling with passengers aboard; never in a closed building with riders. (§4.2)

15. Emergency exits on a bus must be:

- A. Blocked for safety
- ✓ **B. Marked and usable**
- C. Painted shut
- D. Removed

Answer: B — Keep emergency exits clear, marked, and working. (§4.2)

16. Which of these is NOT allowed on a bus?

- A. Small-arms ammunition
- B. Emergency hospital supplies
- ✓ **C. Large amounts of explosives**
- D. A few labeled medical items

Answer: C — Buses can't carry large hazardous loads like explosives; only limited exceptions. (§4.2)

17. Passengers should board and get off:

- A. While the bus moves
- ✓ **B. Only when the bus is stopped**
- C. Through the windows
- D. Out on the highway

Answer: B — Riders get on and off only when the bus is fully stopped. (§4.3)

18. Charter (group) passengers should:

- A. Get off anywhere
- B. Be allowed to drive
- C. Open the exits en route
- ✓ **D. Stay aboard until the destination**

Answer: D — Don't let charter riders off except at the destination unless an emergency. (§4.3)

19. A bus's speed and following distance should be:

- A. Just like a small sports car
- ✓ **B. Managed like other large, heavy vehicles**
- C. Ignored entirely on the road
- D. Always kept at the maximum

Answer: B — Buses are large and heavy; keep space and control speed like other CMVs. (§4.3)

20. Which statement about driving a bus is TRUE?

- A. Riders are allowed to stand anywhere they like
- ✓ **B. Stop at railroad crossings and check for riders after the trip**
- C. Hazmat amounts carried are completely unlimited
- D. You may fuel freely with riders aboard the bus

Answer: B — Stop at crossings, keep exits clear, and check the bus after the route. (§4.3)

21. Keeping riders behind the standee line helps:

- A. Save a little bit of fuel
- ✓ **B. Protect them during sudden stops**
- C. Play some background music
- D. Open the rear doors

Answer: B — It reduces injury risk in a hard stop. (§4.3)

22. At a railroad crossing, stop:

- A. Right on top of the railroad tracks
- ✓ **B. Between 15 and 50 feet before the nearest rail**
- C. Right up against the nearest rail
- D. A good full 100 yards away

Answer: B — Stop no closer than 15 ft and no farther than 50 ft from the nearest rail. (§4.3)

23. A bus must be inspected:

- A. Never
- ✓ **B. Before each trip**
- C. Once a year only
- D. Only after a crash

Answer: B — Do a pre-trip inspection, including passenger safety items, before each trip. (§4.2)

24. Talking with passengers while driving should be:

- A. Constant and detailed
- ✓ **B. Limited so you stay focused**
- C. Done with eyes closed
- D. Through a megaphone always

Answer: B — Avoid distractions; keep conversation minimal while moving. (§4.3)

25. Make sure passengers are seated or secure before:

- A. Turning off the radio
- ✓ **B. Putting the bus in motion**
- C. Reading a map
- D. Closing the windows

Answer: B — Riders should be safe aboard before the bus moves. (§4.3)

26. At stops, a bus driver must watch for:

- A. Passing birds overhead
- B. Clouds in the sky
- C. Loud music nearby
- ✓ **D. Riders crossing in front of the bus**

Answer: D — Watch for people crossing in front and pedestrians at stops. (§4.3)

27. Standing passengers should hold:

- A. Onto nothing
- ✓ **B. A handrail or strap**
- C. Onto the driver
- D. Onto a window

Answer: B — Standing riders should hold a handrail or strap for safety. (§4.3)

28. Seats and seat frames on a bus must be:

- A. Loose and shaky
- ✓ **B. Secure and fastened**
- C. Removed entirely
- D. Wet inside

Answer: B — Seats and frames must be secure and fastened. (§4.2)

29. The aisle of a bus must be kept:

- A. Blocked with bags
- ✓ **B. Clear**
- C. Wet and slick
- D. Dark

Answer: B — Keep the aisle clear so riders can move and exit. (§4.2)

30. A bus driver should accelerate and brake:

- A. Hard and fast
- ✓ **B. Smoothly and gently**
- C. With eyes closed
- D. Only when downhill

Answer: B — Smooth, gentle braking keeps passengers safe and comfortable. (§4.3)

31. If a rider becomes ill or there is an emergency, the driver should:

- A. Just ignore it
- ✓ **B. Stop safely and help**
- C. Speed up fast
- D. Open the roof hatch

Answer: B — Stop in a safe place and get help when needed. (§4.3)

32. Passengers should keep their arms and heads:

- A. Out the windows
- ✓ **B. Inside the bus**
- C. On the driver
- D. Out the door

Answer: B — Riders must keep arms and heads inside the bus. (§4.3)

33. A bus's emergency equipment includes a fire extinguisher and:

- A. A small flat TV
- ✓ **B. Exits and warning devices**
- C. A cold drinks fridge
- D. Plain window curtains

Answer: B — A bus must have emergency exits and warning devices too. (§4.2)

34. When approaching a bus stop, you should:

- A. Speed right past it
- ✓ **B. Slow and pull in safely**
- C. Stop out in a lane
- D. Just honk the horn

Answer: B — Slow down and pull in safely so riders can board. (§4.3)

35. The maximum number of standees may be set by:

- A. The driver's own mood
- ✓ **B. State and local rules**
- C. The loud cab radio
- D. The day's bad weather

Answer: B — State and local rules may limit the number of standing riders. (§4.3)

36. Before moving the bus from a stop, the driver should:

- A. Honk the horn
- ✓ **B. Close doors and check mirrors**
- C. Open the roof hatch
- D. Rev the engine hard

Answer: B — Close the doors and check mirrors before pulling away. (§4.3)

37. The driver should not allow riders to:

- A. Sit down quietly there
- ✓ **B. Stand in the doorway/stairwell**
- C. Hold a handrail tight
- D. Look out a side window

Answer: B — No rider should stand in the doorway or on the stairwell. (§4.3)

38. If the bus breaks down, riders should usually:

- A. Walk on the highway
- ✓ **B. Stay seated until it's safe**
- C. Push the bus along
- D. Climb out the windows

Answer: B — Keep riders seated until it is safe to move them. (§4.3)

39. Passengers should board the bus through:

- A. Through a side window
- ✓ **B. The proper doorway when stopped**
- C. The roof escape hatch
- D. The hot engine area

Answer: B — Riders board through the proper doorway when the bus is stopped. (§4.3)

40. The driver should scan mirrors and the road to spot:

- A. Only nice scenery
- ✓ **B. Hazards and pedestrians**
- C. Local radio stations
- D. Shapes in the clouds

Answer: B — Watch for hazards and pedestrians around the bus. (§4.3)

41. A driver carrying passengers may NOT:

- A. Wear a proper seat belt
- ✓ **B. Use a hand-held phone while driving**
- C. Adjust the side mirrors
- D. Check the bus tires

Answer: B — Using a hand-held phone while driving a bus is prohibited. (§4.3)

42. Good service plus safety means the driver should:

- A. Drive recklessly fast
- ✓ **B. Be courteous and drive safely**
- C. Skip all the stops
- D. Speed between the stops

Answer: B — Be courteous to riders while driving safely. (§4.3)

43. You are loading passengers at a stop and one wants to bring a car battery aboard. What should you do?

- A. Allow it, since passengers may bring anything they can carry onto the bus with them.
- ✓ **B. Refuse it; car batteries and other hazardous materials are not allowed on the bus.**
- C. Store it next to the fuel tank where it will be out of the aisle and the passengers.
- D. Put it in an overhead rack above a passenger's seat so it stays out of the aisle there.

Answer: B — Car batteries and other hazardous materials are not allowed aboard with passengers. (§4.1)

44. A standee on your moving bus is leaning forward of the standee line as you drive. What should you do?

- A. Keep driving since a passenger standing forward of the line does not affect safety.
- ✓ **B. Do not move the bus until the passenger is behind the standee line where it is safe.**
- C. Speed up so the trip ends sooner and the passenger can sit down at the next stop.
- D. Open the front door while driving so the passenger has more room to step backward.

Answer: B — Don't move until all standees are behind the standee line. (§4.2)

45. You're approaching a railroad crossing in a loaded passenger bus. What must you do?

- A. Roll across at normal speed since buses are allowed to cross without ever stopping.
- ✓ **B. Stop 15 to 50 feet before the tracks, look and listen, then cross without shifting gears.**
- C. Stop on the tracks and open the door so you can listen better for a coming train now.
- D. Speed up to clear the tracks quickly because a bus full of people is very heavy indeed.

Answer: B — Stop 15-50 ft before the tracks, then cross without shifting. (§4.3)

46. At the end of your route, all passengers appear to have left the bus. What should you do?

- A. Lock up and leave right away since everyone clearly got off at their own stops already.
- ✓ **B. Walk the whole bus to check for sleeping riders and items left behind before leaving.**
- C. Just glance in the mirror from the driver's seat, which is enough to see the whole bus.
- D. Ask the last passenger off whether anyone is still aboard and trust whatever they say.

Answer: B — Walk the bus to check for sleeping riders and forgotten items. (§4.4)

47. A disruptive passenger is causing a serious safety problem on your moving bus. What should you do?

- A. Open the door and ask them to step off while the bus is still moving down the road.
- ✓ **B. Stop at a safe place and remove the rider there, not in a hazardous or unsafe spot.**
- C. Speed up to your destination so security can deal with the rider when you arrive there.
- D. Ignore the behavior completely and keep driving your normal route without any change.

Answer: B — Remove a disruptive rider only at a safe place. (§4.2)

48. You are doing a pre-trip inspection on your bus. What passenger-specific items must you check?

- A. Only the engine oil and the tires, since a bus checks out like any other vehicle does.
- ✓ **B. Handrails, seats, emergency exits, and signaling devices must all be in good order.**
- C. Just the outside paint and the destination sign so the bus looks ready for service now.
- D. Nothing special at all; a passenger bus needs the same checks as an empty box truck.

Answer: B — Check handrails, seats, emergency exits, and signaling devices. (§4.1)

49. You arrive at a bus stop but it is crowded and unsafe to pull all the way in. What should you do?

- A. Double-park in the travel lane and load there since the marked stop is too crowded now.
- ✓ **B. Load only where you can stop safely, and never where it puts the riders in real danger.**
- C. Tell waiting riders to run out into the street to board your bus from the traffic lane.
- D. Skip every safety concern and just board everyone as fast as you possibly can today.

Answer: B — Load only where it is safe; never where it endangers riders. (§4.2)

50. Common-carrier rules: a rider asks to get off between regular stops on a rural road. What governs this?

- A. You may stop anywhere a rider asks, regardless of whether the spot is safe or legal.
- ✓ **B. Stop only at safe, proper locations; do not discharge riders in unsafe or illegal spots.**
- C. Always refuse; a bus may never let anyone off except at the final destination terminal.
- D. Let them jump off while moving slowly so you do not have to make a full stop at all.

Answer: B — Discharge passengers only at safe, proper locations. (§4.2)

51. You notice a brake problem on your bus before the run. What should you do?

- A. Drive the route anyway since a bus full of waiting passengers cannot be delayed at all.
- ✓ **B. Do not carry passengers until the brake problem is repaired and the bus is safe again.**
- C. Carry only half the usual passengers so the lighter load makes up for the weak brakes.
- D. Drive slowly the whole way and pump the brakes often to make up for the problem today.

Answer: B — Never carry passengers until the brake problem is repaired. (§4.1)

52. You're driving a transit bus and must brake for a stop with standees aboard. How should you brake?

- A. Brake hard and late so the bus stops quickly and you keep right on your tight schedule.
- ✓ **B. Brake smoothly and early so standing passengers are not thrown forward and injured here.**
- C. Pump the brakes sharply several times so the standees grab the rails and hold on tight.
- D. Brake only at the very last second so the bus lurches and wakes up the sleeping riders.

Answer: B — Brake smoothly and early so standees aren't thrown forward. (§4.3)

1. To drive a school bus you need the S endorsement plus:

- ✓ **A. The passenger (P) endorsement**
- B. A motorcycle license
- C. A tank endorsement
- D. Nothing else

Answer: A — School bus drivers need both the P and S endorsements. (§10.1)

2. The most dangerous part of a school bus route is:

- ✓ **A. Loading and unloading students**
- B. The open highway stretches
- C. Empty highway driving
- D. Quiet roadside parking

Answer: A — Most school-bus injuries happen in the danger zone during loading and unloading. (§10.2)

3. The danger zone around a school bus extends about:

- A. 1 foot
- ✓ **B. 10 feet around the bus**
- C. 100 yards
- D. No real distance

Answer: B — The danger zone is up to 10 ft on all sides where the driver may not see students. (§10.2)

4. Mirrors that show the danger zones and students are:

- A. No outside mirrors installed at all
- B. Only one small flat side mirror
- C. Just a single rear-view camera
- ✓ **D. Flat and convex mirrors, including crossover**

Answer: D — Use the left/right flat, convex, and crossover mirrors to see around the bus. (§10.2)

5. As you approach a stop, you first activate the:

- A. Red flashing lights
- ✓ **B. Amber (yellow) warning lights**
- C. The stop arm
- D. The horn

Answer: B — Activate amber lights about 200 ft (or per state law) before the stop, then red at the stop. (§10.3)

6. At the stop, you turn on the red lights and:

- A. The wipers
- B. The defroster
- ✓ **C. The stop arm**
- D. The radio

Answer: C — Red lights and the extended stop arm tell traffic to stop while students load and unload. (§10.3)

7. Students should board or leave only after the bus is:

- A. Slowing down
- ✓ **B. Completely stopped**
- C. Still turning
- D. Backing up

Answer: B — Never let students approach until the bus is fully stopped. (§10.3)

8. Students who must cross the road should walk:

- A. Behind the parked bus
- B. Between the bus wheels
- ✓ C. In front where you can see them
- D. On the far road shoulder

Answer: C — Have them cross about 10 ft in front so you can see them. (§10.3)

9. Backing a school bus is:

- A. Encouraged at stops
- ✓ B. Dangerous and should be avoided
- C. Required at each stop
- D. Safe with students aboard

Answer: B — Avoid backing; if unavoidable, use a lookout. (§10.4)

10. At a railroad crossing, a school bus must:

- A. Speed across
- ✓ B. Stop, open the door, look and listen
- C. Honk and go
- D. Shift gears on the tracks

Answer: B — Stop 15-50 ft before, open the door/window, look and listen, then cross without shifting. (§10.3)

11. After the route, the driver must:

- A. Leave the bus immediately
- B. Lock the doors and drive off
- ✓ C. Walk through to check for sleeping children
- D. Refuel the bus only

Answer: C — A post-trip child check finds sleeping children and left items. (§10.4)

12. The crossover mirrors are used to see:

- A. The engine sitting under the hood
- ✓ B. The danger zone right in front of the bus
- C. The wide open sky up above
- D. The dashboard fuel level gauge

Answer: B — Crossover mirrors show the area directly in front, where small children can hide. (§10.2)

13. If you cannot see a student who left the bus, you should:

- A. Drive away slowly anyway
- B. Just honk and go on
- C. Speed up a little
- ✓ D. Stop, set the brake, and find them

Answer: D — Never move until you know where every student is. (§10.3)

14. The amber warning lights tell drivers the bus is:

- A. Turning around nearby
- ✓ B. About to stop to load or unload
- C. Out of service today
- D. Speeding down the road

Answer: B — Amber means the bus is preparing to stop; red means stopped and loading. (§10.3)

15. Which statement about loading students is TRUE?

- A. Let them all run quickly to the bus
- B. Back the bus up to go and reach them
- ✓ **C. Have them wait, board when stopped, and cross in front**
- D. Skip counting the students at the stop

Answer: C — Students wait, board when stopped, and cross in front where visible. (§10.3)

16. Tail swing on a school bus means the rear:

- A. Stays in place
- ✓ **B. Swings out when turning**
- C. Lifts up
- D. Gets shorter

Answer: B — The rear swings out in turns; watch clearance to objects and people. (§10.4)

17. Using a hand-held cell phone while driving is:

- A. Encouraged
- ✓ **B. Prohibited and unsafe**
- C. Required by law
- D. Fine at stops only

Answer: B — Don't use a hand-held phone; it is a dangerous distraction and generally prohibited. (§10.4)

18. Emergency exits on a school bus should be:

- A. Blocked off for safety
- ✓ **B. Checked and kept usable**
- C. Painted firmly shut
- D. Tied tightly closed

Answer: B — Inspect and keep all emergency exits working for evacuation. (§10.2)

19. When students are in the danger zone, you should:

- A. Start moving the bus forward
- B. Rev the engine loudly twice
- C. Close up the side mirrors
- ✓ **D. Not move until they are clear and seated**

Answer: D — Keep the bus stopped until all students are out of the danger zone and seated. (§10.2)

20. Strobe lights, where equipped, are most useful in:

- A. Bright midday sun
- ✓ **B. Low visibility such as fog**
- C. Wide empty parking lots
- D. Inside tunnels only

Answer: B — A roof strobe helps others see the bus in fog or low visibility. (§10.4)

21. To evacuate the bus in an emergency, the driver should:

- ✓ **A. Direct an orderly evacuation to a safe place**
- B. Tell students to stay seated always
- C. Leave first themselves
- D. Open only one window

Answer: A — Lead an orderly evacuation away from hazards to a safe location. (§10.5)

22. You should count students at the stop so you:

- A. Can know the fuel use
- ✓ **B. Can confirm they all cross and are clear**
- C. Can speed up sooner
- D. Can skip checking the mirrors

Answer: B — Counting helps confirm every student crossed and is clear before moving. (§10.3)

23. Pre-trip on a school bus must include:

- ✓ **A. Mirrors, lights, stop arm, and emergency exits**
- B. Only the bus tires and wheels
- C. Just the cab radio and horn
- D. Nothing special needs checking

Answer: A — Check mirrors, warning lights, stop arm, and exits before each route. (§10.2)

24. If a student drops something near the bus, they should:

- A. Reach under the parked bus
- ✓ **B. Never go after it and tell the driver**
- C. Crawl under to get it
- D. Wait behind a rear wheel

Answer: B — Students must never reach under or near the wheels; tell the driver. (§10.3)

25. Red flashing lights and the stop arm require other traffic to:

- A. Pass quickly
- B. Honk
- ✓ **C. Stop**
- D. Speed up

Answer: C — Traffic must stop for the red lights and extended stop arm while students load or unload. (§10.3)

26. When unsure where a child is, the safest practice is:

- A. Assume that they are safe
- ✓ **B. Do not move until you have located them**
- C. Drive slowly forward anyway
- D. Sound the horn and go on

Answer: B — Never move until every child is accounted for. (§10.3)

27. The danger zone is dangerous because the driver:

- A. Can see everything clearly
- ✓ **B. May not see small children there**
- C. Is sound fast asleep
- D. Is parked and stopped

Answer: B — Small children can be in the danger zone where the driver cannot see them. (§10.2)

28. Before students cross, the driver should make eye contact and:

- A. Look away from them
- ✓ **B. Signal when it's clear to cross**
- C. Honk the horn loudly
- D. Speed up quickly

Answer: B — Make eye contact and signal students only when it is clear and safe to cross. (§10.3)

29. The convex mirrors on a school bus show:

- A. Just the open clear sky
- ✓ **B. A wider but smaller side view**
- C. Nothing useful at all
- D. Only the engine bay area

Answer: B — Convex mirrors give a wider view, but objects look smaller and farther. (§10.2)

30. School buses must stop at railroad crossings even when:

- ✓ **A. No train is in sight**
- B. Only when a train comes
- C. Only late at night
- D. They never must stop

Answer: A — Stop at the tracks even if no train is in sight. (§10.3)

31. When loading, students should approach the bus:

- A. From right behind the bus
- ✓ **B. From where the driver can see**
- C. From between the wheels
- D. From under the bus body

Answer: B — Students should come from where the driver can see them. (§10.3)

32. You should release students to cross only:

- A. Before the bus fully stops
- ✓ **B. After traffic stops and it's safe**
- C. While it is still moving
- D. They never may cross

Answer: B — Let students cross only after traffic stops and it is safe. (§10.3)

33. An item left on a seat is found during:

- A. During the fueling stop
- ✓ **B. The post-trip walk-through**
- C. During a sharp turn
- D. While backing it up

Answer: B — The post-trip walk-through catches items left behind. (§10.4)

34. Students should remain seated:

- A. Only at the bus stops
- ✓ **B. While the bus is moving**
- C. Never at all ever
- D. Standing up is just fine

Answer: B — Keep students seated while the bus is moving. (§10.3)

35. Loading or unloading on a multi-lane road, the driver uses:

- A. No warning lights at all
- ✓ **B. Amber then red warning lights**
- C. Only the loud air horn
- D. Bright high-beam lights

Answer: B — Use amber, then red warning lights, at stops. (§10.3)

36. School bus seats protect students using:

- A. Hard metal bench seats
- ✓ **B. Compartmentalized padded seats**
- C. No seats at all inside
- D. Plain breakable glass seats

Answer: B — Compartmentalization (closely spaced, padded high backs) protects students. (§10.2)

37. If a railroad crossing gate is down, you must:

- A. Drive around the gate
- ✓ **B. Stop and wait**
- C. Honk and cross over
- D. Reverse away fast

Answer: B — Never go around a lowered gate; stop and wait. (§10.3)

38. Drivers who illegally pass a stopped school bus should be:

- A. Ignored and forgotten
- ✓ **B. Reported as required**
- C. Rewarded somehow
- D. Hidden from view

Answer: B — Report illegal passing of a stopped school bus. (§10.3)

39. Students waiting at a stop should stand:

- A. Right out in the road
- ✓ **B. Back from the road until it stops**
- C. On the front bumper
- D. Just behind the rear wheels

Answer: B — Waiting students stay back from the road until the bus stops. (§10.3)

40. A roof hatch on a school bus is used as:

- A. A handy sunroof
- ✓ **B. An emergency exit**
- C. Extra storage space
- D. A vent opening only

Answer: B — The roof hatch is an emergency exit. (§10.5)

41. A school bus driver should avoid distractions such as:

- A. Watching the road ahead
- ✓ **B. Eating or using a phone**
- C. Checking the mirrors
- D. Counting the students

Answer: B — Avoid eating or using a phone while driving. (§10.4)

42. The most important goal for a school bus driver is:

- A. Going fast
- ✓ **B. Student safety**
- C. Loud music
- D. A spotless clean bus

Answer: B — Student safety is the most important goal. (§10.1)

43. You are approaching a school bus stop to pick up children. When should you activate your flashing amber lights?

- A. Only after the children have already started walking out toward the bus in the road.
- ✓ **B. About 200 feet (or as your state requires) before the stop to warn traffic you will stop.**
- C. Never use amber lights; just stop and switch straight to the red flashing lights at once.
- D. Only at night, since amber warning lights are not needed during the daytime hours at all.

Answer: B — Turn on amber lights ~200 ft before the stop (or as your state requires). (§10.2)

44. Children have unloaded and one drops a book under the front of the bus. What should you do?

- A. Pull away slowly since the child will surely move out of the way of the bus in time.
- ✓ **B. Do not move; signal the child to a safe spot and make sure they are clear and seen by you.**
- C. Honk loudly and start rolling so the child knows to hurry up and grab their book fast.
- D. Close the door and drive on; a dropped book is not the bus driver's concern at all here.

Answer: B — Don't move; direct the child to safety and confirm they are clear and visible. (§10.3)

45. You are loading students with the red flashing lights on. When may you turn them off and go?

- A. As soon as the first student steps onto the bus, even if others are still crossing now.
- ✓ **B. Only after all students are aboard or clear and across, and the danger zone is empty.**
- C. Whenever the traffic behind you gets impatient and starts honking for you to move along.
- D. Right after you open the door, since the red lights are only needed for the first second.

Answer: B — Keep red lights on until all students are aboard or safely across. (§10.3)

46. A student needs to cross the road in front of your school bus. What should you have them do?

- A. Cross close to the rear of the bus where you cannot see them in your mirrors at all now.
- ✓ **B. Walk well ahead of the bus where you can see them, and wait for your hand signal first.**
- C. Run across quickly behind the bus so the waiting traffic can get moving again much sooner.
- D. Cross whenever they want without any signal, since children know when it is safe to go.

Answer: B — Have crossing students walk well ahead where you can see them and wait for your signal. (§10.3)

47. You are doing your school bus pre-trip inspection. What is especially important to check?

- A. Only the fuel level and the radio, since a school bus drives like any other vehicle does.
- ✓ **B. Mirrors, the stop arm, the flashing lights, and emergency exits must all work correctly.**
- C. Just the paint color so the bus matches the rest of the district's bus fleet outside there.
- D. Nothing extra; a school bus needs the same checks as an ordinary empty cargo van does.

Answer: B — Check mirrors, stop arm, flashing lights, and emergency exits. (§10.1)

48. While driving your route, you must cross railroad tracks with students aboard. What must you do?

- A. Cross at normal speed without stopping since the bus is on a fixed daily schedule now.
- ✓ **B. Stop, open the door, look and listen, then cross in a low gear without shifting on tracks.**
- C. Stop right on the tracks so you can roll the windows down and listen for a train coming.
- D. Speed up across the tracks because a loaded school bus is heavy and slow to get going.

Answer: B — Stop, open the door, look and listen, then cross in low gear without shifting. (§10.4)

49. You realize a child is in the danger zone right next to the bus where you cannot see them. What should you do?

- A. Begin moving the bus slowly since the child will step back once the bus starts to roll.
- ✓ **B. Do not move the bus at all until you are certain the child is out of the danger zone there.**
- C. Rev the engine loudly so the child understands to move away from the side of the bus now.
- D. Close the door and pull forward; the danger zone is the child's responsibility, not yours.

Answer: B — Never move until you're certain the child is out of the danger zone. (§10.3)

50. You finish your route and pull into the yard. What must you do before leaving the bus?

- A. Lock the doors and head home since all the students got off at their own stops already.
- ✓ **B. Walk the bus from front to back to check that no child has been left behind or is asleep.**
- C. Just check the mirror once from your seat, which is enough to see down the whole aisle.
- D. Ask the last student off if anyone stayed on, and trust their answer without checking it.

Answer: B — Walk the bus front to back so no child is left behind. (§10.5)

51. A car illegally passes your stopped school bus while your red lights flash and children cross. What should you do?

- A. Wave the children across faster so they beat the passing car and clear the road quickly.
- ✓ **B. Keep the children safely back until the road is clear, and report the vehicle afterward.**
- C. Pull out and chase the car so you can get its plate number and confront the driver now.
- D. Send the children anyway since the red lights mean every car is legally required to stop.

Answer: B — Keep children back until it's safe, then report the vehicle. (§10.3)

52. You are about to start your bus in the morning with students waiting. What should you check about the brakes?

- A. Skip the brake check to save time since the students are already waiting out in the cold.
- ✓ **B. Confirm the brakes work properly before loading; never carry students with bad brakes.**
- C. Load the students first and test the brakes later once you are out on the open road there.
- D. Trust that yesterday's brakes are fine and just drive off without any check this morning.

Answer: B — Confirm the brakes work before loading; never carry students with bad brakes. (§10.1)