

EXT: SQL Connector Service

Extension Key: svconnector_sql

Language: en

Keywords: forDevelopers, forIntermediates

Copyright 2009-2012, François Suter, <typo3@cobweb.ch>

This document is published under the Open Content License available from http://www.opencontent.org/opl.shtml

The content of this document is related to TYPO3

- a GNU/GPL CMS/Framework available from www.typo3.org



Table of Contents

EXT: SQL Connector Service	1
Introduction	
Questions and support	
Keeping the developer happy	
Installation	

Configuration	5
Connection methods	
Developer's manual	
Known problems	
To-Do list	



Introduction

This extension implements a specific connector service for reading data from any database. It relies on ADODB to connect to any database system supported by that library (with some limits, due to the many weird syntaxes used for some systems). SQL queries can then be used.

Questions and support

If you have any questions about this extension, please ask them in the TYPO3 English mailing list, so that others can benefit from the answers. Please use the bug tracker on forge.typo3.org to report problem or suggest features (http://forge.typo3.org/projects/extension-svconnector_sql/issues).

Keeping the developer happy

It's unfortunately not possible to rate extensions anymore (maybe that will change again), so feel free to send thanks to the developers or praise the extension in general. If you really want to give something back, you may consider my Amazon wish list: http://www.amazon.co.uk/registry/wishlist/G7DI2AN99Y4F

You may also take a step back and reflect about the beauty of sharing. Think about how much you are benefiting and how much yourself is giving back to the community.



Installation

Install this extension and you can start using it's API for issuing SQL queries to any database inside your own code (although please see the limitations discussed in chapter "Configuration").

It requires extension "svconnector" which provides the base for all connector services and extension "adodb" to load the ADODB library. The "adodb" extension is a system extension provided with the TYPO3 Core.



Configuration

The various "fetch" methods of the SQL connector take the same parameters:

Parameter	Туре	Description	Default
driver	string	Name of the database system to connect to, taken from the list of available ADODB drivers.	
		See http://phplens.com/adodb/supported.databases.html	
server	string	Address of the server to connect to.	
user	string	User name to use to connect to the database.	
password	string	Password to use for the given user.	
database	string	Name of the database to connect to.	
query	string	The actual query to execute.	
init	string	SQL queries to be sent before the actual query (defined in parameter "query") is executed. This is typically used to temporarily change the encoding. Example SET NAMES 'UTF8';	
fetchMode	integer	(available since version 1.1.0) Used to choose ADODB's fetch mode, which influences the type of array returned by the recordset. Set to: • 1 for a numerical array • 2 for an associative array • 3 for both Not setting this value will fall back on the default behavior, which is unpredictable as it depends on each driver. For more information refer to http://phplens.com/lens/adodb/docs-adodb.htm#adodb fetch mode	

Connection methods

The current implementation of the SQL Connector only uses the classic way of setting up a connection:

```
$adodbObject = ADONewConnection($parameters['driver']);
$adodbObject->Connect($parameters['server'], $parameters['user'], $parameters['password'],
$parameters['database']);
```

that is, with the four standard parameters: server, user, password and database. This does not work for all database systems, but I currently had no use for more, nor a proper setup to test with other database system. The current version of the SQL connector was tested only with MySQL and PostgreSQL.

If you encounter problems connecting to some database system, please report an issue in the dedicated bug tracker and indicate as clearly as possible what connection syntax you would need.



Developer's manual

Getting data from another databse using the CSV connector service becomes a really easy task. The first step is to get the proper service object:

On the first line, you get a list of all services that are of type "connector" and subtype "sql". If the result if false, it means no appropriate services were found and you probably want to issue an error message.

On the contrary you are assured that there's at least one valid service and you can get an instance of it by calling t3lib_div::makeInstanceService().

The next step is simply to call the appropriate method from the API – with the right parameters – depending on which format you want to have in return. For a PHP array:

Obviously this is not limited to issuing SELECT queries, although it is what it was designed for, since connector services are really about getting data from some source. However other types of queries have not been tested.

The fetchRaw() method returns the same array as fetchArray(). The fetchXML() method returns the array created by fetchArray() transformed to XML using t3lib div::array2xml cs().

Note that the connection is neither permanent, nor stored in the connector object (as one could imagine the object being called several times but for different connections), so it may not be ideal to use if you need to perform many queries on the same database in a given code execution run.



Known problems

See the discussion about setting up connections in the "Configuration" chapter. Please report problems in the dedicated bug tracker: http://forge.typo3.org/projects/extension-svconnector_sql/issues



To-Do list

There is a roadmap on Forge for the continuing development of this extension:

http://forge.typo3.org/projects/extension-svconnector_csv/roadmap