

Quack Quack What? — API Reference

Version: 1.0

Date: March 2026

Author: Taashi Manyanga

Trademark: © Taashi Manyanga 2026

Base URL

`https://<your-replit-app>.replit.app`

All endpoints are prefixed with `/api/`.

Authentication

Authentication uses OpenID Connect via Replit Auth. Sessions are stored server-side in PostgreSQL.

Login

GET `/api/login`

Redirects the user to the Replit OIDC login page. Supports Google, GitHub, Apple, and email/password.

Response: 302 Redirect to OIDC provider

Callback

GET `/api/callback`

Handles the OIDC callback after authentication. Creates or updates the user record and establishes a session.

Response: 302 Redirect to `/` on success, `/api/login` on failure

Logout

GET `/api/logout`

Destroys the session and redirects to the OIDC end-session endpoint.

Response: 302 Redirect to home page

Get Current User

GET `/api/auth/user`

Returns the authenticated user's profile.

Auth Required: Yes

Success Response (200):

```
{
  "id": "user-uuid",
  "email": "user@example.com",
  "firstName": "John",
  "lastName": "Doe",
  "profileImageUrl": "https://...",
  "createdAt": "2026-03-08T00:00:00.000Z",
  "updatedAt": "2026-03-08T00:00:00.000Z"
}
```

Error Response (401):

```
{ "message": "Unauthorized" }
```

Skill Fetching

Fetch Skill Source

POST /api/fetch-skill

Fetches skill source code from a GitHub repository or URL.

Auth Required: No

Request Body:

```
{
  "source": "owner/repo",
  "sourceType": "github" | "url" | "local"
}
```

Success Response (200):

```
{
  "code": "// Full source code content..."
}
```

Error Response (400/500):

```
{ "message": "Error description" }
```

Evaluation

Run Evaluation

POST /api/evaluate

Runs static analysis on the provided code and stores the evaluation result.

Auth Required: No (Guest mode supported; userId set if authenticated)

Request Body:

```
{
  "source": "owner/repo",
  "sourceType": "github",
  "code": "// The skill code to analyze..."
}
```

Success Response (200):

```
{
  "id": "eval-uuid",
  "userId": "user-uuid" | null,
  "source": "owner/repo",
  "sourceType": "github",
  "skillCode": "// ...",
  "safetyScore": 85,
  "qualityScore": 72,
  "securityScore": 90,
  "overallScore": 82,
  "summary": "Analysis summary text...",
  "safetyFindings": ["Finding 1", "Finding 2"],
  "qualityFindings": ["Finding 1"],
  "securityFindings": [],
  "createdAt": "2026-03-08T00:00:00.000Z"
}
```

List User Evaluations

GET /api/evaluations

Returns the authenticated user's evaluations, most recent first (max 100).

Auth Required: Yes

Success Response (200):

```
[
  { "id": "...", "source": "...", "overallScore": 82, ... }
]
```

Get Single Evaluation

GET /api/evaluations/:id

Returns a single evaluation. Ownership check: returns 404 if the evaluation belongs to another user.

Auth Required: Partial (guests can view guest evaluations)

Success Response (200): Same schema as POST /api/evaluate response

Error Response (404):

```
{ "message": "Evaluation not found" }
```

User History

GET /api/history

Returns the authenticated user's evaluation history, most recent first (max 100).

Auth Required: Yes

Success Response (200): Same as GET /api/evaluations

AI Provider Configuration

Get Provider Config

GET /api/provider-config

Returns the current AI provider configuration with API keys masked.

Auth Required: No

Success Response (200):

```
{
  "id": "config-uuid",
  "provider": "openai",
  "model": "gpt-4o",
  "targetUri": null,
  "region": null,
  "projectId": null,
  "location": null,
  "hasApiKey": true,
  "hasAccessKey": false,
  "hasSecretKey": false
}
```

Save Provider Config

POST /api/provider-config

Creates or updates the AI provider configuration.

Auth Required: No

Request Body:

```
{
  "provider": "openai",
  "apiKey": "sk-...",
  "model": "gpt-4o"
}
```

Supported providers: openai, anthropic, foundry, vertexai, bedrock

Success Response (200):

```
{ "success": true, "provider": "openai" }
```

Chat

Send Chat Message

POST /api/chat

Sends a message to the configured LLM with skill code context.

Auth Required: No

Request Body:

```
{
  "message": "Is this skill safe for production use in a customer service bot?",
  "skillCode": "// optional: the skill code being discussed",
  "evaluationSummary": "optional: summary of evaluation results",
  "conversationHistory": [
    { "role": "user", "content": "Previous message" },
    { "role": "assistant", "content": "Previous response" }
  ]
}
```

Success Response (200):

```
{
  "fit": "Good" | "Moderate" | "Poor",
  "feedback": "Short 2-3 sentence assessment...",
  "report": "Detailed multi-paragraph analysis...",
  "refinedCode": "// Complete refined code..."
}
```

Error Response (400):

```
{
  "message": "No AI provider configured...",
  "needsConfig": true
}
```

Scoring System

Score Ranges

Score	Classification	Color
80-100	PASSED	Green
0-79	REVIEW	Amber

Weight Distribution

Pillar	Weight	Focus
Safety	40%	Dangerous patterns, sandbox escapes
Security	30%	Exposed secrets, hardcoded credentials
Quality	30%	Error handling, types, documentation

Formula

$$\text{overallScore} = (\text{safetyScore} \times 0.4) + (\text{securityScore} \times 0.3) + (\text{qualityScore} \times 0.3)$$
