




Performance

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)



▲ 0–49 50–89 90–100

METRICS Expand view


▲ First Contentful Paint
4.4 s

▲ Largest Contentful Paint
8.9 s

Total Blocking Time
440 ms

Cumulative Layout Shift
0.02

▲ Speed Index
6.4 s







Show audits relevant to: All [FCP](#) [LCP](#) [TBT](#) [CLS](#)

INSIGHTS

▲ Improve image delivery — Est savings of 1,197 KiB

Reducing the download time of images can improve the perceived load time of the page and LCP. [Learn more about optimizing image size](#) [FCP](#) [LCP](#) [Unscored](#)

URL	Resource Size	Est Savings
easyplugmarketplace.com 1st Party	1,283.0 KiB	1,197.3 KiB
 /assets/hero-delivery.png (testing.easyplugmarketplace.com)	572.9 KiB	543.0 KiB

	URL	Resource Size	Est Savings
	Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.		528.3 KiB
	This image file is larger than it needs to be (623x440) for its displayed dimensions (526x350). Use responsive images to reduce the image download size.		188.4 KiB
	img	...images/178....jpg (api-testing.easyplugmarketplace.com)	403.8 KiB 391.3 KiB
	Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.		194.3 KiB
	This image file is larger than it needs to be (1199x1073) for its displayed dimensions (366x210). Use responsive images to reduce the image download size.		379.7 KiB
	div.MuiBox-root > div.MuiBox-	...mampanav%40yahoo.com/178...jpg (api-testing.easyplugmarketplace.com)	70.2 KiB 70.0 KiB
<pre>root > div.MuiAvatar-root > img.MuiAvatar-img </pre>			
	This image file is larger than it needs to be (736x747) for its displayed dimensions (28x60). Use responsive images to reduce the image download size.		70.0 KiB
	img	...images/178....jpg (api-testing.easyplugmarketplace.com)	77.1 KiB 57.5 KiB
	Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.		26.6 KiB
	This image file is larger than it needs to be (590x526) for its displayed dimensions (236x511). Use responsive images to reduce the image download size.		47.2 KiB
		...lourensbotha86%40gmail.com/178....04.49.jpeg (api-testing.easyplugmarketplace.com)	38.4 KiB 38.2 KiB
img.MuiAvatar-img.css-45do71			
	This image file is larger than it needs to be (589x582) for its displayed dimensions (30x65). Use responsive images to reduce the image download size.		38.2 KiB
	img	...images/178....jpg (api-testing.easyplugmarketplace.com)	45.9 KiB 35.1 KiB

	URL	Resource Size	Est Savings
	Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.		10.6 KiB
	This image file is larger than it needs to be (493x440) for its displayed dimensions (315x210). Use responsive images to reduce the image download size.		31.9 KiB
	img	...images/178...jpg (api-testing.easyplugmarketplace.com)	35.6 KiB 32.7 KiB
	This image file is larger than it needs to be (959x853) for its displayed dimensions (315x210). Use responsive images to reduce the image download size.		32.7 KiB
	img	...images/178...-image.png (api-testing.easyplugmarketplace.com)	27.7 KiB 18.3 KiB
	Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.		18.3 KiB
	img	/assets/Sample%20Logo%201%20(4)-CHNpWEXQ.png (testing.easyplugmarketplace.com)	11.3 KiB 11.3 KiB
	This image file is larger than it needs to be (500x500) for its displayed dimensions (41x41). Use responsive images to reduce the image download size.		11.3 KiB

▲ Modern HTTP — Est savings of 1,710 ms ^

HTTP/2 and HTTP/3 offer many benefits over HTTP/1.1, such as multiplexing. [Learn more about using modern HTTP](#) FCP
LCP Unscored

URL	Protocol
easyplugmarketplace.com 1st Party	
https://testing.easyplugmarketplace.com	http/1.1
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	http/1.1
/assets/index-BuGgsLe5.css (testing.easyplugmarketplace.com)	http/1.1
/assets/Sample%20Logo%201%20(4)-CHNpWEXQ.png (testing.easyplugmarketplace.com)	http/1.1
/assets/hero-deli...png (testing.easyplugmarketplace.com)	http/1.1
...listings/featured?latitude=... (api-testing.easyplugmarketplace.com)	http/1.1
/assets/inter-lat...woff2 (testing.easyplugmarketplace.com)	http/1.1
/assets/inter-lat...woff2 (testing.easyplugmarketplace.com)	http/1.1
/assets/inter-lat...woff2 (testing.easyplugmarketplace.com)	http/1.1
/assets/inter-lat...woff2 (testing.easyplugmarketplace.com)	http/1.1
/favicon.ico (testing.easyplugmarketplace.com)	http/1.1
/favicon.png (testing.easyplugmarketplace.com)	http/1.1

URL

Protocol

...images/178....jpg (api-testing.easyplugmarketplace.com)	http/1.1
...mampanav%40yahoo.com/178....jpg (api-testing.easyplugmarketplace.com)	http/1.1
...images/178....jpg (api-testing.easyplugmarketplace.com)	http/1.1
...lourensbotha86%40gmail.com/178....04.49.jpeg (api-testing.easyplugmarketplace.com)	http/1.1
...images/178....image.png (api-testing.easyplugmarketplace.com)	http/1.1
/logo.png (testing.easyplugmarketplace.com)	http/1.1
...v1/listings?latitude=...	http/1.1
...images/178....jpg (api-testing.easyplugmarketplace.com)	http/1.1
...images/178....jpg (api-testing.easyplugmarketplace.com)	http/1.1
...images/178....jpg (api-testing.easyplugmarketplace.com)	http/1.1
/placeholder-image.svg (testing.easyplugmarketplace.com)	http/1.1

▲ Render-blocking requests — Est savings of 300 ms

Requests are blocking the page's initial render, which may delay LCP. [Deferring or inlining](#) can move these network requests out of the critical path. FCP LCP Unscored

URL

Transfer Size

Duration

easyplugmarketplace.com 1st Party	8.7 KiB	180 ms
/assets/index-BuGgsLe5.css (testing.easyplugmarketplace.com)	8.7 KiB	180 ms

▲ LCP breakdown

Each [subpart has specific improvement strategies](#). Ideally, most of the LCP time should be spent on loading the resources, not within delays. LCP Unscored

Subpart

Duration

Time to first byte	700 ms
Resource load delay	1,640 ms
Resource load duration	1,450 ms
Element render delay	30 ms



img.MuiBox-root.css-a1luda

▲ LCP request discovery

[Optimize LCP](#) by making the LCP image discoverable from the HTML immediately, and avoiding lazy-loading LCP Unscored


fetchpriority=high should be applied

Request is discoverable in initial document

LCP resources should not use loading=lazy

about:blank

4/24



img.MuiBox-root.css-a1luda

▲ Network dependency tree ^

[Avoid chaining critical requests](#) by reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. CLP Unscored

Maximum critical path latency: **5,605 ms**

Initial Navigation

- https://testing.easyplugmarketplace.com - **768 ms**, 1.38 KiB
 - /assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com) - **2,224 ms**, 575.52 KiB
 - ...v1/listings?latitude=... (api-testing.easyplugmarketplace.com) - **5,605 ms**, 11.89 KiB
 - ...listings/featured?latitude=... (api-testing.easyplugmarketplace.com) - **3,144 ms**, 9.11 KiB
 - /assets/index-BuGgsLe5.css (testing.easyplugmarketplace.com) - **1,455 ms**, 8.72 KiB
 - /assets/inter-lat....woff2 (testing.easyplugmarketplace.com) - **3,320 ms**, 24.22 KiB
 - /assets/inter-lat....woff2 (testing.easyplugmarketplace.com) - **3,320 ms**, 24.04 KiB
 - /assets/inter-lat....woff2 (testing.easyplugmarketplace.com) - **3,310 ms**, 23.45 KiB
 - /assets/inter-lat....woff2 (testing.easyplugmarketplace.com) - **2,874 ms**, 24.12 KiB

Preconnected origins

[preconnect](#) hints help the browser establish a connection earlier in the page load, saving time when the first request for that origin is made. The following are the origins that the page preconnected to.

no origins were preconnected

Preconnect candidates

Add [preconnect](#) hints to your most important origins, but try to use no more than 4.

Origin	Est LCP savings
https://api-testing.easyplugmarketplace.com	350 ms

○ Layout shift culprits ^

Layout shifts occur when elements move absent any user interaction. [Investigate the causes of layout shifts](#), such as elements being added, removed, or their fonts changing as the page loads. CLS Unscored

Element	Layout shift score
Total	0.020
div.MuiBox-root.css-1k3vekq	0.019
/assets/inter-lat....woff2 (testing.easyplugmarketplace.com)	Web font
/assets/inter-lat....woff2 (testing.easyplugmarketplace.com)	Web font
/assets/inter-lat....woff2 (testing.easyplugmarketplace.com)	Web font
span.MuiBox-root.css-13o7eu2	0.001

Element

Layout shift score



/assets/inter-lat....woff2 (testing.easyplugmarketplace.com) Web font

These insights are also available in the Chrome DevTools Performance Panel - [record a trace](#) to view more detailed information.

DIAGNOSTICS

▲ Minimize main-thread work — 2.8 s

^

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#) (TBT) (Unscored)

Category	Time Spent
Other	1,625 ms
Script Evaluation	745 ms
Style & Layout	333 ms
Rendering	79 ms
Garbage Collection	32 ms
Parse HTML & CSS	12 ms
Script Parsing & Compilation	7 ms

▲ Reduce unused JavaScript — Est savings of 383 KiB

^

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn how to reduce unused JavaScript](#) (FCP) (LCP) (Unscored)

URL	Transfer Size	Est Savings
easyplugmarketplace.com (1st Party)	575.1 KiB	383.2 KiB
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	575.1 KiB	383.2 KiB

Minify CSS — Est savings of 2 KiB

^

Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS](#) (FCP) (LCP) (Unscored)

URL	Transfer Size	Est Savings
.css-fcihry { display: flex; flex-direction: row; -webkit-box-align: center; align-items: center; ... } ...	19.1 KiB	2.3 KiB

Reduce unused CSS — Est savings of 16 KiB

^

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS](#) (FCP) (LCP) (Unscored)

URL	Transfer Size	Est Savings
.css-fcihry { display: flex; flex-direction: row; -webkit-box-align: center; align-items: center; ... } ...	19.1 KiB	15.9 KiB

Avoid long main-thread tasks — 14 long tasks found

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#) TBT Unscored

URL	Start Time	Duration
Unattributable		766 ms
Unattributable	1,433 ms	185 ms
Unattributable	855 ms	115 ms
Unattributable	1,245 ms	99 ms
Unattributable	1,344 ms	89 ms
Unattributable	1,096 ms	79 ms
Unattributable	784 ms	71 ms
Unattributable	1,175 ms	70 ms
Unattributable	1,038 ms	58 ms
easyplugmarketplace.com 1st Party		754 ms
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	5,217 ms	277 ms
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	8,348 ms	127 ms
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	5,121 ms	96 ms
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	8,003 ms	94 ms
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	5,494 ms	93 ms
https://testing.easyplugmarketplace.com	970 ms	67 ms

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

PASSED AUDITS (17) Hide

Use efficient cache lifetimes

A long cache lifetime can speed up repeat visits to your page. [Learn more about caching.](#) FCP LCP Unscored

Document request latency

Your first network request is the most important. [Reduce its latency](#) by avoiding redirects, ensuring a fast server response, and enabling text compression. FCP LCP Unscored

Avoids redirects

Server responds quickly (observed 224 ms)

Applies text compression

Optimize DOM size ^

A large DOM can increase the duration of style calculations and layout reflows, impacting page responsiveness. A large DOM will also increase memory usage. [Learn how to avoid an excessive DOM size.](#) (Unscored)

Statistic	Element	Value
Total elements		688
DOM depth	 path	18
Most children	 div.MuiGrid-root.MuiGrid-container.MuiGrid-direction-xs-row.MuiGrid-spacing-xs-3.css-177xvbk	7

Duplicated JavaScript ^

Remove large, [duplicate JavaScript modules](#) from bundles to reduce unnecessary bytes consumed by network activity. (FCP) (LCP) (Unscored)

Font display ^

Consider setting [font-display](#) to swap or optional to ensure text is consistently visible. swap can be further optimized to mitigate layout shifts with [font metric overrides](#). (Unscored)

Forced reflow ^

A forced reflow occurs when JavaScript queries geometric properties (such as offsetWidth) after styles have been invalidated by a change to the DOM state. This can result in poor performance. Learn more about [forced reflows](#) and possible mitigations. (Unscored)

☐ INP breakdown ^

Start investigating [how to improve INP](#) by looking at the longest subpart. (Unscored)

Legacy JavaScript ^

Polyfills and transforms enable older browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile [Baseline](#) features, unless you know you must support older browsers. [Learn why most sites can deploy ES6+ code without transpiling](#) (FCP) (LCP) (Unscored)

3rd parties ^

3rd party code can significantly impact load performance. [Reduce and defer loading of 3rd party code](#) to prioritize your page's content. (Unscored)

Optimize viewport for mobile ^

Tap interactions may be [delayed by up to 300 ms](#) if the viewport is not optimized for mobile. (Unscored)

meta

Minify JavaScript ^

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript.](#) FCP LCP
Unscored

Avoids enormous network payloads — Total size was 2,184 KiB

Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes.](#) Unscored

URL	Transfer Size
easyplugmarketplace.com 1st Party	2,010.0 KiB
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	575.5 KiB
/assets/hero-deli....png (testing.easyplugmarketplace.com)	573.3 KiB
...images/178....jpg (api-testing.easyplugmarketplace.com)	404.2 KiB
...images/178....jpg (api-testing.easyplugmarketplace.com)	160.0 KiB
...images/178....jpg (api-testing.easyplugmarketplace.com)	77.4 KiB
...mampanav%40yahoo.com/178....jpg (api-testing.easyplugmarketplace.com)	70.6 KiB
...images/178....jpg (api-testing.easyplugmarketplace.com)	46.3 KiB
...lourensbotha86%40gmail.com/178....04.49.jpeg (api-testing.easyplugmarketplace.com)	38.8 KiB
...images/178....jpg (api-testing.easyplugmarketplace.com)	35.9 KiB
...images/178...-image.png (api-testing.easyplugmarketplace.com)	28.1 KiB

User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more about User Timing marks.](#) Unscored

JavaScript execution time — 0.7 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to reduce Javascript execution time.](#) TBT Unscored

URL	Total CPU Time	Script Evaluation	Script Parse
easyplugmarketplace.com 1st Party	1,450 ms	731 ms	7 ms
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	847 ms	697 ms	7 ms
https://testing.easyplugmarketplace.com	603 ms	34 ms	1 ms
Unattributable	1,367 ms	10 ms	0 ms
Unattributable	1,367 ms	10 ms	0 ms

Avoid non-composited animations

Animations which are not composited can be janky and increase CLS. [Learn how to avoid non-composited animations](#) CLS
Unscored

Image elements have explicit `width` and `height`



Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn how to set image dimensions](#) (CLS) (Unscored)

Page didn't prevent back/forward cache restoration



Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. [Learn more about the bfcache](#) (Unscored)



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.


NAMES AND LABELS

▲ Buttons do not have an accessible name




When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible](#).


Failing Elements




button.MuiButtonBase-root.MuiButton-root.MuiButton-contained.MuiButton-containedPrimary.MuiBu...




button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmmbh



button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmmbh



button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmmbh



button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmmbh

Failing Elements

	button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmbh
	button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmbh
	button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmbh
	button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmbh
	button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmbh
	button.MuiButtonBase-root.Mui-disabled.MuilconButton-root.MuilconButton-sizeSmall.css-zgdmbh

▲ Image elements do not have `[alt]` attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

Failing Elements

	div.MuiBox-root > div.MuiBox-root > div.MuiAvatar-root > img.MuiAvatar-img
	div.MuiBox-root > div.MuiBox-root > div.MuiAvatar-root > img.MuiAvatar-img
	div.MuiBox-root > div.MuiBox-root > div.MuiAvatar-root > img.MuiAvatar-img
	img.MuiAvatar-img.css-45do71

Failing Elements

	
	div.MuiBox-root > div.MuiBox-root > div.MuiAvatar-root > img.MuiAvatar-img
	div.MuiBox-root > div.MuiBox-root > div.MuiAvatar-root > img.MuiAvatar-img




These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

CONTRAST

▲ Background and foreground colors do not have a sufficient contrast ratio. ^

Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast.](#)

Failing Elements

	h6.MuiTypography-root.MuiTypography-h6.css-1jwc0ib
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-1o3rglg
	h6.MuiTypography-root.MuiTypography-h6.css-1jwc0ib
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-1o3rglg
	h6.MuiTypography-root.MuiTypography-h6.css-1jwc0ib
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-1o3rglg
	h6.MuiTypography-root.MuiTypography-h6.css-1jwc0ib
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-1o3rglg
	p.MuiTypography-root.MuiTypography-body2.css-xsx5km

Failing Elements

	
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-187j9n4
	p.MuiTypography-root.MuiTypography-body2.css-xsx5km
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-187j9n4
	p.MuiTypography-root.MuiTypography-body2.css-xsx5km
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-187j9n4
	h6.MuiTypography-root.MuiTypography-h6.css-1jwc0ib
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-1o3rglg
	h6.MuiTypography-root.MuiTypography-h6.css-1jwc0ib
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-1o3rglg
	h6.MuiTypography-root.MuiTypography-h6.css-1jwc0ib
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-1o3rglg
	span.MuiBottomNavigationAction-label.Mui-selected.css-w7wnpw
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-1otno83
	div.MuiPaper-root.MuiPaper-elevation.MuiPaper-rounded.MuiPaper-elevation0.css-1fp9l


These are opportunities to improve the legibility of your content.

NAVIGATION

▲ Heading elements are not in a sequentially-descending order ^

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

Failing Elements

	h6.MuiTypography-root.MuiTypography-h6.css-1jwc0ib
	h6.MuiTypography-root.MuiTypography-h6.css-1yclmqn
	h6.MuiTypography-root.MuiTypography-h6.css-1jwc0ib
	h6.MuiTypography-root.MuiTypography-subtitle1.css-1t80spi

These are opportunities to improve keyboard navigation in your application.

BEST PRACTICES

▲ Document does not have a main landmark. ^

One main landmark helps screen reader users navigate a web page. [Learn more about landmarks.](#)

Failing Elements

	html
---	------

These items highlight common accessibility best practices.

ADDITIONAL ITEMS TO MANUALLY CHECK (10) Hide

○ Interactive controls are keyboard focusable ^

Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable.](#) (Unscored)

○ Interactive elements indicate their purpose and state ^

Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints.](#) (Unscored)

- ☐ The page has a logical tab order ^

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering.](#) (Unscored)

- ☐ Visual order on the page follows DOM order ^

DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering.](#) (Unscored)

- ☐ User focus is not accidentally trapped in a region ^

A user can tab into and out of any control or region without accidentally trapping their focus. [Learn how to avoid focus traps.](#) (Unscored)

- ☐ The user's focus is directed to new content added to the page ^

If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn how to direct focus to new content.](#) (Unscored)

- ☐ HTML5 landmark elements are used to improve navigation ^

Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more about landmark elements.](#) (Unscored)

- ☐ Offscreen content is hidden from assistive technology ^

Offscreen content is hidden with display: none or aria-hidden=true. [Learn how to properly hide offscreen content.](#) (Unscored)

- ☐ Custom controls have associated labels ^

Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. [Learn more about custom controls and labels.](#) (Unscored)

- ☐ Custom controls have ARIA roles ^

Custom interactive controls have appropriate ARIA roles. [Learn how to add roles to custom controls.](#) (Unscored)

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review.](#)

PASSED AUDITS (17) Hide

- [\[aria-*\]](#) attributes match their roles ^

Each ARIA role supports a specific subset of aria-* attributes. Mismatching these invalidates the aria-* attributes. [Learn how to match ARIA attributes to their roles.](#)

- [\[aria-hidden="true"\]](#) is not present on the document <body> ^

Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <body>. [Learn how aria-hidden affects the document body.](#)

- [\[role\]](#)s have all required [\[aria-*\]](#) attributes ^

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#)

[role] values are valid	^
ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more about valid ARIA roles.	
[aria-*) attributes have valid values	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more about valid values for ARIA attributes.	
[aria-*) attributes are valid and not misspelled	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more about valid ARIA attributes.	
[user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5.	^
Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more about the viewport meta tag.	
button, link, and menuitem elements have accessible names	^
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to make command elements more accessible.	
ARIA attributes are used as specified for the element's role	^
Some ARIA attributes are only allowed on an element under certain conditions. Learn more about conditional ARIA attributes.	
[aria-hidden="true"] elements do not contain focusable descendents	^
Focusable descendents within an [aria-hidden="true"] element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn how aria-hidden affects focusable elements.	
Elements use only permitted ARIA attributes	^
Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. Learn more about prohibited ARIA roles.	
Document has a <title> element	^
The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more about document titles.	
<html> element has a [lang] attribute	^
If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more about the lang attribute.	
<html> element has a valid value for its [lang] attribute	^
Specifying a valid BCP 47 language helps screen readers announce text properly. Learn how to use the lang attribute.	
No element has a [tabindex] value greater than 0	^
A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more about the tabindex attribute.	

Touch targets have sufficient size and spacing.	^
Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. Learn more about touch targets.	
Deprecated ARIA roles were not used	^
Deprecated ARIA roles may not be processed correctly by assistive technology. Learn more about deprecated ARIA roles.	
NOT APPLICABLE (41)	Hide
☐ [accesskey] values are unique	^
Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more about access keys. Unscored	
☐ Elements with <code>role="dialog"</code> or <code>role="alertdialog"</code> have accessible names.	^
ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. Learn how to make ARIA dialog elements more accessible. Unscored	
☐ ARIA input fields have accessible names	^
When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about input field labels. Unscored	
☐ ARIA <code>meter</code> elements have accessible names	^
When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name meter elements. Unscored	
☐ ARIA <code>progressbar</code> elements have accessible names	^
When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to label progressbar elements. Unscored	
☐ Elements with an ARIA <code>[role]</code> that require children to contain a specific <code>[role]</code> have all required children.	^
Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more about roles and required children elements. Unscored	
☐ <code>[role]</code> s are contained by their required parent element	^
Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more about ARIA roles and required parent element. Unscored	
☐ Elements with the <code>role=text</code> attribute do not have focusable descendents.	^
Adding <code>role=text</code> around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. Learn more about the role=text attribute. Unscored	
☐ ARIA toggle fields have accessible names	^
When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about toggle fields. Unscored	
☐ ARIA <code>tooltip</code> elements have accessible names	^
When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name tooltip elements. Unscored	

ARIA <code>treeitem</code> elements have accessible names	
When a <code>treeitem</code> element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about labeling <code>treeitem</code> elements. Unscored	
The page contains a heading, skip link, or landmark region	
Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more about bypass blocks. Unscored	
<code><dl></code>'s contain only properly-ordered <code><dt></code> and <code><dd></code> groups, <code><script></code>, <code><template></code> or <code><div></code> elements.	
When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn how to structure definition lists correctly. Unscored	
Definition list items are wrapped in <code><dl></code> elements	
Definition list items (<code><dt></code> and <code><dd></code>) must be wrapped in a parent <code><dl></code> element to ensure that screen readers can properly announce them. Learn how to structure definition lists correctly. Unscored	
ARIA IDs are unique	
The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn how to fix duplicate ARIA IDs. Unscored	
No form fields have multiple labels	
Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn how to use form labels. Unscored	
<code><frame></code> or <code><iframe></code> elements have a title	
Screen reader users rely on frame titles to describe the contents of frames. Learn more about frame titles. Unscored	
<code><html></code> element has an <code>[xml:lang]</code> attribute with the same base language as the <code>[lang]</code> attribute.	
If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. Learn more about the <code>lang</code> attribute. Unscored	
Input buttons have discernible text.	
Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. Learn more about input buttons. Unscored	
<code><input type="image"></code> elements have <code>[alt]</code> text	
When an image is being used as an <code><input></code> button, providing alternative text can help screen reader users understand the purpose of the button. Learn about input image alt text. Unscored	
Form elements have associated labels	
Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more about form element labels. Unscored	
Links are distinguishable without relying on color.	
Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. Learn how to make links distinguishable. Unscored	
Links have a discernible name	

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn how to make links accessible.](#) (Unscored)

- ☐ Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#) (Unscored)

- ☐ List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements ^

Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. [Learn more about proper list structure.](#) (Unscored)

- ☐ The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#) (Unscored)

- ☐ `<object>` elements have alternate text ^

Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#) (Unscored)

- ☐ Select elements have associated label elements. ^

Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element.](#) (Unscored)

- ☐ Skip links are focusable. ^

Including a skip link can help users skip to the main content to save time. [Learn more about skip links.](#) (Unscored)

- ☐ Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table. ^

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more about the headers attribute.](#) (Unscored)

- ☐ `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers.](#) (Unscored)

- ☐ `[lang]` attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the lang attribute.](#) (Unscored)

- ☐ `<video>` elements contain a `<track>` element with `[kind="captions"]` ^

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#) (Unscored)

- ☐ `autocomplete` attributes are used correctly ^

The `autocomplete` attribute values must be valid and correctly applied for screen readers to function correctly. [Learn more about valid autocomplete values.](#) (Unscored)

- ☐ Elements with `role="none"` or `role="presentation"` do not have conflicts ^

There are certain cases where the semantic role of an element with role="none" or role="presentation" does not resolve to none or presentation. To ensure the element remains removed from the accessibility tree, you should not add any global ARIA attributes to the element or make it focusable. [Learn more about presentation role conflict.](#) (Unscored)

- SVG elements with an `img` role have an accessible text alternative ^

Ensures SVG elements with an `img`, `graphics-document` or `graphics-symbol` role have an accessible text alternative. [Learn more about SVG alt text.](#) (Unscored)

- Tables have different content in the summary attribute and `<caption>`. ^

The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#) (Unscored)

- All heading elements contain content. ^

A heading with no content or inaccessible text prevent screen reader users from accessing information on the page's structure. [Learn more about headings.](#) (Unscored)

- Uses ARIA roles only on compatible elements ^

Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. [Learn more about ARIA roles.](#) (Unscored)

- Image elements do not have `[alt]` attributes that are redundant text. ^

Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the alt attribute.](#) (Unscored)

- Identical links have the same purpose. ^

Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. [Learn more about identical links.](#) (Unscored)



Best Practices

TRUST AND SAFETY

- Ensure CSP is effective against XSS attacks ^

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS.](#) (Unscored)

Description	Directive	Severity
No CSP found in enforcement mode		High

- Use a strong HSTS policy ^

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. [Learn more about using a strong HSTS policy.](#) (Unscored)

Description	Directive	Severity
No HSTS header found		High

Ensure proper origin isolation with COOP

The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. [Learn more about deploying the COOP header.](#) Unscored

Description	Directive	Severity
No COOP header found		High

Mitigate clickjacking with XFO or CSP

The X-Frame-Options (XFO) header or the frame-ancestors directive in the Content-Security-Policy (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. [Learn more about mitigating clickjacking.](#) Unscored

Description	Severity
No frame control policy found	High

Mitigate DOM-based XSS with Trusted Types

The require-trusted-types-for directive in the Content-Security-Policy (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. [Learn more about mitigating DOM-based XSS with Trusted Types.](#) Unscored

Description	Severity
No `Content-Security-Policy` header with Trusted Types directive found	High

BROWSER COMPATIBILITY

Baseline Features

Lists web features used on the page and their Baseline status as of 2026-06-05. [Learn more about Baseline.](#) Unscored

Web-features	Baseline Status	Source
easypugmarketplace.com 1st Party		
page-visibility-state	Limited Availability	(index):1
long-animation-frames	Limited Availability	(index):1
layout-instability	Limited Availability	(index):1
background-clip-text	Limited Availability	(index):-1
requestidlecallback	Limited Availability	(index):1
font-language-override	Limited Availability	(index):-1
print-color-adjust	Newly Available (2025-05-01)	(index):-1

Web-features	Baseline Status	Source
scrollend	Newly Available (2025-12-12)	<code>index-Dr6WPX-Y.js:8</code>
backdrop-filter	Newly Available (2024-09-16)	<code>index-Dr6WPX-Y.js:11</code>
font-size-adjust	Newly Available (2024-07-25)	<code>(index):-1</code>
nullish-coalescing	Widely Available (2020-09-16)	<code>(index):1</code>
aborting	Widely Available (2019-03-25)	<code>(index):1</code>
js-modules	Widely Available (2018-05-09)	<code>(index):-1</code>
not	Widely Available (2021-01-21)	<code>(index):-1</code>
will-change	Widely Available (2020-01-15)	<code>(index):-1</code>
text-indent	Widely Available (2015-07-29)	<code>(index):-1</code>
logical-assignments	Widely Available (2020-09-16)	<code>(index):1</code>
canvas	Widely Available (2015-07-29)	<code>index-Dr6WPX-Y.js:257</code>
outline	Widely Available (2023-03-27)	<code>index-Dr6WPX-Y.js:11</code>
flexbox	Widely Available (2015-09-30)	<code>(index):-1</code>
grid	Widely Available (2017-10-17)	<code>(index):-1</code>
request-animation-frame	Widely Available (2015-07-29)	<code>index-Dr6WPX-Y.js:251</code>
appearance	Widely Available (2022-03-14)	<code>(index):-1</code>
border-image	Widely Available (2017-02-01)	<code>(index):-1</code>
font-optical-sizing	Widely Available (2020-03-24)	<code>(index):-1</code>
weak-references	Widely Available (2021-04-26)	<code>(index):1</code>
referrer-policy	Widely Available (2021-09-20)	<code>index-Dr6WPX-Y.js:153</code>

GENERAL

○ Detected JavaScript libraries

All front-end JavaScript libraries detected on the page: [Learn more about this JavaScript library detection diagnostic audit.](#) Unscored

Name	Version
Leaflet	1.9.4

▲ Missing source maps for large first-party JavaScript

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps.](#) Unscored

URL	Map URL
easyplugmarketplace.com 1st Party	
/assets/index-Dr6WPX-Y.js (testing.easyplugmarketplace.com)	
Large JavaScript file is missing a source map	

PASSED AUDITS (12)

Hide

Uses HTTPS	^
All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more about HTTPS.	
Avoids deprecated APIs	^
Deprecated APIs will eventually be removed from the browser. Learn more about deprecated APIs.	
Avoids third-party cookies	^
Third-party cookies may be blocked in some contexts. Learn more about preparing for third-party cookie restrictions.	
Allows users to paste into input fields	^
Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. Learn more about user-friendly input fields.	
Avoids requesting the geolocation permission on page load	^
Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more about the geolocation permission. Also consider using the <geolocation> element .	
Avoids requesting the notification permission on page load	^
Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more about responsibly getting permission for notifications.	
Displays images with correct aspect ratio	^
Image display dimensions should match natural aspect ratio. Learn more about image aspect ratio.	
Serves images with appropriate resolution	^
Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn how to provide responsive images.	
Page has the HTML doctype	^
Specifying a doctype prevents the browser from switching to quirks-mode. Learn more about the doctype declaration.	
Properly defines charset	^
A character encoding declaration is required. It can be done with a <code><meta></code> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more about declaring the character encoding.	
No browser errors logged to the console	^

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more about this errors in console diagnostic audit](#)

No issues in the **Issues** panel in Chrome Devtools



Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

NOT APPLICABLE (1)

Hide

☐ Redirects HTTP traffic to HTTPS



Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. [Learn more.](#)
Unscored



Captured at Aug 19, 2026, 6:14 PM GMT+2



Emulated Moto G Power with Lighthouse 13.4.0



Single page session



Initial page load



Slow 4G throttling



Using Chromium 151.0.0.0 with devtools

Generated by **Lighthouse** 13.4.0 | [File an issue](#)