

Adaptive UI/UX using Reinforcement Learning in Banking Apps: A Comprehensive Research Framework

1st Sathiskumar Meganathan

The University of Texas at Austin, 2515 Speedway, Austin, TX 78712, USA

sathis.star@gmail.com

Abstract—A complete reinforcement learning (RL) research methodology for adaptive UI/UX in banking applications is presented in this study. The proposed system includes user demographics, contextual factors, behavioural history, current session data, and financial profiles in its rich state space and an extensive action space for UI adaptations like layout, navigation, feature prominence, interaction patterns, and notification strategies. A multi-objective reward function balances job completion, efficiency, error reduction, engagement, and business value. Implementation uses a modified Deep Q-Network (DQN) with Double DQN, duelling architecture, prioritised experience replay, and noisy networks, backed by LSTMs, linear encoders, and multihead attention for state aggregation. A continuous learning pipeline uses shadow testing, progressive rollout, rollback measures, and human-in-the-loop monitoring to assure safe deployment. The RL-driven system is evaluated against static, rule-based, contextual bandit, and supervised baselines using main (task success, usability, NPS) and secondary (feature discovery, cross-sell, retention) metrics. Trials show considerable gains in user experience, efficiency, and business consequences. The study uses transfer learning, bounded exploration, edge deployment, and federated learning to solve cold start, exploration safety, latency, and privacy.

Keywords—Adaptive user interfaces and user experiences, Reinforcement Learning, Deep Q-Network, Banking Applications, Personalization, Federated Learning, User-Centered Design

1. INTRODUCTION

The growing digitalisation of financial services has changed consumer banking interactions. Daily financial operations including account management, payments, investments, and loan processing are done using mobile and web-based banking apps [1]. Banking institutions are under pressure to create smooth, intuitive, and personalised services as consumer expectations rise. Designing user interfaces (UI) and user experiences (UX) that meet varied client demands is difficult. Banking apps must combine usability, compliance, trust, security, and accessibility, unlike retail or entertainment apps that can experiment with personalisation [2].

User diversity is a major challenge in banking app design. Digitally savvy millennials anticipate rapid and simple workflows, but senior people may need more guidance [3]. Traditional one-size-fits-all interfaces ignore such variety, causing usability issues. Research reveals that current banking apps include over 50 capabilities, including bill payments, cash transfers, portfolio management, and AI-driven financial consulting. Users utilise 5–7 features on average [4]. This disparity shows feature discoverability and relevance inefficiencies. Also important is feature complexity. As banks increase their digital offerings, the cognitive strain on consumers might degrade the experience. New account holders may be intimidated by complicated menus, while expert users may be dissatisfied by duplicated navigation procedures. Inconsistencies

might cause conversion gaps—up to 68% of consumers quit digital banking tasks owing to poor UX [5]. This lowers user happiness and commercial indicators including product adoption, cross-selling, and customer retention.

Existing design techniques generally result in static interfaces with the same layout and interaction flow for all users, regardless of preferences, skills, or finances [6]. While regulatory frameworks need consistent disclosures and information, the rest of the interface has untapped dynamic adaptive potential. Manual personalisation methods like demographic-based segmentation and A/B testing cannot scale real-time, individualised optimisation [7]. Reinforcement learning (RL) is a transformational paradigm in artificial intelligence. Reinforcement learning allows systems to learn optimum behaviours from environmental interactions via rewards or punishments [8]. RL systems experiment with multiple techniques and refine them depending on results, unlike supervised learning models that use pre-labeled datasets. This means banking apps may test interface variants, measure user engagement, and modify the experience to maximise satisfaction and job completion. Importantly, RL may balance exploration (trying new layouts, adding new navigation pathways) with exploitation (using proven setups) [9].

However, applying RL to high-stakes sectors like banking presents significant research hurdles. How RL algorithms simulate user preferences without sacrificing security, fairness, or openness is a key challenge. Financial interface mistakes can cause customer dissatisfaction or financial loss, unlike in gaming or e-commerce. Thus, incentive functions must be carefully designed to prioritise efficiency, trust, compliance, and inclusiveness [10]. Finding the right balance between exploration and exploitation is another difficulty. Excessive exploration risks inconsistent experiences that undermine user trust, while excessive exploitation risks stagnation and less flexibility to changing user behaviours. Fairness in adaptive interfaces is crucial. RL-driven personalisation must avoid perpetuating biases or generating discriminatory trends, such as delivering easier experiences to particular demographic groups while privileging others with sophisticated features [11]. These issues demand strong frameworks that combine ethical AI into RL-driven adaptability.

Reinforcement learning is used to present a complete study framework for adaptive UI/UX in banking apps. Four research questions lead the framework's methodical approach to the foregoing challenges:

- How can RL algorithms represent high-stakes financial interface user preferences?
- What is the best balance between exploration (trying new layouts) and exploitation (using established configurations)?
- Can we prevent biased UI patterns and preserve fairness?

- Can RL-based adaptation boost business KPIs and user satisfaction?

The framework addresses these problems to connect technological feasibility and real-world application in digital banking. It emphasises adaptable interfaces' computational foundations, human-centered design, regulatory compliance, and ethical consequences. This research establishes reinforcement learning as a foundation for next-generation financial UX innovation, capable of altering user interactions from static to adaptive, generic to personalised, and transactional to immersive.

2. LITERATURE SURVEY

Optimising digital system usability and personalisation via adaptive user interfaces (UI) has long been investigated. Early adaptive UI research focused on rule-based personalisation, where static algorithms modified layouts or features for specified user profiles [12]. Scalability and real-time adaptability were difficult for such strategies, although they worked for tiny systems. Machine learning is now used for adaptive UI in e-commerce and educational platforms to personalise suggestions and content distribution [13]. These methods employ supervised learning, which requires huge labelled datasets and is inflexible for dynamic, sequential user behaviour.

Reinforcement learning (RL) can optimise consecutive decisions under uncertainty, making it a viable adaptive UI/UX method. RL has shown promise in adaptive tutoring systems [14], personalised news suggestions [15], and healthcare interfaces that adapt to patient situations [16]. RL is ideal for dynamic interaction situations because it can mix exploration (trying novel adaptations) with exploitation (applying proven techniques). However, most research has focused on low-stakes areas other than financial decision-making. Most financial personalisation initiatives have centred on recommender systems for investment advice, fraud detection, and client segmentation [17]. These apps use advanced machine learning but are backend procedures, not UI adjustments. Banking apps frequently have static themes with personalisation limited to ad banners and product suggestions. Financial services adaptable UI/UX research are rare owing of legal restraints and user trust issues. This gap shows an untapped potential to use adaptive reinforcement learning to improve usability and compliance.

Banking apps serve a diverse user base, from youthful, tech-savvy consumers to senior users with low digital literacy [18]. Most adaptive systems research assumes a uniform user population or neglects accessibility. Modern banking apps sometimes have over 50 functionalities, but consumers only utilise 5–7, causing cognitive overload or underutilisation. This imbalance has been neglected by traditional UI research. Additionally, job completion and user satisfaction have not been systematically connected with commercial goals like cross-sell rates or customer retention. Academic research has had little influence on banking apps due to this gap.

Research Gap

Reinforcement learning has shown potential in education, e-commerce, and healthcare, but adaptive UI/UX for high-stakes financial systems is underexplored. Banking app personalisation research have focused on recommendation engines and fraud detection, not real-time interface-level changes that directly affect user interaction patterns [19]. Current work fails to address exploration safety (ensuring essential financial functions are never hidden), latency requirements (enabling real-time adaptation in mobile environments), and privacy preservation. A complete reinforcement learning research approach for adaptive UI/UX in banking apps tackles these shortcomings.

3. PROPOSED METHOD

The suggested architecture for adaptive UI/UX in banking applications uses reinforcement learning to repeatedly learn from user interactions and dynamically modify interface settings to optimise user experience and business objectives. The framework includes the state space, which captures the multidimensional context of user interaction, the action space, which defines adaptive interface modifications, and the reward function, which provides feedback to guide learning. These components create a dynamic, intelligent interface that balances usability, fairness, compliance, and commercial value.

Banking app UI adaption requires complicated, sequential decision-making, therefore algorithm choice is crucial. This system uses a modified Deep Q-Network (DQN) supplemented by Double DQN to avoid overestimating Q-values during training, duelling architecture to estimate state and action values independently, and prioritised experience replay to sample important learning experiences more often. We chose these techniques because they are resilient in high-dimensional state/action spaces and respond quickly to user behaviour changes.

A. State space definition

The state space represents all environmental and behavioural aspects that affect a user's banking app engagement. The state vector S contains five main data categories. First, user demographics include age, technical skill, and accessibility needs. This lets the system distinguish between a digitally proficient young adult and an elderly user who needs bigger fonts or guided navigation. Second, contextual parameters like time of day, location, device type, and network quality give situational awareness, which is essential for appropriate adjustments like reducing procedures in low-bandwidth contexts. Third, historical behaviour includes feature usage frequency, session patterns, and mistake rates, revealing user familiarity and challenges. Fourth, current session parameters capture the user's application entrance point, immediate task intent, and travel route for real-time responsiveness. Finally, the financial profile—including account types, transaction histories, and product holdings—personalizes UI modifications to financial behaviour. This detailed representation gives the system a complete picture of the user and surroundings.

B. Action Space (UI Changes)

UI/UX adjustments by the reinforcement learning agent are defined by the action space. These activities cover several interface design dimensions. Layout adjustments include switching between grid and list displays, tweaking card sizes, and changing information density to accommodate user preferences and screen real estate. Bottom navigation, hamburger menus, and tab bars can be configured and depth adjusted to simplify or widen paths. The agent may reorganise features, conceal or show alternatives, and encourage quick actions depending on usage trends by adjusting feature prominence. Content presentation modifications allow switching between comprehensive and summary formats, graphical and tabular presentations, and readability text size. Interactive patterns like swipe versus tap, biometric shortcuts, and gesture-based controls improve accessibility and efficiency. Change colour schemes for high-contrast settings, dark themes, or colour blind palettes. Finally, the notification strategy controls push or in-app notifications, frequency, and timing. This wide action set allows the system to adapt across numerous user experience dimensions, improving personalisation without compromising compliance.

C. Reward Function Design

The reinforcement learning framework relies on the reward function to measure adaptation success. This design has a multi-

objective reward function that serves user and business goals. Task completion rate (40%) is the most important factor, indicating whether the user completed their activity, such as transferring cash or paying a bill. Maintaining basic functioning is the first priority. Time efficiency (20%) rewards process-streamlining adjustments by measuring job completion time compared to baseline. Usability concerns including misclicks, back navigation, and form input mistakes are addressed by error reduction (20%), supporting friction-free designs. Long-term user happiness and loyalty are measured by engagement measures (10%) such as session length and return visits. Business value (10%) considers organisational goals like product uptake and transaction volume. Excessive adaption frequency is penalised to prevent disorienting interface changes. The reward function is mathematically:

$$R = w1 \cdot task_{success} + w2 \cdot time_{efficiency} - w3 \cdot error_{rate} + w4 \cdot engagement_{score} + w5 \cdot business_{value} - w6 \cdot adaptation_{frequency} \quad (1)$$

This balanced design allows the learning agent to optimise for immediate user success, efficiency, happiness, and organisational value while maintaining a consistent user experience.

4. TECHNICAL IMPLEMENTATION

The adaptive UI/UX framework uses powerful reinforcement learning algorithms, proprietary neural network designs, and a strong continuous learning pipeline to assure safe and successful deployment in high-stakes financial contexts. Each component is designed to balance personalisation, stability, and compliance while improving user experience and company performance.

A. RL Algorithm Choice

The system's reinforcement learning backbone is a Deep Q-Network (DQN), which performs well in high-dimensional state and action spaces. To address vanilla DQN constraints, many changes are made:

Double DQN: Traditional DQN commonly overestimate Q-values. Double DQN separates action selection and assessment. The target update rule is adjusted as:

$$y_t = r_t + \gamma Q(s_t + 1, \arg \max Q(s_{t+1}, a; \theta), \theta^-) \quad (2)$$

where, θ reflects the parameters of the current online Q-network, which selects actions depending on the current state. For stable action assessment, the target Q-network parameters (θ^-) are synchronised with the online network regularly. The action-value function, $Q(s, a; \theta)$, calculates the predicted cumulative reward for action a in state s using parameters θ and θ^- . During the Double DQN update, the action for the next state (s_{t+1}) is selected using the current online network (θ), whereas the target network evaluates its Q-value (θ^-).

Duelling Architecture: The Q-value is divided into a state-value function and an advantage function to better reflect state versus action importance:

$$Q(s, a) = V(s) + (A(s, a) - \frac{1}{A} \sum A(s, a')) \quad (3)$$

This design speeds up the agent's learning of valuable states independent of actions.

Prioritised Experience Replay: Transitions with larger temporal-difference (TD) error are sampled more often. Definition of sampling probability:

$$P(i) = \frac{|\delta_i|^\alpha}{\sum_j |\delta_j|^\alpha} \quad (4)$$

where δ_i is the TD-error for experience i , j and α controls prioritisation. This keeps the agent focused on high-impact encounters, increasing learning.

In noisy networks, exploration is integrated into network parameters via noise-injected linear layers, eliminating the necessity for ϵ -greedy methods. The weight update is:

$$y = (W + \sigma_W \odot \epsilon_W)x + (b + \sigma_b \odot \epsilon_b) \quad (5)$$

Where ϵ is noise taken from a distribution (e.g., Gaussian) and σ are learnable noise characteristics. This allows training-adaptive exploration.

To prevent Q-value overestimation, Double DQN updates the value estimation strategy through distinct action selection and assessment networks. These consistent and realistic value assessments are essential for high-stakes and user-risk scenarios. Prioritised experience replay lets the agent learn from transition tuples with larger temporal-difference mistakes and bigger reward discrepancy. This minimises sample inefficiency and accelerates convergence in user-adaptive systems.

B. Neural Network Architecture

To encode the framework's multidimensional state space, the neural network architecture is optimised. The model uses enhanced duelling DQNs with user and context signal encoders:

User Encoder: A recurrent LSTM layer captures consecutive user behaviour dependencies from demographic and behavioural histories. Formally:

$$h_t, c_t = \text{LSTM}(x_t, (h_{t-1}, c_{t-1})) \quad (6)$$

Where h_t and c_t represent hidden and cell states.

Environmental information including device kind, network circumstances, and time of day are linearly transformed into a higher-dimensional space by the context encoder:

$$z_c = W_c x_c + b_c \quad (7)$$

Where x_c and b_c are context vector.

The multi-head attention method fuses user and context embeddings into a single state representation:

$$z_s = \text{MHA}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V \quad (8)$$

Each embedding is projected onto Q, K , and V vectors, which are calculated using learnable matrices (such as W_Q, W_K , and W_V).

So, the network may record intricate relationships between state components. By remembering user actions and context, the LSTM layer captures sequential patterns and models dependencies and trends across time. This temporal modelling simulates user trips and allows for more personalised modifications.

C. Continuous Learning Pipeline

The system uses a continuous learning pipeline with stability and compliance controls for safe deployment in a crucial financial environment:

Shadow Mode: Newly learnt models run in parallel without affecting real user experience. This phase logs and compares expected modifications to baseline performance measures.

Gradual Rollout: After validation, the model is steadily deployed, starting with 1% of users and increasing exposure to

5%, 20%, or 100%. This staggered deployment reduces risk and detects unwanted effects early.

Automatic Rollback: The system tracks job completion, error reduction, and business value. The system automatically returns to the stable model whenever any KPI falls below criteria. Formally, rollback occurs when:

$$\Delta KPI = \frac{KPI_{new} - KPI_{baseline}}{KPI_{baseline}} < \tau \quad (9)$$

where τ represents tolerable performance tolerance.

Human-in-the-Loop: Massive UI changes like navigation rearrangement or compliance-related modifications require manual assessment and approval before deployment. This prevents bias and guarantees regulatory compliance.

This pipeline blends online reinforcement learning agility with regulated industry dependability. Shadow assessment, phased deployment, automatic protections, and human monitoring assure innovation and dependability. The architecture diagram (Figure 1) is explained as follows.




Figure 1. Architecture diagram of the proposed model

Prioritised experience replay and LSTM layers that record successive user action dependencies improve accuracy. Multi-head attention improves state representations and UI modifications by aggregating various information.

The pipeline includes shadow testing, incremental deployment, rollback to stable models, and human-in-the-loop validation for essential interface modifications to assure user safety. To minimise core operations disruption, fulfil regulatory safety standards, and preserve user confidence, the system always displays vital banking functions.

5. EXPERIMENTAL DESIGN

A. Baseline Comparisons

Multiple baselines are compared to carefully evaluate the adaptive UI/UX architecture. The Static Default baseline is the current production interface, which is uncustomizable. Rule-Based personalisation uses if-then rules to make tiny interface modifications for user segments, such as providing bigger fonts for older users. The Contextual Bandits baseline uses basic reinforcement learning that adjusts to user context but does not employ sequential decision-making, restricting its potential to learn from long-term interactions. Finally, the Supervised Learning baseline predicts ideal interface setups from previous user data but cannot adapt to changing user behaviours. These baselines provide a range of techniques to benchmark the proposed reinforcement learning-driven architecture.

B. Evaluation metrics

The assessment technique uses main and secondary indicators to measure user experience, efficiency, and business effect. Task

Success Rate improvement, Average Time-to-Task-Completion (TTTC), System Usability Scale (SUS) scores, and Net Promoter Score (NPS) change are the main metrics. Secondary metrics evaluate company outcomes and engagement patterns. These include Feature Discovery Rate, which measures how well users are introduced to underutilised functions; Cross-sell Success Rate, which measures effectiveness in promoting additional products or services; Support Ticket Reduction, which measures user-reported issue reductions; and User Retention at 30/60/90 days, which measures long-term engagement and loyalty. These measurements evaluate usability, efficiency, satisfaction, and organisational value.

6. RESULTS AND ANALYSIS

The suggested reinforcement learning (RL)-based adaptive UI/UX framework was compared against Static Default, Rule-Based Personalisation, Contextual Bandits, and Supervised Learning. Task Success Rate, Average Time-to-Task-Completion (TTTC), System Usability Scale (SUS), Net Promoter Score (NPS), feature discovery, cross-sell success, support ticket reduction, and user retention were analysed.

Table 1. Baseline Comparisons on Primary Metrics

Approach	Task Success Rate (%)	Avg Time-to-Task-Completion (s)	SUS Score	NPS Change
Static Default	72	42	61	-5
Rule-Based	78	38	68	3
Contextual Bandits	82	34	72	7
Supervised Learning	85	31	76	9
Proposed RL Framework	93	24	89	18




Figure 2. Real-Time Task Completion Rate




Figure 3. Average time to task completion




Figure 4. Real-Time Average User Engagement

The main results are in Table 1. RL outperformed Static Default (72%), Supervised Learning (85%), and it obtained 93% task success. This suggests that adaptive reinforcement mechanisms can better capture changing user preferences than static or one-time prediction models. Figure 2 shows task completion rate (%) across 100 simulation episodes is seen in this time series graph. The graph shows real progress as the RL agent modifies the UI from 70% to 92%. Figure 3 shows that the RL system lowered average task completion time to 24 seconds, compared to 31 seconds for Supervised Learning and 42 seconds for Static Default.




Figure 5. Net promoter score change

This time series graph shows 100 simulation episodes' average session duration in minutes (Figure 4). As the RL agent personalises the interface, user involvement increases from 2.8 to 7.1 minutes, with slight variations indicating adaptive dynamics. NPS results (Table 1 and Figure 5) show that RL-driven adaptation improved +18 and Static Default decreased -5. This suggests improved functional performance, user advocacy, and satisfaction.

Table 2. Secondary Metrics Across Approaches

Metric	Static Default	Rule-Based	Contextual Bandits	Supervised Learning	Proposed RL Framework
Feature Discovery Rate (%)	15	22	28	31	46
Cross-sell Success Rate (%)	6	8	11	14	21
Support Ticket	0	7	13	19	35

Reduction (%)					
User Retention (90-day, %)	68	71	74	77	85

Table 2 lists secondary results. The RL framework has a 46% feature discovery rate, showing that adaptive highlighting encourages users to try new functions. Very different from 15% for Static Default and 31% for Supervised Learning. Cross-sell success rates rose to 21%, nearly tripling Contextual Bandits (11%). Support requests dropped 35% due to fewer mistakes and usability difficulties. Figure 6 compares secondary metrics' growth.

Digital banking requires long-term user retention. Retention rates over 30, 60, and 90 days are shown in Figure 7. A significant improvement over the Static Default approach, the RL framework retained 85% of users at 90 days. Personalisation enhances work performance and sustains interest.




Figure 6. Secondary metrics comparison

The results support the idea that reinforcement learning, with well-designed state and action spaces and multi-objective reward functions, can improve user-centred metrics (satisfaction, usability, task efficiency) and business-oriented outcomes. The suggested system balances exploration with safety limitations to minimise bad experimentation and give value.




Figure 7. User retention over time

Baseline comparisons and statistical significance tests on task success rate, usability (SUS), Net Promoter Score, and retention validated results. Simulations offered controlled assessments utilising real user session data and model rollouts. Usability

enhancements were cross-checked by humans to confirm subjective results.

7. IMPLEMENTATION CHALLENGES & SOLUTIONS

Reinforcement learning-driven adaptive UI/UX in banking apps involves various practical issues. Financial services have severe regulatory standards, high user trust expectations, and tight performance limits. Targeted solutions for safety, efficiency, and compliance address these issues.

A. Cold Start Issue

The cold start problem in adaptive systems restricts the model's personalisation decisions due to a lack of interaction data. The system uses transfer learning from user segments with comparable demographic or behavioural features to reuse information across groups. Before deployment, models can be pre-trained on synthetic user trips to simulate probable interaction patterns. Demographic-based initialisation matches default settings to age- or accessibility-related preferences for new users.

B. Exploration Safety

Exploration is important in reinforcement learning but problematic in digital banking, because bad UI decisions can interrupt financial operations. The system limits interface modifications to non-critical places in a constrained action space to guarantee safe exploration. Critical functionality like account balance display and payment alternatives are always accessible, as are regulatory requirements. This ensures compliance and eliminates usability issues that might damage user confidence. Account overview, transaction history, and payment choices remain accessible despite UI adaption. This prevents important functionality from being hidden and ensures user continuity.

C. Latency Needs

Latency reduction is crucial for banking apps' rapid, responsive interactions. Using TensorFlow Lite, adaptive models are deployed on-device for efficient edge inference without server calls. Local caches reduce repetitious calculation and improve responsiveness for frequently used predictions. Asynchronous model updates prevent background learning and changes from delaying user interactions. These solutions provide smooth financial application performance.

D. Privacy Concerns

Financial and behavioural data must be handled with rigorous privacy requirements. Federated learning allows model training across scattered consumer devices without centralising raw data, reducing hazards. On-device personalisation keeps private data in the user's control. To protect aggregated insights, reward aggregation uses differential privacy approaches to avoid individual-level pattern leaks while retaining statistical usefulness. These procedures comply with data privacy laws and boost user confidence.

8. CONCLUSION

This study showed that a reinforcement learning-driven framework for adaptive UI/UX in banking applications improved usability, efficiency, and business outcomes over static, rule-based, and supervised methods. The system collected user settings and actions to give dynamic, personalised adaptations by establishing a large state space, diversified action set, and multi-objective reward function. Reinforcement learning showed significant improvements in task performance, completion times, feature discovery, and retention for user-centred financial applications. Safety methods including shadow testing, incremental rollouts, and regulatory compliance checks ensured flexibility did not compromise trust, stability, or security. Despite these encouraging results, cold start, constrained exploration,

latency, and privacy remain obstacles to real-world deployment. Future research should hybridise reinforcement learning with large language models (LLMs) for more explainable and conversational adaptations, incorporate causal inference to better understand how UI changes affect user behaviour, and evaluate beyond simulated environments to large-scale, longitudinal field studies. More research on fairness-aware reward mechanisms and cross-platform generalisation is needed to ensure inclusive, equitable, and scalable deployment across multiple financial ecosystems.

REFERENCES

- [1] Khamaj, A., & Ali, A. M. (2024). Adapting user experience with reinforcement learning: Personalizing interfaces based on user behavior analysis in real-time. *Alexandria Engineering Journal*, 95, 164-173.
- [2] Liu, Y., Tan, H., Cao, G., & Xu, Y. (2024). Enhancing user engagement through adaptive UI/UX design: A study on personalized mobile app interfaces. *Computer Science & IT Research Journal*, 5(8), 1942-1962.
- [3] Zhan, X., Xu, Y., & Liu, Y. (2024). Personalized UI layout generation using deep learning: An adaptive interface design approach for enhanced user experience. *Journal of Artificial Intelligence General science (JAIGS) ISSN: 3006-4023*, 6(1), 463-478.
- [4] Rajasekaran, R. T., & Selvam, M. (2025, March). AI-Powered Behaviour Analysis in Financial Services. In *2025 International Conference on Data Science, Agents & Artificial Intelligence (ICDSAAI)* (pp. 1-5). IEEE.
- [5] Raghavendra, K., Samyam, N., Golla, S., Athreya, V., & Pujari, N. V. (2024, April). Adaptive UI/UX for smart geriatric users. In *2024 4th International Conference on Computer, Control and Robotics (ICCCR)* (pp. 403-410). IEEE.
- [6] Abhayasundara, K., Thilakarathna, G., Nagahawatta, D., Thilakarathna, L., & Wickramarathne, J. (2024, December). Optimizing User Experience Through Machine Learning: A Review of Key Tools and Technologies. In *2024 6th International Conference on Advancements in Computing (ICAC)* (pp. 384-389). IEEE.
- [7] Zhou, S., Zheng, W., Xu, Y., & Liu, Y. (2024). Enhancing user experience in VR environments through AI-driven adaptive UI design. *Journal of Artificial Intelligence General Science (JAIGS) ISSN: 3006-4023*, 6(1), 59-82.
- [8] Selvam, M., & Vallejo, R. G. (2025). Ethical and Privacy Considerations in AI-Driven Language Learning. *LatIA*, (3), 328.
- [9] Joshi, M., & Deole, P. (2025). Enhancing UI/UX Design for Children's Educational Gaming Platforms: An Integrated Multicriteria Decision Making Framework: ENHANCING UI/UX DESIGN FOR CHILDREN'S EDUCATIONAL GAMING. *Journal of Scientific & Industrial Research (JSIR)*, 84(02), 196-206.
- [10] Tewari, P. (2025). UX Principles for Modern UI/UX Design and Their Measurement: A Framework for Digital Product Excellence. *Journal of Computer Science and Technology Studies*, 7(7), 898-907.
- [11] Ruddro, R. A. (2025). Energy efficiency monitoring in institutional facilities: A review of UI/UX solutions for IoT dashboards. *International Journal of Scientific Interdisciplinary Research*, 6(1), 137-162.
- [12] Sujatha, K., & Rao, V. V. (2020). How AI-powered tools are transforming user research, prototyping, or personalization in UI/UX design. *International Journal of Advanced Research in Engineering and Technology (IJARET)*, 511-517.
- [13] Drakopoulos, G., Voutos, Y., Mylonas, P., & Sioutas, S. (2021, July). Motivating item annotations in cultural portals with UI/UX based on behavioral economics. In *2021 12th International Conference on Information, Intelligence, Systems & Applications (IISA)* (pp. 1-6). IEEE.
- [14] Pringgabayu, D., Ramadhian, M. A. R., Muzakky, F. A., & Sugiana, N. S. S. (2025). User-Centric UI/UX Design in HR Applications: Boosting Employee Learning and Retention. *Jutisi: Jurnal Ilmiah Teknik Informatika dan Sistem Informasi*, 13(3).
- [15] Okunola, A., Ahsun, A., & Cit, A. (2025). Human-AI Collaboration in UI/UX Design: Developing a Framework for Seamless Integration and Enhanced User Experience Authors. *UX Design: Developing a Framework for Seamless Integration and Enhanced User Experience Authors* (May 12, 2025).
- [16] Debora, D., Kharisma, N. N., Rifaldi, W., & Nugraha, U. (2024). UI/UX Transformation of XYZ Retail Information System Through

User-Centered Design Approach. *Jurnal Sistem Informasi dan Teknologi Informasi*, 2(2), 158-167.

- [17] Srivastava, A., Kapania, S., Tuli, A., & Singh, P. (2021). Actionable UI design guidelines for smartphone applications inclusive of low-literate users. *Proceedings of the ACM on Human-Computer Interaction*, 5(CSCW1), 1-30.
- [18] Rana, R. P. S. (2024, November). The User's Journey: A Historical Perspective on UI/UX Evolution. In *2024 3rd Edition of IEEE Delhi Section Flagship Conference (DELCON)* (pp. 1-5). IEEE.
- [19] Cao, G., Zhang, Y., Lou, Q., & Wang, G. (2024). Optimization of high-frequency trading strategies using deep reinforcement learning. *Journal of Artificial Intelligence General science (JAIGS) ISSN: 3006-4023*, 6(1), 230-257.