CAPSTONE PROJECT | FINAL CONSOLIDATED REPORT | SPRINTS 1-5

Container Image Vulnerability Scanner with Reporting

A policy-driven container scanning system with auditable reports, CI gates, Slack notifications, governed exceptions and persistent vulnerability monitoring.

Submitted by: Tabrez Ajaz

GitHub account: TabrezAjaz

Report date: 30 October 2026

Implementation branch: main

Scanner engine: Trivy 0.74.0

Python wrapper: 0.5.0

Implementation baseline: 399d1af

Integrated deterministic suite: 77 tests

https://github.com/TabrezAjaz/CapstoneProject | Operating documentation | Printable PDF edition

> **Project status:** The Sprint 1-5 implementation is integrated on main, with automated tests, CI security gates, reporting and local monitoring validated. Jenkins Slack delivery is verified. Remaining notification configuration and verification limits are listed in Section 13.

This report documents my project objectives, implementation, testing and results across five sprints. Screenshots and original execution artifacts accompany the results. Vulnerability counts depend on the scan date, image and advisory database.

Contents

1. Executive Summary
2. Objectives and Traceability
3. Implementation and Repository
4. Deployment Architecture
5. Sprint 1: Setup and Scanning
6. Scanner and Gate Contract
7. Sprint 2: CI/CD Integration
8. Sprint 3: Reports and Slack
9. Scheduled Automation
10. Sprint 4: History and Monitoring
11. Sprint 5: Exceptions and Reliability
12. Verification Matrix
13. Security and Limitations
14. Reproduction and Handover
15. Challenges and Decisions
16. Evidence Register
17. Milestone Appendices
18. Conclusion

1. Executive Summary

My objective was to integrate container vulnerability scanning into a repeatable development workflow, with clear security decisions and reviewable results. I used Trivy as the scanning engine and implemented a Python wrapper to load configuration, validate results, apply approved exceptions, write normalized evidence and return consistent exit codes. GitHub Actions and Jenkins use the same implementation.

A strict reporting layer renders JSON, HTML and PDF from one canonical model and publishes SHA-256 manifests. Slack messages distinguish severity and scheduled portfolio summaries. A separate local monitoring deployment imports original observations into SQLite and exposes a read-only Flask/Chart.js dashboard and Prometheus metrics; Grafana queries Prometheus for sampled time-series views.

The final implementation includes reasoned, scoped and expiring exceptions, preserved suppression audit, fresh rescan lineage, classified retries, process deadlines and atomic artifact writes. The integrated suite contains 77 deterministic tests. GitHub main run #31, for baseline `399d1af`, completed successfully. Its Slack step was skipped, not delivered, because the repository secret is absent.

2. Objectives and Requirement Traceability

Sprint	Acceptance objective	Delivered implementation	Primary evidence
1	Establish repository, install scanner and perform image scans	Python wrapper, YAML configuration, pinned Trivy and normalized findings	Fresh core verification log; original baseline/rescan artifacts; latest real CI scan

Sprint	Acceptance objective	Delivered implementation	Primary evidence
2	Make vulnerability scanning a CI/CD gate	Shared severity policy, stable exits, GitHub/Jenkins pipelines and retained evidence	Real passing and intentionally blocked GitHub/Jenkins captures
3	Generate reports, notify and automate summaries	JSON/HTML/PDF, checksum manifest, Slack transport, daily/weekly jobs	Generated report bundle; main HIGH/CRITICAL delivery records; default-cadence runs
4	Track findings/history with filters and monitoring	SQLite, Flask API/UI, Prometheus exporter and provisioned Grafana	Desktop/mobile captures, target UP, Grafana panels and browser-check JSON
5	Manage accepted risk, rescans and failures	Expiring scoped policy, suppression audit, fresh lineage, bounded retries and strict validation	Approved/expired artifacts, rescan lineage, audit report and 77-test JUnit evidence

Scope: OS-package vulnerabilities are scanned by default, including unfixed findings. Language dependency scanning, Teams/email delivery, automatic registry-digest watches and a publicly authenticated monitoring service are outside the delivered scope. The submission covers Sprints 1-5, not a separately claimed Sprint 6.

3. Implementation and Repository

Component	Technology / location	Responsibility
Scanning and policy	Trivy 0.74.0; scanner/trivy_scanner.py; scanner/exceptions.py	Execute scans, normalize findings, apply exceptions and enforce exit contracts
Configuration	config.yaml; exceptions/allowlist.yaml; .env.example	Non-secret policy defaults and documented environment overrides
Reporting	reporters/; Jinja2; ReportLab	Strict artifact loading, canonical model, JSON/HTML/PDF and integrity manifests
Notification	notifiers/	Validated Slack webhook transport with bounded retries and mention sanitization
History and metrics	dashboard/; Flask; SQLite; prometheus-client	Idempotent imports, read-only API, exact finding transitions and /metrics
Visualization	Vendored Chart.js and Lucide; Prometheus 3.2.1; Grafana 11.6.0	Local scan exploration and sampled monitoring dashboards
CI and tests	.github/workflows/; ci/; tests/	Real scans, gate/report orchestration, deterministic tests and evidence archives

CI uses Python 3.12; local verification has used Python 3.14. Python dependencies have bounded version ranges, not a claim of fully locked transitive dependencies. Runtime databases, raw operational outputs, credentials and virtual environments are excluded from Git. Small public demonstration artifacts are intentionally archived under docs/evidence.

I maintained milestone branches for the individual sprints and integrated the final implementation on main. The linked milestone runs record the code and test suite available at that stage; final-version verification is identified separately.

4. Implemented Deployment Architecture




Figure 1. Final deployment architecture. Hosted CI and the local monitoring host are separate environments. The dotted handoff represents manual artifact download and import.

Full-size vector | High-resolution PNG | Editable Mermaid source

GitHub runners and Jenkins agents are alternative execution environments. The scanner runs as a short-lived CLI. The persistent local Flask exporter serves SQLite observations after scans finish; Prometheus scrapes it every 15 seconds and Grafana queries Prometheus. SQLite preserves scan timestamps, while Prometheus records samples from the start of scraping.

5. Sprint 1: Foundation and Basic Scanning

The initial structure separated scanner, configuration, CI, reporting, notification, exceptions, tests and documentation. Trivy was chosen as the underlying scanning engine rather than recreating advisory matching in Python. Registry-reference scans do not require mounting the Docker socket. The scanner downloads/refreshes its advisory database and uses the local cache during analysis.

Setup Procedure

1. Clone the project repository and create an isolated Python environment.
2. Install the project and development dependencies, then install Trivy 0.74.0 and verify that it is available on PATH.
3. Configure scan severity, output paths and timeout in config.yaml. Keep credentials outside version control.
4. Scan a clean image and a vulnerable image; check the normalized findings and the corresponding policy exit codes.

Section 14 provides the commands for reproducing the environment, scans, reports and monitoring deployment.

I checked the final scanner version against a clean image and an image with known package vulnerabilities. The command-output log, normalized clean-image and vulnerable-image artifacts record the commands and results. These final verification runs complement the earlier sprint evidence.

Fresh final-version scan	Original scan ID and UTC time	Observed outcome
hello-world:latest	`27c31b93-4f66-423d-8dd4-6fbae32a70da` 2026-10-29T20:54:15.297881Z	0 findings; 0 blocking; exit 0
alpine:3.19	`59b455b0-e86c-40a7-8bbe-0ff1ef0b9a21` 2026-10-29T20:54:17.970747Z	10 active findings including 2 HIGH; 2 blocking; exit 1

The log records the scanner version and cached database timestamps. Artifact timestamps use UTC; the local Python log clock uses the host timezone.

```
Verification captured UTC: 2026-10-29T20:54:11.0881481Z
Version: 0.74.0
Vulnerability DB:
  Version: 2
  UpdatedAt: 2026-10-29 13:09:46.269823229 +0000 UTC
  NextUpdate: 2026-10-30 13:09:46.269822928 +0000 UTC
  DownloadedAt: 2026-10-29 13:57:48.6240251 +0000 UTC
Command: python -m scanner.trivy_scanner hello-world:latest --exceptions-file
exceptions/allowlist.yaml --fail-on HIGH --output-dir scan-results/final-core-clean
2026-10-30 02:24:12,442 INFO Scanning image=hello-world:latest severities=LOW,MEDIUM,HIGH,CRITICAL
2026-10-30 02:24:15,297 INFO Done image=hello-world:latest summary={'CRITICAL': 0, 'HIGH': 0,
'MEDIUM': 0, 'LOW': 0, 'UNKNOWN': 0}
2026-10-30 02:24:15,302 INFO POLICY PASSED image=hello-world:latest
{
  "image": "hello-world:latest",
  "summary": {
    "CRITICAL": 0,
    "HIGH": 0,
    "MEDIUM": 0,
    "LOW": 0,
    "UNKNOWN": 0
  },
  "fail_on": "HIGH",
  "blocking_findings": 0,
  "artifact": "scan-results\\final-core-clean\\hello-world_latest-e6c1104d.json"
}
Observed clean-image exit: 0
Command: python -m scanner.trivy_scanner alpine:3.19 --exceptions-file exceptions/allowlist.yaml --
fail-on HIGH --output-dir scan-results/final-core-vulnerable
2026-10-30 02:24:15,616 INFO Scanning image=alpine:3.19 severities=LOW,MEDIUM,HIGH,CRITICAL
2026-10-30 02:24:17,970 INFO Done image=alpine:3.19 summary={'CRITICAL': 0, 'HIGH': 2, 'MEDIUM': 5,
'LOW': 3, 'UNKNOWN': 0}
2026-10-30 02:24:17,975 ERROR POLICY BLOCKED image=alpine:3.19 blocking_findings=2
{
  "image": "alpine:3.19",
  "summary": {
    "CRITICAL": 0,
    "HIGH": 2,
    "MEDIUM": 5,
    "LOW": 3,
    "UNKNOWN": 0
  },
  "fail_on": "HIGH",
  "blocking_findings": 2,
  "artifact": "scan-results\\final-core-vulnerable\\alpine_3.19-6bd2275d.json"
}
Observed vulnerable-image exit: 1
```

Figure 2. Original saved command output viewed in Chrome: Trivy version, clean scan with exit 0 and vulnerable scan with exit 1. This is a browser view of the retained log, not a terminal screenshot.

Original dated observations remain available in baseline.json and rescan.json. Their source fields, UUIDs, timestamps, scanner versions and full findings provide inspectable evidence beyond a screenshot.

6. Scanner and Policy Contract

```
CLI / environment / YAML configuration
  -> validate policy and exact exception scopes
  -> invoke Trivy and validate result structure
  -> normalize raw findings
  -> separate approved, unexpired findings into suppression audit
  -> recompute active severity counts and gate
  -> atomically write normalized scan evidence
  -> return pass / policy / configuration / operational exit
```

Exit	Meaning	Expected action
0	Completed and passed the configured policy	Continue pipeline
1	Completed but active findings violate the severity gate	Intentional build block; retain reports and artifacts
2	Invalid CLI/configuration/exception policy	Correct the input; never claim the image is clean
3	Scanner/registry/timeout/parsing/write operation failed	Investigate operational failure; fail closed

Precedence is CLI > environment > YAML > defaults. The default threshold is HIGH, with CRITICAL also blocking. Input validation, explicit timeout handling and malformed-output rejection prevent an error or empty malformed object from appearing as a safe scan. The reference environment file is documentation, not automatically loaded dotenv configuration.

7. Sprint 2: CI/CD Integration

GitHub Actions and Jenkins install the pinned engine, refresh the database, run tests and invoke the same wrapper. The scan result is retained while valid artifacts are rendered and archived. Final gate enforcement restores an intentional policy block even when reports and notifications succeed. An upload attempt does not guarantee evidence exists after every possible infrastructure failure.

Historical verification	Observed outcome	Interpretation
GitHub gate run #6	Success with evidence artifact	Passing control path
GitHub gate run #5	Exit 1 with evidence artifact	Successful policy enforcement, not a broken implementation
Jenkins Sprint 2 build #2	hello-world:latest passed; 16 tests at that milestone; JSON archived	Clean image path
Jenkins Sprint 2 build #3	alpine:3.19 blocked with 2 HIGH findings; JSON archived	Threshold block preserved evidence

Historical verification	Observed outcome	Interpretation
Latest baseline main run #31	Success for 399d1af: tests, real scan, reports and upload	Current integrated implementation; Slack skipped




Figure 3. Passing GitHub Actions pipeline at the Sprint 2 milestone.




Figure 4. GitHub Actions pipeline blocked by the vulnerability policy, demonstrating enforcement of the security gate.




Figure 5. Passing Jenkins Sprint 2 build #2 with the clean-image JSON artifact archived.




Figure 6. Jenkins console showing the intentional HIGH-threshold policy block.





Figure 7. Successful main-branch integration run #31 for baseline 399d1af, with the evidence artifact retained.

Machine-readable current verification: run metadata, step outcomes and uploaded artifact metadata. The public run URL is 40951355890 / #31.

8. Sprint 3: Reports and Slack Notifications

Schema 1.0 normalized scans feed a strict loader that validates severity counts, policy state and suppression audit. One canonical model generates JSON, autoescaped HTML and PDF. A manifest records output filename, media type, byte size and SHA-256. Checksums demonstrate integrity against a trusted manifest; they do not prove authorship or approval identity.

The archived approved-scan report is available as JSON, HTML and PDF, with its original checksum manifest. All outputs retain the same report identity.



Container Vulnerability Report

Run security report · 2026-10-29T18:28:39.159725Z

Status: **PASSED**

Executive Summary

1	0	0	5	3
Images	Critical	High	Medium	Low

alpine:3.19

Policy PASSED · threshold HIGH · 0 blocking

Severity	CVE / advisory	Package	Installed	Fixed
MEDIUM	CVE-2024-58251	busybox	1.36.1-r20	1.36.1-r21
MEDIUM	CVE-2024-58251	busybox-binsh	1.36.1-r20	1.36.1-r21
MEDIUM	CVE-2024-58251	ssl_client	1.36.1-r20	1.36.1-r21
MEDIUM	CVE-2026-6042	musl	1.2.4_git20230717-r5	1.2.4_git20230717-r6
MEDIUM	CVE-2026-6042	musl-utils	1.2.4_git20230717-r5	1.2.4_git20230717-r6
LOW	CVE-2025-46394	busybox	1.36.1-r20	1.36.1-r21
LOW	CVE-2025-46394	busybox-binsh	1.36.1-r20	1.36.1-r21
LOW	CVE-2025-46394	ssl_client	1.36.1-r20	1.36.1-r21

Approved exceptions (excluded from gate)

Severity	CVE / advisory	Package	Reason	Expires (UTC)
HIGH	CVE-2026-40200	musl	Local verification only: demonstrate temporary risk acceptance; not approved for production	2026-10-30
HIGH	CVE-2026-40200	musl-utils	Local verification only: demonstrate temporary risk acceptance; not approved for production	2026-10-30

Exception policy: allowlist-alpine-demo.yaml · SHA-256 `1060e0f1fe57d528f43cb996a956d8dda37af0068758526a9377bba0dacf333b`

Report ID 63eae946-6250-4da5-aea1-7e17d20242a1 · Schema 1.0

Figure 8. Generated HTML report for the approved demonstration scan. Active findings and the two temporarily approved HIGH findings are shown separately.

Slack is the implemented provider. Webhooks are injected from environment/CI credentials, validated as permitted HTTPS Slack endpoints and never embedded in project configuration. Messages neutralize mass mentions and limit scan-controlled text. Delivery retries transient HTTP/network conditions and fails operationally after exhaustion.

Jenkins Sprint 3 execution	Evidence-based result
Main build #4: HIGH alert	Intentional policy failure; Slack delivered in one attempt; tests/reports retained
Main build #5: CRITICAL alert	Intentional policy failure; Slack delivered in one attempt; reports retained
Daily #16 / Weekly #4	SUCCESS; real Slack transport delivery and archived summary evidence
Daily #17 / Weekly #5	SUCCESS with saved defaults, correct cadence and delivery in one attempt

These are verified delivery logs, not screenshots proving channel-side receipt. Original controller links: HIGH #4, CRITICAL #5, Daily #17, Weekly #5. Academic Jenkins may require login and is subject to retention.

The following console records, retained in the Sprint 3 milestone report, show successful Slack transport delivery for alerts and scheduled-summary jobs.

Execution	Original delivery line
HIGH main #4	`[2026-10-29T06:37:57.366Z] Slack notification delivered in 1 attempt(s)`
CRITICAL main #5	`[2026-10-29T06:38:56.071Z] Slack notification delivered in 1 attempt(s)`
Daily #16	`[2026-10-29T06:39:35.504Z] Slack notification delivered in 1 attempt(s)`
Weekly #4	`[2026-10-29T06:40:17.337Z] Slack notification delivered in 1 attempt(s)`
Daily #17: saved defaults	`[2026-10-29T18:28:40.484Z] Slack notification delivered in 1 attempt(s)`
Weekly #5: saved defaults	`[2026-10-29T18:27:53.087Z] Slack notification delivered in 1 attempt(s)`




Figure 9. Jenkins daily-summary milestone build #1. Subsequent default-parameter delivery checks are recorded in the table above.




Figure 10. Jenkins weekly-summary milestone build.

9. Scheduled Automation

Platform	Configured cadence	Validation boundary
GitHub Actions	Daily 02:23 UTC; Monday 03:41 UTC	Workflow present on main. Manual daily summary run #1 succeeded; its Slack step was skipped.
Jenkins daily job	H 2 * * * UTC	Saved trigger and default auto cadence/NOTIFY=true verified; manually triggered default build #17 succeeded.
Jenkins weekly job	H 3 * * 1 UTC	Job name ending -Weekly selects weekly in auto mode; manually triggered default build #5 succeeded.

Scheduled summaries refresh the database and rescan configured images. A policy block is a valid portfolio summary result; operational failures fail the summary job. A successful manual dispatch verifies the workflow and defaults, not that a cron event actually fired. GitHub schedules also depend on platform scheduling/availability.

10. Sprint 4: Persistent History and Monitoring

The local importer accepts normalized scan artifacts, not report JSON or raw Trivy output. SQLite imports are transactional and idempotent by scan ID; conflicting ID reuse is rejected. Flask exposes a read-only API, history filters, scan details, approved-exception audit, JSON download and Prometheus exposition. Imports remain a local CLI action.

Service	Loopback URL	Persistence / role
Optional direct local Flask server	127.0.0.1:5050	Local development demonstration using the same history
Container Flask exporter/UI	127.0.0.1:5051	Read-only HTTP surface; host SQLite bind mount
Prometheus	127.0.0.1:9095	15-second scrapes; 15-day TSDB retention; named volume
Grafana	127.0.0.1:3030/d/container-security	Provisioned datasource/eight panels; anonymous Viewer; named volume

Latest active findings are pending. New and resolved findings compare exact advisory/package pairs against the previous stored observation. Suppressed pairs remain in this comparison, so accepting risk is not falsely reported as remediation. First observations are baselines. These transition metrics are gauges, not fabricated cumulative counters.




Figure 11. Desktop dashboard showing stored scan observations, inventory and charts.




Figure 12. Mobile dashboard at 390x844. Browser checks verified readable controls, nonblank charts and no horizontal page overflow.




Figure 13. Prometheus target page confirming that the exporter is UP.




Figure 14. Provisioned Grafana dashboard. Time-series history begins when Prometheus starts scraping the exporter.

Browser verification is archived in the original browser-check JSON. Checks cover 1440x1080 and 390x844, API/UI totals, filters, empty and invalid-date states, scan drilldown, deep-linked exception audit, nonblank canvas pixels and no JavaScript errors.

11. Sprint 5: Governed Exceptions, Rescans and Reliability

Exception rules require an exact advisory ID, a nonempty reason and a real YYYY-MM-DD expiry. Optional image/package scopes also match exactly; wildcards and duplicate scopes are rejected. The default production allowlist is empty. Expiry is inclusive through the specified UTC date, evaluated at scan time. Missing or malformed configured policies fail before scanning.

Suppression occurs before gate evaluation while preserving raw counts, approved findings, scope, justification, expiry and policy checksum. Implicit Trivy ignorefiles are disabled to prevent unaudited suppression. Accepted risk is distinct from a vulnerability being fixed.

Real 29 October Alpine demonstration	Active / suppressed	Exit	Original evidence
Temporary non-production approval	8 active; 2 HIGH suppressed; 0 blocking	0	approved.json

Real 29 October Alpine demonstration	Active / suppressed	Exit	Original evidence
Expired rule	10 active; 0 suppressed; 2 HIGH blocking	1	expired.json
Missing configured exception file	No scan performed	2	Deterministic tests and Sprint 5 execution record




Figure 15. Exception audit for the approved historical scan: two HIGH findings with recorded justification and expiry. The background inventory reflects a later observation.

Fresh Rescan Lineage

Baseline `fa356ec8-553d-4769-bb81-20aeb03b599b` at `2026-10-29T13:57:51.161781Z` was followed by a real new Trivy scan `3531bf6a-0b7e-491d-aebb-b4d881adb621` at `2026-10-29T13:57:53.922734Z`. Its `rescan_of` points to the baseline. Both were blocked; no remediation was invented. The artifacts are linked in the evidence register.

Reliability Controls

Defaults permit two retries after the initial attempt with 1s/2s exponential delays. Recognized transient network/registry conditions and process timeouts may retry; authentication failures, missing manifests/executables and invalid JSON fail fast. Each attempt has the configured Trivy timeout plus a 30s

outer deadline. Database refresh shares the classified retry helper. Atomic replacement prevents partial successful-looking JSON artifacts.

Recovery, exhaustion, permanent failures, deadlines, malformed result structures and write failures are covered by controlled deterministic tests. A live registry outage or network fault injection was not performed and is not claimed.

12. Verification Matrix

Verification	Evidence / observed result	Status
Integrated tests	77 deterministic tests; archived JUnit: 0 failures, 0 errors	**Verified**
Local integrated test run	JUnit results and original test output	**Evidence attached**
Current main CI	Run #31 / 399d1af; success; scan/tests/reports/upload completed	**Verified**
Clean and vulnerable scan paths	Original final-version core log/artifacts plus historical real CI pass/block captures	**Verified**
Report integrity	Original JSON/HTML/PDF manifests match archived bytes, including clean Git checkout verification	**Verified**
Slack transport	Jenkins HIGH/CRITICAL and daily/weekly delivery logs	**Verified on Jenkins**
GitHub Slack	Repository secret absent; notification step skipped	Configuration pending
Historical UI and monitoring	Real screenshots, browser-check JSON and observed exporter/Grafana health	**Verified at capture**
Approved and expired exceptions	Original active/suppressed artifacts and gate exits 0/1	**Verified**
Rescan lineage	New UUID/time and rescan_of; actual new scan invocation	**Verified**

Milestone test counts increased as the project grew: Sprint 2 had 16 tests, Sprint 3 had 28, isolated Sprint 4 had 35 and the integrated final suite has 77. Dashboard verification used eight stored scan observations; large-scale production benchmarking is outside the evaluation scope.

13. Security, Limitations and Outstanding Actions

- Webhooks are stored in CI secret stores. Rotation of the previously exposed webhook remains a required security action.
- GitHub and Jenkins secret stores are separate. GitHub Slack delivery remains unverified until its repository secret is entered and delivery is rerun.

- Channel-side Slack screenshots remain unavailable. A delivery-success log proves transport acceptance, not independent visual receipt.
- Allowlist changes need human review and branch controls. The code does not establish an approver identity or enforce organization governance by itself.
- Loopback binding, read-only API, nonroot dashboard container and restrictive web headers reduce exposure. Flask development hosting and anonymous Grafana Viewer are not a public production security model.
- Monitoring history requires explicit artifact download/import. No central CI collector, remote write API, Node Exporter or Pushgateway is deployed.
- Prometheus rules cover stale scans/exporter health/critical findings. Alertmanager-based external delivery is not configured.
- Registry/image tags and advisory databases change. Pinned scanner versions alone do not make future scan counts deterministic.
- Absence of a finding within the selected scan scope is not proof of patch installation or absence of all security risk.
- Python dependencies are bounded ranges; action references use release tags rather than universal commit-SHA pinning. Broader supply-chain hardening is future work.
- No paid infrastructure is provisioned. Local compute, downloads, service quotas, retention and academic Jenkins availability still have operational constraints.

14. Reproduction and Handover

From the cloned repository root, install Python dependencies and Trivy 0.74.0 on PATH. Registry-reference scans do not require the Docker socket. Docker Desktop/Engine is needed for the optional monitoring stack.

```
python -m venv .venv
.\.venv\Scripts\Activate.ps1
python -m pip install -r requirements-dev.txt
trivy --version
python -m pytest tests -q

python -m scanner.trivy_scanner hello-world:latest
# An Alpine HIGH-threshold scan may intentionally return exit 1.
python -m scanner.trivy_scanner alpine:3.19 --fail-on HIGH
$artifacts = @(Get-ChildItem scan-results -Filter '*-????????.json' | ForEach-Object FullName)
python -m reporters.cli @artifacts --formats json,html,pdf --output-dir reports
python -m dashboard.cli @artifacts --metrics-file reports/scan-metrics.prom
python -m dashboard.app --port 5050
```

Open the local dashboard at http://127.0.0.1:5050. To run the provisioned exporter/Prometheus/Grafana stack, set `GRAFANA_ADMIN_PASSWORD` privately in the terminal and run `docker compose -f dashboard/compose.yaml up -d --build`. Credentials must not be committed to the repository. Avoid `down -v` unless deletion of monitoring history is intended.

CI evidence can be downloaded and imported using the same CLI. Rescan an original normalized artifact with `python -m scanner.trivy_scanner --rescan-artifact previous.json --refresh-db --output-dir scan-results/rescan`. Preserve the previous file and import both observations for historical comparisons. Full operational detail is in the README.

15. Challenges and Architectural Decisions

Challenge	Decision / outcome
Policy failure confused with tool failure	Separate exits distinguish accepted execution with findings from configuration/operational errors.
Evidence lost when a gate stops CI	Preserve the scan result through reporting and attempt archive/upload before final outcome restoration.
Ephemeral CI cannot be a persistent metrics endpoint	Use a separate local persisted history exporter rather than pretending a stopped CLI remains scrapeable.
Count-only remediation metrics hide finding churn	Compare exact advisory/package sets, including suppressed findings.
Risk approval could silently hide findings	Mandatory reason/expiry, exact scope and separate suppression audit; no default approvals.
Different CI agent environments	Use shared Python logic, pinned Trivy and bootstrap pipelines; keep provider-specific orchestration separate.
Original diagram mixed roadmap and implementation	Replace it with deployment boundaries, persisted stores and labelled interfaces; retain old image as historical overview.
Preserving useful verification evidence	Retain original scanner outputs, JUnit results, CI records and browser captures alongside the report.

16. Evidence Register and Provenance

Core command-output logClean artifact / Vulnerable artifactMain run metadata / jobs / artifactsGitHub passing capture / blocked captureJenkins passing capture / blocked consoleSprint 3 delivery recordsGenerated report manifestBrowser checksDesktop / mobilePrometheus / GrafanaApproved / expired / audit captureBaseline / rescanMilestone JUnit / final-verification JUnit / test outputDeployment architectureAdditional capture records

ID	Evidence	Type and interpretation
E01	Fresh actual command output; not a rendered terminal panel	
E02	Original normalized scanner outputs from final verification	
E03	Original public GitHub API responses for run #31; live URL remains authoritative for later changes/retention	
E04	Genuine historical browser screenshots	

ID	Evidence	Type and interpretation
E05	Genuine historical browser screenshots	
E06	Verified Jenkins transport logs and execution details; channel screenshots not available	
E07	Original JSON/HTML/PDF bundle with per-file checksum and size	
E08	Captured checks, timestamps and observed totals	
E09	Genuine local application captures	
E10	Genuine running monitoring captures	
E11	Original date-specific accepted/expired risk demonstrations	
E12	Original observations with fresh UUID/time and linked lineage	
E13	Machine-readable deterministic test evidence; distinct execution times	
E14	Technical documentation, not an execution screenshot	
E15	Sources and preparation records for the log view, rendered report, main-run capture and whitespace-trimmed Jenkins screenshot	

Relative links resolve inside the repository after cloning. HTML files are rendered locally; GitHub normally displays their source. Jenkins URLs may require academic credentials. Report PDFs embed the figures, while original machine-readable evidence remains in the adjacent repository paths. Older terminal-style presentation panels in the milestone appendices are not used as execution proof; this report uses original logs and browser captures.

17. Milestone Appendices

1. Sprint 1: Setup and Basic Scanning - historical design and setup narrative; reconstructed panels are not independent proof.
2. Sprint 2: CI/CD Integration - milestone 16-test and pass/block evidence.
3. Sprint 3: Reporting and Notifications - original report/transport/default-cadence evidence and its later updates.
4. Sprint 4: Dashboard and Monitoring - isolated 35-test milestone and genuine browser captures.
5. Sprint 5: Exceptions and Reliability - integrated 77-test evidence, original audit artifacts and limits.

6. Viva Preparation - 93 searchable questions aligned to the implementation.

Appendices preserve their original dates, version descriptions and evidence context. This consolidated report supersedes obsolete planned-versus-delivered statements for the final Sprint 1-5 state without rewriting historical screenshots.

18. Conclusion

Through this project, I integrated container image scanning with repeatable CI security gates, consistent reports, Jenkins notifications, persistent scan history, monitoring and governed vulnerability exceptions. The five sprints developed a basic scan workflow into a tested system with explicit failure handling and reviewable evidence.

The results demonstrate the implemented Sprint 1-5 scope. Remaining notification setup and verification limits are listed in Section 13. Further work includes production hosting, stronger supply-chain controls and automated collection of CI artifacts.

Tabrez Ajaz | Container Image Vulnerability Scanner with Reporting | Final consolidated report, 30 October 2026 | Source baseline 399d1af