



TB AUDIO PLUG-INS
Team Impulse Impact

USER MANUAL

TB Inverted Phaser

Inverted Phaser

Subtracts an all-pass-shifted copy from the dry signal for deep, hard-edged cancellation notches that move, park, or break apart.

Up to 12 stages

5 LFO shapes + jitter

Phase-response display

13 factory presets



INVERTED PHASER

CUSTOM

SAVE

LOAD

←

→



MOVEMENT

CENTER



720.0 Hz

RATE



0.350 Hz

TYPE

Sine

JITTER



0.0 %

COLOUR

STAGE COUNT



6

RANGE



70.0 %

SPACING



35.0 %

FEEDBACK



28.0 %

MIX

AMOUNT



65.0 %

MIX



100.0 %

OUTPUT



0.0 dB

Contents

- 01 Overview
- 02 Quick start
- 03 Interface
- 04 Controls
- 05 Presets
- 06 Recipes
- 07 Tips and troubleshooting
- 08 Parameter reference
- 09 Version history
- 10 Support and license

01 Overview

A classic phaser adds a phase-shifted copy to the dry signal. TB Inverted Phaser subtracts that copy instead, producing deep cancellation notches with hard, defined edges.

You choose how many notches are cut, where they sit, how far apart they are, and how they move. Amount and Mix are independent, so the sound can range from structured motion to an exposed, strongly coloured residue. It works especially well on pads, sustained chords, and harmonic material.

Key features

- Cascade of up to 12 all-pass stages, subtracted from the dry signal
- CENTER, STAGE COUNT, and SPACING define the notch pattern
- Five LFO shapes plus JITTER for random drift
- RANGE 0% parks the notches as a fixed comb
- Independent AMOUNT and MIX, plus OUTPUT trim
- Display of the input spectrum and the phase response together
- Thirteen factory presets in three banks, with undo and redo

Signal flow



About this manual

This manual describes TB Inverted Phaser 3.0.0 for Windows (VST3). The current macOS build is version 1.0.2 and may differ from the descriptions here.

02 Quick start

- 1 Insert TB Inverted Phaser on a pad, chord, or other sustained sound. The defaults are **CENTER** 720 Hz, **RATE** 0.35 Hz, **RANGE** 70%, **STAGE COUNT** 6, **SPACING** 35%, **FEEDBACK** 28%, **AMOUNT** 65%, **MIX** 100%.
- 2 Move **CENTER** **3** to the part of the sound you want to hollow out.
- 3 Set the speed with **RATE** and the travel with **RANGE** **7**.

- 4 Choose how many notches with **STAGE COUNT** 6 and how far apart they are with **SPACING** 8.
- 5 Raise **FEEDBACK** 9 for sharper, more resonant notch edges.
- 6 Balance **AMOUNT** 10 and **MIX** 11, then match the level with **OUTPUT** 12.

03 Interface



Captured from an earlier visual design. Version 3.0 uses a warm hardware-style skin with the same controls in the same places; its preset bar has previous/next arrows, the preset list, Save, Undo, and Redo.

- 1 **Preset bar** — factory presets grouped by bank, your saved presets, Save, and preset navigation.
- 2 **INPUT / PHASE RESPONSE** — the input spectrum and the notch pattern on a log 20 Hz–20 kHz scale. Small ticks under the curve show the notch positions.
- 3 **CENTER and RATE** — where the pattern is built and how fast it moves.
- 4 **TYPE** — the shape of the movement.
- 5 **JITTER** — random drift on top of the movement.

- 6 STAGE COUNT** — how many notches are cut.
- 7 RANGE** — how far the notches travel from CENTER.
- 8 SPACING** — the distance between notches.
- 9 FEEDBACK** — resonance and notch sharpness.

- 10 AMOUNT** — depth of the cancellation.
- 11 MIX** — level of the dry signal the copy is subtracted from.
- 12 OUTPUT** — final level trim.

04 Controls

Movement

Control	Range · default	What it does
CENTER	120 Hz to 4 kHz · 720 Hz	The frequency the notch pattern is built around. Move it to choose which part of the sound is hollowed out.
RATE	0.02 to 8 Hz · 0.35 Hz	How fast the notches travel. Low values drift; high values warble.
TYPE	Sine, Triangle, Ramp Up, Ramp Down, Square · Sine	The shape of the movement. Sine and Triangle glide, Ramp restarts, and Square jumps between two positions.
JITTER	0 to 100% · 0%	Random drift added on top of the movement. Small amounts loosen the motion; large amounts break it up.

Colour

Control	Range · default	What it does
STAGE COUNT	1 to 12 · 6	How many notches are cut. More stages give a denser, more metallic cancellation.
RANGE	0 to 100% · 70%	How far the notches travel from CENTER. At 0% they stay parked and act as a fixed comb.
SPACING	0 to 100% · 35%	The distance between notches in octaves. Narrow is tight and resonant; wide spreads across the spectrum.
FEEDBACK	0 to 85% · 28%	Returns the shifted copy into the cascade. Raises resonance and sharpens the notch edges.

Mix

Control	Range · default	What it does
AMOUNT	0 to 100% · 65%	How much of the phase-shifted copy is subtracted from the dry signal. This is the depth of the cancellation.
MIX	0 to 100% · 100%	Level of the untouched dry signal that AMOUNT is subtracted from. Lower it to leave mostly the cancelled residue.
OUTPUT	-12 to +6 dB · 0 dB	Final level trim, for matching loudness against bypass.

Because the effect works by cancellation, it can remove parts of the sound and change the level. Large FEEDBACK and RANGE settings are worth checking in mono.

05 Presets

Factory presets are grouped in three banks: Moving Notch, Fixed Comb, and Broken. Selecting a preset replaces every value in a single undo step. Save writes every current value to a .tbipreset file in your Documents folder. Undo steps back through parameter and preset changes; Redo steps forward again.

Factory presets: **Init**, **Pad Drift**, **Slow Orbit**, **Wide Vortex**, **Fast Warble**, **Ramp Sweeper**, **Thin Air**, **Hollow Glass**, **Static Teeth**, **Metal Rail**, **Square Jolt**, **Broken Motion**, and **Ghost Cancel**.

06 Recipes

Starting points for common jobs. Adjust them by ear.

Slow pad motion

Gentle, evolving movement on sustained chords.

Preset	Pad Drift
TYPE	Sine or Triangle
RATE	0.05 to 0.3 Hz
STAGE COUNT	4 to 8

- 1 Place CENTER in the busiest part of the pad.
- 2 Lower MIX slightly if the result is too hollow.

Fixed metallic comb

A static, resonant colour instead of movement.

Preset	Static Teeth or Metal Rail
RANGE	0%
FEEDBACK	50 to 80%
SPACING	Narrow

- 1 Sweep CENTER by hand to tune the comb to the sound.

Stepped rhythmic jumps

Movement that switches between two positions.

Preset	Square Jolt
TYPE	Square
RATE	Set by ear against the groove

- 1 RATE is in hertz; adjust it to match the music.

Exposed residue

An extreme, filtered texture made from what is cancelled.

Preset	Ghost Cancel
MIX	0 to 30%
AMOUNT	High

- 1 Raise OUTPUT to make up the level.

07 Tips and troubleshooting

Symptom	What to check
The sound became thin or quiet.	That is the cancellation. Lower AMOUNT, or raise OUTPUT to match the bypassed level.
The notches do not move.	RANGE is at 0%, which parks them as a fixed comb. Raise RANGE.

Symptom	What to check
The movement sounds too regular.	Add a little JITTER.
The effect is too harsh or resonant.	Lower FEEDBACK or widen SPACING.
The effect is too subtle.	Raise AMOUNT, add stages, or move CENTER to a busier part of the sound.

08 Parameter reference

Panel label	Host parameter	Range	Default
CENTER	Centre	120 Hz to 4 kHz	720 Hz
RATE	Rate	0.02 to 8 Hz	0.35 Hz
TYPE	LFO Shape	Sine, Triangle, Ramp Up, Ramp Down, Square	Sine
JITTER	Jitter	0 to 100%	0%
STAGE COUNT	Stages	1 to 12	6
RANGE	Depth	0 to 100%	70%
SPACING	Spacing	0 to 100%	35%
FEEDBACK	Feedback	0 to 85%	28%
AMOUNT	Amount	0 to 100%	65%
MIX	Mix	0 to 100%	100%
OUTPUT	Output	-12 to +6 dB	0 dB

09 Version history

Version	Changes
3.0.0 · 2026-08-04	The interface was rebuilt as a warm hardware-style rack with the phase-response display in the main panel, and the movement, colour, and mix controls were reorganized into a compact console layout.

10 Support and license

Report problems or request features at github.com/TaebeumKim/TB_Audio-Plugins/issues. Include the plug-in version, your DAW, and your operating system.

TB Audio plug-ins are free for personal and commercial work under the TB Audio Plug-ins Freeware License. If you release or monetize work made with them, add a credit such as **Made with TB Audio Plug-ins by Team Impulse Impact**. Selling or bundling the plug-ins is not allowed.

If the plug-ins help your music, you can support development at ko-fi.com/teamimpulseimpact.