

TB Limiter

USER MANUAL



Purpose

Stops sharp peaks while making the overall signal louder, firmer, and more controlled.

License: MIT License

This software is licensed under the MIT License. Copyright (c) 2026 TaebeumKim. See the repository LICENSE file for the full terms.

Controllable properties

Each control is listed by its panel name. Use the description to decide what to listen for, then make small changes in the context of the music.

Control and settings	What it changes
Attack Range: 0.1 to 2 Default: 2	Sets how quickly the effect reacts when a sound begins. Faster values control the front; slower values keep more punch.
Bypass Range: Off, On Default: Off	Turns the complete effect off or on for a direct before-and-after comparison.
Ceiling Range: -3 to 0 Default: -1	Sets the highest output peak the limiter is allowed to reach.
Dither Range: Off, 16-bit, 24-bit Default: Off	Adds the appropriate very-low-level noise when creating a 16-bit or 24-bit final file.
Enhance Range: 0 to 100 Default: 0	Adds controlled peak detail so the limited result feels more present and energetic.
Input Gain Range: 0 to 18 Default: 4	Sets how loud the sound enters the plug-in. Raise it for a stronger response or lower it for more headroom.
Program Range: 9 factory programs Default: Init	Loads a factory starting point. Adjust the controls afterward to fit the current sound.

Control and settings	What it changes
Release Range: 20 to 500 Default: 120	Sets how quickly the effect relaxes after the sound becomes quieter.
RMS Assist Range: 0 to 100 Default: 65	Adds smoother average-level control alongside the fast peak limiting.
RMS Balance Range: 0 to 100 Default: 0	Corrects longer level differences between the left and right channels without chasing every peak.