

TB Compressor

USER MANUAL



Purpose

Balances uneven volume and shapes the punch, smoothness, and density of a sound.

License: MIT License

This software is licensed under the MIT License. Copyright (c) 2026 TaebeumKim. See the repository LICENSE file for the full terms.

Controllable properties

Each control is listed by its panel name. Use the description to decide what to listen for, then make small changes in the context of the music.

Control and settings	What it changes
Attack Range: 0.1 to 200 Default: 10	Sets how quickly the effect reacts when a sound begins. Faster values control the front; slower values keep more punch.
Bypass Range: Off, On Default: Off	Turns the complete effect off or on for a direct before-and-after comparison.
Input Range: -24 to 24 Default: 0	Sets how loud the sound enters the plug-in. Raise it for a stronger response or lower it for more headroom.
Knee Range: 0 to 6 Default: 6	Softens the point where compression begins. Higher values sound gentler and less obvious.
Lookahead Range: 0 to 20 Default: 0	Helps catch sudden peaks more smoothly. Higher values can feel slightly less immediate.
Makeup Range: 0 to 24 Default: 0	Restores level after compression has made the sound quieter.
Output Range: -24 to 24 Default: 0	Sets the final listening level after processing.

Control and settings	What it changes
Oversampling Range: 1x (Off), 2x, 4x, 8x Default: 1x (Off)	Makes heavy distortion or limiting sound cleaner at the cost of more CPU use.
Program Range: 5 factory programs Default: Clean Control	Loads a factory starting point. Adjust the controls afterward to fit the current sound.
Ratio Range: 1 to 20 Default: 2	Sets how strongly level is controlled after it crosses the threshold.
Release Range: 5 to 1000 Default: 100	Sets how quickly the effect relaxes after the sound becomes quieter.
RMS Range: Off, On Default: Off	Changes the listening behavior from fast peak control to smoother average-level control.
Saturation Range: Clean, Soft, Hard, Punch, Warm, Tape Default: Clean	Chooses the harmonic character added after compression.
Saturation Drive Range: 0 to 4 Default: 1	Sets how strongly the saturation section is pushed.
Saturation Enabled Range: Off, On Default: Off	Turns the harmonic color section on or off.
Saturation Mix Range: 0 to 1 Default: 1	Blends the added harmonic color with the cleaner compressed sound.
Saturator Circuit Model Range: Legacy, XXL, LX-2X, FET-X76, FX-67X Default: Legacy	Chooses the overall response and color of the saturation section.
Sidechain High Cut Range: 100 to 20000 Default: 20000	Removes high frequencies from the current sound or effect layer.

Control and settings	What it changes
Sidechain Low Cut Range: 20 to 10000 Default: 20	Removes low frequencies from the current sound or effect layer.
Stereo Link Range: Off, On Default: On	Makes both channels react together so the stereo image does not lean to one side.
Threshold Range: -60 to 0 Default: -18	Sets how loud the sound must be before the current control begins working.