

TB Disperser

USER MANUAL



Purpose

Stretches the front of drums and synth hits so they feel heavier, sharper, or more elastic.

License: MIT License

This software is licensed under the MIT License. Copyright (c) 2026 TaebeumKim. See the repository LICENSE file for the full terms.

Controllable properties

Each control is listed by its panel name. Use the description to decide what to listen for, then make small changes in the context of the music.

Control and settings	What it changes
Amount Range: 0 % to 100 % Default: 70 %	Sets how strongly the named effect changes the sound.
Bypass Range: Off, On Default: Off	Turns the complete effect off or on for a direct before-and-after comparison.
Frequency Range: 20 Hz to 20 kHz Default: 200 Hz	Chooses the main tonal area or carrier pitch used by this control.
LFO Range Range: ± 0 oct to ± 4 oct Default: ± 1 oct	Sets how far the moving center frequency travels.
LFO Rate Range: 0.01 Hz to 10 Hz Default: 0.25 Hz	Sets how quickly the center frequency moves.
LFO Type Range: OFF, SINE, TRI, SAW, SQR, RND Default: OFF	Chooses the movement shape or turns automatic movement off.

Control and settings	What it changes
Pinch Range: 0 % to 100 % Default: 0 %	Focuses the phase sweep around a narrower frequency area. Higher values sound sharper and more resonant.
Program Range: 10 factory programs Default: Init	Loads a factory starting point. Adjust the controls afterward to fit the current sound.
Speed Range: 0.25 x to 2 x Default: 2 x	Shortens or stretches the phase movement around each hit.