

TB Distortion

USER MANUAL



Purpose

Creates anything from gentle warmth to aggressive breakup and blends it with the original sound.

License: MIT License

This software is licensed under the MIT License. Copyright (c) 2026 TaebeumKim. See the repository LICENSE file for the full terms.

Controllable properties

Each control is listed by its panel name. Use the description to decide what to listen for, then make small changes in the context of the music.

Control and settings	What it changes
Bypass Range: Off, On Default: Off	Turns the complete effect off or on for a direct before-and-after comparison.
Drive Range: 0 to 36 Default: 6	Sets how strongly the sound is pushed into harmonic color or distortion.
Drive Type Range: Soft, Hard, Fuzz, Tube, Tape, Fold Default: Soft	Chooses the main distortion character, from soft and warm to hard or folded.
Dynamics Range: -100 to 100 Default: 0	Changes how distortion follows playing level. Negative and positive values create different kinds of movement.
High Range: 20 to 20000 Default: 20000	Sets the highest frequency included in the focused distortion area.
Low Range: 20 to 20000 Default: 20	Sets the lowest frequency included in the focused distortion area.

Control and settings	What it changes
Mix Range: 0 to 100 Default: 100	Blends the original sound with the processed sound.
Output Range: -24 to 12 Default: 0	Sets the final listening level after processing.
Program Range: 9 factory programs Default: Init	Loads a factory starting point. Adjust the controls afterward to fit the current sound.
TB Drive Range: 0 to 100 Default: 0	Adds a second, parallel layer of distortion character.
TB Type Range: Level, Sample, Time, Bias Default: Level	Chooses how the parallel TB layer changes the sound.