

TB Noise Remover

USER MANUAL



Purpose

Reduces specific recording problems such as hiss, hum, clicks, rumble, and clipped peaks.

License: MIT License

This software is licensed under the MIT License. Copyright (c) 2026 TaebeumKim. See the repository LICENSE file for the full terms.

Controllable properties

Each control is listed by its panel name. Use the description to decide what to listen for, then make small changes in the context of the music.

Control and settings	What it changes
50 Hz Hum Range: Off, On Default: Off	Reduces electrical hum based around 50 Hz.
60 Hz Hum Range: Off, On Default: Off	Reduces electrical hum based around 60 Hz.
Basic Range: Off, On Default: On	Turns on the main broadband cleanup stage for general background noise.
Bypass Range: Off, On Default: Off	Turns the complete effect off or on for a direct before-and-after comparison.
Clicks Range: Off, On Default: Off	Reduces short clicks, pops, and small impulse noises.
Clip Repair Range: Off, On Default: Off	Softens the harsh flat peaks created by an overloaded recording.
Digital Whine Range: Off, On Default: Off	Reduces narrow electronic tones and high-pitched digital whine.

Control and settings	What it changes
Hiss Range: Off, On Default: Off	Reduces steady high-frequency hiss from microphones, tape, or preamps.
Low Rumble Range: Off, On Default: Off	Reduces deep vibration, handling noise, and low-frequency rumble.
Reduction Range: 0 to 100 Default: 70	Sets the overall strength of the enabled cleanup modules.