

TB SubLow

USER MANUAL



Purpose

Adds focused sub-bass at a chosen frequency to strengthen low-end weight and impact.

License: MIT License

This software is licensed under the MIT License. Copyright (c) 2026 TaebeumKim. See the repository LICENSE file for the full terms.

Controllable properties

Each control is listed by its panel name. Use the description to decide what to listen for, then make small changes in the context of the music.

Control and settings	What it changes
Bloom Range: 0 % to 100 % Default: 15 %	Adds a slower, swelling layer around the generated low tone.
Bypass Range: Active, Bypassed Default: Active	Turns the complete effect off or on for a direct before-and-after comparison.
Core Range: 0 % to 100 % Default: 30 %	Sets the steady center and weight of the generated low tone.
Output Range: -12 dB to +6 dB Default: 0 dB	Sets the final listening level after processing.
Program Range: 12 factory programs Default: Init	Loads a factory starting point. Adjust the controls afterward to fit the current sound.
Punch Range: 0 % to 100 % Default: 20 %	Emphasizes the beginning of the generated low tone for stronger impact.
Response Range: 0 % to 100 % Default: 50 %	Sets how quickly the added sub-bass follows changes in the original sound.

Control and settings	What it changes
Target Range: 32 Hz to 250 Hz Default: 55 Hz	Chooses the main frequency of the added sub-bass.