

-

-

... ILL- III\> ..

The UNIX' Programming Environment

Brian W 0 Kernighan Rob Pike

Bell Laboratories Murray Hill, New Jersey

PRENTICE-HALL, INC. Englewood Cliffs, New Jersey 07632

* UNIX is a Trademark of Bell Laboratories

Library of Congress Catalog Card Number 8 3 -6 2 85 1

Prentice-Hall Software Series Brian W. Kernighan, Advisor

Editorial/production supervision: Ros Herion Cover design: Photo Plus Art,
Celine Brandes Manufacturing buyer: Gordon Osbourne

Copyright © 1984 by Bell Telephone Laboratories, Incorporated.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher. Printed in the United States of America. Published simultaneously in Canada.

This book was typeset in Times Roman and Courier by the authors, using a Mer- genthaler Linotron 202 phototypesetter driven by a VAX-11/750 running the 8th Edition of the UNIX operating system.

UNIX is a trademark of Bell Laboratories. DEC, PDP and VAX are trademarks of Digital Equipment Corporation.

20 19 18 17 16 15 14

ISBN ISBN

0-13-937699-2 0-13-937681-X {PBK}

PRENTICE-HALL INTERNATIONAL, INC., London PRENTICE-HALL
 OF AUSTRALIA PTY LIMITED, Sydney EDITORA PRENTICE-HALL
 DO BRASIL, LTDA., Rio de Janeiro PRENTICE-HALL CANADA INC.,
 Toronto PRENTICE-HALL OF INDIA PRIVATE LIMITED, New Delhi
 PRENTICE-HALL OF JAPAN, INC., Tokyo PRENTICE-HALL OF
 SOUTHEAST ASIA PTE. LTD., Singapore WHITEHALL BOOKS
 LIMITED, Wellington, New Zealand

CONTENTS

Preface	ee	VII
1. UNIX for Beginners	1	
1.1 Getting started	2	
1.2 Day-to-day use: files and common commands	11	
1.3 More about files: directories	21	
1.4 The shell	26	
1.5 The rest of the UNIX system	38	
2. The File System	41	
2.1 The basics of files	41	
2.2 What's in a file?	46	
2.3 Directories and filenames	48	
2.4 Permissions	52	
2.5 Inodes	57	
2.6 The directory hierarchy	63	
2.7 Devices	65	
3. Using the Shell	71	
3.1 Command line structure	71	
3.2 Metacharacters	74	
3.3 Creating new commands	80	
3.4 Command arguments and parameters	82	
3.5 Program output as arguments	86	
3.6 Shell variables	88	
3.7 More on I/O redirection	92	
3.8 Looping in shell programs	94	
3.9 bund 1 e: putting it all together	97	
3.10 Why a programmable shell?	99	
4. Filters	101	
4.1 The grep family	102	
4.2 Other filters	106	iii

iv CONTENTS

59

60

7.

8.

4.3 The stream editor sed 4.4 The awk pattern scanning and processing language 4.5 Good files and good filters

108 114 130

Shell Programming 5.1 Customizing the cal command 5.2 Which command is which? 5.3 while and until loops: watching for things 5.4 Traps: catching interrupts 5.5 Replacing a file: overwrite 5.6 zap: killing processes by name 5.7 The pick command: blanks vs. arguments 5.8 The news command: community service messages 5.9 get and put: tracking file changes 5.10 A look back

133 133 138 144 150 152 156 159 162 165 169

Programming with Standard I/O 6.1 Standard input and output: vis 6.2 Program arguments: vis version 2 6.3 File access: vis version 3 6.4 A screen-at-a-time printer: p 6.5 An example: pick 6.6 On bugs and debugging 6.7 An example: zap 6.8 An interactive file comparison program: idiff 6.9 Accessing the environment

171 172 174 176 180 186 187 190 192 199

UNIX System Calls 7.1 Low-level I/O 7.2 File system: directories 7.3 File system: inodes 7.4 Processes 7.5 Signals and interrupts

201 201 208 214 220 225

Program Development 8.1 Stage 1: A four-function calculator 8.2 Stage 2: Variables and error recovery 8.3 Stage 3: Arbitrary variable names; built-in functions 8.4 Stage 4: Compilation into a machine 8.5 Stage 5: Control flow and relational operators 8.6 Stage 6: Functions and procedures; input/output 8.7 Performance evaluation 8.8 A look back

233 234 242 245 258 266 273 284 286

UNI

NI

V

9. Document Preparation 289 9.1 The ms macro package 290 9.2 The troff level 297 9.3 The tbl and eqn preprocessors 301 9.4 The manual page 308 9.5 Other document preparation tools 313 10. Epilog 315 Appendix 1: Editor Summary 319 Appendix 2: hoc Manual 329 Appendix 3: hoc Listing 335 Index 349

iv CONTENTS

59

60

70

80

4.3 The stream editor sed 4.4 The awk pattern scanning and processing language 4.5 Good files and good filters

108 114 130

Shell Programming 5.1 Customizing the cal command 5.2 Which command is which? 5.3 while and until loops: watching for things 5.4 Traps: catching interrupts 5.5 Replacing a file: overwri te 5.6 zap: killing processes by name 5.7 The pick command: blanks vs. arguments 5.8 The news command: community service messages 5.9 get and put: tracking file changes 5.10 A look back

133 133 138 144 150 152 156 159 162 165 169

Programming with Standard I/O 6.1 Standard input and output: vis 6.2
Program arguments: vis version 2 6.3 File access: vis version 3 6.4 A
screen-at-a-time printer: p 6.5 An example: pick 6.6 On bugs and
debugging 6.7 An example: zap 6.8 An interactive file comparison
program: idiff 6.9 Accessing the environment

171 172 174 176 180 186 187 190 192 199

UNIX System Calls 7.1 Low-level I/O 7.2 File system: directories 7.3 File
system: inodes 7.4 Processes 7.5 Signals and interrupts

201 201 208 214 220 225

Program Development 8.1 Stage 1: A four-function calculator 8.2 Stage 2:
Variables and error recovery 8.3 Stage 3: Arbitrary variable names; built-in
functions 8.4 Stage 4: Compilation into a machine 8.5 Stage 5: Control flow
and relational operators 8.6 Stage 6: Functions and procedures; input/output
8.7 Performance evaluation 8.8 A look back

233 234 242 245 258 266 273 284 286

CONTENTS V

9. Document Preparation	289
9.1 The ros macro package	290
9.2 The troff level	297
9.3 The tbl and eqn preprocessors	301
9.4 The manual page	308
9.5 Other document preparation tools	313
10. Epilog	315
Appendix 1: Editor Summary	319
Appendix 2: hoc Manual	329
Appendix 3: hoc Listing	335
Index	349

PREFACE

"The number of UNIX installations has grown to 10, with more expected."
(The UNIX Programmer's Manual, 2nd Edition, June, 1972.)

The UNIX operating system started on a cast-off DEC PDP-7 at Bell Laboratories in 1969. Ken Thompson, with ideas and support from Rudd Canaday, Doug McIlroy, Joe Ossanna, and Dennis Ritchie, wrote a small general-purpose time-sharing system comfortable enough to attract enthusiastic users and eventually enough credibility for the purchase of a larger machine - a PDP-11/20. One of the early users was Ritchie, who helped move the system to the PDP-11 in 1970. Ritchie also designed and wrote a compiler for the C programming language. In 1973, Ritchie and Thompson rewrote the UNIX kernel in C, breaking from the tradition that system software is written in assembly language. With that rewrite, the system became essentially what it is today. Around 1974 it was licensed to universities "for educational purposes" and a few years later became available for commercial use. During this time, UNIX systems prospered at Bell Labs, finding their way into laboratories, software development projects, word processing centers, and operations support systems in telephone companies. Since then, it has spread world-wide, with tens of thousands of systems installed, from microcomputers to the largest mainframes. What makes the UNIX system so successful? We can discern several reasons. First, because it is written in C, it is portable - UNIX systems run on a range of computers from microprocessors to the largest mainframes; this is a strong commercial advantage. Second, the source code

is available and written in a high-level language, which makes the system easy to adapt to particular requirements. Finally, and most important, it is a good operating system,

t UNIX is a trademark of Bell Laboratories. "UNIX" is not an acronym, but a weak pun on MULTICS, the operating system that Thompson and Ritchie worked on before UNIX.

vii

viii PREFACE

especially for programmers. The UNIX programming environment is unusually rich and productive. Even though the UNIX system introduces a number of innovative programs and techniques, no single program or idea makes it work well. Instead, what makes it effective is an approach to programming, a philosophy of using the computer. Although that philosophy can't be written down in a single sentence, at its heart is the idea that the power of a system comes more from the relationships among programs than from the programs themselves. Many UNIX programs do quite trivial tasks in isolation, but, combined with other programs, become general and useful tools. Our goal in this book is to communicate the UNIX programming philosophy. Because the philosophy is based on the relationships between programs, we must devote most of the space to discussions about the individual tools, but throughout run the themes of combining programs and of using programs to build programs. To use the UNIX system and its components well, you must understand not only how to use the programs, but also how they fit into the environment. As the UNIX system has spread, the fraction of its users who are skilled in its application has decreased. Time and again, we have seen experienced users,

ourselves included, find only clumsy solutions to a problem, or write programs to do jobs that existing tools handle easily. Of course, the elegant solutions are not easy to see without some experience and understanding. We hope that by reading this book you will develop the understanding to make your use of the system - whether you are a new or seasoned user - effective and enjoyable. We want you to use the UNIX system well. We are aiming at individual programmers, in the hope that, by making their work more productive, we can in turn make the work of groups more productive. Although our main target is programmers, the first four or five chapters do not require programming experience to be understood, so they should be helpful to other users as well. Wherever possible we have tried to make our points with real examples rather than artificial ones. Although some programs began as examples for the book, they have since become part of our own set of everyday programs. All examples have been tested directly from the text, which is in machine-readable form. The book is organized as follows. Chapter 1 is an introduction to the most basic use of the system. It covers logging in, mail, the file system, commonly- used commands, and the rudiments of the command interpreter. Experienced users can skip this chapter. Chapter 2 is a discussion of the UNIX file system. The file system is central to the operation and use of the system, so you must understand it to use the system well. This chapter describes files and directories, permissions and file modes, and inodes. It concludes with a tour of the file system hierarchy and an explanation of device files.

PREFACE ix

The command interpreter, or shell, is a fundamental tool, not only for running programs, but also for writing them. Chapter 3 describes how to use the shell for your own purposes: creating new commands, command arguments, shell variables, elementary control flow, and input-output redirection. Chapter 4 is about filters: programs that perform some simple transformation on data as it flows through them. The first section deals with the `grep` pattern-searching command and its relatives; the next discusses a few of the more common filters such as `sort`; and the rest of the

chapter is devoted to two general-purpose data transforming programs called `sed` and `awk`. `sed` is a stream editor, a program for making editing changes on a stream of data as it flows by. `awk` is a programming language for simple information retrieval and report generation tasks. It's often possible to avoid conventional programming entirely by using these programs, sometimes in cooperation with the shell. Chapter 5 discusses how to use the shell for writing programs that win stand up to use by other people. Topics include more advanced control flow and variables, traps and interrupt handling. The examples in this chapter make considerable use of `sed` and `awk` as well as the shell. Eventually one reaches the limits of what can be done with the shell and other programs that already exist. Chapter 6 talks about writing new programs using the standard I/O library. The programs are written in C, which the reader is assumed to know, or at least be learning concurrently. We try to show sensible strategies for designing and organizing new programs, how to build them in manageable stages, and how to make use of tools that already exist. Chapter 7 deals with the system calls, the foundation under all the other layers of software. The topics include input-output, file creation, error processing, directories, inodes, processes, and signals. Chapter 8 talks about program development tools: `yacc`, a parser-generator; `make`, which controls the process of compiling a big program; and `lex`, which generates lexical analyzers. The exposition is based on the development of a large program, a C-like programmable calculator. Chapter 9 discusses the document preparation tools, illustrating them with a user-level description and a manual page for the calculator of Chapter 8. It can be read independently of the other chapters. Appendix 1 summarizes the standard editor `ed`. Although many readers will prefer some other editor for daily use, `ed` is universally available, efficient and effective. Its regular expressions are the heart of other programs like `grep` and `sed`, and for that reason alone it is worth learning. Appendix 2 contains the reference manual for the calculator language of Chapter 8. Appendix 3 is a listing of the final version of the calculator program, presenting the code all in one place for convenient reading.

X PREFACE

Some practical matters. First, the UNIX system has become very popular, and there are a number of versions in wide use. For example, the 7th Edition comes from the original source of the UNIX system, the Computing Science Research Center at Bell Labs. System III and System V are the official Bell Labs-supported versions. The University of California at Berkeley distributes systems derived from the 7th Edition, usually known as VCB 4.xBSD. In addition, there are numerous variants, particularly on small computers, that are derived from the 7th Edition. We have tried to cope with this diversity by sticking closely to those aspects that are likely to be the same everywhere. Although the lessons that we want to teach are independent of any particular version, for specific details we have chosen to present things as they were in the 7th Edition, since it forms the basis of most of the UNIX systems in widespread use. We have also run the examples on Bell Labs' System V and on Berkeley 4.1BSD; only trivial changes were required, and only in a few examples. Regardless of the version your machine runs, the differences you find should be minor. Second, although there is a lot of material in this book, it is not a reference manual. We feel it is more important to teach an approach and a style of use than just details. The UNIX Programmer's Manual is the standard source of information. You will need it to resolve points that we did not cover, or to determine how your system differs from ours. Third, we believe that the best way to learn something is by doing it. This book should be read at a terminal, so that you can experiment, verify or contradict what we say, explore the limits and the variations. Read a bit, try it out, then come back and read some more. We believe that the UNIX system, though certainly not perfect, is a marvelous computing environment. We hope that reading this book will help you to reach that conclusion too.

We are grateful to many people for constructive comments and criticisms, and for their help in improving our code. In particular, Jon Bentley, John Linderman, Doug McIlroy, and Peter Weinberger read multiple drafts with great care. We are indebted to Al Aho, Ed Bradford, Bob Flandrena, Dave Hanson, Ron Hardin, Marion Harris, Gerard Holzmann, Steve Johnson,

Nico Lomuto, Bub Martin, Larry Rosler, Chris Van Wyk, and Jim Weythman for their comments on the first draft. We also thank Mike Bianchi, Elizabeth Bimmler, Joe Carfagno, Don Carter, Tom De Marco, Tom Duff, David Gay, Steve Mahaney, Ron Pinter, Dennis Ritchie, Ed Sitar, Ken Thompson, Mike Tilson, Paul Tukey, and Larry Wehr for valuable suggestions.

Brian Kernighan Rob Pike

CHAPTER 1: UNIX FOR BEGINNERS

What is "UNIX"? In the narrowest sense, it is a time-sharing operating system kernel: a program that controls the resources of a computer and allocates them among its users. It lets users run their programs; it controls the peripheral devices (discs, terminals, printers, and the like) connected to the machine; and it provides a file system that manages the long-term storage of information such as programs, data, and documents. In a broader sense, "UNIX" is often taken to include not only the kernel, but also essential programs like compilers, editors, command languages, programs for copying and printing files, and so on. Still more broadly, "UNIX" may even include programs developed by you or other users to be run on your system, such as tools for document preparation, routines for statistical analysis, and graphics packages. Which of these uses of the name "UNIX" is correct depends on which level of the system you are considering. When we use "UNIX" in the rest of this book, context should indicate which meaning is implied. The UNIX system sometimes looks more difficult than it is - it's hard for a newcomer to know how to make the best use of the facilities available. But fortunately it's not hard to get started - knowledge of only a few programs should get you off the ground. This chapter is meant to help you to start using the system as quickly as possible. It's an overview, not a manual; we'll cover most of the material again in more detail in later chapters. We'll talk about these major areas: . basics - logging in and out,

simple commands, correcting typing mistakes, mail, inter-terminal communication. . day-to-day use - files and the file sy

tem, printing files, directories, commonly-used commands. . the command interpreter or shell - filename shorthands, redirecting input and output, pipes, setting erase and kill characters, and defining your own search path for commands. If you've used a UNIX system before, most of this chapter should be familiar; you might want to skip straight to Chapter 2.

1

2 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

You will need a copy of the UNIX Programmer's Manual, even as you read this chapter; it's often easier for us to tell you to read about something in the manual than to repeat its contents here. This book is not supposed to replace it, but to show you how to make best use of the commands described in it. Furthermore, there may be differences between what we say here and what is true on your system. The manual has a permuted index at the beginning that's indispensable for finding the right programs to apply to a problem; learn to use it. Finally, a word of advice: don't be afraid to experiment. If you are a beginner, there are very few accidental things you can do to hurt yourself or other users. So learn how things work by trying them. This is a long chapter, and the best way to read it is a few pages at a time, trying things out as you go.

1.1 Getting started

Some prerequisites about terminals and typing To avoid explaining everything about using computers, we must assume you have some familiarity with computer terminals and how to use them. If any of the following statements are mystifying, you should ask a local expert for help. The UNIX system is full duplex: the characters you type on the keyboard are sent to the system, which sends them back to the terminal to be printed on the screen. Normally, this echo process copies the characters directly to the screen, so you can see what you are typing, but sometimes, such as when you are typing a secret password, the echo is turned off so the characters do not appear on the screen. Most of the keyboard characters are ordinary printing characters with no special significance, but a few tell the computer how to interpret your typing. By far the most important of these is the RETURN key. The RETURN key signifies the end of a line of input; the system echoes it by moving the terminal's cursor to the beginning of the next line on the screen. RETURN must be pressed before the system will interpret the characters you have typed. RETURN is an example of a control character - an invisible character that controls some aspect of input and output on the terminal. On any reasonable terminal, RETURN has a key of its own, but most control characters do not. Instead, they must be typed by holding down the CONTROL key, sometimes called CTL or CNTL or CTRL, then pressing another key, usually a letter. For example, RETURN may be typed by pressing the RETURN key or, equivalently, holding down the CONTROL key and typing an 'm'. RETURN might therefore be called a control-m, which we will write as `ctl-m`. Other control characters include `ctl-d`, which tells a program that there is no more input; `ctl-g`, which rings the bell on the terminal; `ctl-h`, often called backspace, which can be used to correct typing mistakes; and `ctl-i`, often called tab, which

CHAPTER 1

advances the cursor to the next tab stop, much as on a regular typewriter. Tab stops on UNIX systems are eight spaces apart. Both the backspace and tab characters have their own keys on most terminals. Two other keys have special meaning: DELETE, sometimes called RUBOUT or some abbreviation, and BREAK, sometimes called INTERRUPT. On most UNIX systems, the DELETE key stops a program immediately, without waiting for it to finish. On some systems, `ctl-c` provides this service. And on some systems, depending on how the terminals are connected, BREAK is a synonym for DELETE or `ctl-c`.

A Session with UNIX Let's begin with an annotated dialog between you and your UNIX system. Throughout the examples in this book, what you type is printed in slanted letters, computer responses are in typewriter-style characters, and explanations are in italics.

Establish a connection: dial a phone or turn on a switch as necessary. Your system should say login: you Password: You have mail. \$ \$ \$ date Sun Sep 25 23:02:57 EDT \$ who jlb you mary doug ebg bob \$ mail From doug give me a

`ttyO tty2 tty4 tty5 tty7 tty8`

Type your name, then press RETURN Your password won't be echoed as you type it There's mail to be read after you log in The system is now ready for your commands Press RETURN a couple of times What's the date and time? 1983 Who's using the machine? Sep 25 13:59 Sep 25 23:01 Sep 25 19:03 Sep 25 19:22 Sep 25 17:17 Sep 25 20:48 Read your mail Sun Sep 25 20:53 EDT 1983 call sometime monday

? RETURN moves on to the next message From mary Sun Sep 25 19:07 EDT 1983 Next message Lunch at noon tomorrow?

? d \$ \$ mail mary lunch at 12 is fine ctl-d \$

Delete this message No more mail Send mail to mary

End of mail Hang up phone or turn off terminal and that's the end

Sometimes that's all there IS to a session, though occasionally people do

4 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER I

some work too. The rest of this section will discuss the session above, plus other programs that make it possible to do useful things.

Logging in You must have a login name and password, which you can get from your system administrator. The UNIX system is capable of dealing with a wide variety of terminals, but it is strongly oriented towards devices

with lower case; case distinctions matter! If your terminal produces only upper case (like some video and portable terminals), life will be so difficult that you should look for another terminal. Be sure the switches are set appropriately on your device: upper and lower case, full duplex, and any other settings that local experts advise, such as the speed, or baud rate. Establish a connection using whatever magic is needed for your terminal; this may involve dialing a telephone or merely flipping a switch. In either case, the system should type

login:

If it types garbage, you may be at the wrong speed; check the speed setting and other switches. If that fails, press the BREAK or INTERRUPT key a few times, slowly. If nothing produces a login message, you will have to get help. When you get the login: message, type your login name in lower case. Follow it by pressing RETURN. If a password is required, you will be asked for it, and printing will be turned off while you type it. The culmination of your login efforts is a prompt, usually a single character, indicating that the system is ready to accept commands from you. The prompt is most likely to be a dollar sign \$ or a percent sign %, but you can change it to anything you like; we'll show you how a little later. The prompt is actually printed by a program called the command interpreter or shell, which is your main interface to the system. There may be a message of the day just before the prompt, or a notification that you have mail. You may also be asked what kind of terminal you are using; your answer helps the system to use any special properties the terminal might have.

Typing commands Once you receive the prompt, you can type commands, which are requests that the system do something. We will use program as a synonym for command. When you see the prompt (let's assume it's \$), type date and press RETURN. The system should reply with the date and time, then print another prompt, so the whole transaction will look like this

on your terminal: \$ date Mon Sep 26 12:20:57 EDT 1983 \$ Don't forget RETURN, and don't type the \$. If you think you're being

CHAPTER 1

UNIX FOR BEGINNERS 5

ignored, press RETURN; something should happen. RETURN won't be mentioned again, but you need it at the end of every line. The next command to try is who, which tells you everyone who is currently logged in:

```
$ who rlm ttyO Sep 26 11:17 pjw tty4 Sep 26 11:30 gerard tty7 Sep 26
10:27 mark tty9 Sep 26 07:59 you ttya Sep 26 12:20 $
```

The first column is the user name. The second is the system's name for the connection being used ("tty" stands for "teletype," an archaic synonym for "terminal"). The rest tells when the user logged on. You might also try

```
$ who am i you ttya $
```

Sep 26 12:20

If you make a mistake typing the name of a command, and refer to a non-existent command, you will be told that no command of that name can be found:

```
$ whom whom: not found $
```

Misspelled command name ... so system didn't know how to run it

Of course, if you inadvertently type the name of an actual command, it will run, perhaps with mysterious results.

Strange terminal behavior Sometimes your terminal will act strangely, for example, each letter may be typed twice, or RETURN may not put the cursor at the first column of the next line. You can usually fix this by turning the terminal off and on, or by logging out and logging back in. Or you can read the description of the command stty ("set ,terminal options") in Section 1 of the manual. To get intelligent treatment of tab characters if your terminal doesn't have tabs, type the com- mand

```
$ stty -tabs
```

and the system will convert tabs into the right number of spaces. If your terminal does have computer-settable tab stops, the command tabs will set them correctly for you. (You may actually have to say \$ tabs terminal-type to make it work - see the tabs command description in the manual.)

CHAPTER 1

Mistakes in typing If you make a typing mistake, and see it before you have pressed RETURN, there are two ways to recover: erase characters one at a time or kill the whole line and re-type it. If you type the line kill character, by default an at-sign @, it causes the whole line to be discarded, just as if you'd never typed it, and starts you over on a new line:

```
$ ddtae@ date Mon Sep 26 12:23:39 EDT 1983 $
```

Completely botched; start over on a new line

The sharp character # erases the last character typed; each # erases one more character, back to the beginning of the line (but not beyond). So if you type badly, you can correct as you go: \$ dd#atte##e Fix it as you go Mon Sep 26 12:24:02 EDT 1983 \$

The particular erase and line kill characters are very system dependent. On many systems (including the one we use), the erase character has been changed to backspace, which works nicely on video terminals. You can quickly check which is the case on your system:

```
$ datee4- datee
```

```
: not found $ datee# Mon Sep 26 12:26:08 EDT 1983 $
```

Try

It's not

Try # It is #

(We printed the backspace as +- so you can see it.) Another common choice is `ctl-u` for line kill. We will use the sharp as the erase character for the rest of this section because it's visible, but make the mental adjustment if your system is different. Later on, in "tailoring the environment," we will tell you how to set the erase and line kill characters to whatever you like, once and for all. What if you must enter an erase or line kill character as part of the text? If you precede either `#` or `@` by a backslash `\`, it loses its special meaning. So to enter a `#` or `@`, type `\#` or `\@`. The system may advance the terminal's cursor to the next line after your `@`, even if it was preceded by a backslash. Don't worry - the at-sign has been recorded. The backslash, sometimes called the escape character, is used extensively to indicate that the following character is in some way special. To erase a backslash, you have to type two erase characters: `\##`. Do you see why? The characters you type are examined and interpreted by a sequence of programs before they reach their destination, and exactly how they are interpreted

CHAPTER 1

UNIX FOR BEGINNERS 7

depends not only on where they end up but how they got there. Every character you type is immediately echoed to the terminal, unless echoing is turned off, which is rare. Until you press RETURN, the characters are held

temporarily by the kernel, so typing mistakes can be corrected with the erase and line kill characters. When an erase or line kill character is preceded by a backslash, the kernel discards the backslash and holds the following character without interpretation. When you press RETURN, the characters being held are sent to the program that is reading from the terminal. That program may in turn interpret the characters in special ways; for example, the shell turns off any special interpretation of a character if it is preceded by a backslash. We'll come back to this in Chapter 3. For now, you should remember that the kernel processes erase and line kill, and backslash only if it precedes erase or line kill; whatever characters are left after that may be interpreted by other programs as well. Exercise 1-1. Explain what happens with `$ date\@`

o Exercise 1-2. Most shells (though not the 7th Edition shell) interpret `#` as introducing a comment, and ignore all text from the `#` to the end of the line. Given this, explain the following transcript, assuming your erase character is also `#`:
`$ date Mon Sep 26 12:39:56 EDT 1983 $ #date Mon Sep 26 12:40:21 EDT 1983 $ \#date $ \#date #date: not found $`

o

Type-ahead The kernel reads what you type as you type it, even if it's busy with something else, so you can type as fast as you want, whenever you want, even when some command is printing at you. If you type `\` while the system is printing, your input characters will appear intermixed with the output characters, but they will be stored away and interpreted in the correct order. You can type commands one after another without waiting for them to finish or even to begin.

Stopping a program You can stop most commands by typing the character DELETE. The BREAK key found on most terminals may also work, although this is system dependent. In a few programs, like text editors, DELETE stops whatever the program is doing but leaves you in that program. Turning off the terminal or

8 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

hanging up the phone will stop most programs. If you just want output to pause, for example to keep something critical from disappearing off the screen, type etl-s. The output will stop almost immediately; your program is suspended until you start it again. When you want to resume, type etl-q.

Logging out The proper way to log out is to type etl-d instead of a command; this tells the shell that there is no more input. (How this actually works will be explained in the next chapter.) You can usually just turn off the terminal or hang up the phone, but whether this really logs you out depends on your sys- tem.

Mail The system provides a postal system for communicating with other users, so some day when you log in, you will see the message

You have mail.

before the first prompt. To read your mail, type

```
$ mail
```

Your mail will be printed, one message at a time, most recent first. After each item, mail waits for you to say what to do with it. The two basic responses are `d`, which deletes the message, and `RETURN 'I` which does not (so it will still be there the next time you read your mail). Other responses include `p` to reprint a message, `s filename` to save it in the file you named, and `q` to quit from mail. (If you don't know what a file is, think of it as a place where you can store information under a name of your choice, and retrieve it later. Files are the topic of Section 1.2 and indeed of much of this book.) mail is one of those programs that is likely to differ from what we describe here; there are many variants. Look in your manual for details. Sending mail to someone is straightforward. Suppose it is to go to the person with the login name `nicc`. The easiest way is this:

```
$ mail nico Now type in the text of the letter on as many lines as you like ...  
After the last line of the letter type a control-d. ctl-d $
```

The `ctl-d` signals the end of the letter by telling the mail command that there is no more input. If you change your mind half-way through composing the letter, press `DELETE` instead of `ctl-d`. The half-formed letter will be stored in a file called `dead.letter` instead of being sent.

eCHAPTER 1

UNIX FOR BEGINNERS 9

For practice, send mail to yourself, then type mail to read it. (This isn't as aberrant as it might sound - it's a handy reminder mechanism.) There are other ways to send mail - you can send a previously prepared letter, you can mail to a number of people all at once, and you may be able to send mail to people on other machines. For more details see the description of the mail command in Section 1 of the UNIX Programmer's Manual. Henceforth we'll use the notation mail(1) to mean the page describing mail in Section 1 of the manual. All of the commands discussed in this chapter are found in Section 1. There may also be a calendar service (see calendar(1)); we'll show you in Chapter 4 how to set one up if it hasn't been done already.

Writing to other users If your UNIX system has multiple users, someday, out of the blue, your terminal will print something like

Message from mary tty7...

accompanied by a startling beep. Mary wants to write to you, but unless you take explicit action you won't be able to write back. To respond, type

```
$ write mary
```

This establishes a two-way communication path. Now the lines that Mary types on her terminal will appear on yours and vice versa, although the path is slow, rather like talking to the moon. If you are in the middle of something, you have to get to a state where you can type a command.

Normally, whatever program you are running has to stop or be stopped, but some programs, such as the editor and `wri te` itself, have a `!` command to escape temporarily to the shell - see Table 2 in Appendix 1. The `wri te` command imposes no rules, so a protocol is needed to keep what you type from getting garbled up with what Mary types. One convention is to take turns, ending each turn with `(0)`, which stands for "over," and to signal your intent to quit with `(00)`, for "over and out."

10 THE UNIX PROGRAMMING ENVIRONMENT

eCHAPTER 1

Mary's terminal: `$ write you`

Your terminal:

`$ Message from mary tty7... write mary`

`Message from you ttya... did you forget lunch? (0)`

`did you forget lunch? (0) five@ ten minutes (0)`

`ten minutes (0) ok (00)`

ok (00) `ctl-d`

EOF `ctl-d`

\$ EOF

\$

You can also exit from `wr i te` by pressing `DELETE`. Notice that your typing errors do not appear on Mary's terminal. If you try to write to someone who isn't logged in, or who doesn't want to be disturbed, you'll be told. If the target is logged in but doesn't answer after a decent interval, the person may be busy or away from the terminal; simply type `ctl-d` or `DELETE`. If you don't want to be disturbed, use `me sg(1)` .

News Many UNIX systems provide a news service, to keep users abreast of interesting and not so interesting events. Try typing

\$ `news`

There is also a large network of UNIX systems that keep in touch through tele- phone calls; ask a local expert about netnews and USENET.

The manual *The UNIX Programmer's Manual* describes most of what you need to know about the system. Section 1 deals with commands, including those we discuss in this chapter. Section 2 describes the system calls, the subject of Chapter 7, and Section 6 has information about games. The remaining sections talk about functions for use by C programmers, file formats, and system maintenance. (The numbering of these sections varies from system to system.) Don't forget the permuted index at the beginning; you can skim it quickly for commands that might be relevant to what you want to do. There is also an introduction to the system that gives an overview of how things work. Often the manual is kept on-line so that you can read it on your terminal. If you get stuck on something, and can't find an expert to help, you can print any manual page on your terminal with the command `man command-name`.

eHAPTER 1

UNIX FOR BEGINNERS 11

Thus to read about the `who` command, type

```
$ man who
```

and, of course,

```
$ man man
```

tells about the man command.

Computer-aided instruction Your system may have a command called learn, which provides computer-aided instruction on the file system and basic commands, the editor, document preparation, and even C programming. Try

```
$ learn
```

If learn exists on your system, it will tell you what to do from there. If that fails, you might also try teach.

Games It's not always admitted officially, but one of the best ways to get comfortable with a computer and a terminal is to play games. The UNIX system comes with a modest supply of games, often supplemented locally. Ask around, or see Section 6 of the manual.

1.2 Day..to...day use: files and common commands Information in a UNIX system is stored in files, which are much like ordinary office files. Each file has a name, contents, a place to keep it, and some administrative information such as who owns it and how big it is. A file might contain a letter, or a list of names and addresses, or the source statements of a program, or data to be used by a program, or even programs in their executable form and other non-textual material. The UNIX file system is organized so you can maintain your own personal files without interfering with files belonging to other people, and keep people from interfering with you too. There are myriad programs that manipulate files, but for now, we will look at only the more frequently used ones. Chapter 2 contains a

systematic discussion of the file system, and introduces many of the other file-related commands.

Creating files -- the editor If you want to type a paper or a letter or a program, how do you get the information stored in the machine? Most of these tasks are done with a text editor, which is a program for storing and manipulating information in the computer. Almost every UNIX system has a screen editor, an editor that takes advantage of modern terminals to display the effects of your editing changes in context as you make them. Two of the most popular are vi and emacs. We

12 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

won't describe any specific screen editor here, however, partly because of typographic limitations, and partly because there is no standard one. There is, however, an older editor called ed that is certain to be available on your system. It takes no advantage of special terminal features, so it will work on any terminal. It also forms the basis of other essential programs (including some screen editors), so it's worth learning eventually. Appendix 1 contains a concise description. No matter what editor you prefer, you'll have to learn it well enough to be able to create files. We'll use ed here to make the discussion concrete, and to ensure that you can make our examples run on your system, but by all means use whatever editor you like best. To use ed to create a file called junk with some text in it, do the following:

\$ ed a now type in whatever text you want ...

Invokes the text editor ed command to add text

w junk 39 q \$ The command a ("append") tells ed to start collecting text. The "." that signals the end of the text must be typed at the beginning of a line by itself. Don't forget it, for until it is typed, no other ed commands will be recognized - everything you type will be treated as text to be added. The editor command w ("write") stores the information that you typed; "w junk" stores it in a file called junk. The filename can be any word you like; we picked junk to suggest that this file isn't very important. ed responds with the number of characters it put in the file. Until the w command, nothing is stored permanently, so if you hang up and go home the information is not stored in the file. (If you hang up while editing, the data you were working on is saved in a file called ed. hup, which you can continue with at your next session.) If the system crashes (i.e., stops unexpectedly because of software or hardware failure) while you are editing, your file will contain only what the last write command placed there. But after w the information is recorded permanently; you can access it again later by typing

Type a '.' by itself to stop adding text Write your text into a file called junk ed prints number of characters written Quit ed

\$ ed junk Of course, you can edit the text you typed in, to correct spelling mistakes, change wording, rearrange paragraphs and the like. When you're done, the q command ("quit") leaves the editor.

CHAPTER 1

UNIX FOR BEGINNERS 13

What files are out there? Let's create two files, junk and temp, so we know what we have: \$ ed a To be or not to be

w junk 19 q \$ ed a That is the question.

w temp 22 q \$

The character counts from ed include the character at the end of each line, called newline, which is how the system represents RETURN. The ls command lists the names (not contents) of files: \$ ls junk temp \$ which are indeed the two files just created. (There might be others as well that you didn't create yourself.) The names are sorted into alphabetical order automatically. ls, like most commands, has options that may be used to alter its default behavior. Options follow the command name on the command line, and are usually made up of an initial minus sign '-' and a single letter meant to suggest the meaning. For example, ls -t causes the files to be listed in "time" order: the order in which they were last changed, most recent first. \$ ls -t temp junk \$

The -l option gives a "long" listing that provides more information about each file:

\$ ls -l total 2 -rw-r--r-- 1 you -rw-r--r-- 1 you \$

19 Sep 26 16:25 junk 22 Sep 26 16:26 temp

14 THE UNIX PROGRAMMING ENVIRONMENT

eHAPTER 1

"total 2" tells how many blocks of disc space the files occupy; a block is usually either 512 or 1024 characters. The string -rw-r--r-- tells who has permission to read and write the file; in this case, the owner (you) can read and write, but others can only read it. The " 1" that follows is the number of links to the file; ignore it until Chapter 2. "you" is the owner of the file, that is, the person who created it. 19 and 22 are the number of characters in the corresponding files, which agree with the numbers you got from ed. The date and time tell when the file was last changed. Options can be grouped: Is -It gives the same data as Is -l, but sorted with most recent files first. The -u option gives information on when files were used: Is -lut gives a long (-l) listing in the order of most recent use. The option -r reverses the order of the output, so Is -rt lists in order of least recent use. You can also name the files you're interested in, and 1 swill list the information about them only: \$ ls -l junk -rw-r--r-- 1 you \$

19 Sep 26 16:25 junk

The strings that follow the program name on the command line, such as -l and junk in the example above, are called the program's arguments. Arguments are usually options or names of files to be used by the command. Specifying options by a minus sign and a single letter, such as -t or the combined -lt, is a common convention. In general, if a command accepts

such optional arguments, they precede any filename arguments, but may otherwise appear in any order. But UNIX programs are capricious in their treatment of multiple options. For example, standard 7th Edition `ls` won't accept

```
$ ls -l -t
```

Doesn't work in 7th Edition

as a synonym for `ls -lt`, while other programs require multiple options to be separated. As you learn more, you will find that there is little regularity or system to optional arguments. Each command has its own idiosyncrasies, and its own choices of what letter means what (often different from the same function in other commands). This unpredictable behavior is disconcerting and is often cited as a major flaw of the system. Although the situation is improving - new versions often have more uniformity - all we can suggest is that you try to do better when you write your own programs, and in the meantime keep a copy of the manual handy.

Printing files - `cat` and `pr` Now that you have some files, how do you look at their contents? There are many programs to do that, probably more than are needed. One possibility is to use the editor:

eCHAPTER 1

UNIX FOR BEGINNERS 15

```
$ ed junk 1,$p To be or not to be q $
```

ed reports 19 characters in junk Print lines 1 through last File has only one line All done

ed begins by reporting the numb

r of characters in junk; the command 1, \$p tells it to print all the lines in the file. After you learn how to use the editor, you can be selective about the parts you print. There are times when it's not feasible to use an editor for printing. For example, there is a limit - several thousand lines - on how big a file ed can handle. Furthermore, it will only print one file at a time, and sometimes you want to print several, one after another without pausing. So here are a couple of alternatives. First is cat, the simplest of all the printing commands. cat prints the contents of all the files named by its arguments: \$ cat junk To be or not to be \$ cat temp That is the question. \$ cat junk temp To be or not to be That is the question. \$ The named file or files are catenated (hence the name "cat") onto the terminal one after another with nothing between. There's no problem with short files, but for long ones, if you have a high-speed connection to your computer, you have to be quick with `ctl-s` to stop output from cat before it flows off your screen. There is no "standard" command to print a file on a video terminal one screenful at a time, though almost every UNIX system has one. Your system might have one called pg or more. Ours is called p; we'll show you its implementation in Chapter 6. Like cat, the command pr prints the contents of all the files named in a list, but in a form suitable for line printers: every page is 66 lines (11 inches) long, with the date and time that the file was changed, the page number, and the filename at the top of each page, and extra lines to skip over the fold in the paper. Thus, to print junk neatly, then skip to the top of a new page and print temp neatly:

t "Catenate" is a slightly obscure synonym for "concatenate."

16 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

```
$ pr junk temp
```

```
Sep 26 16:25 1983 junk Page 1
```

```
To be or not to be (60 more blank lines)
```

```
Sep 26 16:26 1983 temp Page 1
```

```
That is the question. (60 more blank lines)
```

```
$
```

pr can also produce multi-column output: `$ pr -3 filenames` prints each file in 3-column format. You can use any reasonable number in place of "3" and pr will do its best. (The word `filenames` is a place-holder for a list of names

of files.) `pr -m` will print a set of files in parallel columns. See `pr(1)`. It should be noted that `pr` is not a formatting program in the sense of rearranging lines and justifying margins. The true formatters are `nroff` and `troff`, which are discussed in Chapter 9. There are also commands that print files on a high-speed printer. Look in your manual under names like `lp` and `lpr`, or look up "printer" in the permuted index. Which to use depends on what equipment is attached to your machine. `pr` and `lpr` are often used together; after `pr` formats the information properly, `lpr` handles the mechanics of getting it to the line printer. We will return to this a little later.

Moving, copying, removing files - `mv`, `cp`, `rm` Let's look at some other commands. The first thing is to change the name of a file. Renaming a file is done by "moving" it from one name to another, like this:

```
$ mv junk precious
```

This means that the file that used to be called `junk` is now called `precious`; the contents are unchanged. If you run `ls` now, you will see a different list: `junk` is not there but `precious` is.

eCHAPTER 1

UNIX FOR BEGINNERS 17

```
$ ls precious temp $ cat junk cat: can't open junk $
```

Beware that if you move a file to another one that already exists, the target file is replaced. To make a copy of a file (that is, to have two versions of something), use the cp command:

```
$ cp precious precious.save
```

makes a duplicate copy of precious in precious. save. Finally, when you get tired of creating and moving files, the rm command removes all the files you name: \$ rm temp junk rm: junk nonexistent \$

You will get a warning if one of the files to be removed wasn't there, but otherwise rm, like most UNIX commands, does its work silently. There is no prompting or chatter, and error messages are curt and sometimes unhelpful. Brevity can be disconcerting to newcomers, but experienced users find talkative commands annoying.

What's in a filename? So far we have used filenames without ever saying what a legal name is, so it's time for a couple of rules. First, filenames are limited to 14 characters. Second, although you can use almost any character in a filename, common sense says you should stick to ones that are visible, and that you should avoid characters that might be used with other meanings. We have already se

, for example, that in the ls command, ls -t means to list in time order. So if you had a file whose name was -t, you would have a tough time listing it by name. (How would you do it?) Besides the minus sign as a first character, there are other characters with special meaning. To avoid pitfalls, you would do well to use only letters, numbers, the period and the underscore until you're familiar with the situation. (The period and the underscore are conventionally used to divide filenames into chunks, as in precious. save

above.) Finally, don't forget that case distinctions matter - junk, Junk, and JUN-K are three different names.

A handful of useful commands Now that you have the rudiments of creating files, listing their names, and printing their contents, we can look at a half-dozen file-processing commands.

18 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

To make the discussion concrete, we'll use a file called poem that contains a familiar verse by Augustus De Morgan. Let's create it with ed: \$ ed a Great fleas have little fleas upon their backs to bite 'em, And little fleas have lesser fleas, and so ad infinitum. And the great fleas themselves, in turn, have greater fleas to go on; While these again have greater still, and greater still, and so on.

```
w poem 263 q $
```

The first command counts the lines, words and characters In one or more files; it is named wc after its word-counting function:

```
$ wc poem 8
```


46

263 poem

\$

That is, poem has 8 lines, 46 words, and 263 characters. The definition of a "word" is very simple: any string of characters that doesn't contain a blank, tab or newline. we will count more than one file for you (and print the totals), and it will also suppress any of the counts if requested. See `we(1)` . The second command is called `grep`; it searches files for lines that match a pattern. (The name comes from the `ed` command `g/regular-expression/p`, which is explained in Appendix 1.) Suppose you want to look for the word "fleas" in poem:

```
$ grep fleas poem Great fleas have little fleas And little fleas have lesser  
fleas, And the great fleas themselves, in turn, have greater fleas to go on;
```

\$

`grep` will also look for lines that don't match the pattern, when the option `-v` is used. (It's named 'v' after the editor command; you can think of it as inverting the sense of the match.)

CHAPTER 1

UNIX FOR BEGINNERS 19

```
$ grep -v fleas poem upon their backs to bite 'em, and so ad infinitum.  
While these again have greater still, and greater still, and so on.
```

```
$
```

grep can be used to search several files; in that case it will prefix the filename to each line that matches, so you can tell where the match took place. There are also options for counting, numbering, and so on. grep will also handle much more complicated patterns than just words like "fleas," but we will defer consideration of that until Chapter 4. The third command is sort, which sorts its input into alphabetical order line by line. This isn't very interesting for the poem, but let's do it anyway, just to see what it looks like:

```
$ sort poem and greater still, and so on. and so ad infinitum. have greater  
fleas to go on; upon their backs to bite 'em, And little fleas have lesser fleas,  
And the great fleas themselves, in turn, Great fleas have little fleas While  
these again have greater still, $
```

The sorting is line by line, but the default sorting order puts blanks first, then upper case letters, then lower case, so it's not strictly alphabetical. sort has zillions of options to control the order of sorting - reverse order, numerical order, dictionary order, ignoring leading blanks, sorting on fields

within the line, etc. - but usually one has to look up those options to be sure of them. Here are a handful of the most common:

`sort -r sort -n sort -nr sort -f sort +n`

Reverse normal order Sort in numeric order Sort in reverse numeric order
Fold upper and lower case together Sort starting at n + 1-st field

Chapter 4 has more information about sort. Another file-examining command is tail, which prints the last 10 lines of a file. That's overkill for our eight-line poem, but it's good for larger files. Furthermore, tail has an option to specify the number of lines, so to print the last line of poem:

20 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

`$ tail -1 poem` and greater still, and so on.

`$`

tail can also be used to print a file starting at a specified line: `$ tail +3 filename` starts printing with the 3rd line. (Notice the natural inversion of

the mInus sign convention for arguments.) The final pair of commands is for comparing files. Suppose that we have a variant of poem in the file new_poem:

```
$ cat poem Great fleas have little fleas upon their backs to bite 'em, And
little fleas have lesser fleas, and so ad infinitum. And the great fleas
themselves, in turn, have greater fleas to go on; While these again have
greater still, and greater still, and so on. $ cat new_poem Great fleas have
little fleas upon their backs to bite them, And little fleas have lesser fleas,
and so on ad infinitum. And the great fleas themselves, in turn, have greater
fleas to go on; While these again have greater still, and greater still, and so
on.
```

```
$
```

There's not much difference between the two files; in fact you'll have to look hard to find it. This is where file comparison commands come in handy. `cmp` finds the first place where two files differ:

```
$ cmp poem new_poem poem new_poem differ: char 58, line 2 $
```

This says that the files are different in the second line, which is true enough, but it doesn't say what the difference is, nor does it identify any differences beyond the first. The other file comparison command is `diff`, which reports on all lines that are changed, added or deleted:

CHAPTER 1

UNIX FOR BEGINNERS 21

```
$ diff poem new_poem 2c2 < upon their backs to bite 'em, > upon their  
backs to bite them, 4c4 < and so ad infinitum. > and so on ad infinitum. $
```

This says that line 2 in the first file (poem) has to be changed into line 2 of the second file (new _poem), and similarly for line 4. Generally speaking, `cmp` is used when you want to be sure that two files really have the same contents. It's fast and it works on any kind of file, not just text. `diff` is used when the files are expected to be somewhat different, and you want to know exactly which lines differ. `diff` works only on files of text.

A summary of file system commands Table 1.1 is a brief summary of the commands we've seen so far that deal with files.

1.3 More about files: directories The system distinguishes your file called `junk` from anyone else's of the same name. The distinction is made by grouping files into directories, rather in the way that books are placed on shelves in a library, so files in different directories can have the same name without any conflict. Generally each user has a personal or home directory, sometimes called login directory, that contains only the files that belong to him or her. When you log in, you are "in" your home directory. You may change the directory you are working in - often called your working or current directory - but your home directory is always the same. Unless you take special action, when you create a new file it is made in your current directory. Since this is initially your home directory, the file is unrelated to a file of the same name that might exist in someone else's directory. A directory can contain other directories as well as ordinary files ("Great

directories have lesser directories...). The natural way to picture this organization is as a tree of directories and files. It is possible to move around within this tree, and to find any file in the system by starting at the root of the tree and moving along the proper branches. Conversely, you can start where you are and move toward the root. Let's try the latter first. Our basic tool is the command `pwd` ("print working directory"), which prints the name of the directory you are currently in:

22 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

Table 1.1:

`ls 1 s filenames ls -t ls -l ls -u ls -r`

`ed filename cp file1 file2 mv file1 file2 rm filenames cat filenames pr
filenames pr -n filenames pr -m filenames wc filenames wc -l filenames
grep pattern filenames grep -v pattern files sort filenames tail filename tail -
n filename tail +n filename cpio file1 file2 diff file1 file2`

Common File System Commands list names of all files in current directory
list only the named files list in time order, most recent first. `ls -l` long: more
information; also `ls -lt` hst by time last used; also `ls -lu`, `ls -lut` Ust in
reverse order; also `-rt`, `-r1 t`, etc.

edit named file copy file1 to file2, overwrite old file2 if it exists move file1 to file2, overwrite old file2 if it exists remove named files, irrevocably print contents of named files print contents with header, 66 lines per page print in n columns print named files side by side (multiple columns) count lines, words and characters for each file count lines for each file print lines matching pattern print lines not matching pattern sort files alphabetically by line print last 10 lines of file print last n lines of file start printing file at line n print location of first difference print all differences between files

```
$ pwd /usr/you $
```

This says that you are currently in the directory you, in the directory usr, which in turn is in the root directory, which is conventionally called just 'I'. The / characters separate the components of the name; the limit of 14 characters mentioned above applies to each component of such a name. On many systems, /usr is a directory that contains the directories of all the normal users of the system. (Even if your home directory is not /usr /you, pwd will print something analogous, so you should be able to follow what happens below.) If you now type

CHAPTER 1

UNIX FOR BEGINNERS 23

```
$ ls /usr/you
```

you should get exactly the same list of file names as you get from a plain `ls`. So When no arguments are provided, `ls` lists the contents of the current directory; given the name of a directory, it lists the contents of that directory. Next, try

```
$ ls /usr
```

This should print a long series of names, among which is your own login directory. The next step is to try listing the root itself. You should get a response similar to this:

```
$ ls / bin boot dev etc lib tmp unix usr $
```

(Don't be confused by the two meanings of `/`: it's both the name of the root and a separator in filenames.) Most of these are directories

, but `unix` is actually a file containing the executable form of the UNIX kernel. More on this in Chapter 2. Now try `$ cat /usr/you/junk`

(if `junk` is still in your directory) 0 The name

```
/usr/you/junk
```

is called the pathname of the file. "Pathname" has an intuitive meaning: it represents the full name of the path from the root through the tree of direc-

tories to a particular file. It is a universal rule in the UNIX system that wherever you can use an ordinary filename, you can use a pathname. The file system is structured like a genealogical tree; here is a picture that may make it clearer.

24 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

you mike /

junk

Your file named junk is unrelated to Paul's or to Mary's. Pathnames aren't too exciting if all the files of interest are in your own directory, but if you work with someone else or on several projects concurrently, they become handy indeed. For example, your friends can print your junk by saying \$ cat /usr/you/junk

Similarly, you can find out what files Mary has by saying

\$ Is /usr/mary data junk \$

or make your own copy of one of her files by

```
$ cp /usr/mary/data data
```

or edit her file:

```
$ ed /usr/mary/data
```

If Mary doesn't want you poking around in her files, or vice versa, privacy can be arranged. Each file and directory has read-write-execute permissions for the owner, a group, and everyone else, which can be used to control access. (Recall `ls -l`.) In our local systems, most users most of the time find openness of more benefit than privacy, but policy may be different on your system, so we'll get back to this in Chapter 2. As a final set of experiments with pathnames, try `$ ls /bin /usr/bin`

Do some of the names look familiar? When you run a command by typing its name after the prompt, the system looks for a file of that name. It normally looks first in your current directory (where it probably doesn't find it), then in `/bin`, and finally in `/usr/bin`. There is nothing special about commands

CHAPTER 1

like cat or ls, except that they have been collected into a couple of directories to be easy to find and administer. To verify this, try to execute some of these programs by using their full pathnames:

```
$ /bin/date Mon Sep 26 23:29:32 EDT $ /bin/who srm tty1 cvw "tty4 you  
tty5 $
```

1983

Sep 26 22:20 Sep 26 22:40 Sep 26 23:04

Exercise 1-3. Try

"i

```
$ ls /usr/games
```

and do whatever comes naturally. Things might be more fun outside of normal working hours. 0

Changing directory - cd If you work regularly with Mary on information in her directory, you can say "I want to work on Mary's files instead of my own." This is done by changing your current directory with the cd command:

```
$ cd /usr/mary
```

Now when you use a filename (without /'s) as an argument to cat or pr, it refers to the file in Mary's directory. Changing directories doesn't affect any permissions associated with a file - if you couldn't access a file from your own directory, changing to another directory won't alter that fact. It is usually convenient to arrange your own files so that all the files related to one thing are in a directory separate from other projects. For example, if you want to write a book, you might want to keep all the text in a directory called book. The command mkdir makes a new directory.

```
$ mkdir book $ cd book $ pwd /usr/you/book
```

Make a directory Go to it Make sure you're in the right place

```
$ cd $ pwd /usr/you $
```

Write the book (several minutes pass) Move up one level in file system

, . . ' refers to the parent of whatever directory you are currently in, the directory one level closer to the root. '..' is a synonym for the current directory.

```
$ cd
```

Return to home directory

26 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

all by itself will take you back to your home directory, the directory where you log in. Once your book is published, you can clean up the files. To remove the directory book, remove all the files in it (we'll show a fast way shortly), then cd to the parent directory of book and type

```
$ rmdir book
```

rmdir will only remove an empty directory.

1.4 The shell

When the system prints the prompt \$ and you type commands that get executed, it's not the kernel that is talking to you, but a go-between called the command interpreter or shell. The shell is just an ordinary program like `date` or `who`, although it can do some remarkable things. The fact that the shell sits between you and the facilities of the kernel has real benefits, some of which we'll talk about here. There are three main ones:

- . **Filename shorthands:** you can pick up a whole set of filenames as arguments to a program by specifying a pattern for the names - the shell will find the filenames that match your pattern.
- . **Input-output redirection:** you can arrange for the output of any program to go into a file instead of onto the terminal, and for the input to come from a file instead of the terminal. Input and output can even be connected to other programs.
- . **Personalizing the environment:** you can define your own commands and shorthands.

Filename shorthand Let's begin with filename patterns. Suppose you're typing a large document like a book. Logically this divides into many small pieces, like chapters and perhaps sections. Physically it should be divided too, because it is cumbersome to edit large files. Thus you should type the document as a number of files. You might have separate files for each chapter, called `ch 1`, `ch2`, etc. Or, if each chapter were broken into sections, you might create files called `ch 1 . 1` `ch 1 . 2` `ch 1 . 3`

`ch2.1` `ch2.2`

which is the organization we used for this book. With a systematic naming convention, you can tell at a glance where a particular file fits into the whole. What if you want to print the whole book? You could say

CHAPTER 1

UNIX FOR BEGINNERS 27

\$ pr ch1. 1 ch1.2 ch1.3 ... but you would soon get bored typing filenames and start to make mistakes. This is where filename shorthand comes in. If you say \$ pr ch"*

the shell takes the * to mean "any string of characters," so ch* is a pattern that matches all filenames in the current directory that begin with ch. The shell creates the list, in alphabetical order, and passes the list to pr. The pr command never sees the *; the pattern match that the shell does in the current directory generates a list of strings that are passed to pr. The crucial point is that filename shorthand is not a property of the pr command, but a service of the shell. Thus you can use it to generate a sequence of filenames for any command. For example, to count the words in the first chapter:

```
$ wc ch 1 . "*" 113 562 3200 ch 1 . 0 935 4081 22435 ch 1 . 1 974 4191
22756 ch 1 . 2 378 1561 8481 ch 1 . 3 1293 5298 28841 ch 1 . 4 33 194
1190 ch 1 . 5 75 323 2030 ch 1 . 6 3801 16210 88933 total $
```

There is a program called echo that is especially valuable for experimenting with the meaning of the shorthand characters. As you might guess, echo does nothing more than echo its arguments: \$ echo hello world hello world \$

But the arguments can be generated by pattern-matching: \$ echo ch 1 . "*"

lists the names of all the files in Chapter 1,

```
$ echo "*"
```

lists all the filenames in the current directory in alphabetical order,

```
$ pr "*"
```

prints all your files (in alphabetical order), and

t Again, the order is not strictly alphabetical, in that upper case letters come before lower case letters. See `ascii(7)` for the ordering of the characters used in the sort.

28 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

```
$ rm *
```


removes all files in your current directory. (You had better be very sure that's what you wanted to say!) The * is not limited to the last position in a filename - *'s can be anywhere and can occur several times. Thus

```
$ rm *.save
```

removes all files that end with . save. Notice that the filenames are sorted alphabetically, which is not the same as numerically. If your book has ten chapters, the order might not be what you intended, since ch 10 comes before ch2:

```
$ echo * ch 1 . 1 ch 1 . 2 ... ch 10 . 1 ch 10 . 2 ... ch2. 1 ch2. 2 ... $
```

The * is not the only pattern-matching feature provided by the shell, although it's by far the most frequently used. The pattern [...] matches any of the characters inside the brackets. A range of consecutive letters or digits can be abbreviated:

```
$ pr ch[12346789]* $ pr ch[ 1-46-9]* $ rm temp[a-z]
```

Print chapters 1,2,3,4,6,7,8,9 but not 5 Same thing Remove any of tempa, ..., tempz that exist

The ? pattern matches any single character:

```
$ Is ? $ Is -1 ch? 1 $ rm temp?
```

List files with single-character names List `ch 1` . `1` `ch2. 1` `ch3. 1`, etc. but not `ch 10 . 1` Remove files `temp 1`, ..., `tempa`, etc.

Note that the patterns match only existing filenames. In particular, you cannot make up new filenames by using patterns. For example, if you want to expand `ch` to `chapter` in each filename, you cannot do it this way:

```
$ mv ch.* chapter.*
```

Doesn't work!

because `chapter.*` matches no existing filenames. Pattern characters like `*` can be used in pathnames as well as simple filenames; the match is done for each component of the path that contains a special character. Thus `/usr /mary / *` performs the match in `/usr /mary`, and `/usr / * / calendar` generates a list of pathnames of all user calendar files. If you should ever have to turn off the special meaning of `*`, `?`, etc., enclose the entire argument in single quotes, as in

```
$ Is '?'
```

You can also precede a special character with a backslash:

CHAPTER 1

UNIX FOR BEGINNERS 29

\$ Is \? (Remember that because ? is not the erase or line kill character, this backslash is interpreted by the shell, not by the kernel.) Quoting is treated at length in Chapter 3. Exercise 1-4. What are the differences among these commands?

```
$ ls junk $ echo junk $ ls / $ echo / $ ls $ echo $ ls '*' $ echo '*' $ ls '*' $
echo '*' 0
```

Input-output redirection Most of the commands we have seen so far produce output on the terminal; some, like the editor, also take their input from the terminal. It is nearly universal that the terminal can be replaced by a file for either or both of input and output. As one example, `$ ls` makes a list of filenames on your terminal. But if you say `$ ls >filelist`

that same list of filenames will be placed in the file `filelist` instead. The symbol `>` means "put the output in the following file, rather than on the terminal." The file will be created if it doesn't already exist, or the previous contents overwritten if it does. Nothing is produced on your terminal. As another example, you can combine several files into one by capturing the output of `cat` in a file: `$ cat f1 f2 f3 >temp` The symbol `>>` operates much as `>` does, except that it means "add to the end of." That is,

\$ cat f1 f2 f3 »temp copies the contents of f 1, f2 and f3 onto the end of whatever is already in temp, instead of overwriting the existing contents. As with>, if temp doesn't exist, it will be created initially empty for you. In a similar way, the symbol < means to take the input for a program from the following file, instead of from the terminal. Thus, you can prepare a letter in file 1 et, then send it to several people with

```
$ mail mary joe tom bob <let
```

In all of these examples, blanks are optional on either side of > or <, but our formatting is traditional.

30 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

Given the capability of redirecting output with >, it becomes possible to combine commands to achieve effects not possible otherwise. For example, to print an alphabetical list of users,

```
$ who :>temp $ sort <temp
```

Since who prints one line of output per logged-on user, and wc -l counts lines (suppressing the word and character counts), you can count users with

```
$ who >temp $ we -1 <temp
```

You can count the files in the current directory with `$ ls >temp $ wc -1 <temp`

though this includes the filename `temp` itself in the count. You can print the filenames in three columns with

```
$ ls >temp $ pr -3 <temp
```

And you can see if a particular user is logged on by combining `who` and `grep`:

```
$ who >temp $ grep mary <temp
```

In all of these examples, as with filename pattern characters like `*`, it's important to remember that the interpretation of `>` and `<` is being done by the shell, not by the individual programs. Centralizing the facility in the shell means that input and output redirection can be used with any program; the program itself isn't aware that something unusual has happened. This brings up an important convention. The command

```
$ sort <temp
```

sorts the contents of the file temp, as does

```
$ sort temp
```

but there is a difference. Because the string `<temp` is interpreted by the shell, sort does not see the filename temp as an argument; it instead sorts its standard input, which the shell has redirected so it comes from the file. The latter example, however, passes the name temp as an argument to sort, which reads the file and sorts it. sort can be given a list of filenames, as in `$ sort temp1 temp2 temp3`

but if no filenames are given, it sorts its standard input. This is an essential property of most commands: if no filenames are specified, the standard input is processed. This means that you can simply type at commands to see how they

CHAPTER 1

UNIX FOR BEGINNERS 31

work. For example,

```
$ sort ghi abe def ctl-d abc def ghi $
```

In the next section, we will see how this principle is exploited. Exercise 1

5. Explain why

```
$ 15 >ls.out
```

causes ls.out to be included in the list of names. 0 Exercise 1

6. Explain the output from

```
$ we temp >temp
```

If you misspell a command name, as in

```
$ woh >temp
```

what happens? 0

Pipes All of the examples at the end of the previous section rely on the same trick: putting the output of one program into the input of another via a temporary file. But the temporary file has no other purpose; indeed, it's clumsy to have to use such a file. This observation leads to one of the fundamental contributions of the UNIX system, the idea of a pipe. A pipe

is a way to connect the output of one program to the input of another program without any temporary file; a pipeline is a connection of two or more programs through pipes. Let us revise some of the earlier examples to use pipes instead of temporaries. The vertical bar character `|` tells the shell to set up a pipeline:

```
$ who | sort | wc -l | wc -l | pr -3 | grep mary
```

Print sorted list of users
Count users
Count files
3 -column list of filenames
Look for particular user

Any program that reads from the terminal can read from a pipe instead; any program that writes on the terminal can write to a pipe. This is where the convention of reading the standard input when no files are named pays off: any program that adheres to the convention can be used in pipelines. `grep`, `pr`, `sort` and `wc` are all used that way in the pipelines above. You can have as many programs in a pipeline as you wish:

32 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

```
$ wc -l | pr -3 | wc -l
```


creates a 3-column list of filenames on the line printer, and \$ who : grep
mary : we -1

counts how many times Mary is logged in. The programs in a pipeline actually run at the same time, not one after another. This means that the programs in a pipeline can be interactive; the kernel looks after whatever scheduling and synchronization is needed to make it all work. As you probably suspect by now, the shell arranges things when you ask for a pipe; the individual programs are oblivious to the redirection. Of course, programs have to operate sensibly if they are to be combined this way. Most commands follow a common design, so they will fit properly into pipelines at any position. Normally a command invocation looks like command optional-arguments optional-filenames

If no filenames are given, the command reads its standard input, which is by default the terminal (handy for experimenting) but which can be redirected to come from a file or a pipe. At the same time, on the output side, most commands write their output on the standard output, which is by default sent to the terminal. But it too can be redirected to a file or a pipe. Error messages from commands have to be handled differently, however, or they might disappear into a file or down a pipe. So each command has a standard error output as well, which is normally directed to your terminal. Or, as a picture:

standard input or files

command, options

standard output

standard error

Almost all of the commands we have talked about so far fit this model; the only exceptions are commands like `date` and `who` that read no input, and a few like `crop` and `diff` that have a fixed number of file inputs. (But look at the `'-'` option on these.) Exercise 1-7. Explain the difference between

`$ who | sort`

and

CHAPTER 1

UNIX FOR BEGINNERS 33

`$ who >sort`

o

Processes The shell does quite a few things besides setting up pipes. Let us turn briefly to the basics of running more than one program at a time, since we have already seen a bit of that with pipes. For example, you can run two programs with one command line by separating the commands with a semicolon; the shell recognizes the semicolon and breaks the line into two commands:

```
$ date; Tue Sep ken dmr rob bwk jj you ber $
```

```
who 27 01:03:17 EDT ttyO Sep 27 tty1 Sep 26 tty2 Sep 26 tty3 Sep 27 tty4  
Sep 26 tty5 Sep 26 tty7 Sep 26
```

```
1983 00:43 23:45 23:59 00:06 23:31 23:04 23:34
```

Both commands are executed (in sequence) before the shell returns with a prompt character. You can also have more than one program running simultaneously if you wish. For example, suppose you want to do something time-consuming like counting the words in your book, but you don't want to wait for it to finish before you start something else. Then you can say

```
$ wc eh* >we.out & 6944 $
```

Process-id printed by the shell

The ampersand &. at the end of a command line says to the shell "start this command running, then take further commands from the terminal immediately," that is, don't wait for it to complete. Thus the command will begin, but you can do something else while it's running. Directing the output into the file we'll out keeps it from interfering with whatever you're doing at the same time. An instance of a running program is called a process. The number printed by the shell for a command initiated with &. is called the process-id; you can use it in other commands to refer to a specific running program. It's important to distinguish between programs and processes. wc is a program; each time you run the program wc, that creates a new process. If several instances of the same program are running at the same time, each is a separate process with a different process-id. If a pipeline is initiated with &., as in

34 THE UNIX PROGRAMMING ENVIRONMENT

```
$ pr ch* 6951 $
```

CHAPTER 1

/ lpr & Process-id of lpr

the processes in it are all started at once - the &. applies to the whole pipeline. Only one process-id is printed, however, for the last process in the sequence. The command

```
$ wait
```

waits until an processes initiated with &. have finished. If it doesn't return immediately, you have commands still running. You can interrupt wait with DELETE. You can use the process-id printed by the shell to stop a process initiated with &.:

\$ kill 6944 If you forget the process-id, you can use the command ps to tell you abC'ut everything you have running. If you are desperate, kill 0 will kill all your processes except your login shell. And if you're curious about what other users are doing, ps -ag will tell you about all processes that are currently running. Here is some sample output: \$ ps -ag PID TTY 36 co
6423 5 6704 1 6722 1 4430 2 6612 7 6628 7 6843 2 6949 4 6952 5 6951 5
6959 5 6844 1

\$

```
TIME CMD 6:29 /etc/cron 0:02 -sh 0:04 -sh 0:12 vi paper 0:03 -sh 0:03 -sh  
1:13 rogue 0:02 write dmr 0:01 login bimmler 0:08 pr ch1.1 ch1.2 ch1.3  
ch1.4 0:03 lpr 0:02 ps -ag 0:02 write rob
```

PID is the process-id; TTY is the terminal associated with the process (as in who); TIME is the processor time used in minutes and seconds; and the rest is the command being run. ps is one of those commands that is different on different versions of the system, so your output may not be formatted like this. Even the arguments may be different - see the manual page ps(1). Processes have the same sort of hierarchical structure that files do: each process has a parent, and may well have children. Your shell was created by a process associated with whatever terminal line connects you to the system. As

CHAPTER 1

UNIX FOR BEGINNERS 35

you run commands, those processes are the direct children of your shell. If you run a program from within one of those, for example with the `!` command to escape from `ed`, that creates its own child process which is thus a grandchild of the shell. Sometimes a process takes so long that you would like to start it running, then turn off the terminal and go home without waiting for it to finish. But if you turn off your terminal or break your connection, the process will normally be killed even if you used `&`. The command `nohup` ("no hangup") was created to deal with this situation: if you say `$ nohup command &`.

the command will continue to run if you log out. Any output from the command is saved in a file called `nohup.out`. There is no way to `nohup` a command retroactively. If your process will take a lot of processor resources, it is kind to those who share your system to run your job with lower than normal priority; this is done by another program called `nice`:

`$ nice expensive-command &`.

`nohup` automatically calls `nice`, because if you're going to log out you can afford to have the command take a little longer. Finally, you can simply tell the system to start your process at some wee hour of the morning when normal people are asleep, not computing. The command is called `at(1)`:

\$ at time whatever commands you want ... `ctl-d` \$

This is the typical usage, but of course the commands could come from a file: \$ at 3am <file \$ Times can be written in 24-hour style like 2 1 30, or 12-hour style like 930 pm.

Tailoring the environment One of the virtues of the UNIX system is that there are several ways to bring it closer to your personal taste or the conventions of your local computing environment. For example, we mentioned earlier the problem of different standards for the erase and line kill characters, which by default are usually # and @. You can change these any time you want with \$ stty erase e kill k where e is whatever character you want for erase and k is for line kill. But it's

36 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

a bother to have to type this every time you log in. The shell comes to the rescue. If there is a file named `.. profile` in your login directory, the shell will execute the commands in it when you log in, before printing the first prompt. So you can put commands into `.. profile` to set up your environment as you like it, and they will be executed every time you log in. The first thing most people put in their `.. profile` is

`stty erase ...`

We're using `+-` here so you can see it, but you could put a literal backspace in your `..` profile. `stty` also understands the notation `AX` for `etl-x`, so you can get the same effect with

`stty erase 'J'.h'`

because `etl-h` is backspace. (The `A` character is an obsolete synonym for the pipe operator `:`, so you must protect it with quotes.) If your terminal doesn't have sensible tab stops, you can add `-tabs` to the `stty` line:

`stty erase 'J'.h' -tabs`

If you like to see how busy the system is when you log in, add

`who : we -1`

to count the users. If there's a news service, you can add news. Some people like a fortune cookie:

`/usr/games/fortune`

After a while you may decide that it is taking too long to log in, and cut your .. profile back to the bare necessities. Some of the properties of the shell are actually controlled by so-called shell variables, with values that you can access and set yourself. For example, the prompt string, which we have been showing as \$, is actually stored in a shell variable called PS1, and you can set it to anything you like, like this:

```
PS1='Yes dear? '
```

The quotes are necessary since there are spaces in the prompt string. Spaces are not permitted around the = in this construction. The shell also treats the variables HOME and MAIL specially. HOME is the name of your home directory; it is normally set properly without having to be in .. profile. The variable MAIL names the standard file where your mail is kept. If you define it for the shell, you will be notified after each command if new mail has arrived:

This is implemented badly in the shell. Looking at the file after every command adds perceptibly to the system load. Also, if you are working in an editor for a long time you won't learn about

CHAPTER 1

```
MAIL=/usr/spool/mail/you
```

(The mail file may be different on your system; /usr /mail/you is also common.) Probably the most useful shell variable is the one that controls where the shell looks for commands. Recall that when you type the name of a command, the shell normally looks for it first in the current directory, then in /bin, and then in /usr /bin. This sequence of directories is called the search path, and is stored in a shell variable called PATH. If the default search path isn't what you want, you can change it, again usually in your .. profile. For example, this line sets the path to the standard one plus /usr /games:

```
PATH=.:lbin:/usr/bin:/usr/games
```

One way...

The syntax is a bit strange: a sequence of directory names separated by colons. Remember that '.. ' is the current directory. You can omit the '.. ' ; a null component in PATH means the current directory. An alternate way to set PATH in this specific case is simply to augment the previous value:

```
PATH=$PATH:/usr/games
```

. .. Another way

You can obtain the value of any shell variable by prefixing its name with a \$. In the example above, the expression \$PATH retrieves the current value, to which the new part is added, and the result is assigned back to PATH.

You can verify this with echo: \$ echo PATH is \$PATH PATH is
:/bin:/usr/bin:/usr/games \$ echo \$HOME Your login directory /usr/you \$

If you have some of your own commands, you might want to collect them in a directory of your own and add that to your search path as well. In that case, your PATH might look like this:

```
PATH=$HOME/bin:/bin:/usr/bin:/usr/games
```

We'll talk about writing your own commands in Chapter 3. Another variable, often used by text editors fancier than ed, is TERM, which names the kind of terminal you are using. That information may make it possible for programs to manage your screen more effectively. Thus you might add something like

new mail because you aren't running new commands with your login shell
A better design is to look every few minutes, instead of after every
command. Chapters 5 and 7 show how to implement this kind of mail
checker. A third possibility, not available to everyone, is to have the mail
program notify you itself: it certainly knows when mail comes for you.

38 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 1

TERM=adm3

to your `..profile` file. It is also possible to use variables for abbreviation. If you find yourself frequently referring to some directory with a long name, it might be worthwhile adding a line like `d = / horribly / long / directory / name`

to your profile, so that you can say things like `$ cd $d` Personal variables like `d` are conventionally spelled in lower case to distinguish them from those used by the shell itself, like `PATH`. Finally, it's necessary to tell the shell that you intend to use the variables in other programs; this is done with the command `export`, to which we will return in Chapter 3: `export MAIL PATH TERM`

To summarize, here is what a typical" profile file might look like: `$ cat _profile stty erase '`

```
h' -tabs MAIL=/usr/spool1/mail/you
PATH=$HOME/bin:/bin:/usr/bin:/usr/games TERM=adm3
b=$HOME/book export MAIL PATH TERM b date who : we -1 $
```

We have by no means exhausted the services that the shell provides. One of the most useful is that you can create your own commands by packaging existing commands into a file to be processed by the shell. It is remarkable how much can be achieved by this fundamentally simple mechanism. Our discussion of it begins in Chapter 3.

1.5 The rest of the UNIX system There's much more to the UNIX system than we've addressed in this chapter, but then there's much more to this

book. By now, you should feel comfortable with the system and, particularly, with the

manual. When you have specific questions about when or how to use commands, the manual is the place to look. It is also worth browsing in the manual occasionally, to refresh your knowledge of familiar commands and to discover new ones. The manual describes many programs we won't illustrate, including compilers for languages

CHAPTER 1

UNIX FOR BEGINNERS 39

like FORTRAN 77; calculator programs such as `bc(1)`; `ed(1)` and `uucp(1)` for inter-machine communication; graphics packages; statistics programs; and `esoteric` such as `units(1)`. As we've said before, this book does not replace the manual, it supplements it. In the chapters that follow we will look at pieces and programs of the UNIX system, starting from the information in the manual but following the threads that connect the components. Although the program interrelationships are never made explicit in the manual, they form the fabric of the UNIX programming environment.

History and bibliographic notes The original UNIX paper is by D. M. Ritchie and K. L. Thompson: "The UNIX Time-sharing System," *Communications of the ACM*, July, 1974, and reprinted in *CACM*, January, 1983. (Page 89 of the reprint is in the March 1983 issue.) This overview of the system for people interested in operating systems is worth reading by anyone who programs. The *Bell System Technical Journal (BSTJ)* special issue on the UNIX system (July, 1978) contains many papers describing

subsequent developments, and some retrospective material, including an update of the original CACM paper by Ritchie and Thompson. A second special issue of the BST J, containing new UNIX papers, is scheduled to be published in 1984. "The UNIX Programming Environment," by B. W. Kernighan and J. R. Mashey (IEEE Computer Magazine, April, 1981), attempts to convey the essential features of the system for programmers. The UNIX Programmer's Manual, in whatever version is appropriate for your system, lists commands, system routines and interfaces, file formats, and maintenance procedures. You can't live without this for long, although you will probably only need to read parts of Volume 1 until you start programming. Volume 1 of the 7th Edition manual is published by Holt, Rinehart and Winston. Volume 2 of the UNIX Programmer's Manual is called "Documents for Use with the UNIX Time-sharing System" and contains tutorials and reference manuals for major commands. In particular, it describes document preparation programs and program development tools at some length. You will want to read most of this eventually. A UNIX Primer, by Ann and Nico Lomuto (Prentice-Hall, 1983), is a good introduction for raw beginners, especially non-programmers.

CHAPTER 2: THE FILE SYSTEM

Everything in the UNIX system is a file. That is less of an oversimplification than you might think. When the first version of the system was being designed, before it even had a name, the discussions focused on the structure of a file system that would be clean and easy to use. The file system is central to the success and convenience of the UNIX system. It is one of the best examples of the "keep it simple" philosophy, showing the power achieved by careful implementation of a few well-chosen ideas. To talk comfortably about commands and their interrelationships, we need a good background in the structure and outer workings of the file system. This chapter covers most of the details of using the file system - what files are, how they are represented, directories and the file system hierarchy, permissions, inodes (the system's internal record of files) and device files. Because most use of the UNIX system deals with manipulating files, there

are many commands for file investigation or rearrangement; this chapter introduces the more commonly used ones.

2.1 The basics of files A file is a sequence of bytes. (A byte is a small chunk of information, typically 8 bits long. For our purposes, a byte is equivalent to a character.) No structure is imposed on a file by the system, and no meaning is attached to its contents - the meaning of the bytes depends solely on the programs that interpret the file. Furthermore, as we shall see, this is true not just of disc files but of peripheral devices as well. Magnetic tapes, mail messages, characters typed on the keyboard, line printer output, data flowing in pipes - each of these files is just a sequence of bytes as far as the system and the programs in it are concerned. The best way to learn about files is to play with them, so start by creating a small file:

41

42 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

\$ ed a now is the time for all good people

w junk 36 q \$ 1s -1 junk -rw-r--r-- 1 you \$

36 Sep 27 06:11 junk

junk is a file with 36 bytes - the 36 characters you typed while appending (except, of course, for correction of any typing mistakes). To see the file, \$ cat junk now is the time for all good people \$

cat shows what the file looks like. The command od (octal dump) prints a visible representation of all the bytes of a file:

```
$ od -c junk 0000000 n o w i s t h e t i m e \n 0000020 f o r a l l g o o d p e o  
0 0000040 p l e \n 0000044 $
```

The -c option means "interpret bytes as characters." Turning on the -b option will show the bytes as octal (base 8) numbers as well:

```
$ od -cb junk 0000000 n o w i s t h e t i m e \n 156 157 167 040 151 163  
040 164 150 145 040 164 151 155 145 012 0000020 f o r a l l g o o d p e o  
146 157 162 040 141 154 154 040 147 157 157 144 040 160 145 157  
0000040 p l e \n 160 154 145 012 0000044 $ The 7-digit numbers down  
the left side are positions in the file, that is, the
```

Each byte in a file contains a number large enough to encode a printable character. The encoding on most UNIX systems is called ASCII (American Standard Code for Information Interchange), but some machines, particularly those manufactured by IBM, use an encoding called EBCDIC (Extended Binary-Coded-Decimal Interchange Code).

Throughout this book, we will assume the ASCII encoding; `cat /usr/pub/ascii` or `read ascii(7)` to see the octal values of all the characters.

CHAPTER 2

THE FILE SYSTEM 43

ordinal number of the next character shown, in octal. By the way, the emphasis on octal numbers is a holdover from the PDP-11, for which octal was the preferred notation. Hexadecimal is better suited for other machines; the `-x` option tells `ad` to print in hex. Notice that there is a character after each line, with octal value 012. This is the ASCII newline character; it is what the system places in the input when you press the RETURN key. By a convention borrowed from C, the character representation of a newline is `\n`, but this is only a convention used by programs like `ad` to make it easy to read - the value stored in the file is the single byte 012. Newline is the most common example of a special character. Other characters associated with some terminal control operation include backspace (octal value 010, printed as `\b`), tab (011, `'t'`), and carriage return (015, `\r`). It is important in each case to distinguish between how the character is stored in a file and how it is interpreted in various situations. For example, when you type a backspace on your keyboard (and assuming that your erase character is backspace), the kernel interprets it to mean that you want to discard whatever character you typed previously. Both that character and the backspace disappear, but the backspace is echoed to your terminal, where it makes the cursor move one position backwards. If you type the sequence

`\+-`

(i.e., \ followed by a backspace), however, the kernel interprets that to mean that you want a literal backspace in your input, so the \ is discarded and the byte 010 winds up in your file. When the backspace is echoed on your terminal, it moves the cursor to sit on top of the . When you print a file that contains a backspace, the backspace is passed uninterpreted to your terminal, which again will move the cursor one position backwards. When you use `od` to display a file that contains a backspace, it appears as a byte with value 010, or, with the `-c` option, as `\b`. The story for tabs is much the same: on input, a tab character is echoed to your terminal and sent to the program that is reading; on output, the tab is simply sent to the terminal for interpretation there. There is a difference, though - you can tell the kernel that you want it to interpret tabs for you on output; in that case, each tab that would be printed is replaced by the right number of blanks to get to the next tab stop. Tab stops are set at columns 9, 17, 25, etc. The command

`$ stty -tabs` causes tabs to be replaced by spaces when printed on your terminal. See `stty(1)`. The treatment of RETURN is analogous. The kernel echoes RETURN as a carriage return and a newline, but stores only the newline in the input. On

44 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

output, the newline is expanded into carriage return and newline. The UNIX system is unusual in its approach to representing control information, particularly its use of newlines to terminate lines. Many systems instead provide "records," one per line, each of which contains not only your data but also a count of the number of characters in the line (and no ne

/line). Other systems terminate each line with a carriage return and a newline, because that sequence is necessary for output on most terminals. (The word "linefeed" is a synonym for newline, so this sequence is often called "CRLF," which is nearly pronounceable.) The UNIX system does neither - there are no records, no record counts, and no bytes in any file that you or your programs did not put there. A new-line is expanded into a carriage return and a newline when sent to a terminal, but programs need only deal with the single newline character, because that is all they see. For most purposes, this simple scheme is exactly what is wanted. When a more complicated structure is needed, it can easily be built on top of this; the converse, creating simplicity from complexity, is harder to achieve. Since the end of a line is marked by a newline character, you might expect a file to be terminated by another special character, say `\e` for "end of file." Looking at the output of `ad`, though, you will see no special character at the end of the file - it just stops. Rather than using a special code, the system signifies the end of a file by simply saying there is no more data in the file. The kernel keeps track of file lengths, so a program encounters end-of-file when it has processed all the bytes in a file. Programs retrieve the data in a file by a system call (a subroutine in the kernel) called `read`. Each time `read` is called, it returns the next part of a file - the next line of text typed on the terminal, for example. `read` also says how many bytes of the file were returned, so end of file is assumed when a `read` says "zero bytes are being returned." If there were any bytes left, `read` would have returned some of them. Actually, it makes sense not to represent end of file by a special byte value, because, as we said earlier, the meaning of the bytes depends on the interpretation of the file. But all files must end, and since all files must be accessed through `read`, returning zero is an interpretation-independent way to represent the end of a file without introducing a new special character. When a program reads from your terminal, each input line is given to the program by the kernel only when you type its newline (i.e., press RETURN). Therefore if you make a typing mistake, you can back up and correct it if you realize the mistake before you type newline. If you type newline before realizing the error, the line has been read by the system and you cannot correct it. We can see how this line-at-a-time input works using `cat`. `cat` normally saves up or buffers its output to write in large chunks for efficiency, but `cat -u` "unbuffers" the output, so it is printed immediately as it is read:

CHAPTER 2

THE FILE SYSTEM 45

```
$ cat 123 456 789 ctl- d 123 456 789 $ cat -u 123 123 456 456 789 789 ctl-  
d $
```

Buffered output from cat

Unbuffered output from cat

cat receives each line when you press RETURN; without buffering, it prints the data as it is received. Now try something different: type some characters and then a ctl-d rather than a RETURN:

```
$ cat -u 123ctl-d123
```

cat prints the characters out immediately. ctl-d says, "immediately send the characters I have typed to the program that is reading from my terminal." The ctl-d itself is not sent to the program, unlike a newline. Now type a second ctl-d, with no other characters:

```
$ cat -u 12 3ctl-d 12 3ctl-d$
```

The shell responds with a prompt, because cat read no characters, decided that meant end of file, and stopped. ctl-d sends whatever you have typed to the program that is reading from the terminal. If

you haven't typed anything, the program will therefore read no characters, and that looks like the end of the file. That is why typing `ctl-d` logs you out - the shell sees no more input. Of course, `ctl-d` is usually used to signal an end-of-file but it is interesting that it has a more general function. Exercise 2-1. What happens when you type `ctl-d` to `ed`? Compare this to the command

```
$ ed <file
```

```
o
```

46 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

2.2 What's in a file?

The format of a file is determined by the programs that use it; there is a wide variety of file types, perhaps because there is a wide variety of programs. But since file types are not determined by the file system, the kernel can't tell you the type of a file: it doesn't know it. The `file` command makes an educated guess (we'll explain how shortly):

```
$ file /bin /bin/ed /usr/src/cmd/edec /usr/man/man1/ede 1 /bin: directory
/bin/ed: pure executable /usr/src/cmd/ed.c: c program text
```

/usr/man/man1/ed.1: roff, nroff, or eqn input text \$

These are four fairly typical files, all related to the editor: the directory in which it resides (/bin), the "binary" or runnable program itself (/bin/ ed) , the "source" or C statements that define the program (/usr /src/cmd/ed. c) and the manual page (/usr/man/man 1/ed. 1). To determine the types, file didn't pay attention to the names (although it could have), because naming conventions are just conventions, and thus not perfectly reliable. For example, files suffixed . c are almost always C source, but there is nothing to prevent you from creating a . c file with arbitrary contents. Instead, file reads the first few hundred bytes of a file and looks for clues to the file type. (As we will show later on, files with special system properties, such as directories, can be identified by asking the system, but file could identify a directory by reading it.) Sometimes the clues are obvious. A runnable program is marked by a binary "magic number" at its beginning. ad with no options dumps the file in 16-bit, or 2-byte, words and makes the magic number visible: \$ ad /bin/ed 0000000 000410 025000 000462 011444 000000 000000 000000 000001 0000020 170011 016600 000002 005060 177776 010600 162706 000004 0000040 016616 000004 005720 010066 000002 005720 001376 020076

\$

The octal value 410 marks a pure executable program, one for which the executing code may be shared by several processes. (Specific magic numbers are system dependent.) The bit pattern represented by 410 is not ASCII text, so this value could not be created inadvertently by a program like an editor. But you could certainly create such a file by running a program of your own, and the system understands the convention that such files are program binaries. For text files, the clues may be deeper in the file, so file looks for words like #include to identify C source, or lines beginning

with a period to identify nraff or traff input. You might wonder why the system doesn't track file types more carefully,

eHAPTER 2

THE FILE SYSTEM 47

so that, for example, sort is never given /bin/ed as input. One reason is to avoid foreclosing some useful computation. Although `$ sort /bin/ed`

doesn't make much sense, there are many commands that can operate on any file at all, and there's no reason to restrict their capabilities. `od`, `wc`, `cp`, `crop`, `file` and many others process files regardless of their contents. But the formatless idea goes deeper than that. If, say, nroff input were distinguished from C source, the editor would be forced to make the distinction when it created a file, and probably when it read in a file for editing again. And it would certainly make it harder for us to typeset the C programs in Chapters 6 through 8! Instead of creating distinctions, the UNIX system tries to efface them. All text consists of lines terminated by newline characters, and most programs understand this simple format. Many times while writing this book, we ran commands to create text files, processed them with commands like those listed above, and used an editor to merge them into the troff input for the book. The transcripts you see on almost every page are made by commands like `$ od -c junk >temp` `$ ed ch2.`

```
1 1534 r temp 168
```

`od` produces text on its standard output, which can then be used anywhere text can be used. This uniformity is unusual; most systems have several file

for- mats, even for text, and require negotiation by a program or a user to create a file of a particular type. In UNIX systems there is just one kind of file, and all that is required to access a file is its name. ^t The lack of file formats is an advantage overall - programmers needn't worry about file types, and all the standard programs will work on any file - but there are a handful of drawbacks. Programs that sort and search and edit really expect text as input: `grep` can't examine binary files correctly, nor can `sort` sort them, nor can any standard editor manipulate them. There are implementation limitations with most programs that expect text as input. We tested a number of programs on a 30,000 byte text file containing no newlines, and surprisingly few behaved properly, because most programs make unadvertised assumptions about the maximum length of a line of text (for an exception, see the BUGS section of `sort(1)`).

^t There's a good test of file system uniformity, due originally to Doug McIlroy, that the UNIX file system passes handily. Can the output of a FORTRAN program be used as input to the FORTRAN compiler? A remarkable number of systems have trouble with this test

48 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

Non-text files definitely have their place. For example, very large databases usually need extra address information for rapid access; this has to be binary for efficiency. But every file format that is not text must have its own family of support programs to do things that the standard tools could perform if the format were text. Text files may be a little less efficient in machine cycles, but this must be balanced against the cost of extra software to maintain more specialized formats. If you design a file format, you

should think carefully before choosing a non-textual representation. (You should also think about making your programs robust in the face of long input lines.)

2.3 Directories and filenames

All the files you own have unambiguous names, starting with `/usr/you`, but if the only file you have is `junk`, and you type `ls`, it doesn't print `/usr/you/junk`; the filename is printed without any prefix: `$ ls junk $`

That is because each running program, that is, each process, has a current directory, and all filenames are implicitly assumed to start with the name of that directory, unless they begin directly with a slash. Your login shell, and `ls`, therefore have a current directory. The command `pwd` (print working directory) identifies the current directory: `$ pwd /usr/you $`

The current directory is an attribute of a process, not a person or a program - people have login directories, processes have current directories. If a process creates a child process, the child inherits the current directory of its parent. But if the child then changes to a new directory, the parent is unaffected - its current directory remains the same no matter what the child does. The notion of a current directory is certainly a notational convenience, because it can save a lot of typing, but its real purpose is organizational. Related files belong together in the same directory. `/usr` is often the top directory of the user file system. (user is abbreviated to `usr` in the same spirit as `cmp`, `ls`, etc.) `/usr/you` is your login directory, your current directory when you first log in. `/usr/src` contains source for system programs, `/usr/src/cmd` contains source for UNIX commands, `/usr/src/cmd/sh` contains the source files for the shell, and so on. Whenever you embark on a new

project, or whenever you have a set of related files, say a set of recipes, you could create a new directory with `mkdir` and put the files there.

CHAPTER 2

THE FILE SYSTEM 49

```
$ pwd /usr/you $ mkdir recipes $ cd recipes $ pwd /usr/you/recipes $ mkdir  
pie cookie $ cd pie/apple
```

```
$ cd cookie/choc.chip
```

```
$
```

Notice that it is simple to refer to subdirectories. `pie/apple` has an obvious meaning: the apple pie recipe, in directory `/usr/you/recipes/pie`. You could instead have put the recipe in, say, `recipes/apple.pie`, rather than in a subdirectory of `recipes`, but it seems better organized to put all the pies together, too. For example, the crust recipe could be kept in `recipes/pie/crust` rather than duplicating it in each pie recipe. Although the file system is a powerful organizational tool, you can forget where you put a file, or even what files you've got. The obvious solution is a command or two to rummage around in directories. The `ls` command is certainly helpful for finding files, but it doesn't look in sub-directories.

```
$ cd $ ls junk recipes $ file * junk: recipes: $ ls recipes cookie
```

ascii text directory

```
pie $ ls recipes/pie apple crust $
```

This piece of the file system can be shown pictorially as:

50 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

```
/usr/you /
```

```
    junk recipes /
```

```
        pie /
```

```
            apple
```

```
cookie
```

```
crust
```

choc.chip

The command `du` (disc usage) was written to tell how much disc space is consumed by the files in a directory, including all its subdirectories. `$ du 6 ./recipes/pie 4 ./recipes/cookie 11 ./recipes 13 $`

The filenames are obvious; the numbers are the number of disc blocks - typically 512 or 1024 bytes each - of storage for each file. The value for a directory indicates how many blocks are consumed by all the files in that directory and its subdirectories, including the directory itself. `du` has an option `-a`, for "all," that causes it to print out all the files in a directory. If one of those is a directory, `du` processes that as well: `$ du -a 2 3 6 3 4 11 1 13 $`

```
./recipes/pie/apple ./recipes/pie/crust ./recipes/pie ./recipes/cookie/choc.chip
./recipes/cookie ./recipes ./junk
```

The output of `du -a` can be piped through `grep` to look for specific files:

```
$ du -a : grep choc 3 ./recipes/cookie/choc.chip $
```

Recall from Chapter 1 that the name `'.'` is a directory entry that refers to the directory itself; it permits access to a directory without having to know the full

eCHAPTER 2

THE FILE SYSTEM 51

name. `du` looks in a directory for files; if you don't tell it which directory, it assumes ' . ' the directory you are in now. Therefore, `junk` and `./junk` are names for the same file. Despite their fundamental properties inside the kernel, directories sit in the file system as ordinary files. They can be read as ordinary files. But they can't be created or written as ordinary files - to preserve its sanity and the users' files, the kernel reserves to itself all control over the contents of directories. The time has come to look at the bytes in a directory:

```
$ od -cb . 00000000 4 \0 \0 \0 \0 \0 \0 \0 \0 \0 \0 \0 \0 \0 064 073 056 000 000
000 000 000 000 000 000 000 000 000 000 000 000 000 000 0000020 273 ( \0 \0 \0 \0 \0
\0 \0 \0 \0 \0 \0 \0 273 050 056 056 000 000 000 000 000 000 000 000 000
000 000 000 00000040 252 r e c i p e s \0 \0 \0 \0 \0 \0 \0 252 073 162 145
143 151 160 145 163 000 000 000 000 000 000 000 000 000 00000060 230 = j u n k
\0 \0 \0 \0 \0 \0 \0 \0 \0 \0 \0 230 075 152 165 156 153 000 000 000 000 000
000 000 000 000 000 000 000 000 00000100 $
```

See the filenames buried in there? The directory format is a combination of binary and textual data. A directory consists of 16-byte chunks, the last 14 bytes of which hold the filename, padded with ASCII NUL's (which have value 0) and the first two of which tell the system where the administrative information for the file resides - we'll come back to that. Every directory begins with the two entries ' . ' ("dot") and ' . . ' ("dot-dot").

```
$ cd $ cd recipes $ pwd /usr/you/recipes $ cd ..; pwd /usr/you $ cd ..; pwd /usr $ cd ..; pwd / $ cd ..; pwd / $
```

Home

Up one level

Up another level

Up another level

Up another level Can't go any higher

The directory / is called the root of the file system. Every file in the system is in the root directory or one of its subdirectories, and the root is its own parent directory. Exercise 2-2. Given the information in this section, you should be able to understand roughly how the ls command operates. Hint: cat .>foo; ls -f foo. 0

CHAPTER 2

Exercise 2-3. (Harder) How does the `pwd` command operate? 0 Exercise 2-4. `du` was written to monitor disc usage. Using it to find files in a directory hierarchy is at best a strange idiom, and perhaps inappropriate. As an alternative, look at the manual page for `find(1)`, and compare the two commands. In particular, compare the command `du -a : grep o. 0` with the corresponding invocation of `find`. Which runs faster? Is it better to build a new tool or use a side effect of an old one? 0

2.4 Permissions

Every file has a set of permissions associated with it, which determine who can do what with the file. If you're so organized that you keep your love letters on the system, perhaps hierarchically arranged in a directory, you probably don't want other people to be able to read them. You could therefore change the permissions on each letter to frustrate gossip (or only on some of the letters, to encourage it), or you might just change the permissions on the directory containing the letters, and thwart snoopers that way. But we must warn you: there is a special user on every UNIX system, called the super-user, who can read or modify any file on the system. The special login name `root` carries super-user privileges; it is used by system administrators when they do system maintenance. There is also a command called `su` that grants super-user status if you know the root password. Thus anyone who knows the super-user password can read your love letters, so don't keep sensitive material in the file system. If you need more privacy, you can change the data in a file so that even the super-user cannot read (or at least understand) it, using the `crypt` command (`crypt(1)`). Of course, even `crypt` isn't perfectly secure. A super-user can change the `crypt` command itself, and there are cryptographic attacks on the `crypt` algorithm. The former requires malfeasance and the latter takes hard work, however, so `crypt` is in practice fairly secure. In real life, most security

breaches are due to passwords that are given away or easily guessed. Occasionally, system administrative lapses make it possible for a malicious user to gain super-user permission. Security issues are discussed further in some of the papers cited in the bibliography at the end of this chapter. When you log in, you type a name and then verify that you are that person by typing a password. The name is your login identification, or login-id. But the system actually recognizes you by a number, called your user-id, or uid. In fact different login-id's may have the same uid, making them indistinguishable to the system, although that is relatively rare and perhaps undesirable for security reasons. Besides a uid, you are assigned a group identification, or group-id, which places you in a class of users. On many systems, all ordinary users (as opposed to those with login-id's like root) are placed in a single group called other, but your system may be different. The file system, and therefore the UNIX system in general, determines what you can do by the

CHAPTER 2

THE FILE SYSTEM 53

permissions granted to your uid and group-id. The file /etc/passwd is the password file; it contains all the login information about each user. You can discover your uid and group-id, as does the system, by looking up your name in /etc/passwd: `$ grep you /etc/passwd`
you:gkmbCTrJ04COM:604:1:Y.O.A.People:/usr/you: \$

The fields in the password file are separated by colons and are laid out like this (as seen in `passwd(5)`): login-id: encrypted-password: uid: group-id: miscellany: login-directory: shell The file is ordinary text, but the field definitions and separator are a convention agreed upon by the programs

that use the information in the file. The shell field is often empty, implying that you use the default shell, /bin/sh. The miscellany field may contain anything; often, it has your name and address or phone number. Note that your password appears here in the second field, but only in an encrypted form. Anybody can read the password file (you just did), so if your password itself were there, anyone would be able to use it to masquerade as you. When you give your password to login, it encrypts it and compares the result against the encrypted password in /etc/passwd. If they agree, it lets you log in. The mechanism works because the encryption algorithm has the property that it's easy to go from the clear form to the encrypted form, but very hard to go backwards. For example, if your password is ka-boom, it might be encrypted as gkmbCTrJ04COM, but given the latter, there's no easy way to get back to the original. The kernel decided that you should be allowed to read /etc/passwd by looking at the permissions associated with the file. There are three kinds of permissions for each file: read (i.e., examine its contents), write (i.e., change its contents), and execute (i.e., run it as a program). Furthermore, different permissions can apply to different people. As file owner, you have one set of read, write and execute permissions. Your "group" has a separate set. Every- one else has a third set. The -l option of ls prints the permissions information, among other things:

```
$ ls -l /etc/passwd -rw-r--r-- 1 root 5115 Aug 30 10:40 /etc/passwd $ ls -lg  
/etc/passwd -rw-r--r-- 1 adm 5115 Aug 30 10:40 /etc/passwd $
```

These two lines may be collectively interpreted as: /etc/passwd is owned by login-id root, group adm, is 5115 bytes long, was last modified on August 30 at 10:40 AM, and has one link (one name in the file system; we'll discuss links

CHAPTER 2

in the next section). Some versions of `ls` give both owner and group In one invocation. The string `-rw-r- -r- -` is how `ls` represents the permissions on the file. The first `--` indicates that it is an ordinary file. If it were a directory, there would be a `d` there. The next three characters encode the file owner's (based on uid) read, write and execute permissions. `rw-` means that root (the owner) may read or write, but not execute the file. An executable file would have an `x` instead of a dash. The next three characters (`r--`) encode group permissions, in this case that people in group `adm`, presumably the system administrators, can read the file but not write or execute it. The next three (also `r - -`) define the permissions for everyone else - the rest of the users on the system. On this machine, then, only root can change the login information for a user, but anybody may read the file to discover the information. A plausible alternative would be for group `adm` to also have write permission on `/etc/passwd`. The file `/etc/group` encodes group names and group-id's, and defines which users are in which groups. `/etc/passwd` identifies only your login group; the `newgrp` command changes your group permissions to another group. Anybody can say

```
$ ed /etc/passwd
```

and edit the password file, but only root can write back the changes. You might therefore wonder how you can change your password, since that involves editing the password file. The program to change passwords is called `passwd`; you will probably find it in `/bin`:

```
$ ls -l /bin/passwd -rwsr-xr-x 1 root $
```

8454 Jan 4 1983 /bin/passwd

(Note that /etc/passwd is the text file containing the login information, while /bin/passwd, in a different directory, is a file containing an executable program that lets you change the password information.) The permissions here state that anyone may execute the command, but only root can change the passwd command. But the s instead of an x in the execute field for the file owner states that, when the command is run, it is to be given the permissions corresponding to the file owner, in this case root. Because /bin/passwd is "set-uid" to root, any user can run the passwd command to edit the password file. The set-uid bit is a simple but elegant idea that solves a number of security problems. For example, the author of a game program can make the program set-uid to the owner, so that it can update a score file that is otherwise

t The set-uid bit is patented by Dennis Ritchie.

CHAPTER 2

THE FILE SYSTEM 55

protected from other users' access. But the set-uid concept is potentially dangerous. /bin/passwd has to be correct; if it were not, it could destroy system information under root's auspices. If it had the permissions -rwsrwxrwx, it could be overwritten by any user, who could therefore replace the file with a program that does anything. This is particularly serious for a set-uid program, because root has access permissions to every

file on the system. (Some UNIX systems turn the set-uid bit off whenever a file is modified, to reduce the danger of a security hole.) The set-uid bit is powerful, but used primarily for a few system programs such as `passwd`. Let's look at a more ordinary file. `$ ls -l /bin/who -rwxrwxr-x 1 root`

```
6348 Mar 29 1983 /bin/who
```

```
$
```

`who` is executable by everybody, and writable by root and the owner's group. What "executable" means is this: when you type `$ who`

to the shell, it looks in a set of directories, one of which is `/bin`, for a file named "who." If it finds such a file, and if the file has execute permission, the shell calls the kernel to run it. The kernel checks the permissions, and, if they are valid, runs the program. Note that a program is just a file with execute permission. In the next chapter we will show you programs that are just text files, but that can be executed as commands because they have execute permission set. Directory permissions operate a little differently, but the basic idea is the same.

```
$ ls -ld . drwxrwxr-x 3 you $
```

```
80 Sep 27 06:11 .
```

The -d option of ls asks it to tell you about the directory itself, rather than its contents, and the leading d in the output signifies that ' ' is indeed a directory. An r field means that you can read

the directory, so you can find out what files are in it with ls (or od, for that matter). A w means that you can create and delete files in this directory, because that requires modifying and therefore writing the directory file. Actually, you cannot simply write in a directory - even root is forbidden to do so.

\$ who >. .: cannot create \$

Try to overwrite '.' You can't

Instead there are system calls that create and remove files, and only through them is it possible to change the contents of a directory. The permissions idea,

56 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

however, still applies: the w fields tell who can use the system routines to modify the directory. Permission to remove a file is independent of the file itself. If you have write permission in a directory, you may remove files there, even files that are protected against writing. The rm command asks for confirmation before removing a protected file, however, to check that

you really want to do so - one of the rare occasions that a UNIX program double-checks your intentions. (The -f flag to rm forces it to remove files without question.) The x field in the permissions on a directory does not mean execution; it means "search." Execute permission on a directory determines whether the directory may be searched for a file. It is therefore possible to create a directory with mode - -x for other users, implying that users may access any file that they know about in that directory, but may not run ls on it or read it to see what files are there. Similarly, with directory permissions r - -, users can see (ls) but not use the contents of a directory. Some installations use this device to turn off /usr/games during busy hours. The chmod (change mode) command changes permissions on files. \$ chmod permissions filenames ...

The syntax of the permissions is clumsy, however. They can be specified in two ways, either as octal numbers or by symbolic description. The octal numbers are easier to use, although the symbolic descriptions are sometimes convenient because they can specify relative changes in the permissions. It would be nice if you could say

```
$ chmod rw-rw-rw- junk
```

Doesn't work this way!

rather than

\$ chmod 666 junk but you cannot. The octal modes are specified by adding together a 4 for read, 2 for write and 1 for execute permission. The three digits specify, as in ls, permissions for the owner, group and everyone else.

The symbolic codes are difficult to explain; you must look in `chmod(1)` for a proper description. For our purposes, it is sufficient to note that `+` turns a permission on and that `-` turns it off. For example

```
$ chmod +x command
```

allows everyone to execute command, and `$ chmod -w file`

turns off write permission for everyone, including the file's owner. Except for the usual disclaimer about super-users, only the owner of a file may change the permissions on a file, regardless of the permissions themselves. Even if some- body else allows you to write a file, the system will not allow you to change its

CHAPTER 2

THE FILE SYSTEM 57

```
permission bits. $ ls -ld /usr/mary drwxrwxrwx 5 mary 704 Sep 25 10:18
/usr/mary $ chmod 444 /usr/mary chmod: can't change /usr/mary $
```

If a directory is writable, however, people can remove files in it regardless of the permissions on the files themselves. If you want to make sure that you or your friends never delete files from a directory, remove write permission from it:

```
$ cd $ date >temp $ chmod -w . $ 1s -ld . dr-xr-xr-x 3 you $ rm temp rm:  
temp not removed $ chmod 775 . $ 1s -ld . drwxrwxr-x 3 you $ rm temp $
```

Make directory unwritable

80 Sep 27 11:48 .

Can't remove file Restore permission

80 Sep 27 11:48 .

Now you can

temp is now gone. Notice that changing the permissions on the directory didn't change its modification date. The modification date reflects changes to the file's contents, not its modes. The permissions and dates are not stored in the file itself, but in a system structure called an index node, or i-node, the subject of the next section. Exercise 2-5. Experiment with chmod. Try different simple modes, like 0 and 1. Be careful not to damage your login directory! 0

2.5 Inodes

A file has several components: a name, contents, and administrative information such as permissions and modification times. The administrative information is stored in the inode (over the years, the hyphen fell out of "inode"), along with essential system data such as how long it is, where on the disc the contents of the file are stored, and so on. There are three times in the inode: the time that the contents of the file were last modified (written); the time that the file was last used (read or executed); and the time that the inode itself was last changed, for example to set the permissions.

58 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

```
$ date Tue Sep 27 12:07:24 EDT 1983 $ date >junk $ ls -l junk -rw-rw-rw-  
1 you 29 Sep 27 12:07 junk $ ls -lu junk -rw-rw-rw- 1 you 29 Sep 27 06:11  
junk $ ls -lc junk -rw-rw-rw- 1 you 29 Sep 27 12:07 junk $
```

Changing the contents of a file does not affect its usage time, as reported by `ls -lu`, and changing the permissions affects only the inode change time, as reported by `ls -lc`. `$ chmod 444 junk $ ls -lu junk -r--r--r-- 1 you $ ls -lc
junk -r--r--r-- 1 you $ chmod 666 junk $`

29 Sep 27 06:11 junk

29 Sep 27 12:11 junk

The -t option to ls, which sorts the files according to time, by default that of last modification, can be combined with -c or -u to report the order in which inodes were changed or files were read:

```
$ ls recipes cookie pie $ ls -lut total 2 drwxrwxrwx 4 you -rw-rw-rw- 1 you $
```

64 Sep 27 12:11 recipes 29 Sep 27 06:11 junk

recipes is most recently used, because we just looked at its contents. It is important to understand inodes, not only to appreciate the options on ls, but because in a strong sense the inodes are the files. All the directory hierarchy does is provide convenient names for files. The system's internal name for a file is its i-number: the number of the inode holding the file's information. ls -li reports the i-number in decimal:

```
$ date >x $ ls -li 15768 junk 15274 recipes 15852 x $
```

It is the i-number that is stored in the first two bytes of a directory, before the

CHAPTER 2

THE FILE SYSTEM 59

name. `cd -d` will dump the data in decimal by byte pairs rather than octal by bytes and thus make the i-number visible. `$ od -c .`

```
0000000 4 \0 \0 \0 \0 \0
\0 \0 \0 \0 \0 \0 \0 \0 0000020 273 \0 \0 \0 \0 \0 \0 \0 \0 \0 \0 0000040
252 r e c i p e s \0 \0 \0 \0 \0 \0 \0 0000060 230 = j u n k \0 \0 \0 \0 \0 \0
\0 \0 \0 0000100 354 = x \0 \0 \0 \0 \0 \0 \0 \0 \0 \0 \0 \0 0000120 $ od -d
. 0000000 15156 00046 00000 00000 00000 00000 00000 00000 0000020
10427 11822 00000 00000 00000 00000 00000 00000 0000040 15274
25970 26979 25968 00115 00000 00000 00000 0000060 15768 30058
27502 00000 00000 00000 00000 00000 0000100 15852 00120 00000
00000 00000 00000 00000 00000 0000120 $
```

The first two bytes in each directory entry are the only connection between the name of a file and its contents. A filename in a directory is therefore called a link, because it links a name in the directory hierarchy to the inode, and hence to the data. The same i-number can appear in more than one directory. The `rm` command does not actually remove inodes; it removes directory entries or links. Only when the last link to a file disappears does the system remove the inode, and hence the file itself. If the i-number in a directory entry is zero, it means that the link has been removed, but not necessarily the contents of the file - there may still be a link somewhere else. You can verify that the i-number goes to zero by removing the file:

```
$ rm x $ od -d . 0000000 15156 00046 00000 00000 00000 00000 00000
00000 0000020 10427 11822 00000 00000 00000 00000 00000 00000
0000040 15274 25970 26979 25968 00115 00000 00000 00000 0000060
15768 30058 27502 00000 00000 00000 00000 00000 0000100 00000
00120 00000 00000 00000 00000 00000 00000 0000120 $
```

The next file created in this directory will go into the unused slot, although it will probably have a different i-number. The `ln` command makes a link to an existing file, with the syntax `$ ln old-file new-file`. The purpose of a link is to give two names to the same file, often so it can appear in two different directories. On many systems there is a link to `/bin/ed` called `/bin/e`, so that people can call the editor `e`. Two links to a

60 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

```
file point to the same inode, and hence have the same i-number: $ ls -li junk
linktojunk $ ls -li total 3 15768 -rw-rw-rw- 2 you 15768 -rw-rw-rw- 2 you
15274 drwxrwxrwx 4 you $
```

```
29 Sep 27 12:07 junk 29 Sep 27 12:07 linktojunk 64 Sep 27 09:34 recipes
```

The integer printed between the permissions and the owner is the number of links to the file. Because each link just points to the inode, each link is equally important - there is no difference between the first link and subsequent ones. (Notice that the total disc space computed by `ls` is wrong because of double counting.) When you change a file, access to the file by any of its names will reveal the changes, since all the links point to the same file.

```
$ echo x >junk $ ls -l total 3 -rw-rw-rw- 2 you 2 Sep 27 12:37 junk -rw-  
rw-rw- 2 you 2 Sep 27 12:37 linktojunk drwxrwxrwx 4 you 64 Sep 27  
09:34 recipes $ rm linktojunk $ ls -l total 2 -rw-rw-rw- 1 you 2 Sep 27  
12:37 junk drwxrwxrwx 4 you 64 Sep 27 09:34 recipes $
```

After linktojunk is removed the link count goes back to one. As we said before, rm'ing a file just breaks a link; the file remains until the last link is removed. In practice, of course, most files only have one link, but again we see a simple idea providing great flexibility. A word to the hasty: once the last link to a file is gone, the data is irretrievable. Deleted files go into the incinerator, rather than the waste basket, and there is no way to call them back from the ashes. (There is a faint hope of resurrection. Most large UNIX systems have a formal backup procedure that periodically copies changed files to some safe place like magnetic tape, from which they can be retrieved. For your own protection and peace of mind, you should know just how much backup is provided on your system. If there is none, watch out - some mishap to the discs could be a catastrophe.) Links to files are handy when two people wish to share a file, but sometimes you really want a separate copy - a different file with the same information. You might copy a document before making extensive changes to it, for example, so you can restore the original if you decide you don't like the changes. Making a link wouldn't help, because when the data changed, both

CHAPTER 2

THE FILE SYSTEM 61

```
links would reflect the change. cp makes copies of files: $ cp junk  
copyofjunk $ ls -li total 3 15850 -rw-rw-rw- 1 you 15768 -rw-rw-rw- 1  
you 15274 drwxrwxrwx 4 you $
```

2 Sep 27 13:13 copyofjunk 2 Sep 27 12:37 junk 64 Sep 27 09:34 recipes

The i-numbers of junk and copyof junk are different, because they are different files, even though they currently have the same contents. It's often a good idea to change the permissions on a backup copy so it's harder to remove it accidentally.

```
$ chmod -w copyofjunk Turn off write permission $ ls -li total 3 15850 -r--r--r-- 1 you 2 Sep 27 13:13 copyofjunk 15768 -rw-rw-rw- 1 you 2 Sep 27 12:37 junk 15274 drwxrwxrwx 4 you 64 Sep 27 09:34 recipes $ rm copyofjunk rm: copyofjunk 444 mode n No! It's precious $ date >junk $ ls -li total 3 15850 -r--r--r-- 1 you 2 Sep 27 13: 13 copyofjunk 15768 -rw-rw-rw- 1 you 29 Sep 27 13:16 junk 15274 drwxrwxrwx 4 you 64 Sep 27 09:34 recipes $ rm copyofjunk rm: copyofjunk 444 mode y Well, maybe not so precious $ ls -li total 2 15768 -rw-rw-rw- 1 you 29 Sep 27 13:16 junk 15274 drwxrwxrwx 4 you 64 Sep 27 09:34 recipes $
```

Changing the copy of a file doesn't change the original, and removing the copy has no effect on the original. Notice that because copyof junk had write permission turned off, rm asked for confirmation before removing the file. There is one more common command for manipulating files: mv moves or renames files, simply by rearranging the links. Its syntax is the same as cp and ln:

62 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

```
$ rnv junk sarneo1djunk $ ls -li total 2 15274 drwxrwxrwx 4 you 15768 -  
rw-rw-rw- 1 you $
```

```
64 Sep 27 09:34 recipes 29 Sep 27 13:16 sameoldjunk
```

sameoldjunk is the same file as our old junk, right down to the i-number

only its name - the directory entry associated with inode 15768 - has been changed. We have been doing all this file shuffling in one directory, but it also works across directories. In is often used to put links with the same name in several directories, such as when several people are working on one program or document. mv can move a file or directory from one directory to another. In fact, these are common enough idioms that mv and cp have special syntax for them: `$ rnv (or cp) file1 file2 ...` directory moves (or copies) one or more files to the directory which is the last argument. The links or copies are made with the same filenames. For example, if you wanted to try your hand at beefing up the editor, you might begin by saying

```
$ cp /usr/src/crnd/ed.c .
```

to get your own copy of the source to play with. If you were going to work on the shell, which is in a number of different source files, you would say

```
$ rnkdir sh $ cp /usr/src/crnd/sh/* sh
```

and cp would duplicate all of the shell's source files in your subdirectory sh (assuming no subdirectory structure in /usr/src/cmd/sh - cp is not very clever). On some systems, ln also accepts multiple file arguments, again with a directory as the last argument. And on some systems, mv, cp and ln are themselves links to a single file that examines its name to see what service to perform. Exercise 2-6. Why does ls -l report 4 links to recipes? Hint: try

```
$ ls -ld /usr/you
```

Why is this useful information? 0 Exercise 2-7. What is the difference between

```
$ mv junk junk1
```

and

```
$ cp junk junk1 $ rm junk
```

Hint: make a link to junk, then try it. 0

CHAPTER 2

Exercise 2-8. `cp` doesn't copy subdirectories, it just copies files at the first level of a hierarchy. What does it do if one of the argument files is a directory? Is this kind or even sensible? Discuss the relative merits of three possibilities: an option to `cp` to descend directories, a separate command `rcp` (recursive copy) to do the job, or just having `cp` copy a directory recursively when it finds one. See Chapter 7 for help on providing this facility. What other programs would profit from the ability to traverse the directory tree? 0

206 The directory hierarchy In Chapter 1, we looked at the file system hierarchy rather informally, starting from `/usr/you`. We're now going to investigate it in a more orderly way, starting from the top of the tree, the root. The top directory is `/`.

```
$ ls / bin boot dev etc lib tmp unix usr $
```

`/unix` IS the program for the UNIX kernel itself: when the system starts, `/unix` is read from disc into memory and started. Actually, the process occurs in two steps: first the file `/boot` is read; it then reads in `/unix`. More information about this "bootstrap" process may be found in `boot(8)`. The rest of the files in `/`, at least here, are directories, each a somewhat self-contained section of the total file system. In the following brief tour of the hierarchy, play along with the text: explore a bit in the directories mentioned. The more familiar you are with the layout of the file system, the more effectively you will be able to use it. Table 2.1 suggests good places to look, although some of the names are system dependent. `/bin` (binaries) we have seen before: it is the directory where the basic programs such as `who` and `ed` reside. `/dev` (devices) we will discuss in the next section. `jete` (et

cetera) we have also seen before. It contains various administrative files such as the password file and some system programs such as `/etc/getty`, which initializes a terminal connection for `/bin/login`. `/etc/re` is a file of shell commands that is executed after the system is bootstrapped. `/etc/group` lists the members of each group. `/lib` (library) contains primarily parts of the C compiler, such as `/lib/epp`, the C preprocessor, and `/lib/libe.a`, the C subroutine library. `/tmp` (temporaries) is a repository for short-lived files created during the

64 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

Table 2.1: Interesting Directories (see also `hier(7)`)

root of the file system	essential programs in executable form ("binaries")	device files	system
miscellany	login message of the day	password file	essential libraries, etc.
temporary files;	cleaned when system is restarted	executable form of the	operating system
user file	system administration:	accounting info.,	etc.
user binaries:	<code>troff</code> , etc.	dictionary (words)	and support for <code>spell(1)</code>
game programs	header files for C programs, e.g. <code>math.h</code>	system header	files for C programs, e. g. <code>inode.h</code>
libraries for C, FORTRAN, etc.	on-line	manual	manual pages for section 1 of manual
hardware diagnostics,	bootstrap programs, etc.	community service	messages
public oddments:	see	<code>ascii(7)</code> and <code>eqnchar(7)</code>	source code for utilities and libraries
source for	commands in <code>/bin</code> and <code>/usr/bin</code>	source code for subroutine	libraries
working	directories for communications	programs	line printer
temporary directory	mail in <code>-boxes</code>	working directory for the	<code>uucp</code> programs
source for the	operating system	kernel	alternate temporary directory (little used)
your	login directory	your personal	programs

```
/ /bin /dev /etc /etc/motd /etc/passwd /lib /tmp /unix /usr /usr/adm /usr/bin  
/usr/dict /usr/games /usr/include /usr/include/sys /usr/lib /usr/man  
/usr/man/man1 /usr/mdec /usr/news /usr/pub /usr/src /usr/src/cmd  
/usr/src/lib /usr/spool /usr/spool/lpd /usr/spool/mail /usr/spool/uucp /usr/sys  
/usr/tmp /usr/you /usr/you/bin
```

execution of a program. When you start up the editor `ed`, for example, it creates a file with a name like `/tmp/ eO 0512` to hold its copy of the file you are editing, rather than working with the original file. It could, of course, create the file in your current directory, but there are advantages to placing it in `/tmp`: although it is unlikely, you might already have a file called `e00512` in your directory; `/tmp` is cleaned up automatically when the system starts, so your directory doesn't get an unwanted file if the system crashes; and often `/tmp` is arranged on the disc for fast access.

CHAPTER 2

THE FILE SYSTEM 65

There is a problem, of course, when several programs create files in `/tmp` at once: they might interfere with each other's files. That is why `ed`'s temporary file has a peculiar name: it is constructed in such a way as to guarantee that no other program will choose the same name for its temporary file. In Chapters 5 and 6 we will see ways to do this. `/usr` is called the "user file system," although it may have little to do with the actual users of the system. On our machine, our login directories are `/usr /bwk` and `/usr frob`, but on your machine the `/usr` part might be different, as explained in Chapter 1. Whether or not your personal files are in a subdirectory of `/usr`, there are a number of things you are likely to find there (although local customs vary in this regard , too). Just as in `/`, there are

directories called `/usr/bin`, `/usr/lib` and `/usr/tmp`. These directories have functions similar to their namesakes in `/`, but contain programs less critical to the system. For example, `nc` is usually in `/usr/bin` rather than `/bin`, and the FORTRAN compiler libraries live in `/usr/lib`. Of course, just what is deemed "critical" varies from system to system. Some systems, such as the distributed 7th Edition, have all the programs in `/bin` and do away with `/usr/bin` altogether; others split `/usr/bin` into two directories according to frequency of use. Other directories in `/usr` are `/usr/fadm`, containing accounting information and `/usr/dict`, which holds a modest dictionary (see `spell(1)`). The on-line manual is kept in `/usr/man` - see `/usr/man/man1/spell.1`, for example. If your system has source code on-line, you will probably find it in `/usr/src`. It is worth spending a little time exploring the file system, especially `/usr`, to develop a feeling for how the file system is organized and where you might expect to find things.

2.7 Devices

We skipped over `/dev` in our tour, because the files there provide a nice review of files in general. As you might guess from the n

me, `/dev` contains device files. One of the prettiest ideas in the UNIX system is the way it deals with peripherals - discs, tape drives, line printers, terminals, etc. Rather than having special system routines to, for example, read magnetic tape, there is a file called `/dev/mto` (again, local customs vary). Inside the kernel, references to that file are converted into hardware commands to access the tape, so if a program reads `/dev/mto`, the contents of a tape mounted on the drive are returned. For example, `$ cp /dev/rmt0 junk` copies the contents of the tape to a file called `junk`. `cp` has no idea there is anything special about `/dev/mto`; it is just a file - a sequence of bytes.

CHAPTER 2

The device files are something of a zoo, each creature a little different, but the basic ideas of the file system apply to each. Here is a significantly shortened list of our / dev:

```
$ ls -l /dev crw--w--w- 1 root o , 0 Sep 27 23:09 console crw-r--r-- 1 root 3, 1 Sep 27 14:37 kmem crw-r--r-- 1 root 3, 0 May 6 1981 mem brw-rw-rw- 1 root 1 , 64 Aug 24 17:41 mtO crw-rw-rw- 1 root 3, 2 Sep 28 02:03 null crw-rw-rw- 1 root 4, 64 Sep 9 15:42 rmtO brw-r----- 1 root 2, 0 Sep 8 08:07 rpOO brw-r----- 1 root 2, 1 Sep 27 23:09 rp01 crw-r----- 1 root 13, 0 Apr 12 1983 rrpOO crw-r----- 1 root 13, 1 Jul 28 15:18 rrp01 crw-rw-rw- 1 root 2, 0 Jul 5 08:04 tty crw--w--w- 1 you 1 , 0 Sep 28 02:38 ttyO crw--w--w- 1 root 1 , 1 Sep 27 23:09 tty1 crw--w--w- 1 root 1 , 2 Sep 27 17:33 tty2 crw--w--w- 1 root 1 , 3 Sep 27 18:48 tty3 $
```

The first things to notice are that instead of a byte count there is a pair of small integers, and that the first character of the mode is always a 'b' or a 'c'. This is how ls prints the information from an inode that specifies a device rather than a regular file. The inode of a regular file contains a list of disc blocks that store the file's contents. For a device file, the inode instead contains the internal name for the device, which consists of its type - character (c) or block (b) - and a pair of numbers, called the major and minor device numbers. Discs and tapes are block devices; everything else - terminals, printers, phone lines, etc. - is a character device. The major number encodes the type of device, while the minor number distinguishes different instances of the device. For example, /dev/ttyO and /dev/tty1 are two ports on the same terminal controller, so they have the same major device number but different minor numbers. Disc files are usually named after the particular hardware variant they represent. /dev/rpOO and /dev/rp01 are named after

the DEC RP06 disc drive attached to the system. There is just one drive, divided logically into two file systems. If there were a second drive, its associated files would be named /dev/rp10 and /dev/rp11. The first digit specifies the physical drive, and the second which portion of the drive. You might wonder why there are several disc device files, instead of just one. For historical reasons and for ease of maintenance, the file system is divided into smaller subsystems. The files in a subsystem are accessible through a directory in the main system. The program jete/mount reports the correspondence between device files and directories:

CHAPTER 2

THE FILE SYSTEM 67

```
$ /etc/mount rp01 on /usr $
```

In our case, the root system occupies /dev/rp00 (although this isn't reported by /etc/mount) while the user file system - the files in /usr and its sub-directories - reside on /dev/rp01. The root file system has to be present for the system to execute. /bin, /dev and /etc are always kept on the root system, because when the system starts only files in the root system are accessible, and some files such as /bin/sh are needed to run at all. During the bootstrap operation, all the file systems are checked for self-consistency (see iCheck(8) or fsck(8)), and attached to the root system. This attachment operation is called mounting, the software equivalent of mounting a new disc pack in a drive; it can normally be done only by the super-user. After /dev/rp01 has been mounted as /usr, the files in the user file system are accessible exactly as if they were part of the root system. For the average user, the details of which file subsystem is mounted where are of little interest, but there are a couple of relevant points. First, because the

subsystems may be mounted and dismounted, it is illegal to make a link to a file in another subsystem. For example, it is impossible to link programs in /bin to convenient names in private bin directories, because /usr is in a different file subsystem from /bin:

```
$ ln /bin/mail /usr/you/bin/m In: Cross-device link $
```

There would also be a problem because inode numbers are not unique in different file systems. Second, each subsystem has fixed upper limits on size (number of blocks available for files) and inodes. If a subsystem fills up, it will be impossible to enlarge files in that subsystem until some space is reclaimed. The df (disc free space) command reports the available space on the mounted file subsystems:

```
$ df /dev/rp00 1989 /dev/rp01 21257 $
```

/usr has 21257 free blocks. Whether this is ample space or a crisis depends on how the system is used; some installations need more file space headroom than others. By the way, of all the commands, df probably has the widest variation in output format. Your df output may look quite different. Let's turn now to some more generally useful things. When you log in, you get a terminal line and therefore a file in /dev through which the characters

68 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

you type and receive are sent. The `tty` command tells you which terminal you are using:

```
$ who am i you ttyO Sep 28 01:02 $ tty /dev/ttyO $ ls -l /dev/ttyO crw-rw-rw- 1 you 1, 12 Sep 28 02:40 /dev/ttyO $ date >/dev/ttyO Wed Sep 28 02:40:51 EDT 1983 $
```

Notice that you own the device, and that only you are permitted to read it. In other words, no one else can directly read the characters you are typing. Any one may write on your terminal, however. To prevent this, you could `chmod` the device, thereby preventing people from using write to contact you, or you could just use `mesg`.

```
$ mesg n $ ls -l /dev/ttyO crw-r----- 1 you $ mesg y $
```

Turn off messages

```
1, 12 Sep 28 02:41 /dev/ttyO Restore
```

It is often useful to be able to refer by name to the terminal you are using, but it's inconvenient to determine which one it is. The device `/dev/tty` is a synonym for your login terminal, whatever terminal you are actually using.

```
$ date >/dev/tty Wed Sep 28 02:42:23 EDT 1983 $
```


/dev/tty is particularly useful when a program needs to interact with a user even though its standard input and output are connected to files rather than the terminal. crypt is one program that uses /dev/tty. The "clear text" comes from the standard input, and the encrypted data goes to the standard output, so crypt reads the encryption key from /dev/tty:

```
$ crypt <cleartext >cryptedtext Enter key: Type encryption key $
```

The use of /dev/tty isn't explicit in this example, but it is there. If crypt read the key from the standard input, it would read the first line of the clear text. So instead crypt opens /dev/tty, turns off automatic character echoing so your encryption key doesn't appear on the screen, and reads the key. In Chapters 5 and 6 we will come across several other uses of /dev/tty. Occasionally you want to run a program but don't care what output is produced. For example, you may have already seen today's news, and don't want

CHAPTER 2

THE FILE SYSTEM 69

to read it again. Redirecting news to the file /dev/null causes its output to be thrown away:

```
$ news >/dev/null $
```

Data written to `/dev/null` is discarded without comment, while programs that read from `/dev/null` get end-of-file immediately, because reads from `/dev/null` always return zero bytes. One common use of `/dev/null` is to throwaway regular output so that diagnostic messages are visible. For example, the `time` command (`time(1)`) reports the CPU usage of a program. The information is printed on the standard error, so you can time commands that generate copious output by sending the standard output to `/dev/null`:

```
$ ls -l /usr/dict/words -r--r--r-- 1 bin 196513 Jan 20 1979 /usr/dict/words $  
time grep e /usr/dict/words >/dev/null
```

```
real 13.0 user 9.0 sys 2.7 $ time egrep e /usr/dict/words >/dev/null
```

```
real user sys $
```

```
8.0 3.9 2.8
```

The numbers in the output of `time` are elapsed clock time, CPU time spent in the program and CPU time spent in the kernel while the program was running. `egrep` is a high-powered variant of `grep` that we will discuss in Chapter 4; it's about twice as fast as `grep` when searching through large files. If output from `grep` and `egrep` had not been sent to `/dev/null` or a real file, we would have had to wait for hundreds of thousands of characters to appear on the terminal before finding out the timing information we were after. Exercise 2-9. Find out about the other files in `/dev` by reading Section 4 of the manual. What is the difference between `/dev/mem` and `/dev/rmem`? Comment on the potential advantages of having subdirectories in `/dev` for

discs, tapes, etc. D Exercise 2-10. Tapes written on non-UNIX systems often have different block sizes, such as 800 bytes - ten 80-character card images - but the tape device `/dev/mt0` expects 512-byte blocks. Look up the `dd` command (`dd(1)`) to see how to read such a tape. D Exercise 2-11. Why isn't `/dev/tty` just a link to your login terminal? What would happen if it were mode `rw--w--w-` like your login terminal? D Exercise 2-12. How does `writtee(1)` work? Hint: see `utmp(5)`. D Exercise 2-13. How can you tell if a user has been active at the terminal recently? D

70 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 2

History and bibliographic notes The file system forms one part of the discussion in "UNIX implementation," by Ken Thompson (BSTJ, July, 1978). A paper by Dennis Ritchie, entitled "The evolution of the UNIX time-sharing system" (Symposium on Language Design and Programming Methodology, Sydney, Australia, Sept. 1979) is an fascinating description of how the file system was designed and implemented on the original PDP-7 UNIX system, and how it grew into its present form. The UNIX file system adapts some ideas from the MULTICS file system. The MULTICS System: An Examination of its Structure, by E. I. Organick (MIT Press, 1972) provides a comprehensive treatment of MULTICS. "Password security: a case history," by Bob Morris and Ken Thompson, is an entertaining comparison of password mechanisms on a variety of systems; it can be found in Volume 2B of the UNIX Programmer's Manual. In the same volume, the paper "On the security of UNIX," by Dennis Ritchie, explains how the security of a system depends more on the care taken with its administration than with the details of programs like `crypt`.

CHAPTER 3:

SIN THE SHELL

The shell - the program that interprets your requests to run programs - is the most important program for most UNIX users; with the possible exception of your favorite text editor, you will spend more time working with the shell than any other program. In this chapter and in Chapter 5, we will spend a fair amount of time on the shell's capabilities. The main point we want to make is that you can accomplish a lot without much hard work, and certainly without resorting to programming in a conventional language like C, if you know how to use the shell. We have divided our coverage of the shell into two chapters. This chapter goes one step beyond the necessities covered in Chapter 1 to some fancier but commonly used shell features, such as metacharacters, quoting, creating new commands, passing arguments to them, the use of shell variables, and some elementary control flow. These are topics you should know for your own use of the shell. The material in Chapter 5 is heavier going - it is intended for writing serious shell programs, ones that are bullet-proofed for use by others. The division between the two chapters is somewhat arbitrary, of course, so both should be read eventually.

3.1 Command line structure To proceed, we need a slightly better understanding of just what a command is, and how it is interpreted by the shell. This section is a more formal coverage, with some new information, of the shell basics introduced in the first chapter. The simplest command is a single word, usually naming a file for execution (later we will see some other types of commands):

```
$ who you jpl $
```

Execute the file /bin/who

tty2 tty4

Sep 28 07:51 Sep 28 08:32

A command usually ends with a newline, but a semicolon is also a command terminator:

71

72 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

\$ date; Wed Sep \$ date; Wed Sep you jpl \$

28 09:07:15 EDT 1983 who 28 09:07:23 EDT 1983 tty2 Sep 28 07:51 tty4
Sep 28 08:32

Although semicolons can be used to terminate commands, as usual nothing happens until you type RETURN. Notice that the shell only prints one prompt after multiple commands, but except for the prompt,

```
$ date; who
```

is identical to typing the two commands on different lines. In particular, who doesn't run until date has finished. Try sending the output of "date; who" through a pipe:

```
$ date; who : we Wed Sep 28 09:08:48 EDT 1983 2 10 60
```

```
$
```

This might not be what you expected, because only the output of who goes to wc. Connecting who and wc with a pipe forms a single command, called a pipeline, that runs after date. The precedence of : is higher than that of ';' as the shell parses your command line. Parentheses can be used to group commands: \$ (date; who) Wed Sep 28 09:11:09 EDT 1983 you tty2 Sep 28 07:51 jpl tty4 Sep 28 08:32 \$ (date; who) I we 3 16 89

```
$
```

The outputs of date and who are concatenated into a single stream that can be sent down a pipe. Data flowing through a pipe can be tapped and placed

in a file (but not another pipe) with the tee command, which is not part of the shell, but is nonetheless handy for manipulating pipes. One use is to save intermediate out- put in a file:

CHAPTER 3

USING THE SHELL 73

```
$ (date; who) : tee save : we 3 16 89 $ cat save Wed Sep 28 09:13:22 EDT
1983 you tty2 Sep 28 07:51 jpl tty4 Sep 28 08:32 $ we <save
```

Output from we

3

16

89

\$

tee copies its input to the named file or files, as well as to its output, so wc receives the same data as if tee weren't in the pipeline. Another command terminator is the ampersand &. It's exactly like the semicolon or newline, except that it tells the shell not to wait for the command to complete. Typically, & is used to run a long-running command "in the background" while you continue to type interactive commands:

```
$ long-running-command & 5273 $
```

Process-id of long-running-command Prompt appears immediately

Given the ability to group commands, there are some more interesting uses of background processes. The command sleep waits the specified number of seconds before exiting: \$ sleep 5 \$ \$ (sleep 5; date) & date 5278 Wed Sep 28 09:18:20 EDT 1983 \$ Wed Sep 28 09:18:25 EDT 1983

Five seconds pass before prompt

Output from second date Prompt appears, then date 5 sec. later

The background process starts but immediately sleeps; meanwhile, the second date command prints the current time and the shell prompts for a new command. Five seconds later, the sleep exits and the first date prints the new time. It's hard to represent the passage of time on paper, so you should try this example. (Depending on how busy your machine is and other such details, the difference between the two times might not be

exactly five seconds.) This is an easy way to run a command in the future; consider

```
$ (sleep 300; echo Tea is ready) & 5291 $
```

Tea will be ready in 5 minutes

as a handy reminder mechanism. (A `ctl-g` in the string to be echoed will ring the terminal's bell when it's printed.) The parentheses are needed in these examples, since the precedence of `&` is higher than that of `'`. The `&` terminator applies to commands, and since pipelines are commands you don't need parentheses to run pipelines in the background:

74 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

```
$ pr file : lpr &
```

arranges to print the file on the line printer without making you wait for the command to finish. Parenthesizing the pipeline has the same effect, but requires more typing:

```
$ (pr file | lpr) &
```

Same as last example

Most programs accept arguments on the command line, such as file (an argument to pr) in the above example. Arguments are words, separated by blanks and tabs, that typically name files to be processed by the command, but they are strings that may be interpreted any way the program sees fit. For example, pr accepts names of files to print, echo echoes its arguments without interpretation, and grep's first argument specifies a text pattern to search for. And, of course, most programs also have options, indicated by arguments beginning with a minus sign. The various special characters interpreted by the shell, such as <, >, ;, ; and &, are not arguments to the programs the shell runs. They instead control how the shell runs them. For example,

```
$ echo Hello >junk
```

tells the shell to run echo with the single argument Hello, and place the output in the file junk. The string > junk is not an argument to echo; it is interpreted by the shell and never seen by echo. In fact, it need not be the last string in the command: \$ >junk echo Hello

is identical, but less obvious. Exercise 3-1. What are the differences among the following three commands?

```
$ cat file / pr $ pr <file $ pr file
```

(Over the years the redirection operator < has lost some ground to pipes; people seem to find "cat file :" more natural than "<file".) 0

3.2 Metacharacters

The shell recognizes a number of other characters as special; the most commonly used is the asterisk * which tells the shell to search the directory for filenames in which any string of characters occurs in the position of the *. For example,

```
$ echo '*'
```

is a poor facsimile of 1 s. Something we didn't mention in Chapter 1 is that the filename-matching characters do not look at filenames beginning with a

CHAPTER 3

USING THE SHELL 75

dot, to avoid problems with the names '.' and '..' that are in every directory. The rule is: the filename-matching characters only match filenames beginning with a period if the period is explicitly supplied in the

pattern. As usual, a judicious echo or two will clarify what happens: \$ Is .profile junk temp \$ echo * junk temp \$ echo .* . . . profile \$

Characters like * that have special properties are known as metacharacters. There are a lot of them: Table 3.1 is the complete list, although a few of them won't be discussed until Chapter 5. Given the number of shell metacharacters, there has to be some way to say to the shell, "Leave it alone." The easiest and best way to protect special characters from being interpreted is to enclose them in single quote characters:

```
$ echo '***' ***
```

```
$
```

It's also possible to use the double quotes "...", but the shell actually peeks inside these quotes to look for \$, "...

, and \, so don't use "... If unless you intend some processing of the quoted string. A third possibility is to put a backslash \ in front of each character that you want to protect from the shell, as in

```
$ echo \*\*\*
```

Although \ * \ " * \ * isn't much like English, the shell terminology for it is still a word, which is any single string the shell accepts as a unit, including blanks if they are quoted. Quotes of one kind protect quotes of the other kind:

```
$ echo "Don't do that!" Don't do that! $
```

and they don't have to surround the whole argument:

```
$ echo x'*'y x*y $ echo '*A?' *A? $
```

76 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

```
> »
```

```
<
```

```
< <sfr
```

```
*
```

```
? [ ccc ]
```

&

(...) {...} \$ 1 , \$ 2 etc. \$var \$ { var }

\

, ,

II II

var=value PI && P2 I I PI I I P2

Table 3.1: Shell Metacharacters
prog > file direct standard output to file
prog >> file append standard output to file
prog <file take standard input from file
PI :P2 connect standard output of PI to standard input of P2
here document: standard input follows, up to next str on a line by itself
match any string of zero or more characters in filenames
match any single character in filenames
match any single character from ccc in filenames;
ranges like 0 - 9 or a - z are legal
command terminator: PI ;P2 does P b then P2
like ; but doesn't wait for P I to finish
run command(s) in ...; output replaces '...' run command(s) in ... in a sub-shell
run command(s) in ... in current shell (rarely used)
\$ 0... \$9 replaced by arguments to shell
file value of shell variable var value of var;
avoids confusion when concatenated with text;
see also Table 5.3
\c take character c literally, \newline discarded
take ... literally take ... literally after \$, \...' and \ interpreted if # starts word, rest

of line is a comment (not in 7th Ed.) assign to variable var run PI; if successful, run P 2 run PI; if unsuccessful, run P 2

In this last example, because the quotes are discarded after they've done their job, echo sees a single argument containing no quotes. Quoted strings can contain newlines: `$ echo 'hello > world' hello world $`

The string '>' is a secondary prompt printed by the shell when it expects you to type more input to complete a command. In this example the quote on the first line has to be balanced with another. The secondary prompt string is stored in the shell variable PS2, and can be modified to taste. In all of these examples, the quoting of a metacharacter prevents the shell from trying to interpret it. The command

CHAPTER 3

USING THE SHELL 77

```
$ echo x*y
```

echoes all the filenames beginning x and ending y. As always, echo knows nothing about files or shell metacharacters; the interpretation of *, if any, is supplied by the shell. What happens if no files match the pattern? The shell, rather than complaining (as it did in early versions), passes the string on as though it had been quoted. It's usually a bad idea to depend on this behavior, but it can be exploited to learn of the existence of files matching a

pattern: \$ Is x*y x*y not found \$ >xyzzzy \$ Is x*y xyzzzy \$ Is 'x*y' x*y not found \$

Message from Is: no such files exist Create xyzzzy

File xyzzzy matches x*y

Is doesn't interpret the *

A backslash at the end of a line causes the line to be continued; this is the way to present a very long line to the shell.

```
$ echo abc\ > def\ > ghi abcdefghi $
```

Notice that the newline is discarded when preceded by backslash, but is retained when it appears in quotes. The metacharacter # is almost universally used for shell comments; if a shell word begins with #, the rest of the line is ignored: \$ echo hello # there hello \$ echo hello#there hello#there \$

The # was not part of the original 7th Edition, but it has been adopted very widely, and we will use it in the rest of the book. Exercise 3-2. Explain the output produced by

\$ 1s .*

0

A digression on echo Even though it isn't explicitly asked for, a final newline is provided by echo. A sensible and perhaps cleaner design for echo would be to print only

78 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

what is requested. This would make it easy to issue prompts from the shell:

\$ pure-echo Enter a command: Enter a command:\$

No trailing newline

but has the disadvantage that the most common case - providing a newline - is not the default and takes extra typing:

```
$ pure-echo 'Hello! > '
```

```
Hello! $
```

Since a command should by default execute its most commonly used function, the real `echo` appends the final newline automatically. But what if it isn't desired? The 7th Edition `echo` has a single option, `-n`, to suppress the last newline:

```
$ echo -n Enter a command: Enter a command:$ $ echo -
```

Prompt on same line

Only `-n` is special

```
$
```

The only tricky case is echoing `-n` followed by a newline:

```
$ echo -n '-n'
```

> '

-n \$

It's ugly, but it works, and this is a rare situation anyway. A different approach, taken in System V, is for `echo` to interpret C-like backslash sequences, such as `\b` for backspace and `\c` (which isn't actually in the C language) to suppress the last newline:

```
$ echo 'Enter a command:\c' Enter a command:$
```

System V version

Although this mechanism avoids confusion about echoing a minus sign, it has other problems. `echo` is often used as a diagnostic aid, and backslashes are interpreted by so many programs that having `echo` look at them too just adds to the confusion. Still, both designs of `echo` have good and bad points. We shall use the 7th Edition version (`-n`), so if your local `echo` obeys a different convention, a couple of our programs will need minor revision. Another question of philosophy is what `echo` should do if given no arguments - specifically, should it print a blank line or nothing at all? All the current `echo` implementations we know print a blank line, but past versions didn't, and there were once great debates on the subject. Doug McIlroy imparted the right feelings of mysticism in his discussion of the topic:

CHAPTER 3

USING THE SHELL

79

The UNIX and the Echo There dwelt in the land of New Jersey the UNIX, a fair maid whom savants traveled far to admire. Dazzled by her purity, all sought to espouse her, one for her virginal grace, another for her polished civility, yet another for her agility in performing exacting tasks seldom accomplished even in much richer lands. So large of heart and accommodating of nature was she that the UNIX adopted all but the most insufferably rich of her suitors. Soon many offspring grew and prospered and spread to the ends of the earth. Nature herself smiled and answered to the UNIX more eagerly than to other mortal beings. Humbler folk, who knew little of more courtly manners, delighted in her echo, so precise and crystal clear they scarce believed she could be answered by the same rocks and woods that so garbled their own shouts into the wilderness. And the compliant UNIX obliged with perfect echoes of whatever she was asked. When one impatient swain asked the UNIX, 'Echo nothing,' the UNIX obligingly opened her mouth, echoed nothing, and closed it again. 'Whatever do you mean,' the youth demanded, 'opening your mouth like that? Henceforth never open your mouth when you are supposed to echo nothing!' And the UNIX obliged. 'But I want a perfect performance, even when you echo nothing,' pleaded a sensitive youth, 'and no perfect echoes can come from a closed mouth.' Not wishing to offend either one, the UNIX agreed to say different nothings for the impatient youth and for the sensitive youth. She called the sensitive nothing '\n.' Yet now when she said '\n,' she was really not saying nothing so she had to open her mouth twice, once to say '\n,' and once to say nothing, and so she did not please the sensitive youth, who said forthwith, 'The \n sounds like a perfect nothing to me, but the second one ruins it. I want you to take back one of them.' So the UNIX, who could not abide offending, agreed to undo some echoes, and called that '\c.' Now the sensitive youth could hear a perfect echo of nothing by asking

for '\n' and '\c' together. But they say that he died of a surfeit of notation before he ever heard one.

Exercise 3-3. Predict what each of the following grep commands will do, then verify your understanding.

```
grep \$ grep \ grep \$ grep \\\ grep \\\$ grep \"$\" grep '$' grep '$' grep '$'  
grep \"$\"
```

A file containing these commands themselves makes a good test case if you want to experiment. 0 Exercise 3-4. How do you tell grep to search for a pattern beginning with a '-'? Why doesn't quoting the argument help? Hint: investigate the -e option. 0 Exercise 3-5. Consider

```
$ echo */*
```

Does this produce all names in all directories? In what order do the names appear? 0 Exercise 3-6. (Trick question) How do you get a / into a filename (i.e., a / that doesn't separate components of the path)? 0 Exercise 3-7. What happens with

80 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

```
$ cat x y >y
```

and with

```
$ cat x »x
```

Think before rushing off to try them. 0 Exercise 3-8. If you type

```
$ rm *
```

why can't rm warn you that you're about to delete all your files? 0

3.3 Creating new commands It's now time to move on to something that we promised in Chapter 1 - how to create new commands out of old ones.

Given a sequence of commands that is to be repeated more than a few times, it would be convenient to make it into a "new" command with its own name, so you can use it like a regular command. To be specific, suppose you intend to count users frequently with the pipeline

```
$ who : we -1
```

that was mentioned in Chapter 1, and you want to make a new program `nu` to do that. The first step is to create an ordinary file that contains `'who ; we -1'`. You can use a favorite editor, or you can get creative:

```
$ echo 'who: we -1' >nu
```

(Without the quotes, what would appear in `nu`?) As we said in Chapter 1, the shell is a program just like an editor or `who` or `we`; its name is `sh`. And since it's a program, you can run it and redirect its input. So run the shell with its input coming from the file `nu` instead of the terminal:

```
$ who you tty2 Sep 28 07:51 rhh tty4 Sep 28 10:02 moh tty5 Sep 28 09:38  
ava tty6 Sep 28 10:17 $ cat nu who I we -1 I $ sh <nu 4 $
```

The output is the same as it would have been if you had typed `who ; we -1` at the terminal. Again like most other programs, the shell takes its input from a file if one

CHAPTER 3

USING THE SHELL 81

is named as an argument; you could have written `$ sh nu`

for the same result. But it's a nuisance to have to type "sh" in either case: it's longer, and it creates a distinction between programs written in, say, C, and ones written by connecting programs with the shell. Therefore, if a file is executable and if it contains text, then the shell assumes it to be a file of shell commands. Such a file is called a shell file. All you have to do is to make nu executable, once:

```
$ chmod +x nu
```

and thereafter you can invoke it with \$ nu

From now on, users of nu cannot tell, just by running it, that you implemented it in this easy way. The way the shell actually runs nu is to create a new shell process exactly as if you had typed

```
$ sh nu
```

This child shell is called a sub-shell - a shell process invoked by your current shell. sh nu is not the same as sh <nu, because its standard input is still connected to the terminal. As it stands, nu works only if it's in your current directory (provided, of course, that the current directory is in your PATH, which we will assume from now on). To make nu part of your repertoire regardless of what directory you're in, move it to your private bin directory, and add /usr/you/bin to your search path: \$ pwd /usr/you \$ mkdir bin Make a bin if you haven't already \$ echo \$PATH Check PATH for sure : /usr /you/bin: /bin: /usr /bin Should look like this \$ mv nu bin Install nu \$ ls nu nu not found It's really gone from current directory

\$ nu

4

But it's found by the shell

\$

Of course, your PATH should be set properly by your . profile, so you don't have to reset it every time you log in. There are other simple commands that you might create this way to tailor

t Nonetheless, it is a distinction made on most other operating systems.

82 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

your environment to your own taste. Some that we have found convenient include . es, which echoes the proper sequence of mysterious characters to clear the screen on your terminal (24 newlines is a fairly general implementation); . what, which runs who and ps -a to tell who's logged on and what they are doing; . where, which prints the identifying name of the

UNIX system you're using - it's handy if you use several regularly. (Setting PS 1 serves a similar purpose.) Exercise 3-9. Look in /bin and /usr /bin to see how many commands are actually shell files. Can you do it with one command? Hint: file(1). How accurate are guesses based on file length? 0

3.4 Command arguments and parameters Although nu is adequate as it stands, most shell programs interpret arguments, so that, for example, filenames and options can be specified when the program IS run. Suppose we want to make a program called ex to change the mode of a file to executable, so

```
$ ex nu
```

is a shorthand for

```
$ chmod +x nu
```

We already know almost enough to do this. We need a file called ex whose contents are

```
chmod +x filename
```

The only new thing we need to know is how to tell ex what the name of the file is, since it will be different each time ex is run. When the shell executes a file of commands, each occurrence of \$1 is replaced by the first argument,

each \$ 2 is replaced by the second argument, and so on through \$ 9. So if the file ex contains

```
chmod +x $1
```

when the command

```
$ ex nu
```

is run, the sub-shell replaces "\$1" by its first argument, "nu." Let's look at the whole sequence of operations:

CHAPTER 3

```
$ echo 'chmod +x $1' >cx $ sh ex ex $ echo echo Hi, there! >hello $ hello
hello: cannot execute $ ex hello $ hello Hi, there! $ mv ex /usr/you/bin $ rm
hello $
```

Notice that we said

```
$ sh ex ex
```

USING THE SHELL 83

Create cx originally Make cx itself executable Make a test program Try it

Make it executable Try again It works Install ex Clean up

exactly as the shell would have automatically done if ex were already execut- able and we typed

```
$ ex ex
```

What if you want to handle more than one argument, for example to make a program like ex handle several files at once? A crude first cut is to put nine arguments into the shell program, as in `chmod +x $1 $2 $3 $4 $5 $6 $7 $8 $9` (It only works up to \$ 9, because the string \$ 10 is parsed as "first argument, \$ 1, followed by a a"!) If the user of this shell file provides fewer than nine arguments, the missing ones are nun strings; the effect is that only the argu- ments that were actually provided are passed to ehmod by the sub-shell. So this implementation works, but it's obviously unclean, and it fails if more than nine arguments are provided. Anticipating this problem, the shell provides a shorthand \$* that means "all the arguments." The proper way to define ex, then, is

```
chmod +x $*
```

which works regardless of how many arguments are provided. With `$*` added to your repertoire, you can make some convenient shell files, such as `lc` or `m`:

```
$ cd /usr/you/bin $ cat lc # lc: count number of lines in files wc -l $* $ cat  
m # m: a concise way to type mail mail $* $
```

Both can sensibly be used without arguments. If there are no arguments, `$*`

84 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

will be null, and no arguments at all will be passed to `we` or `mail`. With or without arguments, the command is invoked properly: `$ lc /usr/you/bin/* 1 /usr/you/bin/cx 2 /usr/you/bin/lc 2 /usr/you/bin/m 1 /usr/you/bin/nu 2 /usr/you/bin/what 1 /usr/you/bin/where 9 total $ ls /usr/you/bin : lc 6`

\$

These commands and the others in this chapter are examples of personal programs, the sort of things you write for yourself and put in your bin, but are unlikely to make publicly available because they are too dependent on personal taste. In Chapter 5 we will address the issues of writing shell programs suitable for public use. The arguments to a shell file need not be

filenames. For example, consider searching a personal telephone directory. If you have a file named /usr /you/lib/phone-book that contains lines like dial-a-joke 212-976-3838 dial-a-prayer 212-246-4200 dial santa 212-976-3636 dow jones report 212-976-4141

then the grep command can be used to search it. (Your own lib directory is a good place to store such personal data bases.) Since grep doesn't care about the format of information, you can search for names, addresses, zip codes or anything else that you like. Let's make a directory assistance program, which we'll call 411 in honor of the telephone directory assistance number where we live:

```
$ eeho 'grep $* /usr/you/lib/phone-book' >411 $ ex 411 $ 4 11 joke dial-a-joke 212-976-3838 $ 411 dial dial-a-joke 212-976-3838 dial-a-prayer 212-246-4200 dial santa 212-976-3636 $ 4 11 ' dow jones' grep: can't open jones
Something is wrong $
```

The final example is included to show a potential problem: even though dow j one s is presented to 411 as a single argument, it contains a space and is

CHAPTER 3

USING THE SHELL 85

longer in quotes, so the sub-shell interpreting the 411 command converts it into two arguments to grep: it's as if you had typed \$ grep dow jones

```
/usr/you/lib/phone-book
```

and that's obviously wrong. One remedy relies on the way the shell treats double quotes. Although anything quoted with '...' is inviolate, the shell looks inside If... If for \$'s, \ 's, and '...'s. So if you revise 411 to look like

```
grep "$*" /usr/you/lib/phone-book
```

the \$* will be replaced by the arguments, but it will be passed to grep as a single argument even if it contains spaces. \$ 411 dow jones dow jones report 212-976-4141 \$ By the way, you can make grep (and thus 411) case-independent with the -y option: \$ grep -y pattern ... with -y, lower case letters in pattern will also match upper case letters in the input. (This option is in 7th Edition grep, but is absent from some other sys- terns.) There are fine points about command arguments that we are skipping over until Chapter 5, but one is worth noting here. The argument \$0 is the name of the program being executed - in ex, \$ 0 is "ex." A novel use of \$ 0 is in the implementation of the programs 2, 3, 4, ..., which print their output in that many columns:

```
$ who , 2 , drh ttyO Sep 28 21:23 cvw tty5 Sep 28 21:09 dmr tty6 Sep 28  
22:10 scj tty7 Sep 28 22:11 you tty9 Sep 28 23:00 jlb ttyb Sep 28 19:58 $
```

The implementations of 2, 3, ... are identical; in fact they are links to the same file:

```
$ In 2 3; In 2 4; In 2 5; In 2 6 $ Is -li [1-9] 16722 -rwxrwxrwx 5 you 51 Sep
28 23:21 2 16722 -rwxrwxrwx 5 you 51 Sep 28 23:21 3 16722 -rwxrwxrwx
5 you 51 Sep 28 23:21 4 16722 -rwxrwxrwx 5 you 51 Sep 28 23:21 5
16722 -rwxrwxrwx 5 you 51 Sep 28 23:21 6
```

86 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

```
$ 15 /usr/you/bin I 5 I 2 3 4 411 5 6 ex le m nu what where $ cat 5 # 2, 3 , 0
print in n columns o ... pr -$0 -t -11 $* $
```

The `-t` option turns off the heading at the top of the page and the `-In` option sets the page length to `n` lines. The name of the program becomes the number-of-columns argument to `pr`, so the output is printed a row at a time in the number of columns specified by `$ O`.

3.5 Program output as arguments Let us turn now from command arguments within a shell file to the generation of arguments. Certainly filename expansion from metacharacters like `*` is the most common way to generate arguments (other than by providing them explicitly), but another good way is by running a program. The output of any program can be placed in a command line by enclosing the invocation in back-quotes', . \$ echo At the tone the time will be 'date'. At the tone the time will be Thu Sep 29 00:02:15 EDT 1983. \$

A small change illustrates that `'...'` is interpreted inside double quotes `"... "`:
`$ echo "At the tone > the time will be 'date'." At the tone the time will be Thu
Sep 29 00:03:07 EDT 1983. $`

As another example, suppose you want to send mail to a list of people whose login names are in the file `mailinglist`. A clumsy way to handle this is to edit `mailinglist` into a suitable mail command and present it to the shell, but it's far easier to say

```
$ mail `cat mailinglist` <letter
```

This runs `cat` to produce the list of user names, and those become the arguments to `mail`. (When interpreting output in backquotes as arguments, the shell treats newlines as word separators, not command-line terminators; this subject is discussed fully in Chapter 5.) Backquotes are easy enough to use that there's really no need for a separate mailing-list option to the mail command. A slightly different approach is to convert the file `mailinglist` from just a list of names into a program that prints the list of names:

CHAPTER 3

USING THE SHELL 87

```
$ cat mailinglist echo don whr ejs rob $ ex mailinglist $ mailinglist don whr  
ejs rob $
```

New version

Now mailing the letter to the people on the list becomes

```
$ mail 'mailinglist' <letter
```

With the addition of one more program, it's even possible to modify the user list interactively. The program is called pick:

```
$ pick arguments ...
```

presents the arguments one at a time and waits after each for a response. The output of pick is those arguments selected by y (for "yes") responses; any other response causes the argument to be discarded. For example,

```
$ pr 'pick *.c' / lpr
```

presents each filename that ends in .c; those selected are printed with pr and lpr. (pick is not part of the 7th Edition, but it's so easy and useful that we've included versions of it in Chapters 5 and 6.) Suppose you have the second version of mailinglist. Then

```
$ mail 'pick \'mailinglist\'' <letter don? y whr? ejs? rob? y $
```

sends the letter to don and mb. Notice that there are nested backquotes; the backslashes prevent the interpretation of the inner" "during the parsing of the outer one. Exercise 3-10. If the backslashes are omitted in

```
$ echo 'echo `date`'
```

what happens? 0 Exercise 3-11. Try

```
$ 'date'
```

and explain the result. 0 Exercise 3-12.

```
$ grep -l pattern filenames
```

lists the filenames in which there was a match of pattern, but produces no other output. Try some variations on

88 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

\$ command 'grep -1 pattern filenames'

o

3.6 Shell variables

The shell has variables, like those in most programming languages, which in shell jargon are sometimes called parameters. Strings such as \$ 1 are positional parameters - variables that hold the arguments to a shell file. The digit indicates the position on the command line. We have seen other shell variables: PATH is the list of directories to search for commands, HOME is your login directory, and so on. Unlike variables in a regular language, the argument variables cannot be changed; although PATH is a variable whose value is \$PATH, there is no variable 1 whose value is \$1. \$1 is nothing more than a compact notation for the first argument. Leaving positional parameters aside, shell variables can be created, accessed and modified. For example, \$ PATH=:/bin:/usr/bin

is an assignment that changes the search path. There must be no spaces around the equals sign, and the assigned value must be a single word, which means it must be quoted if it contains shell metacharacters that should not be interpreted. The value of a variable is extracted by preceding the name by a dollar sign: \$ PATH=\$PATH:/usr/games \$ echo \$PATH
:/usr/you/bin:/bin:/usr/bin:/usr/games \$ PATH=: /usr /you/bin: /bin : /usr /bin Restore it \$

Not all variables are special to the shell. You can create new variables by assigning them values; traditionally, variables with special meaning are spelled in upper case, so ordinary names are in lower case. One of the common uses of variables is to remember long strings such as pathnames: `$ pwd /usr/you/bin $ dir= 'pwd" $ cd /usr/mary/bin $ In $dir/cx tJ $ $ cd $dir $ pwd /usr/you/bin $`

Remember where we are Go somewhere else Use the variable in a filename
Work for a while Return

The shell built-in command `set` displays the values of all your defined variables. To see just one or two variables, `echo` is more appropriate.

CHAPTER 3

USING THE SHELL 89

```
$ set HOME=/usr/you IFS=
```

```
PATH=:/usr/you/bin:/bin:/usr/bin PS1=$ PS2=> dir=/usr/you/bin $ echo  
$dir /usr/you/bin $
```

The value of a variable is associated with the shell that creates it, and is not automatically passed to the shell's children.

```
$ x=Hello $ sh $ echo $x
```

Create x New shell

```
$ ctrl-d $ $ echo $x Hello $
```

Newline only: x undefined in the sub-shell Leave this shell Back in original shell

x still defined

This means that a shell file cannot change the value of a variable, because the shell file is run by a sub-shell:

```
$ echo 'x="Good Bye" > echo $x' >setx $ cat setx x="Good Bye" echo $x $  
echo $x Hello $ sh setx Good Bye $ echo $x Hello $
```

Make a two-line shell file... .. to set and print x

x is Hello in original shell

x is Good Bye in sub-shell...

.. .but still Hello in this shell

There are times when using a shell file to change shell variables would be useful, however. An obvious example is a file to add a new directory to your PATH. The shell therefore provides a command '.' (dot) that executes the commands in a file in the current shell, rather than in a sub-shell. This was originally invented so people could conveniently re-execute their .profile files without having to log in again, but it has other uses:

90 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

```
$ cat /usr/you/bin/games PATH=$PATH: /usr/games Append /usr/games to  
PATH $ echo $PATH :/usr/you/bin:/bin:/usr/bin $ . games $ echo $PATH  
:/usr/you/bin:/bin:/usr/bin:/usr/games $
```

The file for the '.' command is searched for with the PATH mechanism, so it can be placed in your bin directory. When a file is executing with '.' it is only superficially like running a shell file. The file is not "executed" in the usual sense of the word. Instead, the commands in it are interpreted exactly as if you had typed them interactively - the standard input of the shell is temporarily redirected to come from the file. Since the file is read but not

executed, it need not have execute permissions. Another difference is that the file does not receive command line arguments; instead, \$1, \$2 and the rest are empty. It would be nice if arguments were passed, but they are not. The other way to set the value of a variable in a sub-shell is to assign to it explicitly on the command line before the command itself:

```
$ echo 'echo $x' >echox $ cx echox $ echo $x Hello $ echox
```

As before

x not set in sub-shell

```
$ x=Hi echox Hi $
```

Value of x passed to sub-shell

(Originally, assignments anywhere in the command line were passed to the command, but this interfered with dd(1).) The '.' mechanism should be used to change the value of a variable permanently, while in-line assignments should be used for temporary changes. As an example, consider again searching /usr/games for commands, with the directory not in your PATH:
\$ ls /usr/games : grep fort fortune Fortune cookie command \$ fortune
fortune: not found \$ echo \$PATH :/usr/you/bin:/bin:/usr/bin /usr/games not
in PATH \$ PATH=/usr/games fortune Ring the bell; close the book; quench
the candle.

CHAPTER 3

USING THE SHELL 91

```
$ echo $PATH : /usr /you/bin: /bin: /usr /bin PATH unchanged $ cat
/usr/you/bin/games PATH=$PATH: /usr/games games command still there $
. games $ fortune Premature optimization is the root of all evil - Knuth $
echo $PATH : /usr/you/bin: /bin: /usr/bin: /usr/games PATH changed this
time $
```

It's possible to exploit both these mechanisms in a single shell file. A slightly different games command can be used to run a single game without changing PATH, or can set PATH permanently to include /usr/games: \$ cat /usr/you/bin/games PATH=\$PATH:/usr/games \$* No

```
e $* $ cx /usr/you/bin/games $ echo $PATH : /usr /you/bin: /bin: /usr /bin
Doesn't have /usr / game s $ games fortune I'd give my right arm to be
ambidextrous. $ echo $PATH : /usr /you/bin : /bin : /usr /bin Still doesn't $ .
games $ echo $PATH :/usr/you/bin:/bin:/usr/bin:/usr/games Now it does $
fortune He who hesitates is sometimes saved. $
```

The first call to games ran the shell file in a sub-shell, where PATH was temporarily modified to include /usr/games. The second example instead interpreted the file in the current shell, with \$ * the empty string, so there was no command on the line, and PATH was modified. Using games in these two ways is tricky, but results in a facility that is convenient and natural to use. When you want to make the value of a variable accessible in sub-shells, the shell's export command should be used. (You might think

about why there is no way to export the value of a variable from a sub-shell to its parent.) Here is one of our earlier examples, this time with the variable exported: `$ x=Hello $ export x $ sh $ echo $x Hello`

New shell

x known in sub-shell

92 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

```
$ x='Good Bye' $ echo $x Good Bye $ ctrl-d $ $ echo $x Hello $
```

Change its value

Leave this shell Back in original shell

x still He 110

export has subtle semantics, but for day-to-day purposes at least, a rule of thumb suffices: don't export temporary variables set for short-term convenience, but always export variables you want set in an your shells and sub-shells (including, for example, shells started with the ed's ! command). Therefore, variables special to the shell, such as PATH and HOME, should be exported. Exercise 3-13. Why do we always include the current directory in PATH? Where should it be placed? 0

3.7 More on I/O redirection

The standard error was invented so that error messages would always appear on the terminal: `$ diff file1 fie12 >diff.out diff: fie12: No such file or directory $`

It's certainly desirable that error messages work this way - it would be most unfortunate if they disappeared into `diff . out`, leaving you with the impression that the erroneous `diff` command had worked properly. Every program has three default files established when it starts, numbered by small integers called file descriptors (which we will return to in Chapter 7). The standard input, 0, and the standard output, 1, which we are already familiar with, are often redirected from and into files and pipes. The last, numbered 2, is the standard error output, and normally finds its way to your terminal. Sometimes programs produce output on the standard error even when they work properly. One common example is the program `time`, which runs a command and then reports on the standard error how much time it took. `$ time we ch3.1 931 4288 22691 ch3.1`

real user sys

```
1 . a 0.4 0.4
```

CHAPTER 3

USING THE SHELL 93

```
$ time we eh3.1 >we.out
```

```
real 2.0 user 0.4 sys 0.3 $ time we eh3.1 >we.out 2>time.out $ cat time.out
```

```
real user sys $
```

```
1 . 0 0.4 0.3
```

The construction `2>filename` (no spaces are allowed between the 2 and the» directs the standard error output in

o the file; it's syntactically graceless but it does the job. (The times produced by `time` are not very accurate for such a short test as this one, but for a sequence of longer tests the numbers are useful and reasonably trustworthy, and you might well want to save them for further analysis; see, for example, Table 8.1.) It is also possible to merge the two output streams:

```
$ time we eh3. 1 >we.out 2>&1 $ cat we. out 931 4288 22691 ch3.1
```

```
real user sys $
```

```
1 . 0 0.4 0.3
```

The notation `2 >& 1` tells the shell to put the standard error on the same stream as the standard output. There is not much mnemonic value to the ampersand; it's simply an idiom to be learned. You can also use `1 >&2` to add the standard output to the standard error: `echo ... 1>&2`

prints on the standard error. In shell files, it prevents the messages from vanishing accidentally down a pipe or into a file. The shell provides a mechanism so you can put the standard input for a command along with the command, rather than in a separate file, so the shell file can be completely self-contained. Our directory information program 411 could be written

94 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

```
$ cat 411 grep "$*" «End dial-a-joke 212-976-3838 dial-a-prayer 212-246-4200 dial santa 212-976-3636 dow jones report 212-976-4141 End $
```

The shell jargon for this construction is a here document; it means that the input is right here instead of in a file somewhere. The `<<` signals the construction; the word that follows (EJ:?^d in our example) is used to delimit the input, which is taken to be everything up to an occurrence of that word on a line by itself. The shell substitutes for \$, '...', and \ in a here document, unless some part of the word is quoted with quotes or a backslash; in that case, the whole document is taken literally. We'll return to here documents at the end of the chapter, with a much more interesting example. Table 3.2 lists the various input-output redirections that the shell understands.

Exercise 3-14. Compare the here-document version of 411 with the original. Which is easier to maintain? Which is a better basis for a general service? 0

```
>file > > file <Ii le I Pl 1 P2
```

A.

```
n>file n»file n>&m n<&m
```

```
<<S
```

```
<<\s <<'s'
```

Table 3.2: Shell I/O Redirections

direct standard output to file append standard output to file take standard
input from file connect standard output of program P1 to input of P2
obsolete synonym for : direct output from file descriptor n to file append
output from file descriptor n to file merge output from file descriptor n with
file descriptor m merge input from file descriptor n with file descriptor m
here document: take standard input until next s at beginning of a line;
substitute for \$, '...', and \ here document with no substitution here
document with no substitution

3.8 Looping in shell programs The shell is actually a programming
language: it has variables, loops, decision-making, and so on. We will
discuss basic looping here, and talk more about control flow in Chapter 5.

CHAPTER 3

USING THE SHELL 95

Looping over a set of filenames is very common, and the shell's `for` state-
ment is the only shell control-flow statement that you might commonly type
at the terminal rather than putting in a file for later execution. The syntax is:
`for var in list of words do`

commands

done

For example, a for statement to echo filenames one per line is just

```
$ for i in * > do > echo $i > done
```

The "i" can be any shell variable, although i is traditional. Note that the variable's value is accessed by \$ i, but that the for loop refers to the variable as i. We used * to pick up all the files in the current directory, but any other list of arguments can be used. Normally you want to do something more interesting than merely printing filenames. One thing we do frequently is to compare a set of files with previous versions. For example, to compare the old version of Chapter 2 (kept in directory old) with the current one:

```
$ ls ch2.* ch2.1 ch2.6 $ for i > do
```

```
ls ch2.2 ch2.7 in ch2.*
```

```
ch2.3
```

```
ch2.4
```

```
ch2.5
```



```
> echo $i: > diff -b o1d/$i $i > echo > done I pr -h "diff 'pwd'/o1d 3712 $
```

Add a blank line for readability 'pwd'" I 1pr &. Process-id

We piped the output into pr and Ipr just to illustrate that it's possible: the standard output of the programs within a for goes to the standard output of the for itself. We put a fancy heading on the output with the -h option of pr, using two embedded calls of pwd. And we set the whole sequence running asynchronously .(&) so we wouldn't have to wait for it; the & applies to the entire loop and pipeline. We prefer to format a for statement as shown, but you can compress it somewhat. The main limitations are that do and done are only recognized as keywords when they appear right after a newline or semicolon. Depending on the size of the for, it's sometimes better to write it all on one line:

```
for i in list; do commands; done
```

You should use the for loop for multiple commands, or where the built-in

96 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

argument processing in individual commands is not suitable. But don't use it when the individual command will already loop over filenames:

Poor idea: for i in \$* do

chmod +x \$i

done

is inferior to

chmod +x \$*

because the for loop executes a separate chmod for each file, which is more expensive in computer resources. (Be sure that you understand the difference between

for i in *

which loops over all filenames in the current directory, and

for i in \$*

which loops over all arguments to the shell file.) The argument list for a for most often comes from pattern matching on filenames, but it can come from anything. It could be

```
$ for i in 'cat ...'
```

or arguments could just be typed. For example, earlier in this chapter we created a group of programs for multi-column printing, called 2, 3, and so on. These are just links to a single file that can be made, once the file 2 has been written, by `$ for i in 3 4 5 6; do ln 2 $i; done`

As a somewhat more interesting use of the for, we could use pick to select which files to compare with those in the backup directory:

CHAPTER 3

USING THE SHELL 97

```
$ :Eor i > do > > > done ch2.1? ch2.2? ch2.3? ch2.4? ch2.5? ch2.6? ch2.7?  
$
```

```
in 'pick ch2.*'
```

```
echo $i: diff old/$i $i | pr , | pr | I Y
```

y y

It's obvious that this loop should be placed in a shell file to save typing next time: if you've done something twice, you're likely to do it again. Exercise 3-15. If the diff loop were placed in a shell file, would you put the pick in the shell file? Why or why not? 0 Exercise 3-16. What happens if the last line of the loop above is

```
> done | pr | | pr &
```

that is, ends with an ampersand? See if you can figure it out, then try it. 0

3e9 bundle: putting it all together To give something of the flavor of how shell files develop, let's work through a larger example. Pretend you have received mail from a friend on another machine, say somewhere! bob, t who would like copies of the shell files in your bin. The simplest way to send them is by return mail, so you might start by typing

```
$ cd /usr/you/bin $ for i in 'pick *' > do > echo ===== This is file  
$i > cat $i > done : mail somewhere!bob $
```

But look at it from somewhere! bob's viewpoint: he's going to get a mail message with all the files clearly demarcated, but he'll need to use an editor to break them into their component files. The flash of insight is that a properly-constructed mail message could automatically unpack itself so the recipient needn't do any work. That implies it should be a shell file containing both the

t There are s

xeral notations for remote machine addresses. The form machine! person is most common. See mail(1). "

98 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

files and the instructions to unpack it. A second insight is that the shell's here documents are a convenient way to combine a command invocation and the data for the command. The rest of the job is just getting the quotes right. Here's a working program, called bundle, that groups the files together into a self-explanatory shell file on its standard output:

```
$ cat bundle # bundle: group files into distribution package
```

```
echo '# To unbundle, sh this file' for i do
```

```
echo "echo $1" && echo "cat >$1 «'End of $1'" cat $1 echo "End of $1"
```

done \$

Quoting "End of \$1" ensures that any shell metacharacters in the files will be ignored. Naturally, you should try it out before inflicting it on somewhere!

```
bob: $ bundle ex lc > junk Make a trial bundle $ cat junk # To
unbundle, sh this file echo ex 1>&2 cat >cx «'End of ex' chmod +x $* End
of ex echo lc 1>&2 cat >lc «'End of lc' # lc: count number of lines in files
we -1 $* End of lc $ mkdir test $ cd test $ sh ../junk Try it out ex lc $ ls ex
lc
```

CHAPTER 3

USING THE SHELL 99

```
$ cat ex chmod +x $* $ cat lc # lc: count number of lines in files we -1 $* $
cd 0 0 $ rm junk test/*; rmdir test $ pwd /usr/you/bin $ bundle 'pick *' f
mail somewhere!bob
```

Looks good

Clean up

Send the files

There's a problem if one of the files you're sending happens to contain a line of the form

End of filename

but it's a low-probability event. To make bundle utterly safe, we need a thing or two from later chapters, but it's eminently usable and convenient as it stands. bundle illustrates much of the flexibility of the UNIX environment: it uses shell loops, I/O redirection, here documents and shell files, it interfaces directly to mail, and, perhaps most interesting, it is a program that creates a program. It's one of the prettiest shell programs we know - a few lines of code that do something simple, useful and elegant. Exercise 3-17. How would you use bundle to send all the files in a directory and its subdirectories? Hint: shell files can be recursive. Exercise 3-18. Modify bundle so it includes with each file the information garnered from ls -l, particularly permissions and date of last change. Contrast the facilities of bundle with the archive program ar(1).

3.10 Why a programmable shell? The "UNIX shell isn't typical of command interpreters: although it lets you run com

d

in the usual way, because it is a programming language it can accomplish much

more. It's worth a brief look back at what we've seen, in part because there's a lot of material in this chapter but more because we "promised to talk about "

commonly used features" and then wrote about 30 pages of shell programming examples. But when using the shell you write little one-line programs all the time: a pipeline is a program, as is our "Tea is ready" example. The shell works like that: you program it constantly, but it's so easy and natural (once you're familiar with it) that you don't think of it as programming. The shell does some things, like looping, I/O redirection with < and >, and filename expansion with *, so that no program need worry about them, and more importantly, so that the application of these facilities is uniform across all programs. Other features, such as shell files and pipes, are really provided by the kernel, but the shell gives a natural syntax for creating them. They go

100 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 3

beyond convenience, to actually increasing the capabilities of the system. Much of the power and convenience of the shell derives from the UNIX kernel underneath it; for example, although the shell sets up pipes, the kernel actually moves the data through them. The way the system treats executable files makes it possible to write shell files so that they are run exactly like compiled programs. The user needn't be aware that they are command files - they aren't invoked with a special command like RUN. Also, the shell is a program itself, not part of the kernel, so it can be tuned, extended and used like any other program. This idea is not unique to the UNIX system, but it has been exploited better there than anywhere else. In Chapter 5, we'll return to the subject of shell programming, but you should

keep in mind that whatever you're doing with the shell, you're programming it - that's largely why it works so well.

History and bibliographic notes The shell has been programmable from earliest times. Originally there were separate commands for `if`, `gata`, and `labels`, and the `gata` command operated by scanning the input file from the beginning looking for the right label. (Because it is not possible to re-read a pipe, it was not possible to pipe into a shell file that had any control flow). The 7th Edition shell was written originally by Steve Bourne with some help and ideas from John Mashey. It contains everything needed for programming, as we shall see in Chapter 5. In addition, input and output are rationalized: it is possible to redirect I/O into and out of shell programs without limit. The parsing of filename metacharacters is also internal to this shell; it had been a separate program in earlier versions, which had to live on very small machines. One other major shell that you may run into (you may already be using it by preference) is `csh`, the so-called "C shell" developed at Berkeley by Bill Joy by building on the 6th Edition shell. The C shell has gone further than the Bourne shell in the direction of helping interaction - most notably, it provides a history mechanism that permits shorthand repetition (perhaps with slight editing) of previously issued commands. The syntax is also somewhat different. But because it is based on an earlier shell, it has less of the programming convenience; it is more an interactive command interpreter than a programming language. In particular, it is not possible to pipe into or out of control flow constructs. `pick` was invented by Tom Duff, and `bundle` was invented independently by Alan Hewett and James Gosling.

CHAPTER 4: FILTERS

There is a large family of UNIX programs that read some input, perform a simple transformation on it, and write some output. Examples include `grep` and `tail` to select part of the input, `sort` to sort it, `wc` to count it, and so on.

Such programs are called filters. This chapter discusses the most frequently used filters. We begin with `grep`, concentrating on patterns more complicated than those illustrated in Chapter 1. We will also present two other members of the `grep` family, `egrep` and `fgrep`. The next section briefly describes a few other useful filters, including `tr` for character transliteration, `dd` for dealing with data from other systems, and `uniq` for detecting repeated text lines. `sort` is also presented in more detail than in Chapter 1. The remainder of the chapter is devoted to two general purpose "data transformers" or "programmable filters." They are called programmable because the particular transformation is expressed as a program in a simple programming language. Different programs can produce very different transformations. The programs are `sed`, which stands for stream editor, and `awk`, named after its authors. Both are derived from a generalization of `grep`: `$ program pattern-action filenames ...`

scans the files in sequence, looking for lines that match a pattern; when one is found a corresponding action is performed. For `grep`, the pattern is a regular expression as in `ed`, and the default action is to print each line that matches the pattern. `sed` and `awk` generalize both the patterns and the actions. `sed` is a derivative of `ed` that takes a "program" of editor commands and streams data from the files past them, doing the commands of the program on every line. `awk` is not as convenient for text substitution as `sed` is, but it includes arithmetic, variables, built-in functions, and a programming language that looks quite a bit like C. This chapter doesn't have the complete story on either program; Volume 2B of the UNIX Programmer's Manual has tutorials on both.

eCHAPTER 4

401 The grep family We mentioned grep briefly in Chapter 1, and have used it in examples since then.

```
$ grep pattern filenames. ..
```

searches the named files or the standard input and prints each line that contains an instance of the pattern. grep is invaluable for finding occurrences of variables in programs or words in documents, or for selecting parts of the output of a program:

```
$ grep -n variable "*. [ch] Locate variable in C source $ grep From $MAIL
Print message headers in mailbox $ grep From $MAIL: grep -v mary
Headers that didn't come from mar $ grep -y mary $HOME/lib/phone-book
Find mary's phone number $ who : grep mary See if mary is logged in $ Is :
grep -v temp Filenames that don't contain temp
```

The option -n prints line numbers, -v inverts the sense of the test, and -y makes lower case letters in the pattern match letters of either case in the file (upper case still matches only upper case). In all the examples we've seen so far, grep has looked for ordinary strings of letters and numbers. But grep can actually search for much more complicated patterns: grep interprets expressions in a simple language for describing strings. Technically, the patterns are a slightly restricted form of the string specifiers called regular expressions. grep interprets the same regular expressions as ed; in fact, grep was originally created (in an evening) by straightforward surgery on ed. Regular expressions are specified by giving special meaning to certain char-

acters, just like the *, etc., used by the shell. There are a few more metacharacters, and, regrettably, differences in meanings. Table 4.1 shows all the regular expression metacharacters, but we will review them briefly here. The metacharacters ^ and \$ "anchor" the pattern to the beginning (^) or end (\$) of the line. For example, \$ grep From \$MAIL locates lines containing From in your mailbox, but \$ grep '^From' \$MAIL

prints lines that begin with From, which are more likely to be message header lines. Regular expression metacharacters overlap with shell metacharacters, so it's always a good idea to enclose grep patterns in single quotes. grep supports character classes much like those in the shell, so [a-z] matches any lower case letter. But there are differences; if a grep character class begins with a circumflex ^, the pattern matches any character except

CHAPTER 4

FILTERS 103

those in the class. Therefore, [^0-9] matches any non-digit. Also, in the shell a backslash protects] and - in a character class, but grep and ed require that these characters appear where their meaning is unambiguous. For example, [] [-] (sic) matches either an opening or closing square bracket or a minus sign. A period '.' is equivalent to the shell's *: it matches any character. (The period is probably the character with the most different meanings to different UNIX programs.) Here are a couple of examples:

```
$ Is -l : grep 'Ad' $ 1 1 I , A , S - I grep . . . . . rw
```

List subdirectory names List files others can read and write

The ,", and seven perio.2-

match any seven characters at the beginning of the line, which when applied the output of `ls -l` means any permission string. The closure operator `*` applies to the previous character or metacharacter (including a character class) in the expression, and collectively they match any number of successive matches of the character or metacharacter. For example, `x*` matches a sequence of x's as long as possible, `[a-zA-Z]*` matches an alphabetic string, `.*` matches anything up to a newline, and `.*x` matches anything up to and including the last x on the line. There are a couple of important things to note about closures. First, closure applies to only one character, so `xy*` matches an x followed by y's, not a sequence like `xyxyxy`. Second, "any number" includes zero, so if you want at least one character to be matched, you must duplicate it. For example, to match a string of letters the correct expression is `[a-zA-Z][a-zA-Z]*` (a letter followed by zero or more letters). The shell's `*` filename matching character is similar to the regular expression `.*`. No `grep` regular expression matches a newline; the expressions are applied to each line individually. With regular expressions, `grep` is a simple programming language. For example, recall that the second field of the password file is the encrypted password. This command searches for users without passwords: `$ grep ,A[A:]*:,: /etc/passwd`

The pattern is: beginning of line, any number of non-colons, double colon. `grep` is actually the oldest of a family of programs, the other members of which are called `fgrep` and `egrep`. Their basic behavior is the same, but `fgrep` searches for many literal strings simultaneously, while `egrep` interprets true regular expressions - the same as `grep`, but with an "or" operator and parentheses to group expressions, explained below. Both `fgrep` and `egrep` accept a `-f` option to specify a file from which to read the pattern. In the file, newlines separate patterns to be searched for in parallel. If there are words you habitually misspell, for example, you could check your

documents for their occurrence by keeping them in a file, one per line, and using fgrep:

104 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

```
$ fgrep -f common-errors document
```

The regular expressions interpreted by egrep (also listed in Table 4.1) are the same as in grep, with a couple of additions. Parentheses can be used to group, so (xy) * matches any of the empty string, xy, xyxy, xyxyxy and so on. The vertical bar | is an "or" operator; today: tomorrow matches either today or tomorrow, as does to (day I morrow) . Finally, there are two other closure operators in egrep, + and ? The pattern x+ matches one or more x's, and x? matches zero or one x, but no more. egrep is excellent at word games that involve searching the dictionary for words with special properties. Our dictionary is Webster's Second International, and is stored on-line as the list of words, one per line, without definitions. Your system may have /usr /dict/words, a smaller dictionary intended for checking spelling; look at it to check the format. Here's a pattern to find words that contain all five vowels in alphabetical order:

```
$ cat alphvowels
```

```
A[Aaeiou]*a[Aaeiou]*e[Aaeiou]*i[Aaeiou]*o[Aaeiou]*u[Aaeiou]*$ $  
egrep -f alphvowels /usr/dict/web2 : 3 abstemious abstemiously acheilous  
acheirous affectionous annelidous arterious bacterious facetious facetiously  
majestious $
```

abstentious acleistous

arsenious

caesious fracedinous

The pattern is not enclosed in quotes in the file alPhvowels'}q

l}

quotes are used to enclose egrep patterns, the shell protects the commands from interpretation but strips off the quotes; egrep never sees them. Since the file is not examined by the shell, however, quotes are not used around its contents. We could have used grep for this example, but because of the way egrep works, it is much faster when searching for patterns that include closures, especially when scanning large files. As another example, to find all words of six or more letters that have the letters in alphabetical order:

```
$ cat monotonic Aa?b?c?d?e?f?g?h?i?j?k?l?m?n?o?p?q?r?s?t?u?v?w?x?y?z?$ $ egrep -f monotonic /usr/dict/web2 : grep '.....' : 5 abdest acknow  
adipsy agnosy befist behind beknow bijoux chintz dehors dehort deinos  
egilops ghosty $
```

almost biopsy dimpsy

(Egilops is a disease that attacks wheat.) Notice the use of grep to filter the output of egrep.

eCHAPTER 4

FILTERS 105

Why are there three grep programs? fgrep interprets no metacharacters, but can look efficiently for thousands of words in parallel (once initialized, its running time is independent of the number of words), and thus is used primarily for tasks like bibliographic searches. The size of typical fgrep patterns is beyond the capacity of the algorithms used in grep and egrep. The distinction between grep and egrep is harder to justify. grep came much earlier, uses the regular expressions familiar from ed, and has tagged regular expressions and a wider set of options. egrep interprets more general expressions (except for tagging), and runs significantly faster (with speed independent of the pattern), but the standard version takes longer to start when the expression is complicated. A newer version exists that starts immediately, so egrep and grep could now be combined into a single pattern matching program.

c \c

A

\$

[.oo] [A...] \n

r* r+ r? rl r2 rl: r2 \ (r\) (r)

Table 401: grep and egrep Regular Expressions (decreasing order of precedence) any non-special character c matches itself turn off any special meaning of character c beginning of line end of line an y single character an y one of characters in ...; ranges like a - z are legal any single character not in ...; ranges are legal what the n'th \ (... \) matched (grep only) zero or more occurrences of r one or more occurrences of r (egrep only) zero or one occurrences of r (egrep only) r 1 followed by r2 rl or r2 (egrep only) tagged regular expression r (grep only); can be nested regular expression r (egrep only); can be nested No regular expression matches a newline.

Exercise 4-1. Look up tagged regular expressions (\ (and \») in Appendix 1 or ed(1), and use grep to search for palindromes - words spelled the same backwards as for- wards. Hint: write a different pattern for each length of word. 0 Exercise 4-2. The structure of grep is to read a single line, check for a match, then loop. How would grep be affected if regular expressions could match newlines? 0

106 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

4.2 Other filters

The purpose of this section is to alert you to the existence and possibilities of the rich set of small filters provided by the system, and to give a few examples of their use. This list is by no means all-inclusive - there are many more that were part of the 7th Edition, and each installation creates some of its own. All of the standard ones are described in Section 1 of the manual. We begin with `sort`, which is probably the most useful of all. The basics of `sort` were covered in Chapter 1: it sorts its input by line in ASCII order. Although this is the obvious thing to do by default, there are lots of other ways that one might want data sorted, and `sort` tries to cater to them by providing lots of different options. For example, the `-f` option causes upper and lower case to be "folded," so case distinctions are eliminated. The `-d` option (dictionary order) ignores all characters except letters, digits and blanks in comparisons. Although alphabetic comparisons are most common, sometimes a numeric comparison is needed. The `-n` option sorts by numeric value, and the `-r` option reverses the sense of any comparison. So,

```
$ Is / sort -f $ Is -s / sort -n $ Is -s / sort -nr
```

Sort filenames in alphabetic order Sort with smallest files first Sort with largest files first

`sort` normally sorts on the entire line, but it can be told to direct its attention only to specific fields. The notation `+m` means that the comparison skips the first `m` fields; `+0` is the beginning of the line. So, for example,

```
$ Is -1 / sort +3nr $ who / sort +4n
```

Sort by byte count, largest first Sort by time of login, oldest first

Other useful sort options include `-0`, which specifies a filename for the output (it can be one of the input files), and `-u`, which suppresses all but one of each group of lines that are identical in the sort fields. Multiple sort keys can be used, as illustrated by this cryptic example from the manual page `sort(1)`:

```
$ sort +Of +0 -u filenames
```

`+Of` sorts the line, folding upper and lower case together, but lines that are identical may not be adjacent. So `+0` is a secondary key that sorts the equal lines from the first sort into normal ASCII order. Finally, `-u` discards any adjacent duplicates. Therefore, given a list of words, one per line, the command prints the unique words. The index for this book was prepared with a similar sort command, using even more of sort's capabilities. See `sort(1)`. The command `uniq` is the inspiration for the `-u` flag of `sort`: it discards all but one of each group of adjacent duplicate lines. Having a separate program for this function allows it to do tasks unrelated to sorting. For example, `uniq` will remove multiple blank lines whether its input is sorted or not.

CHAPTER 4

FILTERS 107

Options invoke special 'ways to process the duplications: `uniq -d` prints only those lines that are duplicated; `uniq -u` prints only those that are unique (i.e., not duplicated); and `uniq -c` counts the number of occurrences of each line. We'll see an example shortly. The `comm` command is a file comparison program. Given two sorted input files `f 1` and `f 2`, `comm` prints three columns of output: lines that occur only in `f 1`, lines that occur only in `f2`, and lines that occur in both files. Any of these columns can be suppressed by an option: `$ comm -12 £1 £2`

prints only those lines that are in both files, and `$ comm -23 £1 £2`

prints the lines that are in the first file but not in the second. This is useful for comparing directories and for comparing a word list with a dictionary. The `tr` command transliterates the characters in its input. By far the most common use of `tr` is case conversion:

```
$ tr a-z A-Z $ tr A-Z a-z
```

Map lower case to upper Map upper case to lower

The `dd` command is rather different from all of the other commands we have looked at. It is intended primarily for processing tape data from other systems - its very name is a reminder of OS/360 job control language. `dd` will do case conversion (with a syntax very different from `tr`); it will convert from ASCII to EBCDIC and vice versa; and it will read or write

data in the fixed size records with blank padding that characterize non-UNIX systems. In practice, `dd` is often used to deal with raw, unformatted data, whatever the source; it encapsulates a set of facilities for dealing with binary data. To illustrate what can be accomplished by combining filters, consider the following pipeline, which prints the 10 most frequent words in its input:

```
cat $* tr -sc A-Za-z '\012' : sort uniq -c sort -n tail 5
```

Compress runs of non-letters into newline

`cat` collects the files, since `tr` only reads its standard input. The `tr` command is from the manual: it compresses adjacent non-letters into newlines, thus converting the input into one word per line. The words are then sorted and `uniq -c` compresses each group of identical words into one line prefixed by a count, which becomes the sort field for `sort -n` (This combination of two sorts around a `uniq` occurs often enough to be called an idiom.) The result is the unique words in the document, sorted in increasing frequency.

`tail`

108 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

selects the 10 most common words (the end of the sorted list) and 5 prints them in five columns. By the way, notice that ending a line with `\` is a valid way to continue it. Exercise 4-3. Use the tools in this section to write a

simple spelling checker, using /usr/dict/words. What are its shortcomings, and how would you address them? 0 Exercise 4-4. Write a word-counting program in your favorite programming language and compare its size, speed and maintainability with the word-counting pipeline. How easily can you convert it into a spelling checker? 0

4.3 The stream editor sed

Let us now turn to sed. Since it is derived directly from ed, it should be easy to learn, and it will consolidate your knowledge of ed. The basic idea of sed is simple: `$ sed 'list of ed commands' filenames ...`

reads lines one at a time from the input files; it applies the commands from the list, in order, to each line and writes its edited form on the standard output. So, for instance, you can change UNIX to UNIX (TM) everywhere it occurs in a set of files with

`$ sed ' s/UNIX/UNIX (TM) /g' filenames... >output` Do not misinterpret what happens here. sed does not alter the contents of its input files. It writes on the standard output, so the original files are not changed. By now you have enough shell experience to realize that

`$ sed '...' file >file`

is a bad idea: to replace the contents of files, you must use a temporary file, or another program. (We will talk later about a program to encapsulate the idea of overwriting an existing file; look at `overwrite` in Chapter 5.) sed

outputs each line automatically, so no `p` was needed after the substitution command above; indeed, if there had been one, each modified line would have been printed twice. Quotes are almost always necessary, however, since so many `sed` metacharacters mean something to the shell as well. For example, consider using `du -a` to generate a list of filenames. Normally, `du` prints the size and the filename:

```
$ du -a 18 13 14 17 2 $
```

```
ch4.* ch4.1 ch4.2 ch4.3 ch4.4 ch4.9
```

You can use `sed` to discard the Size part, but the editing command needs

eCHAPTER 4

FILTERS 109

quotes to protect a `*` and a tab from being interpreted by the shell:

```
$ du -a ch4.* | sed 's/.*'
```

```
//' ch4.1 ch4.2 ch4.3 ch4.4 ch4.9 $
```

The substitution deletes all characters (. *) up to and including the rightmost tab (shown in the pattern as). In a similar way, you could select the user names and login times from the output of who: \$ who lr tty1 ron tty3 you tty4 td tty5 \$ who : sed 's/ lr 07: 14 ron 10:31 you 08:36 td 08:47 \$

```
Sep 29 07:14 Sep 29 10:31 Sep 29 08:36 Sep 29 08:47 .* / /'
```

The s command replaces a blank and everything that follows it (as much as possible, including more blanks) up to another blank by a single blank. Again, quotes are needed. Almost the same sed command can be used to make a program getname that will return your user name:

```
$ cat getname who am i : sed 'sl .*11' $ getname you $
```

Another sed sequence is used so frequently that we have made it into a shell file called indo The ind command indents its input one tab stop; it is handy for moving something over to fit better onto line-printer paper. The implementation of ind is easy - stick a tab at the front of each line:

```
sed 's/"I...I' $*
```

Version 1 of i nd

This version even puts a tab on each empty line, which seems unnecessary. A better version uses sed's ability to select the lines to be modified. If you

pre- fix a pattern to the command, only the lines that match the pattern will be affected:

110 THE UNIX PROGRAMMING ENVIRONMENT

eHAPTER 4

```
sed '/./S/A/
```

```
/' $*
```

Version 2 of ind

The pattern `/./` matches any line that has at least one character on it other than a newline; the `s` command is done for those lines but not for empty lines. Remember that `sed` outputs all lines regardless of whether they were changed, so the empty lines are still produced as they should be. There's yet another way that `ind` could be written. It is possible to do the commands only on lines that don't match the selection pattern, by preceding the command with an exclamation mark `!`. In

```
sed '/A$/!S/A/
```

```
/' $*
```

Version 3 of ind

the pattern `/\" $/` matches empty lines (the end of the line immediately follows the beginning), so `/\" $ / I` says, "don't do the command on empty lines." As we said above, `sed` prints each line automatically, regardless of what was done to it (unless it was deleted). Furthermore, most `ed` commands can be used. So it's easy to write a `sed` program that will print the first three (say) lines of its input, then quit: `sed 3q` Although `3q` is not a legal `ed` command, it makes sense in `sed`: copy lines, then quit after the third one. You might want to do other processing to the data, such as indent it. One way is to run the output from `sed` through `ind`, but since `sed` accepts multiple commands, it can be done with a single (somewhat unlikely) invocation of `sed`:

```
sed 'S/A/
```

```
/ 3q'
```

Notice where the quotes and the newline are: the commands have to be on separate lines, but `sed` ignores leading blanks and tabs. With these ideas, it might seem sensible to write a program, called `head`, to print the first few lines of each filename argument. But `sed 3q` (or `10q`) is so easy to type that we've never felt the need. We do, however, have an `ind`, since its equivalent `sed` command is harder to type. (In the process of writing this book we replaced the existing 30-line C program by version 2 of the one-line implementations shown earlier). There is no clear criterion for when it's worth making a separate command from a complicated command line; the best rule we've found is to put it in your bin and see if you actually use it. It's also possible to put `sed` commands in a file and execute them from there, with `$ sed -f cmdfile ...` You can use line selectors other than numbers like 3:

eCHAPTER 4

FILTERS 111

```
$ sed ' /pattern/ q ,
```

prints its input up to and including the first line matching pattern, and `$ sed ' /pattern/d'`

deletes every line that contains pattern; the deletion happens before the line is automatically printed, so deleted lines are discarded. Although automatic printing is usually convenient, sometimes it gets in the way. It can be turned off by the `-n` option; in that case, only lines explicitly printed with a `p` command appear in the output. For example, `$ sed -n ' /pattern/p ,`

does what `grep` does. Since the matching condition can be inverted by following it with `!`,

```
$ sed -n ' /pattern/! p'
```

is `grep -v`. (So is `sed ' /pattern/d' .`) Why do we have both `sed` and `grep`? After all, `grep` is just a simple special case of `sed`. Part of the reason is history - `grep` came well before `sed`. But `grep` survives, and indeed thrives, because

for the particular job that they both do, it is significantly easier to use than sed is: it does the common case about as succinctly as possible. (It also does a few things that sed won't; look at the -b option, for instance.) Programs do die, however. There was once a program called gres that did simple substitution, but it expired almost immediately when sed was born. Newlines can be inserted with sed, using the same syntax as in ed: \$ sed 's/\$\n > /'

adds a newline to the end of each line, thus double-spacing its input, and \$ sed 's/

l[

]*/\n > /g'

replaces each string of blanks or tabs with a newline and thus splits its input into one word per line. (The regular expression '[....]' matches a blank or tab; '[....] *' matches zero or more of these, so the whole pattern matches one or more blanks and/or tabs.) You can also use pairs of regular expressions or line numbers to select a range of lines over which anyone of the commands will operate.

112 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

\$ sed '\$d'

Print only lines 20 through 30 Delete lines 1 through 10 (== ta i 1 + 11)
Delete up to and including first blank line Print each group of lines from an
empty line to line starting with end Delete last line

```
$ sed -n '20,30p' $ sed '1,10d' $ sed '1 , /A $/d' $ sed -n '/A$/,/Aend/p'
```

Line numbers go from the beginning of the input; they do not reset at the beginning of a new file. There is a fundamental limitation of sed that is not shared by ed, however: relative line numbers are not supported. In particular, + and - are not understood in line number expressions, so it is impossible to reach backwards in the input:

```
$ sed '$-1d' Unrecognized command: $-1d $
```

Illegal: can't refer backward

Once a line is read, the previous line is gone forever: there is no way to identify the next-to-last line, which is what this command requires. (In fairness, there is a way to handle this with sed, but it is pretty advanced. Look up the "hold" command in the manual.) There is also no way to do relative addressing forward:

```
$ sed '/thing/+1d'
```

Illegal: can't refer forward

sed provides the ability to write on multiple output files. For example, `$ sed -n ' /pat/w file 1 > /pat/! w file2' filenames... $`

writes lines matching `pat` on `file 1` and lines not matching `pat` on `file2`. Or, to revisit our first example, `$ sed 's/UNIX/UNIX(TM)/gw Ue out' filenames ... >output` writes the entire output to file `output` as before, but also writes just the changed lines to file `u. out`. Sometimes it's necessary to cooperate with the shell to get shell file arguments into the middle of a `sed` command. One example is the program `newer`, which lists all files in a directory that are newer than a specified one.

```
$ cat newer # newer f: list files newer than f
Is -t : sed ,/A'$1'$/q' $
```

The quotes protect the various special characters aimed at `sed`, while leaving the `$ 1` exposed so the shell will replace it by the filename. An alternate way to write the argument is

CHAPTER 4

FILTERS 113

```
a\ b label c\ d i\ 1 P q r file s/old/new/f
```

t label w file y / str 1/ str2 /

=

!cmd labe I

{

Table 4.2: Summary of sed Commands
append lines to output until one not ending in \
branch to command : label
change lines to following text as in a delete line;
read next input line
insert following text before next output list line,
making all non-printing characters visible
print line
quit
read file, copy contents to output
substitute new for old. If f g, replace all occurrences;
f p, print;
f w file, write to file
test: branch to label if substitution made to current line
write line to file
replace each character from str 1 with corresponding character from str2 (no ranges allowed)
print current input line number
do sed cmd only if line is not selected
set label for band t
commands treat commands up to matching } as a group

"/""\$1\\$/q"

since the \$ 1 will be replaced by the argument while the \
\$ becomes just \$.
In the same way, we can write older, which lists all the files older than the named one:

`$ cat older # older f: list files older than f Is -tr : sed '/1/q' $`

The only difference is the `-r` option on `1s`, to reverse the order. Although `sed` will do much more than we have illustrated, including testing conditions, looping and branching, remembering previous lines, and of course many of the `ed` commands described in Appendix 1, most of the use of `sed` is similar to what we have shown here - one or two simple editing commands - rather than long or complicated sequences. Table 4.2 summarizes some of `sed`'s capabilities, although it omits the multi-line functions. `sed` is convenient because it will handle arbitrarily long inputs, because it is fast, and because it is so similar to `ed` with its regular expressions and line-at-a-time processing. On the other side of the coin, however, `sed` provides a relatively limited form of memory (it's hard to remember text from one line to

114 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

another), it only makes one pass over the data, it's not possible to go backwards, there's no way to do forward references like `/... / + 1`, and it provides no facilities for manipulating numbers - it is purely a text editor. Exercise 4-5. Modify `older` and `newer` so they don't include the argument file in their output. Change them so the files are listed in the opposite order. 0 Exercise 4-6. Use `sed` to make `bundle` robust. Hint: in here documents, the end-marking word is recognized only when it matches the line exactly. 0

4.4 The awk pattern scanning and processing language Some of the limitations of sed are remedied by awk. The idea in awk is much the same as in sed, but the details are based more on the C programming language than on a text editor. Usage is just like sed:

```
$ awk 'program' filenames ...
```

but the program is different:

```
pattern { action } pattern { action }
```

awk reads the input in the filenames one line at a time. Each line is compared with each pattern in order; for each pattern that matches the line, the corresponding action is performed. Like sed, awk does not alter its input files. The patterns can be regular expressions exactly as in egrep, or they can be more complicated conditions reminiscent of C. As a simple example, though, `$ awk '/regular expression/ { print }' filenames ...`

does what egrep does: it prints every line that matches the regular expression. Either the pattern or the action is optional. If the action is omitted, the default action is to print matched lines, so

```
$ awk '/regular expression/' filenames ...
```

does the same job as the previous example. Conversely, if the pattern is omitted, then the action part is done for every input line. So `$ awk ' { print }' filenames...`

does what cat does, albeit more slowly. One final note before we get on to interesting examples. As with sed, it is possible to present the program to awk from a file: `$ awk -f cmdfile filenames...`

CHAPTER 4

FILTERS 115

Fields awk splits each input line automatically into fields, that is, strings of non-blank characters separated by blanks or tabs. By this definition, the output of who has five fields:

```
$ who you jim $
```

```
tty2 tty4
```

```
Sep 29 11:53 Sep 29 11:27
```

awk calls the fields \$1, \$ 2, ..., \$NF, where NF is a variable whose value is set to the number of fields. In this case, NF is 5 for both lines. (Note the difference between NF, the number of fields, and \$NF, the last field on the line. In awk, unlike the shell, only fields begin with a \$; variables are unadorned.) For example, to discard the file sizes produced by `du -a`, `$ du -a : awk '{ print $2 }'`

and to print the names of the people logged in and the time of login, one per line :

```
$ who: awk '{ print $1, $5 }' you 11:53 jim 11:27 $
```

To print the name and time of login sorted by time: `$ who: awk '{ print $5, $1 }' : sort` 11:27 jim 11:53 you \$

These are alternatives to the sed versions shown earlier in this chapter. Although awk is easier to use than sed for operations like these, it is usually slower, both getting started and in execution when there's a lot of input. awk normally assumes that white space (any number of blanks and tabs) separates fields, but the separator can be changed to any single character. One way is with the -F (upper case) command-line option. For example, the fields in the password file /etc/passwd are separated by colons: `$ sed 3q /etc/passwd` root:3DofHR5KoB.3s:0:1:S.User:/:
ken:y.68wd1.ijayz:6:1:K.Thompson:/usr/ken:
dmr:z4u3dJWbg7wCk:7:1:D.M.Ritchie:/usr/dmr: \$

To print the user names, which come from the first field,

CHAPTER 4

\$ sed 3q /etc/passwd : awk -F: '{ print \$1 }' root ken dmr \$ The handling of blanks and tabs is intentionally special. By default, both blanks and tabs are separators, and leading separators are discarded. If the separator is set to anything other than blank, however, then leading separators are counted in determining the fields. In particular, if the separator is a tab, then blanks are not separator characters, leading blanks are part of the field, and each tab defines a field.

Printing awk keeps track of other interesting quantities besides the number of input fields. The built-in variable NR is the number of the current input "record" or line. So to add line numbers to an input stream, use this: \$ awk '{ print NR, \$0 }'

The field \$ 0 is the entire input line, unchanged. In a print statement items separated by commas are printed separated by the output field separator, which is by default a blank. The formatting that print does is often acceptable, but if it isn't, you can use a statement called printf for complete control of your output. For example, to print line numbers in a field four digits wide, you might use the following:

```
$ awk ' { printf "%4d %s\n", NR, $0 }'
```

%4d specifies a decimal integer (NR) in a field four digits wide, %s a string of characters (\$0), and \n a newline character, since printf doesn't print any spaces or newlines automatically. The printf statement in awk is like the C function; see printf(3). We could have written the first version of ind (from early in this chapter)

as

```
awk '{ printf "\t%s\n", $0 }' $*
```

which prints a tab (\t) and the input record.

Patterns Suppose you want to look in /etc/passwd for people who have no pass- words. The encrypted password is the second field, so the program is just a pattern:

```
$ awk -F: ' $2 == "" , /etc/passwd
```

The pattern asks if the second field is an empty string (' == ' is the equality test

CHAPTER 4

FILTERS 117

operator). You can write this pattern in a variety of ways: `$2 == ""` 2nd field is empty `$2 ! ~ /A$/` 2nd field matches empty string `$2 ! ~ /e/` 2nd field doesn't match any character length `(length($2) == 0)` Length of 2nd field is zero The symbol `""` indicates a regular expression match, and `! ~` means "does not match." The regular expression itself is enclosed in slashes. `length` is an awk built-in function that produces the length of a string of characters. A pattern can be preceded by `!` to negate it, as in

```
!(",,:t 2 == "")
```

The `! ~` operator is like that in C, but opposite to `sed`, where the `!` follows the pattern. One common use of patterns in awk is for simple data validation tasks.

Many of these amount to little more than looking for lines that fail to meet some criterion; if there is no output, the data is acceptable ("no news is good news"). For example, the following pattern makes sure that every input record has an even number of fields, using the operator `%` to compute the remainder:

```
NF % 2 != 0
```

```
# print if odd number of fields
```

Another prints excessively long lines, using the built-in function `length`:
`length($0) > 72 # print if too long` awk uses the same comment convention as the shell does: a `#` marks the beginning of a comment. You can make the output somewhat more informative by printing a warning and part of the too-long line, using another built-in function, `substr`:

```
length($0) > 72 { print "Line", NR, "too long:", substr($0,1,60)
```

`substr (s , m, n)` produces the substring of `s` that begins at position `m` and is `n` characters long. (The string begins at position 1.) If `n` is omitted, the substring from `m` to the end is used. `substr` can also be used for extracting fixed-position fields, for instance, selecting the hour and minute from the output of `date`:
`$ date Thu Sep 29 12:17:01 EDT 1983 $ date / awk '{ print substr($4, 1, 5) }'` 12:17 \$

Exercise 4-7. How many awk programs can you write that copy input to output as `cat` does? Which is the shortest? 0

118 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

The `BEGIN` and `END` patterns awk provides two special patterns, `BEGIN` and `END`. `BEGIN` actions are performed before the first input line has been read; you can use the `BEGIN` pattern to initialize variables, to print headings or to set the field separator by assigning to the variable `FS`:

`$ awk 'BEGIN { FS = ":" } > $2 == "" , /etc/passwd $` No output: we all use passwords

END actions are done after the last line of input has been processed: `$ awk 'END { print NR }'` prints the number of lines of input.

Arithmetic and variables The examples so far have involved only simple text manipulation. awk's real strength lies in its ability to do calculations on the input data as well; it is easy to count things, compute sums and averages, and the like. A common use of awk is to sum columns of numbers. For example, to add up all the numbers in the first column: `{ s :: S + $1 } END { print s }`

Since the number of values is available in the variable NR, changing the last line to

```
END { print s, s/NR }
```

prints both sum and average. This example also illustrates the use of variables in awk. `s` is not a built-in variable, but one defined by being used. Variables are initialized to zero by default so you usually don't have to worry about initialization. awk also provides the same shorthand arithmetic operators that C does, so the example would normally be written `{ s += $1 } END { print s }` `S += $1` is the same as `s =: S + $1`, but notationally more compact. You can generalize the example that counts input lines like this:


```
{ nc += length($O) + 1 # number of chars, 1 for \n
nw += NF # number of
worp.s } END { print NR, nw, nc }
```

This counts the lines, words and characters in its input, so it does the same job as `wc` (although it doesn't break the totals down by file). As another example of arithmetic, this program computes the number of

CHAPTER 4

FILTERS 119

66-line pages that will be produced by running a set of files through `pr`. This can be wrapped up in a command called `prpages`:

```
$ cat prpages # prpages: compute number of pages that pr will print
wc $* :
awk 'II total$1 { n += int(($1+55)/56) } END { print n }'
```

\$

`pr` puts 56 lines of text on each page (a fact determined empirically). The number of pages is rounded up, then truncated to an integer with the built-in function `int`, for each line of `wc` output that does not match total at the end of a line.

\$ we eh4. oN- 753 3090 612 2421 637 2462 802 2986 50 213 2854 11172 \$
prpages eh4.oN- 53 \$

18129 13242 13455 16904 1117 62847

ch4.1 ch4.2 ch4.3 ch4.4 ch4.9 total

To verify this result, run pr into awk directly: \$ pr eh4.oN- : awk 'END {
print NR/66 }' 53 \$

Variables in awk also store strings of characters. Whether a variable is to be treated as a number or as a string of characters depends on the context. Roughly speaking, in an arithmetic expression like `s+=$1`, the numeric value is used; in a string context like `x=IV abe "`, the string value is used; and in an ambiguous case like `x>y`, the string value is used unless the operands are clearly numeric. (The rules are stated precisely in the awk manual.) String variables are initialized to the empty string. Coming sections will put strings to good use. awk itself maintains a number of built-in variables of both types, such as NR and FS. Table 4.3 gives the complete list. Table 4.4 lists the operators. Exercise 4-8. Our test of prpages suggests alternate implementations. Experiment to see which is fastest. D

Control flow It is remarkably easy (speaking from experience) to create adjacent dupli- cate words accidentally when editing a big document, and it is obvious that that almost never happens intentionally. To prevent such problems, one of the

120 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

FILENAME FS NF NR OFMT OFS ORS RS

Table 4.3: awk Built-in Variables

name of current input file field separator character (default blank & tab)
number of fields in input record number of input record output format for
numbers (default %g; see printf(3)) output field separator string (default
blank) output record separator string (default newline) input record
separator character (default newline)

Table 4.4: awk Operators (increasing order of precedence) = += -= *= /=
%= assignment; v op= expr is v = v op (expr) : : OR: expr1 I : expr2 true if
either is; expr2 not evaluated if expr1 is true && AND: expr1 && expr2 true
if both are; expr2 not evaluated if expr 1 is false negate value of expression
> > = < < = - - ! = - I - relational operators; - and I - are match and non-
match nothing string concatenation + - plus, minus * / % multiply, divide,
remainder + + increment, decrement (prefix or postfix)

the components of the Writer's Workbench family of programs, called
double, looks for pairs of identical adjacent words. Here is an implementa-
tion of double in awk:

eCHAPTER 4

FILTERS

121

```
$ cat double awk 'FILENAME != prevfile { NR = 1 prevfile = FILENAME
```

```
# new file # reset line number
```

```
} NF > 0 { if ($1 == lastword) printf "double %s, file %s, line  
%d\n",$1,FILENAME,NR for (i = 2; i <= NF; i++) if {$i == $(i-1)» printf  
"double %s, file %s, line %d\n",$i,FILENAME,NR i f (NF > 0) lastword =  
$NF
```

```
} ' $* $
```

The operator ++ increments its operand, and the operator -- decrements. The built-in variable FILENAME contains the name of the current input file. Since NR counts lines from the beginning of the input, we reset it every time the filename changes so an offending line is properly identified. The if statement is just like that in C: if (condition) statement]

else

statement2

If condition is true, then statement] is executed; if it is false, and if there is an else part, then statement2 is executed. The else part is optional. The for statement is a loop like the one in C, but different from the shell's:

for (expression]; condition; expression2) statement

The for is identical to the following while statement, which is also valid in awk:

```
expression] while ( condition) { statement expression2  
  
}
```

For example,

```
for (i = 2; i <= NF; i++)
```

runs the loop with *i* set in turn to 2, 3, ..., up to the number of fields, *NF*. The `break` statement causes an immediate exit from the enclosing `while`

122 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

or `for`; the `continue` statement causes the next iteration to begin (at condition in the `while` and `expression2` in the `for`). The next statement causes the next input line to be read and pattern matching to resume at the beginning of the `awk` program. The `exit` statement causes an immediate transfer to the `END` pattern.

Arrays `awk` provides arrays, as do most programming languages. As a trivial example, this `awk` program collects each line of input in a separate array element, indexed by line number, then prints them out in reverse order: `$ cat backwards # backwards: print input in backward line order awk' {line[NR] = $0 } END { for (i = NR; i > 0; i--) print line[i] } , $* $`

Notice that, like variables, arrays don't have to be declared; the size of an array is limited only by the memory available on your machine. Of course if a very large file is being read into an array, it may eventually run out of memory. To print the end of a large file in reverse order requires cooperation with `tail`:

```
$ tail -5 /usr/dict/web2 : backwards zymurgy zymotically zymotic  
zymosthenic zymosis $
```

tail takes advantage of a file system operation called seeking, to advance to the end of a file without reading the intervening data. Look at the discussion of lseek in Chapter 7. (Our local version of tail has an option -r that prints the lines in reverse order, which supersedes backwards.) Normal input processing splits each input line into fields. It is possible to perform the same field-splitting operation on any string with the built-in function split:

```
n = split(s, arr, sep)
```

. splits the string s into fields that are stored in elements 1 through n of the array arr. If a separator character sep is provided, it is used; otherwise the current value of FS is used. For example, split(\$0 ,a,":") splits the input line on colons, which is suitable for processing etc/passwd, and split ("9/29/83" , date, "/") splits a date on slashes.

CHAPTER 4

FILTERS 123

```
$ sed 1q /etc/passwd : awk '(split($0,a,":"); print a[1])' root $ echo 9/29/83  
: awk '(split($0,date,"/"); print date[3])' 83 $
```

Table 4.5 lists the awk built-in functions.

cos (expr) exp (expr) getline () index (s1 , s2) int(expr) length (s) log (expr) sin (expr) split(s,a,c) sprintf(ftnt, ...) substr (s, m, n)

Table 4.5: awk Built-in Functions

cosine of expr . If expr exponentia 0 expr: e reads next input line; returns 0 if end of file, 1 if not position of string s2 in s1; returns 0 if not present integer part of expr; truncates toward 0 length of string s natural logarithm of expr sine of expr split s into a [1] ...a [n] on character c; return n format ... according to specification fmt n-character substring of s beginning at position m

Associative arrays A standard problem in data processing is to accumulate values for a set of name-value pairs. That is, from input like Susie 400 John 100 Mary 200 Mary 300 John 100 Susie 100 Mary 100 we want to compute the total for each name: John 200 Mary 600 Susie 500

awk provides a neat way to do this, the associative array. Although one normally thinks of array subscripts as integers, in awk any value can be used as a subscript. So

```
{ sum[$1] += $2 } END { for {name in sum} print name, sum [name] }
```

IS the complete program for adding up and printing the sums for the name-

CHAPTER 4

value pairs like those above, whether or not they are sorted. Each name (\$1) is used as a subscript in sum; at the end, a special form of the for statement is used to cycle through all the elements of sum, printing them out. Syntactically, this variant of the for statement is

for (var in array) statement

Although it might look superficially like the for loop in the shell, it's unrelated. It loops over the subscripts of array, not the elements, setting var to each subscript in turn. The subscripts are produced in an unpredictable order, however, so it may be necessary to sort them. In the example above, the output can be piped into sort to list the people with the largest values at the top.

```
$ awk '...' : sort +1nr
```

The implementation of associative memory uses a hashing scheme to ensure that access to any element takes about the same time as to any other, and that (at least for moderate array sizes) the time doesn't depend on how many elements are in the array. The associative memory is effective for tasks like counting all the words in the input:

```
$ cat wordfreq awk' {for (i = 1; i <= NF; i++) num[$i]++ } END { for
(word in num) print word, num[word] }
```

```
, $* $ wordfreq ch4.* , sort +1 , sed 20q , 4 , -nr , , the 372 .cw 345 of 220
is 185 to 175 a 167 in 109 and 100 . P 1 94 .P2 94 .PP 90 $ 87 awk 87 sed
83 that 76 for 75 The 63 are 61 line 55 print 52 $
```

The first for loop looks at each word in the input line, incrementing the element of array num subscripted by the word. (Don't confuse awk's \$i, the i'th field of the input line, with any shell variables.) After the files have been read, the second for loop prints, in arbitrary order, the words and their counts. Exercise 4-9. The output from wordfreq includes text formatting commands like . cw, which is used to print words in this font. How would you get rid of such n,pn- words? How would you use tr to make wordfreq work properly regardless of the case of its input? Compare the implementation and performance of wordfreq to the pipeline from Section 4.2 and to this one: sed '5/[

```
]l
```

```
]*/\ /g' $* : sort : uniq -c : sort -nr
```

o

CHAPTER 4

Strings Although both sed and awk are used for tiny jobs like selecting a single field, only awk is used to any extent for tasks that really require programming. One example is a program that folds long lines to 80 columns. Any line that exceeds 80 characters is broken after the 80th; a \ is appended as a warning, and the residue is processed. The final section of a folded line is right-justified, not left-justified, since this produces more convenient output for program listings, which is what we most often use fold for. As an example, using 20-character lines instead of 80, \$ cat test A short line. A somewhat longer linee This line is quite a bit longer than the last one. \$ fold test A short line. A somewhat longer li\ nee This line is quite a\ bit longer than the\ last one.

\$

Strangely enough, the 7th Edition provides no program for adding or removing tabs, although pr in System V will do both. Our implementation of fold uses sed to convert tabs into spaces so that awk's character count is right. This works properly for leading tabs (again typical of program source) but does not preserve columns for tabs in the middle of a line. # fold: fold long lines sed 's/

/g' \$* : awk '

convert tabs to 8 spaces

BEGIN { N = 80 # folds at column 80 for (i = 1; i <= N; i++) # make a string of blanks blanks ::: blanks VI "

```

} { if (en = length{$O} <= N) print else { for (i ::: 1; n > N; n -::: N) {
printf "%s\\n", substr{$O,i,N) i += N;

```

```

} printf "%s%s\\n", substr{blanks,1,N-n), substr{$O,i)

```

```

}

```

```

} ,

```

In awk there IS no explicit string concatenation operator; strings are

126 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

concatenated when they are adjacent. Initially, blanks is a null string. The loop in the BEGIN part creates a long string of blanks by concatenation: each trip around the loop adds one more blank to the end of blanks. The second loop processes the input line in chunks until the remaining part is short enough. As in C, an assignment statement can be used as an expression, so the construction

if ((n == 1 length (\$ 0 » < :: N) ... assigns the length of the input line to n before testing the value. Notice the parentheses. Exercise 4-10. Modify fold so that it will fold lines at blanks or tabs rather than splitting a word. Make it robust for long words. D

Interaction with the shell Suppose you want to write a program field n that will print the n-th field from each line of input, so that you could say, for example, \$ who 1 field 1

to print only the login names. awk clearly provides the field selection capability; the main problem is passing the field number n to an awk program. Here is one implementation: awk '{ print '\$1' }'

The \$1 is exposed (it's not inside any quotes) and thus becomes the field number seen by awk. Another approach uses double quotes: awk "{ print \"'\$1' }"

In this case, the argument is interpreted by the shell, so the '\$ becomes a \$ and the \$1 is replaced by the value of n. We prefer the single-quote style because so many extra , 's are needed with the double-quote style in a typical awk program. A second example is addup n, which adds up the numbers in the n-th field: awk '{ s += \$1' } END { print s }'

A third example forms separate sums of each of n columns, plus a grand total:

FILTERS 127

```
awk ' BEGIN { n = '$1' } { for (i = 1; i <= n; i++) sum[i] += $i

} END {

for (i = 1; i <= n; i++) { printf "%6g ", sum[i] total += sum[i]

} printf "; total = %6g\n", total

} ,
```

We use a BEGIN to insert the value of n into a variable, rather than cluttering up the rest of the program with quotes. The main problem with all these examples is not keeping track of whether one is inside or outside of the quotes (though that is a bother), but that as currently written, such programs can read only their standard input; there is no way to pass them both the parameter n and an arbitrarily long list of filenames. This requires some shell programming that we'll address in the next chapter.

A calendar service based on awk Our final example uses associative arrays; it is also an illustration of how to interact with the shell, and demonstrates a bit about program evolution. The task is to have the system send you mail

every morning that contains a reminder of upcoming events. (There may already be such a calendar service; see `calendar(1)`. This section shows an alternate approach.) The basic service should tell you of events happening today; the second step is to give a day of warning - events of tomorrow as well as today. The proper handling of weekends and holidays is left as an exercise. The first requirement is a place to keep the calendar. For that, a file called `calendar` in `/usr/you` seems easiest.

```
$ cat calendar Sep 30 mother's birthday Oct 1 lunch with joe, noon Oct 1
meeting 4pm $
```

Second, you need a way to scan the calendar for a date. There are many choices here; we will use `awk` because it is best at doing the arithmetic necessary to get from "today" to "tomorrow," but other programs like `sed` or `egrep` can also serve. The lines selected from the calendar are shipped off by mail, of course. Third, you need a way to have calendar scanned reliably and automatically every day, probably early in the morning. This can be done with `at`, which we mentioned briefly in Chapter 1.

128 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

If we restrict the format of `calendar` so each line begins with a month name and a day as produced by `date`, the first draft of the calendar program is easy:

```
$ date Thu Sep 29 15:23:12 EDT 1983 $ cat bin/calendar # calendar:
version 1 -- today only awk <$HOME/calendar ' BEGIN { split("date",
date) } $1 == date[2] && $2 == date[3] , : mail $NAME $
```

The BEGIN block splits the date produced by date into an array; the second and third elements of the array are the month and the day. We are assuming that the shell variable NAME contains your login name. The remarkable sequence of quote characters is required to capture the date in a string in the middle of the awk program. An alternative that is easier to understand is to pass the date in as the first line of input:

```
$ cat bin/calendar # calendar: version 2 -- today only, no quotes (date; cat
$HOME/calendar) : awk ' NR == 1 { mon = $2; day = $3 } # set the date
NR > 1 && $1 == mon && $2 == day # print calendar lines , : mail
$NAME $
```

The next step is to arrange for calendar to look for tomorrow as well as today. Most of the time all that is needed is to take today's date and add 1 to the day. But at the end of the month, we have to get the next month and set the day back to 1. And of course each month has a different number of days. This is where the associative array comes in handy. Two arrays, days and nextmon, whose subscripts are month names, hold the number of days in the month and the name of the next month. Then days["Jan"] is 31, and nextmon["Jan"] is Feb. Rather than create a whole sequence of statements like

```
days["Jan"] = 31; nextmon["Jan"] = "Feb" days["Feb"] = 28;
nextmon["Feb"] = "Mar"
```


we will use split to convert a convenient data structure into the one really needed:

CHAPTER 4

FILTERS 129

```
$ cat calendar # calendar: version 3 -- today and tomorrow awk
<$HOME/calendar ' BEGIN { x = "Jan 31 Feb 28 Mar 31 Apr 30 May 31
Jun 30 " , "Jul 31 Aug 31 Sep 30 Oct 31 Nov 30 Dec 31 Jan 31" split(x,
data) for (i = 1; i < 24; i += 2) { days[data[i]] = data[i+1] nextmon[data[i]]
= data[i+2]

} split("date", date) mon1 = date[2]; day1 = date[3] mon2 = mon1; day2
= day1 + 1 if (day1 >= days[mon1]) { day2 = 1 mon2 = nextmon[mon1]

}

} $1 -- mon1 && $2 -- day1 I I $1 -- mon2 && $2 -- day2 , I mail $NAME
$
```

Notice that Jan appears twice in the data; a "sentinel" data value like this sim- plifies processing for December. The final stage is to arrange for the calendar program to be run every day. What you want is for someone to

wake up every morning at around 5 AM and run calendar. You can do this yourself by remembering to say (every day!) \$ at Sam calendar ctl-d \$

but that's not exactly automatic or reliable. The trick is to tell at not only to run the calendar, but also to schedule the next run as well.

```
$ cat early.morning calendar echo early.morning I at Sam $
```

The second line schedules another at command for the next day, so once started, this sequence is self-perpetuating. The at command sets your PATH, current directory and other parameters for the commands it processes, so you needn't do anything special. Exercise 4-11. Modify calendar so it knows about weekends: on Friday, "tomorrow" includes Saturday, Sunday and Monday. Modify calendar to handle leap years. Should calendar know about holidays? How would you arrange it? 0

130 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 4

Exercise 4-12. Should calendar know about dates inside a line, not just at the begin- ning? How about dates expressed in other formats, like 10/1/83? 0

Exercise 4-13. Why doesn't calendar use getname instead of \$NAME? 0

Exercise 4-14. Write a personal version of rm that moves files to a temporary directory rather than deleting them, with an at command to clean out the directory while you are sleeping. 0

Loose ends awk is an ungainly language, and it's impossible to show all its capabilities in a chapter of reasonable size. Here are some other things to look at in the manual: . Redirecting the output of print into files and pipes: any print or printf statement can be followed by > and a filename (as a quoted string or in a variable); the output will be sent to that file. As with the shell, » appends instead of overwriting. Printing into a pipe uses | instead of >. . Multi-line records: if the record separator RS is set to newline, then input records will be separated by an empty line. In this way, several input lines can be treated as a single record. . "Pattern, pattern" as a selector: as in ed and sed, a range of lines can be specified by a pair of patterns. This matches lines from an occurrence of the first pattern until the next occurrence of the second. A simple example is

NR == 10, NR == 20 which matches lines 10 through 20 inclusive.

4.5 Good files and good filters Although the last few awk examples are self-contained commands, many uses of awk are simple one- or two-line programs to do some filtering as part of a larger pipeline. This is true of most filters - sometimes the problem at hand can be solved by the application of a single filter, but more commonly it breaks down into subproblems solvable by filters joined together into a pipe- line. This use of tools is often cited as the heart of the UNIX programming environment. That view is overly restrictive; nevertheless, the use of filters pervades the system, and it is worth observing why it works. The output produced by UNIX programs is in a format understood as input by other programs. Filterable files contain lines of text, free of decorative headers, trailers or blank lines. Each line is an object of interest - a filename, a word, a description of a running process - so programs like wc and grep can count interesting items or search for them by name. When more information is present for each object, the file is still line-by-line, but columnated into fields separated by blanks or tabs, as in the output of ls -l. Given data

divided into such fields, programs like `awk` can easily select, process or rearrange the information.

CHAPTER 4

FILTERS 131

Filters share a common design. Each writes on its standard output the result of processing the argument files, or the standard input if no arguments are given. The arguments specify input, never output, so the output of a command can always be fed to a pipeline. Optional arguments (or non-filename arguments such as the `grep` pattern) precede any filenames. Finally, error messages are written on the standard error, so they will not vanish down a pipe. These conventions have little effect on the individual commands, but when uniformly applied to all programs result in a simplicity of interconnection, illustrated by many examples throughout this book, but perhaps most spectacularly by the word-counting example at the end of Section 4.2. If any of the programs demanded a named input or output file, required interaction to specify parameters, or generated headers and trailers, the pipeline wouldn't work. And of course, if the UNIX system didn't provide pipes, someone would have to write a conventional program to do the job. But there are pipes, and the pipeline works, and is even easy to write if you are familiar with the tools. Exercise 4-15. `ps` prints an explanatory header, and `1 s -1` announces the total number of blocks in the files. Comment.

History and bibliographic notes A good review of pattern matching algorithms can be found in the paper "Pattern matching in strings" (Proceedings of the Symposium on Formal Language Theory, Santa Barbara, 1979) by Al Aho, author of `egrep`. `sed` was designed and

implemented by Lee McMahon, using `ed` as a base. `awk` was designed and implemented by Al Aho, Peter Weinberger and Brian Kernighan, by a much less elegant process. Naming a language after its authors also shows a certain poverty of imagination. A paper by the implementors, "A WK - a pattern scanning and processing language," *Software- Practice and Experience*, July 1978, discusses the design. `awk` has its origins in several areas, but has certainly stolen good ideas from `SNOBOL4`, from `sed`, from a validation language designed by Marc Rochkind, from the language tools `yacc` and `lex`, and of course from `C`. Indeed, the similarity between `awk` and `C` is a source of problems - the language looks like `C` but it's not. Some constructions are missing; others differ in subtle ways. An article by Doug Comer entitled "The flat file system FFG: a database system consisting of primitives" (*Software-Practice and Experience*, November, 1982) discusses the use of the shell and `awk` to create a database system.

t An early UNIX file system was destroyed by a maintenance program that violated this rule, because a harmless-looking command scribbled all over the disc.

CHAPTER 5: SHELL PR

RA MING

Although most users think of the shell as an interactive command interpreter, it is really a programming language in which each statement runs a command. Because it must satisfy both the interactive and programming aspects of command execution, it is a strange language, shaped as much by history as by design. The range of its application leads to an unsettling quantity of detail in the language, but you don't need to understand every nuance to use it effectively. This chapter explains the basics of shell

programming by showing the evolution of some useful shell programs. It is not a manual for the shell. That is in the manual page `sh(1)` of the Unix Programmer's Manual, which you should have handy while you are reading. With the shell, as with most commands, the details of behavior can often be most quickly discovered by experimentation. The manual can be cryptic, and there is nothing better than a good example to clear things up. For that reason, this chapter is organized around examples rather than shell features; it is a guide to using the shell for programming, rather than an encyclopedia of its capabilities. We will talk not only about what the shell can do, but also about developing and writing shell programs, with an emphasis on testing ideas interactively. When you've written a program, in the shell or any other language, it may be helpful enough that other people on your system would like to use it. But the standards other people expect of a program are usually more rigorous than those you apply for yourself. A major theme in shell programming is therefore making programs robust so they can handle improper input and give helpful information when things go wrong.

5el Customizing the `cal` command One common use of a shell program is to enhance or to modify the user interface to a program. As an example of a program that could stand enhancement, consider the `cal(1)` command:

```
$ cal usage: cal [month] year Good so far $ cal october 1983 Bad argument
Not so good $ cal 10 1983 October 1983 5 M Tu W Th F 5 1 2 3 4 5 6 7 8 9
10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 $
```

It's a nuisance that the month has to be provided numerically. And, as it turns out, `cal 10` prints out the calendar for the entire year 10, rather than for the current October, so you must always specify the year to get a calendar for a single month. The important point here is that no matter what interface the `cal` command provides, you can change it without changing `cal` itself. You can place a command in your private `bin` directory that converts a more convenient argument syntax into whatever the real `cal` requires. You can even call your version `cal`, which means one less thing for you to remember. The first issue is design: what should `cal` do? Basically, we want `cal` to be reasonable. It should recognize a month by name. With two arguments, it should behave just as the old `cal` does, except for converting month names into numbers. Given one argument, it should print the month or year's calendar as appropriate, and given zero arguments, it should print the current month's calendar, since that is certainly the most common use of a `cal` command. So the problem is to decide how many arguments there are, then map them to what the standard `cal` wants. The shell provides a case statement that is well suited for making such decisions:

```
case word in pattern) commands, , pattern) commands, ,
```

```
esac
```

The case statement compares `word` to the patterns from top to bottom, and performs the commands associated with the first, and only the first, pattern that matches. The patterns are written using the shell's pattern matching rules, slightly generalized from what is available for filename matching.

Each action is terminated by the double semicolon ;;. (The ;; may be left off the last case but we often leave it in for easy editing.)

CHAPTER 5

SHELL PROGRAMMING

135

Our version of cal decides how many arguments are present, processes alphabetic month names, then calls the real cal. The shell variable \$# holds the number of arguments that a shell file was called with; other special shell variables are listed in Table 5.1.

```
$ cat cal # cal: nicer interface to /usr/bin/cal
```

```
case $# in 0) set 'date'; m=$2; y=$6 " 1) m=$1; set 'date'; y=$6 " *) m=$1;
y=$2 ;; esac
```

```
# no args: use today # 1 arg: use this year # 2 args: month and year
```

```
case $m in jan* Jan*) m=1 , , feb* Feb*) m=2 , , mar* Mar*) m=3 , , apr*
Apr*) m=4 , , may* May*) m=5 , , jun* Jun * ) m=6 , , jul* Jul*) m=7 , ,
```



```
aug*IAug*) m=8 , , sep*:Sep*) m=9 , , oct*:Oct*) m=10 , , nov*INov*)  
m=11 , , dec*:Dec*) m=12 , , [1-9]:10:11:12) , , # numeric month * )  
y=$m; m=uuuu , , # plain year
```

```
esac
```

```
/usr/bin/cal $m $y $
```

```
# run the real one
```

The first case checks the number of arguments, \$#, and chooses the appropriate action. The final "*" pattern in the first case is a catch-all: if the number of arguments is neither 0 nor 1, the last case will be executed. (Since patterns are scanned in order, the catch-all must be last.) This sets m and y to the month and year - given two arguments, our cal is going to act the same as the original. The first case statement has a couple of tricky lines containing

```
set 'date'
```

Although not obvious from appearance, it is easy to see what this statement does by trying it:

CHAPTER 5

`$# $* @$ $- $7 $$ $! $HOME $IFS $MAIL $PATH $PS1 $PS2`

Table 5e1: Shell Built-in Variables

the number of arguments all arguments to shell similar to `$*`; see Section 5.7 options supplied to the shell return value of the last command executed process-id of the shell process-id of the last command started with `&`. default argument for `cd` command list of characters that separate words in arguments file that, when changed, triggers "you have mail " message list of directories to search for commands prompt string, default `'$ '`, prompt string for continued command line, default `'> '`

```
$ date Sat Oct 1 06:05:18 EDT 1983 $ set 'date' $ echo $1 Sat $ echo $4
06:05:20 $
```

`set` IS a shell built-in command that does too many things. With no arguments, it shows the values of variables in the environment, as we saw in Chapter 3. Ordinary arguments reset the values of `$1`, `$2`, and so on. So `set`

`date`

sets `$1` to the day of the week, `$2` to the name of the month, and so on. The first case in `cal`, therefore, sets the month and year from the current date if there are no arguments; if there's one argument, it's used as the month and the year is taken from the current date. `aet` also recognizes several options,

of which the most often used are -v and -x; they turn on echoing of commands as they are being processed by the shell. These are indispensable for debugging complicated shell programs. The remaining problem is to convert the month, if it is in textual form, into a number. This is done by the second case statement, which should be largely self-explanatory. The only twist is that the ; character in case statement patterns, as in egrep, indicates an alternative: big I small matches either big or small. Of course, these cases could also be written as [jJ] an* and so on. The program accepts month names either in all lower case, because most commands accept lower case input, or with first letter capitalized, because that is the format printed by date. The rules for shell pattern matching are given in Table 5.2.

CHAPTER 5

SHELL PROGRAMMING 137

*

? [ccc]

II II

\.c a:b /

Table 5.2: Shell Pattern Matching Rules match any string, including the null string match any single character match any of the characters in ccc. [a-dO-3] is equivalent to [abcd0123] match... exactly; quotes protect special characters. Also ' match c literally in case expressions only, matches either a or b in filenames, matched only by an explicit / in the expression; in case, matched like any other character as the first character of a filename, is matched only by an explicit .. in the expression

,

The last two cases in the second case statement deal with a single argument that could be a year; recall that the first case statement assumed it was a month. If it is a number that could be a month, it is left alone. Otherwise, it is assumed to be a year. Finally, the last line calls /usr /bin/ cal (the real cal) with the converted arguments. Our version of cal works as a newcomer might expect:

```
$ date Sat Oct 1 06:09:55 EDT 1983 $ cal October 1983 S M Tu W Th F S
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28
29 30 31 $ cal dec December 1983 S M Tu W Th F S 1 2 3 4 5 6 7 8 9 10
11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 $
```

And cal 1984 prints out the calendar for all of 1984. Our enhanced cal program does the same job as the original, but in a simpler, easier-to-remember way. We therefore chose to call it cal, rather

CHAPTER 5

than calendar (which is already a command) or something less mnemonic like ncal. Leaving the name alone also has the advantage that users don't have to develop a new set of reflexes for printing a calendar. Before we leave the case statement, it's worth a brief comment on why the shell's pattern matching rules are different from those in ed and its derivatives. After all, two kinds of patterns means two sets of rules to learn and two pieces of code to process them. Some of the differences are simply bad choices that were never fixed - for example, there is no reason except compatibility with a past now lost that ed uses '.' and the shell uses '?' for "match any character." But sometimes the patterns do different jobs. Regular expressions in the editor search for a string that can occur anywhere in a line; the special characters ^ and \$ are needed to anchor the search to the beginning and end of the line. For filenames, however, we want the search anchored by default, since that is the most common case; having to write something like

```
$ Is A?*.C$
```

Doesn't work this way

instead of

```
$ Is *.c
```

would be a great nuisance. Exercise 5-1. If users prefer your version of cal, how do you make it globally accessible? What has to be done to put it in /usr/bin? 0 Exercise 5-2. Is it worth fixing cal so cal 83 prints the calendar for 1983? If so, how would you print the calendar for year 83? 0 Exercise 5-3. Modify cal to accept more than one month, as in

```
$ cal oct nov
```

or perhaps a range of months:

```
$ cal oct - dec
```

If it's now December, and you ask for cal jan, should you get this year's January or next year's? When should you have stopped adding features to cal? 0

5.2 Which command is which?

There are problems with making private versions of commands such as cal. The most obvious is that if you are working with Mary and type cal while logged in as mary, you will get the standard cal instead of the new one, unless of course Mary has linked the new cal into her bin directory. This can be confusing - recall that the error messages from the original cal are not very helpful - but is just an example of a general problem. Since the shell searches for commands in a set of directories specified by PATH, it is always possible to get a version of a command other than the one you

expect. For instance, if you type a command, say `echo`, the pathname of the file that is actually run could be `./echo` or `/bin/echo` or `/usr/bin/echo` or

CHAPTER 5

SHELL PROGRAMMING

139

something else, depending on the components of your `PATH` and where the files are. It can be very confusing if there happens to be an executable file with the right name but the wrong behavior earlier in your search path than you expect. Perhaps the most common is the `test` command, which we will discuss later: its name is such an obvious one for a temporary version of a program that the wrong test program gets called annoyingly often. A command that reports which version of a program will be executed would provide a useful service. One implementation is to loop over the directories named in `PATH`, searching each for an executable file of the given name. In Chapter 3, we used the `for` to loop over filenames and arguments. Here, we want a loop that says for `l` in each component of `PATH` do

if given name is in directory `i` print its full pathname

done

Because we can run any command inside backquotes "...", the obvious solution is to run sed over \$PATH, converting colons into spaces. We can test it out with our old friend echo: \$ echo \$PATH :/usr/you/bin:/bin:/usr/bin \$
echo \$PATH : sed

```
s:/ /g
```

```
/usr/you/bin /bin /usr/bin $ echo
```

```
echo $PATH : sed
```

```
s:/ /g
```

```
' /usr/you/bin /bin /usr/bin $
```

4 components

Only 3 printed!

Still only 3

There is clearly a problem. A null string in PATH is a synonym for ' '. Converting the colons in PATH to blanks is therefore not good enough - the information about null components will be lost. To generate the correct list of directories, we must convert a null component of PATH into a dot. The null component could be in the middle or at either end of the string, so it takes a little work to catch all the cases:

```
$ echo $PATH : sed
```



```
S/A:././
```

```
>
```

```
s/././g
```

```
> s:$././ > s:/ /g
```

```
. /usr/bin /bin /usr/bin $
```

We could have written this as four separate sed commands, but Since sed does the substitutions in order, one invocation can do it all.

t Later we will see how to avoid this problem in shell files, where test is usually used.

140 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

Once we have the directory components of PATH, the test(1) command we've mentioned can tell us whether a file exists in each directory. The test command is actually one of the clumsier UNIX programs. For example, test

-r file tests if file exists and can be read, and test -w file tests if file exists and can be written, but the 7th Edition provides no test -x (although the System V and other versions do) which would otherwise be the one for us. We'll settle for test -f, which tests that the file exists and is not a directory, in other words, is a regular file. You should look over the manual page for test on your system, however, since there are several versions in circulation. Every command returns an exit status - a value returned to the shell to indicate what happened. The exit status is a small integer; by convention, 0 means "true" (the command ran successfully) and non-zero means "false" (the command ran unsuccessfully). Note that this is opposite to the values of true and false in C. Since many different values can all represent "false," the reason for failure is often encoded in the "false" exit status. For example, grep returns 0 if there was a match, 1 if there was no match, and 2 if there was an error in the pattern or filenames. Every program returns a status, although we usually aren't interested in its value. test is unusual because its sole purpose is to return an exit status. It produces no output and changes no files. The shell stores the exit status of the last program in the variable \$?:

```
$ cmp /usr/you/.profile /usr/you/.profile $ No output; they're the same $
echo $? 0 Zero implies ran O.K.: files identical $ cmp /usr/you/.profile
/usr/mary/.profile /usr/you/.profile /usr/mary/.profile differ: char 6, line 3 $
echo $? 1 Non-zero means files were different $
```

A few commands, such as cmp and grep, have an option -s that causes them to exit with an appropriate status but suppress all output. The shell's if statement runs commands based on the exit status of a command, as in if command then

commands if condition true

else

commands if condition false

fi

The location of the newlines is important: fi, then and else are recognized only after a newline or a semicolon. The e l s e part is optional. The if statement always runs a command - the condition - whereas the

CHAPTER 5

SHELL PROGRAMMING

141

case statement does pattern matching directly in the shell. In some UNIX versions, including System V, test is a shell built-in function so an if and a test will run as fast as a case. If test isn't built in, case statements are more efficient than if statements, and should be used for any pattern matching:

case "\$1" in hello) command esac

will be faster than

if test "\$1" = hello then

Slower unless test is a shell built-in

command

fi

That is one reason why we sometimes use case statements in the shell for testing things that would be done with an if statement in most programming languages. A case statement, on the other hand, can't easily determine whether a file has read permissions; that is better done with a test and an if. So now the pieces are in place for the first version of the command which, to report which file corresponds to a command: \$ cat which # which cmd: which cmd in PATH is executed, version 1

```
case $# in 0) echo 'Usage: which command' 1>&2; exit 2 esac
for i in `echo $PATH : sed 'S/A:/./'`
```

```
s/ : /./ :/g
```

```
s/ : $/ : . / s:/ /g"
```

```
do
```

```
if test -f $i/$1 then
```

```
# use test -x if you can
```

```
echo $i/$1 exit 0
```

```
# found it
```

```
fi
```

```
done exit 1 $
```

```
# not found
```

Let's test it:

142 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

```
$ cx which $ which which ./which $ which ed /bin/ed $ mv which  
/usr/you/bin $ which which /usr/you/bin/which $
```

Make it executable

The initial case statement is just error-checking. Notice the redirection 1 >&2 on the echo so the error message doesn't vanish down a pipe. The shell built-in command `exit` can be used to return an exit status. We wrote `exit 2` to return an error status if the command didn't work, `exit 1` if it couldn't find the file, and `exit 0` if it found one. If there is no explicit `exit` statement, the exit status from a shell file is the status of the last command executed. What happens if you have a program called `test` in the current directory? (We're assuming that `test` is not a shell built-in.)

```
$ echo 'echo hello' >test $ cx test $ which which hello ./which $
```

Make a fake test Make it executable Try which now Fails!

More error-checking is called for. You could run `which` (if there weren't a test in the current directory!) to find out the full pathname for `test`, and specify it explicitly. But that is unsatisfactory: `test` may be in different directories on different systems, and `which` also depends on `sed` and `echo`, so we should specify their pathnames too. There is a simpler solution: fix `PATH` in the shell file, so it only looks in `/bin` and `/usr/bin` for commands. Of course, for the `which` command only, you have to save the old `PATH` for determining the sequence of directories to be searched.

CHAPTER 5

SHELL PROGRAMMING

143

\$ cat `which` # `which` cmd: which cmd in `PATH` is executed, final version

```
opath=$PATH PATH=/bin:/usr
```

```
/bin
```

```
case $# in 0) echo 'Usage: which command' 1>&2; exit 2 esac
for i in `echo $opath : sed 'S/A:/./ s/: :/./ :/g s:/$/: ./ s:/ /g'`
```

```
do
```

```
if test -f $i/$1 then
```

```
# this is /bin/test I or /usr/bin/test only
```

```
echo $i/$1 exit 0
```

```
# found it
```

```
fi
```

```
done exit 1 $
```

```
# not found
```

which now works even if there is a spurious test (or sed or echo) along the search path. \$ ls -l test -rwxrwxrwx 1 you \$ which which /usr/bin/which \$ which test ./test \$ rm test \$ which test /bin/test \$

11 Oct 1 06:55 test

Still there

The shell provides two other operators for combining commands, `:` and `&&`, that are often more compact and convenient than the `if` statement. For example, `:` can replace some `if` statements: `test -f filename || echo file filename does not exist`

is equivalent to `if test ! -f filename then`

The `!` negates the condition

`echo file filename does not exist`

`fi`

The operator `::`, despite appearances, has nothing to do with pipes - it IS a

144 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

conditional operator meaning OR. The command to the left of `::` is executed. If its exit status is zero (success), the command to the right of `::` is ignored. If the left side returns non-zero (failure), the right side is executed and the value of the entire expression is the exit status of the right side. In other words, `::` is a conditional OR operator that does not execute its right-hand command if the left one succeeds. The corresponding `&&` conditional is AND; it executes its right-hand command only if the left one succeeds. Exercise 5-4. Why doesn't `which` reset `PATH` to `opath` before exiting? 0 Exercise 5-5. Since the shell uses `esac` to terminate a case, and `fi` to terminate an `if`, why does it use `done` to terminate a `do`? 0 Exercise 5-6. Add an option `-a` to `which` so it prints all files in `PATH`, rather than quitting after the first. Hint: `ma tch= ' exit to'`. 0 Exercise 5-7. Modify `which` so it knows about shell built-ins like `exit`. 0 Exercise 5-8. Modify `which` to check for execute permissions on the files. Change it to print an error message when a file cannot be found. 0

5.3 while and until loops: watching for things In Chapter 3, the `for` loop was used for a number of simple iterative programs. Usually, a `for` loop over a set of filenames, as in `'for i in "*" . c'`, or all the arguments to a shell program, as in `'for i in "$@"'`. But shell loops are more general than these idioms would suggest; consider the `for` loop in `which`. There are three loops: `for`, `while` and `until`. The `for` is by far the most commonly used. It executes a set of commands - the loop body - once for each element of a set of words. Most often these are just filenames. The `while` and `until` use the exit status from a command to control the execution of the commands in the body of the loop. The loop body is executed until the condition command returns a non-zero status (for the `while`) or zero (for the `until`). `while` and `until` are identical except for the interpretation of the exit status of the command. Here are the basic forms of each loop: `for i in list of words do`

loop body, `$i` set to successive elements of list

done
for i do
done

(List is implicitly all arguments to shell file, i. e., \$ *)

loop body, \$ i set to successive arguments

CHAPTER 5

SHELL PROGRAMMING

145

while command do

loop body executed as long as command returns true

done

until command do

loop body executed as long as command returns false

done

The second form of the for, in which an empty list implies \$*, is a convenient shorthand for the most common usage. The conditional command that controls a while or until can be any command. As a trivial example, here is a while loop to watch for someone (say Mary) to log in:

```
while sleep 60 do
```

```
who : grep mary
```

```
done
```

The sleep, which pauses for 60 seconds, will always execute normally (unless interrupted) and therefore return "success," so the loop will check once a minute to see if Mary has logged in. This version has the disadvantage that if Mary is already logged in, you must wait 60 seconds to find out. Also, if Mary stays logged in, you will be told about her once a minute. The loop can be turned inside out and written with an until, to provide the information once, without delay, if Mary is on now:

```
until who : grep mary do
```

```
sleep 60
```

```
done
```

This is a more interesting condition. If Mary is logged in, 'who I grep mary' prints out her entry in the who listing and returns "true," because grep returns a status to indicate whether it found something, and the exit status of a pipeline is the exit status of the last element. Finally, we can wrap up this command, give it a name and install it:

146 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

```
$ cat watchfor # watchfor: watch for someone to log in
```

```
PATH=/bin:/usr/bin
```

```
case $# in 0) echo 'Usage: watchfor person' 1>&2; exit 1 esac
```

```
until who : egrep "$1" do
```

sleep 60

```
done $ ex watchfor $ watchfor you you ttyO Oct 1 08:01 $ mv watchfor  
/usr/you/bin $
```

It works Install it

We changed grep to egrep so you can type

```
$ watchfor 'joe/mary'
```

to watch for more than one person. As a more complicated example, we could watch all people logging in and out, and report as people come and go - a sort of incremental who. The basic structure is simple: once a minute, run who, compare its output to that from a minute ago, and report any differences. The who output will be kept in a file, so we will store it in the directory /tmp. To distinguish our files from those belonging to other processes, the shell variable \$\$ (the process id of the shell command), is incorporated into the filenames; this is a common convention. Encoding the command name in the temporary files is done mostly for the system administrator. Commands (including this version of watchwho) often leave files lying around in /tmp, and it's nice to know which command is doing it.

CHAPTER 5

SHELL PROGRAMMING

147

\$ cat watchwho # watchwho: watch who logs in and out

PATH=/bin:/usr/bin new=/tmp/wwho1.\$\$ old=/tmp/wwho2.\$\$ >\$old #
create an empty file

while do

loop forever

done

who >\$new diff \$old \$new mv \$new \$old sleep 60 awk '/>/ { \$1 = "in: /</ {
\$1 = "out:

"; print} "; print }'

\$

" :" is a shell built-in command that does nothing but evaluate its arguments and return "true." Instead, we could have used the command true, which merely returns a true exit status. (There is also a false command.) But ':' is more efficient than true because it does not execute a command from the file system. diff output uses < and > to distinguish data from the two files; the awk program processes this to report the changes in an easier-to-understand format. Notice that the entire while loop is piped into awk, rather than running a fresh awk once a minute. sed is unsuitable for this processing, because its output is always behind its input by one line: there is always a line of input that has been processed but not printed, and this would introduce an unwanted delay. Because old is created empty, the first output from watchwho is a list of all users currently logged in. Changing the command that initially creates old to who >\$old will cause watchwho to print only the changes; it's a matter of taste. Another looping program is one that watches your mailbox periodically; whenever the mailbox changes, the program prints "You have mail." This is a useful alternative to the shell's built-in mechanism using the variable MAIL. We have implemented it with shell variables instead of files, to illustrate a different way of doing things.

148 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

\$ cat checkmail # checkmail: watch mailbox for growth

PATH=/bin:/usr/bin MAIL=/usr/spool/mail/'getname' # system dependent


```
t=${1-60}
```

```
x=""ls -l $MAIL" while do
```

```
y=""ls -l $MAIL" echo $x $y x="$y" sleep $t done awk 'NF < 12 { print  
"You have mail" }' $
```

We have used `awk` again, this time to ensure that the message is printed only when the mailbox grows, not merely when it changes. Otherwise, you'll get a message right after you delete mail. (The shell's built-in version suffers from this drawback.) The time interval is normally set to 60 seconds, but if there is a parameter on the command line, as in `$ checkmail 30`

that is used instead. The shell variable `t` is set to the time if one is supplied, and to 60 if no value was given, by the line `t=${1-60}`. This introduces another feature of the shell. `${var}` is equivalent to `$var`, and can be used to avoid problems with variables inside strings containing letters or numbers:
`$ var=hello $ varx=goodbye $ echo $var hello $ echo $varx goodbye $ echo
${var}x hellox $`

Certain characters inside the braces specify special processing of the variable. If the variable is undefined, and the name is followed by a question mark, then the string after the `?` is printed and the shell exits (unless it's interactive). If the message is not provided, a standard one is printed:

```
$ echo $ {var?} hello $ echo ${junk?} junk: parameter not set $ echo  
${junk?error!} junk: error! $
```

CHAPTER 5

SHELL PROGRAMMING

149

O.K.; var is set

Default message

Message provided

Note that the message generated by the shell always contains the name of the undefined variable. Another form is `${var-thing}` which evaluates to `$var` if it is defined, and `thing` if it is not. `${var=thing}` is similar, but also sets `$var` to `thing`:

```
$ echo ${junk-'Hi there'} Hi there $ echo ${junk?} junk: parameter not set  
$ echo ${junk='Hi there'} Hi there $ echo ${junk?} Hi there $
```

junk unaffected

junk set to Hi there

The rules for evaluating variables are given in Table 5.3. Returning to our original example, `t=${1-60}`

sets `t` to `$ 1`, or if no argument is provided, to `60`.

Table 503: Evaluation of Shell Variables

`$var ${var} ${var-thing}`

`${var=thing}`

`${var?message}`

`${var+thing}`

value of var; nothing if var undefined same; useful if alphanumerics follow variable name value of var if defined; otherwise thing. \$var unchanged. value of var if defined; otherwise thing. If undefined, \$var set to thing if defined, \$var. Otherwise, print message and exit shell. If message empty, print: var: parameter not set thing if \$var defined, otherwise nothing

Exercise 5-9. Look at the implementation of true and false in /bin or /usr/bin. (How would you find out where they are?) 0 Exercise 5-10. Change watchfor so that multiple arguments are treated as different

150 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

people, rather than requiring the user to type ' joe : mary'. 0 Exercise 5-11. Write a version of watchwho that uses conun instead of awk to compare the old and new data. Which version do you prefer? 0 Exercise 5-12. Write a version of watchwho that stores the who output in shell vari- ables instead of files. Which version do you prefer? Which version runs faster? Should watchwho and checkmail do & automatically? 0 Exercise 5-13. What is the difference between the shell : do-nothing command and the # comment character? Are both needed? 0

5.4 Traps: catching interrupts If you hit DEL or hang up the phone while watchwho is running, one or two temporary files are left in /tmp. watchwho should remove the temporary files before it exits. We need a way to detect when such events happen, and a way to recover. When you type DEL, an interrupt signal is sent to all the processes that you are running on that

terminal. Similarly, when you hang up, a hang up signal is sent. There are other signals as well. Unless a program has taken explicit action to deal with signals, the signal will terminate it. The shell protects programs run with `&` from interrupts but not from hangups. Chapter 7 discusses signals in detail, but you needn't know much to be able to handle them in the shell. The shell built-in command `trap` sets up a sequence of commands to be executed when a signal occurs: `trap sequence-of-commands list of signal numbers`

The `sequence-of-commands` is a single argument, so it must almost always be quoted. The signal numbers are small integers that identify the signal. For example, 2 is the signal generated by pressing the DEL key, and 1 is generated by hanging up the phone. The signal numbers most often useful to shell programmers are listed in Table 5.4.

Table 5.4: Shell Signal Numbers
0 shell exit (for any reason, including end of file)
1 hangup
2 interrupt (DEL key)
3 quit (ctl- \; causes program to produce core dump)
9 kill (cannot be caught or ignored)
15 terminate, default signal generated by `kill(1)`

So to clean up the temporary files in `watchwho`, a trap can should go just before the loop, to catch hangup, interrupt and terminate:

CHAPTER 5

SHELL PROGRAMMING

```
trap 'rm -f $new $old; exit 1' 1 2 15
```

while :

The command sequence that forms the first argument to trap is like a subroutine call that occurs immediately when the signal happens. When it finishes, the program that was running will resume where it was unless the signal killed it. Therefore, the trap command sequence must explicitly invoke `exit`, or the shell program will continue to execute after the interrupt. Also, the command sequence will be read twice: once when the trap is set and once when it is invoked. Therefore, the command sequence is best protected with single quotes, so variables are evaluated only when the trap routines are executed. It makes no difference in this case, but we will see one later in which it matters. By the way, the `-f` option tells `rm` not to ask questions. `trap` is sometimes useful interactively, most often to prevent a program from being killed by the hangup signal generated by a broken phone connection:

```
$ (trap " 1; long-running-command" & 2134 $
```

The null command sequence means "ignore interrupts" in this process and its children. The parentheses cause the trap and command to be run together in a background sub-shell; without them, the trap would apply to the login shell as well as to `long-running-command`. The `nohup(1)` command is a short shell program to provide this service. Here is the 7th Edition version, in its entirety:

```
$ cat 'which nohup' trap "" 1 15 if test -t 2>&1 then
```

```
echo "Sending output to 'nohup.out'" exec nice -5 $* »nohup.out 2>&1
```

```
else
```

```
exec nice -5 $* 2>&1
```

```
fi $
```

test -t tests whether the standard output is a terminal, to see if the output should be saved. The background program is run with nice to give it a lower priority than interactive programs. (Notice that nohup doesn't set PATH. Should it?) The exec is just for efficiency; the command would run just as well without it. exec is a shell built-in that replaces the process running this shell

152 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

by the named program, thereby saving one process - the shell that would normally wait for the program to complete. We could have used `exec` in several other places, such as at the end of the enhanced `cal` program when it invokes `/usr/bin/cal`. By way, the signal 9 is one that can't be caught or ignored: it always kills. From the shell, it is sent as `$ kill -9 process id ...` kill - 9 is not the default because a process killed that way is given no chance to put its affairs in order before dying. Exercise 5-14. The version of `nohup` above combines the standard error of the command with the standard output. Is this a good design? If not, how would you separate them cleanly? 0 Exercise 5-15. Look up the `times` shell built-in, and add a line to your `.profile` so that when you log off the shell prints out how much CPU time you have used. 0 Exercise 5-16. Write a program that will find the next available user-id in `/etc/passwd`. If you are enthusiastic (and have permission), make it into a command that will add a new user to the system. What permissions does it need? How should it handle interrupts? 0

5.5 Replacing a file: overwrite The `sort` command has an option `-o` to overwrite a file: `$ sort file1 -o file2`

is equivalent to `$ sort file1 >file2`

If file 1 and file2 are the same file, redirection with `>` will truncate the input file before it is sorted. The `-o` option, however, works correctly, because the input is sorted and saved in a temporary file before the output file is created. Many other commands could also use a `-o` option. For example, `sed` could edit a file in place:

```
$ sed 's/UNIX/UNIX(TM)/g' ch2 -o ch2
```


Doesn't work this way!

It would be impractical to modify all such commands to add the option. Furthermore, it would be bad design: it is better to centralize functions, as the shell does with the > operator. We will provide a program overwrite to do the job. The first design is like this: \$ sed 's/UNIX/UNIX(TM)/g' ch2 1 overwrite ch2

The basic implementation is straightforward - just save away the input until end of file, then copy the data to the argument file:

CHAPTER 5

SHELL PROGRAMMING

153

overwrite: # version 1.

copy standard input to output after EOF BUG here

PATH=/bin:/usr/bin

```
$# in
```

```
case 1 ) * ) esac
```

```
, ,
```

```
echo 'Usage: overwrite file' 1>&2; exit 2
```

```
new=/tmp/overwr.$$ trap 'rm -f $new; exit l' 1 2 15
```

```
cat >$new cp $new $1 rm -f $new
```

```
# collect the input # overwrite the input file
```

cp is used instead of mv so the permissions and owner of the output file aren't changed if it already exists. Appealingly simple as this version is, it has a fatal flaw: if the user types DEL during the cp, the original input file will be ruined. We must prevent an interrupt from stopping the overwriting of the input file:

```
# overwrite: # version 2.
```

copy standard input to output after EOF BUG here too

PATH=/bin:/usr/bin

\$# in

case 1) *) esac

, ,

echo 'Usage: overwrite file' 1>&2; exit 2

new=/tmp/overwr1.\$\$ old=/tmp/overwr2.\$\$ trap 'rm -f \$new \$old; exit 1' 1
2 15

cat >\$new cp \$1 \$old

collect the input # save original file

trap " 1 2 15 cp \$new \$1

```
# we are committed; ignore signals # overwrite the input file
```

```
rm -f $new $old
```

If a DEL happens before the original file is touched, then the temporary files are removed and the file is left alone. After the backup is made, signals are ignored so the last cp won't be interrupted - once the cp starts, overwrite is committed to changing the original file.

154 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

There is still a subtle problem. Consider:

```
$ sed 's/UNIX/UNIX(TM)g' precious : overwrite precious command  
garbled: s/UNIX/UNIX(TM)g $ 1s -1 precious -rw-rw-rw- 1 you 0 Oct 1  
09: 02 precious #$$%@*! $
```

If the program providing input to overwrite gets an error, its output will be empty and overwrite will dutifully and reliably destroy the argument file. A number of solutions are possible. overwrite could ask for confirmation before replacing the file, but making overwrite interactive would negate

much of its merit. overwrite could check that its input is non-empty (by test -z), but that is ugly and not right, either: some output might be generated before an error is detected. The best solution is to run the data-generating program under overwrite's control so its exit status can be checked. This is against tradition and intuition - in a pipeline, overwrite would normally go at the end. But to work properly it must go first. overwrite produces nothing on its standard output, however, so no generality is lost. And its syntax isn't unheard of: time, nice and nohup are all commands that take another command as arguments. Here is the safe version:

```
# overwrite: copy standard input to output after EOF # final version
```

```
opath=$PATH PATH=/bin:/usr/bin
```

```
case $# in 0:1) echo 'Usage: overwrite file cmd [args]' 1>&2; exit 2 esac
```

```
file=$1; shift new=/tmp/overwr1.$$; old=/tmp/overwr2.$$ trap 'rm -f $new $old; exit 1' 1 2 15 # clean up files
```

```
if PATH=$opath "$@" >$new # collect input then
```

```
cp $file $old trap " 1 2 15 cp $new $file
```

```
# save original file # we are committed; ignore signals
```

else

echo "overwrite: \$1 failed, \$file unchanged" 1>&2 exit 1

fi rm -f \$new \$old

CHAPTER 5

SHELL PROGRAMMING

155

The shell built-in command `shift` moves the entire argument list one position to the left: `$ 2` becomes `$1`, `$ 3` becomes `$ 2`, etc. `"$@"` provides all the arguments (after the shift), like `$ *`, but uninterpreted; we'll come back to it in Section 5.7. Notice that `PATH` is restored to run the user's command; if it weren't, commands that were not in `/bin` or `/usr /bin` would be inaccessible to `overwrite`. `overwrite` now works (if somewhat clumsily):

```
$ cat notice UNIX is a Trademark of Bell Laboratories $ overwrite notice
sed 'S/UNIXUNIX(TM)/g' notice command garbled: s/UNIXUNIX(TM)/g
overwrite: sed failed, notice unchanged $ cat notice UNIX is a Trademark
of Bell Laboratories Unchanged $ overwrite notice sed
```

's/UNIX/UNIX(TM)/g' notice \$ cat notice UNIX(TM) is a Trademark of Bell Laboratories \$

Using sed to replace all occurrences of one word with another is a common thing to do. With overwr i te in hand, a shell file to automate the task is easy:

\$ cat replace # replace: replace str1 in files with str2, in place

PATH=/bin:/usr/bin

case \$# in 0:1:2) echo 'Usage: replace str1 str2 files' 1>&2; exit 1 esac

left="\$1"; right="\$2"; shift; shift

for i do

overwrite \$i sed "s@\$left@\$right@g" \$i

done \$ cat footnote UNIX is not an acronym \$ replace UNIX Unix footnote
\$ cat footnote Unix is not an acronym \$

(Recall that if the list on a for statement is empty, it defaults to \$ '*.) We used @ instead of / to delimit the substitute command, since @ is somewhat less likely to conflict with an input string.

156 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

replace sets PATH to /bin: /usr /bin, excluding \$HOME/bin. This means that overwrite must be in /usr/bin for replace to work. We made this assumption for simplicity; if you can't install overwr i te in /usr/bin, you will have to put \$HOME/bin in PATH inside replace, or give overwrite's pathname explicitly. From now on, we will assume that the commands we are writing reside in /usr /bin; they are meant to. Exercise 5-17. Why doesn't overwri te use signal code 0 in the trap so the files are removed when it exits? Hint: Try typing DEL while running the following program:

```
trap "echo exiting; exit 1" 0 2 sleep 10
```

o Exercise 5-18. Add an option -v to replace to print all changed lines on /dev/tty. Strong hint: s/\$left/\$right/g\$vflag. 0 Exercise 5-19. Fix replace so it works regardless of the characters in the substitution strings. 0 Exercise 5-20. Can replace be used to change the variable i to index everywhere in a program? How could you change things to make this work? 0 Exercise 5-21. Is replace convenient and powerful enough to belong in /usr/bin? Is it preferable to simply typing the correct sed commands when needed? Why or why not? 0 Exercise 5-22. (Hard)

\$ overwrite file 'who: sort'

doesn't work. Explain why not, and fix it. Hint: see eval in sh(1). How does your solution affect the interpretation of metacharacters in the command? 0

5.6 zap: killing processes by name The kill command only terminates processes specified by process-id. When a specific background process needs to be killed, you must usually run ps to find the process-id and then laboriously re-type it as an argument to kill. But it's silly to have one program print a number that you immediately transcribe manually to another. Why not write a program, say zap, to automate the job? One reason is that killing processes is dangerous, and care must be taken to kill the right processes. A safeguard is always to run zap interactively, and use pick to select the victims. A quick reminder about pick: it prints each of its arguments in turn and asks the user for a response; if the response is y, the argument is printed. (pick is the subject of the next section.) zap uses pick to verify that the processes chosen by name are the ones the user wants to kill:

CHAPTER 5

SHELL PROGRAMMING

```
$ cat zap # zap pattern: kill all processes matching pattern # BUG in this version
```

```
PATH=/bin:/usr/bin
```

```
case $# in 0) echo 'Usage: zap pattern' 1>&2; exit 1 esac
```

```
kill `pick `ps -ag : grep "$*"` : awk '{print $1}' $
```

Note the nested backquotes, protected by backslashes. The awk program selects the process-id from the ps output selected by the pick: \$ sleep 1000 &. 22126 \$ ps -ag PID TTY TIME CMD

```
22126 0 0:00 sleep 1000
```

```
$ zap sleep 22126 07 q What's going on? $
```

The problem is that the output of ps is being broken into words, which are seen by pick as individual arguments rather than being processed a line at a time. The shell's normal behavior is to break strings into arguments at blank/non-blank boundaries, as in

```
for i in 1 2 3 4 5
```

In this program we must control the shell's division of strings into arguments, so that only newlines separate adjacent "words." The shell variable IFS (internal field separator) is a string of characters that separate words in argument lists such as backquotes and for statements. Normally, IFS contains a blank, a tab and a newline, but we can change it to anything useful, such as just a newline:

158 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

```
$ echo 'echo $#' >nargs $ cx nargs $ who you ttyO pjw tty2 $ nargs 'who' 10  
$ IFS=''
```

Oct Oct

1 05:59 1 11:26

Ten blank and newline-separated fields

,

Just a newline

```
$ nargs 'who' 2 $
```

Two lines, two fields

With IFS set to newline, zap works fine:

```
$ cat zap # zap pat: kill all processes matching pat # final version
```

```
PATH=/bin:/usr/bin IFS='
```

```
,
```

```
# just a newline
```

```
case $1 " " ) -*) esac
```

```
in echo 'Usage: zap [-2] pattern' 1>&2; exit 1 " SIG=$1; shift
```

```
echo' PID TTY TIME CMD' kill $SIG 'pick \ps -ag : egrep "$*"\' $ ps -ag  
PID TTY TIME CMD
```

```
awk '{print $1}'
```

```
22126 0
```

```
0:00 sleep 1000
```

```
$ zap sleep PID TTY TIME CMD 22126 0 0:00 sleep 1000? y 23104 0 0:02  
egrep sleep? n $
```

We added a couple of wrinkles: an optional argument to specify the signal (note that SIG will be undefined, and therefore treated as a null string if the argument is not supplied) and the use of egrep instead of grep to permit more complicated patterns such as 'sleep: date'. An initial echo prints out the column headers for the ps output. You might wonder why this command is called zap instead of just ki 11. The main reason is that, unlike our cal example, we aren't really providing a new kill command: zap is necessarily interactive, for one thing - and we want to retain kill for the real one. zap is also annoyingly slow - the

CHAPTER 5

SHELL PROGRAMMING

overhead of all the extra programs is appreciable, although `ps` (which must be run anyway) is the most expensive. In the next chapter we will provide a more efficient implementation. Exercise 5-23. Modify `zap` to print out the `ps` header from the pipeline so that it is insensitive to changes in the format of `ps` output. How much does this complicate the program? 0

5.7 The `pick` command: blanks vs. arguments We've encountered most of what we need to write a `pick` command in the shell. The only new thing needed is a mechanism to read the user's input. The shell built-in `read` reads one line of text from the standard input and assigns the text (without the newline) as the value of the named variable:

```
$ read greeting hello, world $ echo $greeting hello, world $
```

Type new value for greeting

The most common use of `read` is in `. profile` to set up the environment when logging in, primarily to set shell variables like `TERM`. `read` can only read from the standard input; it can't even be redirected. None of the shell built-in commands (as opposed to the control flow primitives like `for`) can be redirected with `>` or `<`:

```
$ read greeting goodbye illegal io $ echo $greeting goodbye $
```

</etc/passwd Must type a value anyway Now shell reports error

greeting has typed value, not one from file

This might be described as a bug in the shell, but it is a fact of life. Fortunately, it can usually be circumvented by redirecting the loop surrounding the read. This is the key to our implementation of the pick command:

160 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

pick: select arguments

PATH=/bin:/usr/bin

for i do

for each argument

```
echo -n "$i? " >/dev/tty read response case $response in y*) echo $i ;; q* )
break esac </dev/tty
```

done

echo -n suppresses the final newline, so the response can be typed on the same line as the prompt. And, of course, the prompts are printed on /dev/tty because the standard output is almost certainly not the terminal. The break statement is borrowed from C: it terminates the innermost enclosing loop. In this case it breaks out of the for loop when a q is typed. We let q terminate selection because it's easy to do, potentially convenient, and consistent with other programs. It's interesting to play with blanks in the arguments to pick: \$ pick '1 2' 3 1 2? 3? \$

If you want to see how pick is reading its arguments, run it and just press RETURN after each prompt. It's working fine as it stands: for i handles the arguments properly. We could have written the loop other ways:

```
$ grep for pick for i in $* $ pick '1 2' 3 1? 2? 3? $
```

See what this version does

This form doesn't work, because the operands of the loop are rescanned, and the blanks in the first argument cause it to become two arguments. . Try quot- ing the \$*:


```
$ grep for pick for i in "$*" $ pick '1 2' 3 1 2 3? $
```

Try a different version

CHAPTER 5

SHELL PROGRAMMING

161

This doesn't work either, because `$ *` is a single word formed from all the arguments joined together, separated by blanks. Of course there is a solution, but it is almost black magic: the string `$@` is treated specially by the shell, and converted into exactly the arguments to the shell file:

```
$ grep for pick for i in "$@" $ pick '1 2' 3 1 2? 3? $
```

Try a third version

If `$@` is not quoted, it is identical to `$ *`; the behavior is special only when it is enclosed in double quotes. We used it in `overwrite` to preserve the arguments to the user's command. In summary, here are the rules: `$ *` and `$@` expand into the arguments, and are rescanned; blanks in arguments will

result in multiple arguments. . "\$* II is a single word composed of all the arguments to the shell file joined together with spaces. . II \$@n is identical to the arguments received by the shell file: blanks in arguments are ignored, and the result is a list of words identical to the original arguments. If pick has no arguments, it should probably read its standard input, so we could say

```
$ pick <mailinglist
```

instead of

```
$ pick 'cat mailinglist'
```

But we won't investigate this version of pick: it involves some ugly complications and is significantly harder than the same program written in C, which we will present in the next chapter. The first two of the following exercises are difficult, but educational to the advanced shell programmer. Exercise 5-24. Try writing a pick that reads its arguments from the standard input if none are supplied on the command line. It should handle blanks properly. Does a q response work? If not, try the next exercise. 0 Exercise 5-25. Although shell built-ins like read and set cannot be redirected, the shell itself can be temporarily redirected. Read the section of sh(1) that describes exec and work out how to read from /dev/tty without calling a sub-shell. (It might help to read Chapter 7 first.) 0 Exercise 5-26. (Much easier) Use read in your . profile to initialize TERM and whatever else depends on it, such as tab stops. 0

CHAPTER 5

508 The news command: community service messages In Chapter 1 we mentioned that your system might have a news command to report messages of general interest to the user community. Although the name and details of the command differ, most systems provide a news service. Our reason for presenting a news command is not to replace your local command, but to show how easily such a program can be written in the shell. It might be interesting to compare the implementation of our news command to your local version. The basic idea of such programs is usually that individual news items are stored, one per file, in a special directory like /usr/news. news (that is, our news program) operates by comparing the modification times of the files in /usr/news with that of a file in your home directory (.news_time) that serves as a time stamp. For debugging, we can use ',' as the directory for both the news files and "news _ time; it can be changed to /usr /news when the program is ready for general use.

```
$ cat news # news: print news files, version 1
```

```
HOME=. # debugging only cd u # place holder for /usr/news for i in 'ls -t *  
$HOME/.news_time' do
```

```
case $i in */.news time} * } esac
```

```
break ;; echo news: $i
```

```
done touch $HOME/.news time $ touch .news_time $ touch x $ touch Y $  
news news: y news: x $
```

touch changes the last-modified time of its argument file to the present time, without actually modifying the file. For debugging, we just echo the names of the news files, rather than printing them. The loop terminates when it discovers `.. news_time`, thereby listing only those files that are newer. Note that the `*` in case statements can match a `/`, which it cannot in filename patterns. What happens if `news_time` doesn't exist?

CHAPTER 5

SHELL PROGRAMMING

163

```
$ rm .news_time $ news $
```

This silence is unexpected, and wrong. It happens because if `ls` can't find a file, it reports the problem on its standard output, before printing any information about existing files. This is undeniably a bug - the diagnostic should be printed on the standard error - but we can get around it by recognizing the problem in the loop and redirecting standard error to standard output so all versions work the same. (This problem has been fixed in newer versions of the system, but we've left it as is to illustrate how you can often cope with minor botches.)

```
$ cat news # news: print news files, version 2
```

```
HOME=. cd . IFS='
```

```
# debugging only # place holder for /usr/news
```

```
,
```

```
# just a newline 'Is -t * $HOME/.news_time 2>&1'
```

```
for i in do
```

```
case $i in '*' not found'} */.news_time} *} esac
```

```
. . . , break " echo news: $i "
```

```
done touch $HOME/.news_time $ rm . news_ time $ news news: news  
news: y news: x $
```

We must set IFS to newline so the message

```
./news_time not found
```

is not parsed as three words. news must next print the news files, rather than echoing their names. It's useful to know who posted a message and when, so we use the set command and 1 s -1 to print a header before the message itself:

164 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

```
$ 1s -1 news -rwxrwxrwx 1 you 208 Oct 1 12:05 news $ set '1s -1 news' -  
rwxrwxrwx: bad option ( s ) Something is wrong! $
```

Here is one example where the interchangeability of program and data in the shell gets in the way. set complains because its argument ("-rwxrwxrwx") begins with a minus sign and thus looks like an option. An easy (if inelegant) fix is to prefix the argument by an ordinary character:

```
$ set X'1s -1 news' $ echo "news: ($3) $5 $6 $7" news: (you) Oct 1 12:05 $
```

This is a reasonable format, showing the author and date of the message along with the filename. Here is the final version of the news command:

```
# news: print news files, final version
```

```
PATH=/bin:/usr/bin IFS='
```

```
,
```

```
# just a newline
```

```
cd /usr/news
```

```
for i in
```

```
ls -t * $HOME/.news_time 2>&1
```

```
do
```

```
IFS=' , case $i in '*' not found')
```

```
, */.news_time) break" *) set X
```

```
ls -l $i
```

```
echo " $i: ($3) $5 $6 $7
```

```
"
```

```
cat $i
```

```
esac
```

```
done touch $HOME/.news_time
```

The extra newlines in the header separate the news items as they are printed. The first value of IFS is just a newline, so the not found message (if any) from the first 1 s is treated as a single argument. The second assignment to IFS resets it to a blank, so the output of the second Is is split into multiple arguments. Exercise 5-27. Add an option -n (notify) to news to report but not print the news items, and not touch. news_time. This might be placed in your . profile. 0

CHAPTER 5

SHELL PROGRAMMING

Exercise 5-28. Compare our design and implementation of news to the similar command on your system. 0

5.9 get and put: tracking file changes In this section, the last of a long chapter, we will show a larger, more complicated example that illustrates cooperation of the shell with awk and sed. A program evolves as bugs are fixed and features are added. It is sometimes convenient to keep track of these versions, especially if people take the program to other machines - they will come back and ask "What has changed since we got our version?" or "How did you fix the such-and-such bug?" Also, always maintaining backup copies makes it safer to tryout ideas: if something doesn't work out, it's painless to revert to the original program. One solution is to keep copies of all the versions around, but that is difficult to organize and expensive in disc space. Instead, we will capitalize on the likelihood that successive versions have large portions in common, which need to be stored only once. The diff -e command \$ diff -e old new

generates a list of ed commands that will convert old into new. It is therefore possible to keep all the versions of a file in a single (different) file by maintaining one complete version and the set of editing commands to convert it in to any other version. There are two obvious organizations: keep the newest version intact and have editing commands go backwards in time, or keep the oldest version and have editing commands go forwards. Although the latter is slightly easier to program, the former is faster if there are many versions, because we are almost always interested in recent versions. We chose the former organization. In a single file, which we'll call the history file, there is the current version followed by sets of editing commands that convert each version into the previous (i.e., next older) one. Each set of editing commands begins with a line that looks like

@@@ person date summary

The summary is a single line, provided by person, that describes the change. There are two commands to maintain versions: `get` extracts a version from the history file, and `put` enters a new version into the history file after asking for a one-line summary of the changes. Before showing the implementation, here is an example to show how `get` and `put` work and how the history file is maintained:

166 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

```
$ echo a line of text >junk $ put junk Summary: make a new file get: no file
junk.H put: creating junk.H $ cat junk.H a line of text @@@ you Sat Oct 1
13:31:03 EDT 1983 make a new file $ echo another line »junk $ put junk
Summary: one line added $ cat junk.H a line of text another line @@@ you
Sat Oct 1 13:32:28 EDT 1983 one line added 2d @@@ you Sat Oct 1
13:31:03 EDT 1983 make a new file $
```

Type the description History doesn't exist... .. so `put` creates it

The "editing commands" consist of the single line `2d`, which deletes line 2 of the file, turning the new version into the original.

```
$ rm junk $ get junk $ cat junk a line of text another line $ get -1 junk $ cat
junk a line of text $ get junk $ replace another 'a different' junk $ put junk
```

Summary: second line changed \$ cat junk.H a line of text a different line
@@@ you Sat Oct 1 13:34:07 EDT 1983 second line changed 2c another
line

Most recent version

Newest-hut-one version

Most recent again Change it

@@@ you Sat Oct 1 13:32:28 EDT 1983 one line added 2d @@@ you Sat
Oct 1 13:31:03 EDT 1983 make a new file \$

The editing commands run top to bottom throughout the history file to
extract the desired version: the first set converts the newest to the second
newest, the next converts that to the third newest, etc. Therefore, we are
actually convert- ing the new file into the old one a version at a time when
running ed.

CHAPTER 5

SHELL PROGRAMMING

There will clearly be trouble if the file we are modifying contains lines beginning with a triple at-sign, and the BUGS section of diff(1) warns about lines that contain only a period. We chose @@@ to mark the editing commands because it's an unlikely sequence for normal text. Although it might be instructive to show how the get and put commands evolved, they are relatively long and showing their various forms would require too much discussion. We will therefore show you only their finished forms. put is simpler:

```
# put: install file into history
```

```
PATH=/bin:/usr/bin
```

```
case $# in 1) HIST=$1oH ;; *) echo 'Usage: put file' 1>&2; exit 1 "
```

```
esac if test ! -r $1 then
```

```
echo "put: can't open $1" 1>&2 exit 1
```

```
fi trap 'rm -f /tmp/put.[ab]$$; exit 1' 1 2 15 echo -n 'Summary: ' read  
Summary
```

```

if get -0 /tmp/put.a$$ $1 # previous version then # merge pieces cp $1
/tmp/put.b$$ # current version echo "@@@" 'getname' 'date' $Summary"
»/tmp/put.b$$ diff -e $1 /tmp/put.a$$ »/tmp/put.b$$ # latest diffs sed -n
'/A@@@/, $p' <$HIST »/tmp/putob$$ # old diffs overwrite $HIST cat
/tmp/put.b$$ # put it back else # make a new one echo "put: creating
$HIST" cp $1 $HIST echo "@@@" 'getname' 'date' $Summary" »$HIST

```

fi rm -f /tmp/put.[ab]\$\$ After reading the one-line summary, put calls get to extract the previous version of the file from the history file. The -0 option to get specifies an alternate output file. If get couldn't find the history file, it returns an error status and put creates a new history file. If the history file does exist, the then clause creates the new history in a temporary file from, in order, the newest version, the @@@ line, the editor commands to convert from the newest version to the previous, and the old editor commands and @@@ lines. Finally, the temporary file is copied onto the history file using overwrite.

168 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

get is more complicated than put, mostly because it has options.

```
# get: extract file from history
```

```
PATH=/bin:/usr/bin
```

```
VERSION=0 while test "$1" != "" do
```

```
case "$1" in -i) INPUT=$2; shift ;; -o) OUTPUT=$2; shift ;; -[0-9])
VERSION=$1 ;; -*) echo "get: Unknown argument $i" 1>&2; exit 1 " *}
case "$OUTPUT" in "") OUTPUT=$1 ;; *) INPUT=$1.H" esac
```

```
esac shift done OUTPUT=${OUTPUT?"Usage: get [-o outfile] [-i file.H]
file"} INPUT=${INPUT-$OUTPUT.H} test -r $INPUT :: { echo "get: no
file $INPUT" 1>&2; exit 1; } trap 'rm -f /tmp/get.[ab]$$; exit 1' 1 2 15 #
split into current version and editing commands sed <$INPUT -n
'1,/A@@@/W /tmp/get.a'$$' /A@@@/,,$W /tmp/get.b'$$ # perform the
edits awk </tmp/get.b$$ , /A@@@/ {count++} !/A@@@/ && co
```

```
nt > 0 && count <= - '$VERSION' END { print "$d"; print "w",
"$OUTPUT" } , : ed - /tmp/get.a$$ rm -f /tmp/get.[ab]$$ The options are
fairly ordinary. - i and -o specify alternate input and output. - [ 0 - 9] selects
a particular version: 0 is the newest version (the default), - 1 the newest-
but-one, etc. The loop over arguments is a while with a test and a shift,
rather than a for, because some of the options (-i, -o) consume another
argument and must therefore shift it out, and for loops and shifts do not
cooperate properly if the shift is inside the for. The ed option '-' turns off the
character count that normally accompanies reading or writing a file. The
line
```

```
test -r $INPUT :: { echo "get: no file $INPUT" 1>&2; exit 1; }
```

is equivalent to

CHAPTER 5

SHELL PROGRAMMING

169

```
if test ! -r $INPUT then
```

```
echo "get: no file $INPUT" 1>&2 exit 1
```

```
fi
```

(which is the form we used in `put`) but is shorter to write and clearer to programmers who are familiar with the `:` `;` operator. Commands between `{` and `}` are executed in the current shell, not a sub-shell; this is necessary here so the `exit` will exit from `get` and not just a sub-shell. The characters `{` and `}` are like `do` and `done` - they have special meaning only if they follow a semicolon, newline or other command terminator. Finally, we come to the code in `get` that does the work. First, `sed` breaks the history file into two pieces: the most recent version and the set of edits. The `awk` program then processes the editing commands. `@@@` lines are counted (but not printed), and as long as the count is not greater than the desired version, the editing commands are passed through (recall that the default `awk` action is to print the input line). Two `ed` commands are added after those from the history file: `$d` deletes the single `@@@` line that `sed` left on the current version, and a `w` command writes the file to its final location. `overwrite` is unnecessary here because `get` changes only the version of the file, not the

precious history file. Exercise 5-29. Write a command version that does two things:

```
$ version -5 file
```

reports the summary, modification date and person making the modification of the selected version in the history file.

```
$ version sep 20 file
```

reports which version number was current on September 20. This would typically be used in:

```
$ get 'version sep 20 file'
```

(version can echo the history filename for convenience.) 0 Exercise 5-30. Modify get and put so they manipulate the history file in a separate directory, rather than cluttering up the working directory with "H files. 0 Exercise 5-31. Not all versions of a file are worth remembering once things settle down. How can you arrange to delete versions from the middle of the history file? 0

5..10 A look back

When you're faced with writing a new program, there's a natural tendency to start thinking immediately about how to write it in your favorite programming language. In our case, that language is most often the shell. Although it has some unusual syntax, the shell is an excellent programming

170 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 5

language. It is certainly high-level; its operators are whole programs. Since it is interactive, programs can be developed interactively, and refined in small steps until they "work." After that, if they are intended for more than personal use, they can be polished and hardened for a wider user population. In those infrequent cases where a shell program turns out to be too inefficient, some or all of it can be rewritten in C, but with the design already proven and a working implementation in hand. (We'll follow this path a couple of times in the next chapter.) This general approach is characteristic of the UNIX programming environment - build on what others have done instead of starting over from nothing; start with something small and let it evolve; use the tools to experiment with new ideas. In this chapter, we've presented many examples that are easy to do with existing programs and the shell. Sometimes it's enough merely to rearrange arguments; that was the case with `cal`. Sometimes the shell provides a loop over a set of filenames or through a sequence of command executions, as in `watchfor` and `checkmail`. More complicated examples are still less work than they would be in C; for instance, our 20-line shell version of `news` replaces a 350-line [sic] version written in C. But it's not enough to have a programmable command language. Nor is it enough to have a lot of programs. What matters is that all of the components work together. They share conventions about how information is represented and communicated. Each is designed to focus on one job and do it well. The shell then serves to bind them together, easily and efficiently, whenever you have a new idea.

This cooperation is why the UNIX programming environment is so productive.

History and bibliographic notes The idea for get and put comes from the Source Code Control System (SeeS) originated by Marc Rochkind ("The source code control system," IEEE Trans. on Software Engineering, 1975). sees is far more powerful and flexible than our simple programs; it is meant for maintenance of large programs in a production environment. The basis of sees is the same diff program, how- ever.

CHAPTER 6: P

G A MI

IT ST A

ARD I/O

So far we have used existing tools to build new ones, but we are at the limit of what can be reasonably done with the shell, sed and awk. In this chapter we are going to write some simple programs in the C programming language. The basic philosophy of making things that work together will continue to dominate the discussion and the design of the programs - we want to create tools that others can use and build on. In each case, we will also try to show a sensible implementation strategy: start with the bare minimum that does some- thing useful, then add features and options (only) if the need arises. There are good reasons for writing new programs from

scratch. It may be that the problem at hand just can't be solved with existing programs. This is often true when the program must deal with non-text files, for example - the majority of the programs we have shown so far really work well only on textual information. Or it may be too difficult to achieve adequate robustness or "efficiency with just the shell and other general-purpose tools. In such cases, a shell version may be good for honing the definition and user interface of a program. (And if it works well enough, there's no point re-doing it.) The zap program from the last chapter is a good example: it took only a few minutes to write the first version in the shell, and the final version has an adequate user interface, but it's too slow. We will be writing in C because it is the standard language of UNIX systems - the kernel and all user programs are written in C - and, realistically, no other language is nearly as well supported. We will assume that you know C, at least well enough to read along. If not, read *The C Programming Language*, by B. W. Kernighan and D. M. Ritchie (Prentice-Hall, 1978). We will also be using the "standard I/O library," a collection of routines that provide efficient and portable I/O and system services for C programs. The standard I/O library is available on many non-UNIX systems that support C, so programs that confine their system interactions to its facilities can easily be transported. The examples we have chosen for this chapter have a common property: they are small tools that we use regularly, but that were not part of the 7th Edition. If your system has similar programs, you may find it enlightening to 171

172 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

compare designs. And if they are new to you, you may find them as useful as we have. In any case, they should help to make the point that no system is perfect, and that often it is quite easy to improve things and to cover up defects with modest effort.

6.1 Standard input and output: vis Many programs read only one input and write one output; for such programs, I/O that uses only standard input and standard output may be entirely adequate, and it is almost always enough to get started. Let us illustrate with a program called vis that copies its standard input to its standard output, except that it makes all non-printing characters visible by printing them as '\nnn', where nnn is the octal value of the character. vis is invaluable for detecting strange or unwanted characters that may have crept into files. For instance, vis will print each backspace as '\010', which is the octal value of the backspace character:

```
$ cat x aDQ $ vis <x abc,010,010,010___ $
```

To scan multiple files with this rudimentary version of vis, you can use cat to collect the files:

```
$ cat file1 file2
```

```
: vis
```

```
$ cat file1 file2
```

```
: vis / grep
```

```
\\
```

and thus avoid learning how to access files from a program. By the way, it might seem that you could do this job with sed, since the 'l' command displays non-printable characters in an understandable form: `$ sed -n 1 x abc`

____ \$

The sed output is probably clearer than that from vis. But sed was never meant for non-text files:

`$ sed -n 1 /usr/you/bin` \$ Nothing at all! (This was on a POP-II; on one VAX system, sed aborted, probably because the input looks like a very long line of text.) So sed is inadequate, and we are forced to write a new program. The simplest input and output routines are called `getchar` and `putchar`. Each call to `getchar` gets the next character from the standard input, which

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

may be a file or a pipe or the terminal (the default) - the program doesn't know which. Similarly, putchar (c) puts the character c on the standard output, which is also by default the terminal. The function printf(3) does output format conversion. Calls to printf and putchar may be interleaved in any order; the output will appear in the order of the calls. There is a corresponding function scanf(3) for input format conversion; it will read the standard input and break it up into strings, numbers, etc., as desired. Calls to scanf and get char may also be inter-mixed. Here is the first version of vis:

```
/* vis: make funny characters visible (version 1) */
```

```
#include <stdio.h> #include <ctype.h>
```

```
main ( ) {
```

```
int c;
```

```
while «c = getchar(» != EOF) if (isascii(c) && (isprint(c) :: c=='\n' :: c=='\t'  
:: c==' ' » putchar (c) ; else printf("\\%030", c); exit(0);
```

```
}
```

getchar returns the next byte from the input, or the value EOF when it encounters the end of file (or an error). By the way, EOF is not a byte from

the file; recall the discussion of end of file in Chapter 2. The value of EOF is guaranteed to be different from any value that occurs in a single byte so it can be distinguished from real data; `c` is declared `int`, not `char`, so that it is big enough to hold the EOF value. The line

```
#include <stdio.h>
```

should appear at the beginning of each source file. It causes the C compiler to read a header file (`/usr/include/stdio.h`) of standard routines and symbols that includes the definition of EOF. We will use `<stdio.h>` as a shorthand for the full filename in the text. The file `<ctype.h>` is another header file in `usr/include` that defines machine-independent tests for determining the properties of characters. We used `isascii` and `isprint` here, to determine whether the input character is ASCII (i.e., value less than 0200) and printable; other tests are listed in Table 6.1. Notice that newline, tab and blank are not "printable" by the definitions in `<ctype.h>`.

174 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

The call to `exit` at the end of `vis` is not necessary to make the program work properly, but it ensures that any caller of the program will see a normal exit status (conventionally zero) from the program when it completes. An alternate way to return status is to leave `main` with `return 0`; the return value from `main` is the program's exit status. If there is no explicit return or `exit`, the exit status is unpredictable. To compile a C program, put the source in a file whose name ends in `.c`, such as `vis.c`, compile it with `cc`, then run the

result, which the compiler leaves in a file called a.out ('a' is for assembler):

```
$ cc vis.c $ a.out hello worldctl-g hello world\007 ctl-d $
```

Normally you would rename a.out once it's working, or use the cc option -o to do it directly:

```
$ cc -o vis vis.c
```

Output in vis, not a.out

Exercise 6-1. We decided that tabs should be left alone, rather than made visible as \011 or

or \t, since our main use of vis is looking for truly anomalous characters. An alternate design is to identify every character of output unambiguously - tabs, non-graphics, blanks at line ends, etc. Modify vis so that characters like tab, backslash, backspace, formfeed, etc., are printed in their conventional C representations \t, \\\, \b, \f, etc., and so that blanks at the ends of lines are marked. Can you do this unambiguously? Compare your design with

```
$ sed -n 1
```


o Exercise 6-2. Modify `vis` so that it folds long lines at some reasonable length. How does this interact with the unambiguous output required in the previous exercise? 0

6.2 Program arguments: `vis` version 2 When a C program is executed, the command-line arguments are made available to the function `main` as a count `argc` and an array `argv` of pointers to character strings that contain the arguments. By convention, `argv[0]` is the command name itself, so `argc` is always greater than 0; the "useful" arguments are `argv[1] ... argv[argc-1]`. Recall that redirection with `<` and `>` is done by the shell, not by individual programs, so redirection has no effect on the number of arguments seen by the program. To illustrate argument handling, let's modify `vis` by adding an optional argument: `vis -s` strips out any non-printing characters rather than displaying them prominently. This option is handy for cleaning up files from other systems, for example those that use CRLF (carriage return and line feed) instead

CHAPTER 6

PROGRAMMING WITH STANDARD 110

175

Table 601: `<ctype.h>` Character Test Macros

`isalpha(c)` `isupper(c)` `islower(c)` `isdigit(c)` `isxdigit(c)` `isalnum(c)` `isspace(c)`
`ispunct(c)` `isprint(c)` `iscntrl(c)` `isascii(c)`

alphabetic: a - z A - Z upper case: A-Z lower case: a - z digit: 0-9
hexadecimal digit: 0-9 a-f A-F alphabetic or digit blank, tab, newline,
vertical tab, formfeed, return not alphanumeric or control or space
printable: any graphic control character: $0 \leq c < 040 :: c == 0177$ ASCII
character: $0 \leq c \leq 0177$

of newline to terminate lines.

```
/* vis: make funny characters visible (version 2) */
```

```
#include <stdio.h> #include <ctype.h>
```

```
main(argc, argv) int argc; char *argv [ ] ;
```

```
{
```

```
int c, strip = 0;
```

```
if (argc > 1 && strcmp(argv[1], "-s") == 0) strip = 1; while ((c = getchar() != EOF) if (isascii(c) && (isprint(c) :: c=='\n' :: c=='\t' :: c==' ' » putchar ( c ) ; else if (!strip) printf("\\%030", c); exit(0);
```

}

`argv` is a pointer to an array whose individual elements are pointers to arrays of characters; each array is terminated by the ASCII character NUL ('`\0`'), so it can be treated as a string. This version of `vis` starts by checking to see if there is an argument and if it is `-so` (Invalid arguments are ignored.) The function `strcmp(3)` compares two strings, returning zero if they are the same. Table 6.2 lists a set of string handling and general utility functions, of which `strcmp` is one. It's usually best to use these functions instead of writing your own, since they are standard, they are debugged, and they are often

176 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

faster than what you can write yourself because they have been optimized for particular machines (sometimes by being written in assembly language). Exercise 6-3. Change the `-s` argument so that `vis -sn` will print only strings of `n` or more consecutive printable characters, discarding non-printing characters and short sequences of printable ones. This is valuable for isolating the text parts of non-text files such as executable programs. Some versions of the system provide a `strings` program that does this. Is it better to have a separate program or an argument to `vis`? Exercise 6-4. The availability of the C source code is one of the strengths of the UNIX system - the code illustrates elegant solutions to many programming problems. Comment on the tradeoff between readability of the C source and the occasional optimizations obtained from rewriting in assembly language.

streat(s,t) strneat(s,t,n) strepy(s,t) strnepy(s,t,n) stremp(s,t) strnemp(s,t,n)
strlen(s) strehr(s,e) strrchr(s,e)

atoi(s) atof(s)

malloec(n) ealloec(n,m)

free(p)

Table 602: Standard String Functions

append string t to string s; return s append at most n characters of t to s copy
t to s; return s copy exactly n characters; null pad if necessary compare sand
t, return < 0, 0, > 0 for <, =, > compare at most n characters return length
of s return pointer to first e in s, NULL if none return pointer to last e in s,
NULL if none. These are index and r index on older systems return integer
value of s return floating point value of s; needs declaration double atof ()
return pointer to n bytes of memory, NULL if can't return pointer to nX m
bytes, set to 0, NULL if can't. malloec and ealloec return ehar * free memory
allocated by malloec or ealloec

6..3 File access: vis version 3 The first two versions of vis read the standard
input and write the stan- dard output, which are both inherited from the
shell. The next step is to modify vis to access files by their names, so that \$
vis file1 file2 ...

will scan the named files instead of the standard input. If there are no filename arguments, though, we still want vis to read its standard input. The question is how to arrange for the files to be read - that is, how to connect the filenames to the I/O statements that actually read the data. The rules are simple. Before it can be read or written a file must be opened

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

177

by the standard library function `fopen`. `fopen` takes a filename (like `temp` or `/etc/passwd`), does some housekeeping and negotiation with the kernel, and returns an internal name to be used in subsequent operations on the file. This internal name is actually a pointer, called a file pointer, to a structure that contains information about the file, such as the location of a buffer, the current character position in the buffer, whether the file is being read or written, and the like. One of the definitions obtained by including `<stdio.h>` is for a structure called `FILE`. The declaration for a file pointer is `FILE *fp;`

This says that `fp` is a pointer to a `FILE`. `fopen` returns a pointer to a `FILE`; there is a type declaration for `fopen` in `<stdio.h>`. The actual call to `fopen` in a program is

```
char *name, *mode;
```

```
fp = fopen(name, mode);
```

The first argument of `fopen` is the name of the file, as a character string. The second argument, also a character string, indicates how you intend to use the file; the legal modes are read ("r"), write ("w"), or append ("a"). If a file that you open for writing or appending does not exist, it is created, if possible. Opening an existing file for writing causes the old contents to be discarded. Trying to read a file that does not exist is an error, as is trying to read or write a file when you don't have permission. If there is any error, `fopen` will return the invalid pointer value `NULL` (which is defined, usually as `(char *) 0`, in `<stdio.h>`). The next thing needed is a way to read or write the file once it is open. There are several possibilities, of which `getc` and `putc` are the simplest. `getc` gets the next character from a file. `c = getc(fp)` places in `c` the next character from the file referred to by `fp`; it returns `EOF` when it reaches end of file. `putc` is analogous to `getc`: `putc(c, fp)`

puts the character `c` on the file `fp` and returns `c`. `getc` and `putc` return `EOF` if an error occurs. When a program is started, three files are open already, and file pointers are provided for them. These files are the standard input, the standard output, and the standard error output; the corresponding file pointers are called `stdin`, `stdout`, and `stderr`. These file pointers are declared in `<stdio.h>`; they may be used anywhere an object of type `FILE *` can be. They are constants, however, not variables, so you can't assign to them. `getchar ()` is the same as `getc (stdin)` and `putchar (c)` is the same as

CHAPTER 6

putc (c , stdout). In fact, an four of these "functions" are defined as mac-ros in <stdio.. h>, since they run faster by avoiding the overhead of a func- tion can for each character. See Table 6.3 for some other definitions in <stdio..h>. With some of the preliminaries out of the way, we can now write the third version of vis. If there are command-line arguments, they are processed in order. If there are no arguments, the standard input is processed.

1* vis: make funny characters visible (version 3) *1

```
#include <stdio.h> #include <ctype.h> int strip == 0; 1* 1 => discard  
special characters */
```

```
main(argc, argv) int argc; char *argv[];
```

```
{
```

```
int i; FILE *fp;
```

```
while (argc > 1 && argv[1][0] === '-') { switch (argv[1][1]) { case's': 1* -s:  
strip funny chars *1 strip::: 1; break; default: fprintf(stderr, "%s: unknown
```

```
arg %s\n", argv[0], argv[1]); exit ( 1 );
```

```
}
```

```
argc--; argv++;
```

```
} if (argc == 1) vis ( stdin ) ; else for (i == 1; i < argc; i++) if  
«fp==fopen(argv[i], Urn»
```

```
== NULL) { fprintf(stderr, "%s: can't open %s\n", argv[0], argv[i]); exit ( 1 ) ; } else { vis(fp) ; fclose(fp) ;
```

```
} exit(0);
```

```
}
```

This code relies on the convention that optional arguments come first. After

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

stdin stdout stderr EOF NULL FILE BUFSIZ getc(fp) getchar () putc(c,fp)
 putchar(c) feof(fp) ferror(fp) fileno(fp)

Table 6.3: Some <stdio.h> Definitions standard input standard output
 standard error end of file; normally -1 invalid pointer; normally 0 used for
 declaring file pointers normal I/O buffer size (often 512 or 1024)

return one character from stream fp getc(stdin) put character c on stream fp
 putc(c,stdout) non-zero when end of file on stream fp non-zero when any
 error on stream fp file descriptor for stream fp; see Chapter 7

each optional argument is processed, argc and argv are adjusted so the rest of the program is independent of the presence of that argument. Even though vis only recognizes a single option, we wrote the code as a loop to show one way to organize argument processing. In Chapter 1 we remarked on the disorderly way that UNIX programs handle optional arguments. One reason, aside from a taste for anarchy, is that it's obviously easy to write code to handle argument parsing for any variation. The function getopt(3) found on some systems is an attempt to rationalize the situation; you might investigate it before writing your own. The routine vis prints a single file:

```
vis(fp) /* make chars visible in FILE *fp */ FILE *fp;
```

```
{
```

```
int c;
```

```
while ((c = getc(fp) != EOF) if (isascii(c) && (isprint(c) :: c=='\n' :: c=='\t'  
:: c==' ' » putchar (c) ; else if (!strip) printf ( "\\%030", c);
```

```
}
```

The function `fprintf` is identical to `printf`, except for a file pointer argument that specifies the file to be written. The function `fclose` breaks the connection between the file pointer and the external name that was established by `fopen`, freeing the file pointer for

180 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

another file. Since there is a limit (about 20) on the number of files that a program may have open simultaneously, it's best to free files when they are no longer needed. Normally, output produced with any of the standard library functions like `printf`, `putc`, etc., is buffered so it can be written in large chunks for efficiency. (The exception is output to a terminal, which is usually written as it is produced, or at least when a newline is printed.) Calling `fclose` on an output file also forces out any buffered output. `fclose` is also called automatically for each open file when a program calls `exit` or returns from `main`. `stderr` is assigned to a program in the same way that

stdin and stdout are. Output written on stderr appears on the user's terminal even if the standard output is redirected. vis writes its diagnostics on stderr instead of stdout so that if one of the files can't be accessed for some reason, the message finds its way to the user's terminal instead of disappearing down a pipeline or into an output file. (The standard error was invented somewhat after pipes, after error messages did start disappearing into pipelines.) Somewhat arbitrarily, we decided that vis will quit if it can't open an input file; this is reasonable for a program most often used interactively, and with a single input file. You can argue for the other design as well, however. Exercise 6-5. Write a program printable that prints the name of each argument file that contains only printable characters; if the file contains any non-printable character, the name is not printed. printable is useful in situations like this:

```
$ pr 'printable *' / lpr
```

Add the option -v to invert the sense of the test, as in grep. What should printable do if there are no filename arguments? What status should printable return? 0

6.4 A screen...at-a..time printer: p So far we have used cat to examine files. But if a file is long, and if you are connected to your system by a high-speed connection, cat produces the output too fast to be read, even if you are quick with ctrl-s and ctrl-q. There clearly should be a program to print a file in small, controllable chunks, but there isn't a standard one, probably because the original UNIX system was written in the days of hard-copy (paper) terminals and slow communications lines. So our next example is a program called p that will print a file a screenful at a time, waiting for a response from the user after each screen before continuing to the next. ("p" is a nice short name for a program that we use a lot.) As with other programs, p reads either from files named as arguments or from its standard input:

eCHAPTER 6

PROGRAMMING WITH STANDARD I/O 181

```
$ p vis.c
```

```
$ grep '#define' *.[ch] : p
```

```
$
```

This program is best written in C because it's easy in C, and hard otherwise; the standard tools are not good at mixing the input from a file or pipe with terminal input. The basic, no-frills design is to print the input in small chunks. A suitable chunk size is 22 lines: that's slightly less than the 24-line screen of most video terminals, and one third of a standard 66-line page. A simple way for `p` to prompt the user is to not print the last newline of each 22-line chunk. The cursor will thus pause at the right end of the line rather than at the left margin. When the user presses RETURN, that will supply the missing newline and thus cause the next line to appear in the proper place. If the user types `ctl-d` or `q` at the end of a screen, `p` will exit. We will take no special action for long lines. We will also not worry about multiple files: we'll merely skip from one to the next without comment. That way the behavior of `$ p filenames...` will be the same as

```
$ cat filenames... : p
```

If filenames are needed, they can be added with a for loop like \$ for i in filenames... > do > echo \$i: > cat \$i > done : p

Indeed, there are too many features that we can add to this program. It's better to make a stripped-down version, then let it evolve as experience dictates. That way, the features are the ones that people really want, not the ones we thought they would want. The basic structure of p is the same as vis: the main routine cycles through the files, calling a routine print that does the work on each.

182 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

```
/* p: print input in chunks (version 1) */
```

```
#include <stdio.h> #define PAGESIZE char *progname;
```

```
22 /* program name for error message */
```

```
main(argc, argv) int argc; char *argv[];
```

```

{

int i; FILE *fp, *efopen();

programe = argv[0]; if (argc == 1) print(stdin, PAGESIZE); else for (i = 1;
i < argc; i++) { fp = efopen(argv[i], Urn); print(fp, PAGESIZE); fclose(fp) ;

} exit(0);

}

```

The routine efopen encapsulates a very common operation: try to open a file; if it's not possible, print an error message and exit. To encourage error messages that identify the offending (or offended) program, efopen refers to an external string programe containing the name of the program, which is set in main.

```
FILE *efopen(file, mode) char *file, *mode;
```

```
/* fopen file, die if can't */
```

```
{
```

```
FILE *fp, *fopen(); extern char *progname;
```

```
if ((fp = fopen(file, mode) != NULL) return fp; fprintf(stderr, "%s: can't  
open file %s mode %s\n", progname, file, mode); exit(1);
```

```
}
```

We tried a couple of other designs for `efopen` before settling on this. One was to have it return after printing the message, with a null pointer indicating failure. This gives the caller the option of continuing or exiting. Another design provided `efopen` with a third argument specifying whether it should return after failing to open the file. In almost all of our examples, however,

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

183

there's no point to continuing if a file can't be accessed, so the current version of `efopen` is best for our use. The real work of the `print` command is done in `print`:

```
print(fp, pagesize) /* print fp in pagesize chunks */ FILE *fp; int pagesize;
```

```
{
```

```
static int lines = 0; char buf[BUFSIZ];
```

```
/* number of lines so far */
```

```
while (fgets(buf, sizeof buf, fp) != NULL) if (++lines < pagesize)  
fputs(buf, stdout); else { buf[strlen(buf)-1] = '\0'; fputs(buf, stdout); fflush(  
stdout) ; t tyin ( ) ; lines = 0;
```

```
}
```

```
}
```

We used BUFSIZ, which is defined in <stdio.h>, as the size of the input buffer. fgets (buf , size, fp) fetches the next line of input from fp, up to and including a newline, into buf, and adds a terminating \0; at most size-1 characters are copied. It returns NULL at end of file. (fgets could be better designed: it returns buf instead of a character count; furthermore it provides no warning if the input line was too long. No characters are lost, but you have to look at buf to see what really happened.) The function strlen returns

the length of a string; we use that to knock the trailing newline off the last input line. `fputs (buf , fp)` writes the string `buf` on file `fp`. The call to `fflush` at the end of the page forces out any buffered output. The task of reading the response from the user after each page has been printed is delegated to a routine called `ttyin`. `ttyin` can't read the standard input, since `p` must work even when its input comes from a file or pipe. To handle this, the program opens the file `/dev/tty`, which is the user's terminal regardless of any redirection of standard input. We wrote `ttyin` to return the first character of the response, but don't use that feature here.

184 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

```
ttyin() 1* process response from /dev/tty (version 1) *1 {
```

```
char buf[BUFSIZ]; FILE *efopen(); static FILE *tty = NULL;
```

```
if (tty == NULL) tty = efopen("/dev/tty", "r"); if (fgets(buf, BUFSIZ, tty)
== NULL:: buf[0] == 'q') exit(0); else 1* ordinary line *1 return buf[0];
```

```
}
```

The file pointer `devtty` is declared static so that it retains its value from one call of `ttyin` to the next; the file `/dev /tty` is opened on the first call only.

There are obviously extra features that could be added to `p` without much work, but it is worth noting that our first version of this program did just what is described here: print 22 lines and wait. It was a long time before other things were added, and to this day only a few people use the extra features. One easy extra is to make the number of lines per page a variable `pagesize` that can be set from the command line: `$ p -n ...` prints in `n`-line chunks. This requires only adding some familiar code at the beginning of `main`:

```
1* p: print input in chunks (version 2) *1
```

```
int i, pagesize = PAGESIZE;
```

```
programe = argv[0]; if (argc > 1 && argv[1][0] == '-') { pagesize =  
atoi(&argv[1][1]); argc--; argv++;
```

```
}
```

The function `atoi` converts a character string to an integer. (See `atoi(3)`.) Another addition to `p` is the ability to escape temporarily at the end of each page to do some other command. By analogy to `ed` and many other programs, if the user types a line that begins with an exclamation mark, the rest of that line is taken to be a command, and is passed to a shell for execution. This feature is also trivial, since there is a function called `system(3)` to do the work, but read the caveat below. The modified version of `ttyin` follows:

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

185

```
tt Yin() /* process response from /dev/tty (version 2) */ {
```

```
char buf[BUFSIZ]; FILE *efopen ( ) ; static FILE *tty ::: NULL;
```

```
if (tty ::: = NULL) tty :: efopen( "/dev/tty", "r"); for (;;) { if  
(fgets(buf,BUFSIZ,tty) ::::: NULL:: buf[0] -- 'q') exit(0); e l s e if (buf [  
0] ::::: '!') { system(buf+1); /* BUG here */ printf("!\\n");
```

```
} else /* ordinary line */ return buf[0];
```

```
}
```

```
}
```

Unfortunately, this version of `tyin` has a subtle, pernicious bug. The command run by `system` inherits the standard input from `p`, so if `p` is reading from a pipe or a file, the command may interfere with its input: `$ cat /etc/passwd : p -1 root:3D.fHR5KoB.3s:0:1:S.User:/: led ?`

Invoke `ed` from within `p` `ed` reads `/etc/passwd ...` is confused, and quits

The solution requires knowledge about how UNIX processes are controlled, and we will present it in Section 7.4. For now, be aware that the standard system in the library can cause trouble, but that `tyin` works correctly if compiled with the version of `system` in Chapter 7. We have now written two programs, `vis` and `p`, that might be considered variants of `cat`, with some embellishments. So should they all be part of `cat`, accessible by optional arguments like `-v` and `-p`? The question of whether to write a new program or to add features to an old one arises repeatedly as people have new ideas. We don't have a definitive answer, but there are some principles that help to decide. The main principle is that a program should only do one basic job - if it does too many things, it gets bigger, slower, harder to maintain, and harder to use. Indeed, the features often lie unused because people can't remember the options anyway. This suggests that `cat` and `vis` should not be combined. `cat` just copies its input, unchanged, while `vis` transforms it. Merging them makes a program that does two different things. It's almost as clear with `cat` and `p`. `cat` is meant for fast, efficient copying; `p` is meant for browsing. And `p` does transform its output: every 22nd newline is dropped. Three separate programs

seems to be the proper design. Exercise 6-6. Does `p` act sanely if page size is not positive? 0 Exercise 6-7. What else could be done to `p`? Evaluate and implement (if appropriate) the ability to re-print parts of earlier input. (This is one extra feature that we enjoy.) Add a facility to permit printing less than a screenful of input after each pause. Add a facility to scan forward or backward for a line specified by number or content. 0 Exercise 6-8. Use the file manipulation capabilities of the `exec` shell built-in (see `she 1`) to fix `ttyn`'s `can` to `system`. 0 Exercise 6-9. If you forget to specify an input for `p`, it sits quietly waiting for input from the terminal. Is it worth detecting this probable error? If so, how? Hint: `isatty(3)`. 0

6.5 An example: `pick` The version of `pick` in Chapter 5 was clearly stretching the capabilities of the shell. The C version that follows is somewhat different from the one in Chapter 5. If it has arguments, they are processed as before. But if the single argument `'-'` is specified, `pick` processes its standard input. Why not just read the standard input if there are no arguments? Consider the second version of the `zap` command in Section 5.6:

```
kill $SIG 'pick \ps -ag : egrep 88$*"' : awk '{print $1}'
```

What happens if the `egrep` pattern doesn't match anything? In that case, `pick` has no arguments and starts to read its standard input; the `zap` command fails in a mystifying way. Requiring an explicit argument is an easy way to disambiguate such situations, and the `'-'` convention from `cat` and other programs indicates how to specify it.

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

187

```
/* pick: offer choice on each argument */
```

```
#include <stdio.h> char *progname; /* program name for error message */
```

```
main(argc, argv) int argc; char *argv [ ] ;
```

```
{
```

```
int i; char buf[BUFSIZ];
```

```
progname == argv[0]; if (argc == 2 && strcmp(argv[1], "-") == 0)
while (fgets(buf, sizeof buf, stdin) != buf[strlen(buf)-1] == '\0'; /* drop
pick( buf) ;
```

```
/* pick - */ NULL) { newline */
```

```
} else for (i == 1; i < argc; i++) pick(argv[i]); exit(0);
```

```
}
```

```
pick(s) /* offer choice of s */ char *s;
```

```
{
```

```
fprintf(stderr, "%s? ", s); if (ttyin() == 'y') printf("%s\n", s);
```

```
}
```

pick centralizes in one program a facility for interactively selecting arguments. This not only provides a useful service, but also reduces the need for "interactive" options on other commands. Exercise 6-10. Given pick, is there a need for `rm -i`? 0

6.6 On bugs and debugging If you've ever written a program before, the notion of a bug will be familiar. There's no good solution to writing bug-free code except to take care to produce a clean, simple design, to implement it carefully, and to keep it clean as you modify it. There are a handful of UNIX tools that will help you to find bugs, though none is really first-rate. To illustrate them, however, we need a bug, and all of the programs in this book are perfect. Therefore we'll create a typical bug.

Consider the function pick shown above. Here it is again, this time containing an error. (No fair looking back at the original.)

188 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

```
pick(s) /* offer choice of s */ char *s;

{

fprintf( "%s? ", s); if (ttyin() == 'y') printf("%s\n", s);

}
```

If we compile and run it, what happens?

```
$ cc pick.c -o pick $ pick *.c Memory fault - core dumped $
```

Try it Disaster!

"Memory fault" means that your program tried to reference an area of memory that it was not allowed to. It usually means that a pointer points somewhere wild. "Bus error" is another diagnostic with a similar meaning, often caused by scanning a non-terminated string. "Core dumped" means that the kernel saved the state of your executing program in a file called core in the current directory. You can also force a program to dump core by typing `ctl- \` if it is running in the foreground, or by the command `kill -3` if it is in the background. There are two programs for poking around in the corpse, `adb` and `sdb`. Like most debuggers, they are arcane, complicated, and indispensable. `adb` is in the 7th Edition; `sdb` is available on more recent versions of the system. One or the other is sure to be there. We have space here only for the absolute minimum use of each: printing a stack trace, that is, the function that was executing when the program died, the function that called it, and so on. The first function named in the stack trace is where the program was when it aborted. To get a stack trace with `adb`, the command is `$C`:

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

189

```
$ adb pick core Invoke adb $C Stack trace request -
__strout(0175722,011,0,011200) adjust: 0 fillch: 060542
__doprnt(0177345)0176176,011200) -fprintf(011200,0177345) iop: 011200
fmt: 0177345 args : 0 -pick(0177345)
```

s:

0177345

-main(035,0177234) argc: argv:

i:

035 0177234 01 o

buf:

ctl-d \$

Quit

This says that main called pick, which called fprintf, which called _doprnt, which called _strout. Since _doprnt isn't mentioned anywhere in pick. c, our troubles must be somewhere in fprintf or above. (The lines after each subroutine in the traceback show the values of local variables. \$c suppresses this information, as does \$C itself on some versions of adb.) Before revealing all, let's try the same thing with sdb:

```
$ sdb pick core Warning: 'a. out' not compiled with -g lseek: address Oxa64
Routine where program died * t Stack trace request lseek ( )
fprintf(6154,2147479154) pick(2147479154)
main(30,2147478988,2147479112) *q Quh $
```

The information is formatted differently, but there's a common theme: `fprintf`. (The traceback is different because this was run on a different machine - a VAX-11/750 - which has a different implementation of the standard I/O library). And sure enough, if we look at the `fprintf` invocation in the defective version of `pick`, it is wrong:

```
fprintf( "%S? ", s);
```

There's no `stderr`, so the format string `"%s? "` is being used as a `FILE` pointer, and of course chaos ensues. We picked this error because it's common, a result of oversight rather than

190 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

bad design. It's also possible to find errors like this, in which a function is called with the wrong arguments, by using the C verifier `lint(1)`. `lint` examines C programs for potential errors, portability problems, and dubious

constructions. If we run lint on the whole pick.c file, the error is identified:

```
$ lint pickoc
```

```
fprintf, argo 1 used inconsistently "libc"(69) :: "pickoc"(28)
```

```
$
```

In translation, this says that `fprintf`'s first argument is different in the standard library definition from its use in line 28 of our program. That is a strong hint about what's wrong. lint is a mixed success. It says exactly what's wrong with this program, but also produces a lot of irrelevant messages that we've elided above, and it takes some experience to know what to heed and what to ignore. It's worth the effort, though, because lint finds some errors that are almost impossible for people to see. It's always worth running lint after a long stretch of editing, making sure that you understand each warning that it gives.

6.7 An example: `zap` `zap`, which selectively kills processes, is another program that we presented as a shell file in Chapter 5. The main problem with that version is speed: it creates so many processes that it runs slowly, which is especially undesirable for a program that kills errant processes. Rewriting `zap` in C will make it faster. We are not going to do the whole job, however: we will still use `ps` to find the process information. This is much easier than digging the information out of the kernel, and it is also portable. `zap` opens a pipe with `ps` on the input end, and reads from that instead of from a file. The function `popen(3)` is analogous to `fopen`, except

that the first argument is a command instead of a filename. There is also a possibility that we don't need here.

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

191

```
/* zap: interactive process killer */
```

```
#include <stdio.h> #include <signal.h> char *progrname; /* program name  
for error message */ char *ps = "ps -ag"; /* system dependent */
```

```
main(argc, argv) int argc; char *argv [ ] ;
```

```
{
```

```
FILE *fin, *popen(); char buf[BUFSIZ]; int pid;
```

```

programe = argv[0]; if «fin = popen(ps, "r"» == NULL) { fprintf(stderr,
"%s: can't run %s\n" , programe, ps); exit ( 1 ) ; } fgets(buf, sizeof buf,
fin); /* get header line */ fprintf (stderr, "%s", buf); while (fgets(buf, sizeof
buf, fin) != NULL) if (argc == 1 :: strindex(buf, argv[1]) >= 0) {
buf[strlen(buf)-1] == '\0'; /* suppress \n */ fprintf (stderr, "%s? ", buf); if
(ttyin() == 'y') { sscanf(buf, "%d" , &pid); kill(pid, SIGKILL);

}

} exit(0);

}

```

We wrote the program to use `ps -ag` (the option is system dependent), but unless you're the super-user you can kill only your own processes. The first call to `fgets` picks up the header line from `ps`; it's an interesting exercise to deduce what happens if you try to kill the "process" corresponding to that header line. The function `sscanf` is a member of the `scanf(3)` family for doing input format conversion. It converts from a string instead of a file. The system call `kill` sends the specified signal to the process; signal `SIGKILL`, defined in `<signal.h>`, can't be caught or ignored. You may remember from Chapter 5 that its numeric value is 9, but it's better practice to use the symbolic constants from header files than to sprinkle your programs with magic numbers. If there are no arguments, `zap` presents each line of the `ps` output for possible selection. If there is an argument, then `zap` offers only `ps` output lines that match it. The function `strindex(s1, s2)` tests whether the argument

CHAPTER 6

matches any part of a line of ps output, using strncmp (see Table 6.2). strchr returns the position in s 1 where s 2 occurs, or -1 if it does not.

```
strindex(s, t) /* return index of t in s, -1 if none */ char *s, *t;
```

```
{
```

```
int i, n;
```

```
n = strlen(t); for (i = 0; s[i] != '\0'; i++) if (strncmp(s+i, t, n) == 0) return i;
return -1;
```

```
}
```

Table 6.4 summarizes the commonly-used functions from the standard I/O library. Exercise 6-11. Modify zap so that any number of arguments can be supplied. As written, zap will normally echo the line corresponding to itself as one of the choices. Should it? If not, modify the program

accordingly. Hint: `getpid(2)`. 0 Exercise 6-12. Build an `fgrep(1)` around `strindex`. Compare running times for complicated search

words, say ten words in a document. Why does `fgrep` run faster? 0

6.8 An interactive file comparison program: `idiff` A common problem is to have two versions of a file, somewhat different, each containing part of a desired file; this often results when changes are made independently by two different people. `diff` will tell you how the files differ, but it's of no direct help if you want to select some parts of the first file and some of the second. In this section, we will write a program `idiff` ("interactive diff") that presents each chunk of `diff` output and offers the user the option of choosing the "from" part, choosing the "to" part, or editing the parts. `idiff` produces the selected pieces in the proper order, in a file called `idiff..out`. That is, given these two files:

file 1 : This is a test of your skill and comprehension.

file2: This is not a test of our ability.

`diff` produces

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

Table 6..4: Useful Standard I/O Functions

`fp=fopen(s,mode)`

`c=getc(fp) putc(c,fp) ungetc(c,fp)`

`scanf (fmt , a 1 , ...)`

`fscanf(fp,...) sscanf(s,...) printf (fmt, a 1 , .oo) fprintf (fp, oo.) sprintf (s,.oo) fgets(s,n,fp)`

`fputs(s,fp) fflush(fp) fclose(fp) fp=popen(s,mode) pclose(fp) system(s)`

Open file S. mode II r " IV w" " a" for read write , " " append (returns NULL for error) get character; getchar () is getc (s tdin) put character; putchar (c) is putc (c, stdout) put character back on input file fp; at most 1 char can be pushed back at one time read characters from stdin into a 1,... according to fmt. Each ai must be a pointer. Returns EOF or number of fields converted. read from file fp read from string s format a 1,... according to frot, print on stdout print ... on file fp print ... into string s read at most n characters into s from fp. Returns NULL at end of file print string s on file fp flush any buffered output on file fp close file fp open pipe to command s. See fopen. close pipe f p run command s and wait for completion

\$ di

f file1 file2 2c2 < a test

> not a test 4,6c4,5 < your < skill < and comprehension.

> our > ability. \$ A dialog with idiff might look like this:

194 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

\$ idiff file1 file2 2c2 < a test

The first difference

> not a test ? > 4,6c4,5 < your < skill < and comprehension.

User chooses second (« version The second difference

> our > ability. ? < idiff output in \$ cat idiff.out This is not a test of your skill and comprehension. \$

User chooses first «) version file idiff.out Output put in this file

If the response e is given instead of < or >, idiff invokes ed with the two groups of lines already read in. If the second response had been e, the editor buffer would look like this:

your skill and comprehension.

our ability.

Whatever is written back into the file by ed is what goes into the final output. Finally, any command can be executed from within idiff by escaping with ! cmd. Technically, the hardest part of the job is diff, and that has already been done for us. So the real job of idiff is parsing diff's output, and opening, closing, reading and writing the proper files at the right time. The main routine of idiff sets up the files and runs the diff process:

CHAPTER 6

PROGRAMMING WITH STANDARD 110

195

```
/* idiff: interactive diff */
```

```
#include <stdio.h> #include <ctype.h> char *progrname; #define HUGE  
10000
```

```
/* large number of lines */
```

```
main(argc, argv) int argc; char *argv [ ] ;
```

```
{
```

```
FILE *fin, *fout, *f1, *f2, *efopen(); char buf[BUFSIZ], *mktemp(); char  
*diffout = "idiff.XXXXXXX";
```

```
progrname = argv[0]; if (argc != 3) { fprintf(stderr, "Usage: idiff file1  
file2\n"); exit ( 1 ) ;
```

```
} f1 = efopen(argv[1], "r"); f2 = efopen(argv[2], "r"); fout =  
efopen("idiff.out", "w"); mktemp(diffout); sprintf(buf,"diff %s %s  
>%s",argv[1],argv[2],diffout); system( buf ) ; fin = efopen(diffout, "r");
```

```
idiff(f1, f2, fin, fout); unlink(diffout); printf("%s output in file idiff.out\n",
programe); exit(O);

}
```

The function `mktemp(3)` creates a file whose name is guaranteed to be different from any existing file. `mktemp` overwrites its argument: the six x's are replaced by the process-id of the `idiff` process and a letter. The system call `unlink(2)` removes the named file from the file system. The job of looping through the changes reported by `diff` is handled by a function called `idiff`. The basic idea is simple enough: print a chunk of `diff` output, skip over the unwanted data in one file, then copy the desired version from the other. There is a lot of tedious detail, so the code is bigger than we'd like, but it's easy enough to understand in pieces.

196

THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

```
idiff(f1, f2, fin, fout) 1* process diffs *1 FILE *f1, *f2, *fin, *fout;

{
```

```
char *tempfile ::: "idiff.XXXXXXX"; char buf[BUFSIZ], buf2[BUFSIZ],
*mktemp(); FILE *ft, *efopen(); int cmd, n, from1, to1, from2, to2, nf1,
nf2;
```

```
mktemp(tempfile); nf1 :::: nf2 ::: 0; while (fgets(buf, sizeof buf, fin) !=
NULL) { parse(buf, &from1, &to1, &cmd, &from2, &to2); n ::: to1-from1
+ to2-from2 + 1; /* #lines from diff *1 if (cmd ::: 'c') n +::: 2; else if
(cmd == 'a') from1++; else if (cmd == 'd') from2++; printf ( "%s", buf); while
(n-- > 0) { fgets(buf, sizeof buf, fin); printf ( "%s", buf);
```

```
} do { printf("? "); fflush(stdout); fgets(buf, sizeof buf, stdin); switch
(buf[0]) {
```

```
case '>':
```

```
nSkip(f1, to1-nf1); ncopy(f2, to2-nf2, fout); break; case '<': nskip(f2, to2-
nf2); ncopy(f1, to1-nf1, fout); break; case 'e': ncopy(f1, from1-1-nf1,
fout); nskip(f2, from2-1-nf2); ft ::: efopen(tempfile, "w"); ncopy(f1, to1+1-
from1, ft); fprintf(ft, "---\n"); ncopy(f2, to2+1-from2, ft); fclose(ft);
sprintf(buf2, "ed %s", tempfile); system( buf2) ; ft ::: efopen(tempfile, "r");
ncopy(ft, HUGE, fout);
```

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

197

```
fclose(ft) ; break; case 'I': system(buf+1); printf("!\\n"); break; default:  
printf("< or > or e or !\\n"); break;
```

```
} } while (buf[O]!='<' && buf[O]!='>' && buf[O]!='e'); nf 1 = to 1 ; nf2 =  
to2;
```

```
} ncopy(f1, HUGE, fout); /* can fail on very long files */ unlink(tempfile);
```

```
}
```

The function parse does the mundane but tricky job of parsing the lines produced by diff, extracting the four line numbers and the command (one of a, c or d). parse is complicated a bit because diff can produce either one line number or two on either side of the command letter.

```
parse(s, pfrom1, pto1, pcmd, pfrom2, pto2) char *s; int *pcmd, *pfrom1,  
*pto1, *pfrom2, *pto2;
```

```
{ #define a2i(p) while (isdigit(*s» p = 10*(p) + *s++ - '0'
```

```

*pf1 = *pt1 = *pf2 = *pt2 = 0; a2i ( *pf1 ); if (*s == ',') {
s++; a2i ( *pt1 ); } else *pt1 = *pf1; *pcmd = *s++; a2i ( *pf2
); if (*s == ',') { s++; a2i(*pt2); } else *pt2 = *pf2;

}

```

The macro a2i handles our specialized conversion from ASCII to integer in the four places it occurs. nskip and ncopy skip over or copy the specified number of lines from a file:

198 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

```

nskip(fin, n) /* skip n lines of file fin */ FILE *fin;

```

```

{

```

```

char buf[BUFSIZ];

```

```

while (n-- > 0) fgets(buf, sizeof buf, fin);

```



```
}
```

```
ncopy(fin, n, fout) /* copy n lines from fin to fout */ FILE *fin, *fout;
```

```
{
```

```
char buf[BUFSIZ];
```

```
while (n-- > 0) { if (fgets(buf, sizeof buf, fin) == NULL) return; fputs(buf,  
fout);
```

```
}
```

```
}
```

As it stands, idiff doesn't quit gracefully if it is interrupted, since it leaves several files lying around in /tmp. In the next chapter, we will show how to catch interrupts to remove temporary files like those used here. The crucial observation with both zap and idiff is that most of the hard work has been done by someone else. These programs merely put a convenient interface on another program that computes the right information. It's worth watching for opportunities to build on someone else's labor instead of doing it yourself - it's a cheap way to be more productive. Exercise 6-13. Add the command q to idiff: the response q< will take all the rest of the '<' choices automatically; q> will take the all the rest of the '>' choices. 0 Exercise 6-

14. Modify idiff so that any diff arguments are passed on to diff; -b and -h are likely candidates. Modify idiff so that a different editor can be specified, as in

```
$ idiff -e another-editor file 1 file2
```

How do these two modifications interact? 0 Exercise 6-15. Change idiff to use popen and pclose instead of a temporary file for the output of diff. What difference does it make in program speed and complexity? 0 Exercise 6-16. diff has the property that if one of its arguments is a directory, it searches that directory for a file with the same name as the other argument. But if you try the same thing with idiff, it fails in a strange way. Explain what happens, then fix it. 0

CHAPTER 6

PROGRAMMING WITH STANDARD I/O

199

6.9 Accessing the environment It is easy to access shell environment variables from a C program, and this can sometimes be used to make programs adapt to their environment without requiring much of their users. For example, suppose that you are using a terminal in which the screen size is bigger than the normal 24 lines. If you want to use p and take full advantage of your terminal's capabilities, what choices are open to you? It's a bother to have to specify the screen size each time you use p:

\$ P -36 You could always put a shell file in your bin:

```
$ cat /usr/you/bin/p exec lusr/bin/p -36 $* $
```

A third solution is to modify `p` to use an environment variable that defines the properties of your terminal. Suppose that you define the variable `PAGESIZE` in your `0` profile: `PAGESIZE=36 export PAGESIZE` The routine `getenv ("var")` searches the environment for the shell variable `var` and returns its value as a string of characters, or `NULL` if the variable is not defined. Given `getenv`, it's easy to modify `p`. All that is needed is to add a couple of declarations and a call to `getenv` to the beginning of the main routine.

1* `p`: print input in chunks (version 3) *1

```
char *p, *getenv();
```

```
progname = argv[0]; if « p=getenv( "PAGESIZE" ) } != NULL } pagesize  
== atoi(p); if (argc > 1 && argv[1][0] == '-') { pagesize == atoi(&argv[1]  
[1]); argc--; argv++;
```

```
}
```

Optional arguments are processed after the environment variable, so any explicit page size will still override an implicit one. Exercise 6-17. Modify `idiff` to search the environment for the name of the editor to be used. Modify 2, 3, etc., to use `PAGESIZE`. 0

200 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 6

History and bibliographic notes The standard I/O library was designed by Dennis Ritchie, after Mike Lesk's portable I/O library. The intent of both packages was to provide enough standard facilities that programs could be moved from UNIX to non-UNIX systems without change. Our design of `p` is based on a program by Henry Spencer. `adb` was written by Steve Bourne, `sdb` by Howard Katseff, and `lint` by Steve Johnson. `idiff` is loosely based on a program originally written by Joe Maranzano. `diff` itself is by Doug McIlroy, and is based on an algorithm invented independently by Harold Stone and by Wayne Hunt and Tom Szymanski. (See "A fast algorithm for computing longest common subsequences," by J. W. Hunt and T. G. Szymanski, CACM, May, 1977.) The `diff` algorithm is described in M. D. McIlroy and J. W. Hunt, "An algorithm for differential file comparison," Bell Labs Computing Science Technical Report 41, 1976. To quote McIlroy, "I had tried at least three completely different algorithms before the final one. `diff` is a quintessential case of not settling for mere competency in a program but revising it until it was right."

CHAPTER 7: UNIX SYSTEM CALLS

This chapter concentrates on the lowest level of interaction with the UNIX operating system - the system calls. These are the entries to the kernel. They are the facilities that the operating system provides; everything else is built on top of them. We will cover several major areas. First is the I/O system, the foundation beneath library routines like `fopen` and `putc`.

I'll talk more about the file system as well, particularly directories and inodes. Next comes a discussion of processes - how to run programs from within a program. After that we will talk about signals and interrupts: what happens when you push the DELETE key, and how to handle that sensibly in a program. As in Chapter 6, many of our examples are useful programs that were not part of the 7th Edition. Even if they are not directly helpful to you, you should learn something from reading them, and they might suggest similar tools that you could build for your system. Full details on the system calls are in Section 2 of the UNIX Programmer's Manual; this chapter describes the most important parts, but makes no pretense of completeness.

7.1 Low-level I/O

The lowest level of I/O is a direct entry into the operating system. Your program reads or writes files in chunks of any convenient size. The kernel buffers your data into chunks that match the peripheral devices, and schedules operations on the devices to optimize their performance over all users.

File descriptors All input and output is done by reading or writing files, because all peripheral devices, even your terminal, are files in the file system. This means that a single interface handles all communication between a program and peripheral devices. In the most general case, before reading or writing a file, it is necessary to inform the system of your intent to do so, a process called opening the file. If

202 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

you are going to write on a file, it may also be necessary to create it. The system checks your right to do so (Does the file exist? Do you have permission to access it?), and if all is well, returns a non-negative integer called a file descriptor. Whenever I/O is to be done on the file, the file descriptor is used instead of the name to identify the file. All information about an open file is maintained by the system; your program refers to the file only by the file descriptor. A FILE pointer as discussed in Chapter 6 points to a structure that contains, among other things, the file descriptor; the macro `fildeno (f P)` defined in `<stdio. h>` returns the file descriptor. There are special arrangements to make terminal input and output convenient. When it is started by the shell, a program inherits three open files, with file descriptors 0, 1, and 2, called the standard input, the standard output, and the standard error. All of these are by default connected to the terminal, so if a program only reads file descriptor 0 and writes file descriptors 1 and 2, it can do I/O without having to open files. If the program opens any other files, they will have file descriptors 3, 4, etc. If I/O is redirected to or from files or pipes, the shell changes the default assignments for file descriptors 0 and 1 from the terminal to the named files. Normally file descriptor 2 remains attached to the terminal, so error messages can go there. Shell incantations such as `2>filename` and `2>& 1` will cause rearrangements of the defaults, but the file assignments are changed by the shell, not by the program. (The program itself can rearrange these further if it wishes, but this is rare.)

File I/O -- read and write All input and output is done by two system calls, read and write, which are accessed from C by functions of the same name. For both, the first argument is a file descriptor. The second argument is an array of bytes that serves as the data source or destination. The third argument is the number of bytes to be transferred.

```
int fd, n, nread, nwritten; char buf[SIZE];
```

```
nread = read(fd, buf, n); nwritten = write(fd, buf, n);
```

Each call returns a count of the number of bytes transferred. On reading, the number of bytes returned may be less than the number requested, because fewer than *n* bytes remained to be read. (When the file is a terminal, read normally reads only up to the next newline, which is usually less than what was requested.) A return value of zero implies end of file, and -1 indicates an error of some sort. For writing, the value returned is the number of bytes actually written; an error has occurred if this isn't equal to the number supposed to be written. While the number of bytes to be read or written is not restricted, the two

CHAPTER 7

most common values are 1, which means one character at a time ("unbuffered"), and the size of a block on a disc, most often 512 or 1024 bytes. (The parameter BUFSIZ in `<stdio.h>` has this value.) To illustrate, here is a program to copy its input to its output. Since the input and output can be redirected to any file or device, it will actually copy anything to anything: it's a bare-bones implementation of cat.

```
/* cat: minimal version */ #define SIZE 512 /* arbitrary */
```

```
main ( ) {
```

```
char buf[SIZE]; int n;
```

```
while «n = read(O, buf, sizeof buf)» > 0 { write(1, buf, n); exit(O);
```

```
}
```

If the file size is not a multiple of SIZE, some read will return a smaller number of bytes to be written by write; the next call to read after that will return zero. Reading and writing in chunks that match the disc will be most efficient, but even character-at-a-time I/O is feasible -"for modest amounts of data, because the kernel buffers your data; the main cost is the system calls. ed, for example, uses one-byte reads to retrieve its standard input. We timed this version of cat on a file of 54000 bytes, for six values of SIZE:

SIZE 1 10 100 512 1024 5120

Time (user+ system, sec.) PDP-11/70 V AX-11/750 271.0 188.8 29.9 19.3 3.8
2.6 1.3 1.0 1.2 0.6 1.0 0.6

The disc block size is 512 bytes on the PDP-11 system and 1024 on the VAX. It is quite legal for several processes to be accessing the same file at the same time; indeed, one process can be writing while another is reading. If this isn't what you wanted, it can be disconcerting, but it's sometimes useful. Even though one call to read returns 0 and thus signals end of file, if more data is written on that file, a subsequent read will find more bytes available. This observation is the basis of a program called reads low, which continues to read its input, regardless of whether it got an end of file or not. reads low is

204 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

handy for watching the progress of a program:

```
$ slowprog >temp & 5213 $ readslow <temp :
```

Process-id grep something

In other words, a slow program produces output in a file; reads low, perhaps in collaboration with some other program, watches the data accumulate. Structurally, reads low is identical to cat except that it loops instead of quitting when it encounters the current end of the input. It has to use low-level I/O because the standard library routines continue to report EOF after the first end of file.

```
1* reads low: #define SIZE
```

```
keep reading, waiting for more *1 512 1* arbitrary *1
```

```
ma i n ( ) {
```

```
char buf[SIZE]; int n;
```

```
for (;;) { while ((n = read(O, buf, sizeof buf)) > 0) write(1, buf, n);  
sleep(10);
```

```
}
```

```
}
```

The function `sleep` causes the program to be suspended for the specified number of seconds; it is described in `sleep(3)`. We don't want `reads low` to bang away at the file continuously looking for more data; that would be too costly in CPU time. Thus this version of `readslow` copies its input up to the end of file, sleeps a while, then tries again. If more data arrives while it is asleep, it will be read by the next read. Exercise 7-1. Add a `-n` argument to `reads low` so the default sleep time can be changed to `n` seconds. Some systems provide an option `-f` ("forever") for `tail` that combines the functions of `tail` with those of `reads low`. Comment on this design. 0 Exercise 7-2. What happens to `reads low` if the file being read is truncated? How would you fix it? Hint: read about `fstat` in Section 7.3. 0

File creation -- `open`, `creat`, `close`, `unlink` Other than the default standard input, output and error files, you must explicitly open files in order to read or write them. There are two system calls for this, `open` and `creat`.t

t Ken Thompson was once asked what he would do differently if he were redesigning the UNIX sys- tem. His reply: "I'd spell `creat` with an e."

CHAPTER 7

UNIX SYSTEM CALLS 205

`open` is rather like `f open` in the previous chapter, except that instead of returning a file pointer, it returns a file descriptor, which is an `int`

```
char *name; int fd, rwmode;
```

```
fd = open(name, rmode);
```

As with `fopen`, the `name` argument is a character string containing the filename. The access mode argument is different, however: `rmode` is 0 for read, 1 for write, and 2 to open a file for both reading and writing. `open` returns -1 if any error occurs; otherwise it returns a valid file descriptor. It is an error to try to open a file that does not exist. The system call `creat` is provided to create new files, or to rewrite old ones.

```
int perms;
```

```
fd = creat(name, perms);
```

`creat` returns a file descriptor if it was able to create the file called `name`, and -1 if not. If the file does not exist, `creat` creates it with the permissions specified by the `perms` argument. If the file already exists, `creat` will truncate it to zero length; it is not an error to create a file that already exists. (The permissions will not be changed.) Regardless of `perms`, a created file is open for writing. As described in Chapter 2, there are nine bits of protection information associated with a file, controlling read, write and execute permission, so a three-digit octal number is convenient for specifying them. For example, 0755 specifies read, write and execute permission for the owner, and read and execute permission for the group and everyone else. Don't forget the leading 0, which is how octal numbers are specified in C. To illustrate, here is a simplified version of `cpo`. The main simplification is that our version copies only one file, and does not permit the second argument to be a directory. Another blemish is that our version does not

preserve the permissions of the source file; we will show how to remedy this later.

206 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

```
/* cp: mirtimal version */ #include <stdio.h> #define PERMS 0644 /* RW  
for owner, R for group, others */ char *progrname;
```

```
main(argc, argv) int argc; char *argv [ ] ;
```

```
/* cp: copy f1 to f2 */
```

```
{
```

```
int f1, f2, n; char buf[BUFSIZ];
```

```
progrname = argv[0]; if (argc != 3) error("Usage: %s from to", progrname);  
if «f1 :::: open(argv[1], a)» :::::::::: -1} error("can't open %s", argv[1]); if «f2  
= creat(argv[2], PERMS)» === -1} error("can't create %s", argv[2]);
```

```

while «n == read(f1, buf, BUFSIZ)} > 0} if (write(f2, buf, n) != n)
error("write error", (char *) a); exit(0);

}

```

We will discuss error in the next sub-section. There is a limit (typically about 20; look for `NOFILE` in `<sys/param.h>`) on the number of files that a program may have open simultaneously. Accordingly, any program that intends to process many files must be prepared to re-use file descriptors. The system call `close` breaks the connection between a filename and a file descriptor, freeing the file descriptor for use with some other file. Termination of a program via `exit` or return from the main program closes all open files. The system call `unlink` removes a file from the file system.

Error processing -- `errno` The system calls discussed in this section, and in fact all system calls, can incur errors. Usually they indicate an error by returning a value of `-1`. Sometimes it is nice to know what specific error occurred; for this purpose all system calls, when appropriate, leave an error number in an external integer called `errno`. (The meanings of the various error numbers are listed in the introduction to Section 2 of the UNIX Programmer's Manual.) By using `errno`, your program can, for example, determine whether an attempt to open a file failed because it did not exist or because you lacked permission to read it. There is also an array of character strings `sys_errlist` indexed by `errno` that translates the numbers into a meaningful string. Our version of error uses

CHAPTER 7

UNIX SYSTEM CALLS 207

these data structures:

```
error(s1, 52} char *s1,
```

```
1* print error message and die *1 *s2;
```

```
{
```

```
extern int errno, sys_nerr; extern char *sys_errlist[], *progname;
```

```
if (progname) fprintf(stderr, "%s: ", progname); fprintf(stderr, s1, s2); if  
(errno > 0 && errno < sys_nerr) fprintf(stderr, " (%s)", sys_errlist[errno]);  
fprintf ( stderr, "\n"); exit(1);
```

```
}
```

errno is initially zero, and should always be less than sys_nerr. It is not reset to zero when things go well, however, so you must reset it after each error if your program intends to continue. Here is how error messages appear with this version of cp: \$ cp £00 bar cp: can't open foo (No such file

```
or directory) $ date >£00; chmod 0 £00 Make an unreadable file $ cp £00
bar cp: can't open foo (Permission denied) $
```

Random access - lseek File I/O is normally sequential: each read or write takes place in the file right after the previous one. When necessary, however, a file can be read or written in an arbitrary order. The system call lseek provides a way to move around in a file without actually reading or writing:

```
int fd, origin; long offset, pos, lseek();
```

```
pos = lseek(fd, offset, origin);
```

forces the current position in the file whose descriptor is fd to move to position offset, which is taken relative to the location specified by origin. Subsequent reading or writing will begin at that position. origin can be 0, 1, or 2 to specify that offset is to be measured from the beginning, from the current position, or from the end of the file. The value returned is the new absolute position, or - 1 for an error. For example, to append to a file, seek to the end before writing:

```
lseek(fd, 0, 2);
```


CHAPTER 7

To get back to the beginning ("rewind"),

```
lseek(fd, OL, a);
```

To determine the current position, `pos = lseek(fd, OL, 1);`

Notice the OL argument: the offset is a long integer. (The 'l' in lseek stands for 'long,' to distinguish it from the 6th Edition seek system call that used short integers.) With lseek, it is possible to treat files more or less like large arrays, at the price of slower access. For example, the following function reads any number of bytes from any place in a file.

```
get(fd, pos, buf, n) 1* read n bytes from position pos *1 int fd, n; long pos;  
char *buf;
```

```
{
```

```
if (lseek(fd, pos, O) == -1) return -1; else return read(fd, buf, n);
```

```
1* get to pos *1
```

```
}
```

Exercise 7-3. Modify `readslow` to handle a filename argument if one is present. Add the option `-e`:

```
$ readslow -e
```

causes `readslow` to seek to the end of the input before beginning to read. What does `lseek` do on a pipe? 0 Exercise 7-4. Rewrite `efopen` from Chapter 6 to call `error`. 0

7.2 File system: directories The next topic is how to walk through the directory hierarchy. This doesn't actually use any new system calls, just some old ones in a new context. We will illustrate by writing a function called `spname` that tries to cope with misspelled filenames. The function

```
n = spname (name, newname);
```

searches for a file with a name "close enough" to `name`. If one is found, it is copied into `newname`. The value `n` returned by `spname` is `-1` if nothing close enough was found, `0` if there was an exact match, and `1` if a correction was made. `spname` is a convenient addition to the `p` command: if you try to print a file but misspell the name, `p` can ask if you really meant something else:

CHAPTER 7

UNIX SYSTEM CALLS 209

```
$ p /usr/src/cmd/p/spname. c Horribly botched name II  
lusrsrc/cmd/p/spname. c"? y Suggested correction accepted 1* spname:  
return correctly spelled filename *1
```

As we will write it, `spname` will try to correct, in each component of the filename, mismatches in which a single letter has been dropped or added, or a single letter is wrong, or a pair of letters exchanged; all of these are illustrated above. This is a boon for sloppy typists. Before writing the code, a short review of file system structure is in order. A directory is a file containing a list of file names and an indication of where they are located. The "location" is actually an index into another table called the inode table. The inode for a file is where all information about the file except its name is kept. A directory entry thus consists of only two items, an inode number and the file name. The precise specification can be found in the file `<sys/dir.h>`:

```
$ cat /usr/include/sys/dir.h #define DIRSIZ 14 1* max length of file name  
*1
```

```
struct direct {
```

1* structure of directory entry *1

ino_t d_ino; 1* inode number *1 char d_name[DIRSIZ]; 1* file name *1

};

The "type" `ino_t` is a typedef describing the index into the inode table. It happens to be unsigned short on POP-II and VAX versions of the system, but this is definitely not the sort of information to embed in a program: it might be different on a different machine. Hence the typedef. A complete set of "system" types is found in `<sys/types.h>`, which must be included before `<sys/dir.h>`. The operation of `sname` is straightforward enough, although there are a lot of boundary conditions to get right. Suppose the file name is `/dl/d2/lf`. The basic idea is to peel off the first component (`/`), then search that directory for a name close to the next component (`dl`), then search that directory for something near `d2`, and so on, until a match has been found for each component. If at any stage there isn't a plausible candidate in the directory, the search is abandoned. We have divided the job into three functions. `sname` itself isolates the components of the path and builds them into a "best match so far" filename. It calls `mindist`, which searches a given directory for the file that is closest to the current guess, using a third function, `spdist`, to compute the distance between two names.

CHAPTER 7

```
/* spname: return correctly spelled filename */ /* * spname(oldname,  
newname) char *oldname, *newname; * returns -1 if no reasonable match  
to oldname, * 0 if exact match, * 1 if corrected. * stores corrected name in  
newname. */
```

```
#include <sys/types.h> #include <sys/dir.h>
```

```
spname(oldname, newname) char *oldname, *newname;
```

```
{
```

```
char *p, guess[DIRSIZ+1], best[DIRSIZ+1]; char *new = newname, *old =  
oldname;
```

```
for (;;) { while (*old == '/') /* skip slashes */ *new++ = *old++; *new = '\0';  
if (*old == '\0') /* exact or corrected */ return  
strcmp(oldname, newname) != 0; p = guess; /* copy next component into  
guess */ for ( ; *old != '/' && *old != '\0'; old++) if (p < guess+DIRSIZ)  
*p++ = *old; *p = '\0'; if (mindist(newname, guess, best) >= 3) return -1;  
/* hopeless */ for (p = best; *new = *p++; /* add to end */ new++; /* of  
newname */
```

```
}
```

```
}
```

CHAPTER 7

UNIX SYSTEM CALLS 211

```
mindist(dir, guess, best) /* search dir for guess */ char *dir, *guess, *best;
```

```
{
```

```
/* set best, return distance 0003 */ int d, nd, fd; struct { ino_t ino; char  
name[DIRSIZ+1]; /* 1 more than in dir.h */ } nbuf;
```

```
nbuf.name[DIRSIZ] = if (dir[0] == '\0')
```

```
'\0'; /* +1 for terminal '\0' */ /* current directory */
```

```
dir = "0"; d = 3; /* minimum distance */ if («fd=open(dir, 0» == -1) return d;  
while (read(fd, (char *) &nbuf, sizeof(struct direct» > 0) if (nbuf.ino) { nd =  
spdist(nbuf.name, guess); if (nd <= d && nd != 3) { strcpy(best,  
nbuf.name); d = nd; if (d == 0) /* exact match */ break;
```

```
}
```

```
} close(fd) ; return d;
```

```
}
```

If the directory name given to `mindist` is empty, '0' is searched. `mindist` reads one directory entry at a time. Notice that the buffer for read is a structure, not an array of characters. We use `sizeof` to compute the number of bytes, and coerce the address to a character pointer. If a slot in a directory is not currently in use (because a file has been removed), then the inode entry is zero, and this position is skipped. The distance test is

```
if (nd <= d 000)
```

instead of

`if (nd < d 0 0 .)` so that any other single character IS a better match than the first entry in a directory.

```
, ,
```

II , which IS always

212

THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER

```
/* spdist: return distance between two names */ /* * very rough spelling  
metric: * 0 if the strings are identical * 1 if two chars are transposed * 2 if  
one char wrong, added or deleted * 3 otherwise */
```

```
#define EQ(s,t) (strcmp(s,t) == 0)
```

```
spdist(s, t) char *s, *t;
```

```
{
```

```
while (*s++ == *t) if (*t++ == '\0') return 0; 1* exact match */ if (*--s) { if  
(*t) { if (s[1] && t[1] && *s == t[1] && *t == s[1] && EQ(s+2, t+2)»  
return 1; /* transposition */ if (EQ(s+1, t+1)» return 2; 1* 1 char mismatch  
*/
```



```
} if (EQ ( s + 1, t» return 2;
```

```
1* extra character */
```

```
} if (*t && EQ(s, t+1» return 2; return 3;
```

```
1* missing character */
```

```
}
```

Once we have `sname`, integrating spelling correction into `p` is easy:

CHAPTER 7

UNIX SYSTEM CALLS

213

```
/* p: print input in chunks (version 4) */
```

```
#include <stdio.h> #define PAGESIZE char *progrname;
```

```
22 /* program name for error message */
```

```
main(argc, argv) int argc; char *argv[];
```

```
{
```

```
FILE *fp, *efopen(); int i, pagesize = PAGESIZE; char *p, *getenv(),  
buf[BUFSIZ];
```

```
progrname = argv[0]; if («p=getenv("PAGESIZE")» != NULL) pagesize =  
atoi(p); if (argc > 1 && argv[1][0] == '-') { pagesize = atoi(&argv[1][1]);  
argc--; argv++;
```

```
} if (argc == 1) print(stdin, pagesize); else for (i = 1; i < argc; i++) switch  
(spname(argv[i], buf)» { case -1: /* no match possible */ fp = efopen(argv[i],  
"r"); break; case 1: /* corrected */ fprintf(stderr, """"%s""?"", buf); if (ttyin()  
== 'n') break; argv[i] = buf; /* fall through... */ case 0: /* exact match */ fp  
= efopen(argv[i], "r"); print(fp, pagesize); fclose(fp) ;
```

```
} exit(0);
```

}

Spelling correction is not something to be blindly applied to every program that uses filenames. It works well with `p` because `p` is interactive, but it's not suitable for programs that might not be interactive. Exercise 7-5. How much can you improve on the heuristic for selecting the best match in `sname`? For example, it is foolish to treat a regular file as if it were a directory;

214 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

this can happen with the current version. 0 Exercise 7-6. The name `tx` matches whichever of `tc` happens to come last in the directory, for any single character `c`. Can you invent a better distance measure? Implement it and see how well it works with real users. 0 Exercise 7-7. `mindist` reads the directory one entry at a time. Does `p` run perceptibly faster if directory reading is done in bigger chunks? 0 Exercise 7-8. Modify `sname` to return a name that is a prefix of the desired name if no closer match can be found. How should ties be broken if there are several names that all match the prefix? 0 Exercise 7-9. What other programs could profit from `sname`? Design a standalone program that would apply correction to its arguments before passing them along to another program, as in `$ fix prog filenames...`

Can you write a version of `cd` that uses `sname`? How would you install it?
0

703 File system: inodes In this section we will discuss system calls that deal with the file system and in particular with the information about files, such as size, dates, permissions, and so on. These system calls allow you to get at all the information we talked about in Chapter 2. Let's dig into the inode itself. Part of the inode is described by a structure called stat, defined in <sys/stat.. h>:

```
struct stat /* structure returned by stat */ {
```

```
dev_t ino_t short short short short dev_t off_t time_t time_t time_t
```

```
};
```

```
st_dev; st_ino; st_mode; st_nlink; st_uid; st_gid; st_rdev; st_size; st_atime;  
st_mtime; st_ctime;
```

```
/* device of inode */ /* inode number */ /* mode bits */ /* number of links  
to file */ /* owner's userid */ /* owner's group id */ /* for special files */ /*  
file size in characters */ /* time file last read */ /* time file last written or  
created */ /* time file or inode last changed */
```

Most of the fields are explained by the comments. Types like dev_t and ino_t are defined in <sys/types.. h>, as discussed above. The st_mode entry contains a set of flags describing the file; for convenience, the flag definitions are also part of the file <sys/stat.. h>:

CHAPTER 7

```
#define #define #define #define #define #define #define #define #define  
#define #define
```

```
S_IFMT 0170000 /* S_IFDIR 0040000 /* S_IFCHR 0020000 /* S_IFBLK  
0060000 /* S_IFREG 0100000 /* S_ISUID 0004000 /* S_ISGID 0002000  
/* S_ISVTX 0001000 /* S_IREAD 0000400 /* S_IWRITE 0000200 /*  
S_IEXEC 0000100 /*
```

UNIX SYSTEM CALLS 215

type of file */ directory */ character special */ block special */ regular */ set
user id on execution */ set group id on execution */ save swapped text even
after use */ read permission, owner */ write permission, owner */
execute/search permission, owner */

The inode for a file is accessed by a pair of system calls named `stat` and `fstat`. `stat` takes a filename and returns inode information for that file (or -1 if there is an error). `fstat` does the same from a file descriptor for an open file (not from a FILE pointer). That is,

```
char *name; int fd; struct stat stbuf; stat(name, &stbuf); fstat(fd, &stbuf);
```

fills the structure `stbuf` with the inode information for the file name or file descriptor `fd`. With all these facts in hand, we can start to write some useful code. Let us begin with a C version of `checkmail`, a program that watches your mailbox. If the file grows larger, `checkmail` prints "You have mail " and rings the bell. (If the file gets shorter, that is presumably because you have just read and deleted some mail, and no message is wanted.) This is entirely adequate as a first step; you can get fancier once this works.

216 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

```
/* checkmail: watch user's mailbox */ #include <stdio.h> #include  
<sys/types.h> #include <sys/stat.h> char *progname; char *maildir =  
"/usr/spool/mail"; /* system dependent */
```

```
main(argc, argv) int argc; char *argv [ ] ;
```

```
{
```

```
struct stat buf; char *name, *getlogin(); int lastsize = 0;
```

```
progname = argv[0]; if («name = getlogin(» -- NULL) error("can't get login  
name", (char *) 0); if (chdir(maildir) == -1) error("can't cd to %s", maildir);  
for (;;) { if (stat(name, &buf) == -1) /* no mailbox */ buf.st_size = 0; if
```

```
(buf.st_size > lastsize) fprintf(stderr, "\nYou have mail\n"); lastsize =  
buf.st_size; sleep(60);
```

```
}
```

```
}
```

The function `getlogin(3)` returns your login name, or `NULL` if it can't. `checkmail` changes to the mail directory with the system call `chdir`, so that the subsequent `stat` calls will not have to search each directory from the root to the mail directory. You might have to change `maildir` to be correct on your system. We wrote `checkmail` to keep trying even if there is no mailbox, since most versions of mail remove the mailbox if it's empty. We wrote this program in Chapter 5 in part to illustrate shell loops. That version created several processes every time it looked at the mailbox, so it might be more of a system load than you want. The C version is a single process that does a `stat` on the file every minute. How much does it cost to have `checkmail` running in the background all the time? We measured it at well under one second per hour, which is low enough that it hardly matters.

sv: An illustration of error handling We are next going to write a program called `sv`, similar to `cp`, that will copy a set of files to a directory, but change each target file only if it does not exist or is older than the source. "`sv`" stands for "save"; the idea is that `sv`

CHAPTER 7

UNIX SYSTEM CALLS 217

will not overwrite something that appears to be more up to date. sv uses more of the information in the inode than checkmail does. The design we will use for sv is this: \$ sv file1 file2 000 dir

copies file1 to dir/file1, file2 to dir/file2, etc., except that when a target file is newer than its source file, no copy is made and a warning is printed. To avoid making multiple copies of linked files, sv does not allow /'s in any of the source filenames.

```
/* sv: save new files */ #include <stdio.h> #include <sys/types.h> #include  
<sys/diro.h> #include <sys/stat.h> char *progname;
```

```
main(argc, argv) int argc; char *argv[];
```

```
{
```

```
int i; struct stat stbuf; char *dir = argv[argc-1];
```

```
progname = argv[0]; if (argc <= 2) error("Usage: %s filesooo dir",  
progname); if (stat(dir, &stbuf) == -1) error("can't access directory %s",  
dir); if ((stbuf.st_mode & S_IFMT) != S_IFDIR) error("%s is not a  
directory", dir); for (i = 1; i < argc-1; i++) sv(argv[i], dir); exit(0);
```



```
}
```

The times in the inode are in seconds-since-long-ago (0:00 GMT, January 1, 1970), so older files have smaller values in their `st_mtime` field.

218 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

```
sv(file, dir) char *file,
```

```
1* save file in dir *1 *dir;
```

```
{
```

```
struct stat sti, sto; int fin, fout, n; char target[BUFSIZ], buf[BUFSIZ],  
*index();
```

```
sprintf(target, "%s/%s", dir, file); if (index(file, 'I') != NULL) 1* strchr() in  
some systems *1 error("won't handle I's in %s", file); if (stat(file, &sti) ==  
-1) error("can't stat %s", file); if (stat(target, &sto) == -1) 1* target not
```

```

present *1 sto..st_mtime = 0; 1* so make it look old *1 if (sti..st_mtime <
sto..st_mtime) 1* target is newer */ fprintf(stderr, "%s: %s not copied\n",
progname, file); else if «fin = open(file, 0» == -1) error("can't open file
%s", file); else if «fout = creat(target, sti..st_mode» -- -1) error("can't create
%s", target); else while «n = read(fin, buf, sizeof buf» > 0) if (write(fout,
buf, n) 1= n) error("error writing %s", target);

```

```

close(fin) ; close (fout) ;

```

```

}

```

We used `creat` instead of the standard I/O functions so that `sv` can preserve the mode of the input file. (Note that `index` and `strchr` are different names for the same routine; check your manual under `string(3)` to see which name your system uses.) Although the `sv` program is rather specialized, it does indicate some important ideas. Many programs are not "system programs" but may still use information maintained by the operating system and accessed through system calls. For such programs, it is crucial that the representation of the information appear only in standard header files like `<stat.h>` and `<dir.h>`, and that programs include those files instead of embedding the actual declarations in themselves. Such code is much more likely to be portable from one system to another. It is also worth noting that at least two thirds of the code in `sv` is error checking. In the early stages of writing a program, it's tempting to skimp on error handling, since it is a diversion from the main task. And once the program "works," it's hard to be enthusiastic about going back to put in the checks that convert a private program into one that works regardless of what happens.

CHAPTER 7

sv isn't proof against all possible disasters - it doesn't deal with interrupts at awkward times, for instance - but it's more careful than most programs. To focus on just one point for a moment, consider the final write statement. It is rare that a write fails, so many programs ignore the possibility. But discs run out of space; users exceed quotas; communications lines break. All of these can cause write errors, and you are a lot better off if you hear about them than if the program silently pretends that all is well. The moral is that error checking is tedious but important. We have been cavalier in most of the programs in this book because of space limitations and to focus on more interesting topics. But for real, production programs, you can't afford to ignore errors.

Exercise 7-10. Modify checkmail to identify the sender of the mail as part of the "You have mail" message. Hint: sscanf, lseek.

Exercise 7-11. Modify checkmail so that it does not change to the mail directory before it enters its loop. Does this have a measurable effect on its performance? (Harder) Can you write a version of checkmail that only needs one process to notify all users?

Exercise 7-12. Write a program watchfile that monitors a file and prints the file from the beginning each time it changes. When would you use it?

Exercise 7-13. sv is quite rigid in its error handling. Modify it to continue even if it can't process some file.

Exercise 7-14. Make sv recursive: if one of the source files is a directory, that directory and its files are processed in the same manner. Make cp recursive. Discuss whether cp and sv ought to be the same program, so that cp -v doesn't do the copy if the target is newer.

Exercise 7-15. Write the program random:

```
$ random filename
```

produces one line chosen at random from the file. Given a file people of names, random can be used in a program called scapegoat, which is valuable for allocating blame:

```
$ cat scapegoat echo "It's all 'random people's fault!" $ scapegoat It's all  
Ken's fault! $
```

Make sure that random is fair regardless of the distribution of line lengths. 0
Exercise 7-16. There's other information in the inode as well, in particular,
disc addresses where the file blocks are located. Examine the file <sys/ino 0
h>, then write a program icat that will read files specified by in ode number
and disc device. (It will work only if the disc in question is readable, of
course.) Under what circumstances is icat useful? 0

220 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

7.4 Processes

This section describes how to execute one program from within another.
The easiest way is with the standard library routine system, mentioned but
censured in Chapter 6. system takes one argument, a command line exactly
as typed at the terminal (except for the newline at the end) and executes it in
a sub-shell. If the command line has to be built from pieces, the in-memory
for- matting capabilities of sprintf may be useful. At the end of this section

we will show a safer version of system for use by interactive programs, but first we must examine the pieces from which it is built.

Low...level process creation -- `execlp` and `execvp` The most basic operation is to execute another program without returning, by using the system call `execlp`. For example, to print the date as the last action of a running program, use

```
execlp("date", "date", (char *) 0);
```

The first argument to `execlp` is the filename of the command; `execlp` extracts the search path (i.e., `$PATH`) from your environment and does the same search as the shell does. The second and subsequent arguments are the command name and the arguments for the command; these become the `argv` array for the new program. The end of the list is marked by a 0 argument. (Read `exec(2)` for insight on the design of `execlp`.) The `execlp` call overlays the existing program with the new one, runs that, then exits. The original program gets control back only when there is an error, for example if the file can't be found or is not executable:

```
execlp("date", "date", (char *) 0); fprintf(stderr, "Couldn't execute 'date'\n");  
exit(1);
```

A variant of `execlp` called `execvp` is useful when you don't know in advance how many arguments there are going to be. The call is

```
execvp(filename, argp);
```

where `argp` is an array of pointers to the arguments (such as `argv`); the last pointer in the array must be `NULL` so `execvp` can tell where the list ends. As with `execlp`, `filename` is the file in which the program is found, and `argp` is the `argv` array for the new program; `argp[0]` is the program name. Neither of these routines provides expansion of metacharacters like `<`, `>`, `*`, quotes, etc., in the argument list. If you want these, use `execlp` to invoke the shell `/bin/ sh`, which then does all the work. Construct a string `commandline` that contains the complete command as it would have been typed at the terminal, then say

```
execlp("/bin/sh", "Wish", "-c", commandline, (char *) 0);
```

CHAPTER 7

UNIX SYSTEM CALLS 221

The argument `-c` says to treat the next argument as the whole command line, not a single argument. As an illustration of `exec`, consider the program `waitfile`. The `com-` mand

```
$ waitfile filename [command J
```

periodically checks the file named. If it is unchanged since last time, the `com-` mand is executed. If no command is specified, the file is copied to the

standard output. We use waitfile to monitor the progress of troff, as in \$
waitfile troffout echo troff done &

The implementation of waitfile uses fstat to extract the time when the file was last changed.

```
1* waitfile: wait until file stops changing *1 #include <stdio.h> #include  
<sys/types.h> #include <sys/stat.h> char *progname;
```

```
main(argc, argv) int argc; char *argv [ ] ;
```

```
{
```

```
int fd; struct stat stbuf; time_t old_time = 0;
```

```
progname = argv[0]; if (argc < 2) error("Usage: %s filename [cmd]",  
progname); if (fd = open(argv[1], 0) == -1) error("can't open %s", argv[1]);  
fstat(fd, &stbuf); while (stbuf.st_mtime != old_time) { old_time =  
stbuf.st_mtime; sleep(60); fstat(fd, &stbuf);
```

```
} if (argc == 2) { 1* copy file *1 exec lp ( "cat", "cat", argv [ 1 ], (char *)  
0); error("can't execute cat %s", argv[1]); } else { 1* run process *1  
execvp(argv[2], &argv[2]); error("can't execute %s", argv[2]);
```

```
} exit(0);
```

```
}
```

222 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

This illustrates both `execlp` and `execvp`. We picked this design because it's useful, but other variations are plausible. For example, `waitfile` could simply return after the file has stopped changing. Exercise 7-17. Modify `watchfile` (Exercise 7-12) so it has the same property as `waitfile`: if there is no command, it copies the file; otherwise it does the command. Could `watchfile` and `waitfile` share source code? Hint: `argv[0]`.

Control of processes - fork and wait The next step is to regain control after running a program with `execlp` or `execvp`. Since these routines simply overlay the new program on the old one, to save the old one requires that it first be split into two copies; one of these can be overlaid, while the other waits for the new, overlaying program to finish. The splitting is done by a system call named `fork`:

```
proc_id = fork();
```


splits the program into two copies, both of which continue to run. The only difference between the two is the value returned by `fork`, the process-id. In one of these processes (the child), `proc_id` is zero. In the other (the parent), `proc_id` is non-zero; it is the process-id of the child. Thus the basic way to call, and return from, another program is `if (fork () == 0) execlp("/bin/sh", "sh", "-c", commandline, (char *) 0);`

And in fact, except for handling errors, this is sufficient. The `fork` makes two copies of the program. In the child, the value returned by `fork` is zero, so it calls `execlp`, which does the commandline and then dies. In the parent, `fork` returns non-zero so it skips the `execlp`. (If there is any error, `fork` returns - 1 .) More often, the parent waits for the child to terminate before continuing itself. This is done with the system call `wait`:

```
int status;
```

```
if (fork () == 0) execlp(...); wait(&status);
```

```
1* child *1 1* parent *1
```

This still doesn't handle any abnormal conditions, such as a failure of the `execlp` or `fork`, or the possibility that there might be more than one child running simultaneously. (`wait` returns the process-id of the terminated child, if you want to check it against the value returned by `fork`.) Finally, this fragment doesn't deal with any funny behavior on the part of the child. Still, these three lines are the heart of the standard system function. The status returned by `wait` encodes in its low-order eight bits the system's idea of the child's exit status; it is 0 for normal termination and non-

CHAPTER 7

UNIX SYSTEM CALLS 223

zero to indicate various kinds of problems. The next higher eight bits are taken from the argument of the call to `exit` or return from `main` that caused termination of the child process. When a program is called by the shell, the three file descriptors 0, 1, and 2 are set up pointing at the right files, and all other file descriptors are available for use. When this program calls another one, correct etiquette suggests making sure the same conditions hold. Neither `fork` nor `exec` calls affect open files in any way; both parent and child have the same open files. If the parent is buffering output that must come out before output from the child, the parent must flush its buffers before the `execlp`. Conversely, if the parent buffers an input stream, the child will lose any information that has been read by the parent. Output can be flushed, but input cannot be put back. Both of these considerations arise if the input or output is being done with the standard I/O library discussed in Chapter 6, since it normally buffers both input and output. It is the inheritance of file descriptors across an `execlp` that breaks `system`: if the calling program does not have its standard input and output connected to the terminal, neither will the command called by `system`. This may be what is wanted; in an `ed` script, for example, the input for a command started with an exclamation mark `!` should probably come from the script. Even then `ed` must read its input one character at a time to avoid input buffering problems. For interactive programs like `p`, however, `system` should reconnect standard input and output to the terminal. One way is to connect them to `/dev/tty`. The system call `dup (fd)` duplicates the file descriptor `fd` on the lowest-numbered unallocated file descriptor, returning a new descriptor that refers to the same open file. This code connects the standard input of a program to a file:

```
int fd;
```

```
fd = open("file", 0); close(0); dup ( fd ) ; close(fd) ;
```

The close (0) deallocates file descriptor 0, the standard input, but as usual doesn't affect the parent. Here is our version of system for interactive programs; it uses progname for error messages. You should ignore the parts of the function that deal with signals; we will return to them in the next section.

224 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

```
1* * Safer version of system for interactive programs *1 #include  
<signal.h> #include <stdio.h>
```

```
system(s) 1* run command line s *1 char *s;
```

```
{
```

```
int status, pid, w, tty; int (*istat) (), (*qstat) (); extern char *progname;
```

```

fflush (stdout) ; tty = open("/dev/tty", 2); if (tty == -1) { fprintf(stderr, "%s:
can't open /dev/tty'n", progname); return -1;

} if «pid = fork(» == 0) { close(O); dup(tty); elose(1); dup(tty); close(2);
dup(tty); close (tty) ; execlp("sh", "sh", "-en, s, (char *) 0); exit ( 127 ) ;

} close(tty) ; istat = signal(SIGINT, SIG_IGN); qstat = signal (SIGQUIT,
SIG_IGN); while «w = wait(&status» 1= pid && w != -1)

if (w == -1) status = -1; signal(SIGINT, istat); signal(SIGQUIT, qstat);
return status;

}

```

Note that /dev/tty is opened with mode 2 - read and write - and then dup'ed to form the standard input and output. This is actually how the system assembles the standard input, output and error when you log in. Therefore, your standard input is writable: \$ echo hello 1>&0 hello \$

This means we could have dup'ed file descriptor 2 to reconnect the standard input and output, but opening /de'v/tty is cleaner and safer. Even this

CHAPTER 7

system has potential problems: open files in the caller, such as `tty` in the routine `tyyin` in `p`, will be passed to the child process. The lesson here is not that you should use our version of `system` for all your programs - it would break a non-interactive `ed`, for example - but that you should understand how processes are managed and use the primitives correctly; the meaning of "correctly" varies with the application, and may not agree with the standard implementation of `system`.

1.5 Signals and interrupts This section is concerned with how to deal gracefully with signals (like interrupts) from the outside world, and with program faults. Program faults arise mainly from illegal memory references, execution of peculiar instructions, or floating point errors. The most common outside-world signals are `interrupt`, which is sent when the `DEL` character is typed; `quit`, generated by the `FS` character (`ctl- \`); `hangup`, caused by hanging up the phone; and `terminate`, generated by the `kill` command. When one of these events occurs, the signal is sent to all processes that were started from the same terminal; unless other arrangements have been made, the signal terminates the process. For most signals, a core image file is written for potential debugging. (See `adb(1)` and `sdb(1)`.) The system call `signal` alters the default action. It has two arguments. The first is a number that specifies the signal. The second is either the address of a function, or a code which requests that the signal be ignored or be given the default action. The file `<signal.h>` contains definitions for the various arguments. Thus

```
#include <signal.h>
```

signal(SIGINT, SIG_IGN); causes interrupts to be ignored, while signal(SIGINT, SIG_DFL); restores the default action of process termination. In all cases, signal returns the previous value of the signal. If the second argument to signal is the name of a function (which must have been declared already in the same source file), the function will be called when the signal occurs. Most commonly this facility is used to allow the program to clean up unfinished business before terminating, for example to delete a temporary file:

226 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

```
#include <signal.h> char *tempfile = "temp.XXXXXX";
```

```
main ( ) {
```

```
extern onintr ( ) ;
```

```
if (signal(SIGINT, SIG_IGN) != SIG_IGN) signal(SIGINT, onintr);  
mktemp(tempfile);
```

```
1* Process ... *1
```

```
exit(0);
```

```
}
```

```
onintr ( ) {
```

```
1* clean up if interrupted *1
```

```
unlink(tempfile); exit(1);
```

```
}
```

Why the test and the double call to signal in main? Recall that signals are sent to all processes started from a particular terminal. Accordingly, when a program is to be run non-interactively (started by &), the shell arranges that the program will ignore interrupts, so it won't be stopped by interrupts intended for foreground processes. If this program began by announcing that all interrupts were to be sent to the onintr routine regardless, that would undo the shell's effort to protect it when run in the background. The solution, shown above, is to test the state of interrupt handling, and to continue to ignore interrupts if they are already being ignored. The code as written depends on the fact that signal returns the previous state of a particular signal. If signals were already being ignored, the process should continue to ignore them; otherwise, they should be caught. A more sophisticated program may wish to intercept an interrupt and interpret it as a request to stop what it is doing and return to its own command-processing loop. Think of a text editor: interrupting a long printout should

not cause it to exit and lose the work already done. The code for this case can be written like this:

CHAPTER 7

UNIX SYSTEM CALLS 227

```
#include <signal.h> #include <setjmp.h> jmp_buf sjbuf;
```

```
main ( ) {
```

```
int onintr ( ) ;
```

```
if (signal(SIGINT, SIG_IGN) != SIG_IGN) signal(SIGINT, onintr);  
setjmp(sjbuf); 1* save current stack position *1
```

```
for (;;) { 1* main processing loop *1
```

```
}
```

```
}
```



```
onintr ( ) {
```

```
1* reset if interrupted *1
```

```
signal(SIGINT, onintr); 1* reset for next interrupt *1 printf ( VI  
'\nInterrupt\n" ) ; longjmp(sjbuf, 0); 1* return to saved state *1
```

```
}
```

The file <setjmp.. h> declares the type jmp_buf as an object in which the stack position can be saved; sjbuf is declared to be such an object. The function setjmp(3) saves a record of where the program was executing. The values of variables are not saved. When an interrupt occurs, a call is forced to the onintr routine, which can print a message, set flags, or whatever. longjmp takes as argument an object stored into by setjmp, and restore control to the location after the call to set jmp. So control (and the stack level) will pop back to the place in the main routine where the main loop is entered . Notice that the signal is set again in onintr after an interrupt occurs. This is necessary: signals are automatically reset to their default action when they occur. Some programs that want to detect signals simply can't be stopped at an arbitrary point, for example in the middle of updating a complicated data structure. The solution is to have the interrupt routine set a flag and return instead of calling exit or longjmp. Execution will continue at the exact point it was interrupted, and the interrupt flag can be tested later. There is one difficulty associated with this approach. Suppose the program is reading the terminal when the interrupt is sent. The specified routine is duly caned; it sets its flag and returns. If it were really true, as we said above, that execution resumes "at the exact point it was

interrupted," the program would continue reading the terminal until the user typed another line. This behavior

228 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

might well be confusing, since the user might not know that the program is reading, and presumably would prefer to have the signal take effect instantly. To resolve this difficulty, the system terminates the read, but with an error status that indicates what happened: `errno` is set to `EINTR`, defined in `<errno.h>`, to indicate an interrupted system call. Thus programs that catch and resume execution after signals should be prepared for "errors" caused by interrupted system calls. (The system calls to watch out for are reads from a terminal, `wait`, and `pause`.) Such a program could use code like the following when it reads the standard input:

```
#include <errno.h> extern int errno;
```

```
if (read(O, &c, 1) <= 0) 1* EOF or interrupted *1 if (errno == EINTR) { 1*  
EOF caused by interrupt */ errno = 0; /* reset for next time *1
```

```
} else {
```

```
1* true end of file *1
```

```
}
```

There is a final subtlety to keep in mind when signal-catching is combined with execution of other programs. Suppose a program catches interrupts, and also includes a method (like "!" in ed) whereby other programs can be executed. Then the code would look something like this: `if (fork() == 0) execlp(...); signal(SIGINT, SIG_IGN); wait(&status); signal(SIGINT, onintr);`

```
1* parent ignores interrupts *1 1* until child is done *1 1* restore interrupts
*1
```

Why is this? Signals are sent to all your processes. Suppose the program you call catches its own interrupts, as an editor does. If you interrupt the subprogram, it will get the signal and return to its main loop, and probably read your terminal. But the calling program will also pop out of its wait for the subprogram and read your terminal. Having two processes reading your terminal is very confusing, since in effect the system flips a coin to decide who should get each line of input. The solution is to have the parent program ignore interrupts until the child is done. This reasoning is reflected in the signal handling in system:

CHAPTER 7

```
#include <signal.h>
```

```
system(s) /* run command line s */ char *s;
```

```
{
```

```
int status, pid, w, tty; int (*istat) (), (*qstat) ();
```

```
if «pid = fork(» == 0) {
```

```
ex e c 1 p ( II S h ", II S h ", II - C ", s, ( c h a r *) 0); exit ( 127) ;
```

```
}
```

```
istat = signal(SIGINT, SIG_IGN); qstat = signal (SIGQUIT, SIG_IGN);
```

```
while «w = wait(&status» 1= pid && w 1= -1)
```

```
if (w == -1) status = -1; signal (SIGINT, istat); signal (SIGQUIT, qstat);  
return status;
```

```
}
```

As an aside on declarations, the function `signal` obviously has a rather strange second argument. It is in fact a pointer to a function delivering an integer, and this is also the type of the signal routine itself. The two values `SIG_IGN` and `SIG_DFL` have the right type, but are chosen so they coincide with no possible actual functions. For the enthusiast, here is how they are defined for the PDP-11 and VAX; the definitions should be sufficiently ugly to encourage use of `<signal.h>`.

```
#define SIG_DFL (int (*)(int))0
#define SIG_IGN (int (*)(int))-1
```

Alarms The system call `alarm(n)` causes a signal `SIGALRM` to be sent to your process `n` seconds later. The alarm signal can be used for making sure that something happens within the proper amount of time; if the something happens, the alarm signal can be turned off, but if it does not, the process can regain control by catching the alarm signal. To illustrate, here is a program called `timeout` that runs another command; if that command has not finished by the specified time, it will be aborted when the alarm goes off. For example, recall the `watchfor` command from Chapter 5. Rather than having it run indefinitely, you might set a

230 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 7

limit of an hour:

```
$ timeout -3600 watchfor dmg &
```

The code in timeout illustrates almost everything we have talked about in the past two sections. The child is created; the parent sets an alarm and then waits for the child to finish. If the alarm arrives first, the child is killed. An attempt is made to return the child's exit status.

```
/* timeout: set time limit on a process */ #include <stdio.h> #include
<signal.h> int pid; /* child process id */ char *progrname;

main(argc, argv) int argc; char *argv [ ] ;

{

int sec = 10, status, onalarm();

progrname = argv[0]; if (argc > 1 && argv[1][0] != '-') { sec = atoi(&argv[1]
[1]); argc--; argv++;

} if (argc < 2) error("Usage: %s [-10] command", progrname); if
«pid=fork(» == 0) { execvp(argv[1], &argv[1]); error("couldn't start %s",
argv[1]);

} signal (SIGALRM, onalarm); alarm (sec) ; if (wait(&status) == -1 ::
(status & 0177) != 0) error("%s killed", argv[1]); exit«status » 8) & 0377);
```

```
}
```

```
onalarm( ) {
```

```
/* kill child when alarm arrives */
```

```
kill(pid, SIGKILL);
```

```
}
```

Exercise 7-18. Can you infer how sleep is implemented? Hint: pause(2). Under what circumstances, if any, could sleep and alarm interfere with each other? 0

CHAPTER 7

UNIX SYSTEM CALLS 231

History and bibliographic notes There is no detailed description of the UNIX system implementation, in part because the code is proprietary. Ken Thompson's paper "UNIX implementa- tion" (BSTJ, July, 1978) describes

the basic ideas. Other papers that discuss related topics are "The UNIX system-a retrospective" in the same issue of BSTJ, and "The evolution of the UNIX time-sharing system" (Symposium on Language Design and Programming Methodology, Springer-Verlag Lecture Notes in Computer Science #79, 1979.) Both are by Dennis Ritchie. The program reads low was invented by Peter Weinberger, as a low-overhead way for spectators to watch the progress of Belle, Ken Thompson and Joe Condon's chess machine, during chess tournaments. Belle recorded the status of its game in a file; onlookers polled the file with reads low so as not to steal too many precious cycles from Belle. (The newest version of the Belle hardware does little computing on its host machine, so the problem has gone away.) Our inspiration for spname comes from Tom Duff. A paper by Ivor Durham, David Lamb and James Saxe entitled "Spelling correction in user interfaces," CACM, October, 1983, presents a somewhat different design for spelling correction, in the context of a mail program.

CHAPTER 8: PR

RA

DEVELOPMENT

The UNIX system was originally meant as a program development environment. In this chapter we'll talk about some of the tools that are particularly suited for developing programs. Our vehicle is a substantial program, an interpreter for a programming language comparable in power to BASIC. We chose to implement a language because it's representative of problems encountered in large programs. Furthermore, many programs can profitably be viewed as languages that convert a systematic input into a sequence of actions and outputs, so we want to illustrate the language development

tools. In this chapter, we will cover specific lessons about 1) yacc, a parser generator, a program that generates a parser from a grammatical description of a language; 2) make, a program for specifying and controlling the processes by which a complicated program is compiled; 3) lex, a program analogous to yacc, for making lexical analyzers. We also want to convey some notions of how to go about such a project - the importance of starting with something small and letting it grow; language evolution; and the use of tools. We will describe the implementation of the language in six stages, each of which would be useful even if the development went no further. These stages closely parallel the way that we actually wrote the program.

(1) A four-function calculator, providing +, -, *, / and parentheses, that operates on floating point numbers. One expression is typed on each line; its value is printed immediately. (2) Variables with names a through z. This version also has unary minus and some defenses against errors. (3) Arbitrarily-long variable names, built-in functions for sin, exp, etc., useful constants like 1T (spelled PI because of typographic limitations), and an exponentiation operator. (4) A change in internals: code is generated for each statement and subsequently interpreted, rather than being evaluated on the fly. No new features are added, but it leads to (5). (5) Control flow: if-else and while, statement grouping with { and }, and 233

234 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

relational operators like >, <=, etc. (6) Recursive functions and procedures, with arguments. We also added statements for input and for output of strings as well as numbers. The resulting language is described in Chapter 9, where it serves as the main example in our presentation of the UNIX document preparation software. Appendix 2 is the reference manual. This is a very long chapter, because there's a lot of detail involved in getting a non-trivial program written correctly, let alone presented. We are assuming that

you understand C, and that you have a copy of the UNIX Programmer's Manual, Volume 2, close at hand, since we simply don't have space to explain every nuance. Hang in, and be prepared to read the chapter a couple of times. We have also included all of the code for the final version in Appendix 3, so you can see more easily how the pieces fit together. By the way, we wasted a lot of time debating names for this language but never came up with anything satisfactory. We settled on hoc, which stands for "high-order calculator." The versions are thus hoc 1, hoc 2, etc.

8.1 Stage 1: A four-function calculator This section describes the implementation of hoc 1, a program that provides about the same capabilities as a minimal pocket calculator, and is substantially less portable. It has only four functions: +, -, *, and /, but it does have parentheses that can be nested arbitrarily deeply, which few pocket calculators provide. If you type an expression followed by RETURN, the answer will be printed on the next line: `$ boc1 4*3*2`

`24 (1+2) * (3+4) 21`

`1/2`

`005`

`355/113`

`3.1415929`

-3-4 hoc1: syntax error near line 4 \$

It doesn't have unary minus yet

Grammars Ever since Backus-Naur Form was developed for Algol, languages have been described by formal grammars. The grammar for hoc 1 is small and simple in its abstract representation:

CHAPTER 8

PROGRAM DEVELOPMENT 235

`expr \.n list expr \.n NUMBER expr + expr expr - expr expr * expr expr /
expr (expr)` In other words, a list is a sequence of expressions, each followed by a new-line. An expression is a number, or a pair of expressions joined by an operator, or a parenthesized expression. This is not complete. Among other things, it does not specify the normal precedence and associativity of the operators, nor does it attach a meaning to any construct. And although list is defined in terms of expr, and expr is defined in terms of NUMBER, NUMBER itself is nowhere defined. These details have to be filled in to go from a sketch of the language to a working program.

list:

expr:

Overview of yacc yacc is a parser generator, that is, a program for converting a grammatical specification of a language like the one above into a parser that will parse statements in the language. yacc provides a way to associate meanings with the components of the grammar in such a way that as the parsing takes place, the meaning can be "evaluated" as well. The stages in using yacc are the following. First, a grammar is written, like the one above, but more precise. This specifies the syntax of the language. yacc can be used at this stage to warn of errors and ambiguities in the grammar. Second, each rule or production of the grammar can be augmented with an action - a statement of what to do when an instance of that grammatical form is found in a program being parsed. The "what to do" part is written in C, with conventions for connecting the grammar to the C code. This defines the semantics of the language. Third, a lexical analyzer is needed, which will read the input being parsed and break it up into meaningful chunks for the parser. A NUMBER is an example of a lexical chunk that is several characters long; single-character operators like + and * are also chunks. A lexical chunk is traditionally called a token. Finally, a controlling routine is needed, to call the parser that yacc built. yacc processes the grammar and the semantic actions into a parsing function, named yyparse, and writes it out as a file of C code. If yacc finds no errors, the parser, the lexical analyzer, and the control routine can be

yacc stands for "yet another compiler-compiler," a comment by its creator, Steve Johnson, on the number of such programs extant at the time it was being developed (around 1972). yacc is one of a handful that have flourished.

CHAPTER 8

compiled, perhaps linked with other C routines, and executed. The operation of this program is to call repeatedly upon the lexical analyzer for tokens, recognize the grammatical (syntactic) structure in the input, and perform the semantic actions as each grammatical rule is recognized. The entry to the lexical analyzer must be named `yylex`, since that is the function that `yyparse` calls each time it wants another token. (All names used by `yacc` start with `y`.) To be somewhat more precise, the input to `yacc` takes this form: `%{` C statements like `#include`, declarations, etc. This section is optional. `%}` `yacc` declarations: lexical tokens, grammar variables, precedence and associativity information `%%` grammar rules and actions `%%` more C statements (optional): `main () { G G G; yyparse (); G G G } yylex () { G G G }`

This is processed by `yacc` and the result written into a file called `y.tab.c`, whose layout is like this:

C statements from between `% {` and `%}`, if any C statements from after second `%%`, if any: `main () { G G G; yyparse (); G G G } yylex () { G G G }`

`yyparse () { parser, which calls yylex () }` It is typical of the UNIX approach that `yacc` produces C instead of a compiled object (`.o`) file. This is the most flexible arrangement - the generated code is portable and amenable to other processing whenever someone has a good idea. `yacc` itself is a powerful tool. It takes some effort to learn, but the effort is repaid many times over. `yacc`-generated parsers are small, efficient, and correct (though the semantic actions are your own responsibility); many nasty parsing problems are taken care of automatically. Language-recognizing programs

are easy to build, and (probably more important) can be modified repeatedly as the language definition evolves.

Stage 1 program The source code for hoc 1 consists of a grammar with actions, a lexical routine yylex, and a main, all in one file hoc.y. (yacc filenames traditionally end in .y, but this convention is not enforced by yacc itself, unlike cc and .c.) The grammar part is the first half of hoc.y:

CHAPTER 8

PROGRAM DEVELOPMENT 237

```
$ cat hocoY %{ #define YYSTYPE double %} %token NUMBER %left  
%left
```

```
/* data type of yacc stack */
```

```
'+'
```

```
, -'
```

```
/* left associative, same precedence */ /* left assoc., higher precedence */
```

'*' , '/'

```
%% list: /* nothing */ list '\n' list expr '\n' { printf("\t%.8g\n", $2); } expr:
NUMBER { $$ = $1 ; } expr '+' expr { $$ = $1 + $3; } expr '-' , expr { $$ =
$1 $3; } expr '*' expr { $$ = $1 * $3; } expr '/' expr { $$ = $1 / $3; } , ( ,
expr ' ) , { $$ = $2; } %% /* end of grammar */
```

There's a lot of new information packed into these few lines. We are not going to explain all of it, and certainly not how the parser works - for that, you will have to read the yacc manual. Alternate rules are separated by 'J'. Any grammar rule can have an associated action, which will be performed when an instance of that rule is recognized in the input. An action is a sequence of C statements enclosed in braces { and }. Within an action, \$n (that is, \$1, \$2, etc.) refers to the value returned by the n-th component of the rule, and \$\$ is the value to be returned as the value of the whole rule. So, for example, in the rule

expr:

```
NUMBER { $$ = $1; }
```

\$ 1 is the value returned by recognizing NUMBER; that value is to be returned as the value of the expr. The particular assignment \$ \$ = \$ 1 can be omitted - \$ \$ is always set to \$1 unless you explicitly set it to something else. At the next level, when the rule is

expr:

expr '+' expr

{ \$\$ = \$1 + \$3; }

the value of the result expr is the sum of the values from the two component expr's. Notice that '+' is \$2; every component is numbered. At the level above this, an expression followed by a newline ('\n') is recognized as a list and its value printed. If the end of the input follows such a construction, the parsing process terminates cleanly. A list can be an empty string; this is how blank input lines are handled. yacc input is free form; our format is the recommended standard.

238 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

In this implementation, the act of recognizing or parsing the input also causes immediate evaluation of the expression. In more complicated situations (including hoc4 and its successors), the parsing process generates code for later execution. You may find it helpful to visualize parsing as drawing a parse tree like the one in Figure 8.1, and to imagine values being computed and propagated up the tree from the leaves towards the root.

list

/JXP

xpr /" list NUMBER NUMBER NUMBER / / \ (empty) 2 + 3 * 4 \.n

Figure 8.1: Parse Tree for $2 + 3 * 4$

The values of incompletely-recognized rules are actually kept on a stack; this is how the values are passed from one rule to the next. The data type of this stack is normally an int, but since we are processing floating point numbers, we have to override the default. The definition

```
#define YYSTYPE double
```

sets the stack type to double. Syntactic classes that will be recognized by the lexical analyzer have to be declared unless they are single character literals like '+' and '-'. The declaration %token declares one or more such objects. Left or right associativity can be specified if appropriate by using %left or %right instead of %token. (Left associativity means that $a-b-c$ will be parsed as $(a-b)-c$ instead of $a-(b-c)$.) Precedence is determined by order of appearance: tokens in the same declaration are at the same level of precedence; tokens declared later are of higher precedence. In this way the grammar proper is ambiguous (that is, there are multiple ways to parse some inputs), but the extra information in the declarations resolves the ambiguity. The rest of the code is the routines in the second half of the file `hoc.y`:

CHAPTER 8

PROGRAM DEVELOPMENT 239

Continuing hoc. y

```
#include <stdio.h> #include <ctype.h> char *progrname; int lineno = 1;
```

```
1* for error messages *1
```

```
main(argc, argv) char *argv[];
```

```
1* hoc1 */
```

```
{
```

```
progrname = argv[0]; yyparse ( ) ;
```

```
}
```

main calls yyparse to parse the input. Looping from one expression to the next is done entirely within the grammar, by the sequence of productions for list. It would have been equally acceptable to put a loop around the call to yyparse in main and have the action for list print the value and return immediately. yyparse in turn calls yylex repeatedly for input tokens. Our yylex is easy: it skips blanks and tabs, converts strings of digits into a numeric value, counts input lines for error reporting, and returns any other character as itself. Since the grammar expects to see only +, -, *, /, (,), and \n, any other character will cause yyparse to report an error. Returning a 0 signals "end of file" to yyparse.

```
yylex( ) {
```

```
Continuing hoc. y /* hoc1 *1
```

```
int c;
```

```
while ((c=getchar(» --
```

```
, ,
```

```
:: c == "t")
```

```
if (c == EOF) return 0; if (c == '.' :: isdigit(c» { /* number *1 ungetc(c,  
stdin); scanf ( "%If", &.yylval); return NUMBER;
```

```
} if (c == ' ' ) lineno++; return c;  
  
}
```

The variable `yyl val` is used for communication between the parser and the lexical analyzer; it is defined by `yyparse`, and has the same type as the `yacc` stack. `yylex` returns the type of a token as its function value, and sets `yyl val` to the value of the token (if there is one). For instance, a floating

240 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

point number has the type `NUMBER` and a value like `12.34`. For some tokens, especially single characters like `'+'` and `'\n'`, the grammar does not use the value, only the type. In that case, `yyl val` need not be set. The `yacc` declaration `%token NUMBER` is converted into a `#define` statement in the `yacc` output file `y.tab.c`, so `NUMBER` can be used as a constant anywhere in the C program. `yacc` chooses values that won't collide with ASCII characters. If there is a syntax error, `yyparse` calls `yyerror` with a string containing the cryptic message "syntax error." The `yacc` user is expected to provide a `yyerror`; ours just passes the string on to another function, `warning`, which prints somewhat more information. Later versions of `hoc` will make direct use of `warning`.

```
yyerror(s) 1* called for yacc syntax error *1 char *s;
```

```
{
```

```
warning(s, (char *) 0);
```

```
}
```

```
warning(s, t) 1* print warning message *1 char *s, *t;
```

```
{
```

```
fprintf(stderr, "%s: %s", progname, s); if (t) fprintf(stderr, " %s", t);  
fprintf(stderr, " near line %d'n", lineno);
```

```
}
```

This marks the end of the routines in hoc. y. Compilation of a yacc program is a two-step process:

```
$ yacc hoc.y $ cc y.tab.c -O hoc1 $ hoc1 2/3
```

Leaves output in y. tab. c Leaves executable program in hoc 1

0.66666667

-3-4 hoc1: syntax error near line 1 \$

Exercise 8-1. Examine the structure of the y. tab. c file. (It's about 300 lines long for hoc1.) 0

Making changes - unary minus We claimed earlier that using yacc makes it easy to change a language. As an illustration, let's add unary minus to hoc 1, so that expressions like -3-4

CHAPTER 8

PROGRAM DEVELOPMENT 241

are evaluated, not rejected as syntax errors. Exactly two lines have to be added to hoc.. y. A new token UNARYMINUS is added to the end of the precedence section, to make unary minus have highest precedence:

%left %left %left

'+' '-'

'*' '/'

UNARYMINUS

/* new */

The grammar is augmented with one more production for expr:

expr:

NUMBER : '-' expr

{ \$\$ = \$1; } %prec UNARYMINUS { \$\$ = -\$2; } /* new */

The %prec says that a unary minus sign (that is, a minus sign before an expression) has the precedence of UNARYMINUS (high); the action is to change the sign. A minus sign between two expressions takes the default

precedence. Exercise 8-2. Add the operators % (modulus or remainder) and unary + to hoc 1. Suggestion: look at frexp(3). 0

A digression on make It's a nuisance to have to type two commands to compile a new version of hoc 1. Although it's certainly easy to make a shell file that does the job, there's a better way, one that will generalize nicely later on when there is more than one source file in the program. The program make reads a specification of how the components of a program depend on each other, and how to process them to create an up-to-date version of the program. It checks the times at which the various components were last modified, figures out the minimum amount of recompilation that has to be done to make a consistent new version, then runs the processes. make also understands the intricacies of multi-step processes like yacc, so these tasks can be put into a make specification without spelling out the individual steps. make is most useful when the program being created is large enough to be spread over several source files, but it's handy even for something as small as hoc 1. Here is the make specification for hoc 1, which make expects in a file called makefile.

```
$ cat makefile hoc 1 : hoc.o cc hoc.o -o hoc1
```

```
$
```

This says that hoc 1 depends on hoc.o, and that hoc.o is converted into hoc 1 by running the C compiler cc and putting the output in hoc 1. make already knows how to convert the yacc source file in hoc.y to an object file hoc.o:

CHAPTER 8

```
$ make yacc hoc.y cc -c y.tab.c rm y.tab.c mv y.tab.o hoc.o cc hoc.o -O hoc1
$ make 'hoc1' is up to date. $
```

Make the first thing in make file, hoc 1

Do it again make realizes it's unnecessary

8.2 Stage 2: Variables and error recovery The next step (a small one) is to add "memory" to hoc1, to make hoc2. The memory is 26 variables, named a through z. This isn't very elegant, but it's an easy and useful intermediate step. We'll also add some error handling. If you try hoc 1, you'll recognize that its approach to syntax errors is to print a message and die, and its treatment of arithmetic errors like division by zero is reprehensible: \$ hoc1 1/0 Floating exception - core dumped \$

The changes needed for these new features are modest, about 35 lines of code. The lexical analyzer yyl ex has to recognize letters as variables; the grammar has to include productions of the form

expr:

VAR : VAR '=' expr

An expression can contain an assignment, which permits multiple assignments like

x = y = z = 0

The easiest way to store the values of the variables is in a 26-element array; the single-letter variable name can be used to index the array. But if the grammar is to process both variable names and values in the same stack, yacc has to be told that its stack contains a union of a double and an int, not just a double. This is done with a %union declaration near the top. A #define or a typedef is fine for setting the stack to a basic type like double, but the %union mechanism is required for union types because yacc checks for consistency in expressions like \$ \$:: \$:2 . Here is the grammar part of hoc.. y for hoc:2:

```
$ cat hocoY %{ double mem[26]; %} %union { double int
```

CHAPTER 8

```
} %token %token %type %right %left %left %left %% list:
```

PROGRAM DEVELOPMENT 243

/* memory for variables

'a'o.'z' */

val; index;

/* stack type */ /* actual value */ /* index into mem[] */

<val> NUMBER <index> VAR <val> expr

, ='

'+' '-'

'*' '/'

UNARYMINUS

```
/* nothing */ list '\n' list expr '\n' list error '\n'
```

```
{ printf("\t%o8g\n", $2); } { yyerrok; }
```

```
expr: NUMBER VAR { $$ = mem [ $ 1 ] ; } VAR ' =' expr { $$ = mem [ $  
1 ] = $3; } expr ' +' expr { $$ = $1 + $3; } expr ' - ', expr { $$ = $1 - $3; }  
expr ' * ' expr { $$ = $1 * $3; } expr '/' expr { if ($3 -- 0.0)  
execerror("division by zero", WI"); $$ = $1 / $3; } , ( , expr ' ) , { $$ = $2; }  
, - , expr %prec UNARYMINUS { $$ = -$2; } %% /* end of grammar */
```

The %union declaration says that stack elements hold either a double (a number, the usual case), or an int, which is an index into the array memo. The %token declarations have been augmented with a type indicator. The %type declaration specifies that expr is the <val> member of the union, i.e., a double. The type information makes it possible for yacc to generate references to the correct members of the union. Notice also that = is right-associative, while the other operators are left-associative. Error handling comes in several pieces. The obvious one is a test for a zero divisor; if one occurs, an error routine execerror is called. A second test is to catch the "floating point exception" signal that occurs

244 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

when a floating point number overflows. The signal is set in main. The final part of error recovery is the addition of a production for error. "error" is a

reserved word in a yacc grammar; it provides a way to anticipate and recover from a syntax error. If an error occurs, yacc will eventually try to use this production, recognize the error as grammatically "correct," and thus recover. The action `yerrorok` sets a flag in the parser that permits it to get back into a sensible parsing state. Error recovery is difficult in any parser; you should be aware that we have taken only the most elementary steps here, and have skipped rapidly over yacc's capabilities as well. The actions in the `hoc:2` grammar are not much changed. Here is `main`, to which we have added `setjmp` to save a clean state suitable for resuming after an error. `execerror` does the matching `longjmp`. (See Section 7.5 for a description of `setjmp` and `longjmp`.)

```
#include <signal.h> #include <setjmp.h> jmp_buf begin;
```

```
main(argc, argv) char *argv [ ] ;
```

```
/* hoc2 */
```

```
{
```

```
int fpecatch();
```

```
progname = argv[0]; setjmp (begin) ; signal(SIGFPE, fpecatch); yyparse ( )  
;
```

```
}
```

```
execerror(s, t) /* recover from run-time error */ char *s, *t;
```

```
{
```

```
warning(s, t); longjmp(begin, 0);
```

```
}
```

```
fpecatch ( ) {
```

```
/* catch floating point exceptions */
```

```
execerror("floating point exception", (char *) 0);
```

```
}
```

For debugging, we found it convenient to have `execerror` call `abort` (see `abort(3)`), which causes a core dump that can be perused with `adb` or `sdb`. Once the program is fairly robust, `abort` is replaced by `longjmp`. The lexical

analyzer is a little different in hoc:2. There is an extra test for a lower-case letter, and since `yyl val` is now a union, the proper member has to be set before `yylex` returns. Here are the parts that have changed:

CHAPTER 8

PROGRAM DEVELOPMENT 245

```
yylex() /* hoc2 */
```

```
if (c == '.' :: isdigit(c) { /* number */ ungetc(c, stdin); scanf("%lf",
&.yylval.val); return NUMBER;
```

```
} if (islower(c) { .yylval.index = c - 'a'; /* ASCII only */ return VAR;
```

```
}
```

Again, notice how the token type (e.g., `NUMBER`) is distinct from its value (e.g., 3.1416). Let us illustrate variables and error recovery, the new things in hoc:2: `$ hoc2 x = 355`

y = 113

113 p = x/ z z is undefined and thus zero hoc2: division by zero near line 4
Error recovery x/y 3.1415929 1e30 '* 1e30 Overflow hoc2: floating point
exception near line 5

Actually, the PDP-11 requires special arrangements to detect floating point overflow, but on most other machines hoc2 behaves as shown. Exercise 8-3. Add a facility for remembering the most recent value computed, so that it does not have to be retyped in a sequence of related computations. One solution is to make it one of the variables, for instance lOp' for 'previous.' 0 Exercise 8-4. Modify hoc so that a semicolon can be used as an expression terminator equivalent to a newline. 0

8.3 Stage 3: Arbitrary variable names; built-in functions This version, hoc3, adds several major new capabilities, and a corresponding amount of extra code. The main new feature is access to built-in functions:

sin sqrt

cos int

atan abs

exp

log

log10

We have also added an exponentiation operator `^`; it has the highest precedence, and is right-associative. Since the lexical analyzer has to cope with built-in names longer than a

246 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

single character, it isn't much extra effort to permit variable names to be arbitrarily long as well. We will need a more sophisticated symbol table to keep track of these variables, but once we have it, we can pre-load it with names and values for some useful constants:

PI E GAMMA DEG PHI

3.14159265358979323846 2.71828182845904523536
0.57721566490153286060 57.29577951308232087680

1.61803398874989484820

1T Base of natural logarithms Euler-Mascheroni constant Degrees per radian Golden ratio

The result is a useful calculator:

\$ hoc3 105 A 2.3

2.5410306 exp(2.3*log(1.5» 2.5410306 sin (PI/2) 1 atan (1) *DEG 45

We have also cleaned up the behavior a little. In hoc 2, the assignment `x=expr` not only causes the assignment but also prints the value, because all expressions are printed: \$ hoc2 x = 2 * 3.14159 6.28318

Value printed for assignment to variable

In hoc 3, a distinction is made between assignments and expressions; values are printed only for expressions: \$ hoc3 x = 2 * 3.14159

6.28318

Assignment: no value is printed Expression: value is printed

x

The program that results from all these changes is big enough (about 250 lines) that it is best split into separate files for easier editing and faster compilation. There are now five files instead of one:

CHAPTER 8

PROGRAM DEVELOPMENT 247

hoc.y hoc.h symbol.c init.c math.c

Grammar, main, yylex (as before) Global data structures for inclusion
Symbol table routines: lookup, install Built-ins and constants; init
Interfaces to math routines: Sqrt, Log, etc.

This requires that we learn more about how to organize a multi-file C program, and more about how to make it do some of the work for us. We'll get back to that shortly. First, let us look at the symbol table code. A symbol has a name, a type (it's either a VAR or a BLTIN), and a value. If the symbol is a VAR, the value is a double; if the symbol is a built-in, the value is a pointer to a function that returns a double. This information is needed in hoc.y, symbol.c, and init.c. We could just make three copies, but

it's too easy to make a mistake or forget to update one copy when a change is made. Instead we put the common information into a header file `hoc D h` that will be included by any file that needs it. (The suffix `D h` is conventional but not enforced by any program.) We will also add to the make file the fact that these files depend on `hoc D h`, so that when it changes, the necessary recompilations are done too. `$ cat hoc.h`

```
typedef struct Symbol { /* symbol table entry */ char *name; short type; /* VAR, BLTIN, UNDEF */ union {
```

double double

```
val; (*ptr)();
```

```
/* if VAR */ /* if BLTIN */
```

```
} u; struct Symbol *next; /* to link to another */ } Symbol; Symbol  
*install(), *lookup(); $
```

The type `UNDEF` is a `VAR` that has not yet been assigned a value. The symbols are linked together in a list using the `next` field in `Symbol`. The list itself is local to `symbol De`; the only access to it is through the functions `lookup` and `install`. This makes it easy to change to symbol table organization if it becomes necessary. (We did that once.) `lookup` searches the list for a particular name and returns a pointer to the `Symbol` with that name if found, and zero otherwise. The symbol table uses linear search, which is entirely adequate for our interactive calculator, since variables are looked up only during parsing, not execution. `install` puts a variable with its associated type and value at the head of the list. `emalloc` calls `malloc`, the

standard storage allocator (malloc(3)), and checks the result. These three routines are the contents of symbol De. The file y D tab D h is generated by running yacc -d; it contains #define statements that yacc has generated for tokens like NUMBER, VAR, BLTIN, etc.

248

THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

```
$ cat symbol.c #include "hoc.h" #include "y.tab.h"
```

```
static Symbol *symlist = 0; 1* symbol table: linked list *1
```

```
Symbol *lookup(s) char *s;
```

```
1* find s in symbol table *1
```

```
{
```

Symbol *sp;

for (sp = symlist; sp != (Symbol *) 0; sp = sp->next) if (strcmp(sp->name, s) == 0) return sp; return 0; 1* 0 ==> not found *1

} Symbol *install(s, t, d) 1* install s in symbol table *1 char *s; int t; double d;

{

Symbol *sp; char *emalloc();

sp = (Symbol *) emalloc(sizeof(Symbol)); sp->name = emalloc(strlen(s)+1); 1* +1 for "0" *1 strcpy(sp->name, s); sp->type = t; sp->u.val = d; sp->next = symlist; 1* put at front of list *1 symlist = sp; return sp;

} char *emalloc(n) unsigned n;

1* check return from malloc *1

1.

```
char *P, *malloc();
```

```
p = malloc (n) ; if (p == 0) execerror("out of memory", (char *) 0); return p;
```

```
} $
```

The file `init.c` contains definitions for the constants (PI, etc.) and function pointers for built-ins; they are installed in the symbol table by the function `init`, which is called by `main`.

CHAPTER 8

```
$ cat init.c #include "hoc.h" #include "y.tab.h" #include <math.h>
```

```
extern double static struct { char double } consts[] = { "PI", "E",  
"GAMMA" , "DEG" , "PHI", o ,
```

```
} ; static struct { char double } builtins[] =
```

PROGRAM DEVELOPMENT

Log(), Log10(), Exp(), Sqrt(), integer()); 1* Constants *1

*name; cval;

3.14159265358979323846, 2.71828182845904523536,
0.57721566490153286060, 57.29577951308232087680,
1.61803398874989484820, o

1* Euler *1 1* deg/radian *1 1* golden ratio *1

1* Built-ins *1

*name; (*func)(); {

"sin", sin, "cos", cos, "atan", atan, "log", Log, 1* checks argument *1
"10g10", Log10, 1* checks argument *1 "exp", Exp, 1* checks argument *1
"sqrt", Sqrt, 1* checks argument *1 "int", integer, "abs", fabs, 0, 0

} ; init() 1* install constants and built-ins in table *1 {


```
int i; Symbol *s;
```

```
for (i = 0; consts[i].name; i++) install(consts[i].name, VAR, consts[i].cval);  
for (i = 0; builtins[i].name; i++) { s = install(builtins[i].name, BLTIN, 0.0);  
s->u.ptr = builtins[i].func;
```

```
}
```

```
}
```

The data is kept in tables rather than being wired into the code because tables are easier to read and to change. The tables are declared static so that they are visible only within this file rather than throughout the program. We'll come back to the math routines like Log and Sqrt shortly.

250

THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

With the foundation in place, we can move on to the changes In the grammar that make use of it.

```
$ cat hoc.y %{ #include "hoc.h" extern double Pow(); %} %union
```

```
} %token %token %type %right %left %left %left %right %% list:
```

asgn:

expr:

%%

```
{ double Symbol
```

```
val; *sym;
```

```
/* actual value */ /* symbol table pointer */
```

```
<val> <sym> <val>
```

NUMBER VAR BLTIN UNDEF expr asgn

'='

'+' '-'

'*' '/'

UNARYMINUS 'A' /* exponentiation */

/* nothing */ list '\n' list asgn '\n' list expr '\n' list error '\n'

{ printf("\t%.8g\n", \$2); } { yyerrok; }

VAR '=' expr { \$\$=\$1->u.val=\$3; \$1->type = VAR; }

NUMBER VAR { if (\$1->type == UNDEF) execerror("undefined variable",
\$1->name); \$\$ = \$1->u.val; }

asgn BLTIN ' (, expr ') , { \$\$ = (*(\$1->u.ptr»(\$3); } expr '+' expr { \$\$ = \$1
+ \$3; } expr , - , expr { \$\$ \$1 \$3; } = - expr '*' expr { \$\$ = \$1 * \$3; } expr

```
'/' expr { if ($3 == 0.0) execerror("division by zero", ""); $$ = $1 / $3; } expr
' A' expr { $$ Pow ( $ 1 , $3); } = , ( , expr ' ) , { $$ = $2; } , - , expr %prec
UNARYMINUS { $$ = -$2; }
```

```
/* end of grammar */
```

CHAPTER 8

PROGRAM DEVELOPMENT 251

The grammar now has `asgn`, for assignment, as well as `expr`; an input line that contains just

`VAR = expr`

is an assignment, and so no value is printed. Notice, by the way, how easy it was to add exponentiation to the grammar, including its right associativity. The yacc stack has a different `%union`: instead of referring to a variable by its index in a 26-element table, there is a pointer to an object of type `Symbol`. The header file `hoc 0 h` contains the definition of this type. The lexical analyzer recognizes variable names, looks them up in the `symbol` table, and decides whether they are variables (`VAR`) or built-ins (`BLTIN`). The type returned by `yylex` is one of these; both user-defined variables and pre-defined variables like `PI` are `VAR`'s. One of the properties of a variable is whether or not it has been assigned a value, so the use of an undefined variable can be reported as an error by `yyparse`. The test for whether a variable is defined has to be in the grammar, not in the lexical analyzer.

When a VAR is recognized lexically, its context isn't yet known; we don't want a complaint that x is undefined when the context is perfectly legal one such as the left side of an assignment like x= 1. Here is the revised part of yylex:

```
yylex ( )
```

```
1* hoc3 *1
```

```
if (isalpha(c) { Symbol *S; char sbuf[100], *p = sbuf; do {
```

```
*p++ = c; } while ((c=getchar() != EOF && isalnum(c) ungetc(c, stdin);  
*p = '\0' ; if ((s=lookup(sbuf) == 0) s = install(sbuf, UNDEF, 000);  
yylvalosym = s; return s->type == UNDEF ? VAR : s->type;
```

```
}
```

main has one extra line, which calls the initialization routine init to install built-ins and pre-defined names like PI in the symbol table.

252 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

```
main(argc, argv) char *argv[];
```

```
1* hoc3 *1
```

```
{
```

```
int fpecatch{};
```

```
progname = argv[0]; ini t ( ) ; set jmp ( begin) ; signal{SIGFPE, fpecatch};  
yyparse ( ) ;
```

```
}
```

The only remaining file is `math.c`. Some of the standard mathematical functions need an error-checking interface for messages and recovery - for example the standard function `sqrt` silently returns zero if its argument is negative. The code in `math.c` uses the error tests found in Section 2 of the UNIX Programmer's Manual; see Chapter 7. This is more reliable and portable than writing our own tests, since presumably the specific limitations of the routines are best reflected in the "official" code. The header file `<math.h>` contains type declarations for the standard mathematical functions. `<errno.h>` contains names for the errors that can be incurred.

```
$ cat math.c #include <math.h> #include <errno.h> extern int errno;
double errcheck{};
```

```
double Log{x} double x; { return errcheck ( log (x) , "log" ) ; } double
Log10{x} double x; { return errcheck(10g10{x}, "10g10"); } double Exp{x}
double x; {
```

```
return errcheck ( exp (x) , "exp"); } double Sqrt{x} double x; { return
errcheck(sqrt{x}, "sqrt"); }
```

CHAPTER 8

PROGRAM DEVELOPMENT

253

```
double Pow (x, y) double x, y;
```

```
{
```

```
return errcheck(pow(x,y), "exponentiation");
```

```
} double integer(x) double x;
```

```
{
```

```
return (double) (long)x;
```

```
} double errcheck(d, s) double d; char *s;
```

```
/* check result of library call */
```

```
{
```

```
if (errno == EDOM) { errno = 0; execerror(s, "argument out of domain"); }  
else if (errno == ERANGE) { errno = 0; execerror(s, "result out of range");
```

```
} return d;
```

```
} $
```

An interesting (and ungrammatical) diagnostic appears when we run yacc on the new grammar: \$ yacc hoc.y

conflicts: 1 shift/reduce \$

The "shift/reduce" message means that the hoc3 grammar IS ambiguous:
the single line of input

$x = 1$

can be parsed in two ways:

254 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

list I expr list I /1 list asgn list asgn I I I I (empty) $x = 1$ \n (empty) $x = 1$ \n

The parser can decide that the asgn should be reduced to an expr and then to a list, as in the parse tree on the left, or it can decide to use the following \n immediately ("shift") and convert the whole thing to a list without the intermediate rule, as in the tree on the right. Given the ambiguity, yacc chooses to shift, since this is almost always the right thing to do with real grammars. You should try to understand such messages, to be sure that yacc has made the right decision. t Running yacc with the option -v produces a voluminous

file called `Ye` output that hints at the origin of conflicts. Exercise 8-5. As `hoc3` stands, it's legal to say `PI = 3`

Is this a good idea? How would you change `hoc3` to prohibit assignment to "con- stants"? 0

Exercise 8-6. Add the built-in function `atan2 (y, x)`, which returns the angle whose tangent is `y /x`. Add the built-in `rand ()`, which returns a floating point random vari- able uniformly distributed on the interval `(0,1)`. How do you have to change the gram- mar to allow for built-ins with different numbers of arguments? 0 Exercise 8-7. How would you add a facility to execute commands from within `hoc`, similar to the `!` feature of other UNIX programs? 0 Exercise 8-8. Revise the code in `math. c` to use a table instead of the set of essentially identical functions that we presented. 0

Another digression on `make` Since the program for `hoc3` now lives on five files, not one, the `makefile` is more complicated:

t The yacc message "reduce/reduce conflict" indicates a serious problem, more often the symptom of an outright error in the grammar than an intentional ambiguity.

CHAPTER 8

```
$ cat makefile YFLAGS = -d # force creation of y.tab.h OBJS = hocoo  
init.o math.o symbo1.0 # abbreviation
```

```
hoc3: $(OBJS) cc $(OBJS) -1m -0 hoc3
```

```
hoc.o: hoc.h
```

```
init.o symbo1.0:
```

```
hoc.h y.tab.h
```

```
pr:
```

```
@pr hoc.y hoc.h init.c math.c symbo1.c makefile
```

```
clean:
```

```
rm -f $(OBJS) y.tab.[ch]
```

```
$
```

The `YFLAGS = -d` line adds the option `-d` to the `yacc` command line generated by `make`; this tells `yacc` to produce the `y.taboh` file of `#define` statements. The `OBJS=...` line defines a shorthand for a construct to be used several times subsequently. The syntax is not the same as for shell variables - the parentheses are mandatory. The flag `-lm` causes the math library to be searched for the mathematical functions. `hoc3` now depends on four `.. 0` files; some of the `.. 0` files depend on `. h` files. Given these dependencies, `make` can deduce what recompilation is needed after changes are made to any of the files involved. If you want to see what `make` will do without actually running the processes, try

```
$ make -n
```

On the other hand, if you want to force the file times into a consistent state, the `-t` ("touch") option will update them without doing any compilation steps. Notice that we have added not only a set of dependencies for the source files but miscellaneous utility routines as well, all neatly encapsulated in one place. By default, `make` makes the first thing listed in the makefile, but if you name an item that labels a dependency rule, like `symbol.. 0` or `pr`, that will be made instead. An empty dependency is taken to mean that the item is never "up to date," so that action will always be done when requested. Thus `$ make pr / lpr`

produces the listing you asked for on a line printer. (The leading `@` in `"@pr"` suppresses the echo of the command being executed by `make`.) And

```
$ make clean
```

removes the yacc output files and the .. 0 files. This mechanism of empty dependencies In the makefile IS often

256 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

preferable to a shell file as a way to keep all the related computations in a single file. And make is not restricted to program development - it is valuable for packaging any set of operations that have time dependencies.

A digression on lex The program lex creates lexical analyzers in a manner analogous to the way that yacc creates parsers: you write a specification of the lexical rules of your language, using regular expressions and fragments of C to be executed when a matching string is found. lex translates that into a recognizer. lex and yacc cooperate by the same mechanism as the lexical analyzers we have already written. We are not going into any great detail on lex here; the following discussion is mainly to interest you in learning more. See the reference manual for lex in Volume 2B of the UNIX Programmer's Manual. First, here is the lex program, from the file lex. 1; it replaces the function yylex that we have used so far. \$ cat lex. 1 %{
#include "hoc.h" #include "y.tab.h" extern int lineno; %} %% [\t] {;} 1*
skip blanks and tabs *1 [O-9]+\.[0-9]*\.[0-9]+ { sscanf (yytext , "%If",
&yy1va1.va1); return NUMBER; [a-zA-Z][a-zA-ZO-9]* { Symbol *s; if
«s=lookup(yytext» == 0) s = install (yytext , UNDEF, 0.0); yy1va1.sym = s;
return s->type == UNDEF ? VAR : s->type; } \n { lineno++; return '\n';} 1*
everything else *J { return yytext[0]; }

\$

Each "rule" is a regular expression like those in egrep or awk, except that lex recognizes C-style escapes like \t and \n. The action is enclosed in braces. The rules are attempted in order, and constructs like "*" and "+" match as long as a string as possible. If the rule matches the next part of the input, the

action is performed. The input string that matched is accessible in a lex string called yytext. The makefile has to be changed to use lex:

CHAPTER 8

PROGRAM DEVELOPMENT 257

```
$ cat makefile YFLAGS = -d OBJS = hoc.o lex.o init.o math.o symbol.o
```

```
hoc3: $(OBJS) cc $(OBJS) -lm -l11 -l0 hoc3
```

```
hoc.o: hoc.h
```

```
lex.o init.o symbol.o: hoc.h y.tab.h
```

\$

Again, make knows how to get from a „1 file to the proper „0; all it needs from us is the dependency information. (We also have to add the lex library -11 to the list searched by cc since the lex-generated recognizer is not self-contained.) The output is spectacular and completely automatic: \$ make yacc -d hoc.y

```
conflicts: 1 shift/reduce cc -c y.tab.c rm y.tab.c mv y.tab.o hoc.o lex lex. 1
cc -c lex.yy.c rm lex.yy.c mv lex.yy.o lex.o cc -c init.c cc -c math.c cc -c
symbol.c cc hoc.o lex.o init.o math.o symbol.o -1m -11 -0 hoc3 $
```

If a single file is changed, the single command make is enough to make an up-to-date version: \$ touch lex.1 Change modified-time of lex. 1 \$ make lex lex. 1 cc -c lex.yy.c rm lex.yy.c mv lex.yy.o lex.o cc hoc.o lex.o init.o math.o symbol.o -11 -1m -0 hoc3 \$

We debated for quite a while whether to treat lex as a digression, to be illustrated briefly and then dropped, or as the primary tool for lexical analysis once the language got complicated. There are arguments on both sides. The

258 THE UNIX PROGRAMMING ENVIRONMENT

eCHAPTER 8

main problem with lex (aside from requiring that the user learn yet another language) is that it tends to be slow to run and to produce bigger and slower recognizers than the equivalent versions. It is also somewhat harder to adapt its input mechanism if one is doing anything unusual, such as error recovery or even input from files. None of these issues is serious in the context of hoc. The main limitation is space: it takes more pages to describe the lex version, so (regretfully) we will revert to C for subsequent lexical analysis. It is a good exercise to do the lex versions, however. Exercise 8-9. Compare the sizes of the two versions of hoc3. Hint: see size(1). 0

8.4 Stage 4: Compilation into a machine We are heading towards hoeS, an interpreter for a language with control flow. hoe4 is an intermediate step, providing the same functions as hoe3, but implemented within the interpreter framework of hoeS. We actually wrote hoe4 this way, since it gives us two programs that should behave identically, which is valuable for debugging. As the input is parsed, hoe4 generates code for a simple computer instead of immediately computing answers. Once the end of a statement is reached, the generated code is executed ("interpreted") to compute the desired result. The simple computer is a stack machine: when an operand is encountered, it is pushed onto a stack (more precisely, code is generated to push it onto a stack); most operators operate on items on the top of the stack. For example, to handle the assignment

`x = 2 * Y`

the following code is generated:

```
constpush 2 varpush y eval mul varpush x assign pop STOP
```


Push a constant onto stack . . . the constant 2 Push symbol table pointer onto stack . . . for the variable y Evaluate: replace pointer by value Multiply top two items,. product replaces them Push symbol table pointer onto stack . . . for the variable x Store value in variable, pop pointer Clear top value from stack End of instruction sequence

When this code is executed, the expression is evaluated and the result is stored in x, as indicated by the comments. The final pop clears the value off the stack because it is not needed any longer. Stack machines usually result in simple interpreters, and ours is no exception - it's just an array containing operators and operands. The operators are the machine instructions; each is a function call with its arguments, if any, following the instruction. Other operands may already be on the stack, as they

CHAPTER 8

PROGRAM DEVELOPMENT 259

were in the example above. The symbol table code for hoc4 is identical to that for hoc 3; the initialization in init.c and the mathematical functions in math.c are the same as well. The grammar is the same as for hoc3, but the actions are quite different. Basically, each action generates machine instructions and any arguments that go with them. For example, three items are generated for a VAR in an expression: a varpush instruction, the symbol table pointer for the variable, and an eval instruction that will replace the symbol table pointer by its value when executed. The code for '*' is just mul, since the operands for that will already be on the stack. \$ cat hoc.y %{ "include "hoc.h" "define code2(c1,c2) "define code3(c1,c2,c3) %} %union { Symbol *sym; Inst *inst;

```
} %token %right %left %left %left %right %% list:
```

```
asgn:
```

```
code(c1); code(c2) code(c1); code(c2); code(c3)
```

```
/* symbol table pointer */ /* machine instruction */
```

```
<sym>
```

```
NUMBER VAR BLTIN UNDEF
```

```
, '='
```

```
'+' '-'
```

```
'*' '/'
```

```
UNARYMINUS 'A' /* exponentiation */
```

```
/* nothing */ list '\n' list asgn '\n' list expr '\n' list error '\n'
```

```
{ code2(pop, STOP); return 1; } { code2(print, STOP); return 1; } {  
yyerrok; }
```

```
VAR ':' expr {code3(varpush,(Inst)$1,assign); }
```

260 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

expr:

```
NUMBER VAR asgn BLTIN '(' '(' expr expr '+' expr '-' expr '*' expr '/' expr  
'A, '-' expr
```

```
{ code2(constpush, (Inst)$1); } { code3(varpush, (Inst)$1, eval); }
```

```
expr ')' { code2(bltin, (Inst)$1->u.ptr); } , ) , expr { code(add); } expr {  
code(sub); } expr { code(mul); } expr { code(div); } expr { code(power); }  
%prec UNARYMINUS {code(negate); }
```

%%

1* end of grammar *1

Inst is the data type of a machine instruction (a pointer to a function returning an int), which we will return to shortly. Notice that the arguments to code are function names, that is, pointers to functions, or other values that are coerced to function pointers. We have changed main somewhat. The parser now returns after each statement or expression; the code that it generated is executed. yyparse returns zero at end of file.

```
main(argc, argv) char *argv[];
```

1* hoc4 *1

{

```
int fpecatch();
```

```
programe = argv[0]; init ( ) ; set jmp (begin) ; signal(SIGFPE, fpecatch);  
for (initcode(); yyparse(); initcode()» execute(prog); return 0;
```

```
}
```

The lexical analyzer is only a little different. The main change is that numbers have to be preserved, not used immediately. The easiest way to do this is to install them in the symbol table along with the variables. Here is the changed part of yylex:

CHAPTER 8

PROGRAM DEVELOPMENT 261

```
yylex ( )
```

```
1* hoc4 *1
```

```
if (c == '.' :: is d i gi t ( c » { 1* numbe r * I double d; ungetc(c, stdin);  
scanf("%lf", &d); yylval.sym = install("", NUMBER, d); return NUMBER;
```

```
}
```

Each element on the interpreter stack is either a floating point value or a pointer to a symbol table entry; the stack data type is a union of these. The machine itself is an array of pointers that point either to routines like mul

that perform an operation, or to data in the symbol table. The header file `hoc.h` has to be augmented to include these data structures and function declarations for the interpreter, so they will be known where necessary throughout the program. (By the way, we chose to put all this information in one file instead of two. In a larger program, it might be better to divide the header information into several files so that each is included only where really needed.)

```
$ cat hoc.h
typedef struct Symbol {
    1* symbol table entry
    1 char *name;
    short type;
    1* VAR, BLTIN, UNDEF
    1 union {
```

```
double double
```

```
val; ( *ptr ) ( ) ;
```

```
1* if VAR *1
1* if BLTIN *1
```

```
    } u;
    struct Symbol *next; 1* to link to another *1
} Symbol;
Symbol *install(), *lookup();
```

```
typedef union Datum {
    double val;
    Symbol *sym;
} Datum;
extern Datum pope);
```

```
1* interpreter stack type *1
```

```
typedef int (*Inst)();
1* machine instruction *1
#define STOP (Inst) 0
```

```
extern extern extern $
```

```
Inst prog[]; eval(), add(), sub(), mule), dive), negate(), power() assign(),  
bltin(), varpush(), constpush(), print());
```

The routines that execute the machine instructions and manipulate the stack are kept in a new file called code. c. Since it is about 150 lines long, we will

262 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

show it in pieces.

```
$ cat code.c #include "hoc.h" #include "y.tab.h"
```

```
#define NSTACK static Datum static Datum
```

```
256 stack[NSTACK]; *stackp;
```

1* the stack *1 1* next free spot on stack *1

#define NPROG 2000 Inst prog[NPROG]; Inst *progp; Inst *pc;

1* the machine *1 1* next free spot for code generation *1 1* program counter during execution *1

initcode() {

1* initialize for code generation *1

stackp = stack; progp = prog;

}

The stack is manipulated by calls to push and pop: pushed) 1* push d onto stack *1 Datum d;

{


```
if (stackp >= &stack[NSTACK]) execerror("stack overflow", (char *) 0);  
*stackp++ = d;
```

```
}
```

```
Datum pope) {
```

```
1* pop and return top elem from stack *1
```

```
if (stackp <= stack) execerror("stack underflow", (char *) 0); return *--  
stackp;
```

```
}
```

The machine is generated during parsing by calls to the function code, which simply puts an instruction into the next free spot in the array prog. It returns the location of the instruction (which is not used in hoc4).

CHAPTER 8

```
Inst *code(f) /* install one instruction or operand */ Inst f;
```

```
{
```

```
Inst *oprogp = progp; if (progp >= &prog[NPROG]) execerror("program  
too big", (char *) 0); *progp++ = f; return oprog;
```

```
}
```

Execution of the machine is simple; in fact, it's rather neat how small the routine is that "runs" the machine once it's set up: `execute(p) /* run the machine */ Inst *P;`

```
{
```

```
for (pc = p; *pc != STOP; (*(pc++)»());
```

```
}
```

Each cycle executes the function pointed to by the instruction pointed to by the program counter `pc`, and increments `pc` so it's ready for the next instruction. An instruction with opcode `STOP` terminates the loop. Some

instructions, such as constpush and varpush, also increment pc to step over any arguments that follow the instruction.

```
constpush ( ) {
```

```
/* push constant onto stack */
```

```
Datum d; deval = «Symbol *)*pc++)->ueval; push ( d) ;
```

```
}
```

```
varpush( ) {
```

```
/* push variable onto stack */
```

```
Datum d; desym = (Symbol *)(*pc++); push (d) ;
```

```
}
```

The rest of the machine is easy. For instance, the arithmetic operations are all basically the same, and were created by editing a single prototype. Here

is add:

264 THE UNIX PROGRAMMING ENVIRONMENT

```
add ( ) {
```

```
}
```

CHAPTER 8

1* add top two elems on stack *1

```
Datum d1, d2; d2 = pop ( ) ; d 1 = pop ( ) ; d1eval += d2eval; push ( d 1 ) ;
```

The remaining routines are equally simple.

```
eval() {
```

```
} assign ( ) {
```

```
} print ( ) {
```

```
} bltin() {
```

```
}
```

1* evaluate variable on stack *1

```
Datum d; d = pop ( ) ; if (desym->type == UNDEF) execerror("undefined  
variable", d.sym->name); deval = d.sym->ueval; pushed) ;
```

1* assign top value to next value *1

```
Datum d1, d2; d 1 = po p ( ) ; d2 = pope); if (d1
```

```
sym->type 1= VAR && d1esym->type != UNDEF) execerror("assignment  
to non-variable", d 1 e sym->name) ; d1esym->ueval = d2eval; d1esym-  
>type = VAR; push( d2) ;
```

1* pop top value from stack, print it *1

```
Datum d; d = pop ( ) ; printf("\t%e8g\n", de val);
```

1* evaluate built-in on top of stack *1

```
Datwn d; d = pop ( ) ; de val = (*(double (*)(»(*pc++»(deval); push ( d ) ;
```

The hardest part is the cast in bl tin, which says that *pc should be cast to "pointer to function returning a double," and that function executed with d . val as argument. The diagnostics in eval and assign should never occur if everything is

CHAPTER 8

PROGRAM DEVELOPMENT 265

working properly; we left them in in case some program error causes the stack to be curdled. The overhead in time and space is small compared to the bene- fit of detecting the error if we make a careless change in the program. (We did, several times.) C's ability to manipulate pointers to functions leads to compact and efficient code. An alternative, to make the operators constants and combine the seman- tic functions into a big swi tch statement in execute, is straightforward and is left as an exercise.

A third digression on make As the source code for hoc grows, it becomes more and more valuable to keep track mechanically of what has changed and what depends on that. The beauty of make is that it automates jobs that we would otherwise do by hand (and get wrong sometimes) or by creating a

specialized shell file. We have made two improvements to the makefile. The first is based on the observation that although several files depend on the yacc-defined constants in y.tab.h, there's no need to recompile them unless the constants change - changes to the C code in hoc.c don't affect anything else. In the new makefile the .o files depend on a new file x.tab.h that is updated only when the contents of y.tab.h change. The second improvement is to make the rule for pr (printing the source files) depend on the source files, so that only changed files are printed. The first of these changes is a great time-saver for larger programs when the grammar is static but the semantics are not (the usual situation). The second change is a great paper-saver. Here is the new makefile for hoc4: YFLAGS = -d OBJS = hoc.o code.o init.o math.o symbo1.o

hoc4:

\$(OBJS) cc \$(OBJS) -lm -o hoc4

hoc.o code.o init.o symbo1.o:

hoc.h

code.o init.o symbo1.o: x.tab.h

x.tab.h: y.tab.h -cmp -s x.tab.h y.tab.h :: cp y.tab.h x.tab.h

```
pr: hoc.y hoc.h code.c init.c math.c symbo1.c @pr $? @touch pr
```

clean:

```
rm -f $(OBJS) [xy].tab.[ch]
```

266 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

The '-' before cmp tells make to carry on even if the cmp fails; this permits the process to work even if x. tab. h doesn't exist. (The -s option causes cmp to produce no output but set the exit status.) The symbol \$? expands into the list of items from the rule that are not up to date. Regrettably, make's notational conventions are at best loosely related to those of the shell. To illustrate how these operate, suppose that everything is up to date. Then

```
$ touch hocoY $ make yacc -d hoc.y
```

Change date of hoc. Y


```
conflicts: 1 shift/reduce cc -c y.tab.c rm y.tab.c mv y.tab.o hoc.o cmp -s
x.tab.h y.tab.h :: cp y.tab.h x.tab.h cc hoc.o code.o init.o math.o symbol.o
-1m -0 hoc4 $ make -n pr Print changed files pr hoc.y touch pr $
```

Notice that nothing was recompiled except hoc II Y, because the y. tab. h file was the same as the previous one. Exercise 8-10. Make the sizes of stack and prog dynamic, so that hoc4 never runs out of space if memory can be obtained by calling malloc. 0 Exercise 8-11. Modify hoc4 to use a switch on the type of operation in execute instead of calling functions. How do the versions compare in lines of source code and execution speed? How are they likely to compare in ease of maintenance and growth? o

8.5 Stage 5: Control flow and relational operators This version, hoc 5, derives the benefit of the effort we put into making an interpreter. It provides if-else and while statements like those in C, state- ment grouping with { and }, and a print statement. A full set of relational operators is included (>, >=, etc.), as are the AND and OR operators && and : :. (These last two do not guarantee the left-to-right evaluation that is such an asset in C; they evaluate both conditions even if it is not necessary.) The grammar has been augmented with tokens, non-terminals, and produc- tions for if, while, braces, and the relational operators. This makes it quite a bit longer, but (except possibly for the if and while) not much more com- plicated:

CHAPTER 8

PROGRAM DEVELOPMENT

```
$ cat hoc.y %{ #include "hoc.h" #define code2(c1,c2) #define  
code3(c1,c2,c3) %} %union { Symbol *sym; Inst *inst;
```

```
} %token %type %right %left %left %left %left %left %left %right %%  
list:
```

```
code(c1); code(c2) code(c1); code(c2); code(c3)
```

```
1* symbol table pointer *1 1* machine instruction *1
```

```
<sym> <inst>
```

```
NUMBER PRINT VAR BLTIN UNDEF WHILE IF ELSE stmt asgn expr  
stmtlist cond while if end
```

```
'='
```

```
OR AND GT GE LT LE EQ NE
```

```
'+' '-'
```

'*' 'I'

UNARYMINUS NOT

''''

1* nothing *1 list '\n' list asgn '\n' {code2(pop, STOP); return 1; } list stmt
\n' {code(STOP); return 1; } list expr '\n' {code2(print, STOP); return 1; }
list error '\n' { yyerrok; }

asgn: VAR , =' expr { \$\$=\$3; code3(varpush,(Inst)\$1,assign); } stmt: expr {
code (pop) ; } PRINT expr { code(preexpr); \$\$ = \$2; } while cond stmt end
{ (\$ 1) [1] = (Inst)\$3; 1* body of loop *1 (\$1)[2] = (Inst)\$4; } 1* end, if
cond fails *1 if cond stmt end { 1* else-less if *1 (\$ 1) [1] = (Inst)\$3; 1*
thenpart *1 (\$1)[3] = (Inst)\$4; } 1* end, if cond fails *1 if cond stmt end
ELSE stmt end { 1* if with else *1 (\$ 1) [1] = (Inst)\$3; 1* thenpart *1
(\$1)[2] = (Inst)\$6; 1* elsepart *1 (\$1)[3] = (Inst)\$7; } 1* end, if cond fails
*1 , { , stmtlist ' } , { \$\$ = \$2; }

cond:

while:

```
(' expr ')' {code(STOP); $$ = $2; }
```

```
WHILE { $$ = code3(whilecode, STOP, STOP); }
```

268 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

if:

IF

```
{ $$=code(ifcode); code3(STOP, STOP, STOP); }
```

stmtlist:

```
1* nothing *1 { code ( STOP) ; $$ :: progp; } 1* nothing *1 { $$ = progp; }  
stmtlist '\n' stmtlist stmt
```

end:

expr:

NUMBER VAR

```
{ $$ :: code2(constpush, (Inst)$1); } { $$ :: code3(varpush, (Inst)$1, eval); }
}
```

```
asgn BLTIN '(' expr ')' { $$ :: $3; code2(bltin,(Inst)$1->u.ptr); } '(' expr ')'
{ $$ :: $2; } expr '+' expr { code(add); } expr '-' expr { code(sub); } expr '*'
expr { code(mul); } expr 'T' expr { code(div); } expr 'A' expr { code
(power); } '-' expr %prec UNARYMINUS { $$ :: $2; code(negate); } expr
GT expr { code(gt); } expr GE expr { code(ge); } expr LT expr { code(lt); }
expr LE expr { code(le); } expr EQ expr { code(eq); } expr NE expr
{ code(ne); } expr AND expr { code(and); } expr OR expr { code(or); }
NOT expr { $$ :: $2; code(not); }
```

%%

The grammar has five shift/reduce conflicts, all like the one mentioned in hoc 3. Notice that STOP instructions are now generated in several places to terminate a sequence; as before, `progp` is the location of the next instruction that will be generated. When executed these STOP instructions will terminate the loop in `execute`. The production for `end` is in effect a subroutine, called from several places, that generates a STOP and returns the location of the instruction that follows it. The code generated for `while` and `if` needs particular study. When the keyword `while` is encountered, the operation `whilecode` is generated, and its position in the machine is returned as the value of the production `while`: WHILE

At the same time, however, the two following positions in the machine are also reserved, to be filled in later. The next code generated is the expression that makes up the condition part of the while. The value returned by cond is the

CHAPTER 8

PROGRAM DEVELOPMENT 269

beginning of the code for the condition. After the whole while statement has been recognized, the two extra positions reserved after the whilecode instruction are filled with the locations of the loop body and the statement that follows the loop. (Code for that statement will be generated next.) :
while cond stmt end { (\$1)[1] = (Inst)\$3; (\$1)[2] = (Inst)\$4; }

/* body of loop */ /* end, if cond fails */

\$1 is the location in the machine at which whilecode is stored; therefore, (\$ 1) [1] and (\$ 1) [2] are the next two positions. A picture might make this clearer:

whilecode

cond

STOP body

STOP next stmt

The situation for an if is similar, except that three spots are reserved, for the then and else parts and the statement that follows the if. We will return shortly to how this operates. Lexical analysis is somewhat longer this time, mainly to pick up the additional operators:

270

THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

```
yylex ( ) /* hocS */ switch (c) { case '>': return follow ( , '=', GE, GT) ;  
case '<': return follow ( , '=', LE, LT) ; case '-' : return follow ( , '=', EQ, '-'  
) . - . - , case '!' : return follow ( , '=', NE, NOT) ; case '!' , . return  
follow('!', OR, , ! , ) . ! . ! , case '&.': return follow ( , '&', AND, '&.') ; case '  
'\n' : lineno++ ; return '\n' ; default: return c. , } }
```

follow looks ahead one character, and puts it back on the input with ungetc if it was not what was expected.

```
follow(expect, if yes, if no) /* look ahead for >=, etco */ {
```

```
int c = getchar();
```

```
if (c == expect) return if yes; ungetc(c, stdin); return ifno;
```

```
}
```

There are more function declarations in hoc. h - all of the relationals, for instance - but it's otherwise the same idea as in hoc4. Here are the last few lines:

```
$ cat hoc.h
```

```
typedef int (*Inst)(); /* machine instruction */ #define STOP (Inst) 0
```

```
extern extern extern extern extern extern $
```



```
Inst prog[], *progp, *code(); eval(), add(), sub(), mule(), dive(), negate(),
power(); assign(), bltin(), varpush(), constpush(), print(); prexpr ( ) ; gt(),
lt(), eq(), gee(), lee(), nee(), and(), ore(), note); ifcode(), whilecode();
```

Most of code. c is the same too, although there are a lot of obvious new routines to handle the relational operators. The function `Ie` ("less than or equal to") is a typical example:

CHAPTER 8

PROGRAM DEVELOPMENT 271

```
Ie ( ) {
```

```
Datum d1, d2; d2 = pope); d 1 = pop ( ) ; d1.val = (double)(d1.val <=
d2.val); push ( d 1 ) ;
```

```
}
```

The two routines that are not obvious are `while code` and `ifcode`. The critical point for understanding them is to realize that `execute` marches along a sequence of instructions until it finds a `STOP`, whereupon it returns. Code generation during parsing has carefully arranged that a `STOP` terminates each sequence of instructions that should be handled by a single call of `execute`. The body of a `while`, and the condition, then and else parts

of an if are all handled by recursive calls to execute that return to the parent level when they have finished their task. The control of these recursive tasks is done by code in whilecode and if code that corresponds directly to while and if statements.

```
whilecode() {
```

```
Datum d; Inst *savepc = pc;
```

```
/* loop body */
```

```
execute(savepc+2); /* condition */ d = pop ( ) ; while (d. val) {  
execute(*«Inst **)(savepc»); /* body */ execute(savepc+2); d = pop ( ) ;
```

```
} pc = *«Inst **)(savepc+1»); /* next statement */
```

```
}
```

Recall from our discussion earlier that the whilecode operation is followed by a pointer to the body of the loop, a pointer to the next statement, and then the beginning of the condition part. When whilecode is called, pc has already been incremented, so it points to the loop body pointer. Thus pc+ 1 points to the following statement, and pc + 2 points to the condition. ifcode is very similar; in this case, upon entry pc points to the then part, pc+ 1 to the else, pc+2 to the next statement, and pc+3 is the condition.

272 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

```
ifcode() {
```

```
Datum d; Inst *savepc = pc;
```

```
1* then part *1
```

```
execute(savepc+3); 1* condition *1 d = pop ( ) ; if (d. val} execute(*«Inst  
**)(savepc}»); else if (*«Inst **)(savepc+1») 1* else part? *1  
execute(*«Inst **}(savepc+1»); pc = *«Inst **}(savepc+2}); 1* next stmt  
*1
```

```
}
```

The initialization code in `init.c` is augmented a little as well, with a table of keywords that are stored in the symbol table along with everything else:

```
$ cat init.c
```

```
static struct { char int } keywords[] =
```

```
1* Keywords *1
```

```
*name; kval; {
```

```
"if", "else", "while", "print", a ,
```

```
IF, ELSE, WHILE, PRINT, o ,
```

```
} ;
```

We also need one more loop in init, to install keywords.

```
for (i = 0; keywords[i].name; i++) install(keywords[i].name,  
keywords[i].kval, O.O);
```

No changes are needed in any of the symbol table management; code" c contains the routine prexpr, which is called when an statement of the form print expr is executed.

```

preexpr ( ) {

1* print numeric value *1

Datum d; d = pop ( ) ; printf("%.8g\n", d.val);

}

```

This is not the print function that is called automatically to print the final result of an evaluation; that one pops the stack and adds a tab to the output. hoeS is by now quite a serviceable calculator, although for serious programming, more facilities are needed. The following exercises suggest some

CHAPTER 8

PROGRAM DEVELOPMENT 273

possibilities. Exercise 8-12. Modify hoeS to print the machine it generates in a readable form for debugging. 0 Exercise 8-13. Add the assignment operators of C, such as +=, *=, etc., and the increment and decrement operators ++ and --. Modify && and :: so they guarantee left-to-right evaluation and early termination, as in C. 0 Exercise 8-14. Add a for

statement like that of C to hocS. Add break and continue. 0 Exercise 8-15. How would you modify the grammar or the lexical analyzer (or both) of hocS to make it more forgiving about the placement of newlines? How would you add semicolon as a synonym for newline? How would you add a comment convention? What syntax would you use? 0 Exercise 8-16. Add interrupt handling to hocS, so that a runaway computation can be stopped without losing the state of variables already computed. 0 Exercise 8-17. It is a nuisance to have to create a program in a file, run it, then edit the file to make a trivial change. How would you modify hocS to provide an edit command that would cause you to be placed in an editor with a copy of your hoc program already read in? Hint: consider a text opcode. 0

806 Stage 6: Functions and procedures; input/output The final stage in the evolution of hoc, at least for this book, is a major increase in functionality: the addition of functions and procedures. We have also added the ability to print character strings as well as numbers, and to read values from the standard input. hoc6 also accepts filename arguments, including the name "-" for the standard input. Together, these changes add 235 lines of code, bringing the total to about 810, but in effect convert hoc from a calculator into a programming language. We won't show every line here; Appendix 3 is a listing of the entire program so you can see how the pieces fit together. In the grammar, function calls are expressions; procedure calls are statements. Both are explained in detail in Appendix 2, which also has some more examples. For instance, the definition and use of a procedure for printing all the Fibonacci numbers less than its argument looks like this:

274 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

```
$ cat fib proc fib() { a = 0 b = 1 while (b < $1) { print b c = b b = a+b a = c
```

```
} print "\n"
```

```
} $ hoc6 fib - fib(1000) 1 1 2 3 5 8 13 21 34 55 89 144 233 377 610 987
```

This also illustrates the use of files: the filename "-" is the standard input. Here is a factorial function:

```
$ cat fac func fac() { if ($1 <= 0) return 1 else return $1 * fac($1-1}
```

```
} $ hoc6 fac - fac(0) 1 fac (7) 5040 fac(10) 3628800
```

Arguments are referenced within a function or procedure as \$ 1, etc., as in the shell, but it is legal to assign to them as well. Functions and procedures are recursive, but only the arguments are local variables; all other variables are global, that is, accessible throughout the program. hoc distinguishes functions from procedures because doing so gives a level of checking that is valuable in a stack implementation. It is too easy to forget a return or add an extra expression and foul up the stack. There are a fair number of changes to the grammar to convert hocS into hoc6, but they are localized. New tokens and non-terminals are needed, and the %union declaration has a new member to hold argument counts:

CHAPTER 8

PROGRAM DEVELOPMENT

275

\$ cat hoc.y

%union { Symbol Inst int

} %token %token %token %type %type %type %type

*sym; *inst; nargs;

/* symbol table pointer */ /* machine instruction */ /* number of arguments
*/

<sym> <sym> <narg> <inst> <inst> <sym> <narg>

NUMBER STRING PRINT VAR BLTIN UNDEF WHILE IF ELSE
FUNCTION PROCEDURE RETURN FUNC PROC READ ARG expr
stmt asgn prlist stmtlist cond while if begin end procname arglist


```
list: /* nothing */ list '\n' list defn '\n' list asgn '\n' { code2(pop, STOP) ;
return 1 ; } list stmt '\n' { code(STOP); return 1 ; } list expr '\n' {
code2(print, STOP) ; return 1 ; } list error '\n' { yyerrok; }
```

asgn:

stmt:

expr:

begin:

```
VAR '=' expr { code3(varpush,(Inst)$1,assign); $$=$3; } ARG '::' expr {
defnonly("$"); code2(argassign,(Inst)$1); $$==$3;}
```

```
expr {code(pop); } RETURN { defnonly("return"); code(procret); }
RETURN expr { defnonly("return"); $$=$2; code(funcrct); }
PROCEDURE begin '(' arglist ')' { $ $ = $ 2; c ode 3 ( call, (I ns t ) $ 1, ( Ins
t ) $ 4 ); } PRINT prlist { $$ == $2; }
```

```
NUMBER { $$ = code2(constpush, (Inst)$1); } VAR { $$ = code3(varpush,
(Inst)$1, eval); } ARG {defnonly("$"); $$ = code2(arg, (Inst)$1); } asgn
```

```
FUNCTION begin '(' arglist ')' { $$ == $2; code3(call,(Inst)$1,(Inst)$4); }  
READ '(' VAR ')' { $$ = code2(varread, (Inst)$3); }
```

```
/* nothing */
```

```
{ $$ = progp; }
```

276 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

prlist:

expr STRING prlist prlist

, , , , ,

expr STRING

```
{ code(preexpr); } { $$ = code2(prstr, (Inst)$1); } { code(preexpr); } {  
code2(prstr, (Inst)$3); }
```

defn:

```
FUNC procname { $2->type=FUNCTION; indef=1; } '(' ')' stmt {  
code(procret); define($2); indef=O; } PROC procname { $2-  
>type=PROCEDURE; indef=1; } '(' ')' stmt { code(procret); define($2);  
indef=O; }
```

```
procname: VAR I FUNCTION I I PROCEDURE I arglist: 1* nothing *1 {  
$$ = o ; } expr { $$ = 1 ; } arglist , , expr { $$ $1 + 1 ; } , = %%
```

The productions for arglist count the arguments. At first sight it might seem necessary to collect arguments in some way, but it's not, because each expr in an argument list leaves its value on the stack exactly where it's wanted. Knowing how many are on the stack is all that's needed. The rules for defn introduce a new yacc feature, an embedded action. It is possible to put an action in the middle of a rule so that it will be executed during the recognition of the rule. We use that feature here to record the fact that we are in a function or procedure definition. (The alternative is to create a new symbol analogous to begin, to be recognized at the proper time.) The function defnonly prints a warning message if a construct occurs outside of the definition of a function or procedure when it shouldn't. There is often a choice of whether to detect errors syntactically or semantically; we faced one earlier in handling undefined variables. The defnonly function is a good example of a place where the semantic check is easier than the syntactic one. defnonly(s) 1* warn if illegal definition *1 char *s;

{

```
if (!indef) execerror(s, "used outside definition");
```

```
}
```

The variable `indef` is declared in `hoc.y`, and set by the actions for `defn`. The lexical analyzer is augmented by tests for arguments - a `$` followed by a number - and for quoted strings. Backslash sequences like `\n` are interpreted in strings by a function `backslash`.

CHAPTER 8

PROGRAM DEVELOPMENT

277

```
yylex ( )
```

```
/* hoc6 */
```

```
if (c === '$') { /* argument? *1 int n = 0; while (isdigit(c=getc(fin))) n = 10  
* n + C - '0'; ungetc ( c, fin); if (n == 0) execerror("strange $...", (char
```

```
*)O}; yylval.narg :: n; return ARG;
```

```
    } if (c == "") { 1* quoted string */ char sbuf[100], *P, *emalloc(); for (p = s  
buf ; (c:: get c ( fin)) !:: ""; p + +) { if (c == '\n' :: c == EOF)  
execerror("missing quote", ""); if (p >= sbuf + sizeof(sbuf) - 1) { *p :: '\0' ;  
execerror("string too long", sbuf}
```

```
    } *p = backslash(c);
```

```
    } *p :: 0; yylval.sym == (Symbol *)emalloc(strlen(sbuf)+1};  
strcpy(yylval.sym, sbuf}; return STRING;
```

```
}
```

```
backslash(c) /* get next char with \'s interpreted */ int c;
```

```
{
```

```
char *index(); /* 'strchr()' in some systems */ static char transtab[] ::  
"b\bf\fn\nr\rt\t"; if (c != '\\') return c; c :: getc (fin) ; if (islower(c) &&  
index(transtab, c)) return index(transtab, c)[1]; return c;
```

```
}
```

A lexical analyzer is an example of a finite state machine, whether written in C or with a program generator like lex. Our ad hoc C version has grown fairly complicated; for anything beyond this, lex is probably better, both in size of source code and ease of change. Most of the other changes are in code" c, with some additions of function names to hoc" h. The machine is the same as before, except that it has been

278

THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

augmented with a second stack to keep track of nested function and procedure calls. (A second stack is easier than piling more things into the existing one) Here is the beginning of code.. c:

```
$ cat code.c #define NPROG 2000 Inst prog[NPROG]; Inst *progp; Inst
*pc; Inst *progbase = int returning;
```

```
/* the machine */ /* next free spot for code generation */ /* program
counter during execution */ prog; /* start of current subprogram */ ( /* 1 if
return stmt seen */
```

```
typedef struct Frame { Symbol *sp; Inst *retpc; Datum *argn; int nargs; }
Frame; #define NFRAME 100 Frame frame[NFRAME]; Frame *fp; /*
frame pointer */
```

```
initcode() { progp
```

```
progbase; stackp :::: stack; fp :::: frame; returning::: 0;
```

```
}
```

```
$
```

```
/* proc/func call stack frame */ /* symbol table entry */ /* where to resume
after return */ /* n-th argument on stack */ /* number of arguments */
```

Since the symbol table now holds pointers to procedures and functions, and to strings for printing, an addition is made to the union type in hoc.. h: \$ cat hoc.h

```
typedef struct Symbol { /* symbol table entry */ char *name; short
type; union {
```

```
double double int char
```

```
} u; struct Symbol } Symbol;
```

\$

```
val; /* VAR */ ( *ptr ) ( ) ; /* BLTIN */ (*defn)(); /* FUNCTION,  
PROCEDURE *1 *str; /* STRING */ *next; /* to link to another */
```

During compilation, a function is entered into the symbol table by define, which stores its origin in the table and updates the next free location after the

CHAPTER 8

PROGRAM DEVELOPMENT 279

generated code if the compilation is successful. define(sp) /* put func/proc in symbol table */ Symbol *sp;

{

sp->u.defn = (Inst)progbase; /* start of code */ progbase = progp; /* next code starts here */

}

When a function or procedure is called during execution, any arguments have already been computed and pushed onto the stack (the first argument is the deepest). The opcode for call is followed by the symbol table pointer and the number of arguments. A Frame is stacked that contains all the interesting information about the routine - its entry in the symbol table, where to return after the call, where the arguments are on the expression stack, and the number of arguments that it was called with. The frame is created by call, which then executes the code of the routine.

```
call() {
```

```
/* call a function */
```

```
Symbol *sp = (Symbol *)pc[0]; /* symbol table entry */ /* for function */  
if (fp++ >= &frame[NFRAME-1]) execerror(sp->name, "call nested too  
deeply"); fp->sp = sp; fp->nargs = (int)pc[1]; fp->retpc = pc + 2; fp->argn =  
stackp - 1; /* last argument */ execute(sp->u.defn); returning = 0;
```

```
}
```

This structure is illustrated in Figure 8.2. Eventually the called routine will return by executing either a procret or a funcret:

```
funcret() {
```

```
/* return from a function */
```

```
Datum d; if (fp->sp->type == PROCEDURE) execerror(fp->sp->name, "  
(proc) returns value"); d = pope); /* preserve function return value */ ret ( )  
; push ( d ) ;
```

```
}
```

280 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

Machine Frame Stack stackp call argn arg3 *sym nargs arg2 nargs retpc
arg1 sp

*defn

Figure 8.2: Data structures for procedure call

```
procret ( ) {
```

```
/* return from a procedure */
```

```
if (fp->sp->type == FUNCTION) execerror(fp->sp->name, "(func) returns  
no value");
```

```
ret ( ) ;
```

```
}
```

The function `ret` pops the arguments off the stack, restores the frame pointer `fp`, and sets the program counter.

```
ret ( ) {
```

```
/* common return from func or proc */
```

```
int i; for (i = 0; i < fp->nargs; i++) pope); /* pop arguments */ pc = (Inst  
*)fp->retpc; --fp; returning = 1;
```

```
}
```

Several of the interpreter routines need minor fiddling to handle the situation when a return occurs in a nested statement. This is done inelegantly but adequately by a flag called `returning`, which is true when a return statement has been seen. `ifcode`, `whilecode` and `execute` terminate early if `returning` is set; `call` resets it to zero.

CHAPTER 8

PROGRAM DEVELOPMENT

281

```
ifcode() {
```

```
    Datum d; Inst *savepc = pc;
```

```
    /* then part */
```

```
    execute(savepc+3); /* condition */ d = pop ( ) ; if (d.val) execute(*«Inst **»  
    (savepc»); else if (*«Inst **»)(savepc+1») /* else part? */ execute(*«Inst **»  
    (savepc+1»); if (Ireturning) pc = *«Inst **»)(savepc+2»; /* next stmt */
```

```
} whilecode() {
```

```
Datum d; Inst *savepc = pc;
```

```
execute(savepc+2); /* condition */ d = pop ( ) ; while (d.val) {  
execute(*«Inst **)(savepc»); /* body */ if (returning) break;  
execute(savepc+2); /* condition */ d = pop ( ) ;
```

```
} if (Ireturning) pc = *«Inst **)(savepc+1»); /* next stmt */
```

```
} execute(p) Inst *p;
```

```
{
```

```
for (pc = p; *pc != STOP && !returning; ) (*(pc++)());
```

```
}
```

Arguments are fetched for use or assignment by getarg, which does the correct arithmetic on the stack:

```
double *getarg() {
```

```
/* return pointer to argument */
```

```
int nargs = (int) *pc++; if (nargs > fp->nargs) execerror(fp->sp->name, "not  
enough arguments"); return &fp->argn[nargs - fp->nargs].val;
```

```
}
```

282 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

```
arg ( ) {
```

```
/* push argument onto stack */
```

```
Datum d; d.val = *getarg(); push (d) ;
```

```
}
```

```
argassign( ) {
```

```
/* store top of stack in argument */
```

```
Datum d; d = pop ( ) ; pushed); /* leave value on stack */ *getarg() = d.val;
```

```
}
```

Printing of strings and numbers is done by prstr and prexpr.

```
prstr ( ) {
```

```
/* print string value */
```

```
printf("%s", (char *) *pc++);
```

```
}
```

```
prexpr ( ) {
```

```
/* print numeric value */
```

```
Datum d; d = pop ( ) ; printf("%.8g ", d.val);
```

```
}
```

Variables are read by a function called varread. It returns 0 if end of file occurs; otherwise it returns 1 and sets the specified variable.

eCHAPTER 8

PROGRAM DEVELOPMENT 283

```
varread ( ) {
```

```
/* read into variable */
```

```
Datum d; extern FILE *fin; Symbol *var = (Symbol *) *pc++; Again:  
switch (fscanf(fin, "%If", &var->u.val» { case EOF: if (moreinput(» goto  
Again; d.val = var->u.val = 0.0; break;
```


case 0:

```
execerror("non-number read into", var->name break; default: d.val = 1.0;  
break;
```

```
} var->type = VAR; push ( d) ;
```

```
}
```

If end of file occurs on the current input file, varread calls moreinput, which opens the next argument file if there is one. moreinput reveals more about input processing than is appropriate here; full details are given in Appendix 3. This brings us to the end of our development of hoc. For comparison purposes, here is the number of non-blank lines in each version:

hoc1 hoc2 hoc3 hoc4 hoc5 hoc6

59 94 248 396 574 809

(lex version 229)

Of course the counts were computed by programs: \$ sed //""\$/d/ 'pick *.
[chy1J' / we -1

The language is by no means finished, at least in the sense that it's still easy to think of useful extensions, but we will go no further here. The following exercises suggest some of the enhancements that are likely to be of value.

Exercise 8-18. Modify hoc6 to permit named formal parameters in subroutines as an alternative to \$1, etc. 0

Exercise 8-19. As it stands, all variables are global except for parameters. Most of the mechanism for adding local variables maintained on the stack is already present. One approach is to have an auto declaration that makes space on the stack for variables

284 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

listed; variables not so named are assumed to be global. The symbol table will also have to be extended, so that a search is made first for locals, then for globals. How does this interact with named arguments? 0

Exercise 8-20. How would you add arrays to hoc? How should they be passed to functions and procedures? How are they returned? 0

Exercise 8-21. Generalize string handling, so that variables can hold strings instead of numbers. What operators are needed? The hard part of this is storage management: making sure that strings are stored in such a way that they are freed when they are not needed, so that storage does not leak away. As an interim step, add better facilities for output formatting, for example, access to some form of the C printf statement. 0

8.7 Performance evaluation We compared hoc to some of the other UNIX calculator programs, to get a rough idea of how well it works. The table

below should be taken with a grain of salt, but it does indicate that our implementation is reasonable. All times are in seconds of user time on a PDP-11/70. There were two tasks. The first is computing Ackermann's function `ack (3 , 3)`. This is a good test of the function-call mechanism; it requires 2432 calls, some nested quite deeply. `func ack() { if ($1 == 0) return $2+1 if ($2 == 0) return ack($1-1, 1) return ack($1-1, ack($1, $2-1)»`

`} ack(3,3)` The second test is computing the Fibonacci numbers with values less than 1000 a total of one hundred times; this involves mostly arithmetic with an occasional function call.

```
proc fib ( ) { a = 0 b = 1 while (b < $1 ) { c = b b = a+b a = c } } i = 1 while
(i < 100) { fib(1000) i = i + 1 }
```

The four languages were hoc, be(1), bas (an ancient BASIC dialect that only runs on the PDP-11), and C (using double's for all variables). The numbers in Table 8.1 are the sum of the user and system CPU time as

CHAPTER 8

PROGRAM DEVELOPMENT 285

Table 8.1: Seconds of user time (PDP-11/70) program `ack(3,3)` `100Xfib(1000)` hoc 5.5 5.0 bas 1.3 0.7 be 39.7 14.9 C <0.1 <0.1

measured by time. It is also possible to instrument a C program to determine how much of that time each function uses. The program must be recompiled with profiling turned on, by adding the option `-p` to each C compilation and load. If we modify the makefile to read

`$(OBJS) cc $(CFLAGS) $(OBJS) -lm -o hoc6` so that the `cc` command uses the variable `CFLAGS`, and then say

`hoc6:`

`$ make clean; make CFLAGS=-p`

the resulting program will contain the profiling code. When the program runs, it will leave a file called `man.out` of data that is interpreted by the program `prof`. To illustrate these notions briefly, we made a test on `hoc6` with the Fibonacci program above.

```
$ hoc6 <fibtest Run the test $ prof hoc6 | sed 15q Analyze | name %time
cumsecs #call ms/call _pop 15.6 0.85 32182 0.03 _push 14.3 1.63 32182
0.02 mcount 11.3 2.25 csv 10. 1 2.80 cret 8.8 3.28 _assign 8.2 3.73 5050
0.09 eval 8.2 4.18 8218 0.05 execute 6.0 4.51 3567 0.09 _varpush 5.9 4.83
13268 0.02 It 2.7 4.98 1783 0.08 _constpu 2.0 5.09 497 0.22 add 1.7 5.18
1683 0.05 _getarg 1 . 5 5.26 1683 0.05 _yyparse 0.6 5.30 3 11.11 $
```

The measurements obtained from profiling are just as subject to chance fluctuations as are those from time, so they should be treated as indicators,

not absolute truth. The numbers here do suggest how to make hoe faster, however, if it needs to be. About one third of the run time is going into

286 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 8

pushing and popping the stack. The overhead is larger if we include the times for the C subroutine linkage functions `csv` and `crete` (`mcount` is a piece of the profiling code compiled in by `cc -p`.) Replacing the function calls by macros should make a noticeable difference. To test this expectation, we modified code" `c`, replacing calls to `push` and `pop` with macros for stack manipulation: `#define push(d) *stackp++ = (d) #define popm() *--stackp 1` * function still needed *1

(The function `pop` is still needed as an opcode in the machine, so we can't just replace all `pop`'s.) The new version runs about 35 percent faster; the times in Table 8.1 shrink from 5.5 to 3.7 seconds, and from 5.0 to 3.1. Exercise 8-22. The `push` and `popm` macros do no error checking. Comment on the wisdom of this design. How can you combine the error-checking provided by the function versions with the speed of macros? D

8.8 A look back

There are some important lessons to learn from this chapter. First, the language development tools are a boon. They make it possible to concentrate on the interesting part of the job - language design - because it

is so easy to experiment. The use of a grammar also provides an organizing structure for the implementation - routines are linked together by the grammar, and called at the right times as parsing proceeds. A second, more philosophical point, is the value of thinking of the job at hand more as language development than as "writing a program." Organizing a program as a language processor encourages regularity of syntax (which is the user interface), and structures the implementation. It also helps to ensure that new features will mesh smoothly with existing ones. "Languages" are certainly not limited to conventional programming languages - examples from our own experience include eqn and pic, and yacc, lex and make themselves. There are also some lessons about how tools are used. For instance, make is invaluable. It essentially eliminates the class of error that arises from forgetting to recompile some routine. It helps to ensure that no excess work is done. And it provides a convenient way to package a group of related and perhaps dependent operations in a single file. Header files are a good way to manage data declarations that must be visible in more than one file. By centralizing the information, they eliminate errors caused by inconsistent versions, especially when coupled with make. It is also important to organize the data and the routines into files in such a way that they are not made visible when they don't have to be. There are a couple of topics that, for lack of space, we did not stress. One is simply the degree to which we used all the other UNIX tools during

CHAPTER 8

PROGRAM DEVELOPMENT 287

development of the hoe family. Each version of the program is in a separate directory, with identical files linked together; Is and du are used repeatedly to keep track of what is where. Many other questions are answered by programs. For example, where is that variable declared? Use grep. What did we change in this version? Use diff. How do we integrate the changes into

that version? Use `idiff`. How big is the file? Use `wc`. Time to make a backup copy? Use `cp`. How can we back up only the files changed since the last backup? Use `make`. This general style is absolutely typical of day-to-day program development on a UNIX system: a host of small tools, used separately or combined as necessary, help to mechanize work that would otherwise have to be done by hand.

History and bibliographic notes `yacc` was developed by Steve Johnson. Technically, the class of languages for which `yacc` can generate parsers is called LALR(1): left to right parsing, looking ahead at most one token in the input. The notion of a separate description to resolve precedence and ambiguity in the grammar is new with `yacc`. See "Deterministic parsing of ambiguous grammars," by A. V. Aho, S. C. Johnson, and J. D. Ullman, CACM, August, 1975. There are also some innovative algorithms and data structures for creating and storing the parsing tables. A good description of the basic theory underlying `yacc` and other parser generators may be found in *Principles of Compiler Design*, by A. V. Aho and J. D. Ullman (Addison-Wesley, 1977). `yacc` itself is described in Volume 2B of *The UNIX Programmer's Manual*. That section also presents a calculator comparable to `bc`; you might find it instructive to make the comparison. `lex` was originally written by Mike Lesk. Again, the theory is described by Aho and Ullman, and the `lex` language itself is documented in *The UNIX Programmer's Manual*. `yacc`, and to a lesser degree `lex`, have been used to implement many language processors, including the portable C compiler, Pascal, FORTRAN 77, Ratfor, `awk`, `bc`, `eqn`, and `pie`. `make` was written by Stu Feldman. See "MAKE - a program for maintaining computer programs," *Software-Practice & Experience*, April, 1979. *Writing Efficient Programs* by Jon Bentley (Prentice-Hall, 1982) describes techniques for making programs faster. The emphasis is on first finding the right algorithm, then refining the code if necessary.

CHAPTER 9:

E T P EPA

TI

One of the first applications of the UNIX system was editing and formatting documents; indeed, Bell Labs management was persuaded to buy the first PDP-11 hardware by promises of a document preparation system, not an operating system. (Fortunately, they got more than they bargained for.) The first formatting program was called roff. It was small, fast, and easy to work with, so long as one was producing simple documents on a line printer. The next formatter, nroff, by Joe Ossanna, was much more ambitious. Rather than trying to provide every style of document that users might ever want, Ossanna made nroff programmable, so that many formatting tasks were handled by programming in the nroff language. When a small typesetter was acquired in 1973, nroff was extended to handle the multiple sizes and fonts and the richer character set that the typesetter provided. The new program was called troff (which by analogy to "en-foff" is pronounced "tee-roff.") nroff and troff are basically the same program, and accept the same input language; nroff ignores commands like size changes that it can't honor. We will talk mainly about troff but most of our comments apply to nroff as well, subject to the limitations of output devices. The great strength of troff is the flexibility of the basic language and its programmability - it can be made to do almost any formatting task. But the flexibility comes at a high price - troff is often astonishingly hard to use. It is fair to say that almost all of the UNIX document preparation software is designed to cover up some part of naked troff. One example is page layout - the general style of a document, what the titles, headings and paragraphs look like, where the page numbers appear, how big the pages are, and so on. These are not built in; they have to be programmed. Rather than forcing each user to specify all of these details in every document, however, a package of standard formatting commands is provided. A user of the package does not say "the next line is to be centered, in bigger letters, and in a bold font." Instead, the user says "the next line is a title," and the packaged definition of the style of a title is used. Users talk about the logical components of a document -

titles, headings, paragraphs, footnotes, etc. - instead of sizes, fonts, and positions.

289

290 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

Unfortunately, what started out as a "standard" package of formatting commands is no longer standard: there are several packages in wide use, plus many local variants. We'll talk about two general-purpose packages here: `ms`, the original "standard," and `mm`, a newer version that is standard in System V. We'll also describe the `man` package for printing manual pages. We will concentrate on `ms` because it is standard in the 7th Edition, it exemplifies all such packages, and it is powerful enough to do the job: we used it to typeset this book. But we did have to extend it a bit, for example, by adding a command to handle words in this font in the text. This experience is typical - the macro packages are adequate for many formatting tasks, but it is sometimes necessary to revert to the underlying troff commands. We will describe only a small part of troff here. Although troff provides the ability to control output format completely, it's far too hard to use for complicated material like mathematics, tables, and figures. Each of these areas is just as difficult as page layout. The solution to these problems takes a different form, however. Instead of packages of formatting commands, there are special-purpose languages for mathematics, tables and figures that make it easy to describe what is wanted. Each is handled by a separate program that translates its language into troff commands. The programs communicate through pipes. These preprocessors are good examples of the UNIX approach at work - rather than making troff even bigger and

more complicated than it is, separate programs cooperate with it. (Of course, the language development tools described in Chapter 8 have been used to help with the implementations.) We will describe two programs: `tbl`, which formats tables, and `eqn`, which formats mathematical expressions. We will also try to give hints about document preparation and the supporting tools. Our examples throughout the chapter will be a document describing the hoc language of Chapter 8 and a hoc manual page. The document is printed as Appendix 2.

9.1 The `ros` macro package The crucial notion in the macro packages is that a document is described in terms of its logical parts - title, section headings, paragraphs - not by details of spacing, fonts and sizes of letters. This saves you from some very hard work, and insulates your document from irrelevant details; in fact, by using a different set of macro definitions with the same logical names, you can make your document appear quite different. For example, a document might go through the stages of technical report, conference paper, journal article and book chapter with the same formatting commands, but formatted with four different macro packages. Input to `troff`, whether or not a macro package is involved, is ordinary text interspersed with formatting commands. There are two kinds of

CHAPTER 9

DOCUMENT PREPARATION 291

commands. The first consists of a period at the beginning of a line, followed by one or two letters or digits, and perhaps by parameters, as illustrated here: `.PP .ft B` This is a little bold font paragraph.

troff built-in commands all have lower-case names, so by convention commands in macro packages are given upper-case names. In this example, `PP` is the ms command for a paragraph, and `ft B` is a troff command that causes a change to the bold font. (Fonts have upper case names; the fonts available may be different on different typesetters.) The second form of troff command is a sequence of characters that begins with a backslash `\`, and may appear anywhere in the input; for example, `\fB` also causes a switch to the bold font. This form of command is pure troff; we'll come back to it shortly. You can format with nothing more than a `.. PP` command before each paragraph, and for most documents, you can get by with about a dozen different ms commands. For example, Appendix 2, which describes hoc, has a title, the authors' names, an abstract, automatically-numbered section headings, and paragraphs. It uses only 14 distinct commands, several of which come in pairs. The paper takes this general form in ms:

`..TL` Title of document (one or more lines) `.AU` Author names, one per line
`.AB` Abstract, terminated by `. AE` `.AE` `.NH` Numbered heading (automatic numbering) `.PP` Paragraph ... `.PP` Another paragraph ... `.SH` Sub-heading (not numbered) `.PP`

Formatting commands must occur at the beginning of a line. Input between the commands is free form: the location of newlines in the input is unimportant, because troff moves words from line to line to make lines long enough (a process called filling), and spreads extra space uniformly between words to align the margins (justification). It's a good practice, however, to start each sentence on a new line; it makes subsequent editing easier. Here is the beginning of the actual hoc document:

CHAPTER 9

.TL Hoc - An Interactive Language For Floating Point Arithmetic .AU
Brian Kernighan Rob Pike .AB .I Hoc is a simple programmable interpreter
for floating point expressions. It has C-style control flow, function
definition and the usual numerical built-in functions such as cosine and
logarithm. .AE .NH Expressions .PP .I Hoc is an expression language,
much like C: although there are several control-flow statements, most
statements such as assignments are expressions whose value is disregarded.

The `. I` command italicizes its argument, or switches to italic if no argument
is given. If you use a macro package, it's specified as an argument to `trac`:

```
$ trac -ms hoc oms
```

The characters after the `-m` determine the macro package. `t` When formatted
with `mB`, the hoc paper looks like this:

`t` The `ms` macros are in the file `/usr/lib/tmac/tmac. s`, and the `man` macros
are in `/usr/lib/tmac/tmac.an`.

CHAPTER 9

Hoc ... An Interactive Language For Floating Point Arithmetic

Brian Kernighan Rob Pike

ABSTRACT

Hoc is a simple programmable interpreter for floating point expressions. It has C-style control flow, function definition and the usual numerical built-in functions such as cosine and logarithm.

1. Expressions Hoc is an expression language, much like C: although there are several control-flow statements, most statements such as assignments are expressions whose value is disregarded.

Displays Although it is usually convenient that text fills and justifies text, sometimes that isn't desirable - programs, for example, shouldn't have their margins adjusted. Such unformatted material is called display text. The commands .DS (display start) and .DE (display end) demarcate text to be printed as it appears, indented but without rearrangement. Here is the next portion of the hoc manual, which includes a short display: .PP .1 Hoc is an expression language, much like c: although there are several control-flow statements, most statements such as assignments are expressions whose value is disregarded. For example, the assignment operator = assigns the value of its right operand to its left operand, and yields the value, so multiple assignments work. The expression grammar is:

294 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

oDS .1 expr:

number variable (expr) expr binop expr unop expr function (arguments)

.R .DE Numbers are floating point.

which prints as

Hoc is an expression language, much like C: although there are several control- flow statements, most statements such as assignments are expressions whose value is disregarded. For example, the assignment operator = assigns the value of its right operand to its left operand, and yields the value, so multiple assignments work. The expression grammar is:

number variable (expr) expr binop expr unop expr function (arguments)
Numbers are floating point.

expr:

Text inside a display is not normally filled or justified. Furthermore, if there is not enough room on the current page, the displayed material (and everything that follows it) is moved onto the next page. . DS permits several options, including L for left-justified, C, which centers each line individually, and B, which centers the entire display. The items in the display above are separated by tabs. By default, troff tabs are set every half inch, not every eight spaces as is usual. Even if tab stops were every 8 spaces, though, characters are of varying widths, so tabs processed by troff wouldn't always appear as expected.

Font changes The ros macros provide three commands to change the font. . R changes the font to roman, the usual font, . I changes to italic, this font and "B changes to boldface, this font. Unadorned, each command selects the font for the subsequent text:

CHAPTER 9

DOCUMENT PREPARATION 295

This text is roman, but .. I this text is italic, ..R this is roman again, and ..B this is boldface.

appears like t

is:

This text is roman, but this text is italic, this is roman again, and this is boldfaceJ

.. I and .. B take an optional argument, in which case the font change applies only to the argument. In troff, arguments containing blanks must be quoted, although the only quoting character is the double quote VI

This is roman, but .1 this is italic, and "B nthese words" are bold"

is printed as

This is roman, but this is italic, and these words are bold.

Finally, a second argument to .. I or .. B is printed in roman, appended without spaces to the first argument. This feature is most commonly used to produce punctuation in the right font. Compare the last parenthesis of (parenthetical .1 nitalic words)n

which prints incorrectly as

(parenthetical italic words)

with

(parenthetical ..I nitalic words")

which prints correctly as

(parenthetical italic words)

Font distinctions are recognized by nroff, but the results aren't as pretty. Italic characters are underlined, and there are no bold characters, although some versions of nroff simulate bold by overstriking.

296 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

Miscellaneous commands Footnotes are introduced with . FS and terminated with . FE. You are responsible for any identifying mark like an asterisk or a dagger. t This foot- note was created with

identifying mark like an asterisk or a dagger.

(dg .FS

(dg Like this one. .FE This footnote was created with ...

Indented paragraphs, perhaps with a number or other mark in the margin, are created with the . IP command. To make this: (1) First little paragraph. (2) Second paragraph, which we make longer to show that it will be indented on the second line as well as the first. requires the input . IP (1) First little paragraph. ..IP (2) Second paragraph, ...

A . PP or . LP (left-justified paragraph) terminates an . IP. The . IP argument can be any string; use quotes to protect blanks if necessary. A second argument can be used to specify the amount of indent. The command pair . KS and . KE causes text to be kept together; text enclosed between these commands will be forced onto a new page if it won't all fit on the current page. If . KF is used instead of . KS, the text will float past subsequent text to the top of the next page if necessary to keep it on one page. We used . KF for all the tables in this book. You can change most of ms's default values by setting number registers, which are traff variables used by ms. Perhaps the most common are the registers that control the size of text and the spacing between lines. Normal text size (what you are reading now) is "10 point," where a point is about 1/72 of an inch, a unit inherited from the printing industry. Lines are normally printed at 12-point separation. To change these, for example to 9 and 11 (as in our displays), set the number registers PS and vs with .nr PS 9 .nr VS 11

Other number registers include LL for line length, PI for paragraph indent, and PD for the separation between paragraphs. These take effect at the next . PP or 0 LP.

t Like this one.

CHAPTER 9

DOCUMENT PREPARATION 297

.AB .AU .B . DS t

. EQ s .FS . I . IP s .KF .KS .LP .NH n .PP .R .SH .TL .TS

Table 9.1: Common ms Formatting Commands; see also ms(7) start abstract; terminated by .. AE author's name follows on next line; multiple .. AU's permitted begin bold text, or embolden argument if supplied start display (unfilled) text; terminated by . DE t = L (left-adjusted), C (centered), B (block-centered) begin equation s (eqn input); terminated by . EN start footnote; terminated by .. FE begin italic text, or italicize argument if supplied indented paragraph, with s in margin keep text together, float to next page if necessary; end with . KE keep text together on page; end with . KE new left-justified paragraph n-th level numbered heading; heading follows, up to . PP or .. LP new paragraph return to roman font sub-heading; heading follows, up to . PP title follows, up to next ms command begin table (tbl input); terminated by e TE

The rom macro package We won't go into any detail on the rom macro package here, since it is in spirit and often in detail very similar to ms. It provides more control of parameters than ms does, more capabilities (e.g., automatically numbered lists), and better error messages. Table 9.2 shows the rom commands equivalent to the ms commands in Table 9.1. Exercise 9-1. Omitting a terminating command like "AE or "DE is usually a disaster.

Write a program mscheck to detect errors in ms input (or your favorite package). Suggestion: awk. 0

9.2 The troff level

In real life, one sometimes has to go beyond the facilities of ms, rom or other packages to get at some capability of bare troff. Doing so is like programming in assembly language, however, so it should be done cautiously and reluctantly. Three situations arise: access to special characters, in-line size and font changes, and a few basic formatting functions.

Character names Access to strange characters - Greek letters like 1T, graphics like - and t, and a variety of lines and spaces - is easy, though not very systematic. Each

298 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

.AS .AU .B .DF .DS .EQ .FS .I .H n " . HU " .P .R .TL .TS

"

Table 9.2: Common rom Formatting Commands start abstract; terminated by . AE author's name follows as first argument begin bold text, or embolden argument if supplied keep text together, float to next page if necessary; end at start display text; terminated by . DE begin equation (eqn input); terminated by . EN start footnote; terminated by . FE begin italic text, or italicize argument if supplied n-th level numbered heading "..."
 unnumbered heading "..."
 paragraph. Use .. nr pt 1 once for indented paragraphs return to roman font title follows, up to next rom command begin table (tbl input); terminated by . TE

.DE

"

such character has a name that is either 'c where c is a single character, or , (cd where cd is a pair of characters. traff prints an ASCII minus sign as a hyphen - rather than a minus -. A true minus must be typed \- and a dash must be typed \ (em, which stands for "em dash," the character "-". Table 9.3 lists some of the most common special characters; there are many more in the traff manual (and the list may be different on your system). There are times when traff must be told not to interpret a character, especially a backslash or a leading period. The two most common "hands-off" characters are \e and \&. The sequence \e is guaranteed to print as a backslash, uninterpreted, and is used to get a backslash in the output. '&, on the other hand, is "", nothing at all: it is a zero-width blank. Its main use is to prevent traff from interpreting periods at the beginning of lines. We used \e and \& a lot in this chapter. For example, the ms outline at the beginning of this chapter was typed as "\&..TL ..I "Title of document" \&..AU ..I "Author name" \& .. AB \&.. ..

Of course, the section above was typed as

CHAPTER 9

DOCUMENT PREPARATION 299

Table 9.3:

,\{hy \- \{mi \(\em \& \blank \1 \e ,\(\bu ,\{dg \{*a \fX \f {XX \sn \s + n

Some traff special character sequences hyphen hyphen, same as above
minus sign in current font minus sign in the mathematics font em dash
nothing at all; protects leading period unpaddable blank unpaddable half
blank literal escape character, usually \ bullet 8 dagger t ex. \ { * b = J3, \ (
* c =

, \ { * P = "IT, etc. change to font X; X = P is previous change to font XX
change to point size n; n= 0 is previous relative point size change

\e&..TL \&..1 "Title of document" \e&..AU

and you can imagine how that in turn was typed. Another special character
that turns up occasionally is the unpaddable blank, a \ followed by a blank.
Normally, traff will stretch an ordinary blank to align the margins, but an
unpaddable blank is never adjusted: it is like any other character and has a

fixed width. It can also be used to pass multiple words as a single argument:
`.1 Title\ of\ document`

Font and size changes Most font and format changes can be done with the beginning-of-line macros like `. I`, but sometimes changes must be made in-line. In particular, the newline character is a word separator, so if a font change must be made in the middle of the word, the macros are unusable. This subsection discusses how `traff` overcomes this problem - note that it is `traff` that provides the facility, not the `ms` macro package. `traff` uses the backslash character to introduce in-line commands. The two most common commands are `\f` to change font and `\s` to change point Size. The font is specified with `\f` by a character immediately after the `f`:

300 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

a 'fBfriv'fIolous'fR 'fIvar'fBiety'fR of 'fIfonts'fP is output as

a frivolous variety of fonts

The font change `'fP` reverts to the previous font - whatever the font was before the last switch. (There's only one previous font, not a stack.) Some fonts have two-character names. These are specified by the format `'f (XX` where `xx` is the font name. For example, the font on our typesetter in which programs in this book are printed is called `CW` (Courier Constant Width),

so keyword is written as 'f(CWkeyword'fP It's clearly painful to have to type this, so one of

our extensions to ms is a .. CW macro so we don't have to type or read backslashes. We use it to typeset in-line words such as troff, like this: The .CW troff formatter

Formatting decisions defined by macros are also easy to change later. A size change is introduced by the sequence 'sn, where n is one or two digits that specify the new size: 's8 switches to 8 point type. More commonly, relative changes may be made by prefixing a plus or minus to the size. For example, words can be printed in SMALL CAPS by typing 's-2SMALL CAPS'sO

'sO causes the size to revert to its previous value. It's the analog of 'fP, but in the troff tradition, it isn't spelled 'sP. Our extensions to ms include a macro .. UC (upper case) for this job.

Basic troff commands Realistically, even with a good macro package, you have to know a handful of troff commands for controlling spacing and filling, setting tab stops, and the like. The command .br causes a break, that is, the next input that follows the .br will appear on a new output line. This could be used, for example, to split a long title at the proper place: .TL Hoc - An Interactive Language .br For Floating Point Arithmetic

The command .nf turns off the normal filling of output lines; each line of input goes directly into one line of output. The command .fi turns filling

CHAPTER 9

DOCUMENT PREPARATION 301

back on. The command `. ce` centers the next line. The command `. bp` begins a new page. The command `. sp` causes a single blank line to appear in the output. A `. sp` command can be followed by an argument to specify how many blank lines or how much space.

```
.sp 3 .sp .5 .sp 1.5i .sp 3p .sp 3.1c
```

Leave 3 blank lines Leave blank half-line Leave 1.5 inches Leave 3 points
Leave 3.1 centimeters

Extra space at the bottom of a page is discarded, so a large `. sp` is equivalent to a `. e bp`. The `. ta` command sets tab stops (which are initialized to every half inch).

```
. ta n n n ...
```

sets tab stops at the specified distances from the left margin; as with `. sp`, each number `n` is in inches if followed by `'i'`. A tab stop suffixed with `R` will right-justify the text at the next tab stop; `C` causes a centered tab. The command `.. ps n` sets the point size to `n`; the command `.. ft X` sets the font to `X`. The rules about incremental sizes and returning to the previous value are the same as for `\s` and `\f`.

Defining macros Defining macros in full generality would take us much further into the intricacies of `traff` than is appropriate, but we can illustrate some of the basics. For example, here is the definition of `.CW`:

Start a definition Font change around first argument End of definition `\$n`
 produces the value of the *n*-th argument when the macro is invoked; it is empty if no *n*-th argument was provided. The double `\` delays evaluation of `\$n` during macro definition. The `\&` prevents the argument from being interpreted as a `traff` command, in case it begins with a period, as in

```
.de CW \&\f(CW\1\p\2
```

```
. cw . s p
```

9.3 The `tbl` and `eqn` preprocessors `traff` is a big and complicated program, both inside and out, so modifying it to take on a new task is not something to be undertaken lightly. Accordingly the development of programs for typesetting mathematics and tables took a different approach - the design of separate languages implemented by separate programs `eqn` and `tbl` that act as "preprocessors" for `traff`. In effect, `traff` is an assembly language for a typesetting machine, and `eqn` and `tbl` compile into it.

302 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

eqn came first. It was the first use of yacc for a non-programming language. `tbl` came next, in the same spirit as eqn, though with an unrelated syntax. `tbl` doesn't use yacc, since its grammar is simple enough that it's not worthwhile. The UNIX pipe facility strongly suggests the division into separate programs. Besides factoring the job into pieces (which was necessary anyway - troff by itself was already nearly as large as a program could be on a PDP-11), pipes also reduce the communication between the pieces and between the programmers involved. This latter point is significant - one doesn't need access to source code to make a preprocessor. Furthermore, with pipes there are no giant intermediate files to worry about, unless the components are intentionally run separately for debugging. There are problems when separate programs communicate by pipes. Speed suffers somewhat, since there is a lot of input and output: both eqn and tbl typically cause an eight-to-one expansion from input to output. More important, information flows only one direction. There is no way, for example, that eqn can determine the current point size, which leads to some awkwardness in the language. Finally, error reporting is hard; it is sometimes difficult to relate a diagnostic from troff back to the eqn or tbl problem that caused it. Nevertheless, the benefits of separation far outweigh the drawbacks, so several other preprocessors have been written, based on the same model.

Tables Let us begin a brief discussion of tbl, since the first thing we want to show is a table of operators from the hoc document. tbl reads its input files or the standard input and converts text between the commands `TS` (table start) and `TE` (table end) into the troff commands to print the table, aligning columns and taking care of all the typographical details. The `TS` and `TE` lines are also copied through, so a macro package can provide suitable definitions for them, for example to keep the table on one page and set off from surrounding text. Although you will need to look at the tbl manual to produce complicated tables, one example is enough to show most of the common features. Here is one from the hoc document:

t It is improbable that eqn would exist if yacc had not been available at the right time.

CHAPTER 9

DOCUMENT PREPARATION 303

.TS center, box; c s IfCW 1. \fBTable 1:\fP Operators, in decreasing order of precedence .sp .5

'''

exponentiation (\s-1FORTRAN\sO **), right associative (unary) logical and arithmetic negation multiplication, division addition, subtraction relational operators: greater, greater or equal, less, less or equal, equal, not equal (all same precedence) logical AND (both operands always evaluated) logical OR (both operands always evaluated) assignment, right associative

\- * / + \- > >= < <= \&== != && I I I I \&= . FJ:E

which produces the following table:

Table 1: Operators, in decreasing order of precedence

I I I I

exponentiation (FORTRAN **), right associative (unary) logical and arithmetic negation multiplication, division addition, subtraction relational operators: greater, greater or equal, less, less or equal, equal, not equal (all same precedence) logical AND (both operands always evaluated) logical OR (both operands always evaluated) assignment, right associative

"

* /

+ > >=

< <=

- 1= &&

::

The words before the semicolon (center, box) describe global properties of the table: center it horizontally on the page and draw a box around it. Other possibilities include doublebox, allbox (each item in a box), and expand (expand table to page width). The next lines, up to the period, describe the format of various sections of the table, which in this case are the title line and the body of the table. The first specification is for the first line of the table, the second specification applies to the second line, and the last applies to all remaining lines. In Table 1, there are only two specification lines, so the second specification applies to every table line after the first. The format characters are c for items centered in the column, r and l for right or left justification, and n for numeric alignment on the decimal point. s specifies a "spanned" column; in our case 'c s' means center the title over the entire table by spanning the second column as

304 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

well as the first. A font can be defined for a column; the tbl specification IfCW prints a left-justified column in the CW font. The text of the table follows the formatting information. Tab characters separate columns, and some traff commands such as .. sp are understood inside tables. (Note a couple of appearances of \&: unprotected leading - and = signs in columns ten tbl to draw lines across the table at that point.) tbl produces a wider variety of tables than this simple example would suggest: it will fill text in boxes, vertically justify column headings, and so on. The easiest way to use it for complicated tables is to look for a similar example in the manual in Volume 2A of the UNIX Programmer's Manual and adapt the commands.

Mathematical expressions The second traff preprocessor is eqn, which converts a language describ- ing mathematical expressions into the traff commands to print them. It automatically handles font and size changes, and also provides names for stan- dard mathematical characters. eqn input usually appears between .. EQ and .. EN lines, analogous to tbl's .. TS and "TE. For example, ..EQ $x_{sub\ i}$.EN

produces x_i If the ms macro package is used, the equation is printed as a "display," and an optional argument to .. EQ specifies an equation number. For example, the Cauchy integral formula

$$f(z) = \frac{1}{2\pi i} \int_C \frac{f(\zeta)}{z - \zeta} dz$$

(9.1)

is written as

$$..EQ (9.1) \quad f(\zeta) - \frac{1}{2\pi i} \int_C \frac{f(z)}{z - \zeta} dz$$

..EN

The eqn language is based on the way that mathematics is spoken aloud. One difference between spoken mathematics and eqn input is that braces {} are the parentheses of eqn - they override the default precedence rules of the language - but ordinary parentheses have no special significance. Blanks,

however, are significant. Note that the first zeta is surrounded by blanks in the example above: keywords such as zeta and aver are only recognized when surrounded by blanks or braces, neither of which appear in the output. To force blank space into the output, use a tilde character ~, as in ~::~. To get braces, use "{ II and " } VI . There are several classes of eqn keywords. Greek letters are spelled out, in lower or upper case, as in lambda and LAMBDA (A and A). Other

CHAPTER 9

DOCUMENT PREPARATION 305

mathematical characters have names, such as sum, int, infinity, grad: L, f, 00, V. There are positional operators such as sub, sup, from, to, and over:

00 1 LX? -+ - i =0 27r

IS

sum from i=0 to infinity x sub i sup 2 -->- 1 over {2 pi}

There are operators like sqrt and expandable parentheses, braces., etc. eqn will also create columns and matrices of objects. There are also commands to control sizes, fonts and positions when the defaults are not correct. It is common to place small mathematical expressions such as IOgI0(X) in the

body of the text, rather than in displays. The eqn keyword delim specifies a pair of characters to bracket in-line expressions. The characters used as left and right delimiters are usually the same; often a dollar sign \$ is used. But since hoc uses \$ for arguments, we use @ in our examples. % is also a suitable delimiter, but avoid the others: so many characters have special properties in the various programs that you can get spectacularly anomalous behavior. (We certainly did as we wrote this chapter.) So, after saying .EQ delim @@ .EN

00

in-line expressions such as $\sum_{i=0}^{\infty} x_i$ can be printed:

in-line expressions such as $\sum_{i=0}^{\infty} x_i$ can be printed:

In-line expressions are used for mathematics within a table, as this example from the hoc document shows:

```
.TS center, box; c s s lfCW n 1. \fBTable 3:\fP .sp .5 DEG E GAMMA PHI
PI .TE
```

Built-in Constants

57.29577951308232087680 2.71828182845904523536
0.57721566490153286060 1.61803398874989484820
3.14159265358979323846

@180/ pi@, degrees per radian @e@, base of natural logarithms
@gamma@, Euler-Mascheroni constant @((sqrt 5 +1)/2@, the golden ratio
@pi@, circular transcendental number

This table also shows how tbl lines up the decimal points in numeric (n)
columns. The output appears below.

306 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

Table 3: Built-in Constants

DEG E GAMMA PHI PI

57.29577951308232087680 2.71828182845904523536
0.57721566490153286060 1.61803398874989484820
3.14159265358979323846

180/7&, degrees per radian e, base of natural logarithms 'Y, E uler-
Mascheroni constant ($\sqrt{5} + 1$)/2, the golden ratio 7&, circular transcendental
number

Finally, since eqn italicizes any string of letters that it doesn't recognize, it is
a common idiom to italicize ordinary words using eqn. @Word@, for
exam- ple, prints as Word. But beware: eqn recognizes some common
words (such as from and to) and treats them specially, and it discards
blanks, so this trick has to be used carefully.

Getting output Once you have your document ready, you have to line up all
the preproces- sors and troff to get output. The order of commands is tbl,
then eqn, then troff. If you are just using troff, type

```
$ troff -ms filenames
```

(Or -rom)

Otherwise, you must specify the argument filenames to the first command
in the pipeline and let the others read their standard input, as in \$ eqn
filenames | troff -ms

or

```
$ tbl filenames : eqn : troff -ms
```

It's a nuisance keeping track of which of the preprocessors are really needed to print any particular document. We found it useful to write a program called `doctype` that deduces the proper sequence of commands:

```
$ doctype ch9.* cat ch9.1 ch9.2 ch903 ch904 : pic: tbl : eqn : troff -ms $
doctype hoc.ms cat hoc.ms : tbl : eqn : troff -ms $
```

`doctype` is implemented with tools discussed at length in Chapter 4; in particular, an `awk` program looks for the command sequences used by the preprocessors and prints the command line to invoke those needed to format the document. It also looks for the `.PP` (paragraph) command used by the `ms` package of formatting requests.

CHAPTER 9

DOCUMENT PREPARATION 307

```
$ cat doctype # doctype: synthesize proper command line for troff echo -n
"cat $* : " egrep -h 'A\.(EQ:TS:\[:PS:IS:PP)' $* : sort -u : awk ' /A\..PP/ {
ms++ } /A\..EQ/ { eqn++ } /A\..TS/ { tbl++ } /A\..PS/ { pic++ } /A\..IS/ {
ideal++ } /A\..[/ { refer++ } END {
```

```
if (refer> 0) if (pic> 0) if (ideal> 0) if (tbl > 0) if (eqn > 0) printf "troff " if
(ms > 0) printf "-ms" printf "\n"
```

```
printf printf printf printf printf
```

```
"refer : " "pic : " "ideal : " "tbl : " " eqn : "
```

```
} , $
```

(The `-h` option to `egrep` causes it to suppress the filename headers on each line; unfortunately this option is not in all versions of the system.) The input is scanned, collecting information about what kinds of components are used. After all the input has been examined, it's processed in the right order to print the output. The details are specific to formatting troff documents with the standard preprocessors, but the idea is general: let the machine take care of the details. `doctype` is an example, like `bundle`, of a program that creates a program. As it is written, however, it requires the user to retype the line to the shell; one of the exercises is to fix that. When it comes to running the actual troff command, you should bear in mind that the behavior of troff is system-dependent: at some installations it drives the typesetter directly, while on other systems it produces information on its standard output that must be sent to the typesetter by a separate program. By the way, the first version of this program didn't use `egrep` or `sort`; `awk` itself scanned all the input. It turned out to be too slow for large documents, so we added `egrep` to do a fast search, and then `sort -u` to toss out duplicates. For typical documents, the overhead of creating two extra processes to winnow the data is less than that of running `awk` on a lot of input. To illustrate, here is a comparison between `doctype` and a version that just runs `awk`, applied to the contents of this chapter (about 52000 characters):

CHAPTER 9

\$ time awk

... doctype without egrep ...

ch9.* cat ch9.1 ch9.2 ch9.3 ch9.4 : pic: tbl : eqn

troff -ms

real 31.0 user 8.9 sys 2.8 \$ time doctype ch9.* cat ch9.1 ch9.2 ch9.3 ch9.4

pic

tbl

eqn

troff -ms

real user sys \$

7.0 1 . 0 2.3

The comparison is evidently in favor of the version using three processes. (This was done on a machine with only one user; the ratio of real times would favor the egrep version even more on a heavily loaded system.) Notice that we did get a simple working version first, before we started to optimize. Exercise 9-2. How did we format this chapter? 0 Exercise 9-3. If your eqn delimiter is a dollar sign, how do you get a dollar sign in the output? Hint: investigate quotes and the pre-defined words of eqn. 0 Exercise 9-4. Why doesn't

\$ 'doctype filenames'

work? Modify doctype to run the resulting command, instead of printing it. 0 Exercise 9-5. Is the overhead of the extra cat in doc type important? Rewrite doctype to avoid the extra process. Which version is simpler? 0 Exercise 9-6. Is it better to use doctype or to write a shell file containing the commands to format a specific document? 0 Exercise 9-7. Experiment with various combinations of grep, egrep, fgrep, sed, awk and sort to create the fastest possible version of doctype. 0

9.4 The manual page The main documentation for a command is usually the manual page - a one-page description in the UNIX Programmer's Manual. (See Figure 9.2.) The manual page is stored in a standard directory, usually /usr /man, in a sub- directory numbered according to the section of the manual. Our hoc manual page, for example, because it describes a user command, is kept in /usr/man/man1/hocc1. Manual pages are printed with the man(1) command, a shell file that runs nroff -man, so man hoc prints the hoc manual. If the same name appears in more than one section, as does

man itself (Section 1 describes the command, while Section 7 describes the macros), the section can be specified to man:

CHAPTER 9

DOCUMENT PREPARATION 309

```
$ man 7 man
```

prints only the description of the macros. The default action is to print all pages with the specified name, using nroff, but man -t generates typeset pages using troff. The author of a manual page creates a file in the proper subdirectory of /usr /man. The man command calls nroff or troff with a macro package to print the page, as we can see by searching the man command for formatter invocations. Our result would be

```
$ grep roff 'which man' nroff $opt -man $all ;; neqn $all : nroff $opt -man ;;  
troff $opt -man $all ;; troff -t $opt -man $all : tc ;; eqn $all : troff $opt -man  
;; eqn $all : troff -t $opt -man: tc "
```

```
$
```

The variety is to deal with options: nroff vs. troff, whether or not to run eqn, etc. The manual macros, invoked by troff -man, define troff commands that format in the style of the manual. They are basically the same as the ms

macros, but there are differences, particularly in setting up the title and in the font change commands. The macros are documented - briefly - in `man(7)`, but the basics are easy to remember. The layout of a manual page is: `. TH COMMAND section-number .SH NAME command \ - brief description of function .SH SYNOPSIS . B command options .SH DESCRIPTION` Detailed explanation of programs and options. Paragraphs are introduced by `. PP`. `.PP` This is a new paragraph. `.SH FILES` Files used by the command, e.g., `passwd(1)` mentions `/etc/passwd`. `.SH "SEE ALSO"` References to related documents, including other manual pages. `.SH DIAGNOSTICS` Description of any unusual output (e.g., see `cmp(1)`). `.SH BUGS` Surprising features (not always bugs; see below)

If any section is empty, its header is omitted. The `. TH` line and the `NAME`, `SYNOPSIS` and `DESCRIPTION` sections are mandatory. The line

310 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

o `TH COMMAND section-number`

names the command and specifies the section number. The various `.. SH` lines identify sections of the manual page. The `NAME` and `SYNOPSIS` sections are special; the others contain ordinary prose. The `NAME` section names the command (this time in lower case) and provides a one-line description of it. The `SYNOPSIS` section names the options, but doesn't describe them. As in any section, the input is free form, so font changes can be specified with the `.. B`, `.. I` and `"R` macros. In the `SYNOPSIS` section,

the name and options are bold, and the rest of the information is roman. The ed(1) NAME and SYNOPSIS sections, for example, are: **..SH NAME ed** \- text editor **..SH SYNOPSIS** **..B ed [..B \-] [..B \-x] [name]** These come out as:

NAME ed - text editor **SYNOPSIS** ed [-] r -x] [name] Note the use of \. - rather than a plain -. The DESCRIPTION section describes the command and its options. In most cases, it is a description of the command, not the language the command defines. The cc(1) manual page doesn't define the C language; it says how to run the cc command to compile C programs, how to invoke the optimizer, where the output is left, and so on. The language is specified in the C reference manual, cited in the SEE ALSO section of cc(1). On the other hand, the categories are not absolute: man(7) is a description of the language of manual macros. By convention, in the DESCRIPTION section, command names and the tags for options (such as "name" in the ed page) are printed in italics. The macros **.. I** (print first argument in italics) and **"IR** (print first argument in italic, second in roman) make this easy. The **.. IR** macro is there because the **.. I** macro in the man package doesn't share with that in ms the undocumented but convenient treatment of the second argument. The FILES section mentions any files implicitly used by the command. DIAGNOSTICS need only be included if there is unusual output produced by the command. This may be diagnostic messages, exit statuses or surprising

CHAPTER 9

DOCUMENT PREPARATION

.TH HOC 1 .SH NAME hoc

- interactive floating point language .SH SYNOPSIS .B hoc [file ...] .SH DESCRIPTION .I Hoc interprets a simple language for floating point arithmetic, at about the level of BASIC, with C-like syntax and functions and procedures with arguments and recursion. .PP The named .IR file s are read and interpreted in order. If no .I file is given or if .1 file is '

- ' .I hoc interprets the standard input. .PP oI Hoc input consists of .1 expressions and .IR statements. Expressions are evaluated and their results printed. Statements, typically assignments and function or procedure definitions, produce no output unless they explicitly call .IR print. .SH "SEE ALSO" .I Hoc

- An Interactive Language for Floating Point Arithmetic by Brian Kernighan and Rob Pike. .br .IR bas (1), .IR bc (1) and .IR dc (1). .SH BUGS Error recovery is imperfect within function and procedure definitions. .br The treatment of newlines is not exactly user-friendly.

Figure 9.1: /usr/man/man1/hoc.1

variations of the command's normal behavior. The BUGS section is also some- what misnamed. Defects reported here aren't so much bugs as shortcomings - simple bugs should be fixed before the command is installed. To get a feel- lng for what goes in the DIAGNOSTICS and BUGS sections, you might browse :hrough the standard manual.

CHAPTER 9

An example should clarify how to write the manual page. The source for `hoc(1)`, `/usr/man/man1/hoc..1`, is shown in Figure 9.1, and Figure 9.2 is the output of

```
$ man -t hoc
```

Exercise 9-8. Write a manual page for `doctype`. Write a version of the `man` command that looks in your own man directory for documentation on your personal programs. 0

HOC(I)

HOC(l)

NAME hoc - interactive floating point language SYNOPSIS hoc [file ...]

DESCRIPTION Hoc interprets a simple language for floating point arithmetic, at about the level of BASIC, with C-like syntax and functions and procedures with arguments and recursion. The named files are read and interpreted in order. If no file is given or if file is '-' hoc interprets the standard input. Hoc input consists of expressions and statements.

Expressions are evaluated and their results printed. Statements, typically assignments and function or procedure definitions, produce no output unless they explicitly call `print`. SEE ALSO Hoc - An Interactive Language for Floating Point Arithmetic by Brian Kernighan and Rob Pike. `bas (1)`, `be (1)` and `de (1)`. BUGS Error recovery is imperfect within function and

procedure definitions. The treatment of newlines is not exactly user-friendly.

8th Edition

1

Figure 9.2: hoc(1)

CHAPTER 9

DOCUMENT PREPARATION 313

9.5 Other document preparation tools There are several other programs to help with document preparation. The `refer(1)` command looks up references by keywords and installs in your document the in-line citations and a reference section at the end. By defining suitable macros, you can arrange that `refer` print references in the particular style you want. There are existing definitions for a variety of computer science journals. `refer` is part of the 7th Edition, but has not been picked up in some other versions. `pic(1)` and `ideal(1)` do for pictures what `eqn` does for equations. Pictures are significantly more intricate than equations (at least to typeset), and there is no oral tradition of how to talk about pictures, so both languages take some work to learn and to use. To give the flavor of `pic`, here is a simple picture and its expression in `pic`. `ePS ops -1 box invis "document"; arrow box dashed "pic"; arrow box dashed "tbl"; arrow box dashed "eqn"; arrow box`

"troff"; arrow box invis "typesetter" [box invis "macro" "package" spline
right then up ->] with one at 2nd last boxes ops +1 "PE

document

r-----, I I

pIC : I I '-_____.J

r-----, I I

tbl : I I '-_____.J

r-----, I I

eqn : I I '-_____.J

troff

typesetter

macro package

The pictures in this book were all done with pic. pic and ideal are not part of the 7th Edition but are now available. refer, pic and ideal are all troff preprocessors. There are also programs to examine and comment on the prose in your documents. The best known of these is spe11(1), which reports on possible spelling errors in files; we used it extensively. style(1) and diction(1) analyze punctuation, grammar and language usage. These in turn developed into the Writer's Workbench, a set of programs to help improve writing style. The Writer's Workbench programs are good at identifying clichés, unnecessary words and sexist phrases. spell is standard. The others may be on your system; you can easily find out by using man:

314 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 9

`$ man style diction wwbench`

or by listing /bin and /usr/bin.

History and bibliographic notes troff, written by the late Joe Ossanna for the Graphics Systems CAT-4 typesetter, has a long lineage, going back to RUNOFF, which was written by J. E. Saltzer for CTSS at MIT in the early 1960's. These programs share the basic command syntax and ideas, although troff is certainly the most complicated and powerful, and the pre-

sence of eqn and the other preprocessors adds significantly to its utility. There are several newer typesetting programs with more civilized input format; TEX, by Don Knuth (TEX and Metafont: New Directions in Typesetting, Digital Press, 1979), and Scribe, by Brian Reid ("Scribe: a

high-level approach to computer document formatting," 7th Symposium on the Principles of Programming Languages, 1980), are probably the best known. The paper "Document Formatting Systems: Survey, Concepts and Issues" by Richard Furuta, Jeffrey Scofield, and Alan Shaw (Computing Surveys, September, 1982) is a good survey of the field. The original paper on eqn is "A system for typesetting mathematics" (CACM, March 1975), by Brian Kernighan and Lorinda Cherry. The `ros` macro package, `tbl` and `refer` are all by Mike Lesk; they are documented only in the UNIX Programmer's Manual, Volume 2A. `pic` is described in "PIC - a language for typesetting graphics," by Brian Kernighan, Software-Practice and Experience, January, 1982. `ideal` is described in "A high-level language for describing pictures," by Chris Van Wyk, ACM Transactions on Graphics, April, 1982. `spell` is a command that turned from a shell file, written by Steve Johnson, into a C program, by Doug McIlroy. The 7th Edition `spell` uses a hashing mechanism for quick lookup, and rules for automatically stripping suffixes and prefixes to keep the dictionary small. See "Development of a spelling list," M. D. McIlroy, IEEE Transactions on Communications, January, 1982. The style and diction programs are described in "Computer aids for writers," by Lorinda Cherry, SIGPLAN Symposium on Text Manipulation, Portland, Oregon (June 1981).

CHAPTER 10: EIL

The UNIX operating system is well over ten years old, but the number of computers running it is growing faster than ever. For a system designed with no marketing goals or even intentions, it has been singularly successful. The main reason for its commercial success is probably its portability - the feature that everything but small parts of the compilers and kernel runs unchanged on any computer. Manufacturers that run UNIX software on their machines therefore have comparatively little work to do to get the system running on new hardware, and can benefit from the expanding commercial market for UNIX programs. But the UNIX system was popular long before it was of commercial significance, and even before it ran on anything but the PDP-11. The 1974 CACM paper by Ritchie

and Thompson generated interest in the academic community, and by 1975, 6th Edition systems were becoming common in universities. Through the mid-1970's UNIX knowledge spread by word of mouth: although the system came unsupported and without guarantee, the people who used it were enthusiastic enough to convince others to try it too. Once people tried it, they tended to stick with it; another reason for its current success is that the generation of programmers who used academic UNIX systems now expect to find the UNIX environment where they work. Why did it become popular in the first place? The central factor is that it was designed and built by a small number (two) of exceptionally talented people, whose sole purpose was to create an environment that would be convenient for program development, and who had the freedom to pursue that ideal. Free of market pressure, the early systems were small enough to be understood by a single person. John Lions taught the 6th Edition kernel in an undergraduate operating systems course at the University of New South Wales in Australia. In notes prepared for the class, he wrote, "... the whole documentation is not unreasonably transportable in a student's briefcase." (This has been fixed in recent versions.) In that early system were packed a number of inventive applications of computer science, including stream processing (pipes), regular expressions, language theory (yacc, lex, etc.) and more specific instances like the 315

316 THE UNIX PROGRAMMING ENVIRONMENT

CHAPTER 10

algorithm in diff. Binding it all together was a kernel with features seldom found even in larger operating systems." As an example, consider the I/O structure: a hierarchical file system, rare at the time; devices installed as names in the file system, so they require no special utilities; and perhaps a dozen critical system calls, such as an open primitive with exactly two arguments. The software was all written in a high-level

language and distributed with the system so it could be studied and modified. The UNIX system has since become one of the computer market's standard operating systems, and with market dominance has come responsibility and the need for "features" provided by competing systems. As a result, the kernel has grown in size by a factor of 10 in the past decade, although it has certainly not improved by the same amount. This growth has been accompanied by a surfeit of ill-conceived programs that don't build on the existing environment. Creeping featurism encrusts commands with options that obscure the original intention of the programs. Because source code is often not distributed with the system, models of good style are harder come by. Fortunately, however, even the large versions are still suffused with the ideas that made the early versions so popular. The principles on which UNIX is based - simplicity of structure, the lack of disproportionate means, building on existing programs rather than recreating, programmability of the command interpreter, a tree-structured file system, and so on - are therefore spreading and displacing the ideas in the monolithic systems that preceded it. The UNIX system can't last forever, but systems that hope to supersede it will have to incorporate many of its fundamental ideas. We said in the preface that there is a UNIX approach or philosophy, a style of how to approach a programming task. Looking back over the book, you should be able to see the elements of that style illustrated in our examples. First, let the machine do the work. Use programs like `grep` and `awk` to mechanize tasks that you might do by hand on other systems. Second, let other people do the work. Use programs that already exist as building blocks in your programs, with the shell and the programmable filters to glue them together. Write a small program to interface to an existing one that does the real work, as we did with `idiff`. The UNIX environment is rich in tools that can be combined in myriad ways; your job is often just to think of the right combination. Third, do the job in stages. Build the simplest thing that will be useful, and let your experience with that determine what (if anything) is worth doing next. Don't add features and options until usage patterns tell you which ones are needed. Fourth, build tools. Write programs that mesh with the existing environment, enhancing it rather than merely adding to it. Built well, such programs themselves become a part of everyone's toolkit. We also said in the preface that the system was not perfect. After nine chapters describing programs with strange conventions, pointless differences,

eCHAPTER 10

EPILOG 317

and arbitrary limitations, you will surely agree. In spite of such blemishes, however, the positive benefits far outweigh the occasional irritating rough edges. The UNIX system is really good at what it was designed to do: providing a comfortable programming environment. So although UNIX has begun to show some signs of middle age, it's still viable and still gaining in popularity. And that popularity can be traced to the clear thinking of a few people in 1969, who sketched on the blackboard a design for a programming environment they would find comfortable. Although they didn't expect their system to spread to tens of thousands of computers, a generation of programmers is glad that it did.

APPENDIX 1: E IT

SUMMA Y

The "standard" UNIX text editor is a program called `ed`, originally written by Ken Thompson. `ed` was designed in the early 1970's, for a computing environment on tiny machines (the first UNIX system limited user programs to 8K bytes) with hard-copy terminals running at very low speeds (10-15 characters per second). It was derived from an earlier editor called `qed` that was popular at the time. As technology has advanced, `ed` has remained much the same. You are almost certain to find on your system other editors with appealing features; of these, "visual" or "screen" editing,

in which the screen of your terminal reflects your editing changes as you make them, is probably the most common. So why are we spending time on such a old-fashioned program? The answer is that `ed`, in spite of its age, does some things really well. It is available on all UNIX systems; you can be sure that it will be around as you move from one system to another. It works well over slow-speed telephone lines and with any kind of terminal. `ed` is also easy to run from a script; most screen editors assume that they are driving a terminal, and can't conveniently take their input from a file. `ed` provides regular expressions for pattern matching. Regular expressions based on those in `ed` permeate the system: `grep` and `sed` use almost identical ones; `egrep`, `awk` and `lex` extend them; the shell uses a different syntax but the same ideas for filename matching. Some screen editors have a "line mode" that reverts to a version of `ed` so that you can use regular expressions. Finally, `ed` runs fast. It's quite possible to invoke `ed`, make a one-line change to a file, write out the new version, and quit, all before a bigger and fancier screen editor has even started.

Basics `ed` edits one file at a time. It works on a copy of the file; to record your changes in the original file, you have to give an explicit command. `ed` provides commands to manipulate consecutive lines or lines that match a pattern, and to make changes within lines. Each `ed` command is a single character, usually a letter. Most commands

can be preceded by one or two line numbers, which indicate what line or lines are to be affected by the command; a default line number is used otherwise. Line numbers can be specified by absolute position in the file (1, 2, ...), by shorthand like \$ for the last line and '.' for the current line, by pattern searches using regular expressions, and by additive combinations of these. Let us review how to create files with ed, using De Morgan's poem from Chapter 1.

```
$ ed poem ?poem Warning: the file poem doesn't exist a Start adding lines
Great fleas have little fleas upon their backs to bite 'em, And little fleas
have lesser fleas, and so ad infinitum.
```

```
w poem 121 q $
```

```
Type a '.' to stop adding Write lines to file poem ed reports 121 characters
written Quit
```

The command a adds or appends lines; the appending mode is terminated by a line with a 'II' by itself. There is no indication of which mode you are in, so two common mistakes to watch for are typing text without an a command, and typing commands before typing the '..'. ed will never write your text into a file automatically; you have to tell it to do so with the w command. If you try to quit without writing your changes, however, ed prints a ? as a warning. At that point, another q command will let you exit without writing. Q always quits regardless of changes. \$ ed poem 121 File exists, and has 121 characters a Add some more lines at the end And the great fleas themselves, in turn, have greater fleas to go on; While these again have greater still, and greater still, and so on. Type a '.' to stop adding q Try to quit ? Warning: you didn't write first w No filename given; poem is assumed 263 q \$ we poem 8

Now it's OK to quit Check for sure

46

263 poem

\$

APPENDIX 1

EDITOR SUMMARY 321

Escape to the shell with ! If you are running ed, you can escape temporarily to run another shell command; there's no need to quit. The ed command to do this is '! ':

\$ ed poem 263 fwc poem 8

R un we without leaving e d

46

263 poem

q \$

You have returned from the command Quit without w is OK: no change was made

Printing The lines of the file are numbered 1, 2, ...; you can print the n-th line by giving the command np or just the number n, and lines m through n with m, np. The "line number" \$ is the last line, so you don't have to count lines.

1 \$ 1,\$p

Print 1 st line; same as 1 p Print last line; same as \$ p Print lines 1 through last

You can print a file one line at a time just by pressing RETURN; you can back up one line at a time with '-'. Line numbers can be combined with + and -:

`$-2,$p 1,2+3p`

Print last 3 lines Print lines 1 through 5

But you can't print past the end or in reverse order; commands like `$`, `$ + 1` `p` and `$, 1p` are illegal. The list command `l` prints in a format that makes all characters visible; it's good for finding control characters in files, for distinguishing blanks from tabs, and so on. (See `vis` in Chapter 6.)

Patterns Once a file becomes longer than a few lines, it's a bother to have to print it all to find a particular line, so `ed` provides a way to search for lines that match a particular pattern: `/pattern/` finds the next occurrence of `pattern`.

```
$ ed poem 263 /flea/ Great fleas have little /flea/ And little fleas // And ??  
And
```

Search for next line containing `flea fleas` Search for next one have lesser fleas, Search for next using same pattern the great fleas themselves, in turn, Search backwards for same pattern little fleas have lesser fleas,

`ed` remembers the pattern you used last, so you can repeat a search with just

APPENDIX 1

// To search backwards, use ?pattern? and ?? Searches with /... / and ?..?
"wrap around" at either end of the text: \$ p Print last line. ('p' is optional)
and greater still, and so on. /flea/ Next flea is near beginning Great fleas
have little fleas ?? Wrap around beginning going backwards have greater
fleas to go on;

A pattern search like /flea/ is a line number just as 1 or \$ is, and can be used
in the same contexts:

```
1,/flea/p ?flea?+1,$p
```

Print from 1 to next flea Print from previous flea + 1 to end

Where are we anyway? ed keeps track of the last line where you did
something: printing or adding text or reading a file. The name of this line is
'.'; it is pronounced "dot" and is called the current line. Each command has
a defined effect on dot, usually setting it to the last line affected by the
command. You can use dot in the same way that you use \$ or a number like
1: \$ ed poem 263

Print current line; same as \$ after reading and greater still, and so on. . - 1 , .
p Print previous line and this one While these again have greater still, and
greater still, and so on.

Line number expressions can be abbreviated:

Shorthand: Same as: Shorthand: Same as: . -1 + . + 1 or -2 .-2 ++ or +2 .+2
-n .-n +n .+n \$- \$-1 . 3 .+3

Append, change, delete, insert The append command a adds lines after the specified line; the delete command d deletes lines; the insert command i inserts lines before the specified line; the change command c changes lines, a combination of delete and insert.

na ni m,nd m,nc

Add text after line n Insert text before line n Delete lines m through n
Change lines m through n

If no line numbers are given, dot is used. The new text for a, c and i

APPENDIX 1

EDITOR SUMMARY 323

commands is terminated by a '.' on a line by itself; dot is left at the last line added. Dot is set to the next line after the last deleted line, except that it doesn't go past line \$.

Oa dp .. , \$dp 1,\$d ? pat? , .. - 1 d \$dp \$c 1,\$c

Add text at beginning (same as 1 i) Delete current line, print next (or last, if at \$) Delete from here to end, print new last Delete everything Delete from previous 'pat' to just before dot Delete last line, print new last line Change last line. (\$a adds after last line) Change all lines

Substitution,. undo It's a pain to have to re-type a whole line to change a few letters in it. The substitute command s is the way to replace one string of letters by another:

s/old/new/ s/old/new/p s/old/new/g s/old/new/gp

Change first old into new on current line Change first old into new and print line Change each old into new on current line Change each old into new and print line

Only the leftmost occurrence of the pattern in the line is replaced, unless a 'g' follows. The s command doesn't print the changed line unless there is a 'p' at the end. In fact, most ed commands do their job silently, but almost any command can be followed by p to print the result. If a substitution didn't do what you wanted, the undo command u will undo the most recent substitution. Dot must be set to the substituted line.

u up

Undo most recent substitution Undo most recent substitution and print

Just as the p and d commands can be preceded by one or two line numbers to indicate which lines are affected, so can the s command:

1,\$s/old/new/p

Find next old; change to new Find next old; change to new (pattern is remembered) Change first old to new on each line; print last line changed Change each old to nL.W on each line; print last line changed

/old/s/old/new/ /old/s//new/

1,\$s/old/new/gp

Note that 1, \$s applies the s command to each line, but it still means only the leftmost match on each line; the trailing 'g' is needed to replace all occurrences in each line. Furthermore, the p prints only the last affected line; to print all changed lines requires a global command, which we'll get to shortly. The character & is shorthand; if it appears anywhere on

he right side of an s command, it is replaced by whatever was matched on the left side:

324 THE UNIX PROGRAMMING ENVIRONMENT

APPENDIX 1

s/big/very &1 s/big/& &1 s/o*/(&)1 s/and/^\&1

Replace big by very big Replace big by big big Parenthesize entire line (see 0 * below) Replace and by & (\ turns off special meaning)

Metacharacters and regular expressions In the same way that characters like * and > and : have special meaning to the shell, certain characters have special meaning to ed when they appear in a search pattern or in the left-hand part of an s command. Such characters are called metacharacters, and the patterns that use them are called regular expressions. Table 1 lists the characters and their meanings; the examples below should be read in conjunction with the table. The special meaning of any character can be turned off by preceding it with a backslash.

[...] [A...]

Table 1: Editor Regular Expressions any non-special character c matches itself turn off any special meaning of character c matches beginning of line

when A begins pattern matches end of line when \$ ends pattern matches any single character matches anyone of characters in ...; ranges like a - z are legal matches any single character not in ...; ranges are legal matches zero or more occurrences of r, where r is a character, . or [...] on right side of s only, produces what was matched tagged regular expression; the matched string is available as \ 1, etc., on both left and right side No regular expression matches a newline.

c \c

A

\$

r*

& \(...\)

Pattern: IA\$I 1..1 IAI Ithingl IAt thingl Ithing\$1 IAt thing\$1 Ithing..\$1 /thing\..\$1 1\thing\11 l[tT]hingl Ithing[O-9]1

Matches: empty line, i. e ., newline only non-empty, i. e ., at least one character all lines thing anywhere on line thing at beginning of line thi ng at end of line line that contains only thing thing plus any character at end of

line thing.. at end of line Ithingl anywhere on line thing or Thing anywhere
on line thing followed by one digit

APPENDIX 1

EDITOR SUMMARY 325

Ithing["Q-9]1 Ithing[Q-9]["Q-9]1 Ithing1e*thing21 l"thing1e*thing2\$1

thing followed by a non-digit thing followed by digit, non-digit thing 1 then
any string then thing2 thing 1 at beginning and thing2 at end

Regular expressions involving * choose the leftmost match and make it as
long as possible. Note that x* can match zero characters; xx* matches one
or more.

Global commands The global commands g and v apply one or more other
commands to a set of lines selected by a regular expression. The g
command is most often used for printing, substituting or deleting a set of
lines:

m,nlrelcmd m,nvlrelcmd

For all lines between m and n that match re, do cmd For all lines between m and n that don't match re, do cmd

The g or v commands can be preceded by line numbers to limit the range; the default range is 1, \$.

g/.../p g/.../d g/.../sllrepllp g/.../sl Irepllgp g I... I slpatlrepllp g I... I slpatlrepllp g/.../slpatlrepll v I... I slpatlrepllp gp v/"\$/p g/... Icmdl \cmd2\cmd3

Print all lines matching regular expression ... Delete all lines matching... Replace 1st... on each line by 'repl', print changed lines Replace each ... by 'repl', print changed lines On lines matching ..., replace 1 st 'pat' by 'repl' On lines matching ..., replace 1 st 'pat' by 'repl' and print On lines matching ..., replace all 'pat' by 'repl' and print On lines not matching ..., replace all 'pat' by 'repl', print Print all non-blank lines To do multiple commands with a single g, append \ to each cmd but the last

The commands controlled by a g or v command can also use line numbers. Dot is set in turn to each line selected.

g Ithing I . , . + 1 P Print each line with thing and next g/"\ e EQI .1 ,1"\ e ENI -s/alpha/beta/gp Change alpha to beta only between e EQ and . EN, and print changed lines

Moving and copying lines The command m moves a contiguous group of lines; the t command makes a copy of a group of lines somewhere else.

m,nm d m,n t d

Move lines m through n to after line d Copy lines m through n to after line d

If no source lines are specified, dot is used. The destination line d cannot be in the range m, n - 1. Here are some common idioms using m and t:

326 THE UNIX PROGRAMMING ENVIRONMENT

APPENDIX 1

-, .. t..

Move current line to after next one (interchange) Move current line to before previous one Same: -- is the same as -2 Does nothing Move current line to end (roO moves to beginning) Duplicate current line (t\$ duplicates at end) Duplicate previous and current lines Duplicate entire set of lines Reverse order of lines

m+ m-2

m-- m- m\$ t..

1,\$t\$ g"/roO

Marks and line numbers The command = prints the line number of line \$ (a poor default), .. = prints the number of the current line, and so on. Dot is unchanged. The command kc marks the addressed line with the lower case letter c; the line can subsequently be addressed as ' c. The k command does not change dot. Marks are convenient for moving large chunks of text, since they remain permanently attached to lines, as in this sequence:

, a , , bro ..

Find line... and mark with a Find line ... and mark with b Print entire range to be sure Find target line Move selected lines after it

I. ../ka I. ../kb , a , , bp 1...1

Joining, splitting and rearranging lines Lines can be joined with the j command (no blanks are added):

m,nj

Join lines m through n into one line

The default range is " , .. + 1, so jp - , .. jp

Join current line to next and print Join previous line to current and print

Lines can be split with the substitute command by quoting a newline:

```
s/part1part2/part1\ part21 sl 1\ Ig
```

Split line into two parts

Split at each blank; makes one word per line

Dot is left at the last line created. To talk about parts of the matched regular expression, not just the whole thing, use tagged regular expressions: if the construction `\ (... \)` appears in a regular expression, the part of the whole that it matches is available on both the right hand side and the left as `\ 1`. There can be up to nine tagged expressions, referred to as `\1`, `\2`, etc.

APPENDIX 1

EDITOR SUMMARY 327

`s/^(...)\(.*\)^2\1/ ^(..*\)\1/`

Move first 3 characters to end Find lines that contain a repeated adjacent string

File handling commands The read and write commands `r` and `w` can be preceded by line numbers:

`n r file m,nw file m,nW file`

Read file; add it after line `n`; set dot to last line read Write lines `m-n` to file; dot is unchanged Append lines `m-n` to file; dot is unchanged

The default range for `w` and `W` is the whole file. The default `n` for `r` is `$`, an unfortunate choice. Beware. `ed` remembers the first file name used, either from the command line or from an `r` or `w` command. The file command `f` prints or changes the name of the remembered file:

`f f file`

Print name of remembered file Set remembered name to 'file'

The edit command `e` reinitializes `ed` with the remembered file or with a new one:

`e e file`

Begin editing remembered file Begin editing 'file'

The `e` command is protected the same way as `q` is: if you haven't written your changes, the first `e` will draw an error message. `E` reinitializes regardless of changes. On some systems, `ed` is linked to `e` so that the same command (`e filename`) can be used inside and outside the editor.

Encryption Files may be encrypted upon writing and decrypted upon reading by giving the `x` command; a password will be asked for. The encryption is the same as in `crypt(1)`. The `x` command has been changed to `X` (upper case) on some systems, to make it harder to encrypt unintentionally.

Summary of commands Table 2 is a summary of `ed` commands, and Table 3 lists the valid line numbers. Each command is preceded by zero, one or two line numbers that indicate how many line numbers can be provided, and the default values if they are not. Most commands can be followed by a `p` to print the last line affected, or `1` for list format. Dot is normally set to the last line affected; it is unchanged by `f`, `k`, `w`, `x`, `=`, and `!`. Exercise. When you think you know `ed`, try the editor quiz; see `quiz(6)`. 0

328 THE UNIX PROGRAMMING ENVIRONMENT

APPENDIX 1

.a

., "C

., . d

e file f file 1 , \$g Irel cmds

.].

.,.+1j . kc

., . 1 . , . m line

., . p

q \$ r file . , . slrelnewl .. , . t line

..U

1 , \$v/relcmds 1 , \$w file x \$= ! cmdline (. + 1) newline

Table 2: Summary of ed Commands
add text until a line containing just . is typed
change lines; new text terminated as with a delete
lines reinitialize with file. E resets even if changes not written
set remembered file to file do ed cmds on each line matching regular expression re;
multiple cmds separated by \newline
insert text before line, terminated as with a join
lines into one mark line with letter c
list lines, making invisible characters visible
move lines to after line
print lines quit. Q quits even if changes not written
read file substitute new for whatever matched re
copy lines after line undo last substitution on line (only one)
do ed cmds on each line not matching re
write lines to file; w appends instead of overwriting
enter encryption mode (or ed -x filename)
print line number execute UNIX command cmdline
print line

n

\$ Ire I ?re?

'c

NI + n NI,N2 NI ;N2

Table 3: Summary of ed Line Numbers absolute line number n, n = 0, 1, 2, ... current line last line of text next line matching re; wraps around from \$ to 1 previous line matching re; wraps around from 1 to \$ line with mark c line NI + n (additive combination) lines N 1 through N2 set dot to N 1, then evaluate N2 NI and N2 may be specified with any of the above

APPENDIX 2: HOC MANUAL

Hoc - An Interactive Language For Floating Point Arithmetic

Brian Kernighan Rob Pike

ABSTRACT

Hoc is a simple programmable interpreter for floating point expressions. It has C-style control flow, function definition and the usual numerical built-in functions such as cosine and logarithm.

1. Expressions Hoc is an expression language, much like C: although there are several control-flow statements, most statements such as assignments are expressions whose value is disregarded. For example, the assignment operator = assigns the value of its right operand to its left operand, and

yields the value, so multiple assignments work. The expression grammar IS:

number variable (expr) expr binop expr unop expr function (arguments)
Numbers are floating point. The input format is that recognized by scanf (3): digits, decimal point, digits, e or E, signed exponent. At least one digit or a decimal point must be present; the other components are optional. Variable names are formed from a letter followed by a string of letters and numbers. binop refers to binary operators such as addition or logical comparison; unop refers to the two negation operators, '!' (logical negation, 'not') and '-' (arithmetic negation, sign change). Table 1 lists the operators.

expr:

329

330 THE UNIX PROGRAMMING ENVIRONMENT

APPENDIX 2

Table 1: Operators, in decreasing order of precedence

A

* / +

> >=

< <=

-- 1= &&

I I I I

=

exponentiation (FORTRAN **), right associative (unary) logical and arithmetic negation multiplication, division addition, subtraction relational operators: greater, greater or equal, less, less or equal, equal, not equal (all same precedence) logical AND (both operands always evaluated) logical OR (both operands always evaluated) assignment, right associative

Functions, as described later, may be defined by the user. Function arguments are expressions separated by commas. There are also a number of built-in functions, all of which take a single argument, described in Table 2.

abs(x) atan(x) cos(x) exp(x) int(x) log (x) log10(x) sin (x) sqrt(x)

Table 2: Built-in Functions
Ix I, absolute value of x
arc tangent of x
cos(x), cosine of x
eX , exponential of x
integer part of x , truncated towards zero
log(x), logarithm base e of x
logIQ(x), logarithm base 10 of x
sin(x), sine of x

,x%

Logical expressions have value 1.0 (true) and 0.0 (false). As in C, any non-zero value is taken to be true. As is always the case with floating point numbers, equality comparisons are inherently suspect. Hoc also has a few built-in constants, shown in Table 3.

Table 3: Built-in Constants

DEG E GAMMA PHI PI

57.29577951308232087680 2.71828182845904523536
0.57721566490153286060 1.61803398874989484820
3.14159265358979323846

180/71', degrees per radian
e, base of natural logarithms
'Y, Euler-Mascheroni constant
CVS + 1)/2, the golden ratio
71', circular transcendental number

2. Statements and Control Flow Hoc statements have the following grammar:

APPENDIX 2

HOC MANUAL

331

stmt:

expr variable = expr procedure (arglist) while (expr) stmt if (expr) stmt
if (expr) stmt else stmt { stmtlist } print expr-list return optional-expr

stmtlist:

(nothing) stmtlist stmt

An assignment is parsed by default as a statement rather than an expression, so assignments typed interactively do not print their value. Note that semicolons are not special to hoc: statements are terminated by newlines. This causes some peculiar behavior. The following are legal if statements: if (x < 0) print(y) else print(z)

```

if (x < 0) { print(y) } else { print(z)

}

```

In the second example, the braces are mandatory: the newline after the if would terminate the statement and produce a syntax error were the brace omitted. The syntax and semantics of hoc control flow facilities are basically the same as in C. The while and if statements are just as in C, except there are no break or continue statements.

3. Input and Output: read and print The input function read, like the other built-ins, takes a single argument. Unlike the built-ins, though, the argument is not an expression: it is the name of a variable. The next number (as defined above) is read from the standard input and assigned to the named variable. The return value of read is 1 (true) if a value was read, and 0 (false) if read encountered end of file or an error. Output is ge

erated with the print statement. The arguments to print are a comma-separated list of expressions and strings in double quotes, as in C. Newlines must be supplied; they are never provided automatically by print. Note that read is a special built-in function, and therefore takes a single parenthesized argument, while print is a statement that takes a comma-separated, unparenthesized list: while (read(x» { print "value is" x, "\n"

```

}

```

THE UNIX PROGRAMMING ENVIRONMENT

APPENDIX 2

4. Functions and Procedures Functions and procedures are distinct in hoc, although they are defined by the same mechanism. This distinction is simply for run-time error checking: it is an error for a procedure to return a value, and for a function not to return one. The definition syntax is:

Junction:

June name() stmt

procedure:

proc name() stmt

name may be the name of any variable - built-in functions are excluded. The definition, up to the opening brace or statement, must be on one line, as with the if statements above. Unlike C, the body of a function or procedure may be any statement, not necessarily a compound (brace-enclosed) statement. Since semicolons have no meaning in hoc, a null procedure body is formed by an empty pair of braces. Functions and

procedures may take arguments, separated by commas, when invoked. Arguments are referred to as in the shell: \$3 refers to the third (I-indexed) argument. They are passed by value and within functions are semantically equivalent to variables. It is an error to refer to an argument numbered greater than the number of arguments passed to the routine. The error checking is done dynamically, however, so a routine may have variable numbers of arguments if initial arguments affect the number of arguments to be referenced (as in C's printf). Functions and procedures may recurse, but the stack has limited depth (about a hundred calls). The following shows a hoc definition of Ackermann's function: \$ hoc func ack() { if (\$1 == 0) return \$2+1 if (\$2 == 0) return ack(\$1-1, 1) return ack(\$1-1, ack(\$1, \$2-1))

} ack(3, 2) 29 ack (3, 3) 61 a ck (3, 4) hoc: stack too deep near line 8

APPENDIX 2

HOC MANUAL 333

5. Examples Stirling's formula:

$n!$

$Y2n1T (n/e)n(1+-L) 12n$

\$ hoc func stirl() (return sqrt(2*\$1*PI) * (\$1/E)

```
$1*(1 + 1/(12*$1))
```

```
} stirl (10) 3628684.7 stirl(20) 2.4328818e+18
```

Factorial function, n !:

```
func fac() if ($1 <= 0) return 1 else return $1 * fac($1-1) Ratio of factorial  
to Stirling approximation: i = 9 while ((i = i+1) <= print i, "
```

```
20) ( ", fac(i)/stirl(i),
```

```
" \n "
```

```
} 10 1.0000318 11 1.0000265 12 1.0000224 13 1.0000192 14 1.0000166 15  
1.0000146 16 1.0000128 17 1.0000114 18 1.0000102 19 1.0000092 20  
1.0000083
```

APPENDIX 3:

The following IS a listing of hoc6 In its entirety.

hoc.y

H

C LISTING


```
%{ #include "hoc.h" #define code2(c1,c2) #define code3(c1,c2,c3) %}  
%union
```

```
} %token %token %token %type %type %t:type %type %r1ght %left %left  
%left %left %left %left %r1ght %% l1st:
```

asgn:

```
{ Symbol Inst 1nt
```

<sym> <sym> <narg> <1nst> <1nst> <sym> <narg>

, ='

code(c1); code(c2) code(c1); code(c2); code(c3)

*sym; *1nst; narg;

1* symbol table p01nter *1 1* mach1ne 1nstruct1on *1 1* number of
arguments *1

NUMBER STRING PRINT VAR BLTIN UNDEF WHILE IF ELSE
FUNCTION PROCEDURE RETURN FUNC PROC READ ARG expr
stmt asgn pr11st stmt11st cond while 1f beg1n end procname arg11st

OR AND GT GE LT LE EQ NE

'+' '-' '*' 'I'

UNARYMINUS NOT

```
1* nothing *1 l1st '\n' l1st defn '\n' l1st asgn '\n' l1st stmt '\n' l1st expr '\n'
l1st error '\n'
```

```
code2(pop, STOP); return 1; } code(STOP); return 1; } code2(print,
STOP); return 1; yerror; }
```

```
VAR '=' expr { code3(varpush, (Inst)$1,asgn); $$=$3; ARG '=' expr {
defnonly("$"); code2(argasgn,(Inst)$1); $$=$3;}
```

335

336

THE UNIX PROGRAMMING ENVIRONMENT

APPENDIX 3

stmt:

cond:

while:

1f:

beg1n:

end:

```
expr {code{pop); } RETURN { defnonly{"return"); code{procret); }  
RETURN expr { defnonly{"return"); $$=$2; code{funcrct); PROCEDURE  
beg1n '(' arg11st ')' { $$ = $2; code3{call, {Inst)$1, (Inst)$4); PRINT pr11st  
{ $$ = $2; } wh1le cond stmt end { ($1)[1] = {Inst)$3; /* body of loop */  
{ $1)[2] = {Inst)$4; } /* end, 1f cond fa1ls */ 1f cond stmt end { /* else-less  
1f */ ($1)[1] = {Inst)$3; /* thenpart */ ($1)[3] = {Inst)$4; } /* end, 1f cond  
fa1ls */ 1f cond stmt end ELSE stmt end { /* 1f with else */ ($1)[1]  
{Inst)$3; /* thenpart */ { $1)[2] = (Inst)$6; /* elsepart */ { $1)[3] =  
(Inst)$7; } /* end, 1f cond fa1ls */ '{' stmt11st '}' { $$ = $2; }
```

```
, ( , expr ' ) , WHILE $$ IF $$ /* noth1ng */ /* noth1ng */
```

```
{ code(STOP); $$ = $2;
```

```
code3{wh1lecode,STOP,STOP);
```

code(1fcode); code3(STOP,STOP,STOP);

\$\$ = progp;

code(STOP); \$\$

progp; }

stmt11st: /* nothing */ : stmt11st '\n' : stmt11st stmt

expr:

pr11st:

defn:

\$\$ = progp;

NUMBER VAR ARG

```

$$ = code2(constpush, (Inst)$1); } $$ = code3(varpush, (Inst)$1, eval); }
defnonly("$"); $$ = code2(arg, (Inst)$1);

```

```

asgn FUNCTION beg1n '(' arg11st ')' { $$ = $2; code3(call,(Inst)$1,
(Inst)$4); } READ '(' VAR ')' { $$

```

```

code2(varread, (Inst)$3); } BLTIN '(' expr ')' { $$=$3; code2(blt1n,
(Inst)$1->u.ptr); '(' expr ')' { $$ = $2; } expr '+' expr { code(add); expr ' ,
expr { code(sub); expr '*' expr { code(mul); expr '/' expr { code(d1v); } expr
expr { code (power); '-' expr %prec UNARYMINUS $$=$2; code(negate);
} expr GT expr {code(gt); } expr GE expr {code(ge); } expr LT expr
{code(lt); } expr LE expr {code(le);} expr EQ expr {code(eq); } expr NE
expr {code(ne); } expr AND expr { code(and); } expr OR expr {code(or); }
NOT expr { $$ = $2; code(not);

```

```

expr STRING pr11st pr11st

```

```

code(preexpr)j } $$ = code2(prstr, (Inst)$1); code(preexpr); } code2(prstr,
(Inst)$3);

```

```

, , , , ,

```

```

expr STRING

```

```

FUNC procname { $2->type=FUNCTION; 1ndef=1; } '(' ')' stmt {
code(procret); def1ne{$2); 1ndef=0; PROC procname { $2-

```

```
>type=PROCEDURE; 1ndef=1; } '(' ')' stmt { code(procret); define{$2);  
1ndef=0;
```

```
procname: VAR \ FUNCTION \ PROCEDURE
```

```
arg11st: /* noth1ng */ expr arg11st ',' expr
```

```
%%
```

```
$$ $$ $$
```

```
0; 1 ; $1 + 1; }
```

APPENDIX 3

HOC LISTING

337

```
/* end of grammar #
```

```
nclude <std
```

```
o.h> #
```

```
nclude <ctype.h> char *progrname;
```

```
nt l
```

```
nenno = 1; #
```

```
nclude <s
```

```
gnal.h> #
```

```
nclude <setjmp.h> jmp_buf beg
```

```
n;
```

```
nt
```

```
ndef; char *
```

```
nf
```

```
le; FILE *f
```

```
n; char **gargv;
```

```
nt gargc;
```

```
*/
```

```
/*
```

```
nput f
```

```
le name */ /*
```


input f

le po

nter */ /* global argument list */

nt c; yylex () {

/* global for use by warn

ng() */ /* hoc6 */

wh

le «c=getc(f

n»

:: c == '\t')

if (c == EOF) return 0;

f (c == '.' ::

sdig

t(c» /* number */ double d; ungetc(c, f

n); fscanf(f

```

n, "%If", &d); yylval.sym =
ninstall("", NUMBER, d); return NUMBER;

}

f (
s alpha ( c » { Symbol *S; char sbuf[100], *p = sbuf; do {

f (p >= sbuf + s
feof(sbuf) - 1) { *p = '\0' ; execerror("name too long", sbuf);

*P++ c; } wh
le «c=getc(f
n» 1= EOF &&
salnum(c»); ungetc(c, f
n); *p = '\0' ;
f «s=lookup(sbuf» == 0) s =
ninstall(sbuf, UNDEF, 0.0); yylval.sym = s; return s->type == UNDEF ? VAR
: s->type;

} if (c == '$') { /* argument? */
nt n = 0; wh

```

```

le (
sd

g
t(c=getc(f
n») n = 10 * n + c - '0'; ungetc(c, f
n);

f (n == 0) execerror("strange $. ..", (char *)0); yylval.narg = n; return ARG;

}

f (c == '"') { /* quoted str
ng */ char sbuf[100], *P, *emalloc(); for (p = sbuf; (c=getc(f
n») 1= '"'; p++) {
f (c == '\n' :: c == EOF) execerror("m
ss
ng quote", "");
f (p >= sbuf + s
zeof(sbuf) - 1) { *p = '\0' ; execerror("str
ng too long", sbuf);

*p backslash(c);

```

```
*p = 0; yylval.sym = (Symbol *)emalloc(strlen(sbuf)+1);
strcpy(yylval.sym, sbuf); return STRING;
```

```
} switch (c) case '>' : return follow( , '=', GE, GT) ; case I <' : return
follow('=', LE, LT) ; case '=' : return follow( , '=', EQ, '='); case '1' : return
follow( , '=', NE, NOT) ; case ' , , . return follow(':', OR, , ':' ) ; I . case '&' :
return follow( , '&' , AND, '&'); case '\n' : l
```

```
nenno++; return '\n' ; default: return c; }
```

338

THE UNIX PROGRAMMING ENVIRONMENT

```
backslash(c) 1* get next char w1th \s interpreted *1 1nt c;
```

```
char *index(); 1* 'strchr()' in some systems *1 stat1c char transtab[] =
"b\bf\fn\nr\rt\t"; 1f (c 1= '\\') return c; c = getc (fin) ; 1f (1slower(c) &&
1index(transtab, c» return 1index(transtab, c)[1]; return c;
```

```
follow(expect, 1fyes, 1fno) {
```

```
1* look ahead for >=, etc. *1
```

```
int c = getc(f1n); 1f (c == expect) return if yes; ungetc(c, f1n); return ifno;
```

```
defnonly(s) 1* warn if 1llegal def1n1t1on *1 char *s;
```

```
1f (l1ndef) execerror(s, "used outside def1n1t1on");
```

```
yyerror(s) 1* report comp1le-t1me error *1 char *s;
```

```
warning(s, (char *)0);
```

```
execerror(s, t) 1* recover from run-t1me error *1 char *s, *t;
```

```
warn1ng ( s, t); fseek(f1n, OL, 2); longJmp(beg1n, 0);
```

```
1* flush rest of f1le *1
```

```
fpecatch( ) {
```

```
1* catch float1ng p01nt except10ns *1
```

```
execerror("floating point exception", (char *) 0);
```

```
main(argc, argv) char *argv [ ] ;
```

```
1* hoc6 *1
```

```
int i, fpecatch(); progname = argv[0]; if (argc == 1) { 1* fake an  
argument list *1 static char *std1nonly[] {""};
```

```
gargv gargc } else {
```

```
std1nonly; i . ,
```

```
gargv gargc
```

```
argv+1; argc-1;
```

```
} in1 t ( ) ; while (more1nput(» run ( ) ; return 0;
```

APPENDIX 3

HOC LISTING

339

```
moreinput() {
```

```
    if (gargc-- <= 0) return 0;
```

```
    f (fin && f
```

```
        n 1= std
```

```
        n) fclose(f
```

```
        n);
```

```
        nf
```

```
        le = *gargv++; l
```

```
        neno = 1; if (strcmp(inf
```

```
        le, "-") 0) { f
```

```
        n = std
```

```
        n;
```

```
        nf
```

```
        le = 0; } else
```

```

f «f
n=fopen(
nf
le, "r"» == NULL) { fpr
ntf(stderr, "%s: can't open %s'n" , progname,
nf
le); return more
nput();

} return 1;

run ( ) {

1* execute until EOF *1

set jmp (begin) ; s
gnal(SIGFPE, fpecatch); for (
n
tcode(); yyparse(); initcode(» execute(progbase);

```


warning(s, t) 1* pr

nt warn

ng message *1 char *s, *t;

fpr

ntf(stderr, "%s: %s", progname, s);

f (t) fpr

ntf(stderr, " %s", t);

f (

nf

le) fpr

ntf(stderr, "

n %s",

nf

le); fpr

ntf(stderr, " near l

ne %d'n" , lineno); wh

le (c != 'n' && c != EOF) c = getc(f

n); 1* flush rest of

nput l

ne *1

f (c == 'n') lineno++;

hoc.h

typedef struct Symbol { 1* symbol table entry *1 char *name; short type;
union

double double

nt char

val; (*ptr) () ; (*defn) () ; *str;

1* VAR *1 1* BLTIN *1 1* FUNCTION, PROCEDURE *1 1* STRING
*1

```

} u; struct Symbol *next; 1* to link to another *1 } Symbol; Symbol *
ninstall(), *lookup(); typedef un
on Datum { 1* interpreter stack type *1 double val; Symbol *sym; Datum;

```

340

THE UNIX PROGRAMMING ENVIRONMENT

APPENDIX 3

```
extern extern
```

```
Datum pop ( ) ; eval(), add(), sub()t mul(), d1V(), negate ( }, power();
```

```
typedef 1nt (*Inst}()); #def1ne STOP (Inst) 0
```

```
extern extern extern extern extern extern
```

```
Inst *progp, *progbase, prog[], *code(); ass1gn(), blt1n(), varpush(),
constpush(), pr1nt()t varr
```

```
ad(); prexpr(), prstr(); gt(), lt(), eq(), ge(), le(), ne(), and(), or(), not();
1fcodet}t wh11ecode()t call()t arg()t argass1gn(); funcrct(), procrct();
```

```
*****
```

symbol.c

```
*****
***
```

```
#1nclude "hoc.h" #1nclude "y.tab.h" stat1c Symbol *sym11st = 0; 1*
symbol table: 11nked 11st *1 Symbol *lookup(s) 1* f1nd s 1n symbol table
*1 char *s;
```

```
Symbol *sp; for (sp = sym11st; sp 1= (Symbol *) 0; sp 1f (strcmp(sp-
>name, s) == 0) return sp; return 0; 1* 0 ==> not found *1
```

```
sp->next}
```

```
Symbol *1ninstall(s, t, d} 1* 1ninstall s 1n symbol table *1 char *s; 1nt t;
double d;
```

```

Symbol *sp; char *emalloc(); sp = (Symbol *) emalloc(sizeof(Symbol));
sp->name = emalloc(strlen(s)+1); 1* +1 for '\0' *1 strcpy(sp->name, s); sp-
>type = t; sp->u.val = d; sp->next = sym11st; 1* put at front of 11st *1
sym11st = sp; return sp;

```

```

char *emalloc(n) unsigned n;

```

```

1* check return from malloc *1

```

```

char *P, *malloc(); p = ma 11 oc ( n) ; 1f (p == 0) execerror("out of
memory", (char *) 0); return p;

```

```

*****

```

```

code.c

```

```

*****

```

```

***

```

```

#include "hoc.h" #include "y.tab.h" #include <Std10.h>

```

```

#define NSTACK 256 static Datum stack[NSTACK]; static Datum
*stackp;

```

1* the stack *1 1* next free spot on stack *1

#define Inst Inst Inst Inst 1nt

NPROG 2000 prog [NPROG) ; *prog; *pc; *progbase return1ng;

1* the machine *1 1* next free spot for code generation *1 1* program
counter during execution *1 prog; 1* start of current subprogram *1 1* 1
1f return stmt seen *1

typedef struct Symbol Inst Datum 1nt Frame;

Frame *sp; *retpc; *argn; nargs;

1* proc/func call stack frame *1 1* symbol table entry *1 1* where to
resume after return *1 1* n-th argument on stack *1 1* number of
arguments *1

APPENDIX 3

```
#define NFRAME 100
Frame frame[NFRAME];
Frame *fp;
1* frame
p01nter *1 1n1tcode() {
    progp progbase;
    stackp = stack;
    fp = frame;
    return1ng = 0;
}
```

```
pushed)
```

```
Datum d;
```

```
if (stackp >= &stack[NSTACK])
    execerror("stack too deep", (char *)0);
*stackp++ = d;
```

```
Datum pop ( ) {
```

```
1f (stackp == stack)
    execerror("stack underflow", (char *)0);
return *--stackp;
```

```
constpush( ) {
```

```
Datum d;
d.val = «Symbol *)*pc++->u.val;
push (d) ;
```

```
varpush ( ) {
```

```
Datum d; d.sym = (Symbol *)(*pc++); push( d) ;
```

```
whilecode ( ) {
```

```
Datum d; Inst *savepc = pc; execute(savepc+2); 1* cond1t10n *1 d = pop (
) ; while (d.val) { execute(*«Inst **)(savepc»); 1* body *1 if (returning)
break; execute(savepc+2); 1* cond1t1on *1 d = pop ( ) ;
```

```
} 1f (lreturn1ng) pc = *«Inst **)(savepc+1»; 1* next stmt *1
```

```
1fcode ( ) {
```

```
Datum d; Inst *savepc = pc;
```

```
1* then part *1
```

```
execute(savepc+3); 1* cond1t1on *1 d = pop ( ) ; 1f (d. val) execute(*({Inst
**)(savepc»); else if (*«Inst **){savepc+1») 1* else part? *1
execute(*«Inst **)(savepc+1»); 1f (lreturn1ng) pc = *«Inst **)(savepc+2»;
1* next stmt *1
```

```
define(sp) 1* put func/proc 1n symbol table *1 Symbol *sp;
```


sp->u.defn (Inst)progbase; 1* start of code *1 progbase = progp; 1* next code starts here *1

HOC LISTING

341

342

THE UNIX PROGRAMMING ENVIRONMENT

APPENDIX 3

call () {

1* call a funct10n *1

Symbol *sp = (Symbol *)pc[0]; 1* symbol table entry *1 1* for funct10n *1 1f (fp++ >= &frame[NFRAME-1]) execerror(sp->name, "call nested too deeply"); fp->sp = sp; fp->nargs = (1nt)pc[1]; fp->retpc = pc + 2; fp->argn = stackp - 1; 1* last argument *1 execute(sp->u.defn); return1ng = 0;

```
ret ( ) {
```

```
1* common return from func or proc *1
```

```
1nt 1; for (1 = 0; 1 < fp->nargs; 1++) pop(); 1* pop arguments *1 pc = (Inst  
*)fp->retpc; --fp; return 1ng = 1;
```

```
funcrret ( ) {
```

```
1* return from a funct10n *1
```

```
Datum d; 1f (fp->sp->type == PROCEDURE) execerror(fp->sp->name, "  
(proc) returns value"); d = pop(); 1* preserve funct10n return value *1 ret (  
); push(d);
```

```
procrret() {
```

```
1* return from a procedure *1
```

```
1f (fp->sp->type == FUNCTION) execerror(fp->sp->name, "(func) returns  
no value");
```

```
ret ( ) ;
```

```
double *getarg() {
```

```
1* return pointer to argument *1
```

```
1nt nargs (1nt) *pc++; 1f (nargs > fp->nargs) execerror(fp->sp->name, "not  
enough arguments"); return &fp->argn[nargs - fp->nargs].val;
```

```
arg ( ) {
```

```
1* push argument onto stack *1
```

```
Datum d; d.val = *getarg(); push(d);
```

```
argassign( ) {
```

```
1* store top of stack 1n argument *1
```

```
Datum d; d = pop ( ) ; push(d); 1* leave value on stack *1 *getarg() = d.val;
```

```
blt1n() {
```

```
Datum d; d = pop ( ) ; d.val = (*(double (*)(»*pc++))(d.val); push(d) ;
```

APPENDIX 3

```
eval() {
```

```
add ( ) {
```

```
sub ( ) {
```

```
mul ( ) {
```

```
di v ( ) {
```

```
}
```

```
negate() {
```

```
} gt () {
```

```
lt () {
```

HOC LISTING

343

```
/* evaluate variable on stack */
```

```
Datum d; d = pop ( ) ; if (d.sym->type != VAR && d.sym->type !=  
UNDEF) execerror("attempt to evaluate non-variable", d.sym->name); if  
(d.sym->type == UNDEF) execerror{"undefined variable", d.sym->name};  
d.val = d.sym->u.val; pushed) ;
```

```
Datum d1, d2; d2 = pop ( ) ; d1 = pop ( ) ; d1.val += d2.val; push ( d1 ) ;
```

```
Datum d1, d2; d2 = pop ( ) ; d1 = pop ( ) ; d1.val -= d2.val; push ( d1 ) ;
```

```
Datum d1, d2; d2 = pop ( ) ; d1 = pop ( ) ; d1.val *= d2.val; push ( d1 ) ;
```

```
Datum d1, d2; d2 = pop ( ) ; if (d2.val == 0.0) execerror("division by zero",
(char *)0); d1 = pop ( ) ; d1.val /= d2.val; push ( d1 ) ;
```

```
Datum d; d = pop ( ) ; d.val = -d.val; push ( d ) ;
```

```
Datum d1, d2; d2 = pop ( ) ; d1 = pop ( ) ; d1.val = (double)(d1.val >
d2.val); push ( d1 ) ;
```

```
Datum d1, d2; d2 = pop ( ) ; d1 = pop ( ) ; d1.val = (double)(d1.val <
d2.val); push ( d1 ) ;
```

344 THE UNIX PROGRAMMING ENVIRONMENT

```
ge ( ) {
```

```
le() {
```

```
eq() {
```

```
ne ( ) {
```

and () {

or () {

not () {

power () {

Datum d1, d2; d2 = pope); d 1 = pop () ; d1.val = (double)(d1.val >= d2.val); push (d 1) ;

Datum d1, d2; d 2 = pop () ; d 1 = pop () ; d1.val = (double)(d1.val <= d2.val); push(d 1) ;

Datum d1, d2; d 2 = pop () ; d 1 = pop () ; d1.val = (double)(d1.val push (d 1) ;

d2 . val) ;

Datum d1, d2; d2 = pope); d 1 = pop () ; d1.val = (double)(d1.val 1= d2.val); push (d 1) ;

```
Datum d1, d2; d2 = pope); d 1 = pop ( ) ; d1.val = (double)(d1.val 1= 0.0
&& d2.val 1= 0.0); push( d 1) ;
```

```
Datum d1, d2; d2 = pop ( ) ; d 1 = pop ( ) ; d1.val = (double)(d1.val 1= 0.0
:: d2.val 1= 0.0); pushed 1) ;
```

```
Datum d; d = pop ( ) ; d.val = (double)(d.val push (d) ;
```

```
O. 0) ;
```

```
Datum d1, d2; extern double pow(); d2 = pop ( ) ; d 1 = pop ( ) ; d1.val =
Pow(d1.val, d2.val); push( d 1) ;
```

APPENDIX 3

```
ass 1 gn ( ) {
```

```
Datum d1, d2; d 1 = pop ( ) ; d2 = pope); 1f (d1.sym->type 1= VAR &&
d1.sym->type 1= UNDEF) execerror(nass1gnment to non-var1able", d 1.
sym->name) ; d1.sym->u.val = d2.val; d1.sym->type = VAR; push(d2);
```



```
pr1nt() 1* pop top value from stack, pr1nt 1t *1 {
```

```
Datum d; d = pop ( ) ; pr1ntf("\t%.8g\n", d.val);
```

```
prexpr ( ) {
```

```
1* pr1nt numer1c value *1
```

```
Datum d; d = pop ( ) ; pr1ntf("%.8g ", d.val);
```

```
prstr ( ) {
```

```
1* pr1nt str1ng value *1
```

```
pr1ntf("%s", (char *) *pc++);
```

```
varread ( ) {
```

```
1* read 1nto var1able *1
```

```

Datwn d; extern FILE *f1n; Symbol *var = (Symbol *) *pc++; Aga1n:
sW1tch (fscanf(f1n, "%If", &var->u.val» case EOF: 1f (more1nput(» goto
Aga1n; d.val = var->u.val = 0.0; break;

```

```

case O.

```

```

execerror("non-number read 1nto", var->name); break; default: d.val = 1.0;
break;

```

```

} var->type = VAR; pushed) ;

```

```

Inst *code(f) 1* 1nsta1l one instruct10n or operand *1 Inst f;

```

```

Inst *oprogp = progp; 1f (progp >= &prog[NPROG) execerror("program
too b1g", (char *)0); *progp++ = f; return oprogp;

```

```

execute(p) Inst *p;

```

```

for (pc p; *pc 1= STOP && Ireturn1ng; ) (*( *pc++»( );

```

HOC LISTING

345

346

THE UNIX PROGRAMMING ENVIRONMENT

APPENDIX 3

in1t.c


```
#1include "hoc.h" #1include "y.tab.h" #1include <math.h>
```

```
stat1c struct char 1nt keywords[] "proc" , "func" , "return", "1f", "else",  
"wh11e", "pr1nt", "read", 0,
```

```
Log(), Log10(), Sqrt(), Exp(), 1nteger(); 1* Keywords *1
```

extern double

*name; kva 1 ; {

PROC, FUNC, RETURN, IF, ELSE, WHILE, PRINT, READ, 0,

} ; stat1c struct { 1* Constants *1 char *name; double cval; consts[] = {
"PI", 3.14159265358979323846, "E", 2.71828182845904523536,
"GAMMA", 0.57721566490153286060, "DEG",
57.29577951308232087680, "PHI", 1.61803398874989484820, 0, 0

1* Euler *1 1* deg/rad1an *1 1* golden rat10 *1

} ;

stat1c struct { char *name; double (*func)(); bU11t1ns[] = { "s1n", S1n, "
cos" , cos, "atan", atan, "log", Log, 1* checks "10g10", Log10, 1* checks
"exp", Exp, 1* checks "sqrt", Sqrt, 1* checks " 1nt" , 1nteger, "abs", fabs, 0,
0

1* BU11t-1ns *1

```
range *1 range *1 range *1 range *1
```

```
} ; 1n1t() 1* 1n1t constants and bU11t-1ns 1n table *1 {
```

```
1n1 1; Symbol *S; for (1 = 0; keywords[1].name; 1++)  
1n1t(keywords[1].name, keywords[1].kval, O.O}; for (1 = 0;  
consts[1].name; 1++) 1n1t(consts[1].name, VAR, consts[1].cval}; for (1  
= 0; bU11t1ns[1].name; 1++) { s = 1n1t(bu11t1ns[1].name, BLTIN,  
O.O}; s->u.ptr = bU11t1ns[1].func;
```

```
*****
```

math.c

```
*****  
*****
```

```
#1nclude <math.h> #1nclude <errno.h> extern 1n1t errno; double errcheck();  
double Log(x} double x;
```

```
return errcheck(log(x}, "log");
```

APPENDIX 3

HOC LISTING

347

```
double Log10(x) double X; return errcheck(log10(x), "log10"); double  
Sqrt(x) double X; return errcheck(sqrt(x), " sqrt" ); double Exp(x) double  
X; return errcheck ( exp (x) , "exp");
```

```
double Pow(x, y) double x, y;
```

```
return errcheck(pow(x,y), "exponentiation");
```

```
double integer(x) double X;
```

```
return (double) (long)x;
```

```
double errcheck(d, s) double d; char *s;
```

```
1* check result of library call *1
```

```
if (errno == EDOM) { errno = 0; execerror(s, "argument out of domain"); }  
else if (errno == ERANGE) { errno = 0; execerror (s, "result out of range");
```

```
} return d;
```

```
*****
```

```
makefile
```

```
*****  
***
```

```
YFLAGS = -d OBJS = hoc.o code.o init.o math.o symbol.o
```

```
hoc6:
```

```
$(OBJS) cc $(CFLAGS) $(OBJS) -lm -o hoc6
```

```
hoc.o code.o init.o symbol.o: code.o init.o symbol.o: x.tab.h x.tab.h: y.tab.h  
-cmp -s x.tab.h y.tab.h :: cp y.tab.h x.tab.h
```

hoc.h

pr: hoc.y hoc.h code.c init.c math.c symbol.c @pr \$? @touch pr

clean:

rm -f \$(OBJS) [xy].tab.[ch]

& and signals 150 > > appending output 29 & background process 33, 73, 226 , 'backquotes 86, 139 ; ; case separator 134 [], character class 102 . command 89 : command 147 \$? command, make 266 - command, make 266 @ command, make 255 ; command separator 33, 71 \\$ command, troff 301 \& command, troff 298, 304 # comment, awk 117 . current directory 21, 25, 37, 48, 51, 75 & ed replacement character 323 # erase character 6 \ escape character 6 I escape to shell 9, 35, 92, 184, 194, 228, 254, 321 " exponentiation operator 245 < input redirection 29 @ line kill 6 I negation, sed 110 I negation, test 143 " obsolete: 36 % operator, awk 117 + + operator, awk 121 + = operator, awk 118 -- operator, awk 121 > output redirection 29 > > output redirection 29 . . parent directory 25, 51, 75 () parentheses, shell 72, 73 { } parentheses, shell 168 * pattern, shell 27 ? pattern, shell 28 [] pattern, shell 28 : pipe 31, 72 & precedence 73, 95 ; precedence 72 : precedence 72 " "quotes 75, 85 , quotes 75, 85 , quotes 85 < < redirection 94 \$ regular expression 102, 324 () regular expression 104 * regular expression 103, 324 + regular expression 104

. regular expression 103, 324 . * regular expression 109 ? regular expression 104 [] regular expression 102, 324 ["] regular expression 102, 324 " regular expression 102, 324 && shell AND 143 \$# shell argument count

135 "\$@" shell arguments 161 \$* shell arguments 83, 85, 145, 155, 161 \$@ shell arguments 155 # shell comment 7, 77 \$? shell exit status 140 : : shell OR 143, 169 * shell pattern 74, 162 \$ \$ shell process-id 146 \$ shell variable value 37, 88 \${ } variables, shell 148 \$ { } variables, table of shell 149 \$ 0 awk input line 116 \0, NUL character 175 \$ 0 shell argument 85 1 >&2 redirection 142 2, 3, 4, S, 6 commands 85 2>& 1 redirection 93, 202 2>filename redirection 93 411 command 84, 93 4 1 BSD x abort 244 access mode, open 205 aek function 332 Ackermann's function 284, 332 action, embedded 276 adb command 188 add function, hoe4 264 addup command 126 Aho, Al x, 131, 287 alarm signal call 229 ambiguous parse 254 analyzer, lexical 235 AND, && shell 143 appending output, > > 29 ar command 99 arg function 282 argass1gn function 282 arge 174, 178 argument count, \$# shell 135 arguments, blanks in 161 arguments, command 14, 74, 178

349

INDEX

arguments, hoc 332 arguments, null 84 arguments, optional 178 arguments, program 174, 220 arguments, shell 82, 160 arguments, troff macro 301 argv 174, 178 arithmetic, awk 118 ASCII character set 42, 106, 107 ass1gn function, hoe4 264 assignment, command-line 90 assignment expression 242, 329 assignment expression, awk 126 assignment, multiple 242, 329 assignment vs expression 246 associative array, awk 123, 128 associativity 238, 243, 251 at command 35, 129 at command, perpetual 129 at01 184 awk # comment 117 awk % operator 117 awk ++ operator 121 awk += operator 118 awk -- operator 121 awk arithmetic 118 awk assignment expression 126 awk associative array 123, 128 awk BEGIN pattern 118 awk break statement 121 awk command 114 awk control flow 119 awk END pattern 118 awk eX1 t statement 122 awk -f 114 awk -F 115 awk field, \$n 115 awk field separators 116 awk fields 115 awk FILENAME variable 121

awk for statement 121, 124 awk FS variable 118, 122 awk functions, table of 123 awk if-else statement 121 awk input line, \$0 116 awk I/O redirection 130 awk length function 117 awk, meaning of 131 awk multiline record 130 awk negated pattern 117 awk next statement 122 awk NF variable 115

350 THE UNIX PROGRAMMING ENVIRONMENT

awk NR variable 116 awk operators, table of 119 awk pattern range 130 awk patterns 116 awk print statement 114 awk printf statement 116 awk split function 122 awk string concatenation 125 awk strings 119, 125 awk substr function 117 awk variable initialization 118, 119 awk variables, table of 119 awk variables vs shell variables 115 awk while statement 121 \b backspace convention 43 . B command, ms 294 background process, & 33, 73, 226 backquotes, ' , 86, 139 backquotes, nested 87, 157 backslash 78, 157 backslash, erasing a backslash function 277 backslash into troff, getting 298 backslash, quoting with 6, 29, 75, 324 backspace 6, 172 backspace convention, \b 43 backspace, ctrl-h 2, 36 backup, file 60 Backus-Naur Form 234 backwards command 122 bas command 284 BASIC 233 be command 39, 284 BEGIN pattern, awk 118 Belle chess computer 231 Bentley, Jon x, 287 Berkeley 4 BSD x Bianchi, Mike x Bimmler, Elizabeth x, 34 /bin directory 24, 37, 63, 142 bin directory, personal 81, 90, 134 binary files 47 blank, unprintable 299 blanks in arguments 161 block device 66 block, disc 14, 50, 66, 203 bltin function, troff 264 BNF 234 bootstrap 63, 67 Bourne, Steve 100, 200 . bp command, troff 301 . br command, troff 300 Bradford, Ed x BREAK 3, 7 break statement, awk 121 break statement, shell 160 buffering 45, 180, 201, 203, 223 BUFSIZ 183, 203 bug, diff 167 bug, ls 14, 60, 163 bug, nohup 151 bug, p 185 bug, perl 188 bug, sed 172 bug, shell 159 bug, sort 47 bug, sqrt 252

bug, system 185, 223 bug, zap 186 built-in functions, troff 245 bundle command 98 bundle, reliability of 99 bus error 188 byte 41, 202 . e filename

convention 46 `\e` in `echo` 78 `e` program, compiling a 174 `e` programming language 171 `e` shell 100 `eal` command 133, 135 `calendar` command 9, 127, 129 `calendar`, design of 128 `call` function 279 `eanaday`, Rudd vii `earfagno`, Joe x carriage return convention, `\r` 43 `earter`, Don x case conversion 107 case separator, `;;` 134 case statement, shell 134 case vs `1f` 141 `cast` 211, 264 `cat` command 15, 203 `cat`, meaning of 15 `cat -u` 44 catching interrupts 150, 198 catching signals 153 `ee` command 174 `ee -1` 255 `ee -0` 174 `ee -p` 285, 286 `cd` command 25 `CFLAGS` 285 change, font 299 change, point size 300 changing a password 54 changing directory 25 changing permissions 56 character `\0`, `NUL` 175 character class `[]` 102 character class, negated 102 character device 66 character names, `troff` 297 character set, `Asen` 42, 106, 107 character set, `EBeDIe` 42, 107 `ehd1r` system call 216 `eheckma1l` command 148, 216 `eheckma1l`, evolution of 215 `eherry`, Lorinda 314 chess computer, Belle 231 child process 34, 222 `ehmod` command 56 `ehmod -w` 56 `ehmod +x` 56, 81 choice of language 170, 171, 181, 258, 277 `close` system call 206 closure 103, 104 `emp` command 20 `emp -s` 140, 266 code function, `hoe4` 263 code generation, `hoe4` 258 code generation, `1f` 269 code generation, `wh1le` 268 code. `e` file, `hoe4` 262 code. `e` file, `hoe6` 278 coercion, type 211, 264 combining programs viii, 30, 32, 170 `eomer`, Doug 131

`comm` command 107 command arguments 14, 74, 178 command interpreter 26 command options 13, 14 command separator, `;` 33, 71 command-line assignment 90 commands, creating shell 80 commands executable, making 81 commands, `ms` 291 commands, permuted index to 2, 10 commands, personal 84 commands, table of `ed` 327 commands, table of file 21 commands, table of `sed` 112 comment, `#` shell 7, 77 comment, `awk /I` 117 comparing files 20, 107 compiler-compiler 235 compiling a `e` program 174 computer-aided instruction 11 concatenation, `awk` string 125 `eondon`, Joe 231 conflict, shift/reduce 253, 268 constants, table of `hoc` 246, 330 `eonstpush` function, `hoe4` 263 continuation, shell line 77 `eONTROL` 2 control character 2 control flow, `awk` 119 convention, `\b` backspace 43 convention, `.` `e` filename 46 convention, filename 26 convention, `.h` 247 convention, `.1` filename 257 convention, `\n` newline 43 convention, `\r` carriage return 43 convention, `\t` tab 43 convention, `.` `y` filename 236

copying a file 17, 61 core dump 188, 225, 242 core dump, `ctl-\` 150, 188
correction, spelling 208, 213 counting files 30 counting users 30 counting
words 18 `ep` command 17,61,206 crash, system 12, 64 `ereat` permissions
205 `ereat` system call 205 create a program, program to 99, 307 creating a
file 202 creating shell commands 80 creation, process 220 `eRLF` 44, 174
cross-device link 67 `crypt` command 52, 68 `esh` command 100 `ctl-\` core
dump 150, 188 `ctl-\` quit signal 225 `ctl-e DELETE` 3 `ctl-d` end of file 2, 8,
31, 45 `ctl-d` to logout 8 `ctl-g` ring bell 2, 73 `ctl-h` backspace 2, 36 `ctl-i` tab 2
`ctl-q` resuming output 8 `ctl-s` stopping output 8, 15 `ctl-u` line kill 6 `etyp`
tests, table of 174 `etyp`. `h` header file 173 `eu` command 39

current directory, `.` 21,25,37, 48, 51, 75 `ex` command 82 `d` command, `sed` III
data structures, `hoe4` 262 data structures, `hoe6` 278 data structures,
procedure call 279 `date` command 4 dates, file 57 `dd` command 69, 107 `. DE`
command, `ms` 293 `. de` command, `troff` 301 De Marco, Tom x De Morgan,
Augustus 18, 320 dead. letter 8 debugger, `adb` 188 debugger, `sdb` 189
debugging 187,244,258,265, 302 default signal handling 225, 227 `def1ne`
function 279 defining `troff` macros 301 definitions, table of `std1o`. `h` 178
`defnonly` function 276 `DELETE` 3, 7, 10, 150, 225 `DELETE`, `ctl-e` 3
dependency rule, empty 255 descriptor, file 92, 201, 223 design of calendar
128 design of `echo` 78 design of `e f` open 182 design of `grep` family 105
design of `idiff` 194, 198 `designofp` 181,184,185 design of `p1ek` 186 design
of `set` 136 design of `sname` 209 design of `sv` 217 design of `V1S` 172, 174,
179, 185 design of `zap` 198 design, program 110, 134, 147, 154, 165,
170,222,265,286, 302 `/dev` directory 63, 65 device, block 66 device,
character 66 device file 41, 65 device, peripheral 1, 41, 65, 201 `/dev/null` 69
`/dev/tty` 68, 160, 183, 223, 224 `df` command 67 `dial-a-joke` 84 `diet10n`
command 313 dictionary, `/usr /d1et/words` 104 `d1ff -b` 198 `d1ff` bug 167
`d1ff` command 20 `d1ff -e` 165 `d1ff -h` 198 `d1ff -s` 140 directories, table of 63
directory 21 directory, `.` current 21, 25, 37, 48, 51, 75 directory, `..` parent 25,
51, 75 `dlfactory`, `/bin` 24, 37, 63, 142 directory, changing 25 directory, `/ dev`
63, 65 directory, `jete` 63

directory format 51, 59, 209 directory hierarchy 63, 208 directory, home 21, 36 directory, /lib 63 directory, making a 25 directory, moving a 62
 directory permissions 55, 56 directory, personal bin 81, 90, 134 directory, removing a 26 directory, root 22, 51 directory structure 48 directory, /tmp 63, 146 directory, /usr 22, 48, 65 directory, /usr/bin 24, 37, 65, 142 directory, /usr/games 25, 90 directory, /usr/include 173 directory, /usr/man 308 directory, /usr/src 48 dir. h header file 209 disc block 14, 50, 66, 203 disc free space 67 discarding output 69 doetype command 307 doetype, evolution of 308 doetype timing 307 double command 120 . DS commaQd, ms 293 du -a 50, 108 du command 50 Duff, Tom x, 100, 231 dump, core 188, 225, 242 dup system call 223 Durham, Ivor 231 \e command, troff 298 EBCDIC character set 42, 107 echo, \e in 78 echo command 27, 77 echo, design of 78 echo -n 78, 160 echo, terminal 2, 43 Echo, UNIX and the 78 ed - 168 ed command 12, 320 ed commands, table of 327 ed editor 11 ed encryption command 327 ed global commands 325 ed line \$ 322 ed line. 322 ed line number expressions 322 ed line numbers 320 ed line numbers, table of 327 ed line-moving commands 325 ed mark command 326 ed regular expression examples 325 ed regular expressions, table of 324 ed replacement character, & 323 ed undo command 323 ed.hup 12 editor, screen 11, 319 efficiency 124, 141, 147, 151, 158, 165, 171, 178, 180, 190, 204, 216, 236, 247, 258, 265, 266, 285, 286, 302, 307, 319 efopen, design of 182 efopen function 182 egilops 104 egrep command 69, 103 egrep -f 103

INDEX 351

egrep -h 307 emacs screen editor 11 emacs function 248 embedded action 276 empty dependency rule 255 empty production 237 encryption 52 encryption command, ed 327 encryption, password 53 end of file 44, 202, 203 end of file, ctrl-d 2, 8, 31, 45 END pattern, awk 118 EOF 173, 204 eqn examples 304 erase character 7, 29 erase character, # 6 erase character, setting 35 erasing a backslash 6 erreheck function 253 errno 206, 228 errno. h header file 228, 252 error function 207 error handling 218 error message 5, 17, 32, 56, 61, 93, 142, 148, 180, 182, 302 error recovery, hoc 2 244, 245

error recovery, hoc 3 252 error recovery, hoe6 276 error, standard 32, 92, 177, 202 error status, system call 206 error, write 219 escape character, \ 6 escape to shell, I 9, 35, 92, 184, 194, 228, 254, 321 / etc directory 63 jete/group 54 jete/mount command 66 /etc/passwd password file 53, 103, 115 eval command 156 eval function, hoe4 264 evolution of eheekmail 215 evolution of doetype 308 evolution of hoc 233 exception, floating point 242, 243 exeerror function, hoe2 244 exeelp system call 220 executable, making commands 81 execute function, hoe4 263 execute function, hoe6 281 exeenv system call 220 eX1 t command 142 eX1 t function 174 exit statement, awk 122 exit status 140, 142, 144, 174, 222 exit status, \$? shell 140 exit status of pipeline 145 exit status of shell file 142 Exp function 252 exponentiation operator, " 245 export command 38, 91 expression, assignment 242, 329 expressions, ed line number 322 \f command, troff 291, 299 fae function 274, 333 false command 147, 149 felose 179 . FE command, ms 296 features 185, 316 Feldman, Stu 287 fflush 183 fgets 183

352 THE UNIX PROGRAMMING ENVIRONMENT

fgrep command 103 fgrep -f 103 . f1 command, troff 300 f1b function 274, 284 f1eld command 126 field, \$n awk 115 field separator, shell 157, 160, 163, 164 field separators, awk 116 fields, awk 115 fields, sorting on 106 file 11 file access, random 207 file access, simultaneous 203 file backup 60 file command 46 file commands, table of 21 file, copying a 17, 61 file, creating a 202 file dates 57 file descriptor 92, 201, 223 file, device 41, 65 file, moving a 16 file open 176 file, opening a 201 file permissions 52, 54, 205 FILE pointer 177, 202 file, removing a 17 file, renaming a 16 file restore 60 file, shell 81 file structure 41, 47 file system 11, 21, 209 file system hierarchy 24, 63 file system mounting 67 file times 57 file types 46, 47 filename convention 26 filename convention, . c 46 filename convention, .1 257 filename convention, . y 236 filename rules 17 filename search 50 filename shorthand 26 FILENAME variable, awk 121 fleno macro 202 files, comparing 20, 107 files, formatless 47 files, text 47 filling, line 291 filters ix, 101 find command 52 finding a file 50, 52 finite state machine 277 Flandrena, Bob x fleas 18, 320 floating point exception 242, 243 fold

command 125 follow function 270 font change 299 font changes, ms 294
fopen 176 f open modes 177 for 1 loop, shell 145 for loop format, shell 95
for statement, awk 121, 124 for syntax, shell 95, 144 for k system call 222
format, directory 51,59,209 format independence 290 format, inode 214
format, shell for loop 95 formatless files 47

formatter, nroff 289 formatter, roff 289 formatter, Scribe 314 formatter,
TEX 314 formatter, troff 289 FORTRAN 47 FOR TRAN 77 39, 287
fortune game 36 fpecateh function, hoc2 244 fpr1ntf 179 fputs 183 free
space, disc 67 frexp 241 . FS command, ms 296 FS variable, awk 118, 122
fstat system call 215 . ft command, troff 291, 301 full duplex 2, 4 funcrct
function 279 function definition, hoc 332 functions, hoe3 built-in 245
functions, table of awk 123 functions, table of hoc 330 functions, table of
standard 110 192 functions, table of string 176 Furuta, Richard 314 game,
fortune 36 game, QU1Z 327 games 11, 25 Gay, David x get command 168
getarg function 281 getc 177 getchar 172 getehar macro 177 getenv 199
getlog1n 216 getname command 109 getopt 179 getting backslash into trof
f 298 global commands, ed 325 Gosling, James 100 grammar 234 grammar,
hoc 1 237 grammar, hoe2 243 grammar, hoc 3 250 grammar, hoc4 259
grammar, hoc S 267 grammar, hoc6 275 grammar production 235 grep -b
III grep command 18, 102 grep -e 79 grep examples 102 grep family, design
of 105 grep -l 87 grep, meaning of 18 grep -n 102 grep regular expressions
102 grep -v 18, 102, III grep -y 85, 102 group-id 52 . h convention 247
hangup signal 150, 225 Hanson, Dave x Hardin, Ron x Harris, Marion x
hashing 124, 314 header file 247, 261, 286 header file, etype. h 173 header
file, d1r. h 209 header file, errno. h 228

header fHe, 1no. h 219 header file, math. h 252 header fHe, setjmp. h 227
header file, signal. h 191, 225 header file, stat.h 214 header file, std10. h
173 header file, types. h 214 here document 94, 98 Hewett, Alan 100
hierarchy, directory 63, 208 hierarchy, file system 24, 63 hierarchy, process
34, 48 hoc arguments 332 hoc constants, table of 246, 330 hoc, evolution of
233 hoc function definition 332 hoc functions, table of 330 hoc input format
331 hoc manual 329 hoc, meaning of 234 hoc operators, table of 330 hoc

pr1nt statement 331 hoc procedure definition 332 hoc read statement 331
hoc, reliability of 265, 274 hoc sizes, table of 283 hoc stages 233 hoc times,
table of 284 hoc 1 grammar 237 hoc 1 main function 239 hoc 1 make file
241 hoc 1 unary minus 240 hoc 1 warn1ng function 240 hoc 1 yyerror
function 240 hoc 1 yylex function 239 hoc2 error recovery 244, 245 hoc2
exeerror function 244 hoc2 fpecateh function 244 hoc 2 grammar 243 hoc2
main function 244 hoe2 yylex function 245 hoc3 built-in functions 245
hoc3 error recovery 252 hoc 3 grammar 250 hoc3 hoc. h 247 hoc 3 1n1 t
function 249 hoc 3 1n1 t . e file 249 hoc3 lex makef1le 257 hoe3 lex
version 256 hoc 3 ma1n function 252 hoc3 makef1le 255 hoe3 math. e file
252 hoc3 source files 247 hoe3 yylex function 251 hoe4 add function 264
hoe4 ass1gn function 264 hoe4 bl t1n function 264 hoc4 code function 263
hoc4 code generation 258 hoe4 code. c file 262 hoc4 eonstpush function
263 hoc4 data structures 262 hoc4 eval function 264 hoe4 execute function
263 hoc4 grammar 259 hoe4 hoc. h 261 hoc4 ma1n function 260 hoe4
makef1le 266 hoc4 pop function 262 hoe4 pr1nt function 264 hoe4 push
function 262 hoc4 varpush function 263 hoc4 yylex function 261

hoc S grammar 267 hoeS hoc. h 270 hoeS 1feode function 272 hoeS 1n1 t.
e file 272 hoeS yylex function 270 hoe6 code. e file 278 hoe6 data
structures 278 hoe6 error recovery 276 hoe6 execute function 281 hoe6
grammar 275 hoe6 hoc. h 278 hoe6 1feode function 281 hoe6 1n1 teode
function 278 hoe6 makef1le 285 hoe6 yylex function 277 hoc. h, hoe3 247
hoc. h, hoe4 261 hoc. h, hoeS 270 hoc. h, hoe6 278 Holzmann, Gerard x
home directory 21, 36 HOME shell variable 36, 88 Hunt, Wayne 200 . I
command, ms 292, 294 1deal command 313 1d1ff command 193 id1ff,
design of 194, 198 1d1ff function 197 id1ff ma1n function 195 1f code
generation 269 1f vs case 141 ifeode function, hoeS 272 ifeode function,
hoe6 281 1f-else statement, awk 121 1f-else statement, shell 140 IFS shell
variable 157, 163, 164 ignoring interrupts 228 ignoring signals 151,
153,226 #1nelude 173 ind command 109, 116 1ndex 218 index to
commands, permuted 2, 10 inheritance, open file 223 inheritance, shell
variable 89, 91 in1 t function, hoe3 249 in1 t. e file, hoe3 249 in1 t. e file,
hoeS 272 in1 teode function, hoe6 278 initialization, awk variable 118, 119
inode 57 in ode format 214 inode table 209 1no. h header file 219 input

form, yae 236 input format, hoc 331 input line, \$0 awk 116 input redirection, < 29 input, standard 30, 92, 177, 202 input, troff 290 inserting newline, sed 111 1n stall function 248 instruction, computer-aided 11 1n teger function 253 interpreter 258 interpreter, command 26 INTERRUPT 3 interrupt signal 150, 225 interrupted system call 228 interrupts, catching 150, 198 interrupts, ignoring 226, 228 i-number 58

i-number, zero 59 I/O library, standard 171 110, low-level 201 110 redirection 29, 30, 47, 74, 80, 92, 180, 183, 202 I/O redirection, awk 130 110 redirection, shell 159 110 timing, table of 203 . IP command, ms 296 1sase1i 173 1sprint 173 Johnson, Steve x, 200, 235, 287, 314 Joy, Bill 100 justification, line 291 Katseff, Howard 200 . KE command, ms 296 kernel 1,7,23,32,43,53,55, 99, 201 Kernighan, Brian 39, 131, 171, 314 . KF command, ms 296 kill V111 188 kill -g 152 kill command 34, 225 Knuth, Don 90, 314 . KS command, ms 296 1 command, sed 172, 174 . 1 filename convention 257 Lamb, David 231 language, choice of 170, 171, 181, 258, 277 language development 233, 286 language, special-purpose 286, 290 layout, page 289 le command 83 le function 271 learn command 11 %left 238 length function, awk 117 Lesk, Mike 200, 287 1 ex library, -11 257 lex makefile, hoe3 257 lex regular expressions 256 1 ex version, hoc 3 256 lexical analyzer 235 lexical token 235 /11b directory 63 library, -11 1 ex 257 library, -1m math 255 limit, open file 206 Linderman, John x line \$, ed 322 line " ed 322 line continuation, shell 77, 108 line filling 291 line justification 291 line kill 7 line kill, @ 6 line kill character 29 line kill character, setting 35 line kill, ctl-u 6 line number expressions, ed 322 line numbers, ed 320 line numbers, table of ed 327 line printer 16 line spacing 296 line-moving commands, ed 325 link 59, 85, 96 link, cross-device 67 link, making a 59 l1nt command 190

INDEX 353

Lions, John 315 -11 lex library 257 -1m math library 255 In command 59
 Log function 252 Log 1 0 function 252 logout 8, 45 logout, ctl-d to 8
 Lomuto, Ann 39 Lomuto, Nico x, 39 long jmp 227, 244 lookup function
 248 loop, shell for i 145 loops, shell 94 low-level I/O 201 . LP command,
 ms 296 lpr command 16 ls bug 14, 60, 163 ls -e 58 1 s command 13 1 s -d
 55 ls -f 51 1 s -g 53 ls -l 58 ls -l 13, 14 ls -r 14 ls -t 13, 58 ls -u 58 lseek
 system call 122, 207 m command 83 macro arguments, troff 301 macro,
 f1leno 202 macro, getehar 177 macro package 289 macro package, man 309
 macro package, mm 290, 297 macro package, ms 290 macro, pop 286
 macro, push 286 macro, putehar 177 macros, defining troff 301 macros,
 yae 255 magic number 46, 191 Mahaney, Steve x mail command 8 mail,
 notification of 8, 36, 147, 215 mail, remote 9, 97 mail, sending 8 MAIL
 shell variable 36, 147 main function, hoc 1 239 main function, hoe2 244
 main function, hoe3 252 main function, hoe4 260 main function, 1d1ff
 195 main function, p 182, 184, 199, 213 main function, pick 187 main
 function, sv 217 main function, V1 s 178 main function, zap 191 make \$?
 command 266 make - command 266 make @ command 255 make
 command 241 make -n 255 make -t 255 makefile, hoe1 241 makefile, hoe3
 255 makefile, hoe3 lex 257 makefile, hoe4 266 makefile, hoe6 285 making
 a directory 25

354 THE UNIX PROGRAMMING ENVIRONMENT

making a link 59 making commands executable 81 man command 11, 309
 man macro package 309 man -t 309 manual, hoc 329 manual organization
 10 manual page 308 Maranzano, Joe 200 mark command, ed 326 Martin,
 Bob x Mashey, John 39, 100 math library, -1m 255 math. e file, hoe3 252
 ma th . h header file 252 McIlroy, Doug vii, x, 47, 78, 200, 314 McMahon,
 Lee 131 meaning of awk 131 meaning of cat 15 meaning of grep 18
 meaning of hoc 234 meaning of UNIX vii, 1 memory fault 188 mesg
 command 10, 68 message, error 5, 17, 32, 56, 61, 93, 142, 148, 180, 182, 302
 metacharacters 102, 220 metacharacters, shell 74 metacharacters, table of
 shell 75 mind1st function 211 mkd1r command 25, 48 mktemp 195 mm
 commands, table of 297 mm macro package 290, 297 modes, fopen 177

modularity 209, 247, 261, 302 mon. out 285 more command 15 Morris, Bob 70 mounting, file system 67 moving a directory 62 moving a file 16 ms . B command 294 ms commands 291 ms commands, table of 296 ms . DE command 293 ms . DS command 293 ms . FE command 296 ms font changes 294 ms . FS command 296 ms . I command 292, 294 ms . IP command 296 ms . KE command 296 ms . KF command 296 ms . KS command 296 ms . LP command 296 ms macro package 290 ms . PP command 291 ms . R command 294 MUL TIEs vii, 70 multi-line record, awk 130 multiple assignment 242, 329 mv command 16, 61 \$n awk field 115 \n newline convention 43 \$n shell argument 82 \$n yae value 237 names, table of troff 298 names, troff character 297 nargs command 158 neopy function 198 negated character class 102

negated pattern, awk 117 nested backquotes 87, 157 nested quotes 75, 86, 112, 128 netnews command 10 newer command 112 newgrp command 54 newline 13, 43, 202 newline as terminator 44 newline convention, \n 43 newline, sed inserting III news command 10, 162, 163, 164 next statement, awk 122 . nf command, trof f 300 NF variable, awk 115 nice command 35 nlee -n 151 nohup bug 151 nohup command 35, 151 notification of mail 8, 36, 147, 215 NR variable, awk 116 nrof f formatter 289 nsk1p function 198 nu command 80 NUL character \0 175 null arguments 84 NULL pointer 177 null string in PATH 139 number register, troff 296 obsolete ;," 36 octal numbers in e 205 od -b 42 od -e 42 od command 42 od -d 42, 59 od -x 43 older command 113 on-line dictionary 104 open access mode 205 open, file 176 open file inheritance 223 open file limit 206 open system call 205 opening a file 201 operator, "exponentiation 245 operator, awk % 117 operator, awk ++ 121 operator, awk += 118 operator, awk -- 121 operators, relational 266 operators, table of awk 119 operators, table of hoc 330 optional arguments 178, 179, 199 options, command 13, 14 options, parsing ! 78 options vs programs 185 OR, : : shell 143, 169 order of sorting 19, 27, 28 Organick, E I 70 organization, manual 10 Ossanna, Joe vii, 289, 314 output, discarding 69 output form, yae 236 output redirection, > 29 output redirection,» 29 output, standard 32, 92, 177, 202 overflow 243, 245 overwr1 te command 153, 155 p bug 185 p command 181,213 p, design of 181, 184, 185 p main function 182, 184, 199, 213

page layout 289 page, manual 308 parameters, shell 88 par am . h header
file 206 parent directory, .. 25, 51, 75 parent process 34, 222 parentheses,
shell (. .) 72, 73 parentheses, shell { .} 168 parse, ambiguous 254 parse
function 197 parse tree 238, 254 parser-generator 235 parsing options 178
parsing process, yae 237 parsing, shell argument 161 Pascal 287 passwd
command 54 password 4 password, changing a 54 password encryption 53
password file, /etc/passwd 53, 103, 115 password security 70 PATH, null
string in 139 path, search 37,81,88, 139, 142, 220 PATH shell variable 37,
81, 88, 138, 139, 142, 220 pathname 23, 25 pathnames, shell patterns in 28
pattern, '*' shell 74, 162 pattern matching, shell 26, 134, 136, 162 pattern
range, awk 130 pattern searching 18 pattern, shell '*' 27 pattern, shell? 28
pattern, shell [] 28 patterns. awk 116 patterns in pathnames, shell 28
patterns, table of shell 136 pelose 190 peripheral device 1, 41, 65, 201
permission, root 55 permission, set-uid 54 permissions, changing 56
permissions, ereat 205 permissions, directory 55, 56 permissions, file 52,
54, 205 permissions, /usr/games 56 permuted index to commands 2, 10
perpetual at command 129 personal bin directory 81,90, 134 personal
commands 84 pg command 15 p1e command 313 p1e example 313 p1ek
bug 188 p1ek command 87, 156, 160, 186 pick, design of 186 pick function
187 pick main function 187 Pinter, Ron x pipe, : 31, 72 pipeline 72, 180
pipeline examples 31 pipeline, exit status of 145 point size 296, 300 point
size change 300 pointer, FILE 177, 202

pointer, NULL 177 pop function, hoe4 262 pop macro 286 popen 190
portability vii, 190, 209, 218, 234, 252, 315 Pow function 252 . pp
command, ms 291 pr command 15 pr - h 95 pr -1 86 pr -m 16 pr -n 16 pr -t
86 %pre 241 precedence 238, 241 precedence, & 73, 95 precedence, ; 72
precedence, I 72 preprocessor 290, 301 prexpr function 272, 282 print
function 183 print function, hoe4 264 pr1nt statement, awk 114 print
statement, hoc 331 pr1ntf 173 printf statement, awk 116 procedure call data
structures 279 procedure definition, hoc 332 process, & background 33, 73,
226 process creation 220 process hierarchy 34, 48 process status 34
processes 33 process-id 33, 146, 222 process-id, \$\$ shell 146 proeret

function 280 production, empty 237 production, grammar 235 prof
command 285 .profile 36,81,89, 159 . profile example 38 profiling 285
program arguments 174, 220 program design 110, 134, 147, 154, 165, 170,
222, 265, 286, 302 program, stopping a 7, 34 program to create a program
99, 307 programmable formatter 289 programmable shell 99 programming
language, e 171 programming, shell 99, 133 programs, combining viii, 30,
32, 170 programs vs options 185 prompt 4, 26, 72 prompt, secondary 76
protocol, write 9 prpages command 119 pr str function 282 ps -a 34, 191 ps
command 34 . ps command, troff 301 PS 1 shell variable 36, 82 PS2 shell
variable 76 push function, hoe4 262 push macro 286 put command 167 pute
177 putehar 172

putehar macro 177 pwd command 21, 48 q command, sed 110 quit signal
225 quit signal, ctl- \ 225 qui z game 327 quotes 28, 85, 94, 104, 126
quotes, " "75, 85 quotes, ' , 75, 85 quotes, ' . ' 85 quotes, nested 75, 86, 112,
128 quotes, troff 295 quoting with backslash 6, 29, 75, 324 \r carriage
return convention 43 . R command, ms 294 random file access 207 range,
awk pattern 130 range selection, sed 111 Ratfor 287 read command 159
read statement, hoc 331 read system call 44, 202 reads low command 204,
231 record, awk multi-line 130 recursion 18, 355 redirection, < < 94
redirection, < input 29 redirection, > output 29 redirection, > > output 29
redirection, 1 >&2 142 redirection, 2 >& 1 93, 202 redirection, 2 >filename
93 redirection, awk I/O 130 redirection, I/O 29, 30, 47, 74, 80, 92, 180, 183,
202 redirection, shell 110 159 redirections, table of shell 94 refer command
313 regular expression 102,315,319 regular expression, \$ 102, 324 regular
expression, () 104 regular expression, * 103, 324 regular expression, + 104
regular expression,. 103, 324 regular expression, . * 109 regular
expression,? 104 regular expression, [] 102, 324 regular expression, [" .]
102, 324 regular expression," 102, 324 regular expression examples, ed 325
regular expression, tagged 105, 324, 326 regular expressions, grep 102
regular expressions, lex 256 regular expressions, shell vs ed itor 138 regular
expressions, table of 105 regular expressions, table of ed 324 Reid, Brian
314 relational operators 266 reliability of bundl e 99 reliability of hoc 265,
274 reliability of shell programs 133 remote mail 9, 97 removing a
directory 26 removing a file 17 renaming a file 16 replace command 155

INDEX 355

replacement character, & ed 323 resetting signals 227 restore, file 60
resuming output, `ctl-q` 8 `ret` function 280 `RETURN` 2, 4, 7, 13, 43 rewind
208 %right 238 ring bell, `ctl-g` 2, 73 Ritchie, Dennis vii, x, 39, 54,
70,171,200,231,315 `rm` command 17,61 `rm -f` 56, 151 `rm -r` 187 `rmdir`
command 26 Rochkind, Marc 131, 170 `rof` `f` formatter 289 root directory
22, 51 root permission 55 root user 52, 55 Rosier, Larry x `RUBOUT` 3
rules, filename 17 `s` command, `sed` 108 `\s` command, `troff` 300 Saltzer, J E
314 Saxe, James 231 `scanf` 173, 329 scapegoat command 219 sees 170
Scofield, Jeffrey 314 screen editor 11, 319 screen editor, `emac s` 11 screen
editor, `V1` 11 Scribe formatter 314 `sdb` command 189 search, filename 50
search path 37,81,88, 139, 142, 220 searching, pattern 18 secondary prompt
76 security, password 70 `sed` `I` negation 110 `sed` bug 172 `sed` command 108
`sed` commands, table of 112 `sed d` command 111 `sed -f` 110 `sed` inserting
newline 111 `sed l` command 172, 174 `sed -n` 111 `sed q` command 110 `sed`
range selection 111 `sed s` command 108 `sed` stream editor 101 `sed w`
command 112 `seek` 122 sending mail 8 separator, `;` command 33, 71
separator, shell field 157, 160, 163, 164 separators, `awk` field 116
separators, shell word 86 `set` command 88, 136, 164 `set`, design of 136 `set -`
`v` 136 `set -x` 136 `set jmp` 227, 244 `set jmp . h` header file 227 setting erase
character 35 setting line kill character 35 setting tab stops 43 `set-uid`
permission 54

356 THE UNIX PROGRAMMING ENVIRONMENT

Seventh Edition x, 7, 14, 39, 65, 75, 77, 78, 85, 87, 100, 106, 125, 140, 151,
171, 188, 201, 290,313,314 `sh -e` 221 `sh` command 80 Shaw, Alan 314 shell
ix, 26 shell, `I` escape to 9, 35, 92, 184, 194, 228, 254, 321 shell ()
parentheses 72, 73 shell { } parentheses 168 shell * pattern 27 shell ?

pattern 28 shell [] pattern 28 shell \$ { } variables 148 shell \$ { } variables, table of 149 shell AND, && 143 shell argument, \$ 0 85 shell argument count, \$# 135 shell argument, \$n 82 shell argument parsing 161 shell arguments 82, 160 shell arguments, "\$@" 161 shell arguments, \$* 83, 85, 145, 155, 161 shell arguments, \$@ 155 shell break statement 160 shell bug 159 shell case statement 134 shell commands, creating 80 shell comment, # 7, 77 shell exit status, \$? 140 shell field separator 157, 160, 163, 164 shell file 81 shell file, exit status of 142 shell for 1 loop 145 shell f or loop format 95 shell for syntax 95, 144 shell if-else statement 140 shell I/O redirection 159 shell line continuation 77, 108 shell loops 94 shell metacharacters 74 shell metacharacters, table of 75 shell OR, :: 143, 169 shell parameters 88 shell pattern, * 74, 162 shell pattern matching 26, 134, 136, 162 shell patterns in pathnames 28 shell patterns, table of 136 shell process-id, \$\$ 146 shell, programmable 99 shell programming 99, 133 shell programs, reliability of 133 shell redirections, table of 94 shell until syntax 145 shell variable inheritance 89, 91 shell variable, TERM 159 shell variable value, \$ 37, 88 shell variables 36, 88 shell variables, awk variables vs 115 shell variables, table of 135 shell vs editor regular expressions 138 shell while syntax 144 shell word 71, 95, 157 shell word separators 86 shift command 155, 168

shift/reduce conflict 253, 268 shorthand, filename 26 signal call, alarm 229 signal, ctrl-\ quit 225 signal handling, default 225, 227 signal, hangup 150, 225 signal, interrupt 150, 225 signal numbers, table of 150 signal, quit 225 signal system call 225 signal, terminate 225 signal.h header file 191, 225 signals 225 signals, & and 150 signals, catching 153 signals, ignoring 151, 153, 226 signals, resetting 227 simultaneous file access 203 Sitar, Ed x Sixth Edition 100, 208, 315 size change, point 300 size command 258 size, point 296, 300 sizeof 211 sizes, table of 283 sleep 204 sleep command 73 SNOBOL4 131 sort bug 47 sort command 19, 106 sort -d 106 sort -f 106 sort -n 19 sort -n 19, 106 sort -o 106, 152 sort -r 19, 106 sort -u 106, 307 sorting on fields 106 sorting, order of 19, 27, 28 source code control 165, 17C source files, hoe3 247 .sp command, troff 301 spacing, line 296 Spd1St function 212 special-purpose language 286, 290 spell command 313 spelling correction 208, 213 Spencer, Henry 200 split function, awk 122

spname, design of 209 s pname function 210 sqrt bug 252 Sqrt function 252
sscanf 191 stack machine 258 stack trace 188 stack, yae 238 stages, hoc
233 standard error 32, 92, 177, 202 standard input 30, 92, 177, 202 standard
I/O functions, table of 192 standard I/O library 171 standard output 32, 92,
177, 202 startup, system 63, 67 stat system call 215 stat. h header file 214
status, process 34 status return, wa1 t 222 stderr 177, 180 std1n 177 std10.h
173

Std10. h definitions, table of 178 stdio. h header file 173 stdout 177
Strling's formula 333 Stone, Harold 200 stopping a program 7, 34 stopping
output, ctl-s 8, 15 strehr 218 stremp 175 stream editor, sed 101 str 1n index
function 192 string concatenation, awk 125 string functions, table of 176
strings, awk 119, 125 strlen 183 strnemp 192 structure, directory 48
structure, file 41, 47 stty command 5, 35, 43 stty -tabs 5, 43 style command
313 su command 52 sub-shell 81,85,89,91, 151, 169 substr function, awk
117 super-user 52. 191 sv command 217 sv, design of 217 sv function 218
sv ma1n function 217 syntax errors, yae 240 syntax, shell for 95, 144
syntax, shell until 145 syntax, shell while 144 sys_err11st 206 sys_nerr
206 system 184, 220 system bug 185, 223 system call error status 206
system call, interrupted 228 system call, read 44 system call,

n11nk 195 system crash 12, 64 system dependency 6 system function 224,
229 system startup 63, 67 System V x, 78, 125, 140, 141 Szymanski, Tom
200 \ t tab convention 43 . ta command, troff 301 tab convention, \ t 43 tab,
Ctl-1 2 tab stops 5 tab stops, setting 43 table of awk functions 123 table of
awk operators 119 table of awk variables 119 table of etype tests 174 table
of directories 63 table of ed commands 327 table of ed line numbers 327
table of ed regular expressions 324 table of file commands 21 table of hoc
constants 246, 330 table of hoc functions 330 table of hoc operators 330
table of hoc sizes 283 table of hoc times 284 table of I/O timing 203 table
of rom commands 297 table of InS commands 296 table of regular
expressions 105

table of sed commands 112 table of shell \$ { . } variables 149 table of shell metacharacters 75 table of shell patterns 136 table of shell redirections 94 table of shell variables 135 table of signal numbers 150 table of standard I/O functions 192 table of stdio. h definitions 178 table of string functions 176 table of troff f names 298 tabs command 5 tagged regular expression 105, 324, 326 tail command 19 tail -f 204 ta1l

n 20 tai 1 -r 122 tbl example 303 tee command 72 TERM shell variable 37, 159 terminal echo 2, 43 terminate signal 225 terminator, newline as 44 test I negation 143 test command 140 test -f 140 test -r 140 test -t 151 test -w 140 test -x 140 test -z 154 TEX formatter 314 text editor 11 text files 47 Thompson, Ken vii, x, 39,70, 204,219,231,315,319 Tilson, Mike x time command 69,92 t1meout command 230 times command 152 times, file 57 times, table of hoc 284 timing, doctype 307 timing, table of I/O 203 /tmp directory 63, 146 %token 238, 243 token, lexical 235 tools viii, 170, 171,233,287 touch command 162 tr command 107 trace, stack 188 trap command 150 tree, parse 238, 254 troff \\$ command 301 troff \& command 298, 304 troff . bp command 301 troff . br command 300 troff character names 297 troff f command 292, 306 troff . de command 301 troff \e command 298 troff \f command 291, 299 troff . f 1 command 300 troff formatter 289 troff . ft command 291, 301 troff f, getting backslash into 298 troff input 290 troff f -m 292 troff macro arguments 301

troff macros, defining 301 troff names, table of 298 troff . nf command 300 troff number register 296 troff . ps command 301 troff quotes 295 troff \s command 300 troff . sp command 301 troff . ta command 301 true command 147, 149 tty command 68 ttY1n function 184, 185 Tukey, Paul x %type 243 type coercion 211, 264 type-ahead 7 types, file 47 types. h 209 types. h header file 214 Ullman, Jeff 287 unary minus, hoc1 240 undefined variable 251, 276 undo command, ed 323 ungetc 270 %union 242, 243, 251, 274 un1q -c 107 un1q command 106 uni q -d 107 un1q -u 107 uni ts command 39 /unix 23, 63 UNIX and the Echo 78 UNIX, meaning of vii, 1 unlink system call 195, 206 unpaddable blank 299 until syntax, shell 145 USENET 10 user, root 55 user-id 52 /usr directory 22, 48, 65 /usr /bin directory 24, 37, 65, 142 /usr /dict/words dictionary 104 /usr /games

directory 25, 90 /usr/games permissions 56 /usr/include directory 173 /usr/man directory 308 /usr/pub/ascii 42 /usr/src directory 48 uucp command 39 Van Wyk, Chris x, 314 variable initialization, awk 118, 119 variable, undefined 251, 276 variables, shell 36, 88 variables, table of awk 119 variables, table of shell 135 varpush function, hoc4 263 varread function 283 V1 screen editor 11 vis command 173, 175, 178 vis, design of 172, 174, 179, 185 vi s function 179 vi s main function 178 V1S -s 174 w command, sed 112 wai t command 34 wa it status return 222 wai t system call 222 wa1tfile command 222 warning function, hoc 1 240

INDEX 357

watchfor command 145 watchwho command 147 wc command 18 wc -l 30, 80 Wehr, Larry x Weinberger, Peter x, 131, 231 W eythman, Jim x which command 141, 143 while code generation 268 wh1le statement, awk 121 while syntax, shell 144 whilecode function 271, 281 who am i command 5 who command 5 word separators, shell 86 word, shell 71, 95, 157 wordfreq command 124 words, counting 18 working directory 21 write command 9 wr1te error 219 wr 1 te protocol 9 wr i te system call 202 Writer's Workbench 313 . y filename convention 236 yacc command 240 yacc -d 247, 255 yacc input form 236 yacc macros 255 yacc output form 236 yacc overview 235 yacc parsing process 237 yacc stack 238 yacc syntax errors 240 yacc -v 254 yacc value, \$n 237) FLAGS 255 y.tab.c 236 y. tab. h 247, 265 yyerrok 244 yyerror function, hoc 1 240 yylex 236 yylex function, hoc 1 239 yylex function, hoc2 245 yylex function, hoc3 251 yylex function, hoc4 261 yylex function, hocS 270 yylex function, hoc6 277 yylval 239, 244 yyparse 235, 239 yytext 256 zap bug 186 zap command 157, 158, 191 zap, design of 198 zap main function 191 zero i-number 59