Actionability as an Explanation of Grid Cells: A Critical Review of Dorrell et al. (2023)

Tafara Chibanda (2683459)
University of the Witwatersrand

Nathan Le Roux (2717495)
University of the Witwatersrand

Summary

Dorrell et al. (2023) ask why spatial representations should take the form of grid cells: neurons whose firing fields repeat on a hexagonal lattice. Their proposal is that a useful representation must preserve the consequences of actions. Moving by a given displacement should update neural activity through the same linear transformation wherever the movement begins. Combining this *actionability* requirement with non-negative, bounded activity and an objective that separates distinct locations produces grid-like codes in their simulations. Representation theory restricts the code to combinations of spatial waves; the authors then explain how the other constraints favour frequency lattices and, in suitable regimes, hexagonal grids and multiple modules. Predictions concern field width, relative module orientation, and adaptation to room geometry. The paper's central contribution is an interpretable account of why these representations may be useful, rather than a detailed circuit or learning mechanism.

Originality

Earlier continuous-attractor models explained grid activity and velocity integration (Burak and Fiete, 2009), while task-trained networks produced grid-like units for navigation (Banino et al., 2018). More directly, Gao et al. (2021) already connected path integration to group representations and linear transformations, alongside isotropic scaling. Neither grid formation nor the group-theoretic perspective is therefore entirely new. Dorrell et al. combine actionability with functional and biological constraints to explain several features, including modules, without the additional isotropy constraint (Appendix H). This unification is the distinctive contribution.

This is a more abstract approach than specifying synaptic connectivity or training a complete navigating agent. Its advantage is that it separates a computational requirement from a particular implementation: several circuits could realise the same useful code. The framework also extends beyond planar position to variables with other transformation groups. However, it is not more general in every respect. Requiring a location-independent *linear* action on activity is a substantive restriction; representations that use context-dependent or nonlinear updates are outside the analysed class. Periodic components are therefore partly a consequence of the chosen mathematical formulation, even though hexagonal organisation is not directly imposed.

The claim of *minimal constraints* is best read as applying to this modelling framework. The ablations in Appendix I strengthen the argument that the chosen ingredients matter within it. They do not establish that these are the uniquely necessary assumptions across all possible neural mechanisms. The paper would be stronger if this distinction were made as prominent as the unifying claim.

Clarity

The progression from angular representations to two-dimensional space is effective. It gives the reader a concrete interpretation of actionability before introducing the more demanding representation-theoretic argument. Figure 4 is particularly helpful: the frequency-space explanation connects the two spatial lengthscales to the preference for a hexagonal lattice. Figure 5 then separates the model's predictions into identifiable experimental questions. These illustrations make the mathematical framework more accessible.

Some practical details are harder to reconstruct. Figure 8 describes the spatial-resolution comparison, while the principal parameter table in Appendix B.3 concerns Figure 2B; Appendix B.4 notes further adjustments to optimisation settings. A configuration file for each figure would make the chain from equations to results easier to follow. There is also a potentially consequential distinction between the main-text integral normalisation and the sampled sum in equation 22: the numerical scale of neural distances, and therefore of σ, depends on the convention.

The public code helps, but does not resolve every ambiguity. In the inspected version (commit 940659e), the norm routine forms normalised responses and subsequently aggregates unnormalised responses, whereas equation 25 uses normalised responses. Its `sigma_sq` argument also needs to be distinguished from the paper's σ. These observations call for clarification of the exact figure-generating setup, rather than a conclusion that the reported results are wrong.

Quality

A major strength is the combination of analytic reasoning, numerical optimisation, and biological predictions. The frequency-space account explains why non-negativity, location discrimination, and actionability can interact to produce structured codes. The parameter studies and ablations go beyond presenting a single at-

tractive firing map. The authors also acknowledge limitations, including firing-field intensity variation and distortions in irregular environments.

The account of modules is particularly useful. Harmonic components help individual neurons construct non-negative, peaked responses, while harmonically unrelated frequencies help a population distinguish locations that would otherwise share a code. Modules provide a way to accommodate both demands. This connects a population-level objective to single-cell tuning, although the numerical evidence for several clean hexagonal modules is less robust in some parameter regimes, as Appendix B.4.2 acknowledges.

The abstraction is appropriate for asking what makes a representation useful. It is less sufficient for explaining how a rodent learns and maintains that representation. The optimiser has access to position samples and an explicitly specified objective; the paper does not demonstrate a biologically local learning rule or noisy velocity integration in a circuit. Boundedness and non-negativity are reasonable biological constraints, but they do not specify spiking variability, sensory correction, or connectivity. Accordingly, obtaining an optimal code does not establish that an animal can learn it or use it robustly.

The supporting evidence also varies in strength across claims. The mathematical restrictions on admissible codes are more direct than the claim that hexagonal grids globally minimise the full objective. Several lattice arguments are heuristic, and Appendix G acknowledges the non-convex frequency-selection problem and the need for further tools to prove optimality. The simulations support a plausible explanation, rather than a general certificate of the optimum. Appendix B.4 also distinguishes optimisation parameters from parameters defining the objective. That distinction is useful theoretically, but practical reliability still matters when simulation is used as evidence. Reporting distributions across initialisations, constraint residuals, and convergence diagnostics alongside the maps would clarify this boundary.

Finally, the comparisons with biological data are encouraging rather than decisive. The authors describe several as rudimentary. For example, the relationship between field width and recorded cell counts depends on assumptions about sampling neurons across modules. Agreement in a qualitative trend cannot by itself distinguish the proposed explanation from alternatives. Our own unsuccessful reproduction, described below, reinforces the need for numerical clarity but does not refute the theoretical argument.

Significance

The strongest prospective contribution is a set of interpretable links between representational demands and measurable neural organisation. This complements circuit models: the theory proposes which codes are useful, while mechanistic models can investigate whether plausible networks can implement them. Recordings showing toroidal population structure in grid-cell modules (Gardner et al., 2022) make this relationship between population geometry and neural dynamics especially relevant. Such evidence is compatible with the framework, but does not uniquely verify its objective.

A concrete theory–experiment loop follows from the prediction about room geometry. Record the same modules in an arena before and after a controlled change in aspect ratio, measure occupancy, and predict how field spacing and orientation should change under the model. Fit any free parameters using the original environment and assess predictions in the changed environment, rather than refitting each condition. The paper predicts that some codes can remain stable when they are suitable for both geometries, while others should adjust. Comparing that pattern with a competing model would be more informative than checking whether both produce grids.

A useful refinement would separate changes in physical boundaries from changes in sampled occupancy, because the theory expresses environmental effects through $p(x)$. Persistent disagreement after accounting for occupancy would motivate adding sensory anchoring or learning-history effects. This would allow experiments to modify the assumptions of the model, completing the loop. The present work offers valuable hypotheses for this process; it does not yet provide a validated account of all environmental responses.

Reproducibility

We implemented a restricted test of Figure 8: $N = 64$, 31 learned frequency pairs, $\sigma = 0.4$, and $l = 0.5$ versus $l = 0.1$. Each seed-0 run used 150,000 updates. The implementation follows the sampled original-room normalisation in equations 22–25 and checks constraints in shifted rooms. Independent loss, gradient, translation, and checkpoint-continuation tests support the implementation, but cannot certify convergence.

This is an explicitly specified interpretation, not an exact rerun of the authors' code. In particular, we used a norm-loss target of 0.02; this is our numerical choice, not a reported Figure 8 setting. Other conventions and departures are recorded in the repository. Both final populations showed elongated periodic patterns rather than a clean hexagonal baseline (Figure 1). Median descriptive grid scores were 0.0503 and 0.00884 respectively. Mean negative-activity penalties met their tolerance, but 3.61% and 5.08% of sampled rates were still below -10^{-6}. The $l = 0.5$ run also exceeded our norm-error target (Table 1).

We corrected an initially undersampled plotting grid using the learned frequencies and evaluated both final checkpoints on the same finer grid. No training result

was changed by this correction. Grid scores are descriptive, without a shuffled significance test, and neurons within one trained population are not independent repetitions. With one seed per condition and an unsuccessful baseline, these results do not establish the predicted dependence on l or demonstrate that the paper is irreproducible.

The useful outcome is a reproducible audit of assumptions and failure modes. On identical small float64 inputs, the two independently written implementations agree on the three unweighted losses to within 3×10^{-13}. After explicitly aligning their functional-loss weighting, directional derivatives agree with the independent finite-difference reference to within 6×10^{-11}. This checks equations on that fixture, not equivalence of the full training procedures: initialisation, norm targets, and Adam conventions still differ.

We then completed nine 150,000-step runs: baseline, $\sigma = \sqrt{0.4}$, and norm target $\exp(4)$, with three matched seeds and otherwise fixed settings. On a common evaluation grid, changing sigma modestly increased descriptive scores in each pair but did not establish a hexagonal baseline. Relaxing the norm target produced much larger held-out norm errors (1.77–3.87 versus 0.0209–0.0301 for baseline). None met both original tolerances (Figure 2). These isolated changes do not resolve our reproduction, but three seeds and our chosen tolerances cannot establish failure of the published model.

A constructed-control check also qualifies our tolerance choice. A known non-negative hexagonal code, whose exact Gaussian room energy was nearly translation-invariant (relative error below 7.2×10^{-8} in the tested rooms), had mean sampled norm penalties of 0.0961, 0.0274 and 0.00644 for 50, 150 and 600 points over 128 batches (Figure 3). Thus our 0.02 target can penalise valid geometry through sampling variation. This is a diagnostic control, not a learned result or proof of the cause of training failure.

References

Dorrell, W., Latham, P. E., Behrens, T. E. J., & Whittington, J. C. R. (2023). Actionable neural representations: Grid cells from minimal constraints. *International Conference on Learning Representations*. https://arxiv.org/abs/2209.15563

Burak, Y., & Fiete, I. R. (2009). Accurate path integration in continuous attractor network models of grid cells. *PLoS Computational Biology, 5*(2), e1000291. https://doi.org/10.1371/journal.pcbi.1000291

Banino, A., Barry, C., Uria, B., et al. (2018). Vector-based navigation using grid-like representations in artificial agents. *Nature, 557*, 429–433. https://doi.org/10.1038/s41586-018-0102-6

Gao, R., Xie, J., Wei, X.-X., Zhu, S.-C., & Wu, Y. N. (2021). On path integration of grid cells: Group representation and isotropic scaling. *Advances in Neural Information Processing Systems, 34*. https://arxiv.org/abs/2006.10259

Gardner, R. J., Hermansen, E., Pachitariu, M., Burak, Y., Baas, N. A., Dunn, B. A., Moser, M.-B., & Moser, E. I. (2022). Toroidal topology of population activity in grid cells. *Nature, 602*, 123–128. https://doi.org/10.1038/s41586-021-04268-7

Contribution statement

Tafara Chibanda and Nathan Le Roux implemented the model independently. This draft reports Tafara's saved reproduction runs and a shared-input numerical audit of Nathan's code at commit 7db3147. It does not merge the two implementations or compare their trained maps on unequal settings. Both authors must confirm the final account of their contributions and the review's judgements before submission.

AI assistance disclosure

OpenAI Codex assisted with literature checking, implementation, tests, analysis, and drafting this review. This disclosure is not a signed declaration of the authors' verification or a replacement for the required Wits Science Faculty AI Ethics Form. Both authors need to review the text, adopt or revise its judgements, and complete the official form.

Appendix: Evidence for the reproduction section

Table 1: Final seed-0 checkpoints after 150,000 steps. Constraint measurements use eight held-out batches. Tolerances are $\exp(-9)$ for the mean negative-activity penalty and 0.02 for the norm loss; the latter is our implementation choice. These are descriptive single-run results.

Measurement	$l = 0.5$	$l = 0.1$
Median descriptive grid score	0.0503	0.00884
Mean negative-activity penalty	0.0000996	0.0001106
Mean squared shifted-room norm error	0.03011	0.01950
Mean negativity target met	Yes	Yes
Norm target met	No	Yes
Sampled rates below -10^{-6}	3.61%	5.08%




Figure 1: The two completed reproduction runs. Neuron 0 is shown by a fixed index choice, with its spatial autocorrelation and the distribution of scores across all 64 neurons. The elongated periodic patterns and near-zero median scores do not establish a hexagonal baseline. Rate-map colour scales differ between panels. Maps use 320 samples per axis over $[-1.5, 1.5]^2$; the evaluator checks that learned frequencies are resolved.

Appendix: Controlled diagnostics and calibration




Figure 2: All nine final checkpoints, each trained for 150,000 steps. Lines connect matched seeds; initial states are identical within each seed. Only the named setting changes: baseline uses $\sigma = 0.4$ and norm target 0.02; sigma_variance uses $\sigma = \sqrt{0.4}$; norm_table uses norm target $\exp(4)$. All evaluations use the same 352-by-352 grid over $[-1.5, 1.5]^2$ and held-out samples. Negative rates are those below -10^{-6}. The norm axis is logarithmic. Descriptive grid scores have no shuffled significance calibration. The relaxed-target condition is not a full rerun of the authors' public code.




Figure 3: The constructed-code check discussed in the reproduction section. Left: one fixed-index neuron from a deliberately constructed, non-negative hexagonal population; no training is involved. Centre: the sampled norm penalty decreases with the number of positions used to estimate room energy. Error bars are one standard error across 128 independent sampling batches for the fixed code. Right: the distribution at 150 points shows why our chosen 0.02 threshold can be exceeded even with valid geometry. These sampling batches are not independent training seeds.

NeurIPS checklist: reproduction submission

Answers apply to our reproduction, not to Dorrell et al.'s paper. The questions below are abbreviated and paraphrased from the NeurIPS checklist. Author-dependent declarations remain unconfirmed.

1. **Are the claims supported and appropriately scoped? Yes.** The review distinguishes the paper's claims, our limited reproduction, and proposed follow-up work. No successful hexagonal baseline is claimed.
2. **Are limitations explained? Yes.** The reproduction section reports one seed per original spatial-scale condition, three matched seeds in the diagnostic study, numerical departures, unmet constraints, and descriptive rather than inferential grid scores.
3. **Are new theoretical claims proved? N/A.** We introduce no new theorem; the reviewed theory is attributed to Dorrell et al.
4. **Can the numerical findings be checked? Yes.** Saved initial/final checkpoints, configurations, metadata, evaluation summaries, and tests accompany the code. Reproduction instructions are in the repository README.
5. **Are code, inputs, and instructions available? Yes.** The branch codex/independent-reproduction contains the original implementation and results. Synthetic positions are generated from recorded seeds; no external dataset is required. Include the updated source with the submission.
6. **Are experimental choices documented? Yes.** The reproduction section and `references/implementation_notes.md` identify the sampling scheme, budget, optimiser, targets, and deviations. Configurations accompany each checkpoint.
7. **Is uncertainty quantified statistically? No, not for the trained models.** The spatial-scale comparison has one seed per condition; all three seed outcomes are shown for the diagnostics without inferential intervals. Neurons are not treated as independent runs. The constructed control reports sampling standard errors across 128 batches, not training uncertainty.
8. **Are computing requirements fully reported? No.** The original CPU runs each took approximately 9.3 minutes concurrently; the nine diagnostic training durations sum to 71.2 minutes across processes with two workers. Software and hardware metadata are saved. Peak memory, evaluation cost and total preliminary compute were not fully measured.
9. **Have the authors confirmed compliance with the ethics code? No; pending author confirmation.** This draft cannot attest that both students have read the code. No new human or animal experiment was conducted.
10. **Are application-specific societal risks discussed? N/A.** This is a small synthetic modelling exercise without a deployed application or personal data. Its immediate risk is scientific overinterpretation, addressed through explicit limits on claims.
11. **Are special release safeguards required? N/A.** The released artefacts are a small spatial representation model and synthetic numerical results.
12. **Are all asset permissions and licences verified? No.** Sources are credited and the model code was independently written, but a complete dependency/licensing audit and a repository redistribution licence remain outstanding before an upstream contribution. The course template is used for its supplied purpose.
13. **Are newly released artefacts fully documented? No.** Methods, configurations, checkpoints, and limitations are documented; redistribution licensing is still unresolved.
14. **Are human-participant instructions and compensation described? N/A.** No participants or crowdworkers were recruited.
15. **Was participant ethics approval obtained where needed? N/A.** No human-subject research was performed, and no new animal data were collected.
16. **Is substantive LLM assistance disclosed? Yes.** The AI assistance disclosure identifies assistance with code, analysis, literature checking, and drafting. The signed institutional form must still be completed by the authors.