

# Computing Methods for Physics – 14 June 2022

**Your exam material (code files, plots, datafiles, etc.) must be submitted via google classroom by 13:00 as a single zip file.**

**C++ evaluation will be based on:** correct syntax, proper return types, proper arguments of functions, data members and class interfaces, comments throughout the code, separation of class implementations and interfaces.

**Python evaluation will be based on:** correct syntax, avoiding C-style loops, using Python features in general, comments throughout the notebook/scripts, labels, legends and plot styling and clarity in general.

## Part 1 – Binary Black Holes in C++

Implement a C++ class to represent black holes. A black hole is fully described by its gravitational mass  $m$ , which we will handle as a multiple of the solar mass, and its dimensionless rotational angular momentum parameter  $\chi \in [0, 1]$ . Given these two parameters, one can define the irreducible mass of a black hole,

$$m_{\text{irr}}^2 = \frac{m^2}{2} \left[ 1 + \sqrt{1 - \chi^2} \right],$$

and the energy  $E_{\text{Penrose}} = m - m_{\text{irr}}$  that may be extracted from it. Your BH class must have:

- Constructors (when the user only provides  $m$  assume  $\chi = 0$ , when the user only provides  $\chi$  assume  $m = 1$ ); the user should be allowed to construct a black hole using any two parameters in the set  $\{m, m_{\text{irr}}, \chi\}$ .
- A copy constructor.
- A `Print()` method that informs about the values of  $\{m, m_{\text{irr}}, \chi, E_{\text{Penrose}}\}$ .
- Setter and getter methods.

Build a second C++ class capable of representing a binary black hole system. This must be able to handle a pair of BH instances. The requirements for the BBH class are the following:

- It must include a copy constructor.
- It must include a constructor that takes as arguments two gravitational masses, two dimensionless rotational angular momentum parameters, and two angles  $\theta_1$  and  $\theta_2$ . The angles are between 0 and  $\pi$ . There is no request to implement other constructors.
- It must have an attribute that represents the effective rotational angular momentum

of the binary black hole. This is defined as

$$\chi_{\text{eff}} = \frac{\chi_1 m_1 \cos \theta_1 + \chi_2 m_2 \cos \theta_2}{m_1 + m_2} .$$

- It must have a `Print()` method that informs about the individual black holes as well as  $\{\chi_{\text{eff}}, \theta_1, \theta_2\}$ .

**Your submitted material must include a file `app.cpp` that showcases the classes you implemented.**

## Part 2 – Binary Black Holes in Python

Use a Python notebook or Python scripts to complete the following tasks **with dictionaries**.

1. Draw  $N = 10^4$  random values of  $\{m_1, \chi_1, m_2, \chi_2, \theta_1, \theta_2\}$ , which have the same meaning as in the previous sections. Draw the  $\chi_i$ 's uniformly, the  $\theta_i$ 's uniformly in their cosine, and the  $m_i$ 's uniformly between 10 and 100 (solar masses).
2. Calculate and store the values of:  $\chi_{\text{eff}}$ , the total mass  $M = m_1 + m_2$ , the symmetric mass ratio

$$\eta = \frac{1}{4} \frac{m_1 m_2}{M^2} ,$$

the chirp mass

$$\mathcal{M} = \frac{(m_1 m_2)^{3/5}}{M^{1/5}} ,$$

and the time spent (in seconds) by the binary black hole in the sensitivity band of current gravitational-wave detectors:

$$t_c = \frac{50}{256} \frac{r_0^4}{m_1 m_2 M} \nu_{10} \quad \text{where} \quad r_0 = \left( \frac{M}{\pi^2 \nu_{10}^2} \right)^{1/3} \quad \text{and} \quad \nu_{10} = 4.916 \cdot 10^{-5} .$$

3. Plot the distributions of these 5 quantities.
4. Use `scipy.optimize.curve_fit` to fit the  $\chi_{\text{eff}}$  data with a Lorentzian Function

$$L(x) = \frac{1}{\pi} \frac{\Gamma}{(x - x_0)^2 + \Gamma^2} .$$

Plot your data and your fit.