Assignment # 01 - Report

Data Science Tools & Techniques (MS DS)

Name: Taha Abbas Naqvi
Roll No: 261-8004
Class: MS (DS)
Section: A

Task 1: Pre-processing

The two datasets are broken in different ways, so they needed different treatment.

The attached dataset has bad values. The word "unknown" was used instead of a blank in annual_income and credit_score, so pandas read both of them as text and they did not even show up in describe(). There were also 1509 empty cells across six columns, 49 duplicated rows, and the same country written three ways (us, USA, U.S.). Some values are not possible at all: hours_per_week goes up to 391 when a week only has 168 hours, BMI reaches 204, twelve salaries are negative, and 1926 people have more years of work experience than their age minus 16.

The cleaning order was: replace the sentinel and fix the data types, drop duplicates, set out of range values to NaN, cap the money columns at the 1st and 99th percentile, and only then impute, using the median for numbers and the mode for categories. Imputing first would have been a mistake, because the medians would then be calculated from the corrupt values.

The census dataset is the opposite case. Its values are fine but the structure is difficult. There is no header row, so the column names came from census-income.names. Missing values are written as "?" (415717 of them), and thirteen columns are full of "Not in universe", which is not missing data at all. It means the question did not apply to that person, so I kept it as a normal category.

There are 46627 duplicate records once the survey weight is ignored, and that weight, instance_weight, must not be used as a feature because it says how many people each row stands for. Five more columns look numeric but are really codes, and four money columns are 89 to 98 percent zeros.

For encoding I picked the method per column rather than using one method everywhere. Education, smoking status and physical activity have a real order, so they got integer codes. Two level variables got a single 0/1 column. Short nominal lists got one hot encoding with drop_first, so the dummies are not

perfectly collinear. For the nine census columns with many levels, such as the 51 states and the 43 birth countries, one hot would have added around 220 almost empty columns, so I used frequency encoding there.

Task 2: EDA before and after

The first EDA pass is what made the issue lists possible. info() exposed the two columns whose type gave away the hidden sentinel, the missing value report showed where the gaps were, the boxplots showed the impossible BMI and hour values, and the skew numbers (16.1 for annual_income, 27.8 for dividends) showed how far the tails were pulling the averages.
The second pass shows the result: no missing cells, no duplicates, no text columns left, features on a comparable scale, and skew down to 0.1 and 2.6. The shape of the sensible part of each distribution is unchanged, so the cleaning removed noise and not the pattern.
One choice was made by testing instead of by habit. A log transform of income is the usual advice, but after capping, the skew was already near zero and the log pushed it to -1.3, so I left it out.

Why this matters

Almost a quarter of the census rows were duplicates, and left alone they would make whatever pattern they carry look more certain than it is. One stray string turned a numeric column into text. Features that differ by four orders of magnitude dominates any model based on distances or gradients. Pre-processing decides whether the analysis that follows measures the data or the mistakes in the file.