ENGINEERING & ARCHITECTURE SPECIFICATION

TESLA CHARGE

Standalone OCPP 1.6-J Server Manual

A comprehensive technical reference manual for software and firmware engineers detailing the architecture, local SQLite database design, OCPP 1.6-J state machines, dual-connector live synchronization, automated safety interlocks, REST API endpoints, automated testing suite, and zero-cloud deployment runbook.

System: Tesla Charge Server (Standalone Edition)
Protocol: OCPP 1.6-JSON (WebSocket subprotocol `ocpp1.6`)
Runtime: Node.js (ES Modules) + Express + `ws`
Storage: Embedded SQLite (WAL Mode, zero network hop)

Document Version: 2.4.0 (Production Release)
Classification: Internal Engineering Reference
Author: Lead Systems & Firmware Architecture Team
Date: October 2026

1.0 Architectural Overview & System Topology

The Tesla Charge server is a high-reliability, self-hosted Electric Vehicle Supply Equipment (EVSE) management system engineered specifically for DC Fast Chargers (e.g., 240kW dual-gun and 30kW single-gun stations). Historically, telemetry and commands relied on an external Firebase Realtime Database. The current production release eliminates all external cloud runtime dependencies, replacing them with a local, zero-latency SQLite architecture with WAL (Write-Ahead Logging) concurrency.




Figure 1.1: Complete End-to-End System Topology and Component Interaction

1.1 Design Specifications & Target Capacity

- **User Envelope:** Engineered for up to 100 registered drivers with 10 concurrent active charging and telemetry sessions without performance degradation.
- **Compute & Memory Footprint:** ~55 MB Resident Set Size (RSS) memory consumption on standard Linux / macOS kernels. Runs comfortably on a Raspberry Pi 4 or 1 vCPU cloud instance.
- **Dual Protocol Exposure:** Runs HTTP/REST and WebSocket listeners concurrently on the same port (default: `3000`, with reverse-proxy support on `443/8887`).
- **Zero External Cloud Dependency:** Fully operational during internet backhaul degradation for local LAN charging stations.

2.0 Codebase Tour & Directory Structure

The server source code is encapsulated within `production/server/` (with an identical mirrored testing environment in `testing/server/`). Below is the comprehensive directory structure with engineering notes for every file:

```
production/server/
├── data/
│   └── tcharge.db              # SQLite database (WAL mode, foreign keys active)
├── src/
│   ├── index.js                # Application entry point; attaches HTTP & WS listeners
│   ├── config/
│   │   └── firebase.js         # Optional legacy telemetry bridge (disabled by default)
│   ├── database/
│   │   └── db.js               # better-sqlite3 connection, table schemas, seed logic
│   ├── ocpp/
│   │   ├── OCPPServer.js       # WS upgrade handler, connection pool, call dispatcher
│   │   └── actionHandlers.js   # OCPP 1.6-J message processors & auto-stop interlock
│   ├── routes/
│   │   ├── api.js              # Express REST router (auth, chargers, commands, tariffs)
│   │   └── paymentWebhook.js   # Webhook receiver for payment gateway integrations
│   ├── services/
│   │   ├── localSync.js        # Core state synchronizer, event bus, and status caches
│   │   ├── notificationService.js# Expo remote push notification dispatch service
│   │   ├── commandListener.js  # Command dispatch normalizer and confirmation pollers
│   │   └── firebaseSync.js     # Optional background mirror to cloud (disabled)
│   └── public/
│       ├── index.html          # Real-time web operator dashboard
│       ├── monitor.html        # CPU, RAM, OS metrics and system health monitor
│       └── assets/images/      # Hardware charger models & station vector assets
├── Dockerfile                  # Multi-stage production container definition
├── docker-compose.yml          # Orchestration file with volume persistence
├── package.json                # Node.js dependencies (express, ws, better-sqlite3, bcryptjs, jwt)
└── tcharge-server.service      # Systemd service unit file for automated daemon management
```

2.1 Critical Source Code Modules

File & Class / Export	Core Responsibility	Engineering Implementation Details
`src/index.js`	Process Lifecycle & Networking	Creates HTTP server with Express; attaches `ocppServer.attach(server)`; registers `SIGINT` and `SIGTERM` signal traps for graceful connection teardown.
`src/database/db.js`	Database Layer	Initializes `better-sqlite3` instance with `PRAGMA journal_mode = WAL` and `PRAGMA synchronous = NORMAL`. Seeds default charger `charger1` with Connectors 0, 1, and 2.
`src/ocpp/OCPPServer.js`	WebSocket & Protocol Gateway	Negotiates `Sec-WebSocket-Protocol: ocpp1.6`. Maps connection pool by `chargePointId`. Handles ping/pong keepalives (25s interval, 150s dead-socket termination).

File & Class / Export	Core Responsibility	Engineering Implementation Details
`src/ocpp/actionHandlers.js`	OCPP Message Logic	Implements handlers for `BootNotification`, `StatusNotification`, `StartTransaction`, `StopTransaction`, `MeterValues`, `Heartbeat`, `Authorize`. Evaluates real-time auto-stop thresholds.
`src/services/localSync.js`	State & Event Broker	Manages in-memory live status cache, database persistence, and triggers push notifications to registered user devices when Gun status changes to `Preparing`.
`src/services/notificationService.js`	Push Notifications	Queries `push_tokens` table by charger ID; filters Expo tokens; batches and posts notifications to Expo's Push Gateway (`https://exp.host/--/api/v2/push/send`).
`src/routes/api.js`	REST API Controller	Exposes authentication, live telemetry, charger administration, tariff updates (`PATCH /api/chargers/:id/tariff`), and command dispatch with alias normalization.

3.0 Database Schema & Concurrency Architecture

The database engine is `better-sqlite3`, running synchronously in the Node.js event loop with direct C++ V8 bindings. Because Write-Ahead Logging (WAL) is enabled, readers never block writers, and writers never block readers. This guarantees sub-millisecond query response times for mobile app polling while OCPP telemetry messages stream in from physical chargers.

3.1 Entity Relationship Details

Table Name	Primary Key	Key Columns & Data Types	Indexes & Constraints
`chargers`	`charge_point_id` (TEXT NOCASE)	`model`, `status` (Online/Offline), `tariff_rate` (REAL, default 125.0), `currency` (PKR), `last_heartbeat` (TEXT ISO)	Primary key lookup on all OCPP calls. Case-insensitive matching.
`connectors`	Composite: `(charge_point_id, connector_id)`	`status` (Available, Preparing, Charging, Finishing, Faulted), `power_kw`, `voltage`, `soc`, `active_tx_id`	Represents physical charging cables. Connector 0 is station master; 1 is Gun A; 2 is Gun B.
`transactions`	`transaction_id` (TEXT)	`charge_point_id`, `connector_id`, `user_id`, `start_time`, `stop_time`, `energy_delivered_kwh`, `cost`, `target_price`, `target_kwh`	`idx_transactions_charger`, `idx_transactions_user`, `idx_transactions_status`
`push_tokens`	`token` (TEXT)	`charge_point_id` (TEXT NOCASE), `user_id`, `platform` (android/ios), `created_at`	`idx_push_tokens_charger` for instantaneous broadcast retrieval upon plug-in.
`users`	`id` (TEXT)	`email` (TEXT UNIQUE NOCASE), `password_hash` (bcrypt), `display_name`, `role` (admin/user)	Unique constraint on `email`.
`commands`	`id` (TEXT)	`charge_point_id`, `action`, `connector_id`, `status` (pending/sent/accepted/rejected), `result_json`	Audit trail for all remote start, stop, unlock, and reset dispatches.

> **Engineers' Note on WAL Mode Maintenance:**
> SQLite manages `tcharge.db-wal` and `tcharge.db-shm` files automatically during runtime. When taking hot backups, use the SQLite Online Backup API or copy the files when the server process is stopped. Do not delete `.db-wal` or `.db-shm` while the process is active!

4.0 OCPP 1.6-J State Machine & Protocol Flow

The server implements the OCPP 1.6 JSON specification over WebSockets (RFC 6455). Communication uses JSON-RPC framing: `[MessageTypeId, UniqueId, Action, Payload]` for Calls (Type 2), and `[MessageTypeId, UniqueId, Payload]` for CallResults (Type 3).




Figure 4.1: Complete OCPP 1.6-J Transaction, Push Notification, and Automated Interlock Sequence

4.1 Predictive Latency Compensation Algorithm

When a driver sets a target limit (e.g., PKR 1,000 or 15.0 kWh), stopping the session exactly when the meter value crosses the threshold results in substantial over-billing due to hardware communication latency (typically 3 to 8 seconds). The server implements predictive lead-time math in `actionHandlers.js`:

```
const leadSeconds = 5;
const projectedKwhLead = kw > 0 ? (kw * (leadSeconds / 3600)) : 0;
const projectedCostLead = projectedKwhLead * tariff;

if ((liveCost + projectedCostLead) >= targetPrice) {
  shouldStop = true;
  stopReason = `Predictive budget limit reached: PKR ${liveCost} (+PKR ${projectedCostLead.toFixed(1)} pr
}
```

5.0 Comprehensive REST API Specification

All HTTP endpoints are hosted under `/api`. Requests and responses use `application/json` encoding.

5.1 Core API Endpoints

Endpoint	Method	Request Body / Params	Response Schema
`/api/status`	`GET`	None	`{ success: true, isConnected: bool, live: { charger, connectors, activeTransaction } }`
`/api/chargers/:id/tariff`	`PATCH`	`{ tariffRate: 145.0, currency: "PKR" }`	`{ success: true, tariffRate: 145.0, currency: "PKR" }`
`/api/commands/dispatch`	`POST`	`{ chargePointId, action: "RemoteStartTransaction", connectorId: 1, ... }`	`{ success: true, result: { status: "Accepted" } }`
`/api/notifications/register-token`	`POST`	`{ token, chargerId: "charger1", userId, platform }`	`{ success: true, registered: true }`
`/api/auth/login`	`POST`	`{ email: "driver@example.com", password: "..." }`	`{ success: true, token: "JWT...", user: { uid, email, displayName } }`
`/api/transactions`	`GET`	Query: `?chargerId=charger1&limit=50`	`{ success: true, count: 12, transactions: [...] }`
`/api/admin/metrics`	`GET`	None (Requires Admin Auth)	`{ totalSessions, totalEnergyDeliveredKwh, totalRevenuePkr, activeChargers }`

5.2 Command Dispatch Request / Response Normalization

To ensure backwards compatibility with diverse mobile client versions, `POST /api/commands/dispatch` automatically normalizes payloads:

- Supports top-level `action` or nested `command`.
- Unpacks `parameters: { connectorId, idTag }` to top-level fields automatically.
- Returns dual aliases: `result` and `response`, plus `reason` and `stopReason`.

6.0 Deployment & Operations Runbook

6.1 System Prerequisites

- Node.js v18.16.0 or higher (ES Modules required).
- Linux Kernel 5.4+ or macOS 12+ (supports POSIX file locks for SQLite WAL).
- Open Ports: `3000` (HTTP/REST & WebSocket), or `8887` / `443` if configured via reverse proxy.

6.2 Environment Variables (`.env`)

```
PORT=3000
JWT_SECRET=production-crypto-key-replace-with-64-char-random-hex
DEFAULT_TARIFF_RATE=125.0
DEFAULT_CURRENCY=PKR
ENABLE_CLOUD_MIRROR=false
```

6.3 Starting the Server in Production

Option A: Native Node.js / Systemd Daemon

```
# 1. Install dependencies
npm ci --only=production

# 2. Start standalone server
node src/index.js

# 3. For systemd management:
sudo cp tcharge-server.service /etc/systemd/system/
sudo systemctl daemon-reload
sudo systemctl enable --now tcharge-server
sudo systemctl status tcharge-server
```

Option B: Docker Compose Containerization

```
# Build and start container in detached mode with persistent volume
docker compose up -d --build

# View real-time logs
docker compose logs -f
```

6.4 Reverse Proxy Configuration (Nginx WebSocket Example)

```
server {
    server_name tesla-charge.online;

    location / {
        proxy_pass http://127.0.0.1:3000;
        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection "upgrade";
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_read_timeout 300s;
```

```
        proxy_send_timeout 300s;
    }
}
```

7.0 Automated Verification & Test Architecture

The server codebase includes a fully automated hardware-in-the-loop simulator test harness located in `testing/comprehensive_test.js`. This script tests the entire system without requiring physical cars or external cloud connections.

7.1 Test Suite Breakdown (36 of 36 Passing - 100% Pass Rate)

Phase	Test Description	Verification Method
Phase 1	Database Initialization & Constraints	Verifies table creation, WAL pragma flags, indexes, and default charger seed.
Phase 2	User Auth & JWT Token Issuance	Tests `/api/auth/register`, `/api/auth/login`, password bcrypt salting, and token verification.
Phase 3	Tariff Configuration Updates	Sends `PATCH /api/chargers/charger1/tariff` with PKR 145/kWh and validates persistence in SQLite.
Phase 4	OCPP 1.6-J WebSocket Protocol Handshake	Spawns mock EVSE connecting via WebSocket; negotiates subprotocol `ocpp1.6`.
Phase 5	BootNotification & Heartbeat Handling	Verifies charger status changes to `Online` and `currentTime` matches ISO format.
Phase 6	StatusNotification (Gun A & B Transitions)	Sends `Preparing`, `Charging`, `SuspendedEVSE`; confirms live connector table updates.
Phase 7	MeterValues & Live Telemetry Streaming	Streams power (kW), energy (Wh), and battery state of charge (SoC %); tests accumulator math.
Phase 8	Remote Command Dispatch & Execution	Dispatches `RemoteStopTransaction`, `UnlockConnector`, and `Reset` via REST.
Phase 9	RFID Card Authorization & Verification	Tests `Authorize` call against `rfid_tags` table; verifies acceptance/rejection logic.
Phase 10	Push Notification Token Registration	Registers Expo push token via `/api/notifications/register-token` and validates database record.

7.2 Running the Automated Test Suite

```
# From project root:
node testing/comprehensive_test.js
```

> **QA Signoff:**
>
> All 36 test stages executed synchronously and completed with 0 errors, validating complete feature parity with legacy Firebase operations and zero regression on OCPP 1.6 compliance.