

## Poszukiwanie tekstu pisanego odręcznie

Ten notatnik analizuje metody identyfikowania fragmentów pisanych odręcznie z obrazów zawierających tekst drukowany i pisany odręcznie za pomocą **DCNN**.

Jako wejście algorytm przyjmuje plik png ze zbioru danych IAM z typem danych wejściowych jako formularz oraz typem wyjściowych „bb” i formularz.

Na wyjściu otrzymujemy ramki ograniczające akapity.

```
[2]: import multiprocessing
import time
import random
import os

import matplotlib.pyplot as plt
import matplotlib.patches as patches

import mxnet as mx
import numpy as np
from skimage.draw import line_aa
from skimage import transform as skimage_transform

from mxnet import nd, autograd, gluon
from mxnet.image import resize_short
from mxboard import SummaryWriter

from ocr.utils.iam_dataset import IAMDataset
from ocr.utils.iou_loss import IOU_loss
from ocr.utils.draw_box_on_image import draw_box_on_image

model_checkpoint_folder = "model_checkpoint"
if not os.path.isdir(model_checkpoint_folder):
    os.makedirs(model_checkpoint_folder)

ctx = mx.gpu()
mx.random.seed(42)
```

## Wczytanie zbioru danych

```
[4]: train_ds = IAMDataset("form", output_data="bb", output_parse_method="form",
    ↪train=True)
print("Number of training samples: {}".format(len(train_ds)))
```

```
test_ds = IAMDataset("form", output_data="bb", output_parse_method="form",
    ↪train=False)
print("Number of testing samples: {}".format(len(test_ds)))
```

Processing data:

```
Completed: [----- ] 99%Number of training
    ↪samples: 967
Number of testing samples: 232
```

Zastosowaliśmy dwie transformacje, funkcja „transform” zmienia rozmiar i normalizuje obraz. Funkcja „augment\_transform” losowo przesuwaa obraz i przewidywane pole ograniczające o 5%.

```
[5]: batch_size = 32

random_y_translation, random_x_translation = (0.2, 0.2) # Randomly translate
    ↪the input image
expand_bb_scale = 0.03 # Expand the bounding box to relax the boundaries
```

```
[6]: def transform(data, label):
    '''
    Function that converts "data" into the input image tensor for a CNN
    Label is converted into a float tensor.
    '''
    image = mx.nd.array(data).expand_dims(axis=2)
    image = resize_short(image, int(800/3))
    image = image.transpose([2, 0, 1])/255.
    label = label[0].astype(np.float32)

    bb = label.copy()
    new_w = (1 + expand_bb_scale) * bb[2]
    new_h = (1 + expand_bb_scale) * bb[3]

    bb[0] = bb[0] - (new_w - bb[2])/2
    bb[1] = bb[1] - (new_h - bb[3])/2
    bb[2] = new_w
    bb[3] = new_h

    return image, mx.nd.array(bb)

def augment_transform(data, label):
    '''
```

```

    Function that randomly translates the input image by +-width_range and
    ↪+-height_range.

    The labels (bounding boxes) are also translated by the same amount.
    '''

    ty = random.uniform(-random_y_translation, random_y_translation)
    tx = random.uniform(-random_x_translation, random_x_translation)
    st = skimage_transform.SimilarityTransform(translation=(tx*data.shape[1],
    ↪ty*data.shape[0]))
    data = skimage_transform.warp(data, st)
    label = label.copy()
    label[0][0] = label[0][0] - tx
    label[0][1] = label[0][1] - ty
    return transform(data*255., label)

```

```

[7]: train_data = gluon.data.DataLoader(train_ds.transform(augment_transform),
    ↪batch_size, shuffle=True, num_workers=8)
test_data = gluon.data.DataLoader(test_ds.transform(transform), batch_size,
    ↪shuffle=False, num_workers=8)

```

## Tworzenie sieci

```

[9]: class SegmentationNetwork(gluon.nn.HybridBlock):

    def __init__(self, p_dropout = 0.5, ctx=mx.cpu()):
        super(SegmentationNetwork, self).__init__()

        pretrained = gluon.model_zoo.vision.resnet34_v1(pretrained=True,
    ↪ctx=ctx)
        first_weights = pretrained.features[0].weight.data().mean(axis=1).
    ↪expand_dims(axis=1)

        body = gluon.nn.HybridSequential(prefix="SegmentationNetwork_")
        with body.name_scope():
            first_layer = gluon.nn.Conv2D(channels=64, kernel_size=(7, 7),
    ↪padding=(3, 3), strides=(2, 2), in_channels=1, use_bias=False)
            first_layer.initialize(mx.init.Normal(), ctx=ctx)
            first_layer.weight.set_data(first_weights)
            body.add(first_layer)
            body.add(*pretrained.features[1:6])

        output = gluon.nn.HybridSequential()

```

```

        with output.name_scope():
            output.add(gluon.nn.Flatten())
            output.add(gluon.nn.Dense(64, activation='relu'))
            output.add(gluon.nn.Dropout(p_dropout))
            output.add(gluon.nn.Dense(64, activation='relu'))
            output.add(gluon.nn.Dropout(p_dropout))
            output.add(gluon.nn.Dense(4, activation='sigmoid'))

        output.collect_params().initialize(mx.init.Normal(), ctx=ctx)
        body.add(output)
    self.cnn = body

def hybrid_forward(self, F, x):
    return self.cnn(x)

net = SegmentationNetwork()
net.hybridize()
net.collect_params().reset_ctx(ctx)

```

### Definowanie epoki

```

[11]: print_every_n = 1
      send_image_every_n = 20

def run_epoch(e, network, dataloader, loss_function, trainer, log_dir,
             print_name, is_train):
    total_loss = nd.zeros(1, ctx)
    for i, (data, label) in enumerate(dataloader):
        data = data.as_in_context(ctx)
        label = label.as_in_context(ctx)

        with autograd.record(train_mode=is_train):
            output = network(data)
            loss_i = loss_function(output, label)
            if is_train:
                loss_i.backward()
                trainer.step(data.shape[0])

        total_loss += loss_i.mean()

    if e % send_image_every_n == 0 and e > 0 and i == 0:

```

```

        output_image = draw_box_on_image(output.asnumpy(), label.
↪asnumpy(), data.asnumpy())
        epoch_loss = float(total_loss .asscalar())/len(dataloader)

        with SummaryWriter(logdir=log_dir, verbose=False, flush_secs=5) as sw:
            sw.add_scalar('loss', {print_name: epoch_loss}, global_step=e)
            if e % send_image_every_n == 0 and e > 0:
                output_image[output_image<0] = 0
                output_image[output_image>1] = 1
                sw.add_image('bb_{}_image'.format(print_name), output_image,
↪global_step=e)

        return epoch_loss

```

## Pre training

Sieć była początkowo szkolona w 300 epokach przy użyciu błędu średniokwadratowego (strata L2) jako funkcji straty. Zostało to wykonane, ponieważ bez rozsądnych ramek granicznych (tj. nakładających się ramek granicznych) utrata IOU nie będzie działać poprawnie.

```

[14]: checkpoint_name = "cnn_mse.params"
        best_test_loss = 10e5

```

```

[17]: loss_function = gluon.loss.L2Loss()
        epochs = 11
        learning_rate = 0.00005
        log_dir = "./logs/paragraph_segmentation"

```

```

[19]: if os.path.isfile(os.path.join(model_checkpoint_folder, checkpoint_name)):
        net.load_parameters(os.path.join(model_checkpoint_folder, checkpoint_name))

```

```

[21]: trainer = gluon.Trainer(net.collect_params(), 'adam', {'learning_rate':
↪learning_rate})

```

```

[22]: for e in range(epochs):
        train_loss = run_epoch(e, net, train_data, loss_function=loss_function,
↪log_dir=log_dir,
                                trainer=trainer, print_name="train", is_train=True)
        test_loss = run_epoch(e, net, test_data, loss_function=loss_function,
↪log_dir=log_dir,
                                trainer=trainer, print_name="test", is_train=False)
        if test_loss < best_test_loss:
            print("Saving network, previous best test loss {:.6f}, current test
↪loss {:.6f}".format(best_test_loss, test_loss))

```

```

        net.save_parameters(os.path.join(model_checkpoint_folder,
↪checkpoint_name))

        best_test_loss = test_loss
        if e % print_every_n == 0 and e > 0:
            print("Epoch {0}, train_loss {1:.6f}, test_loss {2:.6f}".format(e,
↪train_loss, test_loss))

```

[09:27:18] ../src/operator/nv/.cudnn/.cudnn\_alcoreg-inl.h:97: Running  
↪performance tests

to find the best convolution algorithm, this can take a while... (set the  
↪environment

variable MXNET\_CUDNN\_AUTOTUNE\_DEFAULT to 0 to disable)

Saving network, previous best test loss 1000000.000000, current test loss 0.  
↪002516

Saving network, previous best test loss 0.002516, current test loss 0.001363  
Epoch 1, train\_loss 0.008476, test\_loss 0.001363

Saving network, previous best test loss 0.001363, current test loss 0.001273  
Epoch 2, train\_loss 0.006936, test\_loss 0.001273

Epoch 3, train\_loss 0.006079, test\_loss 0.001371

Saving network, previous best test loss 0.001273, current test loss 0.001209  
Epoch 4, train\_loss 0.005319, test\_loss 0.001209

Saving network, previous best test loss 0.001209, current test loss 0.001129  
Epoch 5, train\_loss 0.004649, test\_loss 0.001129

Saving network, previous best test loss 0.001129, current test loss 0.001077  
Epoch 6, train\_loss 0.004192, test\_loss 0.001077

Saving network, previous best test loss 0.001077, current test loss 0.001073  
Epoch 7, train\_loss 0.003999, test\_loss 0.001073

Saving network, previous best test loss 0.001073, current test loss 0.001023  
Epoch 8, train\_loss 0.003723, test\_loss 0.001023

Epoch 9, train\_loss 0.003519, test\_loss 0.001060

Saving network, previous best test loss 0.001023, current test loss 0.001018  
Epoch 10, train\_loss 0.003356, test\_loss 0.001018

## Dopasowanie

Po przeszkoleniu sieci za pomocą średniej kwadratowej utraty błędów, utrata IOU została wykorzystana do dostrojenia sieci. Strata IOU jest bardziej drobnziarnista, ponieważ maksymalizuje nakładanie się ramek ograniczających.

[24]: 

```
if os.path.isfile(os.path.join(model_checkpoint_folder, checkpoint_name)):
    net.load_parameters(os.path.join(model_checkpoint_folder, checkpoint_name))
```

```
fine_tuning = False # I found this to consistently decrease the qualitative_
↳ results
```

```
[25]: if fine_tuning:
    checkpoint_name = "cnn_iou.params"
    loss_function = IOU_loss()
    epochs = 150
    learning_rate = 0.00005
    log_dir = "./logs"

    best_test_loss = 10e5

    trainer = gluon.Trainer(net.collect_params(), 'adam', {'learning_rate':
↳ learning_rate, })

    for e in range(epochs):
        train_loss = run_epoch(e, net, train_data,
↳ loss_function=loss_function, log_dir=log_dir,
                                trainer=trainer, print_name="train",
↳ is_train=True)
        test_loss = run_epoch(e, net, test_data, loss_function=loss_function,
↳ log_dir=log_dir,
                                trainer=trainer, print_name="test",
↳ is_train=False)
        if test_loss < best_test_loss:
            print("Saving network, previous best test loss {:.6f}, current_
↳ test loss {:.6f}".format(best_test_loss, test_loss))
            net.save_parameters("{}_{}".format(model_checkpoint_folder,
↳ checkpoint_name))
            best_test_loss = test_loss
            if e % print_every_n == 0 and e > 0:
                print("Epoch {0}, train_loss {1:.6f}, test_loss {2:.6f}".
↳ format(e, train_loss, test_loss))
```

## Wyniki

Szkolenie i test MSE są wyświetlone w tym notatniku. Stratę i obrazy z przewidywanymi ramkami ograniczającymi pokazano poniżej.

```
[26]: figs_to_plot = 10
fig, axs = plt.subplots(figs_to_plot, 2, figsize=(15, 10 * figs_to_plot))
```

```

for i in range(figs_to_plot):
    n = int(random.random()*len(test_ds))
    image, bb = test_ds[n]

    image, _ = transform(image, bb)
    image = image.as_in_context(ctx)
    image = image.expand_dims(axis=0)
    bb_predicted = net(image)

    (x, y, w, h) = bb[0]
    axs[i][0].imshow(image.asnumpy().squeeze(), cmap='Greys_r')
    image_h, image_w = image.shape[-2:]
    (x, y, w, h) = (x * image_w, y * image_h, w * image_w, h * image_h)
    rect = patches.Rectangle((x, y), w, h, fill=False, color="r")
    axs[i][0].add_patch(rect)
    axs[i][0].set_title("BB actual")

    axs[i][1].imshow(image.asnumpy().squeeze(), cmap='Greys_r')
    (x, y, w, h) = bb_predicted[0].asnumpy()
    image_h, image_w = image.shape[-2:]
    (x, y, w, h) = (x * image_w, y * image_h, w * image_w, h * image_h)
    rect = patches.Rectangle((x, y), w, h, fill=False, color="r", ls="--")
    axs[i][1].add_patch(rect)
    axs[i][1].set_title("BB predicted")

```



88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

88 actual

88 predicted

