

PRACTICAL 1

A) Write the query for the following.

1) Create the following table and include the necessary constraints NOT NULL, DEFAULT, CHECK, PRIMARY KEY, UNIQUE.

A) Student (sid,sname,gender,dob,marks,class,email)

```
SQL> create table student(sid int primary key,sname varchar(10) not
null,gender varchar(10) not null,dob date not null,marks int check
(marks>50),class varchar(10) default 'FYCS',emailid varchar(10));

Table created.

SQL> desc student
+-----+-----+-----+
| Name          | Null? | Type          |
+-----+-----+-----+
| SID           | NOT NULL | NUMBER(38)    |
| SNAME         | NOT NULL | VARCHAR2(10)  |
| GENDER        | NOT NULL | VARCHAR2(10)  |
| DOB           | NOT NULL | DATE          |
| MARKS         |         | NUMBER(38)    |
| CLASS         |         | VARCHAR2(10)  |
| EMAILID       |         | VARCHAR2(10)  |
+-----+-----+-----+
```

B) Course(CID,CNAME,CREDITS)

```
SQL> create table course(cid int primary key,cname varchar(10) not
null,credits int not null);

Table created.

SQL> desc course
+-----+-----+-----+
| Name          | Null? | Type          |
+-----+-----+-----+
| CID           | NOT NULL | NUMBER(38)    |
| CNAME         | NOT NULL | VARCHAR2(10)  |
| CREDITS       | NOT NULL | NUMBER(38)    |
+-----+-----+-----+
```

2) Alter the structure of the course table

C) Modify data type of cname

```
SQL> alter table course
2 modify cname varchar(20);
```

Table altered.

```
SQL> desc course
```

Name	Null?	Type
CID	NOT NULL	NUMBER(38)
CNAME	NOT NULL	VARCHAR2(20)
CREDITS	NOT NULL	NUMBER(38)

D) Add a column coursehours with minimum course hours greater than 45.

```
SQL> alter table course
2 add coursehours int check(coursehours>45);
```

Table altered.

```
SQL> desc course
```

Name	Null?	Type
CID	NOT NULL	NUMBER(38)
CNAME	NOT NULL	VARCHAR2(20)
CREDITS	NOT NULL	NUMBER(38)
COURSEHOURS		NUMBER(38)

E) ADD A COLUMN CDESC

```
SQL> alter table course
2 add cdesc varchar(10);
```

Table altered.

```
SQL> desc course
```

Name	Null?	Type
CID	NOT NULL	NUMBER(38)
CNAME	NOT NULL	VARCHAR2(20)
CREDITS	NOT NULL	NUMBER(38)
COURSEHOURS		NUMBER(38)
CDESC		VARCHAR2(10)

3) Alter the structure of the student table

F) Add column age with minimum age as 17

```
SQL> alter table student
      2 add age int check(age>17);
```

Table altered.

```
SQL> desc student
```

Name	Null?	Type
SID	NOT NULL	NUMBER(38)
SNAME	NOT NULL	VARCHAR2(10)
GENDER	NOT NULL	VARCHAR2(10)
DOB	NOT NULL	DATE
MARKS		NUMBER(38)
CLASS		VARCHAR2(10)
EMAILID		VARCHAR2(10)
AGE		NUMBER(38)

G) Delete column dob

```
SQL> alter table student
      2 drop column dob;
```

Table altered.

```
SQL> desc student
```

Name	Null?	Type
SID	NOT NULL	NUMBER(38)
SNAME	NOT NULL	VARCHAR2(10)
GENDER	NOT NULL	VARCHAR2(10)
MARKS		NUMBER(38)
CLASS		VARCHAR2(10)
EMAILID		VARCHAR2(10)
AGE		NUMBER(38)

H) Add a column phoneno

```
SQL> alter table student
2 add phoneno int;
```

Table altered.

```
SQL> desc student
```

Name	Null?	Type
-----	-----	-----
SID	NOT NULL	NUMBER(38)
SNAME	NOT NULL	VARCHAR2(10)
GENDER	NOT NULL	VARCHAR2(10)
MARKS		NUMBER(38)
CLASS		VARCHAR2(10)
EMAILID		VARCHAR2(10)
AGE		NUMBER(38)
PHONENO		NUMBER(38)

l)Rename phoneno to contactno

```
SQL> alter table student
2 rename column phoneno to contactno;
```

Table altered.

```
SQL> desc student
```

Name	Null?	Type
-----	-----	-----
SID	NOT NULL	NUMBER(38)
SNAME	NOT NULL	VARCHAR2(10)
GENDER	NOT NULL	VARCHAR2(10)
MARKS		NUMBER(38)
CLASS		VARCHAR2(10)
EMAILID		VARCHAR2(10)
AGE		NUMBER(38)
CONTACTNO		NUMBER(38)

4) Rename student table as Student_details

```
SQL> alter table student  
2 rename to student_details;
```

Table altered.

```
SQL> desc student_details
```

Name	Null?	Type
SID	NOT NULL	NUMBER(38)
SNAME	NOT NULL	VARCHAR2(10)
GENDER	NOT NULL	VARCHAR2(10)
MARKS		NUMBER(38)
CLASS		VARCHAR2(10)
EMAILID		VARCHAR2(10)
AGE		NUMBER(38)
CONTACTNO		NUMBER(38)

6) Drop the table student_details and course.

```
SQL> drop table course;
```

Table dropped.

```
SQL> drop table student_details;
```

Table dropped.

```
SQL> desc course
```

ERROR:

ORA-04043: object course does not exist

```
SQL> desc student_details
```

ERROR:

ORA-04043: object student_details does not exist

B)1. Create a table EMPLOYEE with following attributes and specific data types and constraints required (Emp_no, E_name, E_address, E_ph_no, Dept_no, Dept_name, Job_id, Salary)

```
SQL> create table employee(Emp_no int primary key,E_name varchar(10) not null,E_
address varchar(20),E_ph_no int,Dept_no int not null,Dept_name varchar(10),Job_i
d int,salary int);
```

Table created.

```
SQL> desc employee
```

Name	Null?	Type
EMP_NO	NOT NULL	NUMBER(38)
E_NAME	NOT NULL	VARCHAR2(10)
E_ADDRESS		VARCHAR2(20)
E_PH_NO		NUMBER(38)
DEPT_NO	NOT NULL	NUMBER(38)
DEPT_NAME		VARCHAR2(10)
JOB_ID		NUMBER(38)
SALARY		NUMBER(38)

2. Add a new column HIREDATE to the existing relation.

```
SQL> alter table employee
2 add hiredate date;
```

Table altered.

```
SQL> desc employee
```

Name	Null?	Type
EMP_NO	NOT NULL	NUMBER(38)
E_NAME	NOT NULL	VARCHAR2(10)
E_ADDRESS		VARCHAR2(20)
E_PH_NO		NUMBER(38)
DEPT_NO	NOT NULL	NUMBER(38)
DEPT_NAME		VARCHAR2(10)
JOB_ID		NUMBER(38)
SALARY		NUMBER(38)
HIREDATE		DATE

3. Change the datatype of JOB_ID from char to varchar2.

```
SQL> alter table employee
2 modify Job_id varchar(20);
```

Table altered.

```
SQL> desc employee
```

Name	Null?	Type
EMP_NO	NOT NULL	NUMBER(38)
E_NAME	NOT NULL	VARCHAR2(10)
E_ADDRESS		VARCHAR2(20)
E_PH_NO		NUMBER(38)
DEPT_NO	NOT NULL	NUMBER(38)
DEPT_NAME		VARCHAR2(10)
JOB_ID		VARCHAR2(20)
SALARY		NUMBER(38)
HIREDATE		DATE

4. Change the name of column/field Emp_no to E_no.

```
SQL> alter table employee
2 rename column Emp_no to E_no;
```

Table altered.

```
SQL> desc employee
```

Name	Null?	Type
E_NO	NOT NULL	NUMBER(38)
E_NAME	NOT NULL	VARCHAR2(10)
E_ADDRESS		VARCHAR2(20)
E_PH_NO		NUMBER(38)
DEPT_NO	NOT NULL	NUMBER(38)
DEPT_NAME		VARCHAR2(10)
JOB_ID		VARCHAR2(20)
SALARY		NUMBER(38)
HIREDATE		DATE

5. Modify the column width of the job field of emp table.

```
SQL> alter table employee
2 modify Job_id varchar(10);
```

Table altered.

```
SQL> desc employee
```

Name	Null?	Type
E_NO	NOT NULL	NUMBER(38)
E_NAME	NOT NULL	VARCHAR2(10)
E_ADDRESS		VARCHAR2(20)
E_PH_NO		NUMBER(38)
DEPT_NO	NOT NULL	NUMBER(38)
DEPT_NAME		VARCHAR2(10)
JOB_ID		VARCHAR2(10)
SALARY		NUMBER(38)
HIREDATE		DATE

C) Create the following tables with specified attributes and constraints

1) Department Table: Department_Id varchar2(20) primary key, Department_Name varchar2(25) with required data.

```
SQL> create table Department(Department_Id varchar(20) primary key, Department_Name varchar(25));
```

Table created.

```
SQL> alter table Department
```

```
2 modify Department_Name varchar(25) not null;
```

Table altered.

```
SQL> desc Department
```

Name	Null?	Type
DEPARTMENT_ID	NOT NULL	VARCHAR2(20)
DEPARTMENT_NAME	NOT NULL	VARCHAR2(25)

2) Instructor Table: Instructor_id varchar2(20) primary key, Department_Id varchar2(20) Foreign key, Last_Name varchar2(25), First_Name varchar2(200) must have value, Telephone varchar2(20) must be unique, gender char(1) must be either 'F' or 'M', city varchar(10) default value must be 'MUMBAI'.


```
SQL> create table Instructor(Instructor_id varchar(20) primary key, Department_Id varchar(20) references
Department(Department_Id),Last_name varchar(20),First_name varchar(200) not null,Telephone varchar(20)
unique,gender char(1) check(gender='F' or gender='M'),city varchar(10) default 'MUMBAI');
```

Table created.

```
SQL> desc Instructor
```

Name	Null?	Type
-----	-----	-----
INSTRUCTOR_ID	NOT NULL	VARCHAR2(20)
DEPARTMENT_ID		VARCHAR2(20)
LAST_NAME		VARCHAR2(20)
FIRST_NAME	NOT NULL	VARCHAR2(200)
TELEPHONE		VARCHAR2(20)
GENDER		CHAR(1)
CITY		VARCHAR2(10)

D) Create the following described below:

Table Name: EMP

Column	Data Type	Length	Precision	Scale	Primary Key	Nullable
EMPNO	Int	-	-	-	Yes	-
ENAME	Varchar2	10	-	-	-	No
JOB	Varchar2	9	-	-	-	✓
MGR	Int	-	-	-	-	✓
HIREDATE	Date	-	-	-	-	✓
SAL	Number	-	7	2	-	✓
COMM	Int	-	-	-	-	✓
DEPTNO	Int	-	-	-	-	✓

Table Name: DEPT

Column	Data Type	Length	Precision	Scale	Primary Key	Nullable
DEPTNO	Int	-	-	-	Yes	-
DNAME	Varchar2	14	-	-	-	No
LOC	Varchar2	13	-	-	-	✓

```
SQL> create table tahir_DEPT(Dept_no int primary key,Dname varchar(14) not null,Loc varchar(13));
```

Table created.

```
SQL> desc tahir_DEPT
```

Name	Null?	Type
-----	-----	-----
DEPT_NO	NOT NULL	NUMBER(38)
DNAME	NOT NULL	VARCHAR2(14)
LOC		VARCHAR2(13)

```
SQL> create table tahirr_EMP(EMP_no int primary key,ENAME varchar(10) not null,Job varchar(9),
MGR int,Hiredate date,SAL decimal(7,2),Comm int,Dept_no int references tahir_DEPT(Dept_no));
```

Table created.

```
SQL> desc tahirr_EMP
```

Name	Null?	Type
EMP_NO	NOT NULL	NUMBER(38)
ENAME	NOT NULL	VARCHAR2(10)
JOB		VARCHAR2(9)
MGR		NUMBER(38)
HIREDATE		DATE
SAL		NUMBER(7,2)
COMM		NUMBER(38)
DEPT_NO		NUMBER(38)

Practical 2: Study of Data Manipulation Language Statement

A) Insert the following records in above created table

EMP TABLE

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7839	KING	PRESIDENT		17-Nov-81	5000		10
7698	BLAKE	MANAGER	7839	01-May-81	2850		30
7782	CLARK	MANAGER	7839	09-Jun-81	2450		10
7566	JONES	MANAGER	7839	02-Apr-81	2975		20
7788	SCOTT	ANALYST	7566	19-Apr-87	3000		20
7902	FORD	ANALYST	7566	03-Dec-81	3000		20
7369	SMITH	CLERK	7902	17-Dec-80	800		20
7499	ALLEN	SALESMAN	7698	20-Feb-81	1600	300	30
7521	WARD	SALESMAN	7698	22-Feb-81	1250	500	30
7654	MARTIN	SALESMAN	7698	28-Sep-81	1250	1400	30
7844	TURNER	SALESMAN	7698	08-Sep-81	1500	0	30
7876	ADAMS	CLERK	7788	23-May-87	1100		20
7900	JAMES	CLERK	7698	03-Dec-81	950		30
7934	MILLER	CLERK	7782	23-Jan-82	1300		10

DEPT TABLE

DEPTNO	DNAME	LOC
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
40	OPERATIONS	BOSTON

```
SQL> insert into tahir_DEPT values(10,'ACCOUNTING','NEW YORK');
```

```
1 row created.
```

```
SQL> insert into tahir_DEPT values(20,'RESEARCH','DALLAS');
```

```
1 row created.
```

```
SQL> insert into tahir_DEPT values(30,'SALES','CHICAGO');
```

```
1 row created.
```

```
SQL> insert into tahir_DEPT values(40,'OPERATIONS','BOSTON');
```

```
1 row created.
```

```
SQL> select * from tahir_DEPT;
```

DEPT_NO	DNAME	LOC
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
40	OPERATIONS	BOSTON

```
SQL> select * from tahirr_EMP;
```

EMP_NO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPT_NO
7839	KING	PRESIDENT		17-NOV-81	5000		10
7698	BLAKE	MANAGER	7839	01-MAY-81	2850		30
7782	CLARK	MANAGER	7839	09-JUN-81	2450		10
7566	JONES	MANAGER	7839	02-APR-81	2975		20
7788	SCOTT	ANALYST	7566	19-APR-87	3000		20
7902	FORD	ANALYST	7566	03-DEC-81	3000		20
7369	SMITH	CLERK	7902	17-DEC-80	800		20
7499	ALLEN	SALESMAN	7698	20-FEB-81	1600	300	30
7521	WARD	SALESMAN	7698	22-FEB-81	1250	500	30
7654	MARTIN	SALESMAN	7698	28-SEP-81	1250	1400	30
7844	TURNER	SALESMAN	7698	08-SEP-81	1500	0	30
7876	ADAMS	CLERK	7788	23-MAY-87	1100		20
7900	JAMES	CLERK	7698	03-DEC-81	950		30
7934	MILLER	CLERK	7782	23-JAN-82	1300		10

```
14 rows selected.
```

B) Update and Delete Queries

1) Update the salary of employees working as CLERK by 500.

```
SQL> update tahirr_EMP
2 set SAL=SAL+500
3 where Job='CLERK';
```

4 rows updated.

```
SQL> select * from tahirr_EMP;
```

EMP_NO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPT_NO
7839	KING	PRESIDENT		17-NOV-81	5000		10
7698	BLAKE	MANAGER	7839	01-MAY-81	2850		30
7782	CLARK	MANAGER	7839	09-JUN-81	2450		10
7566	JONES	MANAGER	7839	02-APR-81	2975		20
7788	SCOTT	ANALYST	7566	19-APR-87	3000		20
7902	FORD	ANALYST	7566	03-DEC-81	3000		20
7369	SMITH	CLERK	7902	17-DEC-80	1300		20
7499	ALLEN	SALESMAN	7698	20-FEB-81	1600	300	30
7521	WARD	SALESMAN	7698	22-FEB-81	1250	500	30
7654	MARTIN	SALESMAN	7698	28-SEP-81	1250	1400	30
7844	TURNER	SALESMAN	7698	08-SEP-81	1500	0	30
7876	ADAMS	CLERK	7788	23-MAY-87	1600		20
7900	JAMES	CLERK	7698	03-DEC-81	1450		30
7934	MILLER	CLERK	7782	23-JAN-82	1800		10

14 rows selected.

2) Update the manager of James as CLARK.

```
SQL> update tahirr_EMP
2 set Job='CLARK'
3 where Ename='JAMES';
```

1 row updated.

```
SQL> select * from tahirr_EMP;
```

EMP_NO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPT_NO
7839	KING	PRESIDENT		17-NOV-81	5000		10
7698	BLAKE	MANAGER	7839	01-MAY-81	2850		30
7782	CLARK	MANAGER	7839	09-JUN-81	2450		10
7566	JONES	MANAGER	7839	02-APR-81	2975		20
7788	SCOTT	ANALYST	7566	19-APR-87	3000		20
7902	FORD	ANALYST	7566	03-DEC-81	3000		20
7369	SMITH	CLERK	7902	17-DEC-80	1300		20
7499	ALLEN	SALESMAN	7698	20-FEB-81	1600	300	30
7521	WARD	SALESMAN	7698	22-FEB-81	1250	500	30
7654	MARTIN	SALESMAN	7698	28-SEP-81	1250	1400	30
7844	TURNER	SALESMAN	7698	08-SEP-81	1500	0	30
7876	ADAMS	CLERK	7788	23-MAY-87	1600		20
7900	JAMES	CLARK	7698	03-DEC-81	1450		30
7934	MILLER	CLERK	7782	23-JAN-82	1800		10

14 rows selected.

3) Change the role of Miller as MANAGER.

```
SQL> update tahirr_EMP
  2  set Job='MANAGER'
  3  where Ename='MILLER';
```

1 row updated.

7934	MILLER	MANAGER	7782	23-JAN-82	1800		10
------	--------	---------	------	-----------	------	--	----

4) Delete the records of Manager

```
SQL> delete from tahirr_EMP
  2  where Job='MANAGER';
```

4 rows deleted.

EMP_NO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPT_NO
7839	KING	PRESIDENT		17-NOV-81	5000		10
7788	SCOTT	ANALYST	7566	19-APR-87	3000		20
7902	FORD	ANALYST	7566	03-DEC-81	3000		20
7369	SMITH	CLERK	7902	17-DEC-80	1300		20
7499	ALLEN	SALESMAN	7698	20-FEB-81	1600	300	30
7521	WARD	SALESMAN	7698	22-FEB-81	1250	500	30
7654	MARTIN	SALESMAN	7698	28-SEP-81	1250	1400	30
7844	TURNER	SALESMAN	7698	08-SEP-81	1500	0	30
7876	ADAMS	CLERK	7788	23-MAY-87	1600		20
7900	JAMES	CLARK	7698	03-DEC-81	1450		30

10 rows selected.

5) Delete the records when salary is greater than 1000.

```
SQL> delete from tahirr_EMP
2 where SAL>1000;
```

10 rows deleted.

```
SQL> select * from tahirr_EMP;
```

no rows selected