Problem: 01

```
Public class First {
    // Attributes
  private String name;
  Private double salary;

  // Constructor
Public ObFirst (String name, double salary){
    this. name = name;
    this. double = salary;
  }
  // Method that return
  Public double getSalary() {
      return Salary;
    }
  // Method that have parameter
  Public void increaseSalary (int newSalary) {
      this. salary = newSalary;
    }
}
```

```
Public class Second{
    Private String gender;
    Private double bmi;

Public Second (String gender, double bmi){
    this.gender = gender;
    this.bmi = bmi;
}
Public double updatebmi () {
        return bmi;
    }
Public void setGender (String newGender){
        this.gender = newGender;
    }
}
```

```
Public class Third{
    Private String type;
    Private int number;
Public Third (String type, int number){
    this.type = type;
    this.number = number;
}
public String getType(){
        return type;
    }
Public void updateNumber(int newNumber){
    this.number = newNumber;
    }
}
```

Problem: 02

```
Public class MainClass {
  Public static void main (String [] args) {
  First f1 = new First ("Tahsin", 25000);
  Second S2 = new Second("Male", 24.9);
  Third t3 = new Third("Book", 25);
  // call the methods
     f1.getSalary();
     f1.increaseSalary(5);
  System.out.println("Salary is: "+ f1.getSalary());
  System.out.println("Increased: "+ f1.increaseSalary(5));

   System.out.println("BMI: "+ S2.updatebmi(22.5));
    S2.setGender();

   t3.updateNumber(26);
  System.out.println("Type of item: "+t3.getType());
  }
}
```