



1500N.M以上皆分為前後段組裝使用，不可單獨使用，將提供更好的扭力力矩使用

MIT2 視窗型可調扭力扳手

具備雙向扭力使用

CW:±4% ; CCW:±6%

S.I.單位

ITEM NO.	mm	Range	mm	L mm	kg
MIT2-15N	9x12	3-15 Nm	0.2 Nm	188	0.34
MIT2-30N	9x12	6-30 Nm	0.2 Nm	290	0.58
MIT2-60N	9x12	10-60 Nm	0.25 Nm	424	0.90
MIT2-100N	9x12	20-100 Nm	0.5 Nm	459	1.40
MIT2-100NS	14x18	20-100 Nm	0.5 Nm	464	1.41
MIT2-200N	14x18	40-200 Nm	1 Nm	483	2.10
MIT2-320N	14x18	60-320 Nm	2 Nm	552	2.20
MIT2-500N	14x18	100-500 Nm	4 Nm	794	3.50
ITEM NO.	mm	Range	mm	L mm	kg
MIT2-800N	20x28.5	100-800 Nm	5 Nm	1101	5.38
MIT2-1000N	20x28.5	200-1000 Nm	5 Nm	1325	6.00
MIT2-1500N	20x28.5	300-1500 Nm	10 Nm	1555	11.70
MIT2-2000N	20x28.5	400-2000 Nm	10 Nm	2026	12.90



英制單位

ITEM NO.	mm	Range	mm	L mm	kg
MIT2-150i	9x12	30-150 in.lb	2 in.lb	188	0.34
MIT2-250i	9x12	50-250 in.lb	2 in.lb	290	0.58
MIT2-45F	9x12	9-45 ft.lb	0.25 ft.lb	424	0.90
MIT2-75F	9x12	15-75 ft.lb	0.5 ft.lb	459	1.40
MIT2-75FS	14x18	15-75 ft.lb	0.5 ft.lb	464	1.41
MIT2-150F	14x18	30-150 ft.lb	0.5 ft.lb	483	2.10
MIT2-230F	14x18	60-230 ft.lb	1 ft.lb	552	2.20
MIT2-300F	14x18	60-300 ft.lb	2.5 ft.lb	794	3.50
ITEM NO.	mm	Range	mm	L mm	kg
MIT2-600F	20x28.5	100-600 ft.lb	2.5 ft.lb	1101	5.38
MIT2-700F	20x28.5	150-700 ft.lb	2.5 ft.lb	1325	6.00
MIT2-1000F	20x28.5	200-1000 ft.lb	5 ft.lb	1555	11.70
MIT2-1500F	20x28.5	300-1500 ft.lb	5 ft.lb	2026	12.90



MIT2, CPS, 系列

20x28.5 頭部可交換型式

可與WUMA 20x28.5頭部可交換配件搭配使用



MIT2, CPS, MEB 系列

9x12 & 14x18 頭部可交換型式

可與 WUMA 9X12 or 14X18 頭部可交換配件搭配使用。

請參考型錄P12 ~ P15頁頭部可交換型式配件。