Optional and official Bootstrap classes v3.2x Cheat Sheet by Aurelius Wendelken (hamburg) via cheatography.com/19322/cs/2376/

.navbar-left

.navbar-right

.navbar-btn

.navbar-nav

.navbar-link

.navbar-text

.navbar-form

.navbar-toggle

.breadcrumb

.pager

Columns		
.col-xs-	Always	Full
.col-sm-	> 768px	750 wide
.col-md-	> 992px	970 wide
.col-lg-	> 1200px	1170 wide

Nav classes .nav-tabs .nav .nav-pills .nav-tabs-justified .nav-divder .nav-stacked ul class="nav nav-tabs" role="tablist"> class="active">*

```
List classes
.list-inline
.list-unstyled
.dl-horizontal
.list-group
.list-group-item
.list-group-item-heading
.list-group-item-text
.list-group-item-info
.list-group-item-warning
.list-group-item-danger
.list-group-item-success
<dl class="dl-horizontal">...</dl>
ul class="list-unstyled">...
ul class="list-inline">...
cli class="list-group-item">...
  cli class="list-group-item">...
```

Navbar classes .navbar .navbar-brand .navbar-default .navbar-fixed-top .navbar-static-top .navbar-fixed-bottom .navbar-collapse .navbar-inverse <div class="navbar-header"> <butoon class="navbar-toggle"> ... </button> ... </div> **Nav Uitlity classes** .pagination .pagination-sm

.pagination-lg	.fade	
.active	.in	
<pre><ol #"="" class="breadcru . . cli class="active"</pre>		
 <ul #"="" class="pagination 2 2 2 4 5	1 2 3 4	

*...

By Aurelius Wendelken
(hamburg)
cheatography.com/hamburg
twitter.com/webtobesocial

```
Published 28th July, 2014.
Last updated 31st July, 2014.
Page 1 of 6.
```

<div class="tab-content">

<div class="tab-pane active">...</div>

<div class="tab-pane">...</div> <div class="tab-pane">...</div>

Tab classes

.tab-content

</div>

Media classes	
.media	.media-list
.media-heading	.media-body
.media-object	
<div class="media"> <a <="" class="pull-left" th=""><td>edia-object" ></td></div>	edia-object" >

```
Progress classes
.progress
.progress-bar
.progress-striped
.progress-bar-striped
.progress-bar-info
.progress-bar-warning
.progress-bar-danger
.progress-bar-success
<div class="progress">
  <div class="progress-bar"
```

```
role="progressbar"
    aria-valuenow="60"
    aria-valuemin="0"
    aria-valuemax="100">
    <span class="sr-only">...</span>
  </div>
</div>
```

General Offset classes
.margin-[xs sm md lg]-6[-only]
.margin-[xs sm md lg]-9[-only]
.margin-[xs sm md lg]-12[-only]
.margin-[xs sm md lg]-15[-only]
.margin-[xs sm md lg]-18[-only]
.margin-[xs sm md lg]-21[-only]

Optional and official Bootstrap classes v3.2x Cheat Sheet by Aurelius Wendelken (hamburg) via cheatography.com/19322/cs/2376/

Top Offset classes

.margin-top -[xs|sm|md|lg]-6[-only]

.margin-top -[xs|sm|md|lg]-9[-only]

.margin-top -[xs|sm|md|lg]-12[-only]

.margin-top -[xs|sm|md|lg]-15[-only]

.margin-top -[xs|sm|md|lg]-18[-only]

.margin-top -[xs|sm|md|lg]-21[-only]

Right Offset classes

.margin-right-[xs|sm|md|lg]-6[-only]

.margin-right-[xs|sm|md|lg]-9[-only]

.margin-right-[xs|sm|md|lg]-12[-only]

.margin-right-[xs|sm|md|lg]-15[-only]

.margin-right-[xs|sm|md|lg]-18[-only]

.margin-right-[xs|sm|md|lg]-21[-only]

Bottom Offset classes

.margin-bottom-[xs|sm|md|lg]-6[-only]

.margin-bottom-[xs|sm|md|lg]-9[-only]

.margin-bottom-[xs|sm|md|lg]-12[-only]

.margin-bottom-[xs|sm|md|lg]-15[-only]

.margin-bottom-[xs|sm|md|lg]-18[-only]

.margin-bottom-[xs|sm|md|lg]-21[-only]

Left Offset classes

Well classes

Cite classes

...

</blockquote>

.blockquote-reverse

Screenreader classes

<div class="well">...</div>

<div class="well well-sm">...</div>

<div class="well well-lg">...</div>

<blook/duote class="blockquote-reverse">

.well

.well-lg

.margin-left-[xs|sm|md|lg]-6[-only]

.margin-left-[xs|sm|md|lg]-9[-only]

.margin-left-[xs|sm|md|lg]-12[-only]

.margin-left-[xs|sm|md|lg]-15[-only]

.margin-left-[xs|sm|md|lg]-18[-only]

.margin-left-[xs|sm|md|lg]-21[-only]

.well-sm

.close

Tooltip Helper classes

.in .top .right
.bottom .left .top-left

.top-right .bottom-left .bottom-right

<button type="button"

class="btn btn-default"

data-toggle="tooltip" title="..."

data-placement="left">...</button>

General Padding classes

.padding-[xs|sm|md|lg]-0[-only]

.padding-[xs|sm|md|lg]-6[-only]

.padding-[xs|sm|md|lg]-9[-only]

.padding-[xs|sm|md|lg]-12[-only]

.padding-[xs|sm|md|lg]-15[-only]

.padding-[xs|sm|md|lg]-18[-only]

.padding-[xs|sm|md|lg]-21[-only]

Top Padding classes

.padding-top-[xs|sm|md|lg]-0[-only]

.padding-top-[xs|sm|md|lg]-6[-only]

.padding-top-[xs|sm|md|lg]-9[-only]

.padding-top-[xs|sm|md|lg]-12[-only]

.padding-top-[xs|sm|md|lg]-15[-only]

.padding-top-[xs|sm|md|lg]-18[-only]

.padding-top-[xs|sm|md|lg]-21[-only]

Tooltip classes

.tooltip

.tooltip-inner

.sr-only-focusable

.tooltip-arrow

<div class="tooltip top" role="tooltip">
 <div class="tooltip-arrow"></div>
 <div class="tooltip-inner">...</div>

</div

Published 28th July, 2014. Last updated 31st July, 2014.

Page 2 of 6.

Sponsored by **Readability-Score.com**Measure your website readability!

https://readability-score.com

C

By Aurelius Wendelken (hamburg) cheatography.com/hamburg/ twitter.com/webtobesocial

Optional and official Bootstrap classes v3.2x Cheat Sheet by Aurelius Wendelken (hamburg) via cheatography.com/19322/cs/2376/

Right Padding classes

.padding-right-[xs|sm|md|lg]-0[-only]

.padding-right-[xs|sm|md|lg]-6[-only]

.padding-right-[xs|sm|md|lg]-9[-only]

.padding-right-[xs|sm|md|lg]-12[-only]

.padding-right-[xs|sm|md|lg]-15[-only]

.padding-right-[xs|sm|md|lg]-18[-only]

.padding-right-[xs|sm|md|lg]-21[-only]

Bottom Padding classes

.padding-bottom-[xs|sm|md|lg]-0[-only]

.padding-bottom-[xs|sm|md|lg]-6[-only]

.padding-bottom-[xs|sm|md|lg]-9[-only]

.padding-bottom-[xs|sm|md|lg]-12[-only]

.padding-bottom-[xs|sm|md|lg]-15[-only]

.padding-bottom-[xs|sm|md|lg]-18[-only]

.padding-bottom-[xs|sm|md|lg]-21[-only]

Left Padding classes

.padding-left-[xs|sm|md|lg]-0[-only]

.padding-left-[xs|sm|md|lg]-6[-only]

.padding-left-[xs|sm|md|lg]-9[-only]

.padding-left-[xs|sm|md|lg]-12[-only]

.padding-left-[xs|sm|md|lg]-15[-only]

.padding-left-[xs|sm|md|lg]-18[-only]

.padding-left-[xs|sm|md|lg]-21[-only]

Wrapper classes

.container .container-fluid

.row

<div class="container">

<div class="col-xs-4">...</div>

<div class="col-xs-8">...</div>

</div>

<div class="container-fluid">

<div class="row">

<div class="col-sm-12">...</div>

</div>

</div>

Position classes

.pos-static-[xs|sm|md][-only|lg-only]

.pos-relative-[xs|sm|md][-only|lg-only]

.pos-absolute-[xs|sm|md][-only|lg-only]

.pos-fixed-[xs|sm|md][-only|lg-only]

<div class="pos-relative-xs">

<div class="pos-absolute-xs">...</div>

Text Weight classes

. text-normal-[xs|sm|md][-only|Ig-only]

. text-strong-[xs|sm|md][-only|lg-only]

I'm default

class="text-strong">I'm bold

Header classes

. h1[-xs|-sm|-md][-only|Ig-only]

.h2[-xs|-sm|-md][-only|lg-only]

.h3[-xs|-sm|-md][-only|lg-only]

.h4[-xs|-sm|-md][-only|lg-only]

.h5[-xs|-sm|-md][-only|lg-only]
.h6[-xs|-sm|-md][-only|lg-only]

...

Layout Helper classes

.pull-left[-xs|-sm|-md][-only|lg-only]

.pull-right[-xs|-sm|-md][-only|lg-only]

<div class="pull-left">...</div>
<div class="pull-right-sm">...</div>

Table classes

.table .table-responsive

.table-condensed .table-striped

.table-bordered .table-hover

...

<div class="table-responsive">

...

</div>

Table Helper classes

.active .info

.warning .danger

.success

...

...

...

...

Text Utility classes

.text-info	.text-lowercase
.text-muted	.text-uppercase
.text-warning	.text-capitalize
.text-danger	.text-nowrap
.text-success	.text-primary
.lead	.mark

...

...

...

...

...

...

...

...

...

By Aurelius Wendelken (hamburg) cheatography.com/hamburg/ twitter.com/webtobesocial Published 28th July, 2014. Last updated 31st July, 2014. Page 3 of 6.



...

Optional and official Bootstrap classes v3.2x Cheat Sheet by Aurelius Wendelken (hamburg) via cheatography.com/19322/cs/2376/

Text Helper classes .text-left .text-right .text-center .text-justify

Label classes	
.label	.label-default
.label-info	.label-warning
.label-success	.label-danger
.label-primary	
<pre><span class="label la <span class=" la<="" label="" pre=""></pre>	

Capari ciasa- laber laber default/>
Modal classes
.modal
.modal-open
.modal-dialog
.modal-header
.modal-content
.modal-footer
.modal-title
.modal-body
.modal-sm
.modal-lg
.modal-backdrop
.modal-scrollbar-measure

Carousel classes	
.carousel	.carousel-control
.carousel-inner	.carousel-indicators
.carousel-caption	
	ctive">
	ousel-caption" />

Carousel Helper classes	
.left	.right
.prev	.next
.item	.active
.icon-prev	.icon-next
 	

Ca class= right care	baser-control >\a>
Modal Helper clas	ses
.fade	.in
.close	
<button class="clos</td><td>se"></button>	
<button <="" class="btn</td><td>btn-primary" td=""></button>	
data-toggle="mo	dal"
data-target="#tai	rget">

Lilibed diasses
.embed-responsive
.embed-responsive-item
.embed-responsive-4by3
.embed-responsive-16by9
tbd

Img classes		
.img-responsive	.caption	
.img-rounded	.jumbotron	
.img-thumbnail	.thumbnail	
.img-circle		
<pre> </pre>		

.popover	.popover-content
.popover-title	
<div class="po</td><td>ppover" role="tooltip"></div>	
<div class="</td"><td>"arrow"></td></div>	"arrow">
<h3 class="</td><td>" popover-title"=""></h3>	
<div class="</td"><td>"popover-content"></td></div>	"popover-content">

Popover classes

1 opover riciper classes			
.top	.right	.bottom	
.left	.arrow		
<button< th=""><th>type="button"</th><th></th><th></th></button<>	type="button"		
class:	="btn btn-lg btn-	danger"	
data-toggle="popover" title=""			
data-content="">			

Col	umn Visibility classes
.hid	den-[xs sm md lg]
.vis	ble-[xs sm md lg]
.vis	ble-[xs sm md lg]-block
.vis	ble-[xs sm md lg]-inline
.vis	ble-[xs sm md lg]-inline-block
<div< td=""><td>/ class="visible-xs-block"> / class="visible-lg-block"> / class="hidden-lg"></td></div<>	/ class="visible-xs-block"> / class="visible-lg-block"> / class="hidden-lg">



By Aurelius Wendelken (hamburg) cheatography.com/hamburg/ twitter.com/webtobesocial

Published 28th July, 2014. Last updated 31st July, 2014. Page 4 of 6.

Optional and official Bootstrap classes v3.2x Cheat Sheet by Aurelius Wendelken (hamburg) via cheatography.com/19322/cs/2376/

Column Helper classes .col-[xs|sm|md|lg]-[push|pull|offset]-0 .col-[xs|sm|md|lg]-[push|pull|offset]-1 . col-[xs|sm|md|lg]-[push|pull|offset]-2. col-[xs|sm|md|lg]-[push|pull|offset]-3.col-[xs|sm|md|lg]-[push|pull|offset]-4 .col-[xs|sm|md|lg]-[push|pull|offset]-5 . col-[xs|sm|md|lg]-[push|pull|offset]-6. col-[xs|sm|md|lg]-[push|pull|offset]-7. col-[xs|sm|md|lg]-[push|pull|offset]-8.col-[xs|sm|md|lg]-[push|pull|offset]-9 . col-[xs|sm|md|lg]-[push|pull|offset]-10.col-[xs|sm|md|lg]-[push|pull|offset]-11 .col-[xs|sm|md|lg]-[push|pull|offset]-12 <div class="col-md-9 col-md-push-3" ... /> <div class="col-md-3 col-md-pull-9" ... />

Grid classes
.col-[xs sm md]-1[-only lg-only]
.col-[xs sm md]-2[- only lg-only]
.col-[xs sm md]-3[- only lg-only]
.col-[xs sm md]-4[- only lg-only]
.col-[xs sm md]-5[- only lg-only]
.col-[xs sm md]-6[- only lg-only]
.col-[xs sm md]-7[- only lg-only]
.col-[xs sm md]-8[- only lg-only]
.col-[xs sm md]-9[- only lg-only]
.col-[xs sm md]-10[-only lg-only]

d	
-	
<	
<	
<	
<	
<	
E	

.bg-s	se
<div< th=""><th>cl</th></div<>	cl
Butt	or
.btn	
.btn-	Wa
.btn-	int
.btn-	da
.btn-	SL
<but< th=""><th>to</th></but<>	to
<but< th=""><th>to</th></but<>	to

Grid classes (cont)		
.col-[xs sm md]-11[-only lg-only]		
.col-[xs sm md]-12[-only lg-only]		
Default Background classes		
.bg-info	.bg-search	
.bg-warning	.bg-default	
.bg-danger	.bg-primary	
.bg-success	.bg-secondary	
<pre></pre>		

<div class="bg-white-xs-only"></div>
.bg-secondary-[xs sm md][-only lg-only
.bg-default-[xs sm md][-only lg-only]
.bg-white-[xs sm md][-only lg-only]-

Background Color classes

Button classes		
.btn	.btn-toolbar	
.btn-warning	.btn-secondary	
.btn-info	.btn-primary	
.btn-danger	.btn-default	
.btn-success	.btn-link	
<button class="btn btn-info"></button> <button class="btn btn-link"></button>		
<button class="btn</th><th>btn-link"></button> blbar" role="toolbar"> group"> group">		

Button Helper classes		
.btn-xs	.btn-group-xs	
.btn-sm	.btn-group-sm	
.btn-lg	.btn-group-lg	
.btn-block	.btn-group-justified	
.btn-group	.btn-group-vertical	
.disabled		
 		

Visibility classes		
.hide	.show	
.hidden	.invisible	
.text-hide		
<h1 class="text-hide"></h1> <div class="show"></div> <div class="hidden"></div>		

Print classes
.hidden-print
.visible-print-block
.visible-print-inline
.visible-print-inline-block
<div class="hidden-print"></div> <div class="visible-print-block"></div>
<div class="visible-print-block"></div>



By Aurelius Wendelken (hamburg) cheatography.com/hamburg/ twitter.com/webtobesocial

Published 28th July, 2014. Last updated 31st July, 2014. Page 5 of 6.



Optional and official Bootstrap classes v3.2x Cheat Sheet by Aurelius Wendelken (hamburg) via cheatography.com/19322/cs/2376/

Form classes

.form-control

.form-control-static

.form-control-feedback

.form-horizontal

.form-inline

.input-group-addon

.input-group-btn

.form-group

.input-group

<form class="form-inline" role="form">
 <div class="form-group">
 <label class="sr-only">...</label>
 <input ... class="form-control">
 </div>
 </from>

Form Helper classes

.has-feedback .has-error
.has-warning .has-success
.help-block .sr-only

<div class="form-group has-success">
 <label class="control-label">...</label>
 <input ... class="form-control">
 </div>

Form Utility classes

.disabled

</div>

.input-sm .input-lg
.form-group-sm .form-group-lg
.checkbox .checkbox-inline
.radio .radio-inline

<div class="form-group form-group-lg"> <label class="control-label">...</label> <input ... class="form-control">

Alert classes

.alert .alert-link
.alert-info .alert-danger
.alert-warning .alert-success

.alert-dismissable

<div class="alert alert-info">...</div>
<div class="alert alert-success">...</div>
<div class="alert alert-warning">...</div>
<div class="alert alert-danger">...</div>

Dropdown classes

.dropdown

.dropdown-menu

.dropdown-menu-left

.dropdown-menu-right

.dropdown-backdrop

.dropdown-toggle

.dropdown-header

.dropup

 class="dropdown">
 <a href="#target"
 data-toggle="dropdown">...

 id="target" role="menu">...

Panel classes

.panel .panel-title
.panel-info .panel-body
.panel-heading .panel-footer
.panel-collapse .panel-default
.panel-group .panel-primary
.panel-warning .panel-danger

Panel classes (cont)

.panel-success

<div id="..." class="panel panel-default">
 <div class="panel-heading">
 <h3 class="panel-title">...</h3>
 </div>
 <div class="panel-body">...</div>
 <div class="panel-footer">...</div>
</div>

<div class="panel panel-info">...</div>
<div class="panel panel-primary">...</div>
<div class="collapse in">...</div>

Panel Helper classes

.collapse .in
collapsing .fade

data-toggle="collapse"

data-target="#target">...</button>

<div id="target">...</div>

Code classes

.pre-scrollable

class="pre-scrollable">...

Page classes

.page-header

<div class="page-header"> <h1>...</h1> </div>



By Aurelius Wendelken (hamburg) cheatography.com/hamburg/ twitter.com/webtobesocial Published 28th July, 2014. Last updated 31st July, 2014.

Page 6 of 6.