

H6

Designing Databases: Mapping a Conceptual into a Logical Design

Fundamentals of Databases

Alvaro A A Fernandes, SCS, UoM

[COMP23111 2014-2015 Lecture 06 of 12]

Acknowledgements

- These slides are adaptations (mostly minor, but some major) of material authored and made available to instructors by **Ramez Elmasri and Shamkant B. Navathe** to accompany their textbook **Database Systems: Models, Languages, Design, and Application Programming, 6th (Global) Edition, Addison-Wesley Pearson, 2011, 978-0-13-214498-8**
- Copyright remains with them and the publishers, whom I thank.
- Some slides had input from Sandra Sampaio, whom I thank.
- All errors are my responsibility.

In Previous Lectures

- We learned how data models lead to a distinction between schemas and instances that enables a logical view of the data.
- We learned about the relational approach to logical data modelling.
- We learned about the relational algebra and SQL, both its DDL and DML capabilities and its querying constructs.
- We learned of the practical benefits of performing conceptual modelling before logical design and why the EER approach serves well this purpose.

In This Lecture


- We'll learn how a conceptual model can be mapped into a logical model that is capable of being implemented in a relational DBMS.

Relational Database Design through (E)ER-to-Relational Mapping

- The goal is to derive a relational schema (i.e., logical, implementable) from an (E)ER conceptual schema
- As we have seen, a conceptual schema (because it is more abstract and expressive) is better suited to serve as a bridge between the DB designer and the various kinds of DB users when the latter are expressing interactively and iteratively their data requirements to the former.
- There is a seven-step semi-formal procedure to convert an ER model into a relational schema.
- Then, two further steps suffice for converting an EER model into a relational schema.

An Example ER Diagram for a COMPANY DB

7



A
model like this one is the
starting point.

An Example Relational Schema for a COMPANY DB

8

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------

A
schema like this one is
the end point.

Step 1: Mapping of Regular Entity Types

9

- For each regular (i.e., not weak) entity type E , create a relation R that includes all the simple attributes of E .
- Then include the leaf-level component attributes of a composite attribute.
- Then choose one of the keys in E as the primary key (PK) of R .
- If the chosen key is composite in E , then make the set of component attributes in it the composite PK of R .
- Then make the other keys in E secondary keys in R (i.e., assert them as unique in the DDL).
- Such relations are called **entity relations** and *each tuple represents an entity instance*.

After Step 1: Entity Relations

10

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary
-------	-------	-------	------------	-------	---------	-----	--------

DEPARTMENT

Dname	<u>Dnumber</u>
-------	----------------

PROJECT

Pname	<u>Pnumber</u>	Plocation
-------	----------------	-----------

Step 2: Mapping of Weak Entity Types

11

- For each weak entity type W with owner entity type E , create a relation R that includes all the simple attributes (or components of a composite attribute) of W as attributes of R .
- Then include the PK attributes of E as foreign key (FK) attributes of R .
- Then make the PK of R the composition of the PK of E and the weak/partial key of W .
- If the owner of W is another weak entity type W' with owner E , then map W' first and map W subsequently.

After Steps 1-2

12

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary
-------	-------	-------	------------	-------	---------	-----	--------

DEPARTMENT

Dname	<u>Dnumber</u>
-------	----------------

PROJECT

Pname	<u>Pnumber</u>	Plocation
-------	----------------	-----------

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------



Step 3: Mapping of Binary 1:1 Relationship Types

13

- For each binary 1:1 relationship type **R**, identify the relations S and T that correspond to the entity types participating in it.
- There are three possible approaches:
 - ▶ Foreign key approach (FKA)
 - ▶ Merged relationship approach (MRA)
 - ▶ Cross-reference or relationship relation approach (RRA)

Step 3: Mapping of Binary 1:1 Relationship Types

14

- The foreign key approach is very useful, in general.
- In **FKA**:
 - ▶ Choose one of the relations, say, S, and include the PK of T (the parent, or exporter, as it were) as FK in S (the child, or importer, as it were).
 - ▶ Then include all the simple (or component of composite) attributes of the relationship type as attributes in S.
 - ▶ It is better to choose an entity type with total participation in **R** for the role of S (i.e., as the PK importer).

Step 3: Mapping of Binary 1:1 Relationship Types

15

- In **MRA**:
 - ▶ Merge the two entity types and the relationship into a single relation.
 - ▶ This is possible when both participations are total, since the two relations will have the same number of tuples at all times.

Step 3: Mapping of Binary 1:1 Relationship Types

16

- In **RRA**:
 - ▶ Create a new, distinct relation R' for capturing the cross-referencing between S and T .
 - ▶ Then include as FKs of R' the PK of S and the PK of T .
 - ▶ Then choose one of them to be the PK of R' and assert the other to be unique (i.e., a secondary key).
 - ▶ This relation is then called a **relationship relation** (or a lookup table).

Step 4: Mapping of Binary 1:N Relationship Types

17

- For each regular binary 1:N relationship type **R** between entity types S and T, use FKA:
 - ▶ Identify the relation, say S, that stands at the N-side of R (i.e., is the child, or importer)
 - ▶ Then include the PK of T (i.e., the parent, or exporter) as FK in S
 - ▶ Then include the simple (or component of composite) attributes of **R** as attributes of S.
- Alternatively, use RRA.

Step 5: Mapping of Binary M:N Relationship Types

18

- For each binary M:N relationship type **R** between entity types S and T, use RRA:
 - ▶ Create a new relation R'.
 - ▶ Then include as FKs of R', the PKs of S and T.
 - ▶ Then make the PK of R' the composition of the PKs of S and T.
 - ▶ Then include any simple (or components of composite) attributes of **R** in R'.

After Steps 1-5

19

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

PROJECT


Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------



Step 6: Mapping of Multivalued Attributes

20

- For each multivalued attribute A in an entity type S
 - ▶ Create a new relation A' with the attribute A .
 - ▶ Then include the PK of S as an FK of A' .
 - ▶ Then make the PK of A' the composition of A and the PK of S .
 - ▶ Then, if the multivalued attribute is composite, include its components.

After Steps 1-6

21

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

PROJECT


Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------



Step 7: Mapping of N-ary Relationship Types

22

- For each n-ary, $n > 2$, relationship type **R**:
 - ▶ Create a new relation R' to represent **R**.
 - ▶ Then include the PKs of participating entity types as FKs in R' .
 - ▶ Then make the PK of R' the concatenation of the PKs of participating entity types.
 - ▶ But, if any participating entity type X does so with a cardinality constraint of 1, then do not include the PK of X in the PK of R' .
 - ▶ Then include any simple (or components of composite) attributes of **R** in R' .

Correspondence between ER and Relational

23

ER MODEL

Entity type

1:1 or 1:N relationship type

M:N relationship type

n -ary relationship type

Simple attribute

Composite attribute

Multivalued attribute

Value set

Key attribute

RELATIONAL MODEL

Entity relation

Foreign key (or *relationship* relation)

Relationship relation and *two* foreign keys

Relationship relation and n foreign keys

Attribute

Set of simple component attributes

Relation and foreign key

Domain

Primary (or secondary) key

Major Contrasts

- In a relational schema, relationship types are not represented explicitly.
- Instead, they are represented by having two attributes A and B, where one is a primary key and the other a foreign key.
- Composite and multivalued attributes are decomposed in the relational schema .
- Derived attributes need triggers and procedures (studied later in the course) to be supported.
- Specialization and generalization are only indirectly supported (as we shall now explore).



Step 8: Options for Mapping Specialization or Generalization

25

- Option 8A: Using *multiple relations* (superclass and subclasses) works for any specialization (total or partial, disjoint or overlapping).

Step 8 Example: Option 8A

26




Step 8: Options for Mapping Specialization or Generalization

27

- Option 8B: Using *multiple relations on subclass relations* only works if subclasses are total.
- It is only recommended if the specialization has disjointedness constraint.
- Otherwise, the same entity may be duplicated in several relations.

Step 8 Example: Option 8B

28



CAR

<u>Vehicle_id</u>	License_plate_no	Price	Max_speed	No_of_passengers
-------------------	------------------	-------	-----------	------------------

TRUCK

<u>Vehicle_id</u>	License_plate_no	Price	No_of_axles	Tonnage
-------------------	------------------	-------	-------------	---------


Step 8: Options for Mapping Specialization or Generalization

29

- Option 8C: Using a *single relation with one so-called type (or discriminating) attribute* whose value in a tuple indicates which subclass the tuple belongs to.
- This works only if subclasses are disjoint and still has the potential for generating many NULL values if many specific attributes exist in the subclasses.

Step 8 Example: Option 8C

30



EMPLOYEE

<u>Ssn</u>	Fname	Minit	Lname	Birth_date	Address	Job_type	Typing_speed	Tgrade	Eng_type
------------	-------	-------	-------	------------	---------	----------	--------------	--------	----------


Step 8: Options for Mapping Specialization or Generalization

31

- Option 8D: Using a *single relation with multiple Boolean type attributes*, each of which indicates whether or not the tuple belongs to the corresponding subclass.
- This work when subclasses are overlapping and will also work for a disjoint specialization.

Step 8 Example: Option 8D

32




PART

<u>Part_no</u>	Description	Mflag	Drawing_no	Manufacture_date	Batch_no	Pflag	Supplier_name	List_price
----------------	-------------	-------	------------	------------------	----------	-------	---------------	------------


A Specialization Lattice with Multiple Inheritance

33



Mapping the Lattice Using Various Options

34



Step 9: Mapping of Union Types (Categories)

35

- A category (or union type) is a subclass of the union of two or more superclasses that have different keys because they can be of different entity types.
- If the defining superclasses have different keys, the custom is to specify a new key attribute, called a **surrogate key**.



Step 9: Mapping of Union Types (Categories)

36

- For a category C, create a relation C' that includes all the attributes of C.
- Then make the PK of C' the surrogate key of C.
- Then include the PK of C' as FK in the relations corresponding to each of the superclasses of C.
- Then, optionally, add a type (or discriminating) attribute to C' to indicate the entity type (i.e., what is the superclass) of each tuple.
- Note that if a particular entity in a superclass is not a member of C, it would have a NULL surrogate key, i.e., it does not appear as a tuple in C'.

Step 9 Example: Mapping Categories

37



In The Next Lecture

- We'll learn how to analyze, evaluate and improve a logical model.
- For that we will study the theory of normalization, based on functional dependencies.