
INNOVATIVE DECKING SOLUTIONS



501.945.1919 * 888.450.DECK * 3912 E. Progress * N. Little Rock, AR 72114

Deckrite.com | 





CHOICE

DeckRite is a durable, low maintenance, flexible vinyl covering designed for applications on wooden or concrete decks, patios, balconies, breezeways, or any exterior walkway. It is slip-resistant, mildew-resistant, waterproof, and engineered specifically for long-term performance. The membrane comes in five standard colors and is suitable for all climates.*

VALUE

DeckRite also acts as a waterproofing membrane which can be used on installations over living areas or on raised decks to keep the space below dry. It is also great for multiple deck applications on apartments and condominiums. No other product gives you more value for your dollars.



INSTALLATION

Installation of the product is simple, clean, and fast. DeckRite can recommend installers in your area or general contractors should be capable of the installation process. For do-it-yourselfers, our customer service department can help guide you through your DeckRite installation by providing all of the necessary materials to make your installation quick and trouble-free. This includes adhesives (water-based for wood, solvent-based for concrete), color coordinated, powder-coated aluminum termination bar, screws, and caulk. Hot air welding guns (for seaming) are available for rental. Installation DVD (upon request), written installation instructions, and technical data are also available on our website.



MAINTENANCE

Traditional wood decks require the Rites of Spring: sanding, power washing, staining, or sealing to keep them looking nice. With DeckRite, maintenance translates to little more than an occasional spray from the garden hose to keep the surface looking clean and new. DeckRite is resistant to staining from most household products. Make Spring a time for enjoyment.

SERVICE

DeckRite offers a 7-year limited warranty for 50 mil and 10-year limited warranty for 60 mil against manufacturing defects. Please read the DeckRite warranty for full details. Customer service at DeckRite is the lifeline to our customers. This attitude is paramount for every employee at DeckRite, who individually and collectively share the same commitment to serving our customers.

DeckRite 500 & 600 SERIES

DeckRite *500 Series* (50 mil, 3 Ply) & *600 Series* (60 mil, 3 Ply)

Physical Property		Unit	Test Method	DeckRite 500	DeckRite 600
Color				Tan, Gray, Marble, Cream, Sand*	Tan, Gray*
Width		Inches		68"	68"
Length		Yards		30 yds	30 yds
Thickness		Mils**	ASTM D751	50 mils (1.25mm)	60 mils (1.5 mm)
Elongation (at break)	w	%	ASTM D751	32	32
	f	%	ASTM D751	38	38
Abrasion Resistance Tabor, cs10, 1000g. 1500 cycles		Visual		Pass	Pass
Low Temp Impact		-22°F (-30°C)	ASTM D1790	Pass	Pass
UV Exposure		5000 hrs.	ASTM G53	No Change	No Change
Heat Aging		7 days @ 158°F (70°C)	Visual	ASTM D751	No Change
Dimensional Stability		DeckRite 600 %		DeckRite 600 CAN/CGSB 37.54-94	Mach Dir. -0.08% Cross Dir. -0.14%

Colors: Special Order Colors Available

Fade-Resistant: No appreciable color change after accelerated exposure of 5,000 hours using Weatherometer and/or FadeMeter.

This information is intended as a general specification guideline. Properties may vary from those stated or change without notice.

* As with most exterior materials, colors may change with time. Check warranty details.

**1 Mil = 0.001 inches

- Enhances the look of exterior walkways and decks
- Eliminates painting or staining wooden decks each year
- Can be applied to most surfaces
- Durable
- Slip-resistant
- Easy to install
- Easy to keep clean
- Waterproofing system
- Resists mildew, chemicals, and ultraviolet rays
- Eliminates the hazards of wood splinters and unsightly concrete spalling and cracking
- Complies with the ADA (Americans with Disabilities Act) for slip resistance

Deckrite.com |



SAHARA TAN



SLATE GRAY



TUSCANY SAND



LAKEWOOD MARBLE



TROPICAL CREAM

