

ProGuard PVC Walk Tread

Diamond-plate textured PVC walk tread for rooftop access and service paths

PRODUCT DESCRIPTION

DeckRite **ProGuard PVC Walk Tread** is a three-ply PVC membrane with heavy-duty polyester reinforcement laminated between two vinyl films. The diamond-plate texture improves slip resistance while the construction is formulated for sun exposure, mildew resistance and routine foot traffic.



COLOR OPTIONS

Safety Yellow	Gray
---------------	------

INSTALLATION GUIDELINES

- PREPARE SURFACE** Clean the PVC membrane completely. The surface must be dry and free of debris.
- POSITION MATERIAL** Place ProGuard with the textured side up. Cut into manageable lengths and allow the material to relax before welding.
- MAINTAIN DRAINAGE** Lay out sections so they do not create or worsen ponding water.
- PROTECT SEAMS** Do not install the walk tread directly over PVC membrane seams.
- HOT-AIR WELD** Weld the perimeter of each section to the compatible PVC membrane. Original guidance specifies installation at 60°F-80°F (16°C-27°C); adjust welder settings for ambient conditions.

PRODUCT DETAILS

PROPERTY	VALUE
Thickness	80 mil
Roll width	36 in.
Roll length	60 ft
Weight	8.79 oz/sq. ft.

PHYSICAL PROPERTIES

PROPERTY	RESULT	METHOD
Tensile strength	147 lbf/in.	ASTM D751
Tear strength	58 lbf	ASTM D751
Peel strength	15 lbf/in.	ASTM D751

QUALITY TESTING

TEST	RESULT / OBSERVATION
Mildew - G21	PASS - no mold after 28 days
Abrasion - D3389	PASS - <0.5 g loss after 1,000 revolutions
UV - D751	PASS - 5,000 hr at 50°C
Cold crack - D746	PASS - no visible crazing at -25°C
Flame - GM 9070P	PASS - does not support combustion after ignition
Tensile retention - UL 1581	PASS - <5% dimensional change
Slip resistance - C1028	PASS - no change when wet