

```
vcitty
DT> No request selected -> looking for one!
DT> Counting requests
DT> Starting loop
DT> Send sync
DT> Send sync not executable
DT> Counting requests=: 0
DT> No pending requests
DT> Adding pending request in outWaitqueue
DT - Controller -> Waiting for request!
DT - Controller -> Releasing mutex
my name = Magnetron
DT> Trace function
DT - Magnetron -> -> (====) Entering state + WaitForStart
DT> Trace function
DT - Magnetron -> Locking mutex
DT - Magnetron -> Mutex locked
DT - Magnetron -> Going to execute request
DT> No request selected -> looking for one!
DT> Counting requests
DT> Starting loop
DT> receive sync
DT> Counting requests=: 1
DT> At least one pending request: 1
DT> selectedIndex=: 1
DT> Getting request at index: 0
```

```
Terminal — xterm — 88x24

SystemC 2.2.0 --- Oct 10 2009 07:49:18
Copyright (c) 1996-2006 by all Contributors
ALL RIGHTS RESERVED
Packaged for MacOS by Logic Poet: http://www.logicpoet.com

Initializing memories with 5a
caba-vgmn-mutekh_kernel_tutorial SoCLib simulator for MutekH
Initializing memories with 5a
Initializing memories with 5a
[GDB] SOCLIB_GDB env variable may contain the following flag letters:
  X (dont break on except),      S (wait connect on except),
  C (functions branch trace),    Z (functions entry trace),    D (gdb protocol debug),
  W (dont break on watchpoints), T (exit simulation on trap), F (start frozen)
=> See http://www.soclib.fr/trac/dev/wiki/Tools/GdbServer
[GDB] listening on port 2346
Loading at 0x60000000 size 1048576: .text .rodata .except .contextdata .data .bss
Warning: locale not supported by Xlib, locale set to C
Loading at 0x802000 size 4096: nothing
Loading at 0 size 4096: nothing
Loading at 0xbfc00000 size 4096: .boot
Loading at 0xffffffff80 size 128: nothing
Loading at 0x80000000 size 16777216: nothing
Loading at 0x7f000000 size 16777216: nothing
```