



PLONK: A Universal zkSNARK Proof System

Tal Derei



1. **Primer** into Zero-Knowledge
2. **General Background:** Proof Systems
3. **PLONK**
4. **Tutorial:** Circom and SnarkJS

1. Zero-Knowledge




What is Zero Knowledge?




Zero Knowledge: “Way for a prover to convince verifier that something is true without revealing anything about why it's true.”

Rooted in advanced mathematics and cryptography!



- **zkSNARKs** = cryptographic **proofs**
 - Enables a prover to prove a mathematical statement to a verifier with a short proof and succinct verification using zero knowledge techniques




Where's Waldo?




Blockchain Example



- **zk-Rollups** = Layer-2 scaling solutions that use zero-knowledge proofs to prove to the Layer-1 blockchain that transactions were executed correctly.




2. General Background: Proof Systems



Generic Proof System Mechanics



- **Circuits**
- **Arithmetization**
- **Polynomial Commitments**



Arithmetic Circuit: A program you want to generate a proof for.

Circuits consist of **constraints** must be of the form $A * B + C = 0$, where A, B and C are linear combinations of signals.

Circom Circuit

```
pragma circom 2.0.0;


/*This circuit template checks that c is the multiplication of a and b.*/

template Multiplier2 () {

    // Declaration of signals.
    signal input a;
    signal input b;
    signal output c;

    // Constraints.
    c <== a * b;
}
```

But how do we generate a proof for an arbitrary circuit?



Arithmetize the circuit!

...

The circuit defines some statement you want to prove, and arithmetization transforms a statement, for example:

[1] “this transaction is valid, and I know the private keys used to generate it”

→

[2] “I know some polynomials that satisfies some polynomial identity”

Arithmetization: Process of converting a Computational Integrity (CI) statement into an algebraic representation represented by polynomials

Arithmetization itself is composed of two steps:

[1] Generating the execution trace and polynomial constraints

[2] Transforming these two objects into a single low-degree polynomial

How does this apply back to prover-verifier?

- prover and the verifier agree on what the polynomial constraints are in advance.
- prover then generates an execution trace of the program, and tries to convince the verifier that the polynomial constraints are satisfied over this execution trace, unseen by the verifier.

Concrete Example: Supermarket Receipt

item	price
Avocado	\$4.98
Apple	\$7.98
Milk	\$3.45
Bread	\$2.65
Brown Sugar	\$1.40
<hr/>	
total	\$20.46

CI statement: prove the total sum we should pay at the supermarket was computed correctly!

- **Proof** = Receipt
- **Naive Verification:** Compute the total sum by going over every item in the list, and check it against the number at the bottom of the receipt
- **Succinct Verification:** Arithmetization (Execution Trace + Polynomial Constraints)

Execution Trace: Table that represents all the steps of the underlying computation

item	price	running total
Avocado	\$4.98	\$0.00
Apple	\$7.98	\$4.98
Milk	\$3.45	\$12.96
Bread	\$2.65	\$16.41
Brown Sugar	\$1.40	\$19.06
<hr/>		
total	\$20.46	\$20.46

Adding “running total” column allows us to verify each row individually, given its previous row.

Notice that the same constraint is applied to each pair of rows.

Polynomial Constraints: Rephrase the correctness conditions as a set of linear polynomial constraints in $A_{i,j}$.

- 1) $A_{0,2} = 0$ // We start the running total from 0.
- 2) $\forall 1 \leq i \leq 5 : A_{i,2} - A_{i-1,2} - A_{i-1,1} = 0$ // Each row's running total is correct.
- 3) $A_{5,1} - A_{5,2} = 0$ // The last running total is the total sum.

Now we can transform these **constraints** into **polynomials**, and play a challenge game between prover and verifier.

Polynomial Commitments



- **Polynomial Commitments**: Allows a prover to publish a value (*commitment*), while keeping the value hidden to others (*hiding*).
 - Prover commits to a polynomial P (i.e. bind original message with a polynomial)

PC Schemes	KZG10	IPA	FRI	DARKS
Low level tech	Pairing group	Discrete log group	Hash function	Unknown order group
Setup	G_1, G_2 groups g_1, g_2 generators e pairing function s_k secret value in F	G elliptic curve g^n independent elements in G	H hash function w unity root	N unknown order g random in N q large integer
Commitment	$(a_0s^0 + \dots + a_ns^n)g_1$	$a_0g_0 + \dots + a_ng_n$	$H(f(w^0), \dots, f(w^n))$	$(a_0q^0 + \dots + a_dq^d)g$

**Different ZKPs
have different
Commitment
Schemes**

Polynomial Commitment



- Prover commits to certain polynomial \mathbf{P} (bind original message to polynomial)
- Prover proves the value of polynomial at certain point \mathbf{Z} satisfies $\mathbf{P(Z)}$ through the proof WITHOUT revealing the polynomial

$$\mathbf{P(Z)} = \mathbf{z}$$

Polynomial Commitment



A polynomial commitment is a sort of “hash” of some polynomial $P(x)$ with the property that you can perform arithmetic checks on hashes.

Polynomial Commitments:

$h_P = \text{commit}(P(x)) \text{ on } P(x)$

$h_Q = \text{commit}(Q(x)) \text{ on } Q(x)$

$h_R = \text{commit}(R(x)) \text{ on } R(x)$

We can show:

- If $P(x) + Q(x) = R(x)$ OR $P(x) * Q(x) = R(x)$, you can generate a proof that proves this relation against h_P, h_Q, h_R
- If $P(z) = a$ you can generate a proof (known as an “opening proof”) that the evaluation of P at z is indeed a


...What's the point?

There exists verifiable relationships between **polynomials**!

-
-
-

Therefore a prover can convince a verifier using
PLONK proofs composed of these polynomials!

3. PLONK



→ PLONK **Overview**

→ PLONK **Recipe** and Ingredients

→ **Intuition** about PLONK

Overview

To understand **PLONK**, you have to first understand the concept of an **MPC Ceremony**
...and how PLONK improves it.

Multi-Party Computation (MPC) Ceremony: coordinated event that generates the parameters that kick off SNARK-based systems

-
-
-

These parameters are the **private keys** used to generate and verify proofs for circuits!

These events are known as **trusted-setups** and are necessary to generate proofs!

Three Flavours of SNARK/STARK



Non-Universal

- Example: **Groth16**
- Circuit-specific trusted setup
- Large CRS required


Universal

- Example: **PLONK**
- Requires trusted setup only once
- Smaller SRS than non-universal

Transparent


- Example: **STARKs**
- No trusted setup
- Small CRS, Larger proof sizes

Comparing SNARKs



PLONK: A Universal zkSNARK Proof System

Developed by **AZTEC** and **Protocol Labs**




Protocol Labs



aztec

<u>Proof Generation:</u>	Log-Linear $O(n \log n)$ for <u>ALL</u> zk-SNARKs
<u>Proof Verification:</u>	Poly-Logarithmic $O(\log n)$
<u>Proof Size:</u>	0.5 - 1 KB
<u>Trusted Setup:</u>	Yes, <u>Universal</u>

PLONK Recipe



We need to **transform** an arbitrary program into something a proving system can understand...so we can generate a **proof**!

...

These ZKP constructions understand **polynomials** under the hood.

How do we generate a PLONK proof for an arbitrary program? What are the ingredients needed?

1. **Circuit**: Represent your program as an arithmetic circuit (i.e. gates).
2. **Arithmetization**: Convert your circuit description into a polynomial identity / relationship.
3. **Polynomial Commitments**: Evaluate the polynomial identity using a succinct polynomial commitment scheme.

The Final Product



PLONK is fundamentally a **protocol** to prove:

$$f(x) = 0, \forall x \in H, H = \{h_1, h_2, \dots, h_n\}$$

Prover sends that polynomial to verifier, who verifies:

$$f(h_1) = 0$$

$$f(h_2) = 0$$

.

we can find the number of polynomial roots by,

.

$$f(h_n) = 0$$

But there's a more **succinct** verification method:

$$f(x) = (h_1 - x)(h_2 - x) \dots t(x)$$

Where the product $Z_H(x)$ is **vanishing** polynomial of domain H , and $t(x)$ is the **quotient polynomial**.

So if we have $f(x)$ and we divide it by the vanishing polynomial $Z_H(x)$, the remainder is the quotient polynomial $t(x)$.

Now comes in the **Schwartz-Zippel Lemma**:

$$\text{polynomial } f = g, \text{ then } f(x) = g(x) \forall x$$

And

$$L(x) = f(x) - g(x) = 0$$

Using this knowledge, we can show: **[SEE NEXT SLIDE]**


The Final Product



ZKP Protocol: Trying to prove that polynomial is vanishing in the domain of H

PROVER

VERIFIER




Verifier checks whether $f(r) = Z_H(r) \cdot t(r)$

Instead of checking all the evaluations of domain H , we're checking the evaluation of two polynomials at random points.

This is **succinct verification**!

Programs → Circuits



PLONK Circuits



PROVER

VERIFIER

Public Inputs
(solution)

Sudoku
Problem
(Python)

Program P

Output
**(TRUE /
FALSE)**


...Now we convert the program into an **arithmetic circuit** composed of **gates**!

PLONK Circuits



PROVER

VERIFIER



- Arithmetic Circuits described with $+$ and $*$ **gates**

- **Addition** gates aren't free



- ...but '**custom**' gates are!



Arithmetization:


Arithmetic Circuits \rightarrow Constraint System

PLONK Constraint System



Prover: knows a such that $b - 1 = a^2$.
example, $a = 5, b = 26$.

Arithmetic Circuit:



Let's write these constraints as set of equations, For
known as a **constraint system**:

$$(1) l_1 \cdot r_1 - o_1 = 0$$

$$(2) l_2 + 1 - o_2 = 0$$

and set of **copy constraints**:

$$l_1 = r_1$$

$$o_1 = l_2$$

Now we normalize these equations before we can
convert them to polynomials. PLONK has a special
equation to do it:

$$l_i \cdot q_{L_i} + r_i \cdot q_{R_i} + o_i \cdot q_{o_i} + q_{c_i} + l_i \cdot r_i \cdot q_{M_i} = 0$$

$$5 \cdot 0 + 5 \cdot 0 - 25 \cdot 1 + 0 + 5 \cdot 5 \cdot 1 = 0$$

$$- 25 \cdot 1 + 0 \cdot 0 - 26 \cdot 1 - 1 - 25 \cdot 0 \cdot 0 = 0$$

Constraint System \rightarrow Polynomials

View as a **table**, and treat all the columns as separate **vectors**:

$$l \cdot q_L + r \cdot q_R + o \cdot q_o + q_c + l \cdot r \cdot q_M = 0$$

$$5 \cdot 0 + 5 \cdot 0 - 25 \cdot 1 + 0 + 5 \cdot 5 \cdot 1 = 0$$

$$-25 \cdot 1 + 0 \cdot 0 - 26 \cdot 1 - 1 - 25 \cdot 0 \cdot 0 = 0$$

So the **vectors** look like this:

$$l = (5, -25)$$

$$q_L = (0, 1)$$

...

Now we convert the vectors into polynomials, known as **interpolation**

So let's create a domain $H = \{h_1, h_2\}$ in a field F .

Now let's take a polynomial $l(x)$ such that

$$l(1) = 5$$

$$l(2) = -25$$

So we're **interpolating** the vector l into $l(x)$.

Now, let's do it for all vectors.

$$f(x) = l(x) \cdot q_L(x) + r(x) \cdot q_R(x) + o(x) \cdot q_o(x) + q_c(x) + l(x) \cdot r(x) \cdot q_M(x) = 0$$

and we compress circuit into single polynomial!

So where are we?

→ We have **compressed** an entire circuit into a single polynomial!

and

→ The verifier needs to **verify** that the prover's polynomial, which represents the execution of the circuit, is equal to 0!

→ Let's see what the PLONK protocol does with this polynomial.

The Protocol

The Protocol



PLONK is fundamentally a **protocol** to prove:

$$f(x) = 0, \forall x \in H, H = \{1, 2\} \in F$$


We can rewrite the polynomial as:

$$f(x) = (1 - x)(2 - x) \dots t(x)$$

Where the product $Z_H(x)$ is **vanishing** polynomial of domain H , and $t(x)$ is the **quotient polynomial**.

...

ZKP Protocol: Trying to prove that polynomial is vanishing in the domain of H



Verifier checks whether $f(r) = Z_H(r) \cdot t(r)$

Instead of checking all the evaluations of domain H , we're checking the evaluation of two polynomials at random points

This is **succinct verification!**


BUT...how do we know the prover sending $f(r)$ and $t(r)$ to the verifier is correct?

AND...The prover and verifier want to perform this polynomial dance in such a way that allows the prover to hide some parts of the polynomial.

So how do we perform this dance?

Polynomial

$$f(x) = l(x) \cdot q_L(x) + r(x) \cdot q_R(x) + o(x) \cdot q_0(x) + q_c(x) + l(x) \cdot r(x) \cdot q_M(x) = 0$$



Verifier checks whether: $f(z) = Z_H(z) \cdot t(z)$

where $Z_H(z) \cdot t(z) = l(z) \cdot q_L(z) + r(z) \cdot q_R(z) + o(z) \cdot q_0(z) + q_c(z) + l(z) \cdot r(z) \cdot q_M(z)$

Polynomial Commitment Scheme (PCS)

Polynomial Commitments



Let's take the polynomial $l = l_0 + l_1x + l_2x^2 \dots$

Then prover can **commit** the polynomial and publish the commitment

$$L = \text{commit}(l)$$

Verifier can then ask to **evaluate** the polynomial at some point z , and prover sends back:

(1) The polynomial evaluated at z $l(z)$

(2) Proof π

PLONK uses the **KZG PCS**, requires **trusted setup**

Final Intuition

Lagrange Bases and Multiplicative Subgroups

Lagrange Bases and Multiplicative Subgroups



Lagrange Bases: a different way of encoding a polynomial


PlonK: Permutations over Lagrange-bases for
Oecumenical Noninteractive arguments of
Knowledge

Ariel Gabizon*
Aztec

Zachary J. Williamson
Aztec


Oana Ciobotaru

April 27, 2022



Lagrange Interpolation

4. Tutorial: Circom and SnarkJS



Tutorial on building circuits and generating **PLONK proofs** using Circom and SnarkJS.


- **Circom:** compiler written in Rust for compiling circuits written in the circom programming language. The compiler outputs the representation of the arithmetic circuit as a set of constraints.

==> circom
CIRCUIT COMPILER

- **SnarkJS:** a javascript and pure web assembly implementation of the Groth16/PLONK schemes, generating and validating proofs for circom circuits.

Future research involves applying **RDMA** integration to PLONK and creating a **GPU-based PLONK prover**.

It would be interesting to see how this implementation scales for general computations, like arbitrary smart contract calls, on **Layer-2 zkEVMs**.



References



<https://eprint.iacr.org/2019/953.pdf>
<https://www.youtube.com/watch?v=ty-LZf0YCK0>
https://www.youtube.com/watch?v=n6_nicl4ckM
<https://medium.com/starkware/arithmeticization-i-15c046390862>
<https://aztec.network/research/>
https://www.youtube.com/watch?v=bz16BURH_u8
https://www.youtube.com/watch?v=RUZcam_jrz0
<https://hackmd.io/@aztec-network/plonk-arithmeticization-air>
<https://zeroknowledge.fm/news-2-on-optimization-plonk/>

Thank you!



<https://sss.cse.lehigh.edu/>