


# Chapter 4:

## Making Decisions



# Relational Operators

● Used to compare numbers to determine relative order

● Operators:

>	Greater than
<	Less than
>=	Greater than or equal to
<=	Less than or equal to
==	Equal to
!=	Not equal to

# Relational Expressions

- Boolean expressions – `true` or `false`

- Examples:

`12 > 5` **is** `true`

`7 <= 5` **is** `false`

if `x` is 10, then

`x == 10` **is** `true`,

`x != 8` **is** `true`, and

`x == 8` **is** `false`

# Relational Expressions

- Can be assigned to a variable:

```
result = x <= y;
```


- Assigns 0 for `false`, 1 for `true`

- Do not confuse `=` and `==`

# The `if` Statement

- Allows statements to be conditionally executed or skipped over
- Models the way we mentally evaluate situations:
  - "If it is raining, take an umbrella."
  - "If it is cold outside, wear a coat."

# Flowchart for Evaluating a Decision



# The `if` Statement

## ● General Format:

```
if (expression)  
    statement;
```

● If the *expression* is true, then *statement* is executed.

● If the *expression* is false, then *statement* is skipped.

# if Statement in Program 4-2

## Program 4-2

```
1 // This program averages three test scores
2 #include <iostream>
3 #include <iomanip>
4 using namespace std;
5
6 int main()
7 {
8     int score1, score2, score3; // To hold three test scores
9     double average;             // To hold the average score
10
```

Continued...  
8



# if Statement in Program 4-2

## Program 4-2 *(continued)*

```
11    // Get the three test scores.
12    cout << "Enter 3 test scores and I will average them: ";
13    cin >> score1 >> score2 >> score3;
14
15    // Calculate and display the average score.
16    average = (score1 + score2 + score3) / 3.0;
17
18    cout << "Your average is " << average << endl;
19
20    // If the average is greater than 95, congratulate the user.
21    if (average > 95)
22        cout << "Congratulations! That's a high score!\n";
23    return 0;
24 }
```


### Program Output with Example Input Shown in Bold

Enter 3 test scores and I will average them: **80 90 70** [Enter]  
Your average is 80.0

### Program Output with Other Example Input Shown in Bold

Enter 3 test scores and I will average them: **100 100 100** [Enter]  
Your average is 100.0  
Congratulations! That's a high score!

# Flowchart for Program 4-2 Lines 21 and 22



# if Statement Notes

- Do not place `;` after *(expression)*
- Place *statement;* on a separate line after *(expression)*, indented:

```
if (score > 90)  
    grade = 'A';
```

# Expanding the `if` Statement

- To execute more than one statement as part of an `if` statement, enclose them in `{ }`:

```
if (score > 90)
{
    grade = 'A';
    cout << "Good Job!\n";
}
```

- `{ }` creates a block of code

# The `if/else` statement

- Provides two possible paths of execution
- Performs one statement or block if the *expression* is true, otherwise performs another statement or block.

# The `if/else` statement

## General Format:

```
if (expression)  
    statement1;    // or block  
else  
    statement2;    // or block
```

- If the *expression* is true, then *statement1* is executed and *statement2* is skipped.
- If the *expression* is false, then *statement1* is skipped and *statement2* is executed.

# The `if/else` statement and Modulus Operator in Program 4-8


## Program 4-8

```
1 // This program uses the modulus operator to determine
2 // if a number is odd or even. If the number is evenly divisible
3 // by 2, it is an even number. A remainder indicates it is odd.
4 #include <iostream>
5 using namespace std;
6
7 int main()
8 {
9     int number;
10
11     cout << "Enter an integer and I will tell you if it\n";
12     cout << "is odd or even. ";
13     cin >> number;
14     if (number % 2 == 0)
15         cout << number << " is even.\n";
16     else
17         cout << number << " is odd.\n";
18     return 0;
19 }
```

### Program Output with Example Input Shown in Bold

```
Enter an integer and I will tell you if it
is odd or even. 17 [Enter]
17 is odd.
```

# Flowchart for Program 4-8 Lines 14 through 18





# Testing the Divisor in Program 4-9

## Program 4-9

```
1  // This program asks the user for two numbers, num1 and num2.
2  // num1 is divided by num2 and the result is displayed.
3  // Before the division operation, however, num2 is tested
4  // for the value 0. If it contains 0, the division does not
5  // take place.
6  #include <iostream>
7  using namespace std;
8
9  int main()
10 {
11     double num1, num2, quotient;
12
```

Continued...  
17

# Testing the Divisor in Program 4-9

## Program 4-9 *(continued)*

```
13     // Get the first number.
14     cout << "Enter a number: ";
15     cin >> num1;
16
17     // Get the second number.
18     cout << "Enter another number: ";
19     cin >> num2;
20
21     // If num2 is not zero, perform the division.
22     if (num2 == 0)
23     {
24         cout << "Division by zero is not possible.\n";
25         cout << "Please run the program again and enter\n";
26         cout << "a number other than zero.\n";
27     }
28     else
29     {
30         quotient = num1 / num2;
31         cout << "The quotient of " << num1 << " divided by ";
32         cout << num2 << " is " << quotient << ".\n";
33     }
34     return 0;
35 }
```

### Program Output with Example Input Shown in Bold

(When the user enters 0 for num2)

Enter a number: **10 [Enter]**

Enter another number: **0 [Enter]**

Division by zero is not possible.

Please run the program again and enter  
a number other than zero.

# Nested `if` Statements

- An `if` statement that is nested inside another `if` statement
- Nested `if` statements can be used to test more than one condition

# Use Proper Indentation!


```
if (employed == 'Y')
{
    if (recentGrad == 'Y') // Nested if
    {
        cout << "You qualify for the special ";
        cout << "interest rate.\n";
    }
    else // Not a recent grad, but employed
    {
        cout << "You must have graduated from ";
        cout << "college in the past two\n";
        cout << "years to qualify.\n";
    }
}
else // Not employed
{
    cout << "You must be employed to qualify.\n";
}
```

This if and else go together.

This if and else go together.

This if and else go together.

# Flowchart for a Nested `if` Statement



# The `if/else if` Statement

- Tests a series of conditions until one is found to be true
- Often simpler than using nested `if/else` statements
- Can be used to model thought processes such as:

"If it is raining, take an umbrella,  
else, if it is windy, take a hat,  
else, take sunglasses"

# if/else if Format

```
if (expression)  
    statement1;    // or block  
else if (expression)  
    statement2;    // or block  
.  
. // other else ifs  
.  
else if (expression)  
    statementn;    // or block
```

# The `if/else if` Statement in Program 4-13

```
21    // Determine the letter grade.
22    if (testScore >= A_SCORE)
23        cout << "Your grade is A.\n";
24    else if (testScore >= B_SCORE)
25        cout << "Your grade is B.\n";
26    else if (testScore >= C_SCORE)
27        cout << "Your grade is C.\n";
28    else if (testScore >= D_SCORE)
29        cout << "Your grade is D.\n";
30    else
31        cout << "Your grade is F.\n";
```



# Logical Operators

- Used to create relational expressions from other relational expressions
- Operators, meaning, and explanation:

& &	AND	New relational expression is true if both expressions are true
	OR	New relational expression is true if either expression is true
!	NOT	Reverses the value of an expression – true expression becomes false, and false becomes true

# Logical Operators-Examples

```
int x = 12, y = 5, z = -4;
```

<code>(x &gt; y) &amp;&amp; (y &gt; z)</code>	true
<code>(x &gt; y) &amp;&amp; (z &gt; y)</code>	false
<code>(x &lt;= z)    (y == z)</code>	false
<code>(x &lt;= z)    (y != z)</code>	true
<code>! (x &gt;= z)</code>	false

# The logical operators in Coding

- The logical **&&** Operator :

```
if (x > y && y > z)
    cout << "x is greater than y and z";
```

- The logical **||** Operator :

```
if (z < x || z == y)
    cout << "z is less than x OR z equals y";
```

- The logical **!** Operator :

```
if (!(y >= z))
    cout << "y is less than z";
else
    cout << "y is greater than z ";
```

# Checking Numeric Ranges with Logical Operators

- Used to test to see if a value falls **inside** a range:

```
if (grade >= 0 && grade <= 100)
    cout << "Valid grade";
```

- Can also test to see if value falls **outside** of range:

```
if (grade <= 0 || grade >= 100)
    cout << "Invalid grade";
```

- Cannot use mathematical notation:

```
if (0 <= grade <= 100) //doesn't work!
```

# Menus

- Menu-driven program: program execution controlled by user selecting from a list of actions
- Menu: list of choices on the screen
- Menus can be implemented using `if/else if` statements

# Menu-Driven Program Example

```
#include <iostream>

using namespace std;

int main()
{
    char choice;

    cout << "Good day! Welcome to The Bakery! What would you like today?\n";
    cout << "A: Earl Gray Tea and Biscuits\n";
    cout << "B: Coffee and a blueberry scone\n";
    cout << "C: Espresso and a tea biscuit\n";
    cout << "D: Coffee and a Muffin\n";
    cout << "E: The Assorted Tea, Scones, and Biscuits Platter\n";

    cout << "\n Select your choice: ";
    cin >> choice;

    if (choice == 'A' || choice == 'a')
        cout << "A: Earl Gray Tea and Biscuits\n";

    else if (choice == 'B' || choice == 'b')
        cout << "B: Coffee and a blueberry scone\n";

    else if (choice == 'C' || choice == 'c')
        cout << "A: Earl Gray Tea and Biscuits\n";

    else if (choice == 'D' || choice == 'd')
        cout << "D: Coffee and a Muffin\n";

    else if (choice == 'E' || choice == 'e')
        cout << "E: The Assorted Tea, Scones, and Biscuits Platter\n";

    else //Displaying error message
        cout << "Invalid input\n";

    return 0;
}
```

# Validating User Input

- Input validation: inspecting input data to determine whether it is acceptable
- Bad output will be produced from bad input

# Input Validation in Program 4-19

```
16     int testScore; // To hold a numeric test score
17
18     // Get the numeric test score.
19     cout << "Enter your numeric test score and I will\n"
20           << "tell you the letter grade you earned: ";
21     cin >> testScore;
22
23     // Validate the input and determine the grade.
24     if (testScore >= MIN_SCORE && testScore <= MAX_SCORE)
25     {
26         // Determine the letter grade.
27         if (testScore >= A_SCORE)
28             cout << "Your grade is A.\n";
29         else if (testScore >= B_SCORE)
30             cout << "Your grade is B.\n";
31         else if (testScore >= C_SCORE)
32             cout << "Your grade is C.\n";
33         else if (testScore >= D_SCORE)
34             cout << "Your grade is D.\n";
35         else
36             cout << "Your grade is F.\n";
37     }
38     else
39     {
40         // An invalid score was entered.
41         cout << "That is an invalid score. Run the program\n"
42              << "again and enter a value in the range of\n"
43              << MIN_SCORE << " through " << MAX_SCORE << ".\n";
44     }
```



# Comparing Characters

- Characters are compared using their ASCII values
- 'A' < 'B'
  - The ASCII value of 'A' (65) is less than the ASCII value of 'B'(66)
- '1' < '2'
  - The ASCII value of '1' (49) is less than the ASCII value of '2' (50)
- Lowercase letters have higher ASCII codes than uppercase letters, so 'a' > 'Z'

# Relational Operators Compare Characters in Program 4-20

```
10    // Get a character from the user.
11    cout << "Enter a digit or a letter: ";
12    ch = cin.get();
13
14    // Determine what the user entered.
15    if (ch >= '0' && ch <= '9')
16        cout << "You entered a digit.\n";
17    else if (ch >= 'A' && ch <= 'Z')
18        cout << "You entered an uppercase letter.\n";
19    else if (ch >= 'a' && ch <= 'z')
20        cout << "You entered a lowercase letter.\n";
21    else
22        cout << "That is not a digit or a letter.\n";
```

# Comparing `string` Objects

- Like characters, strings are compared using their ASCII values

```
string name1 = "Mary";  
string name2 = "Mark";
```

The characters in each string must match before they are equal

```
name1 > name2 // true  
name1 <= name2 // false  
name1 != name2 // true
```

```
name1 < "Mary Jane" // true
```


# Relational Operators Compare Strings in Program 4-21

```
26      // Determine and display the correct price
27      if (partNum == "S-29A")
28          cout << "The price is $" << PRICE_A << endl;
29      else if (partNum == "S-29B")
30          cout << "The price is $" << PRICE_B << endl;
31      else
32          cout << partNum << " is not a valid part number.\n";
```

# The Conditional Operator

- Can use to create short `if/else` statements

- Format: `expr ? expr : expr;`



# The `switch` Statement

- Used to select among statements from several alternatives
- In some cases, can be used instead of `if/else if` statements

# switch Statement Format

```
switch (expression) //integer
{
    case exp1: statement1;
    case exp2: statement2;
    ...
    case expn: statementn;
    default:    statementn+1;
}
```

# The `switch` Statement in Program 4-23

## Program 4-23

```
1  // The switch statement in this program tells the user something
2  // he or she already knows: the data just entered!
3  #include <iostream>
4  using namespace std;
5
6  int main()
7  {
8      char choice;
9
10     cout << "Enter A, B, or C: ";
11     cin >> choice;
12     switch (choice)
13     {
14         case 'A': cout << "You entered A.\n";
15                 break;
16         case 'B': cout << "You entered B.\n";
17                 break;
18         case 'C': cout << "You entered C.\n";
19                 break;
20         default:  cout << "You did not enter A, B, or C!\n";
21     }
22     return 0;
23 }
```

### Program Output with Example Input Shown in Bold

Enter A, B, or C: **B** [Enter]  
You entered B.

### Program Output with Example Input Shown in Bold

Enter A, B, or C: **F** [Enter]  
You did not enter A, B, or C!



# switch Statement Requirements

- 1) *expression* must be an integer variable or an expression that evaluates to an integer value
- 2) *exp1* through *expn* must be constant integer expressions or literals, and must be unique in the `switch` statement
- 3) `default` is optional but recommended

# switch Statement-How it Works

- 1) *expression* is evaluated
- 2) The value of *expression* is compared against *exp1* through *expn*.
- 3) If *expression* matches value *expi*, the program branches to the statement following *expi* and continues to the end of the `switch`
- 4) If no matching value is found, the program branches to the statement after `default:`

# break Statement

- Used to exit a `switch` statement
- If it is left out, the program "falls through" the remaining statements in the `switch` statement

# break and default statements in Program 4-25

## Program 4-25

```
1  // This program is carefully constructed to use the "fall through"
2  // feature of the switch statement.
3  #include <iostream>
4  using namespace std;
5
6  int main()
7  {
8      int modelNum;  // Model number
9
10     // Get a model number from the user.
11     cout << "Our TVs come in three models:\n";
12     cout << "The 100, 200, and 300. Which do you want? ";
13     cin >> modelNum;
14
15     // Display the model's features.
16     cout << "That model has the following features:\n";
17     switch (modelNum)
18     {
19         case 300: cout << "\tPicture-in-a-picture.\n";
20         case 200: cout << "\tStereo sound.\n";
21         case 100: cout << "\tRemote control.\n";
22                 break;
23         default:  cout << "You can only choose the 100,";
24                 cout << "200, or 300.\n";
25     }
26     return 0;
27 }
```

Continued...  
44

# break and default statements in Program 4-25

## **Program Output with Example Input Shown in Bold**

Our TVs come in three models:

The 100, 200, and 300. Which do you want? **100 [Enter]**

That model has the following features:

Remote control.

## **Program Output with Example Input Shown in Bold**

Our TVs come in three models:

The 100, 200, and 300. Which do you want? **200 [Enter]**

That model has the following features:

Stereo sound.

Remote control.

## **Program Output with Example Input Shown in Bold**

Our TVs come in three models:

The 100, 200, and 300. Which do you want? **300 [Enter]**

That model has the following features:

Picture-in-a-picture.

Stereo sound.

Remote control.

## **Program Output with Example Input Shown in Bold**

Our TVs come in three models:

The 100, 200, and 300. Which do you want? **500 [Enter]**

That model has the following features:

You can only choose the 100, 200, or 300.

# Using `switch` in Menu Systems

- `switch` statement is a natural choice for menu-driven program:
  - display the menu
  - then, get the user's menu selection
  - use user input as `expression` in `switch` statement
  - use menu choices as `expr` in `case` statements

# Variables with the Same Name

- Variables defined inside { } have local or block scope
- When inside a block within another block, can define variables with the same name as in the outer block.
  - When in inner block, outer definition is not available
  - Not a good idea

# Two Variables with the Same Name in Program 4-30

## Program 4-30

```
1 // This program uses two variables with the name number.
2 #include <iostream>
3 using namespace std;
4
5 int main()
6 {
7     // Define a variable named number.
8     int number;
9
10    cout << "Enter a number greater than 0: ";
11    cin >> number;
12    if (number > 0)
13    {
14        int number; // Another variable named number.
15        cout << "Now enter another number: ";
16        cin >> number;
17        cout << "The second number you entered was "
18             << number << endl;
19    }
20    cout << "Your first number was " << number << endl;
21    return 0;
22 }
```

## Program Output with Example Input Shown in Bold

```
Enter a number greater than 0: 2 [Enter]
Now enter another number: 7 [Enter]
The second number you entered was 7
Your first number was 2
```