

LAB 06: Stack and Queue

CS211 – Data Structures and Algorithms

Usman Institute of Technology

Fall 2019

- **How to submit:**

- Create an account on <http://www.turnitin.com/> as a Student (if you don't have already)
- Use following information at time of sign-up

- CS Section A**

- Class ID: 22664649
 - Enrollment Key: DSFALL19CSA

- CS Section B**

- Class ID: 22664651
 - Enrollment Key: DSFALL19CSB

A. Create a class ArrayStack and implement the Stack operations in the following order.

1. Add a constructor of the class that takes one argument size in order to set the size of the stack.

```
class ArrayStack:  
    def __init__(self, size):  
        // your code goes here
```

2. Add a function **IsEmpty()** that returns true if the stack is empty otherwise returns False.

```
def IsEmpty(self):  
    // your code goes here
```

3. Add a function **Push()** which takes an argument item to insert data into the stack. The function should also check the overflow condition.

```
def Push(self, item):  
    // your code goes here
```

4. Add a function **Pop()** that removes the elements from the stack. The function should also check the underflow condition.

```
def Pop():  
    // your code goes here
```

5. Add a function **Peek()** which returns the value from top of the stack.

```
def Peek(self):  
    // your code goes here
```

6. Add a function **Count()** that returns number of elements in the stack.

```
def Count():  
    // your code goes here
```

7. Add a function **Print()** which prints all the elements of the stack.

```
def Print(self):  
    // your code goes here
```

B. Create a class ArrayQueue and implement the Stack operations in the following order.

1. Add a constructor of the class that takes one argument size in order to set the size of the Queue.

```
class ArrayQueue:  
    def __init__(self, size):  
        // your code goes here
```

2. Add a function **IsEmpty()** that returns true if the queue is empty otherwise returns False.

```
def IsEmpty(self):  
    // your code goes here
```

3. Add a function **Enqueue()** which takes an argument item to insert data into the queue. The function should also check the overflow condition.

```
def Enqueue(self, item):  
    // your code goes here
```

4. Add a function **Dequeue()** that removes the elements from the queue. The function should also check the underflow condition.

```
def Dequeue(self):  
    // your code goes here
```

5. Add a function **Count()** that returns number of elements in the queue.

```
def Count():  
    // your code goes here
```

6. Add a function **Print()** that prints number of elements in the queue.

```
def Print():  
    // your code goes here
```

C. Given an expression string exp , write a function StringExp() to examine whether the pairs and the orders of “{“,”}”,“(“,”)”, “[“,”]” are correct in exp.

```
def StringExp():  
    // your code goes here
```

For example: the program should return true for exp = “[()]{ {[()]}” and false for exp = “[()]”