

Natural Language Processing (NLP)

Core of Modern NLP

Equipping You with Research Depth and Industry Skills – Data Science Oriented By:

Dr. Zohair Ahmed





www.youtube.com/@ZohairAl



Recommended Books

Speech and Language Processing

An Introduction to Natural Language Processing, Computational Linguistics, and Speech Recognition with Language Models


Third Edition draft

Daniel Jurafsky Stanford University

James H. Martin University of Colorado at Boulder

Copyright ©2025. All rights reserved.

Draft of August 24, 2025. Comments and typos welcome!



Natural Language Processing (NLP)

- Natural Language Processing (NLP) is a branch of artificial intelligence (AI) that focuses on helping computers understand, interpret, and respond to human language.
- Think of it like this:
- Humans speak in natural languages (like English, Arabic, Hindi, French).
- Computers "speak" in binary or programming languages.
- NLP acts as the bridge between the two.
- Some common examples of NLP you already interact with:
- Google Translate (language translation)
- Siri or Alexa (voice assistants)
- ChatGPT (text understanding and generation)
- Spam filters in email (detecting unwanted messages)



Real Time Use Cases













Smart **Assistants**

Search Results

Predictive text

Language **Translations**

Digital Phone Calls

Text Analytics







Detecting Duplications



Social Media Monitoring



Marketing Strategies



Descriptive Analytics



Automatic Insights

Common NLP Libraries

- General NLP toolkits
- NLTK (Natural Language Toolkit) classic library, great for teaching basics: tokenization, stemming, POS tagging.
- **spaCy** fast, industrial-strength, with built-in pipelines for tokenization, lemmatization, POS tagging, dependency parsing, and named entity recognition.
- Deep Learning-based NLP
- **Hugging Face Transformers** the go-to for pretrained models like BERT, GPT, T5. Widely used in research & production.
- AllenNLP built on PyTorch, good for experiments in academic NLP.
- Fairseq (Meta AI) powerful for sequence-to-sequence models like translation and summarization.



Common NLP Libraries

- Text Processing & Utilities
- **TextBlob** simple API for sentiment analysis, part-of-speech tagging, and translation (good for quick demos).
- Gensim specializes in topic modeling and word embeddings (e.g., Word2Vec, Doc2Vec, LDA).
- Stanford CoreNLP Java-based, but very strong for parsing and linguistic features.
- Speech & Multimodal NLP
- SpeechRecognition for converting speech to text.
- OpenAl Whisper (and Hugging Face integration) state-of-the-art speech recognition.



Why NLP is Popular right now

- Why is NLP Booming Today?
- NLP has existed in academia for decades.
- Real industry applications rushed in the last 7–10 years.

Reason 1 - Pre-trained Models & APIs

- Training NLP models needs huge data + compute.
- Big companies (Google, Facebook, OpenAl, Amazon) provide pre-trained models:
 - fastText (Facebook)
 - TensorFlow Hub (Google) BERT, USE, etc.
 - GPT-3 (OpenAI) \$4M training cost, now accessible.
- Transfer learning makes NLP accessible to small companies.

Reason 2 – Open-Source Ecosystem

- Earlier: coding from scratch in C++
- Now: Python + open-source libraries = rapid prototyping
 - spaCy
 - Gensim
 - NLTK
- Backed by community, continuously improving.

Reason 3 – Affordable Hardware & Cloud

- Past: costly GPUs & infrastructure.
- Present:
 - Cheaper GPUs.
 - Cloud platforms: AWS, Azure, Google Cloud.
 - Rent resources instead of buying.

Reason 4 – Learning Resources

- Reason 4 Learning Resources
- Before: limited access (only universities).
- Now: global accessibility.
 - Free content: YouTube, blogs, Kaggle, StackOverflow
 - Courses: Coursera, Udemy, bootcamps
 - Communities: Discord, Zoom, competitions
- Anyone can learn NLP quickly.

Reason 5 - Big Tech Investments

- Tech giants building ecosystem:
 - Google: TensorFlow, Google Home
 - Amazon: Alexa, Echo devices
 - Meta: fastText, FAIR research
- Heavy investments → smaller companies follow (FOMO effect).
- FOMO = Fear of Missing Out
- When big tech companies (Google, Amazon, Meta, etc.) invest in NLP
- Smaller companies feel pressure to adopt it too, because they don't want to miss opportunities, market share, or innovation trends.



NLP is booming

- Free pre-trained models
- Open-source libraries
- Cloud & cheap hardware
- Easy learning resources
- Big tech investments
- Future: More rapid advancements, wider adoption.

Techniques to Solve NLP Problems

- Techniques to Solve NLP Problems
- NLP has many approaches.
- 3 broad categories of techniques.

Technique 1 – Rules & Heuristics

- Based on patterns, rules, and regex.
- Example: Gmail flight ticket → auto-extracted summary.
- Regex approach:
 - Booking Ref: XXXXX" → extract confirmation number.
- Pros: Simple, precise.
- Cons: Not scalable, hard for complex text.
- Example Rules in Action
- Search "Elon Musk" → Google sidebar info.
- · Likely uses pattern-based extraction.
- Key idea: Rules can solve information extraction tasks without ML.



Technique 2 – Statistical / Machine Learning

Spam Detection

- Raw email text → Number vector → Classifier.
- Common workflow:
 - Raw text
 - Preprocessing (cleaning, lemmatization, etc.)
 - Convert text → numbers (e.g., CountVectorizer,
 TF-IDF)
 - Classification (e.g., Naïve Bayes)
- Pros: More general than rules.
- Cons: Struggles with unseen words/phrases.

Example – Spam Email

- Text: "Urgent business assistance... 55 million USD..."
- Suspicious keywords trigger spam detection.

• Pipeline:

- CountVectorizer → numeric representation.
- Naïve Bayes → spam/not spam.

Technique 2 – Statistical / Machine Learning

Spam Detection

- Raw email text → Number vector → Classifier.
- Common workflow:
 - Raw text
 - Preprocessing (cleaning, lemmatization, etc.)
 - Convert text → numbers (e.g., CountVectorizer,
 TF-IDF)
 - Classification (e.g., Naïve Bayes)
- Pros: More general than rules.
- Cons: Struggles with unseen words/phrases.

Example – Spam Email

- Text: "Urgent business assistance... 55 million USD..."
- Suspicious keywords trigger spam detection.

• Pipeline:

- CountVectorizer → numeric representation.
- Naïve Bayes → spam/not spam.

What is CountVectorizer?

• CountVectorizer is a technique to convert text into a numeric representation that machine learning models can understand. It essentially counts how often each word appears in a document. This is also known as **Bag of Words** (BoW).

What is CountVectorizer?

Step 1 – Tokenization

- Split text into individual words (tokens).
- Sentence 1: "I love NLP." → Tokens: ["I", "love", "NLP"]
- Sentence 2: "NLP is amazing!" → Tokens: ["NLP", "is", "amazing"]

Step 2 - Build Vocabulary

- Create a vocabulary of unique words from the entire text.
- Vocabulary: ["I", "love", "NLP", "is", "amazing"]
- Step 3 Count Word Occurrences
 - Count how often each word appears in each document.
 - Sentence 1: ["I", "love", "NLP"] → Word counts: I:1, love:1, NLP:1
 - Sentence 2: ["NLP", "is", "amazing"] → Word counts: NLP:1, is:1, amazing:1
- Step 4 Create Vectors
 - Convert the word counts into vectors (numeric form).
 - Sentence 1 Vector: [1, 1, 1, 0, 0]
 - Sentence 2 Vector: [0, 0, 1, 1, 1]

Word	I	love	NLP	is	amazing
Sentence 1	1	1	1	0	0
Sentence 2	0	0	1	1	1

Challenge with Statistical ML

- Example:
 - Training: "Hurry up to win cash", "You won a laptop".
 - New text: "Rush for this great deal to win money".
- CountVectorizer fails if words are unseen.
- Solution: Use embeddings that capture semantic meaning.

Technique 3 – Deep Learning

- · Uses word embeddings / sentence embeddings.
- Example: **BERT (Google)**, Hugging Face Transformers.
- Embeddings allow similar sentences to have similar vectors.
- Example:
 - "Win cash fast" ≈ "Hurry up to win money"
 - Embedding vectors → Cosine similarity.
- Hugging Face Sentence Transformers
- Input: "I love baby yoda!" vs. spam sentences.
- Output: Similarity scores (cosine similarity).
- Shows how embeddings capture semantic meaning
- https://huggingface.co/sentence-transformers





Cosine Similarity

- Imagine two arrows (vectors) starting at the
 For two vectors A and B: same point.
- If they point in exactly the same direction, they are **very similar**.
- If they point in opposite directions, they are ||B||= length (magnitude) of vector B. very different.
- If they are at a right angle, they are not similar at all.
- Cosine similarity just measures the angle between two vectors.

- Cosine Similarity= $\frac{A.B}{\|A\| \|B\|}$
- ||A||= length (magnitude) of vector A.
- Cosine similarity high (close meaning).
- Cosine similarity low (different meaning).

Naive Bayes

- Naive Bayes is a simple but effective probabilistic machine learning algorithm based on Bayes' Theorem, and it's particularly well-suited for classification tasks like text classification (e.g., spam detection, sentiment analysis).
- It's called "Naive" because it assumes that all features (words, in this case) are **independent** of each other, which is often **not true** in real-world scenarios. However, this simplification works surprisingly well in practice.

Bayes' Theorem:

Bayes' Theorem is the foundation of Naive Bayes. It calculates the probability of a class C given some features X (in NLP, the features are words in the document).

$$P(C|X) = \frac{P(X|C) \cdot P(C)}{P(X)}$$

- Where:
- P(C|X) = Posterior: Probability of class C given the features X.
- P(X|C) = Likelihood: Probability of features X given the class C.
- P(C) = Prior: The probability of class C occurring in the dataset.
- P(X) = Evidence: The probability of features X occurring, independent of the class.

Bayes' Theorem:

Bayes' Theorem is the foundation of Naive Bayes. It calculates the probability of a class C given some features X (in NLP, the features are words in the document).

$$P(C|X) = \frac{P(X|C) \cdot P(C)}{P(X)}$$

- Where:
- P(C|X) = Posterior: Probability of class C given the features X.
- P(X|C) = Likelihood: Probability of features X given the class C.
- P(C) = Prior: The probability of class C occurring in the dataset.
- P(X) = Evidence: The probability of features X occurring, independent of the class.

Bayes' Theorem:

Class Priors:

•
$$P(Spam) = \frac{2}{4} = 0.5$$
; $P(Not Spam) = \frac{2}{4} = 0.5$

- Likelihoods:
- Let's say we are given the new email: "win money".
- **P(win|Spam)**: From the training data, "win" appears 2 times in 2 spam emails (out of 2 total spam emails). So,
- $P(\text{win}|\text{Spam}) = \frac{2}{2} = 1$
- P(money|Spam): "money" appears 1 time in 2 spam emails (out of 2 total spam emails). So,
- $P(\text{money}|\text{Spam}) = \frac{1}{2} = 0.5$
- Similarly, we calculate for the Not Spam class.

Email	Class	
"Win money now"	Spam	
"Cheap offer, win now"	Spam	
"Meeting schedule"	Not Spam	
"Lunch at noon"	Not Spam	

Posterior Calculation:

- For Spam:
- P(Spam|win, money) \propto P(win|Spam) · P(money|Spam) · P(Spam) = 1 · 0.5 · 0.5 = 0.25
- For Not Spam:
- $P(\text{Not Spam}|\text{win, money}) \propto P(\text{win}|\text{Not Spam})$ · $P(\text{money}|\text{Not Spam}) \cdot P(\text{Not Spam}) = 0.25 \cdot 0.25 \cdot 0.5 = 0.03125$
- Prediction:
- Since the posterior probability of Spam is higher (0.25 vs. 0.03125), the algorithm classifies the email as Spam.