

ADVANCED ENTERPRISE STORAGE CAPABILITIES

Govern Your Storage Like an Enterprise

A step-by-step guide for pilot admins: scoped access credentials, version history, compliance-grade locked retention, legal hold, automated lifecycle policies, and a native desktop drive.

SECTION 01

What This Gives You

Beyond basic upload/download, Inaya's storage layer includes the controls enterprise IT and compliance teams expect: who can access what and for how long, the ability to recover an overwritten file, storage that genuinely cannot be deleted during a retention period, legal holds for litigation/investigation, automatic cleanup policies, and a real drive-letter view of your storage on Windows. This guide walks through each one, in Business Workspace, step by step.

CAPABILITY	WHERE TO FIND IT
Scoped access credentials	Business Workspace → S3-Compatible Storage
Versioning, locked retention, legal hold, lifecycle, health	Business Workspace → S3-Compatible Storage → Buckets, Versions & Object Protection
Desktop drive mount	Inaya Business Workspace desktop app (Windows)

SECTION 02

Scoped Access Credentials

Instead of every integration or team member holding a full-access credential, issue one scoped to exactly what it needs.

1. **Go to S3-Compatible Storage → "Restrict scope."** Click this before creating a new credential.
2. **Set a bucket.** Confines the credential to one bucket only, e.g. "finance."
3. **(Optional) Set a prefix.** Further confines it to a folder path within that bucket, e.g. "invoices/2026/." Requires a bucket to already be set.
4. **Choose operations.** Toggle any combination of READ, WRITE, DELETE, LIST. A credential with only READ selected can never write or delete, even if the raw credential is compromised.
5. **Set an expiry date.** The credential automatically stops working after this date — no manual revocation needed for time-boxed engagements (a contractor, a fixed-term integration).

Example. "Give the accounts-payable system read-only access to finance/invoices/2026/ for the next 90 days" is one credential, configured with all four fields above — enforced by Inaya's server on every request, not just hidden by the UI.

SECTION 03

Version History & Restore

1. **Open "Buckets, Versions & Object Protection."** Find the bucket you want version history for.
2. **Click "Enable versioning."** From this point forward, overwriting a file keeps the previous version instead of discarding it. Files uploaded before this point are not retroactively versioned.
3. **Click an object to see its version history.** Every version is listed with its date, and whether it's the current ("latest") one.
4. **Click "Restore" on any older version.** This makes that version's content the new current version — the file reverts, and the restore itself becomes a new entry in the version history.

Versioning can be suspended later (new overwrites stop keeping history), but every version already kept remains retrievable — nothing already protected is ever silently lost by suspending.

SECTION 04

Locked Retention (Compliance Hold)

1. **1. Enable versioning on the bucket first.** Locked retention requires versioning to already be on — this is enforced, not just recommended.
2. **2. Click "Enable Object Lock."** Turns on locked-retention support for this bucket.
3. **3. Open the object's version list, click "Lock."** Enter how many days to retain it for. The object cannot be deleted or overwritten until that date, by anyone — including through a direct API call, not just the Business Workspace interface.

Important. A retention period can be extended later but never shortened — this is deliberate: a lock a compliance team is relying on can't be quietly weakened by anyone with UI access.

SECTION 05

Legal Hold

Separate from locked retention — a legal hold blocks deletion indefinitely, with no expiry date, until someone explicitly releases it. Use this for litigation holds and active investigations.

1. **1. Open the object's version list.** Click "Legal hold."
2. **2. The object is now protected.** Deletion and overwrite are both blocked — again enforced server-side, not just in the interface.
3. **3. Click "Release hold" when the hold is no longer needed.** The object becomes deletable again (subject to any separate locked-retention period still in effect).

SECTION 06

Automatic Lifecycle Policies

1. **1. Open a bucket's section in "Buckets, Versions & Object Protection."** Find the "Lifecycle: expire after ___ days" field.
2. **2. Enter a number of days.** Objects in this bucket older than that are automatically cleaned up. Leave it blank to disable the policy.
3. **3. Click "Run lifecycle enforcement now" to apply it immediately.** Otherwise it runs on Inaya's own regular schedule.

Safety guarantee. A locked (retention) or legal-held object is never auto-deleted by a lifecycle policy, even past its expiration day — protection always wins over automatic cleanup.

SECTION 07

Storage Health

Click any object in "Buckets, Versions & Object Protection" to see its real redundancy status — how many independent copies of each half of the encrypted, sharded file currently exist, and its overall health state. This is live telemetry, not a static label.

SECTION 08

Inaya Drive — A Real Drive Letter (Windows)

Inside the Inaya Business Workspace desktop app, mount your storage as an ordinary Windows drive letter — browse, open, and save files directly, the same way you would with any local or network drive.

1. **Issue (or reuse) an S3-compatible credential.** See Section 02 — a scoped credential works here too, e.g. a read-only drive limited to one bucket.
2. **Open the "Inaya Drive" panel in the desktop app.** Enter the Access Key ID, Secret Access Key, and a drive letter (e.g. "I:").
3. **Click "Mount."** The drive appears in File Explorer within a few seconds.
4. **Use it like any other drive.** Open, edit and save files directly, drag-and-drop uploads, delete files — every change is written straight through to Inaya's real storage.
5. **Click "Unmount" when finished.** Or simply close the desktop app.

Known limitation. Creating a brand-new empty folder isn't supported yet — a folder appears automatically as soon as you save a file inside that path, the same behavior as other cloud-drive tools. Available on Windows for this pilot; macOS/Linux support is planned.

SECTION 09

Everything Is Audited

- Credential creation and revocation
- Every object upload, download, and delete
- Version restores
- Locked-retention and legal-hold changes
- Lifecycle policy changes and every automatic expiration

All of the above write to your organization's own audit trail, visible to your admins — not just asserted, independently checkable.

SECTION 10

Getting Help

During the pilot, route questions about scope configuration, retention/legal-hold behavior, or the desktop drive to your assigned Inaya technical contact — pilot feedback directly shapes the general-availability release.