DATA MIGRATION

Migrate Your Existing Cloud Data to Inaya

A step-by-step guide for pilot IT/ops teams: move data from AWS S3, Azure Blob Storage, or Google Cloud Storage into Inaya using the Inaya Migration Agent — a local command-line tool that keeps every credential on your own machine.

Pilot Guide · Data Migration · September 2026

SECTION 01

What This Gives You

The Inaya Migration Agent is a small command-line tool that runs on your own machine (or a server you control) and copies objects from an existing AWS S3, Azure Blob, or Google Cloud Storage source directly into Inaya. It streams each object through — nothing is written to a third party, and nothing is uploaded to Inaya's web application first. Source and destination credentials both stay local to the tool's own process; Business Workspace and Inaya's browser UI never see them.

PROPERTY	BEHAVIOR
Resumable	If the tool is interrupted (network drop, closed terminal, power loss), running the exact same command again picks up where it left off — already-migrated objects are skipped automatically, never re-copied or duplicated.
Verified	Every object is checked against the destination immediately after upload; a mismatch is recorded as a real failure, never silently ignored.
Selective	Migrate an entire bucket, one folder/prefix, or a specific list of object keys — your choice.
Safe to preview	A dry-run mode lists exactly what would be migrated without moving or changing anything.

Where to get the tool. The Migration Agent is not (yet) published to a public package registry — your Inaya technical contact will provide you with the tool's folder directly. It requires Node.js 18 or newer, which you can confirm with `node --version` in a terminal.

SECTION 02

Step 1 — Install the Tool

1. **1. Get the inaya-migration-agent folder from your Inaya contact.** Place it anywhere on the machine that will run the migration.
2. **2. Open a terminal in that folder and install its dependencies.**
3. **3. Confirm it runs.**

TERMINAL

```
cd inaya-migration-agent
npm install
node bin/inaya-migrate.mjs --help
```

SECTION 03

Step 2 — Get Your Inaya Destination Credentials

1. **1. Sign in to Business Workspace.** Open the "S3-Compatible Storage" panel from the left navigation.
2. **2. Click "+ New S3 credential."** Give it a label such as "migration-agent" so you can identify it later.
3. **3. Save the Access Key ID and Secret Access Key immediately.** The secret is shown exactly once and can never be retrieved again — only reissued.

TERMINAL — SET THESE ONCE PER SESSION

```
export INAYA_ACCESS_KEY_ID="<your Inaya Access Key ID>"
export INAYA_SECRET_ACCESS_KEY="<your Inaya Secret Access Key>"
```

> The migration agent always reads your Inaya credential from these two environment variables — never from a command-line flag — so it never appears in your shell history or a process list.

SECTION 04

Step 3A — Migrate from AWS S3

Uses your existing AWS credentials — nothing AWS-specific to install beyond what you likely already have.

TERMINAL

```
export AWS_ACCESS_KEY_ID="<your AWS access key>"
export AWS_SECRET_ACCESS_KEY="<your AWS secret key>"

node bin/inaya-migrate.mjs migrate \
  --source aws \
  --source-bucket my-existing-bucket \
  --source-region us-east-1 \
  --dest-endpoint https://<your-inaya-host>/api/s3 \
  --dest-bucket my-inaya-bucket
```

SECTION 05

Step 3B — Migrate from Azure Blob Storage

Uses either a storage account name/key pair or a full connection string — whichever you already have on hand.

TERMINAL — USING AN ACCOUNT NAME AND KEY

```
export AZURE_STORAGE_ACCOUNT="myaccount"
export AZURE_STORAGE_KEY="<your Azure storage account key>"

node bin/inaya-migrate.mjs migrate \
  --source azure \
  --source-bucket my-existing-container \
  --dest-endpoint https://<your-inaya-host>/api/s3 \
  --dest-bucket my-inaya-bucket
```

> To use a connection string instead, set AZURE_STORAGE_CONNECTION_STRING and omit AZURE_STORAGE_ACCOUNT/AZURE_STORAGE_KEY.

SECTION 06

Step 3C — Migrate from Google Cloud Storage

Uses a Google Cloud Storage HMAC key pair (Cloud Console → Cloud Storage → Settings → Interoperability → Create a key for a service account), via Google's own documented S3-compatible XML API path — the same interoperability mode Inaya's own GCS compatibility layer already speaks natively.

TERMINAL

```
export GCS_HMAC_ACCESS_ID="<your GCS HMAC access ID>"
export GCS_HMAC_SECRET="<your GCS HMAC secret>"

node bin/inaya-migrate.mjs migrate \
  --source gcs \
  --source-bucket my-existing-gcs-bucket \
  --dest-endpoint https://<your-inaya-host>/api/s3 \
  --dest-bucket my-inaya-bucket
```

SECTION 07

Migration Options

- Preview first, migrate nothing: add `--dry-run` to any command above to list exactly what would be migrated, with no reads or writes actually performed.
- Migrate one folder only: add `--source-prefix documents/2026/` to restrict the migration to that path.
- Migrate specific files only: add `--objects file1.txt,folder/file2.pdf` (comma-separated, exact keys) instead of an entire bucket.
- Resume after an interruption: simply run the exact same command again. Objects already recorded as migrated are skipped automatically — nothing is re-copied or duplicated.

> **What the manifest file is.** Each run writes progress to a local file named inaya-migration-manifest.jsonl (in the folder you ran the command from, unless you set --manifest <path>) — this is how resume works, and it's a real, readable record of every object's outcome. Keep it until you've confirmed the migration is complete; deleting it before then would cause a re-run to start over.

SECTION 08

Step 4 — Verify the Migration

1. **1. Check the terminal summary.** Every run ends with a count of objects migrated, failed, and skipped. Zero failures is the goal — any failure is named individually above the summary.
2. **2. Re-run the exact same command if anything failed.** Already-succeeded objects are skipped; only the real failures are retried.
3. **3. Confirm in Business Workspace.** Open the S3-Compatible Storage panel and browse the destination bucket — your migrated objects should be visible there, confirming Inaya's own storage/encryption/redundancy pipeline actually received them, not just a local acknowledgment.
4. **4. Spot-check a few files.** Download a handful of migrated objects and confirm they open correctly and match the originals.

SECTION 09

Getting Help

During the pilot, route migration questions, unexpected failures, or requests for a different migration mode to your assigned Inaya technical contact rather than general support — pilot feedback is what shapes the general-availability release.