

M0 — Application Scaffold

Goal: stand up the complete Gabriel Desktop application shell and every P0/P1 workspace against a mock data layer, so the UX and the layer boundaries can be evaluated end-to-end before any Gateway/Core exists.

What M0 delivers

- **Monorepo** (`apps/web` , plus reserved `apps/gateway` , `services/` , `packages/`).
- **Design system:** OKLCH dark (default) + light themes, Tailwind v4 `@theme` , and a hand-rolled shadcn/Radix component set under `components/ui` .
- **Workspace shell (ADR-035):** persistent sidebar + topbar + assistant rail + ⌘K command palette that never unmount across route changes.
- **Every workspace wired:** Home, Chat, Agents (+ config editor), Documents, Memory, Resources, Settings, Login.
- **Transport-agnostic streaming (ADR-033)** via a mock realtime transport that emits the same frames a live WebSocket will.
- **Dev Identity Provider login (ADR-007)** backed by seeded pilot-org principals.

Key seams (where later milestones plug in)

Seam	File	Milestone that activates it
<code>USE MOCK</code> flag	<code>src/services/gateway-client.ts</code>	M2 (Gateway)
Mock data source	<code>src/services/mock/data.ts</code>	deleted at M2
Realtime transport factory	<code>src/services/realtime/index.ts</code>	M3 (live WS)
Session hydration	<code>src/components/layout/session-guard.tsx</code>	M1 (Identity)
Provider registry (per-agent)	<code>src/types/agent.ts</code> <code>LLMProviderId</code>	M3 (LLM providers)

Boundaries asserted by M0

- Web app talks only to the (future) Gateway, never to Core.
- Session view carries **identity only** — no tokens, no permissions.
- No provider-specific LLM code in the app; provider is per-agent config.
- No business logic in the shell; features are self-contained modules.

Verification

```
pnpm typecheck  # tsc --noEmit --clean
pnpm lint       # eslint --clean
pnpm build      # 11 routes, production build succeeds
pnpm dev        # smoke: login → dashboard → chat streaming → agent config
```