HAZMAT SAFETY DATA SHEET

0xe1cE2345d25462996AE27F58E3e001245e043EA4 (verified as ClausManagedProject, CounterV2)

Read 522 bytes of deployed bytecode and checked it against 16 registered hazards. Nothing matched, which is not the same as safe.

What this is: It is a proxy: what you call goes to the logic at 0xc2f10e8bdd63277a235b255cb1e840a34b50e98a, and that is what was read.
What matched: Nothing. None of the 16 registered hazards are present in this bytecode.
What that means: Unfamiliar rather than sound. The register is shaped after a small number of projects, so a contract can be perfectly normal and still match nothing. A famous example on this register: The DAO, EtherDelta and Fomo3D all match nothing.

ASSERTION LEVEL: PATTERN MATCH ONLY; CONFIRMATION RUNS ARE SEPARATE
A match is a candidate, not a clearance: this sheet fingerprints a contract against registered hazard shapes, it does not audit it. A clean sheet is not the same as safe.

HAZARDS FOUND
None of the registered hazards are present. That is not the same as safe: the register is shaped after a handful of projects, so this contract may simply be unfamiliar to it.

WHAT WAS READ
a match means the selectors a placard asks about are present. It does not mean reachable, and a clean sheet is not a clearance.
placards checked 16 classes 7 selectors in code 6 the register asks about 0 otherwise unaccounted 6
0x06661abd unnamed
0x35420fd9 unnamed
0x4e487b71 Panic(uint256)
0xb326e4a9 unnamed
0xc34c08e5 unnamed
0xd09de08a unnamed

NOT CHECKED AT ALL
- resolution is best effort: unknown proxy patterns, diamond facets and beacons pointing at beacons
- are labelled not followed
- reachability
- economic preconditions
- state at any particular block
- source-level reasoning
- anything not covered by a placard

THE TECHNICAL PART
target 0xe1cE2345d25462996AE27F58E3e001245e043EA4
family evm
code sha256 0x9251b2adbf675d67bf9be858847910353b8c175af8aaa4c2f4573912891ba6a1
body bytes read 522
metadata excluded 0 bytes (CBOR trailer, appended after compilation)
four-byte constants 6
register 16 placards v0xd7dea67cdf60b0bc
anchor epoch 3 root 0xed6a388e080b234215fcd1d0fc845207714daece4261c0ff9d7e39ce45c5a26c (epoch-3.json)
register digest 0xd7dea67cdf60b0bc
anchor root 0xed6a388e080b234215fcd1d0fc845207714daece4261c0ff9d7e39ce45c5a26c
selector index 783 names, a convenience reading and not verification

ADDRESSES SCANNED
a proxy reads as two rows: the proxy itself, and the implementation its logic came from
requested 0xe1ce2345d25462996ae27f58e3e001245e043ea4 12 selectors 1936 bytes
implementation 0xc2f10e8bdd63277a235b255cb1e840a34b50e98a 6 selectors 522 bytes

Cite the placard id, the code sha256 and the register digest. The HTML sheet is the artifact that carries its own digest; this PDF is the sam