

STA4026S Assignment 2 - Collider Data Classification

Shriyaa Sooklal SKLSHR001 and Tamika Surajpal SRJTAM001

a)

```
dat$response <- apply(dat[, c("Y1", "Y2", "Y3")], 1, function (x){  
  if (x[1] == 1) return("code-Alpha")  
  if (x[2] == 1) return("code-Beta")  
  if (x[3] == 1) return("code-Rho")  
})  
  
ggplot(dat, aes(x=X1, y=X2, color=response))+  
  geom_point(size=2)+  
  coord_fixed()+ # 1:1 aspect ratio  
  labs(title = "Scatterplot of particles in feature space",  
        x = "First coordinate (X1)", y = "Second coordinate (X2)",  
        color = "Particle type")+  
  theme_minimal()
```




Figure 1: This is a scatter plot of the Collider data in the X1 and X2 feature space, with points colour-coded by true particle class (in red, in blue, in green), illustrating non-linear boundaries that motivate using a neural network for classification.

Figure 1 shows three distinct clusters corresponding to the particle types: `code-Alpha`, `code-Beta`, and

code-Rho. While the classes are broadly separated — with **code-Alpha** particles primarily located on the right, **code-Beta** particles on the left, and **code-Rho** particles clustered near the center — the boundaries between these regions are clearly non-linear. This structure suggests that linear classifiers would struggle to accurately separate the classes.

Thus, using non-linear models such as a neural network is appropriate for this classification task, as they can capture the curved, complex boundaries observed in the feature space.

b)

```
softmax <- function(Z) {
  Z_shift <- Z - matrix(apply(Z, 2, max), nrow = 3, ncol = ncol(Z), byrow = TRUE)

  # Subtract the column max for numerical stability (to avoid computational
  # overflow when exponentiating)
  expZ <- exp(Z_shift)
  denom <- matrix(colSums(expZ), nrow = 3, ncol = ncol(Z), byrow = TRUE)
  # column-wise sums...sum across 3 classes convert to matrix for
  # conformability
  expZ/denom
}
```

c)

We can define the contribution of a single observation i to the cross-entropy loss, C_i , using the following case-based function:

$$C_i = \begin{cases} -\log(\hat{y}_{ij}) & \text{if } y_{ij} = 1, \\ 0 & \text{otherwise.} \end{cases}$$

It is advantageous, for numerical purposes, to evaluate only the term corresponding to the class where $y_{ij} = 1$. This is because for all other classes, $y_{ij} = 0$, and their contributions to the sum are therefore exactly zero. Avoiding unnecessary computation of terms like $0 \times \log(\hat{y}_{ij})$ improves numerical stability, reduces computational cost, and prevents possible undefined operations such as taking the logarithm of zero.

d)

```
g <- function(Yhat, Y, eps = 1e-15) {
  # Yhat, Y : N x q matrices (rows = observations, columns = classes)
  N <- nrow(Y)
  -sum(Y * log(pmax(Yhat, eps)))/N
  # pmax() replaces any element of Yhat that is smaller than eps with eps
  # #ensures no value passed to log() is <= zero
}
```

e)

The number of parameters n_{pars} in an (m, m) -Auto-Feature network with input dimension p and output dimension q is given by:

$$n_{\text{pars}} = 2p^2 + 2p + 2pm + 2m + m^2 + mq + q.$$

f)

```
# X: input matrix (N x p) Y: output matrix (N x q) theta: parameter vector with
# all weights and biases m: number of nodes on hidden layer v: regularisation
# parameter
af_forward <- function(X, Y, theta, m, v) {
  N <- nrow(X)
  p <- ncol(X)
  q <- ncol(Y)

  # Populate weight-matrix and bias vectors by unpacking theta:
  index <- 1:(2 * (p^2)) #W1 : p(p+p)
  W1 <- matrix(theta[index], nrow = p)

  index <- max(index) + 1:(2 * p) #b1 : (p+p)
  b1 <- theta[index]

  index <- max(index) + 1:((2 * p) * m) #W2 : (p+p)*m
  W2 <- matrix(theta[index], nrow = 2 * p)

  index <- max(index) + 1:m #b2 : m
  b2 <- theta[index]

  index <- max(index) + 1:(m * m) #W3 : (m*m)
  W3 <- matrix(theta[index], nrow = m)

  index <- max(index) + 1:m #b3 : m
  b3 <- theta[index]

  index <- max(index) + 1:(m * q) #W4 : (m*q)
  W4 <- matrix(theta[index], nrow = m)

  index <- max(index) + 1:q #b4 : q
  b4 <- theta[index]

  # forward propagation
  H1 <- tanh(X %*% W1 + matrix(b1, N, 2 * p, TRUE)) # aug-layer output
  H2 <- tanh(H1 %*% W2 + matrix(b2, N, m, TRUE)) # 1st hidden layer output
  H3 <- tanh(H2 %*% W3 + matrix(b3, N, m, TRUE)) # 2nd hidden layer output
  Z <- H3 %*% W4 + matrix(b4, N, q, TRUE) # final layer to get logits

  # apply softmax across logits
  P_3byN <- softmax(t(Z))
  # temporarily transpose because softmax expects input where columns are
  # different samples
  probs <- t(P_3byN)

  # losses & objective
  loss <- g(probs, Y) # cross-entropy
  obj <- loss + (v/2) * sum(theta^2) # L2 regularisation
```

```

    list(probs = probs, loss = loss, obj = obj)
}

```

g)

```

set.seed(2025)
m <- 4
# Step 1: Split the data into training and validation sets (80%/20%)
n <- nrow(dat)
train_size <- floor(0.8 * n)
train_indices <- sample(1:n, train_size)
train_data <- dat[train_indices, ]
valid_data <- dat[-train_indices, ]

# Step 2: Prepare the training and validation datasets
X_train <- as.matrix(train_data[, 1:3]) # Input features
Y_train <- as.matrix(train_data[, 4:6]) # Response variables (one-hot encoded)

X_valid <- as.matrix(valid_data[, 1:3]) # Input features
Y_valid <- as.matrix(valid_data[, 4:6]) # Response variables (one-hot encoded)

# Step 3: Define the objective function with regularization
v = 0.01
obj_pen <- function(theta) {
  result <- af_forward(X_train, Y_train, theta, m, v)
  return(result$obj)
}

# Initial random theta
p <- ncol(X_train)
q <- ncol(Y_train)
m <- 4
npars <- 2 * p^2 + 2 * p + 2 * p * m + 2 * m + m^2 + m * q + q
theta_rand = runif(npars, -1, 1)
obj_pen(theta_rand)

```

```
[1] 1.721321
```

```

res_opt = nlm(obj_pen, theta_rand, iterlim = 1000)
res_opt

```

```
$minimum
```

```
[1] 0.4028883
```

```
$estimate
```

```

[1] -0.21279461  0.64139962 -0.03414711  0.25306968  0.58090334  0.22547251
[7] -0.18506384  0.94015306  0.23865817 -0.55235912 -0.84187982 -0.39718576
[13] -0.62861470 -0.28466363 -0.09739992 -0.01353363  0.07253863  0.39480491
[19] -0.90082348  1.41132067  0.37673789 -0.68916472  1.13852784  0.33616084
[25] -0.54425357 -0.07585497  0.27925771 -0.50692552  0.59708925 -0.32579596
[31]  1.02274762 -0.94985880  0.33542515  0.50927865 -0.45891431  0.51035714

```

```

[37] -0.37855116 -0.69093695  0.64979105 -0.69620285  0.94825999 -0.21502926
[43]  0.37852868  0.69092201 -0.64985169  0.69617908 -0.94831806  0.21506050
[49] -0.51251015  0.90816926 -0.10619265  0.10616986  0.47782309  0.17396115
[55]  0.94022324 -0.94022924  0.92232234 -1.92644474  0.20156180 -0.20158096
[61] -0.47782300 -0.17397110 -0.94023380  0.94030589 -0.47782194 -0.17400343
[67] -0.94024871  0.94027719 -0.01525412 -0.43408754  0.01522879  0.01523206
[73] -1.32291225  0.13332233  1.32295129  1.32292470  0.62600725 -1.96385963
[79] -0.62604595 -0.62607405  0.69687986  1.83053712 -0.69690812 -0.69689335
[85]  0.33733033 -0.22712004 -0.11021825

```

\$gradient

```

[1] 2.899903e-07 -5.247469e-07 -2.710610e-07 -6.133982e-08 1.386113e-07
[6] -3.691492e-08 -1.743050e-08 -1.193490e-08 6.844525e-08 4.008460e-07
[11] -2.002287e-07 -1.681988e-08 9.942047e-08 7.400192e-07 1.261768e-07
[16] -1.705303e-07 -2.588485e-07 -6.594725e-08 8.826273e-09 2.670695e-08
[21] -2.947087e-07 1.556533e-07 -1.793281e-07 -2.381428e-08 2.424172e-07
[26] -1.786349e-07 4.398149e-07 -1.131872e-07 5.240253e-08 -2.516320e-07
[31] -1.505087e-07 7.077672e-08 -3.740341e-07 2.929323e-07 3.191891e-08
[36] 1.965650e-07 4.571343e-07 7.466250e-08 1.345035e-07 1.011968e-07
[41] 1.206257e-07 1.457168e-07 -1.329492e-07 -8.276713e-08 -2.290945e-07
[46] 8.032464e-08 -1.720846e-09 5.351275e-08 3.502199e-07 -1.439404e-07
[51] 2.618461e-07 1.196265e-07 3.813616e-08 -2.917666e-07 5.162537e-09
[56] 2.018941e-07 1.579292e-07 -2.642654e-07 -1.296185e-07 -2.962630e-07
[61] 2.173817e-07 2.839950e-07 1.150746e-07 3.692047e-07 2.014500e-07
[66] -2.214340e-07 -1.050826e-07 1.533773e-07 -3.458345e-07 4.380385e-07
[71] -3.356759e-07 -1.088019e-08 -9.185334e-08 4.216627e-07 7.951436e-08
[76] -1.516468e-07 -9.781065e-08 -3.263916e-07 1.120215e-07 -5.939693e-08
[81] -1.360023e-08 -1.213002e-08 -1.711409e-07 -1.676992e-07 -1.444955e-07
[86] 2.903233e-08 1.398326e-07

```

\$code

```
[1] 1
```

\$iterations

```
[1] 305
```

```

# Step 4: Grid search over regularization parameter nu
n_v <- 25
validation_errors = rep(NA, n_v)
v_values <- exp(seq(-10, 1, length.out = n_v))
# validation_errors <- numeric(length(v_values))

for (i in 1:n_v) {
  v <- v_values[i]
  res_opt = nlm(obj_pen, theta_rand, iterlim = 1000)

  res_val = af_forward(X_valid, Y_valid, res_opt$estimate, m, 0)
  validation_errors[i] = res_val$objj
}

best_i <- which.min(validation_errors)
best_v <- v_values[best_i]

# Step 5: Plot validation error vs v


```

```

par(pty = "s")
plot(v_values, validation_errors, type = "b", log = "x", pch = 16, xlab = expression(nu),
     ylab = "Validation Cross-Entropy Loss", main = "Validation Loss vs Regularization (m = 4)",
     asp = 1)
abline(v = best_v, col = "red", lty = 2)
points(best_v, validation_errors[best_i], col = "red", pch = 16)
legend("topright", legend = paste0("Chosen  = ", signif(best_v, 3)), col = "red",
     lty = 2, pch = 16, bty = "n")

```

Validation Loss vs Regularization (m = 4)



The optimal regularization parameter is 0.0044 as it minimizes the validation error.

h)

```

m <- 4

# Re-train model at best nu
obj_pen_best <- function(pars) {
  af_forward(X_train, Y_train, pars, m, v)$obj
}

# Reinitialize random parameters
theta_rand <- runif(npars, -1, 1)

res_opt_best <- nlm(obj_pen_best, p = theta_rand, iterlim = 1000)
theta_best <- res_opt_best$estimate

# Plot response curves by varying X1 and X2 separately Helper function to
# predict probability curves
predict_curve <- function(var_seq, varname, fixed_X2 = 0, fixed_X3 = 0, pars, m) {
  n <- length(var_seq)
  input <- matrix(0, nrow = n, ncol = 3)
  colnames(input) <- c("X1", "X2", "X3")
}

```

```

input[, "X1"] <- if (varname == "X1")
  var_seq else fixed_X2
input[, "X2"] <- if (varname == "X2")
  var_seq else fixed_X2
input[, "X3"] <- fixed_X3

q <- 3

preds <- af_forward(input, Y = matrix(0, nrow = n, ncol = q), pars, m, v = 0)$probs

out <- as.data.frame(preds)
colnames(out) <- c("alpha", "beta", "rho")
out[[varname]] <- var_seq

return(out)
}

# Create sequences
X_seq <- seq(-4, 4, length.out = 100)

# Response curves for Detector Type A (X3=1) and Type B (X3=0)

curve_X1_A <- predict_curve(X_seq, "X1", fixed_X2 = 0, fixed_X3 = 1, theta_best,
  m)
curve_X1_B <- predict_curve(X_seq, "X1", fixed_X2 = 0, fixed_X3 = 0, theta_best,
  m)

curve_X2_A <- predict_curve(X_seq, "X2", fixed_X2 = 0, fixed_X3 = 1, theta_best,
  m)
curve_X2_B <- predict_curve(X_seq, "X2", fixed_X2 = 0, fixed_X3 = 0, theta_best,
  m)

# Helper to prepare data
prepare_plot_data <- function(curve_data, varname, type_label) {
  df <- as.data.frame(curve_data)
  colnames(df) <- c(varname, "alpha", "beta", "rho")
  df$Detector <- type_label
  df <- pivot_longer(df, cols = c("alpha", "beta", "rho"), names_to = "Class",
    values_to = "Probability")
  return(df)
}

plot_data_X1 <- bind_rows(prepare_plot_data(curve_X1_A, "X1", "Type A"), prepare_plot_data(curve_X1_B,
  "X1", "Type B"))

ggplot(plot_data_X1, aes(x = X1, y = Probability, color = Class)) + geom_line() +
  facet_wrap(~Detector) + labs(title = "Predicted Class Probabilities vs X1", x = "X1",
  y = "Probability") + theme_minimal() + theme(aspect.ratio = 1)

```




Figure 2: This figure shows two faceted line plots showing how the neural network's predicted class probabilities vary as X_1 changes, separately for Detector Type A ($X_3 = 1$) and Type B ($X_3 = 0$).

```
plot_data_X2 <- bind_rows(prepare_plot_data(curve_X2_A, "X2", "Type A"), prepare_plot_data(curve_X2_B,
  "X2", "Type B"))

ggplot(plot_data_X2, aes(x = X2, y = Probability, color = Class)) + geom_line() +
  facet_wrap(~Detector) + labs(title = "Predicted Class Probabilities vs X2", x = "X2",
    y = "Probability") + theme_minimal() + theme(aspect.ratio = 1)
```




Figure 3: This figure shows two faceted line plots showing how the neural network's predicted class probabilities vary as X_2 changes, separately for Detector Type A ($X_3 = 1$) and Type B ($X_3 = 0$).

i)

One practical advantage of using an AF network over a standard feed forward neural network is that AF networks automatically discover important transformations of the input variables, such as quadratic terms

and interactions, without requiring manual feature engineering. In our Prac, we saw that the AF network easily captured structured nonlinear relationships between X_1 , X_2 , and the class probabilities α , β , ρ — for example, the probability of class ρ showed a clear nonlinear upward trend with X_1 , even though no complex hidden layers were manually designed. This shows that the AF network can model nonlinearity efficiently with simple transformations.

Another advantage is interpretability. Because the AF network was designed to learn specific types of feature mappings (rather than arbitrary complex patterns), we could directly observe how the inputs influenced the outputs through the plotted response curves. For instance, the nearly linear but slightly sloped trends for α and β made it clear how X_1 and X_2 affected the probabilities. In contrast, a standard feed forward network would have created highly entangled hidden features, making it difficult to extract such insights. Finally, by constraining the feature space, the AF network also helped prevent over fitting, which is especially important when working with limited training data, as we had in this Prac.