


Week 12

## Question 1

Correct

Marked out of 1.00

 [Flag question](#)

You are a bank account hacker. Initially you have 1 rupee in your account, and you want exactly ***N*** rupees in your account. You wrote two hacks, first hack can multiply the amount of money you own by 10, while the second can multiply it by 20. These hacks can be used any number of time. Can you achieve the desired amount ***N*** using these hacks.

### Constraints:

$$1 \leq T \leq 100$$

$$1 \leq N \leq 10^{12}$$

### Input

- The test case contains a single integer *N*.

### Output

For each test case, print a single line containing the string "1" if you can make exactly *N* rupees or "0" otherwise.

### SAMPLE INPUT

1

### SAMPLE OUTPUT

1

### SAMPLE INPUT

2

### SAMPLE OUTPUT

Reset answer

```
1 #include <stdio.h>
2
3 /*
4  * Complete the 'powerSum' function below.
5  *
6  * The function is expected to return an INTEGER.
7  * The function accepts following parameters:
8  * 1. INTEGER x
9  * 2. INTEGER n
10 */
11 int powerSum(int x, int m, int n) {
12     int temp;
13     temp=1;
14     for(int i=1;i<=n;i++)
15         temp=temp*m;
16     if(temp==x)
17         return 1;
18     if(temp>x)
19         return 0;
20     return (powerSum(x,m+1,n)+powerSum(x-temp,m+1,n));
21 }
```

	Test	Expected	Got	
	printf("%d", powerSum(10, 1, 2))	1	1	

Passed all tests!

Finish review

Quiz navigation



Show one page at a time

## Question 2

Correct

Marked out of 1.00

[Flag question](#)

Find the number of ways that a given integer,  $X$ , can be expressed as the sum of the  $N^{\text{th}}$  powers of unique, natural numbers.

For example, if  $X = 13$  and  $N = 2$ , we have to find all combinations of unique squares adding up to  $13$ . The only solution is  $2^2 + 3^2$ .

### Function Description

Complete the powerSum function in the editor below. It should return an integer that represents the number of possible combinations.

powerSum has the following parameter(s):

$X$ : the integer to sum to

$N$ : the integer power to raise numbers to

Input Format

The first line contains an integer  $X$ .

The second line contains an integer  $N$ .

### Constraints

$$1 \leq X \leq 1000$$

$$2 \leq N \leq 10$$

### Output Format

Output a single integer, the number of possible combinations calculated.

### Sample Input 0

10

2

### Sample Output 0

1

### Explanation 0

If  $X = 10$  and  $N = 2$ , we need to find the number of ways that  $10$  can be represented as the sum of squares of unique numbers.

$$10 = 1^2 + 3^2$$

This is the only way in which  $10$  can be expressed as the sum of unique squares.

#### Sample Input 1

100

2

#### Sample Output 1

3

#### Explanation 1

$$100 = (10^2) = (6^2 + 8^2) = (1^2 + 3^2 + 4^2 + 5^2 + 7^2)$$

#### Sample Input 2

100

~

#### Sample Output 2

1

#### Explanation 2

$100$  can be expressed as the sum of the cubes of  $1, 2, 3, 4$ .

$(1 + 8 + 27 + 64 = 100)$ . There is no other way to express  $100$  as the sum of cubes.

**Answer:** (penalty regime: 0 %)

Reset answer

Reset answer

```
1 #include <stdio.h>
2
3 /*
4  * Complete the 'powerSum' function below.
5  *
6  * The function is expected to return an INTEGER.
7  * The function accepts following parameters:
8  * 1. INTEGER x
9  * 2. INTEGER n
10 */
11 int powerSum(int x, int m, int n) {
12     int temp;
13     temp=1;
14     for(int i=1;i<=n;i++)
15         temp=temp*m;
16     if(temp==x)
17         return 1;
18     if(temp>x)
19         return 0;
20     return (powerSum(x,m+1,n)+powerSum(x-temp,m+1,n));
21 }
```

	Test	Expected	Got	
	printf("%d", powerSum(10, 1, 2))	1	1	

Passed all tests!

Finish review

Quiz navigation



Show one page at a time