

Glossary

Several terms below mean something narrower in this system than they do in general use. Where that happens, the definition given is the one that applies across this project. Part 1 lists every term alphabetically. Part 2 lists the same terms grouped by the part of the system they belong to.

AGENT AND DISPATCH CONTROL AND MOTION PERCEPTION AND MODELS

PART 1 All terms, A to Z

Twenty-nine terms in one list. The coloured marker beside each term shows which part of the system it comes from.

A

Agent	A language model given tools and run in a loop, so it can act, observe the outcome, and act again. Distinct from a single question and answer.
Architectural constraint	A restriction enforced by removing the capability. The model cannot route around it, because there is nothing to route to.

C

COCO classes	The eighty everyday object categories the detection model was trained on – person, chair, bottle and so on. Anything outside that list cannot be detected.
Confidence	The model's own score for a detection, from zero to one. A threshold decides what counts as found, and that threshold is a choice, not a fact.
Context	Everything the model can see when deciding: the instruction, the skill descriptions, and the results of previous steps in the session.

D

DDS	Data Distribution Service – the publish and subscribe protocol the Go2 speaks. The workstation joins the robot's network and exchanges messages over it.
Dead reckoning	Estimating position from speed and elapsed time rather than observation. Error accumulates and is never corrected.

Deny list	A list of tools the agent is not allowed to use. The deny list is applied last, so a tool on it stays blocked even if something else in the config gave the agent wide access.
Discrete dispatch	One skill per turn, with the result read before the next choice. The opposite of writing a loop that runs the whole task in a single call.
Dispatcher	What the LLM does here: it reads the user's message, picks one skill, chooses its parameters, and stops. It does not write robot code.
G	
Gateway	The OpenClaw process that receives a Telegram message, assembles the prompt, applies the tool profile, and calls the model. Everything passes through it.
H	
High-level control	Telling the robot where to go and letting its own controller work out the joints. This project is entirely high-level.
I	
Inference size	The resolution an image is scaled to before detection. Smaller is faster and misses more, this project uses 640 pixels.
L	
Low-level control	Commanding individual joint torques and positions directly. More powerful, far easier to damage the robot with. Not used here.
O	
Odometry	Estimating position from sensors such as wheel or joint encoders. Not used here, which is why drift accumulates.
Open loop	Acting without measuring the outcome. Walking two metres means walking at a known speed for a calculated time and assuming it worked.
P	
Prompt-level rule	An instruction written in the system prompt. Constrains what the model is told to do, not what it is able to do.

Q

Quadruped

A robot with four legs. You control it by telling it how fast to move, not where to go, so distance is speed × time and is only an estimate.

R

Result line

The single line a skill prints when it finishes, beginning with **RESULT** and followed by name and value pairs. The model's only view of what happened.

S

Session

One continuous conversation with the bot, carrying the full message history. Editing a skill mid-session leaves stale instructions in that history.

Session log

A JSONL file recording every message and tool call. The authoritative record of what the model did, as opposed to what it said it did.

Skill

A folder containing a description the model reads and a script the machine runs. The unit the model is allowed to invoke.

Skill runner

The single tool that executes a named skill with parameters. Kept deliberately minimal: if it could run arbitrary code, the tool profile would mean nothing.

Sport controller

The Go2's built-in high-level controller. Accepts commands like walk, sit and stand, and handles balance and gait itself.

T

Tool call

A structured request from the model to run something. The gateway checks it against the tool profile before executing it.

Tool profile

The list of tools an agent may call. Enforced by the framework rather than requested in the prompt, which is what makes it reliable.

W

Watchdog

A safety timeout in the controller. If no new command arrives for about a second it stops the robot, on the assumption the controlling program has died. Motion commands must therefore be resent continuously.

Y

Yaw rate

Rotation speed about the vertical axis, in radians per second. Turning is commanded as a rate held for a duration, not as an angle.

YOLO

A family of object detection models that locate and classify objects in one pass. Fast enough to run per frame.

PART 2 The same terms, by domain

The vocabulary comes from three different worlds, and knowing which one a term belongs to is often half the definition. One line each here; the full entry is in Part 1.

Agent and dispatch

10 terms

Agent	A model given tools and run in a loop.
Deny list	Tools explicitly withheld; denial always wins.
Discrete dispatch	One skill per turn, result read before the next.
Dispatcher	The model's job here: pick one skill and stop.
Gateway	The process every message and tool call passes through.
Session	One conversation, carrying its full history.
Session log	The JSONL record of what actually ran.
Skill	A description plus a script – the unit the model invokes.
Skill runner	The one tool that executes a named skill.
Tool profile	The tools an agent may call, enforced by the framework.

Control and motion

10 terms

DDS	The publish and subscribe protocol the Go2 speaks.
Dead reckoning	Position from speed and time; error accumulates.
High-level control	Command the motion, let the robot handle the joints.
Low-level control	Command the joints directly. Not used here.
Odometry	Position from sensors. Not used here.
Open loop	Acting without measuring the outcome.
Quadruped	A four-legged robot, commanded in velocities.
Sport controller	The Go2's built-in controller for walk, sit and stand.
Watchdog	Stops the robot if commands stop arriving.
Yaw rate	Turn speed in radians per second, held for a duration.

Architectural constraint	A limit enforced by removing the capability.
COCO classes	The eighty categories detection is limited to.
Confidence	The detector's own score, and a threshold you choose.
Context	Everything the model can see when it decides.
Inference size	Resolution before detection; 640 pixels here.
Prompt-level rule	An instruction, not a barrier.
Result line	The one line a skill prints back to the model.
Tool call	A structured request, checked against the profile.
YOLO	Detection models that locate and classify in one pass.