

## כללי:

- השרת הוא שרת HTTP בסיסי הבנוי על סמך פרוטוקול RFC 2616 ותומך בקבצי text/HTML בלבד.  
בנוסף השרת תומך בפקודות GET, POST, PUT, DELETE, TRACE, OPTIONS, HEAD ובאפשרויות הבאות:
- Timeout כלומר הקשר לשרת ייסגר אם עברו יותר מ-3 דקות מאז נשלח הבית האחרון מהלקוח.
  - תמיכה בפרמטר Language אשר מחזיר את האובייקט לפי השפה המומלצת הנשלחת מהלקוח (במידה וקיימת).

## ערכים קבועים:

- תיקיית ROOT של השרת:  
`const char * ROOT_DIR = "C:/webServer"`
- PORT שהשרת מאזין לו:  
`const int PORT = 8080`
- מספר חיבורים מקסימלי לשרת:  
`const int MAX_SOCKETS = 60`
- זמן ניתוק לאחר חוסר פעילות:  
`const int TIMEOUT_IN_SEC = 180`

## כלים לבדיקה:

- POSTMAN Desktop
- WireShark
- Chrome browser


## מימוש ותצולמי מסך:

### :GET

בבקשת GET נבקש אובייקט HTML מהשרת, במידה והקובץ נמצא תוחזר הודעת OK 200, אחרת תוחזר הודעת 404 NOT FOUND.

### צילומי מסך

אנגלית, לקוח



לקוח, WIRESHARK

✓ Hypertext Transfer Protocol  
 > GET /hfile.html HTTP/1.1\r\n  
 Accept-Language: en-US\r\n  
 User-Agent: PostmanRuntime/7.26.8\r\n  
 Accept: \*/\*\r\n  
 Postman-Token: 5a8a7d60-04f4-423f-92e8-a7c159eef24b\r\n  
 Host: localhost:8080\r\n  
 Accept-Encoding: gzip, deflate, br\r\n  
 Connection: keep-alive\r\n  
 \r\n  
[\[Full request URI: http://localhost:8080/hfile.html\]](http://localhost:8080/hfile.html)  
 [HTTP request 1/1]  
[\[Response in frame: 22\]](#)

0000	02 00 00 00	45 00 01 13	2e 43 40 00	80 06 00 00	....E... .C@.....
0010	7f 00 00 01	7f 00 00 01	f5 26 1f 90	20 a8 1a 84	.....&.. ...
0020	c0 2e 2e df	50 18 27 f9	9c 4f 00 00	47 45 54 20	...P-' ' -O-GET
0030	2f 68 66 69	6c 65 2e 68	74 6d 6c 20	48 54 54 50	/hfile.h tml HTTP
0040	2f 31 2e 31	0d 0a 41 63	63 65 70 74	2d 4c 61 6e	/1.1- Ac cept-Lan
0050	67 75 61 67	65 3a 20 65	6e 2d 55 53	0d 0a 55 73	guage: e n-US-Us
0060	65 72 2d 41	67 65 6e 74	3a 20 50 6f	73 74 6d 61	er-Agent : Postma
0070	6e 52 75 6e	74 69 6d 65	2f 37 2e 32	36 2e 38 0d	nRuntime /7.26.8-
0080	0a 41 63 63	65 70 74 3a	20 2a 2f 2a	0d 0a 50 6f	-Accept: */* -Po
0090	73 74 6d 61	6e 2d 54 6f	6b 65 6e 3a	20 35 61 38	stman-To ken: 5a8
00a0	61 37 64 36	30 2d 30 34	66 34 2d 34	32 33 66 2d	a7d60-04 f4-423f-
00b0	39 32 65 38	2d 61 37 63	31 35 39 65	65 66 32 34	92e8-a7c 159eef24
00c0	62 0d 0a 48	6f 73 74 3a	20 6c 6f 63	61 6c 68 6f	b-Host: localho
00d0	73 74 3a 38	30 38 30 0d	0a 41 63 63	65 70 74 2d	st:8080- Accept-

אנגלית, שרת

```
HTTP Server: Client 127.0.0.1:62758 is connected.  
HTTP Server: Recieved: 235 bytes of  
"GET /hfile.html HTTP/1.1  
Accept-Language: en-US  
User-Agent: PostmanRuntime/7.26.8  
Accept: */*  
Postman-Token: 5a8a7d60-04f4-423f-92e8-a7c159eef24b  
Host: localhost:8080  
Accept-Encoding: gzip, deflate, br  
Connection: keep-alive
```

```
" message.
```

```
HTTP Server: Sent: 395\395 bytes of "HTTP/1.1 200 OK  
Content-type: text/html  
Content-length: 330
```

```
<!DOCTYPE html>  
<html>  
<head>  
<style>  
code {  
    font-family: Consolas,"courier new";  
    color: crimson;  
    background-color: #f1f1f1;  
    padding: 2px;  
    font-size: 105%;  
}  
</style>  
</head>  
<body>  
  
<h1>This is HTML file- English version</h1>  
  
<p>Tamir is great person and amazing friend!</p>  
<p>Dor is fine too...</p>  
  
</body>  
</html>  
" message.
```

שרת, wireshark

```

v Hypertext Transfer Protocol
  > HTTP/1.1 200 OK\r\n
    Content-type: text/html\r\n
  > Content-length: 330\r\n
    \r\n
    [HTTP response 1/1]
    [Time since request: 0.002180000 seconds]
    [Request in frame: 20]
    [Request URI: http://localhost:8080/hfile.html]
    File Data: 330 bytes
  > Line-based text data: text/html (22 lines)

```

0000	02 00 00 00 45 00 01 b3	2e 45 40 00 80 06 00 00	....E... .E@.....
0010	7f 00 00 01 7f 00 00 01	1f 90 f5 26 c0 2e 2e df	.....&...
0020	20 a8 1b 6f 50 18 27 f9	17 af 00 00 48 54 54 50	..oP.''. ...HTTP
0030	2f 31 2e 31 20 32 30 30	20 4f 4b 0d 0a 43 6f 6e	/1.1 200 OK-Con
0040	74 65 6e 74 2d 74 79 70	65 3a 20 74 65 78 74 2f	tent-typ e: text/
0050	68 74 6d 6c 0d 0a 43 6f	6e 74 65 6e 74 2d 6c 65	html-Co ntent-le
0060	6e 67 74 68 3a 20 33 33	30 0d 0a 0d 0a 3c 21 44	ngth: 33 0-...<!D
0070	4f 43 54 59 50 45 20 68	74 6d 6c 3e 0a 3c 68 74	OCTYPE h tml>.<ht
0080	6d 6c 3e 0a 3c 68 65 61	64 3e 0a 3c 73 74 79 6c	ml>.<hea d>.<styl
0090	65 3e 0a 63 6f 64 65 20	7b 0a 20 20 66 6f 6e 74	e>.code { . font
00a0	2d 66 61 6d 69 6c 79 3a	20 43 6f 6e 73 6f 6c 61	-family: Consola
00b0	73 2c 22 63 6f 75 72 69	65 72 20 6e 65 77 22 3b	s,"couri er new";
00c0	0a 20 20 63 6f 6c 6f 72	3a 20 63 72 69 6d 73 6f	. color : crimso
00d0	6e 3b 0a 20 20 62 61 63	6b 67 72 6f 75 6e 64 2d	n;- bac kground-
00e0	63 6f 6c 6f 72 3a 20 23	66 31 66 31 66 31 3b 0a	color: # f1f1f1;-
00f0	20 20 70 61 64 69 6e 6e	67 3a 20 32 70 78 3b 0a	paddin g: 2px;-
0100	20 20 66 6f 6e 74 2d 73	69 7a 65 3a 20 31 30 35	font-s ize: 105
0110	25 3b 0a 7d 0a 3c 2f 73	74 79 6c 65 3e 0a 3c 2f	%;-}</s tyle>.</
0120	68 65 61 64 3e 0a 3c 62	6f 64 79 3e 0a 0a 3c 68	head>.<b ody>.<h
0130	31 3e 54 68 69 73 20 69	73 20 48 54 4d 4c 20 66	1>This i s HTML f
0140	69 6c 65 2d 20 45 6e 67	6c 69 73 68 20 76 65 72	ile- Eng lish ver
0150	73 69 6f 6e 3c 2f 68 31	3e 0a 0a 3c 70 3e 54 61	sion</h1 >.<p>Ta
0160	6d 69 72 20 69 73 20 67	72 65 61 74 20 70 65 72	mir is g reat per
0170	73 6f 6e 20 61 6e 64 20	61 6d 61 7a 69 6e 67 20	son and amazing

## :HEAD

בבקשת HEAD נבקש אובייקט HTML מהשרת, אך נחזיר את תוכן הHEADERS ולא את ההודעה. במידה והקובץ נמצא תוחזר הודעת 200 OK, אחרת תוחזר הודעת 404 NOT FOUND.

## צילומי מסך

לקוח

HEADlocalhost:8080/hfile.html

SendSave

ParamsAuthorizationHeaders (7)BodyPre-request ScriptTestsSettings

CookiesCode

<input checked="" type="checkbox"/>	Accept		*/*	
<input checked="" type="checkbox"/>	Accept-Encoding		gzip, deflate, br	
<input checked="" type="checkbox"/>	Connection		keep-alive	
<input checked="" type="checkbox"/>	Accept-Language		he-il	
	Key		Value	Description

BodyCookiesHeaders (2)Test Results

Status: 200 OKTime: 18 msSize: 65 BSave Response

PrettyRawPreviewVisualize

Wireshark

▼ Hypertext Transfer Protocol	
> HEAD /hfile.html HTTP/1.1\r\n	
Accept-Language: he-IL\r\n	
User-Agent: PostmanRuntime/7.26.8\r\n	
Accept: */*\r\n	
Postman-Token: e8e5c063-0a95-4584-9872-931cc6451e43\r\n	
Host: localhost:8080\r\n	
Accept-Encoding: gzip, deflate, br\r\n	
Connection: keep-alive\r\n	
\r\n	
<a href="http://localhost:8080/hfile.html">[Full request URI: http://localhost:8080/hfile.html]</a>	
[HTTP request 2/2]	
<a href="#">[Prev request in frame: 20]</a>	
<a href="#">[Response in frame: 1025]</a>	
0000	02 00 00 00 45 00 01 14 31 09 40 00 80 06 00 00 ....E... 1.@.....
0010	7f 00 00 01 7f 00 00 01 f5 26 1f 90 20 a8 1b 6f .....-&...o
0020	c0 2e 30 6a 50 18 27 f8 39 09 00 00 48 45 41 44 -.0jP-' 9...HEAD
0030	20 2f 68 66 69 6c 65 2e 68 74 6d 6c 20 48 54 54 /hfile. html HTT
0040	50 2f 31 2e 31 0d 0a 41 63 63 65 70 74 2d 4c 61 P/1.1..A ccept-La
0050	6e 67 75 61 67 65 3a 20 68 65 2d 49 4c 0d 0a 55 nguage: he-IL..U
0060	73 65 72 2d 41 67 65 6e 74 3a 20 50 6f 73 74 6d ser-Agen t: Postm
0070	61 6e 52 75 6e 74 69 6d 65 2f 37 2e 32 36 2e 38 anRuntim e/7.26.8
0080	0d 0a 41 63 63 65 70 74 3a 20 2a 2f 2a 0d 0a 50 ..Accept : */*..P
0090	6f 73 74 6d 61 6e 2d 54 6f 6b 65 6e 3a 20 65 38 ostman-T oken: e8
00a0	65 35 63 30 36 33 2d 30 61 39 35 2d 34 35 38 34 e5c063-0 a95-4584
00b0	2d 39 38 37 32 2d 39 33 31 63 63 36 34 35 31 65 -9872-93 1cc6451e
00c0	34 33 0d 0a 48 6f 73 74 3a 20 6c 6f 63 61 6c 68 43..Host : localh
00d0	6f 73 74 3a 38 30 38 30 0d 0a 41 63 63 65 70 74 ost:8080 ..Accept
00e0	2d 45 6e 63 6f 64 69 6e 67 3a 20 67 7a 69 70 2c -Encodin g: gzip,
00f0	20 64 65 66 6c 61 74 65 2c 20 62 72 0d 0a 43 6f deflate , br..Co
0100	6e 6e 65 63 74 69 6f 6e 3a 20 6b 65 65 70 2d 61 nnection : keep-a
0110	6c 69 76 65 0d 0a 0d 0a live....

שרת

```
HTTP Server: Recieved: 236 bytes of
"HEAD /hfile.html HTTP/1.1
Accept-Language: he-IL
User-Agent: PostmanRuntime/7.26.8
Accept: */*
Postman-Token: e8e5c063-0a95-4584-9872-931cc6451e43
Host: localhost:8080
Accept-Encoding: gzip, deflate, br
Connection: keep-alive

" message.
HTTP Server: Sent: 65\65 bytes of "HTTP/1.1 200 OK
Content-type: text/html
Content-length: 687

" message.
```

wireShark

```

v Hypertext Transfer Protocol
  > HTTP/1.1 200 OK\r\n
    Content-type: text/html\r\n
  > Content-length: 687\r\n
    \r\n
    [HTTP response 2/2]
    [Time since request: 0.013504000 seconds]
    \[Prev request in frame: 20\]
    \[Prev response in frame: 22\]
    \[Request in frame: 1023\]
    [Request URI: http://localhost:8080/hfile.html]

```

```

0000  02 00 00 00 45 00 00 69 31 0b 40 00 80 06 00 00  ....E..i 1.@....
0010  7f 00 00 01 7f 00 00 01 1f 90 f5 26 c0 2e 30 6a  .....&..&..0j
0020  20 a8 1c 5b 50 18 27 f8 b5 9f 00 00 48 54 54 50  ..[P'..HTTP
0030  2f 31 2e 31 20 32 30 30 20 4f 4b 0d 0a 43 6f 6e  /1.1 200 OK..Con
0040  74 65 6e 74 2d 74 79 70 65 3a 20 74 65 78 74 2f  tent-typ e: text/
0050  68 74 6d 6c 0d 0a 43 6f 6e 74 65 6e 74 2d 6c 65  html..Co ntent-le
0060  6e 67 74 68 3a 20 36 38 37 0d 0a 0d 0a  ngth: 68 7....

```


**:POST**

לפי פרוטוקול RFC 2616 בקשת POST מסוגלת לבצע מספר פעולות. בשרת שלנו בחרנו לבצע את הפעולה הבאה:

- Extending a database through an append operation.

כלומר להוסיף את גוף הודעת הPOST לאובייקט שקיים בשרת.  
במידה והקובץ נמצא תוחזר הודעת 200 OK, במידה והקובץ לא נמצא בתיקיית השרת תוחזר שגיאה  
500 SERVER ERROR ואם לא נשלח טקסט בגוף ההודעה תוחזר שגיאה 204 NO CONTENT

צילומי מסך  
לפני-




# This is HTML file- English version

Tamir is great person and amazing friend!

Dor is fine too...

אחרי-




# This is HTML file- English version

Tamir is great person and amazing friend!

Dor is fine too...

hey, could you please add this? thank you!

לקוח-



-WIRESHARK



▼ Hypertext Transfer Protocol		
> POST /hfile.html HTTP/1.1\r\n		
Accept-Language: en-US\r\n		
Content-Type: text/plain\r\n		
User-Agent: PostmanRuntime/7.26.8\r\n		
Accept: */*\r\n		
Postman-Token: ff323ae3-fb6f-4376-a23e-6402aecb9a69\r\n		
Host: localhost:8080\r\n		
Accept-Encoding: gzip, deflate, br\r\n		
Connection: keep-alive\r\n		
> Content-Length: 43\r\n		
0000	02 00 00 00 45 00 01 6d 34 9f 40 00 80 06 00 00	....E..m 4.@.....
0010	7f 00 00 01 7f 00 00 01 f5 26 1f 90 20 a8 1d bd	.....-&... ..
0020	c0 2e 30 ea 50 18 27 f7 a9 72 00 00 50 4f 53 54	..0.P.'..r..POST
0030	20 2f 68 66 69 6c 65 2e 68 74 6d 6c 20 48 54 54	/hfile. html HTT
0040	50 2f 31 2e 31 0d 0a 41 63 63 65 70 74 2d 4c 61	P/1.1..A ccept-La
0050	6e 67 75 61 67 65 3a 20 65 6e 2d 55 53 0d 0a 43	nguage: en-US..C
0060	6f 6e 74 65 6e 74 2d 54 79 70 65 3a 20 74 65 78	ontent-T ype: tex
0070	74 2f 70 6c 61 69 6e 0d 0a 55 73 65 72 2d 41 67	t/plain..User-Ag
0080	65 6e 74 3a 20 50 6f 73 74 6d 61 6e 52 75 6e 74	ent: Pos tmanRunt
0090	69 6d 65 2f 37 2e 32 36 2e 38 0d 0a 41 63 63 65	ime/7.26 .8..Acce
00a0	70 74 3a 20 2a 2f 2a 0d 0a 50 6f 73 74 6d 61 6e	pt: */*. ..Postman
00b0	2d 54 6f 6b 65 6e 3a 20 66 66 33 32 33 61 65 33	-Token: ff323ae3
00c0	2d 66 62 36 66 2d 34 33 37 36 2d 61 32 33 65 2d	-fb6f-43 76-a23e-
00d0	36 34 30 32 61 65 63 62 39 61 36 39 0d 0a 48 6f	6402aecb 9a69..Ho
00e0	73 74 3a 20 6c 6f 63 61 6c 68 6f 73 74 3a 38 30	st: loca lhost:80
00f0	38 30 0d 0a 41 63 63 65 70 74 2d 45 6e 63 6f 64	80..Acce pt-Encod
0100	69 6e 67 3a 20 67 7a 69 70 2c 20 64 65 66 6c 61	ing: gzi p, defla
0110	74 65 2c 20 62 72 0d 0a 43 6f 6e 6e 65 63 74 69	te, br.. Connecti
0120	6f 6e 3a 20 6b 65 65 70 2d 61 6c 69 76 65 0d 0a	on: keep -alive..

שרת-

```

HTTP Server: Recieved: 325 bytes of
"POST /hfile.html HTTP/1.1
Accept-Language: en-US
Content-Type: text/plain
User-Agent: PostmanRuntime/7.26.8
Accept: */*
Postman-Token: ff323ae3-fb6f-4376-a23e-6402aecb9a69
Host: localhost:8080
Accept-Encoding: gzip, deflate, br
Connection: keep-alive
Content-Length: 43

hey, could you please add this?
thank you!" message.
HTTP Server: Sent: 63\63 bytes of "HTTP/1.1 200 OK
Content-type: text/html
Content-length: 0

" message.

```

wireShark-

▼ Hypertext Transfer Protocol		
> HTTP/1.1 200 OK\r\n		
Content-type: text/html\r\n		
> Content-length: 0\r\n		
\r\n		
[HTTP response 4/4]		
[Time since request: 0.008939000 seconds]		
<a href="#">[Prev request in frame: 1629]</a>		
<a href="#">[Prev response in frame: 1631]</a>		
<a href="#">[Request in frame: 2177]</a>		
[Request URI: http://localhost:8080/hfile.html]		
0000	02 00 00 00 45 00 00 67 34 a1 40 00 80 06 00 00	....E..g 4..@.....
0010	7f 00 00 01 7f 00 00 01 1f 90 f5 26 c0 2e 30 ea	.....&..0.
0020	20 a8 1f 02 50 18 27 f6 ef b4 00 00 48 54 54 50	...P.'...HTTP
0030	2f 31 2e 31 20 32 30 30 20 4f 4b 0d 0a 43 6f 6e	/1.1 200 OK..Con
0040	74 65 6e 74 2d 74 79 70 65 3a 20 74 65 78 74 2f	tent-type: text/
0050	68 74 6d 6c 0d 0a 43 6f 6e 74 65 6e 74 2d 6c 65	html..Co ntent-le
0060	6e 67 74 68 3a 20 30 0d 0a 0d 0a	ngth: 0. ...

**:PUT**

העלאת דף לשרת.


במידה והקובץ קיים תוחזר הודעה 200 OK

אם הקובץ לא קיים בתיקיית השרת, גוף ההודעה ייכתב לקובץ חדש ותוחזר הודעה 201 CREATED  
אם הקובץ קיים ולא נפתח תוחזר הודעה 500 SERVER ERROR  
במידה ותוכן גוף ההודעה ריק נחזיר הודעה 204 NO CONTENT ולא נעדכן את הקובץ הנדרש, בהתאם



לדרישות RFC 2616

צילומי מסך-

לפני



אחרי



לקוח-

PUT

localhost:8080/newPut.txt

Send

Save

Params

Authorization

Headers (9)

Body

Pre-request Script

Tests

Settings

Cookies

Code

none

form-data

x-www-form-urlencoded

raw

binary

GraphQL

Text

```

1  this is put body
2  add this
3  thank you

```

Body

Cookies

Headers (2)

Test Results

Status: 201 Created

Time: 520 ms

Size: 68 B

Save Response

Pretty

Raw

Preview

Visualize

wireShark

Hypertext Transfer Protocol									
<div> <div>PUT /newPut.txt HTTP/1.1\r\n</div> <div>Accept-Language: en-US\r\n</div> <div>Content-Type: text/plain\r\n</div> <div>User-Agent: PostmanRuntime/7.26.8\r\n</div> <div>Accept: */*\r\n</div> <div>Postman-Token: 8ff759ed-142a-4398-91bf-3877bc5a7d30\r\n</div> <div>Host: localhost:8080\r\n</div> <div>Accept-Encoding: gzip, deflate, br\r\n</div> <div>Connection: keep-alive\r\n</div> <div>Content-Length: 37\r\n</div> <div>\r\n</div> <div> <a href="#">[Full request URI: http://localhost:8080/newPut.txt]</a>  <a href="#">[HTTP request 2/2]</a>  <a href="#">[Prev request in frame: 3124]</a> </div> </div>									
0000	02 00 00 00 45 00 01 66	37 dc 40 00 80 06 00 00	....E..f 7-@-....						
0010	7f 00 00 01 7f 00 00 01	f5 81 1f 90 b6 1f c2 42	.....B						
0020	e5 a6 2c ab 50 18 27 f9	f3 0f 00 00 50 55 54 20	.., .P- '- ....PUT						
0030	2f 6e 65 77 50 75 74 2e	74 78 74 20 48 54 54 50	/newPut. txt HTTP						
0040	2f 31 2e 31 0d 0a 41 63	63 65 70 74 2d 4c 61 6e	/1.1- Ac cept-Lan						
0050	67 75 61 67 65 3a 20 65	6e 2d 55 53 0d 0a 43 6f	guage: e n-US- Co						
0060	6e 74 65 6e 74 2d 54 79	70 65 3a 20 74 65 78 74	ntent-Ty pe: text						
0070	2f 70 6c 61 69 6e 0d 0a	55 73 65 72 2d 41 67 65	/plain- User-Age						
0080	6e 74 3a 20 50 6f 73 74	6d 61 6e 52 75 6e 74 69	nt: Post manRunti						
0090	6d 65 2f 37 2e 32 36 2e	38 0d 0a 41 63 63 65 70	me/7.26. 8- Accep						
00a0	74 3a 20 2a 2f 2a 0d 0a	50 6f 73 74 6d 61 6e 2d	t: */*- Postman-						
00b0	54 6f 6b 65 6e 3a 20 38	66 66 37 35 39 65 64 2d	Token: 8 ff759ed-						
00c0	31 34 32 61 2d 34 33 39	38 2d 39 31 62 66 2d 33	142a-439 8-91bf-3						
00d0	38 37 37 62 63 35 61 37	64 33 30 0d 0a 48 6f 73	877bc5a7 d30- Hos						
00e0	74 3a 20 6c 6f 63 61 6c	68 6f 73 74 3a 38 30 38	t: local host:808						
00f0	30 0d 0a 41 63 63 65 70	74 2d 45 6e 63 6f 64 69	0- Accep t-Encodi						
0100	6e 67 3a 20 67 7a 69 70	2c 20 64 65 66 6c 61 74	ng: gzip , deflat						
0110	65 2c 20 62 72 0d 0a 43	6f 6e 6e 65 63 74 69 6f	e, br- C connectio						
0120	6e 3a 20 6b 65 65 70 2d	61 6c 69 76 65 0d 0a 43	n: keep- alive- C						
0130	6f 6e 74 65 6e 74 2d 4c	65 6e 67 74 68 3a 20 33	ontent-L ength: 3						
0140	37 0d 0a 0d 0a 74 68 69	73 20 69 73 20 70 75 74	7- thi s is put						
0150	20 62 6f 64 79 0d 0a 61	64 64 20 74 68 69 73 0d	body- a dd this-						
0160	0a 74 68 61 6e 6b 20 79	6f 75	-thank y ou						

```

HTTP Server: Recieved: 318 bytes of
"PUT /newPut.txt HTTP/1.1
Accept-Language: en-US
Content-Type: text/plain
User-Agent: PostmanRuntime/7.26.8
Accept: */*
Postman-Token: 8ff759ed-142a-4398-91bf-3877bc5a7d30
Host: localhost:8080
Accept-Encoding: gzip, deflate, br
Connection: keep-alive
Content-Length: 37

this is put body
add this
thank you" message.
HTTP Server: Sent: 68\68 bytes of "HTTP/1.1 201 Created
Content-type: text/html
Content-length: 0

" message.

```

WireShark

▼ Hypertext Transfer Protocol		
> HTTP/1.1 201 Created\r\n		
Content-type: text/html\r\n		
> Content-length: 0\r\n		
\r\n		
[HTTP response 2/2]		
[Time since request: 0.003122000 seconds]		
<a href="#">[Prev request in frame: 3124]</a>		
<a href="#">[Prev response in frame: 3126]</a>		
<a href="#">[Request in frame: 3236]</a>		
[Request URI: http://localhost:8080/newPut.txt]		
0000	02 00 00 00 45 00 00 6c 37 de 40 00 80 06 00 00	....E..l 7.@.....
0010	7f 00 00 01 7f 00 00 01 1f 90 f5 81 e5 a6 2c ab	..... ,.
0020	b6 1f c3 80 50 18 27 f8 96 ff 00 00 48 54 54 50	....P.' . . . .HTTP
0030	2f 31 2e 31 20 32 30 31 20 43 72 65 61 74 65 64	/1.1 201 Created
0040	0d 0a 43 6f 6e 74 65 6e 74 2d 74 79 70 65 3a 20	..Content-type:
0050	74 65 78 74 2f 68 74 6d 6c 0d 0a 43 6f 6e 74 65	text/html..Conte
0060	6e 74 2d 6c 65 6e 67 74 68 3a 20 30 0d 0a 0d 0a	nt-length: 0....

## :DELETE

מחיקת אובייקט מהשרת.

תוחזר הודעה OK 200

## צילומי מסך

לקוח-

The screenshot displays the Postman application interface for a DELETE request. At the top, the request method is 'DELETE' and the URL is 'localhost:8080/newPut.txt'. The 'Send' button is highlighted in blue. Below the URL bar, the 'Headers' tab is selected, showing a list of headers with checkboxes for each:

Header	Value
<input checked="" type="checkbox"/> User-Agent	PostmanRuntime/7.26.8
<input checked="" type="checkbox"/> Accept	*/*
<input checked="" type="checkbox"/> Accept-Encoding	gzip, deflate, br
<input checked="" type="checkbox"/> Connection	keep-alive
<input checked="" type="checkbox"/> Accept-Language	en-US

At the bottom, the 'Body' tab is selected, and the status bar indicates a successful response: Status: 200 OK, Time: 8 ms, Size: 66 B. The 'Save Response' button is visible on the right.

wireShark

▼ Hypertext Transfer Protocol		
> DELETE /newPut.txt HTTP/1.1\r\n		
Accept-Language: en-US\r\n		
Content-Type: text/plain\r\n		
User-Agent: PostmanRuntime/7.26.8\r\n		
Accept: */*\r\n		
Postman-Token: 64d59e0a-e3fa-4eae-9ed2-6060a342ee2f\r\n		
Host: localhost:8080\r\n		
Accept-Encoding: gzip, deflate, br\r\n		
Connection: keep-alive\r\n		
> Content-Length: 37\r\n		
0000	02 00 00 00 45 00 01 69 38 fa 40 00 80 06 00 00	....E-i 8-@.....
0010	7f 00 00 01 7f 00 00 01 f5 81 1f 90 b6 1f c3 80	.....
0020	e5 a6 2c ef 50 18 27 f9 7b 9f 00 00 44 45 4c 45	..,P-' {...DELE
0030	54 45 20 2f 6e 65 77 50 75 74 2e 74 78 74 20 48	TE /newP ut.txt H
0040	54 54 50 2f 31 2e 31 0d 0a 41 63 63 65 70 74 2d	TTP/1.1- Accept-
0050	4c 61 6e 67 75 61 67 65 3a 20 65 6e 2d 55 53 0d	Language : en-US-
0060	0a 43 6f 6e 74 65 6e 74 2d 54 79 70 65 3a 20 74	-Content -Type: t
0070	65 78 74 2f 70 6c 61 69 6e 0d 0a 55 73 65 72 2d	ext/plai n--User-
0080	41 67 65 6e 74 3a 20 50 6f 73 74 6d 61 6e 52 75	Agent: P ostmanRu
0090	6e 74 69 6d 65 2f 37 2e 32 36 2e 38 0d 0a 41 63	ntime/7. 26.8--Ac
00a0	63 65 70 74 3a 20 2a 2f 2a 0d 0a 50 6f 73 74 6d	cept: */ *-Postm
00b0	61 6e 2d 54 6f 6b 65 6e 3a 20 36 34 64 35 39 65	an-Token : 64d59e
00c0	30 61 2d 65 33 66 61 2d 34 65 61 65 2d 39 65 64	0a-e3fa- 4eae-9ed
00d0	32 2d 36 30 36 30 61 33 34 32 65 65 32 66 0d 0a	2-6060a3 42ee2f--
00e0	48 6f 73 74 3a 20 6c 6f 63 61 6c 68 6f 73 74 3a	Host: lo calhost:
00f0	38 30 38 30 0d 0a 41 63 63 65 70 74 2d 45 6e 63	8080--Ac cept-Enc
0100	6f 64 69 6e 67 3a 20 67 7a 69 70 2c 20 64 65 66	oding: g zip, def
0110	6c 61 74 65 2c 20 62 72 0d 0a 43 6f 6e 6e 65 63	late, br --Connec
0120	74 69 6f 6e 3a 20 6b 65 65 70 2d 61 6c 69 76 65	tion: ke ep-alive

שרת-

```

HTTP Server: Recieved: 321 bytes of
"DELETE /newPut.txt HTTP/1.1
Accept-Language: en-US
Content-Type: text/plain
User-Agent: PostmanRuntime/7.26.8
Accept: */*
Postman-Token: 64d59e0a-e3fa-4eae-9ed2-6060a342ee2f
Host: localhost:8080
Accept-Encoding: gzip, deflate, br
Connection: keep-alive
Content-Length: 37

this is put body
add this
thank you" message.
HTTP Server: Sent: 66\66 bytes of "HTTP/1.1 200 OK
Content-type: message/http
Content-length: 0

" message.

```

Wireshark

▼ Hypertext Transfer Protocol									
> HTTP/1.1 200 OK\r\n									
Content-type: message/http\r\n									
> Content-length: 0\r\n									
\r\n									
[HTTP response 3/3]									
[Time since request: 0.004275000 seconds]									
<a href="#">[Prev request in frame: 3236]</a>									
<a href="#">[Prev response in frame: 3238]</a>									
<a href="#">[Request in frame: 3537]</a>									
[Request URI: http://localhost:8080/newPut.txt]									
0000	02 00 00 00 45 00 00 6a	38 fc 40 00 80 06 00 00	....E..j 8-@.....						
0010	7f 00 00 01 7f 00 00 01	1f 90 f5 81 e5 a6 2c ef	.....,.						
0020	b6 1f c4 c1 50 18 27 f7	5a ad 00 00 48 54 54 50	....P-'. Z...HTTP						
0030	2f 31 2e 31 20 32 30 30	20 4f 4b 0d 0a 43 6f 6e	/1.1 200 OK..Con						
0040	74 65 6e 74 2d 74 79 70	65 3a 20 6d 65 73 73 61	tent-type: messa						
0050	67 65 2f 68 74 74 70 0d	0a 43 6f 6e 74 65 6e 74	ge/http..Content						
0060	2d 6c 65 6e 67 74 68 3a	20 30 0d 0a 0d 0a	-length: 0....						

**:TRACE**




הודעת LOOPBACK מהשרת חזרה אל הלקוח.


תוחזר הודעה OK 200 כאשר גוף ההודעה זהה להודעה שנשלחה

צילומי מסך-

לקוח



wireshark



```

HTTP Server: Recieved: 294 bytes of
"TRACE /hfile.html HTTP/1.1
Accept-Language: en-US
Content-Type: text/plain
User-Agent: PostmanRuntime/7.26.8
Accept: */*
Postman-Token: f7bd0e00-a901-4117-a485-8d55311f90aa
Host: localhost:8080
Accept-Encoding: gzip, deflate, br
Connection: keep-alive
Content-Length: 11

trace????
" message.
HTTP Server: Sent: 78\78 bytes of "HTTP/1.1 200 OK
Content-type: message/http
Content-length: 11

trace????
" message.

```

Wireshark-

▼ Hypertext Transfer Protocol

```

> HTTP/1.1 200 OK\r\n
  Content-type: message/http\r\n
> Content-length: 11\r\n
  \r\n
[HTTP response 4/4]
[Time since request: 0.015729000 seconds]
\[Prev request in frame: 3537\]
\[Prev response in frame: 3539\]
\[Request in frame: 4045\]
[Request URI: http://localhost:8080/hfile.html]

```

0000	02 00 00 00 45 00 00 76	3a 9a 40 00 80 06 00 00	....E..v :.@.....
0010	7f 00 00 01 7f 00 00 01	1f 90 f5 81 e5 a6 2d 31	.....-1
0020	b6 1f c5 e7 50 18 27 f5	cc 70 00 00 48 54 54 50	....P.' -p-HTTP
0030	2f 31 2e 31 20 32 30 30	20 4f 4b 0d 0a 43 6f 6e	/1.1 200 OK-Con
0040	74 65 6e 74 2d 74 79 70	65 3a 20 6d 65 73 73 61	tent-type: messa
0050	67 65 2f 68 74 74 70 0d	0a 43 6f 6e 74 65 6e 74	ge/http-Content
0060	2d 6c 65 6e 67 74 68 3a	20 31 31 0d 0a 0d 0a 74	-length: 11...t
0070	72 61 63 65 3f 3f 3f 3f	0d 0a	race???? ..

## :OPTIONS

תוחזר הודעה כאשר גוף ההודעה ריק ובנוסף Header בשם Allow שיכיל את כל המתודות שהשרת תומך בהם כעת בנוסף יוחזר סטטוס 200 OK

לקוח-

The screenshot shows a web browser's developer tools interface. The top bar indicates the URL is localhost:8080/hfile.html. The 'Send' button is highlighted. Below the address bar, the 'Headers' tab is selected, showing a list of headers. The 'Body' tab is also visible. The 'Headers' tab shows a table with the following data:

KEY	VALUE
Allow	OPTIONS,GET,HEAD,PUT,POST,DELETE,TRACE
Content-type	message/http
Content-length	0

The status bar at the bottom indicates a 200 OK status, 32 ms time, and 113 B size. The 'Save Response' button is visible.

-Wireshark



```

HTTP Server: Recieved: 239 bytes of
"OPTIONS /hfile.html HTTP/1.1
Accept-Language: en-US
User-Agent: PostmanRuntime/7.26.8
Accept: */*
Postman-Token: 08cc2cd7-0f53-4481-860e-4d77a725267b
Host: localhost:8080
Accept-Encoding: gzip, deflate, br
Connection: keep-alive

" message.
HTTP Server: Sent: 113\113 bytes of "HTTP/1.1 200 OK
Allow: OPTIONS,GET,HEAD,PUT,POST,DELETE,TRACE
Content-type: message/http
Content-length: 0

" message.

```

-Wireshark

▼ Hypertext Transfer Protocol		
> HTTP/1.1 200 OK\r\n		
Allow: OPTIONS,GET,HEAD,PUT,POST,DELETE,TRACE\r\n		
Content-type: message/http\r\n		
> Content-length: 0\r\n		
\r\n		
[HTTP response 5/5]		
[Time since request: 0.028274000 seconds]		
<a href="#">[Prev request in frame: 4045]</a>		
<a href="#">[Prev response in frame: 4047]</a>		
<a href="#">[Request in frame: 4591]</a>		
0000	02 00 00 00 45 00 00 99	3c 34 40 00 80 06 00 00
0010	7f 00 00 01 7f 00 00 01	1f 90 f5 81 e5 a6 2d 7f
0020	b6 1f c6 d6 50 18 27 f5	09 26 00 00 48 54 54 50
0030	2f 31 2e 31 20 32 30 30	20 4f 4b 0d 0a 41 6c 6c
0040	6f 77 3a 20 4f 50 54 49	4f 4e 53 2c 47 45 54 2c
0050	48 45 41 44 2c 50 55 54	2c 50 4f 53 54 2c 44 45
0060	4c 45 54 45 2c 54 52 41	43 45 0d 0a 43 6f 6e 74
0070	65 6e 74 2d 74 79 70 65	3a 20 6d 65 73 73 61 67
0080	65 2f 68 74 74 70 0d 0a	43 6f 6e 74 65 6e 74 2d
0090	6c 65 6e 67 74 68 3a 20	30 0d 0a 0d 0a

