



jQuery Selectors

[« Previous](#)
[Next Chapter »](#)

jQuery Selectors

Use our [jQuery Selector Tester](#) to demonstrate the different selectors.

| <u>*</u> | \$("#*") | All elements |
|-----------------------|---------------------|---|
| <u>#id</u> | \$("#lastname") | The element with id="lastname" |
| <u>.class</u> | \$(".intro") | All elements with class="intro" |
| <u>.class, .class</u> | \$(".intro, .demo") | All elements with the class "intro" or "demo" |
| <u>element</u> | \$("p") | All <p> elements |
| <u>e1, e2, e3</u> | \$("#h1, div, p") | All <h1>, <div> and <p> elements |
| <u>:first</u> | \$("p:first") | The first <p> element |
| <u>:last</u> | \$("p:last") | The last <p> element |
| <u>:even</u> | \$("tr:even") | All even <tr> elements |
| <u>:odd</u> | \$("tr:odd") | All odd <tr> elements |
| | | |

| | | |
|------------------------------------|-----------------------------|---|
| <u>:first-child</u> | \$("p:first-child") | All <p> elements that are the first child of their parent |
| <u>:first-of-type</u> | \$("p:first-of-type") | All <p> elements that are the first <p> element of their parent |
| <u>:last-child</u> | \$("p:last-child") | All <p> elements that are the last child of their parent |
| <u>:last-of-type</u> | \$("p:last-of-type") | All <p> elements that are the last <p> element of their parent |
| <u>:nth-child(<i>n</i>)</u> | \$("p:nth-child(2)") | All <p> elements that are the 2nd child of their parent |
| <u>:nth-last-child(<i>n</i>)</u> | \$("p:nth-last-child(2)") | All <p> elements that are the 2nd child of their parent, counting from the last child |
| <u>:nth-of-type(<i>n</i>)</u> | \$("p:nth-of-type(2)") | All <p> elements that are the 2nd <p> element of their parent |
| <u>:nth-last-of-type(<i>n</i>)</u> | \$("p:nth-last-of-type(2)") | All <p> elements that are the 2nd <p> element of their parent, counting from the last child |



JQUERY



| | | |
|---------------------------|----------------------|--|
| <u>:only-of-type</u> | \$("p:only-of-type") | All <p> elements that are the only child, of its type, of their parent |
| <u>parent > child</u> | \$("div > p") | All <p> elements that are a direct child of a <div> element |
| <u>parent descendant</u> | \$("div p") | All <p> elements that are descendants of a <div> element |
| <u>element + next</u> | \$("div + p") | The <p> element that are next to each <div> elements |
| <u>element ~ siblings</u> | \$("div ~ p") | All <p> elements that are siblings of a <div> element |
| <u>:eq(<i>index</i>)</u> | \$("ul li:eq(3)") | The fourth element in a list (index starts at 0) |
| <u>:gt(<i>no</i>)</u> | \$("ul li:gt(3)") | List elements with an index greater than 3 |

| | | |
|-------------------------------|---------------------------------------|---|
| <u>:lt(<i>no</i>)</u> | <code>\$("ul li:lt(3)")</code> | List elements with an index less than 3 |
| <u>:not(<i>selector</i>)</u> | <code>\$("input:not(:empty)")</code> | All input elements that are not empty |
| <u>:header</u> | <code>\$(":header")</code> | All header elements <h1>, <h2> ... |
| <u>:animated</u> | <code>\$(":animated")</code> | All animated elements |
| <u>:focus</u> | <code>\$(":focus")</code> | The element that currently has focus |
| <u>:contains(<i>text</i>)</u> | <code>\$(":contains('Hello'))"</code> | All elements which contains the text "Hello" |
| <u>:has(<i>selector</i>)</u> | <code>\$("div:has(p)")</code> | All <div> elements that have a <p> element |
| <u>:empty</u> | <code>\$(":empty")</code> | All elements that are empty |
| <u>:parent</u> | <code>\$(":parent")</code> | All elements that are a parent of another element |
| <u>:hidden</u> | <code>\$("p:hidden")</code> | All hidden <p> elements |




JQUERY




| | | |
|--|--|---|
| <u>:root</u> | <code>\$(":root")</code> | The document's root element |
| <u>:lang(<i>language</i>)</u> | <code>\$("p:lang(de)")</code> | All <p> elements with a lang attribute value starting with "de" |
| <u>[<i>attribute</i>]</u> | <code>\$("[href]")</code> | All elements with a href attribute |
| <u>[<i>attribute</i>=<i>value</i>]</u> | <code>\$("[href='default.htm']")</code> | All elements with a href attribute value equal to "default.htm" |
| <u>[<i>attribute</i>!=<i>value</i>]</u> | <code>\$("[href!='default.htm']")</code> | All elements with a href attribute value not equal to "default.htm" |
| <u>[<i>attribute</i>\$=<i>value</i>]</u> | <code>\$("[href\$='.jpg']")</code> | All elements with a href attribute value ending with ".jpg" |
| <u>[<i>attribute</i> =<i>value</i>]</u> | <code>\$("[title='Tomorrow']")</code> | All elements with a title attribute value equal to 'Tomorrow', or starting with 'Tomorrow' followed by a hyphen |
| <u>[<i>attribute</i>^=<i>value</i>]</u> | <code>\$("[title^='Tom']")</code> | All elements with a title attribute value starting with "Tom" |

| | | |
|---------------------------|-------------------------------------|--|
| <u>[attribute~=value]</u> | <code>\$("[title~='hello']")</code> | All elements with a title attribute value containing the specific word "hello" |
| <u>[attribute*=value]</u> | <code>\$("[title*='hello']")</code> | All elements with a title attribute value containing the word "hello" |
| <u>:input</u> | <code>\$(":input")</code> | All input elements |
| <u>:text</u> | <code>\$(":text")</code> | All input elements with type="text" |
| <u>:password</u> | <code>\$(":password")</code> | All input elements with type="password" |
| <u>:radio</u> | <code>\$(":radio")</code> | All input elements with type="radio" |
| <u>:checkbox</u> | <code>\$(":checkbox")</code> | All input elements with type="checkbox" |
| <u>:submit</u> | <code>\$(":submit")</code> | All input elements with type="submit" |
| <u>:reset</u> | <code>\$(":reset")</code> | All input elements with type="reset" |
| <u>:button</u> | <code>\$(":button")</code> | All input elements with type="button" |
| <u>:image</u> | <code>\$(":image")</code> | All input elements with type="image" |




JQUERY




| | | |
|------------------|------------------------------|-----------------------------|
| <u>:enabled</u> | <code>\$(":enabled")</code> | All enabled input elements |
| <u>:disabled</u> | <code>\$(":disabled")</code> | All disabled input elements |
| <u>:selected</u> | <code>\$(":selected")</code> | All selected input elements |
| <u>:checked</u> | <code>\$(":checked")</code> | All checked input elements |

[« Previous](#)[Next Chapter »](#)



COLOR PICKER



LEARN MORE

- HTML Cards
- Google Maps
- Animated Buttons
- Modal Boxes
- Modal Images
- Tooltips
- Loaders
- Filter List
- JS Animations

Progress Bars
Dropdowns
Slideshow
Accordions
Side Navigation
Top Navigation
HTML Includes
Tabs

SHARE



CERTIFICATES

HTML, CSS, JavaScript, PHP, jQuery, Bootstrap and XML.

[Read More »](#)





[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

Top 10 Tutorials

[HTML Tutorial](#)

[CSS Tutorial](#)

[Bootstrap Tutorial](#)

[SQL Tutorial](#)

[PHP Tutorial](#)

[jQuery Tutorial](#)

[Angular Tutorial](#)

[XML Tutorial](#)

Top 10 References

[HTML Reference](#)

[CSS Reference](#)

[JavaScript Reference](#)

[W3.CSS Reference](#)

[Browser Statistics](#)

[PHP Reference](#)

[HTML Colors](#)

[HTML Character Sets](#)

[jQuery Reference](#)

[AngularJS Reference](#)

Top 10 Examples

[HTML Examples](#)

[CSS Examples](#)

[JavaScript Examples](#)

[W3.CSS Examples](#)

[HTML DOM Examples](#)

[PHP Examples](#)

ASP Examples
jQuery Examples
Angular Examples
XML Examples

Web Certificates

HTML Certificate
HTML5 Certificate
CSS Certificate
JavaScript Certificate
jQuery Certificate
PHP Certificate
Bootstrap Certificate
XML Certificate

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2016 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.



JQUERY

